INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 49, NO. 12 **DECEMBER 21, 1966**

AUTHOR INDEX TO THE JOURNAL

The number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Achar, B. N. N. See Sharp, J. H.
Adelsberg, L. M., Cadoff, L. H., and Tobin, J. M. Group IVB and VB metal carbide-carbon eutectic temperatures, (10) 573–74.
Agajanian, A. H., and Turk, H. L. Magnetic properties of nonstoichiometric NiZn ferrites, (8) 459–60.
Allen, W. C. Temperature dependence of properties of magnesium ferrite, (5) 257–60.
Altemose, V. O. Outgassing of glass caused by thermal neutrons and gamma radiation, (8) 446–50.
Amata, C. D. See Smith, A. W.
Anderson, O. L. See Schreiber, Edward; Soga, Naohiro.
Anderson, O. L., and Andreatch, P., Jr. Pressure derivatives of elastic constants of single crystal MgO at 23° and −195.8°C, (8) 404–409.
Andreatch, P., Jr. See Anderson, O. L.
Ansell, G. S. See Cooke, F. W.
Arafa, S. See Bishay, A. M.
Arias, Alan. Thermal shock resistance of zirconia with 15 mole % titanium, (6) 334–38; Mechanism by which metal additions improve the thermal shock resistance of zirconia, (6) 339–41; Effect of inclusions on grain growth of oxides, (11) 621–24.
Aronson, S., Cisney, E., and Auskern, A. B. Thermal expansion of nonstoichiometric zirconium carbides, (8) 456.
Atlas, L. M., Schlehman, G. J., and Readey, D. W. Defects in PuO_{2-x}: Density measurements at high temperatures, (11) 624–25.
Auskern, A. B. See Aronson, S.
Austerman, S. B., and Wagner, J. W. Cation diffusion in single-crystal and polycrystalline BeO, (2) 94–99.
Ayer, J. E., and Soppet, F. E. Vibratory compaction: II, Compaction of angular shapes, (4) 207–10.

Barker, J. See Busby, T. S.
Barrington, Jonathan. See Bergmann, O. R.
Barry, T. L., Stubican, V. S., and Roy, Rustum. Phase equilibria in the system CaO-Yb_2O_3, (12) 667–70.
Barsom, J. M. Effect of stress and strain on producing hackle in a glass plate, (1) 6–10.
Baskin, Y. Properties of uranium monophosphide, (10) 541–46.
Bates, J. L. Melting points of hypostoichiometric uranium dioxide, (7) 395–96.
Beatty, R. See Westman, A. E. R.
Beisler, J. F. See Pearce, M. L.
Bentle, G. G. Elastic constants of single-crystal BeO at room temperature, (3) 125–28.
Bergeron, C. G. See Liedberg, D. J.
Bergmann, O. R., and Barrington, Jonathan. Effect of explosive shock waves on ceramic powders, (9) 502–507.
Berry, J. M. See Mehan, R. L.
Bishay, A. M., and Arafa, S. Gamma-induced absorption and structural studies of arsenic borate glasses, (8) 423–30.
Blachere, J. R. Desulfurization of pyrite, (11) 590–93.
Blair, R. See O'Bryan, H. M.
Blau, H. H. See Shonebarger, F. J.
Bloor, D. Discussion of paper, "Infrared absorption spectrum of silicon dioxide," (12) 682–83.
Boffe, M. See Plumat, E.
Bolz, L. H. See Ormsby, W. C.
Borom, M. P., and Pask, J. A. Role of "adherence oxides" in the development of chemical bonding at glass-metal interfaces, (1) 1–6.
Bourne, H. L. Silicon monoxide technique for observing surface microtopography, (1) 53–54.
Bradt, R. C. See Cooke, F. W.
Bright, N. F. H., and Turnock, A. C. Nonstoichiometric tantalian magnetites, (3) 170–71.
Brindley, G. W. See Sharp, J. H.
Brissette, L. A., Burnett, P. L., Spriggs, R. M., and Vasilos, T. Thermochemically deformed Y_2O_3, (3) 165–66.
Brittain, J. O. See Carnahan, R. D.
Buehl, W. M. See Cowan, J. H.
Buessem, W. R., Cross, L. E., and Goswami, A. K. Phenomenological theory of high permittivity in fine-grained barium titanate, (1) 33–36; Effect of two-dimensional pressure on the permittivity of fine- and coarse-grained barium titanate, (1) 36–39.
Burggraaf, A. J. Sorption of argon by glass in a gas-discharge lamp, (8) 450–54.
Burnett, P. L. See Brissette, L. A.
Busby, T. S., and Barker, J. Simulative studies of upward drilling, (8) 441–46.

Cable, Michael. Kinetics and mechanisms of fining glasses, (8) 436–41; see also Rasul, C. G.
Cadoff, L. H. See Adelsberg, L. M.
Callister, W. D., Jr., Cutler, I. B., and Gordon, R. S. Thermal decomposition kinetics of boehmite, (8) 419–22.
Cameron, N. M. Relation between melt treatment and glass fiber strength, (3) 144–48.
Carnahan, R. D., and Brittain, J. O. Dislocation damping in rutile single crystals, (1) 15–19.
Caron, L. G. See Newnham, R. E.
Carter, J. R. See Kestigian, M.
Carter, R. E. See Rhodes, W. H.; Simpson, L. A.
Cass, T. R., and Washburn, J. Dislocation etch pits on {110} planes of magnesium oxide, (6) 343–44.
Chaklader, A. C. D., and McKenzie, L. G. Reactive hot-pressing of clays and alumina, (9) 477–83.
Chakrabarty, M. R. See Van Loan, P. R.
Chang, L. L. Y., Scroger, M. G., and Phillips, Bert. Alkaline-earth tungstates: Equilibrium and stability in the M–W–O systems, (7) 385–90.
Chapman, I. D. See Hair, M. L.
Charles, R. J. Metastable liquid immiscibility in alkali metal oxide–silica systems, (2) 55–62.
Chase, A. B. Habit modification of corundum crystals grown from molten PbF_2-Bi_2O_3, (5) 233–36.
Chase, A. B., and Wilcox, W. R. Elimination of inclusions from flux-grown crystals, (8) 460.
Chelko, A. See Johnston, W. D.
Chopra, S. K. See Dave, N. G.
Cimino, A., Porta, P., and Valigi, M. Dependence of the lattice parameter of magnesium oxide on crystallite size, (3) 152–56.
Cisney, E. See Aronson, S.
Clare, T. E. Sintering kinetics of beryllia, (3) 159–65; see also Reeve, K. D.
Class, W. H., and Machlin, E. S. Crack propagation method for measuring grain boundary energies in brittle materials, (6) 306–309.
Coble, R. L. See Farnsworth, P. L.
Cockayne, B. Observation and control of deviations in molar composition in single-crystal growth of mixed oxides, (4) 204–207.
Comer, J. J., Tombs, N. C., and Fitzgerald, J. F. Growth of single-crystal and polycrystalline thin films of $MgAl_2O_4$ and $MgFe_2O_4$, (5) 237–40.
Cook, R. L. See Vernetti, R. A.
Cooke, F. W., Brandt, R. C., DeVries, R. C., and Ansell, G. S. Dielectric aging and microstructure in the system $BaTiO_3$-$CaTiO_3$, (12) 648–51.
Cooper, A. R., Jr., and Heasley, J. H. Extension of Darken's equation to binary diffusion in ceramics, (5) 280–84.
Cowan, J. H., Buehl, W. M., and Hutchins, J. R., III. An electrochemical theory for oxygen reboil, (10) 559–62.
Cross, L. E. See Buessem, W. R.
Cutler, I. B. See Callister, W. D., Jr.; Eastman, P. F.; Hansen, K. W.; Johnson, H. B.; Jones, J. T.; Wilcox, P. D.; Winkler, E. R.

Dave, N. G., and Chopra, S. K. Preparation and thermal decomposition of calcium hydroxide crystals, (10) 575.
Day, R. B., and Stokes, R. J. Effect of crystal orientation on the mechanical behavior of magnesium oxide at high temperatures, (2) 72–80; Mechanical behavior of polycrystalline magnesium oxide at high temperatures, (7) 345–54.
DeClerck, D. H., and Su, Gouq-Jen. Rheological and electrokinetic properties of glass-frit and quartz suspensions, (5) 252–56.
de Menezes, I. See Stubican, V. S.
de Menezes, I., and Stubican, V. S. Grain-boundary reactions in magnesia-chrome refractories: Application of the electron probe, II, (11) 609–12.
DeVries, R. C. See Cooke, F. W.
Dickson, R. W. Anomaly in Young's modulus and internal friction of $5SrTiO_3 \cdot 3La_{2/3}TiO_3$ below 100°C, (11) 628.
Doremus, R. H. Physical solubility of gases in fused silica, (9) 461–62.
Duff, R. H. See Passmore, E. M.

Eastman, P. F., and Cutler, I. B. Effect of water vapor on initial sintering of magnesia, (10) 526–30.
Edwards, P. L., and Huang, S. Comparison of whisker growth sites and dislocation etch pits on single-crystal sapphire, (3) 122–25.
Eiss, N. S., Jr., and Fabiniak, R. C. Chemical and mechanical mechanisms in wear of sapphire on steel, (4) 221–26.
Elmer, T. H. See Mochel, E. L.
Eppler, R. A. Viscosity of molten B_2O_3, (12) 679–80.
Ernsberger, F. M. See Neely, J. E.

Fabiniak, R. C. See Eiss, N. S., Jr.
Faile, S. P., and Roy, D. M. Solubilities of Ar, N_2, CO_2, and He in glasses at pressures to 10 kbars, (12) 638–43.
Farnsworth, P. L., and Coble, R. L. Deformation behavior of dense polycrystalline SiC, (5) 264–68.
Feldman, R. F., and Ramachandran, V. S. Character of hydration of $3CaO \cdot Al_2O_3$, (5) 268–73.
Felten, E. J. See Pettit, F. S.
Felten, E. J., Sprang, P. G., and Rosen, S. Phase relations in the system $CoNb_2O_6$-$CoTa_2O_6$, (5) 273–76.
Finnie, Iain. Method for predicting creep in tension and compression from bending tests, (4) 218–20.
Fitzgerald, J. F. See Comer, J. J.
Foster, P. K., and Hughes, I. R. Internal stress in ceramics containing cristobalite, (9) 515.

INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 49, NO. 12 **DECEMBER 21, 1966**

AUTHOR INDEX TO THE JOURNAL

The number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Achar, B. N. N. See Sharp, J. H.
Adelsberg, L. M., Cadoff, L. H., and Tobin, J. M. Group IVB and VB metal carbide-carbon eutectic temperatures, (10) 573–74.
Agajanian, A. H., and Turk, H. L. Magnetic properties of nonstoichiometric NiZn ferrites, (8) 459–60.
Allen, W. C. Temperature dependence of properties of magnesium ferrite, (5) 257–60.
Altemose, V. O. Outgassing of glass caused by thermal neutrons and gamma radiation, (8) 446–50.
Amata, C. D. See Smith, A. W.
Anderson, O. L. See Schreiber, Edward; Soga, Naohiro.
Anderson, O. L., and Andreatch, P., Jr. Pressure derivatives of elastic constants of single crystal MgO at 23° and −195.8°C, (8) 404–409.
Andreatch, P., Jr. See Anderson, O. L.
Ansell, G. S. See Cooke, F. W.
Arafa, S. See Bishay, A. M.
Arias, Alan. Thermal shock resistance of zirconia with 15 mole % titanium, (6) 334–38; Mechanism by which metal additions improve the thermal shock resistance of zirconia, (6) 339–41; Effect of inclusions on grain growth of oxides, (11) 621–24.
Aronson, S., Cisney, E., and Auskern, A. B. Thermal expansion of nonstoichiometric zirconium carbides, (8) 456.
Atlas, L. M., Schlehman, G. J., and Readey, D. W. Defects in PuO_{2-x}: Density measurements at high temperatures, (11) 624–25.
Auskern, A. B. See Aronson, S.
Austerman, S. B., and Wagner, J. W. Cation diffusion in single-crystal and polycrystalline BeO, (2) 94–99.
Ayer, J. E., and Soppet, F. E. Vibratory compaction: II, Compaction of angular shapes, (4) 207–10.

Barker, J. See Busby, T. S.
Barrington, Jonathan. See Bergmann, O. R.
Barry, T. L., Stubican, V. S., and Roy, Rustum. Phase equilibria in the system CaO-Yb_2O_3, (12) 667–70.
Barsom, J. M. Effect of stress and strain on producing hackle in a glass plate, (1) 6–10.
Baskin, Y. Properties of uranium monophosphide, (10) 541–46.
Bates, J. L. Melting points of hypostoichiometric uranium dioxide, (7) 395–96.
Beatty, R. See Westman, A. E. R.
Beisler, J. F. See Pearce, M. L.
Bentle, G. G. Elastic constants of single-crystal BeO at room temperature, (3) 125–28.
Bergeron, C. G. See Liedberg, D. J.
Bergmann, O. R., and Barrington, Jonathan. Effect of explosive shock waves on ceramic powders, (9) 502–507.
Berry, J. M. See Mehan, R. L.
Bishay, A. M., and Arafa, S. Gamma-induced absorption and structural studies of arsenic borate glasses, (8) 423–30.
Blachere, J. R. Desulfurization of pyrite, (11) 590–93.
Blair, R. See O'Bryan, H. M.
Blau, H. H. See Shonebarger, F. J.
Bloor, D. Discussion of paper, "Infrared absorption spectrum of silicon dioxide," (12) 682–83.
Boffe, M. See Plumat, E.
Bolz, L. H. See Ormsby, W. C.
Borom, M. P., and Pask, J. A. Role of "adherence oxides" in the development of chemical bonding at glass-metal interfaces, (1) 1–6.
Bourne, H. L. Silicon monoxide technique for observing surface microtopography, (1) 53–54.
Bradt, R. C. See Cooke, F. W.
Bright, N. F. H., and Turnock, A. C. Nonstoichiometric tantalian magnetites, (3) 170–71.
Brindley, G. W. See Sharp, J. H.
Brissette, L. A., Burnett, P. L., Spriggs, R. M., and Vasilos, T. Thermochemically deformed Y_2O_3, (3) 165–66.
Brittain, J. O. See Carnahan, R. D.
Buehl, W. M. See Cowan, J. H.
Buessem, W. R., Cross, L. E., and Goswami, A. K. Phenomenological theory of high permittivity in fine-grained barium titanate, (1) 33–36; Effect of two-dimensional pressure on the permittivity of fine- and coarse-grained barium titanate, (1) 36–39.
Burggraaf, A. J. Sorption of argon by glass in a gas-discharge lamp, (8) 450–54.
Burnett, P. L. See Brissette, L. A.
Busby, T. S., and Barker, J. Simulative studies of upward drilling, (8) 441–46.

Cable, Michael. Kinetics and mechanisms of fining glasses, (8) 436–41; see also Rasul, C. G.
Cadoff, L. H. See Adelsberg, L. M.
Callister, W. D., Jr., Cutler, I. B., and Gordon, R. S. Thermal decomposition kinetics of boehmite, (8) 419–22.
Cameron, N. M. Relation between melt treatment and glass fiber strength, (3) 144–48.
Carnahan, R. D., and Brittain, J. O. Dislocation damping in rutile single crystals, (1) 15–19.
Caron, L. G. See Newnham, R. E.
Carter, J. R. See Kestigian, M.
Carter, R. E. See Rhodes, W. H.; Simpson, L. A.
Cass, T. R., and Washburn, J. Dislocation etch pits on {110} planes of magnesium oxide, (6) 343–44.
Chaklader, A. C. D., and McKenzie, L. G. Reactive hot-pressing of clays and alumina, (9) 477–83.
Chakrabarty, M. R. See Van Loan, P. R.
Chang, L. L. Y., Scroger, M. G., and Phillips, Bert. Alkaline-earth tungstates: Equilibrium and stability in the M–W–O systems, (7) 385–90.
Chapman, I. D. See Hair, M. L.
Charles, R. J. Metastable liquid immiscibility in alkali metal oxide–silica systems, (2) 55–62.
Chase, A. B. Habit modification of corundum crystals grown from molten PbF_2-Bi_2O_3, (5) 233–36.
Chase, A. B., and Wilcox, W. R. Elimination of inclusions from flux-grown crystals, (8) 460.
Chelko, A. See Johnston, W. D.
Chopra, S. K. See Dave, N. G.
Cimino, A., Porta, P., and Valigi, M. Dependence of the lattice parameter of magnesium oxide on crystallite size, (3) 152–56.
Cisney, E. See Aronson, S.
Clare, T. E. Sintering kinetics of beryllia, (3) 159–65; see also Reeve, K. D.
Class, W. H., and Machlin, E. S. Crack propagation method for measuring grain boundary energies in brittle materials, (6) 306–309.
Coble, R. L. See Farnsworth, P. L.
Cockayne, B. Observation and control of deviations in molar composition in single-crystal growth of mixed oxides, (4) 204–207.
Comer, J. J., Tombs, N. C., and Fitzgerald, J. F. Growth of single-crystal and polycrystalline thin films of $MgAl_2O_4$ and $MgFe_2O_4$, (5) 237–40.
Cook, R. L. See Vernetti, R. A.
Cooke, F. W., Brandt, R. C., DeVries, R. C., and Ansell, G. S. Dielectric aging and microstructure in the system $BaTiO_3$-$CaTiO_3$, (12) 648–51.
Cooper, A. R., Jr., and Heasley, J. H. Extension of Darken's equation to binary diffusion in ceramics, (5) 280–84.
Cowan, J. H., Buehl, W. M., and Hutchins, J. R., III. An electrochemical theory for oxygen reboil, (10) 559–62.
Cross, L. E. See Buessem, W. R.
Cutler, I. B. See Callister, W. D., Jr.; Eastman, P. F.; Hansen, K. W.; Johnson, H. B.; Jones, J. T.; Wilcox, P. D.; Winkler, E. R.

Dave, N. G., and Chopra, S. K. Preparation and thermal decomposition of calcium hydroxide crystals, (10) 575.
Day, R. B., and Stokes, R. J. Effect of crystal orientation on the mechanical behavior of magnesium oxide at high temperatures, (2) 72–80; Mechanical behavior of polycrystalline magnesium oxide at high temperatures, (7) 345–54.
DeClerck, D. H., and Su, Gouq-Jen. Rheological and electrokinetic properties of glass-frit and quartz suspensions, (5) 252–56.
de Menezes, I. See Stubican, V. S.
de Menezes, I., and Stubican, V. S. Grain-boundary reactions in magnesia-chrome refractories: Application of the electron probe, II, (11) 609–12.
DeVries, R. C. See Cooke, F. W.
Dickson, R. W. Anomaly in Young's modulus and internal friction of $5SrTiO_3 \cdot 3La_{2/3}TiO_3$ below 100°C, (11) 628.
Doremus, R. H. Physical solubility of gases in fused silica, (9) 461–62.
Duff, R. H. See Passmore, E. M.

Eastman, P. F., and Cutler, I. B. Effect of water vapor on initial sintering of magnesia, (10) 526–30.
Edwards, P. L., and Huang, S. Comparison of whisker growth sites and dislocation etch pits on single-crystal sapphire, (3) 122–25.
Eiss, N. S., Jr., and Fabiniak, R. C. Chemical and mechanical mechanisms in wear of sapphire on steel, (4) 221–26.
Elmer, T. H. See Mochel, E. L.
Eppler, R. A. Viscosity of molten B_2O_3, (12) 679–80.
Ernsberger, F. M. See Neely, J. E.

Fabiniak, R. C. See Eiss, N. S., Jr.
Faile, S. P., and Roy, D. M. Solubilities of Ar, N_2, CO_2, and He in glasses at pressures to 10 kbars, (12) 638–43.
Farnsworth, P. L., and Coble, R. L. Deformation behavior of dense polycrystalline SiC, (5) 264–68.
Feldman, R. F., and Ramachandran, V. S. Character of hydration of $3CaO \cdot Al_2O_3$, (5) 268–73.
Felten, E. J. See Pettit, F. S.
Felten, E. J., Sprang, P. G., and Rosen, S. Phase relations in the system $CoNb_2O_6$-$CoTa_2O_6$, (5) 273–76.
Finnie, Iain. Method for predicting creep in tension and compression from bending tests, (4) 218–20.
Fitzgerald, J. F. See Comer, J. J.
Foster, P. K., and Hughes, I. R. Internal stress in ceramics containing cristobalite, (9) 515.

Foster, W. R. See Rockett, T. J.
Franz, Helmut. Solubility of water vapor in alkali borate melts, (9) 473–77.
Fullmer, L. D. See Wilcox, W. R.
Fulrath, R. M. See Hasselman, D. P. H.

Gaines, A. M., Perrotta, A. J., and Stephenson, D. A. Phenacite-spinel transition in $LiAlGeO_4$, (9) 516.
Garabedian, F. G. See Kestigian, M.
Giess, E. A. Vaporization of PbO-PbF_2 melt during solution growth of YIG crystals, (2) 104–105.
Gilles, P. W. See Wahlbeck, P. G.
Goldman, A. See Lewis, H. D.
Gordon, R. S. See Callister, W. D., Jr.
Gordon, R. S., and Kingery, W. D. Thermal decomposition of brucite: I, Electron and optical microscope studies, (12) 654–60.
Goswami, A. K. See Buessem, W. R.
Greene, P. E. See Sobon, L. E.
Grenis, A. F., and Levitt, A. P. Infrared radiation of titanium boronitride, (12) 629–31.
Greskovich, C. See Stubican, V. S.
Grodkiewicz, W. H., and Nitti, D. J. Oxide crystal growth by flux evaporation, (10) 576.
Gruver, R. M. See Kirchner, H. P.

Haertling, G. H. Grain growth and densification of hot-pressed lead zirconate-lead titanate ceramics containing bismuth, (3) 113–18.
Hagel, W. C., Jorgensen, P. J., and Tomalin, D. S. Initial sintering of α-Cr_2O_3, (1) 23–26.
Hair, M. L., and Chapman, I. D. Surface composition of porous glass, (12) 651–54.
Hansen, K. W. See Kolb, K. E.
Hansen, K. W., and Cutler, I. B. Electrical conductivity in $Fe_{1-x}O$-MgO solid solutions, (2) 100–102.
Harkulich, T. M., Magder, Jules, Vukasovich, M. S., and Lockhart, R. J. Ferroelectrics of ultrafine particle size: II, Grain growth inhibition studies, (6) 295–99.
Hasselman, D. P. H. Theory of thermal shock resistance of semitransparent ceramics under radiation heating, (2) 103–104.
Hasselman, D. P. H., and Fulrath, R. M. Proposed fracture theory of a dispersion-strengthened glass matrix, (2) 68–72.
Hayakawa, Shigeru. See Nitta, Tsuneharu; Ouchi, Hiromu.
Heasley, J. H. See Cooper, A. R., Jr.
Hirota, Eiichi. See Nakayama, Nobuo.
Hirthe, W. M., Melville, A. T., and Wackman, P. H. Preparation by ion bombardment of near-stoichiometric rutile (TiO_2) for transmission electron microscopy, (8) 454–55.
Hoenig, C. L., and Searcy, A. W. Knudsen and Langmuir evaporation studies of stannic oxide, (3) 128–34.
Holmquist, S. B. Ionic formulation of redox equilibria in glass melts, (4) 228–29; Hydrothermal silica transformations, (7) 397–98; Oxygen ion activity and the solubility of sulfur trioxide in sodium silicate melts, (9) 467–73; Reply to comment on note "Hydrothermal silica transformations, (12) 678.
Horiguchi, Yoshikazu. Formation of zinc orthosilicate by explosive shock, (9) 519.
Huang, S. See Edwards, P. L.
Hughes, I. R. See Foster, P. K.
Hulse, C. O., and Pask, J. A. Analysis of deformation of a fireclay refractory, (6) 312–18.
Hulse, C. O., and Tice, W. K. General fracture method for preparation of foils for transmission electron microscopy, (4) 190–94.
Humenik, M., Jr. See McHugh, C. O.
Hutchins, J. R., III. See Cowan, J. H.

Janakirama-Rao, Bh. V. Infrared spectra of GeO_2-P_4O_{10}-V_2O_5 glasses and their relation to structure and electronic conduction, (11) 605–609.
Jeschke, Peter. Texture analysis of basic refractory brick, (7) 360–63.
Jetzt, J. J. See MacChesney, J. B.
Johnson, H. B., Johnson, O. W., and Cutler, I. B. Effect of water vapor on dielectric loss in MgO, (7) 390–94.
Johnson, H. B., Tolar, N. J., Miller, G. R., and Cutler, I. B. Dipole relaxation in CaF_2 doped with NaF, (8) 458.
Johnson, O. W. See Johnson, H. B.
Johnston, W. D. Formulation of oxidation-reduction reactions in glass melts, (9) 513–14.
Johnston, W. D., and Chelko, A. Oxidation-reduction equilibria in molten $Na_2O \cdot 2SiO_2$ glass in contact with metallic copper and silver, (10) 562–64.
Jones, J. T., and Cutler, I. B. Stoichiometry of MgO-Mn_2O solid solutions in air at high temperatures, (10) 572–73.
Jorgensen, P. J. See Hagel, W. C.

Katz, Gerald, and Roy, Rustum. Flux growth and characterization of β-Ga_2O_3 single crystals, (3) 168–69.
Kerper, M. J., and Scuderi, T. G. Mechanical properties of chemically strengthened glasses at high temperatures, (11) 613–18.
Kestigian, M., Leipziger, F. D., Carter, J. R., and Garabedian, F. G. Preparation of $K_4Nb_6O_{17}$ single crystals, (9) 517.
Kingery, W. D. See Gordon, R. S.; Rhodes, W. H.
Kirchner, H. P., and Gruver, R. M. Chemical strengthening of polycrystalline ceramics, (6) 330–33.
Kiss, Klara, Magder, Jules, Vukasovich, M. S., and Lockhart, R. J. Ferroelectrics of ultrafine particle size: I, Synthesis of titanate powders of ultrafine particle size, (6) 291–95.
Kivlighn, H. D., Jr. Solid state reactivity and glass crystallization behavior of some alkali aluminogermanates, (3) 148–51.
Klinger, N., Strauss, E. L., and Komarek, K. L. Reactions between silica and graphite, (7) 369–75.
Kolb, E. D., and Laudise, R. A. Hydrothermally grown ZnO crystals of low and intermediate resistivity, (6) 302–305.
Kolb, K. E., and Hansen, K. W. Time and temperature effects on silica distribution in borate glasses, (2) 105–106.
Komarek, K. L. See Klinger, N.
Kramer, W. E., and Mazelsky, R. Crystal growth of β-spodumene, (5) 290.
Krause, J. T. See Kurkjian, C. R.
Krishnan, R. Influence of NiO on the yield of yttrium-iron garnet crystals grown from flux, (12) 678–79.
Kroenke, W. J. Mechanical test for anisotropy; failure of aluminoborosilicate glass fibers under combined loadings of tension and torsion, (9) 508–13.
Kröger, F. A. Electronic conductivity of calcia-stabilized zirconia, (4) 215–18.
Kruger, O. L., and Moser, J. B. Sintering characteristics and properties of PuS and PuP, (12) 661–67.
Kuczynski, G. C. See Readey, D. W.
Kumar, S., and Nag, B. B. Electrical properties of crystallized glasses in the system MgO–Al_2O_3–SiO_2–TiO_2, (1) 10–14.
Kurkjian, C. R., and Krause, J. T. Acoustic spectra of Na_2O-GeO_2 glasses, (3) 134–38; Effect of OH content on the acoustic spectra of B_2O_3 glass, (3) 171–72.

Lahiri, D. See Paul, A.
Laudise, R. A. See Kolb, E. D.
Leipold, M. H. Impurity distribution in MgO, (9) 498–502; see also Nielsen, T. H.
Leipziger, F. D. See Kestigian, M.
Lennon, J. W. Nomograph for converting average intercept size to average grain size, (7) 398–99.
Levitt, A. P. See Grenis, A. F.
Lewis, D., and Lindley, M. W. Enhanced activity and the characterization of ball-milled alumina, (1) 49–50.
Lewis, H. D., and Goldman, A. Theorems for calculation of weight ratios to produce maximum packing density of powder mixtures, (6) 323–27.
Liedberg, D. J., Smid, R. J., and Bergeron, C. G. Microseparation in lead borate glasses, (2) 80–83.
Lindley, M. W. See Lewis, D.
Lockhart, R. J. See Harkulich, T. M.; Kiss, Klara.
Lockhart, R. J., and Magder, Jules. Ferroelectrics of ultrafine particle size: III, Thin barium titanate layers for capacitors, (6) 299–302.
Lynch, C. T. See Mazdiyasni, K. S.

MacChesney, J. B., Jetzt, J. J., Potter, J. F., Willams, H. J., and Sherwood, R. C. Electrical and magnetic properties of the system $SrFeO_3$-$BiFeO_3$, (12) 644–47.
McCormick, G. R. Subsolidus equilibria in the system MgO–GeO_2–MgF_2, (11) 618–20.
McDaniel, C. L., and Schneider, S. J. Phase relations between Cr_2O_3 and IrO_2 in air, (5) 285–86.
McGee, T. D. Constitution of fireclays at high temperatures: I, Methods of analysis, (2) 83–87; II, Mineralogical composition, (2) 87–90; III, Deformation characteristics, (2) 90–94.
McHugh, C. O., Whalen, T. J., and Humenik, M., Jr. Dispersion-strengthened aluminum oxide, (9) 486–91.
Machlin, E. S. See Class, W. H.
Mackenzie, J. D. See Schwartz, Michael.
McKenzie, L. G. See Chaklader, A. C. D.
Magder, Jules. See Harkulich, T. M.; Kiss, Klara; and Lockhart, R. J.
Manning, W. R., Marlowe, M. O., and Wilder, D. R. Temperature and porosity dependence of Young's modulus of polycrystalline dysprosium oxide and erbium oxide, (4) 227–28.
Marlowe, M. O. See Manning, W. R.
Masse, D. P., Rosén, Erik, and Muan, Arnulf. Activity-composition relations in Co_2SiO_4-Fe_2SiO_4 solid solutions at 1180°C, (6) 328–29.
Matsuo, Yoshihiro, and Sasaki, Hiromu. Effect of grain size on microcracking in lead titanate ceramics, (4) 229–30.
Mazdiyasni, K. S., Lynch, C. T., and Smith, J. S. Metastable transitions of zirconium oxide obtained from decomposition of alkoxides, (5) 286–87.
Mazelsky, R. See Kramer, W. E.
Mehan, R. L., and Berry, J. M. Nonlinear behavior in three-point bending of high-strength, high-modulus fibers, (3) 169–70; correction, (12) 683.
Melville, A. T. See Hirthe, W. M.
Meszaros, F. W. See Smith, A. W.
Miller, G. R. See Johnson, H. B.
Mochel, E. L., Nordberg, M. E., and Elmer, T. H. Strengthening of glass surfaces by sulfur trioxide treatment, (11) 585–89.
Mockrin, I. See Phillips, Bert.
Monforte, F. E. See O'Bryan, H. M.
Moodie, A. F., Warble, C. E., and Williams, L. S. Magnesia precursor and sintering study, (12) 676–77.
Mori, Saburo. Phase transformation in barium orthoferrate, $BaFeO_{3-x}$, (11) 600–605.
Moser, J. B. See Kruger, O. L.
Muan, Arnulf. See Masse, D. P.; Rosén, Erik.
Mulfinger, Hans-Otto. Physical and chemica solubility of nitrogen in glass melts, (9) 462–67.
Murthy, M. K., and Westman, A. E. R. Constitution of mixed-alkali phosphate glasses: IV, Constitution of lithium-cesium phosphate glasses, (6) 310–11.

Nag, B. B. See Kumar, S.
Nagase, Kaneomi. See Nitta, Tsuneharu.
Nakayama, Nobuo, Hirota, Eiichi, and Nishikawa, Tomozo. Hot-pressing of CrO_2, (1) 52–53.
Neely, J. E., and Ernsberger, F. M. Absence of devitrification at bubble surfaces in soda-lime glasses, (7) 396–97.
Newnham, R. E., Caron, L. G., and Santoro, R. P. Magnetic properties of $CaCoSiO_4$ and $CaFeSiO_4$, (5) 284–85.
Nicholson, G. C. Grain growth in magnesium oxide containing iron oxide or titanium dioxide, (1) 47–49.
Nielsen, T. H., and Leipold, M. H. Surface hydroxyl in MgO, (11) 626–27.
Nishida, Masamitsu. See Ouchi, Hiromu.
Nishikawa, Tomozo. See Nakayama, Nobuo.
Nitta, Tsuneharu, Nagase, Kaneomi, and Hayakawa, Shigeru. Electroless nickel-phosphorus alloy electrode for semiconductive barium titanate ceramics, (8) 457.
Nitti, D. J. See Grodkiewicz, W. H.
Nordberg, M. E. See Mochel, E. L.

O'Bryan, H. M., Monforte, F. R., and Blair, R. Reply to discussion of paper "Oxygen content of nickel ferrite at 1300°C," (12) 680–81.
Ohashi, Tokuyoshi, and Watanabe, Akinori. Sintering of vanadium dioxide, (1) 46–47; Temperature dependence of electrical resistivity of VO_2 powder, (9) 519–20.
Ormsby, W. C., and Bolz, L. H. Microtexture and composition of reaction products in the system kaolin-lime-water, (7) 364–66.
Osborn, E. F. Comment on note, "Hydrothermal silica transformations," (12) 677.
Ouchi, Hiromu, Nishida, Masamitsu, and Hayakawa, Shigeru. Piezoelectric properties of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics modified with certain additives, (11) 577–82.

Paladino, A. E. Discussion of paper, "Oxygen content of nickel ferrites at 1300°C," (5) 288–89.
Paladino, A. E., and Roiter, B. D. Czochralski growth of yttrium-gallium garnet, (1) 51–52.
Pask, J. A. See Borom, M. P.; Hulse, C. O.
Passmore, E. M., Duff, R. H., and Vasilos, T. Creep of dense, polycrystalline magnesium oxide, (11) 594–600.
Passmore, E. M., and Vasilos, T. Creep of dense, pure, fine-grained aluminum oxide, (3) 166–68.
Paul, A., and Lahiri, D. Manganous-manganic equilibrium in alkali borate glasses, (10) 565–68.
Pearce, M. L., and Beisler, J. F. Diffusion studies of Na_2O-SiO_2-Fe_2O_3 melts at 1200°C, (10) 547–51.
Perrotta, A. J. See Gaines, A. M.
Pettit, F. S., Randklev, E. H., and Felten, E. J. Formation of $NiAl_2O_4$ by solid state reaction, (4) 199–203.
Phillips, Bert. See Chang, L. L. Y.
Phillips, Bert, Warshaw, C. M., and Mockrin, I. Equilibria in $KAlF_4$-containing systems, (12) 631–34.
Plumat, E., Toussaint, F., and Boffe, M. Formation of bubbles by electrochemical processes in glass, (10) 551–58.
Porta, P. See Cimino, A.
Poteat, L. E., and Yust, C. S. Creep of polycrystalline thorium dioxide, (8) 410–14.
Potter, J. F. See MacChesney, J. B.
Probst, H. B. See Sanders, W. A.

Ramachandran, V. S. See Feldman, R. F.
Randklev, E. H. See Pettit, F. S.
Rasul, C. G., and Cable, M. Spontaneous bubble formation in silicate melts at high temperatures, (10) 568–71.
Readey, D. W. Mass transport and sintering in impure ionic solids, (7) 366–69; Nonstoichiometry of cadmium sulfide thin films, (12) 681–82; see also Atlas, L. M.
Readey, D. W., and Kuczynski, G. C. Sublimation of aluminum oxide in hydrogen, (1) 26–29.
Reeve, K. D., and Clare, T. E. Comments on papers "Sintering in very pure magnesium oxide and magnesium oxide containing vanadium" and "Sintering in calcium oxide and calcium oxide containing strontium," (7) 400.
Rhodes, W. H. Etching and chemical polishing of single-crystal $SrTiO_3$, (2) 110–12.
Rhodes, W. H., and Carter, R. E. Cationic self-diffusion in calcia-stabilized zirconia, (5) 244–49.

Rhodes, W. H., and Kingery, W. D. Dislocation dependence of cationic diffusion in $SrTiO_3$, (10) 521–26.
Richards, K. J. Oriented growth of dehydration products of calcium sulfate dihydrate, (6) 342–43; see also Wagstaff, F. E.
Riebling, E. F. Structure of B_2O_3 and binary aluminoborate melts at 1600°C, (1) 19–23.
Rockett, T. J., and Foster, W. R. System silica–sodium tetraborate, (1) 30–33.
Roiter, B. D. See Paladino, A. E.
Rosén, Erik. See Masse, D. P.
Rosén, Erik, and Muan, Arnulf. Stability of $MgAl_2O_4$ at 1400°C as derived from equilibrium measurements in $CoAl_2O_4$-$MgAl_2O_4$ solid solutions, (2) 107–108.
Rosen, S. See Felten, E. J.
Roy, D. M. See Faile, S. P.; Schlaudt, C. M.
Roy, Rustum. See Barry, T. L.; Katz, Gerald; Vedam, K.

Sanders, W. A., and Probst, H. B. Hardness of five borides at 1625°C, (4) 231–32.
Santoro, R. P. See Newnham, R. E.
Sarver, J. F. See Winkler, E. R.
Sasaki, Hiromu. See Matsuo, Yoshihiro.
Schlaudt, C. M., and Roy, D. M. The join Ca_3SiO_5-$CaMgSiO_4$, (8) 430–32.
Schlehman, G. J. See Atlas, L. M.
Schmidt, E. D. D. See Vedam, K.
Schneider, S. J. See McDaniel, C. L.
Schreiber, Edward, and Anderson, O. L. Pressure derivatives of the sound velocities of polycrystalline alumina, (4) 184–90.
Schreiber, Edward, and Soga, Naohiro. Elastic constants of silicon carbide, (6) 342.
Schwartz, Michael, and Mackenzie, J. D. Ionic conductivity in calcium silicate glasses, (11) 582–85.
Scroger, M. G. See Chang, L. L. Y.
Scuderi, T. G. See Kerper, M. J.
Searcy, A. W. See Hoenig, C. L.
Shafer, M. W., and Suits, J. C. Preparation and Faraday rotation of divalent europium glasses, (5) 261–64.
Sharp, J. H., Brindley, G. W., and Achar, B. N. N. Numerical data for some commonly used solid state reaction equations, (7) 379–82.
Sherwood, R. C. See MacChesney, J. B.
Shonebarger, F. J., and Blau, H. H. Study of glass surfaces by generation of electrostatic charges, (9) 492–97.
Simpson, L. A., and Carter, R. E. Oxygen exchange and diffusion in calcia-stabilized zirconia, (3) 139–44.
Smid, R. J. See Liedberg, D. J.
Smith, A. W., Meszaros, F. W., and Amata, C. D. Permeability of zirconia, hafnia, and thoria to oxygen, (5) 240–44.
Smith, D. K. The nonexistence of yttrium zirconate, (11) 625–26.
Smith, J. S. See Mazdiyasni, K. S.
Smoke, E. J. See Ulrich, D. R.
Sobon, L. E., and Greene, P. E. Crystal growth of some vanadium oxides, (2) 106–107.
Soga, Naohiro. See Schreiber, Edward.
Soga, Naohiro, and Anderson, O. L. Simplified method for calculating elastic moduli of ceramic powder from compressibility and Debye temperature data, (6) 318–22; High-temperature elastic properties of polycrystalline MgO and Al_2O_3, (7) 355–59.
Soppet, F. E. See Ayer, J. E.
Sprang, P. G. See Felten, E. J.
Spriggs, R. M. See Brissette, L. A.
Stephenson, D. A. See Gaines, A. M.
Stokes, R. J. Thermal-mechanical history and the strength of magnesium oxide single crystals: II, Etch pit and electron transmission studies, (1) 39–46; see also Day, R. B.
Strauss, E. L. See Klinger, N.
Stubican, V. S. See Barry, T. L.; de Menezes, I.
Stubican, V. S., and de Menezes, I. Grain-boundary reactions in magnesia-chrome refractories: application of the electron probe, I, (10) 535–40.
Stubican, V. S., and Greskovich, C. Jahn-Teller distortion induced by tetrahedral-site Cr^{2+} ions in spinels, (9) 518–19.
Su, Goug-Jen. See DeClerck, D. H.
Sucov, E. W. Correction: Diffusion of oxygen in vitreous silica, (4) 232.
Suits, J. C. See Shafer, M. W.

Tallan, N. M., and Vest, R. W. Electrical properties and defect structure of Y_2O_3, (8) 401–404.
Tennery, V. J. Dielectric properties and phase transitions of ferroelectric sodium-strontium niobates, (7) 376–79; High-temperature phase transitions in $PbZrO_3$, (9) 483–86.
Tice, W. K. See Hulse, C. O.
Tobin, J. M. See Adelsberg, L. M.
Tolar, N. J. See Johnson, H. B.
Tomalin, D. S. See Hagel, W. C.
Tombs, N. C. See Comer, J. J.
Toussaint, F. See Plumat, E.
Turk, H. L. See Agajanian, A. H.
Turnock, A. C. Fe-Nb oxides: phase relations at 1180°C, (4) 177–80; Mn-Ta oxides: phase relations at 1200°C, (7) 382–84; see also Bright, N. F. H.

Ulmer, G. C., and White, W. B. Existence of chromous ion in the spinel solid solution series $FeCr_2O_4$-$MgCr_2O_4$, (1) 50–51.
Ulrich, D. R., and Smoke, E. J. Devitrified barium titanate dielectrics, (4) 210–15.

Valigi, M. See Cimino, A.
Van Loan, P. R., and Chakrabarty, M. R. Crystal chemistry and dielectric properties in the systems $BaTiO_3$-UO_2 and $BaTiO_3$-$BaUO_3$, (5) 276–80.
Vasilos, T. See Brissette, L. A.; Passmore, E. M.; Wuensch, B. J.
Vedam, K., Schmidt, E. D. D., and Roy, Rustum. Nonlinear variation of refractive index of vitreous silica with pressure to 7 kbars, (10) 531–35.
Vernetti, R. A., and Cook, R. L. Effect of metal oxide additions on the high-temperature electrical conductivity of alumina, (4) 194–99.
Vest, R. W. See Tallan, N. M.
Vukasovich, M. S. See Harkulich, T. M.; Kiss, Klara.

Wackman, P. H. See Hirthe, W. M.
Wagner, J. W. See Austerman, S. B.
Wagstaff, F. E., and Richards, K. J. Kinetics of crystallization of stoichiometric SiO_2 glass in H_2O atmospheres, (3) 118–21.
Wahlbeck, P. G., and Gilles, P. W. Reinvestigation of the phase diagram for the system titanium–oxygen, (4) 180–83.
Warble, C. E. See Moodie, A. F.
Warshaw, C. M. See Phillips, Bert.
Washburn, J. See Cass, T. R.
Watanabe, Akinori. See Ohashi, Tokuyoshi.
Westman, A. E. R. See Murthy, M. K.
Westman, A. E. R., and Beatty, R. Equations for calculating chain length distributions in polyphosphoric acids and polyphosphate glasses, (2) 63–67.
Whalen, T. J. See McHugh, C. O.
White, W. B. See Ulmer, G. C.
Wilcox, P. D., and Cutler, I. B. Strength of partly sintered alumina compacts, (5) 249–52.
Wilcox, W. R. See Chase, A. B.
Wilcox, W. R., and Fullmer, L. D. Growth of $KTaO_3$-$KNbO_3$ mixed crystals, (8) 415–18.
Wilder, D. R. See Manning, W. R.; Wirkus, C. D.
Williams, H. J. See MacChesney, J. B.
Williams, L. S. See Moodie, A. F.
Williams, W. S. High-temperature thermal conductivity of transition metal carbides and nitrides, (3) 156–59.
Winkler, E. R., Sarver, J. F., and Cutler, I. B. Solid solution of titanium dioxide in aluminum oxide, (12) 634–37.
Wirkus, C. D., and Wilder, D. R. High-temperature oxidation of molybdenum disilicide, (4) 173–77.
Wuensch, B. J., and Vasilos, T. Origin of grain-boundary diffusion in MgO, (8) 433–36.
Wuttig, M. Grain-boundary diffusion of Ni^{2+} in MgO, (2) 112.

Yakhkind, A. K. Tellurite glasses, (12) 670–75.
Yust, C. S. See Poteat, L. E.

Zaplatynsky, I. Observations on zeta phase in the system Ta–C, (2) 109–10.

SUBJECT INDEX TO THE JOURNAL

Volume 49, 1966

The number in parentheses refers to the *monthly* issue of *The Journal;* the number following is the *page* number.

Absorption, of argon by glass in gas-discharge lamp, (8) 450.
γ-induced, of arsenic borate glasses, (8) 423.
infrared, at 1.4μ and 20°C for B_2O_3, (3) 172.
infrared spectrum, of SiO_2, discussion of paper, (12) 682.
Acids. *See also specific types.*
polyphosphoric, equations for calculating chain length distributions in, (2) 63.
Adherence, oxides, in development of chemical bonding at glass-metal interfaces, (1) 1.
Adsorption, of ammonia on porous glass surfaces, (12) 653.
Aging, characteristics, of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, (11) 580; dielectric, and microstructure in system $BaTiO_3$-$CaTiO_3$, (12) 648; effect on deflocculated and flocculated frit suspensions, (5) 255.
Argon, solubility in glasses, (12) 638.
Alkaline earths, tungstates, equilibrium and stability in the M-W-O systems, (7) 385.
Alkalis. See *Systems.*
Alkoxides, ZrO_2 from decomposition of, metastable transition in, (5) 286.
Alumina. See also *Aluminum, oxide; Phase diagrams; Systems.*
alpha, monohydrate, decomposition of, (8) 419.
ball-milled, enhanced activity and characterization, (1) 49.
effect on glass surface strength after SO_3 treatment, (11) 588.
high-temperature electrical conductivity, effect of metal oxide additions, (4) 194.
polycrystalline, pressure derivatives of the sound velocities, (4) 184.
-pyrite mixtures, reactions during heating, (11) 591.
spheres, dispersed in glass matrix, effect on Griffith cracks, (2) 70.
spheres, opaque and transparent, determination of thermal shock resistance, (2) 104.
Aluminoborates, melts, structure at 1600°C, (1) 19.
Aluminogermanates, alkali, solid state reactivity and glass crystallization behavior, (3) 148.
Aluminum. See also *Phase diagrams; Systems.*
Al_2O_3-NiO diffusion couples, growth of $NiAl_2O_4$ in, (4) 199.
Aluminum (*continued*)
oxide, ceramics, strengthened by Al_2O_3-Cr_2O_3 surface layers, (6) 330.
dispersion-strengthened, (9) 486.
fine-grained creep of, (3) 166.
grain growth studies, (11) 622.
polycrystalline, elastic moduli, as function of porosity, (6) 321.
polycrystalline, high-temperature elastic properties, (7) 355.
reactive hot-pressing of, (9) 477.
solid solution of TiO_2 in, (12) 634.
strength of partly sintered compacts, (5) 249.
Ammonia, adsorption on porous glass, (12) 653; reactions with silicate melts, (9) 464.
Analysis. See also *Thermal analysis; X rays.*
chemical, of hot-pressed MgO, effect of impurity segregation, (9) 498.
methods, for constitution of fireclays at high temperatures, (2) 83.
spectrographic, of $BaTiO_3$ from pyrolysis of barium titanyl oxalate, (6) 292.

Analysis (*continued*)
spectrographic, of La in sapphire crystals, (5) 235.
thermogravimetric, of $MoSi_2$, (4) 173.
Anisotropy, mechanical test for, (9) 508.
Argon, sorption, by glass in gas-discharge lamp, (8) 450.
Arsenic, effect on infrared absorption in borate glasses, (8) 423.
Atmosphere, effect on foaming in silicate melts, (10) 568; effect on reactions during heating of pyrite, (11) 590.

Barium. See also *Phase diagrams; Systems.*
orthoferrate, $BaFeO_{3-x}$, phase transformation in, (11) 600.
oxides, molar refractions for different wavelengths, (12) 674.
titanate, dielectric, preparation by devitrification, (4) 210.
effect of $CaTiO_3$ on ferroelectric domains in, (12) 648.
effect of UO_2 and $BaUO_3$ additions on structure, (5) 276.
fine-grained, theory of high permittivity in, (1) 33.
fine- and coarse-grained, effect of two-dimensional pressure on permittivity, (1) 36.
semiconductive, electroless Ni–P alloy electrode for, (8) 457.
thin layers, for capacitors, (6) 299.
titanyl oxalate, ferroelectrics of ultrafine particle size, (6) 291.
Bending, tests, prediction of creep in tension and compression from, (4) 218; three-point, nonlinear behavior of high-strength, high-modulus fibers in, (3) 169.
Beryllia. See *Beryllium, oxide.*
Beryllium. See also *Systems.*
oxide, cation diffusion in, (2) 94.
single-crystal, room temperature elastic constants, (3) 125.
sintering kinetics of, (3) 159.
Bismuth. See also *Systems.*
effect on electrical and magnetic properties of $SrFeO_3$, (12) 644.
effect on grain growth and densification of hot-pressed $PbZrO_3$–$PbTiO_3$ ceramics, (3) 113.
Boehmite, compacts, compressive strength as function of temperature, (9) 479; thermal decomposition kinetics of, (8) 419.
Bonding, chemical, at glass-metal interfaces, role of "adherence oxides" in, (1) 1.
Borides, of transition metals, hardness at 1625°C, (4) 231.
Boron. See also *Phase diagrams; Systems.*
filaments, behavior in three-point bending, (3) 170.
oxide, glass, effect of OH content on acoustic spectra, (3) 171.
on surface of porous glass, (12) 651.
trioxide, structure at 1600°C, (1) 19.
Brucite, thermal decomposition: I, electron and optical microscope studies, (12) 654.

Cadmium, sulfide, nonstoichiometry of thin films, (12) 681.
Calcination, relation to sinterability of MgO, (12) 676.
Calcium. See also *Phase diagrams; Systems.*
$3CaO \cdot Al_2O_3$, hydration of, (5) 268.
fluoride, doped with NaF, dipole relaxation in, (8) 458.
hydroxide, crystals, preparation and thermal decomposition, (10) 575.
ion diffusion in Ca-stabilized ZrO_2, (5) 247.
orthosilicates, of Co, Mn, and Fe, magnetic properties of, (5) 284.
oxide, and CaO containing Sr, sintering in, comment on paper, (7) 400.
oxide, effect on electronic conductivity of ZrO_2, (4) 215.
sulfate dihydrate, oriented growth of dehydration products, (6) 342.
titanate, solid solution in $BaTiO_3$, (12) 648.
Capacitors, thin barium titanate layers for, (6) 299.
Carbides, of groups IVB and VB metals, eutectic temperatures with carbon, (10) 573.
transition metal, high-temperature thermal conductivity of, (3) 156.
U-Pu, in nuclear fuel rods made by vibratory compaction, (4) 210.
zirconium, thermal expansion of, (8) 456.
Carbon. See also *Graphite; Systems.*
dioxide, solubility in glasses, (12) 638.
and group IVB and VB metal carbides, eutectic temperatures for, (10) 573.
monoxide, amount formed in reactions between silica and graphite, (7) 370.
Casting, of films, from dispersion of $BaTiO_3$, (6) 300.
Cathodoluminescence. See *Luminescence.*
Cells, thermal, cause of O_2 reboil in glass, (10) 562.
Cement, portland, aluminate phase in early hydration reactions, (5) 269.
Ceramographs, of fine-grained $BaTiO_3$ from oxalate pyrolysis flash-fired at 1300°C for 1 min, (6) 297.
Cesium, $CsAlGeO_4$, X-ray powder data, (3) 149; -lithium phosphate glasses, constitution of, (6) 310.
Chemical potentials, of constituents of impure ionic solids, as function of pressure and impurity concentration, (7) 366.
Chromium. See also *Phase diagrams; Systems.*
α-Cr_2O_3, initial sintering, (1) 23.
Cr_2O_3 and IrO_2, phase relations, in air, (5) 285.
content, of Al_2O_3–Cr_2O_3 solid solution vs. distance from Al_2O_3 surface, (6) 331.
dioxide, hot-pressing of, (1) 52.
ions, tetrahedral site, in spinels, Jahn-Teller distortion induced by, (9) 518.
Circuits, equivalent, to explain dielectric loss behavior of porous MgO, (7) 391.
Clays, reactive hot-pressing of, (9) 477.
Coatings, Al_2O_3–Cr_2O_3, effect on properties of Al_2O_3 bars, (7) 333; glass, argon sorption at 270°C, (8) 452; thin, single crystal and polycrystalline, of $MgAl_2O_4$ and $MgFe_2O_4$, growth on MgO, (5) 237.
Cobalt. See also *Phase diagrams; Systems.*
Co^{2+}, preferential diffusion along grain boundaries in MgO bicrystals, (8) 434; orthosilicate, in cobalt-iron-orthosilicate solid solutions, activity-composition relations of, (6) 328.
Color, γ-induced, in arsenic borate glasses, in study of structure, (8) 423.
Compaction, vibratory, II, (4) 207.
Compatibility, relations, in system MgO–GeO_2–MgF_2 below 1200°C, (11) 620.
Compressibility, ambient adiabatic, of Al_2O_3, (4) 186.
Compression, apparatus for testing polycrystalline ThO_2, (8) 411; and Debye temperature data, calculation of elastic moduli of ceramic powder from, (6) 318; two-dimensional, variation of permittivity with, for $BaTiO_3$ specimens of different grain sizes, (1) 37.
Conductivity, electrical, ac, of porous MgO, effect of H_2O partial pressures on, (7) 392.
of Al_2O_3, effect of metal oxide additions, (4) 194.
of high-purity, polycrystalline Y_2O_3, (8) 402.
in $Fe_{1-x}O$–MgO solid solutions, (2) 100.
in Li-doped ZnO crystals, (6) 305.
Conductivity, electronic, of CaO-stabilized ZrO_2, (4) 215; of GeO_2–P_4O_{10}–V_2O_5 glasses, relation of infrared spectra to, (11) 605.
Conductivity, ionic, in calcium silicate glasses, (11) 582.
Conductivity, thermal, high-temperature, of transition metal carbides and nitrides, (3) 156; of PuS and PuP, (12) 666; of zirconia with 15 mole % titanium, (6) 335.
Conductors, ionic or electronic, noble metals, soda-lime-silicate glass, and oxides as, (10) 551.
Cooling, rate, effect on cristobalite and mullite content of fireclays, (2) 85; rate, effect on thermal contraction of $MgFe_2O_4$, (5) 257.
Copper, effect on oxidation-reduction equilibria in molten $Na_2O \cdot SiO_2$ glass, (10) 562.
Corrections, of "Diffusion of Oxygen in Vitreous Silica," (4) 232; on "Nonlinear Behavior in Three-Point Bending of High-Strength, High-Modulus Fibers," (12) 683.
Corrosion, profile at horizontal joints caused by upward drilling in glass, (8) 442.
Corundum, crystals, grown from molten PbF_2–Bi_2O_3, habit modification, (5) 233.
Cracks, in brucite crystal, micrographs of, (12) 659.
Griffith, in glass matrix, effect of hard crystalline dispersions on, (2) 70.
propagation, mechanism, in production of thin foils, (4) 190.
propagation method, for measuring grain boundary energies in brittle materials, (6) 306.
Creep, data, for firebrick under compressive load, (6) 314.
of dense, polycrystalline MgO, (11) 594.
of fine-grained Al_2O_3, (3) 166.
of polycrystalline thorium dioxide, (8) 410.
tensile and compressive, prediction from deflection measurements in bending tests, (4) 218.
Cristobalite, content, in fireclays, effect of quenching, (2) 86; internal stress in ceramics containing, (9) 515.
Crystal chemistry, in systems $BaTiO_3$–UO_2 and $BaTiO_3$-$BaUO_3$, (5) 276.
Crystallites, size, dependence of MgO lattice parameter on, (3) 153.
Crystallization, rates, of stoichiometric SiO_2 glass in H_2O, N_2, and vacuum, (2) 119; re-, prevention in sintered Al_2O_3, (9) 491; re-, single-crystal, of MgO, effect on high-temperature tensile deformation, (7) 345.
Crystals, β-spodumene, growth of, (5) 290.
bi- of MgO, diffusion couples prepared with, (8) 435.
brucite, changes in physical state caused by decomposition, (12) 654.
calcium hydroxide, preparation and thermal decomposition, (10) 575.
Czochralski-grown $Y_3Ga_5O_{12}$, (1) 52.
dislocation damping in, (1) 17.
flux-grown, elimination of inclusions, (8) 460.
growth of some vanadium oxides, (2) 106.
habit, of β-Ga_2O_3, (3) 168.
habits of primary phases, in system SiO_2–Na_2O–$4B_2O_3$, (1) 32.
MgO, dislocations grown-in, (1) 41.
orientation, effect on mechanical behavior of MgO at high temperatures, (2) 72.
oxide, growth by flux evaporation, (10) 576.
$KTaO_3$-$KNbO_3$ mixed, growth of, (8) 415.
screw dislocations etched on surface of Al_2O_3 sphere heated in H_2 at 1850°C, (1) 29.
single, and poly-, of $MgAl_2O_4$ and $MgFe_2O_4$, growth as thin films on MgO, (5) 237.
MgO, pressure derivatives of elastic constants at 25° and −195.8°C, (8) 404.
mixed oxide, deviations in molar composition in growth of, (4) 204.
Crystals (*continued*)
$K_4Nb_6O_{17}$, preparation of, (9) 517.
of $SrTiO_3$, diffusion coefficient of Sr and Ti as a function of dislocation density in, (10) 524.
yttrium-iron garnet grown from flux, influence of NiO on growth, (12) 678.
ZnO, of low and intermediate resistivity, (6) 302.

Damping, dislocation, in rutile single crystals, (1) 15.
Decomposition, of alkoxides, metastable transitions of zirconium oxide from, (5) 286.
pressures, of stannic oxide, (3) 129.
thermal, of barium titanyl oxalate, (6) 292.
of boehmite, kinetics of, (8) 419.
of brucite: I, electron and optical microscope studies, (12) 654.
of calcium hydroxide crystals, (10) 575.
of pyrite, (11) 591.
Defects, in PuO_{2-x}, density measurements at high temperatures, (11) 624.
Deformation, characteristics, of fireclays at high temperatures, (2) 90.
of fireclay refractory, analysis of, (6) 312.
high-temperature tensile, of polycrystalline magnesia, (7) 345.
mechanisms, in polycrystalline SiC, (5) 264.
modes, for [110] oriented MgO crystals, (2) 74.
plastic, of zirconia with 15 mole % titanium, (6) 340.
thermomechanical, of Y_2O_3, (3) 165.
Dehydration, products, of calcium sulfate dihydrate, oriented growth of, (6) 342.
Dendrites, and associated Fe content in adjacent glass, approximate metallic content, (1) 4.
Densification, of BeO compacts, (3) 161.
of hot-pressed $PbZrO_3$-$PbTiO_3$ ceramics containing Bi, (3) 113.
of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, promoted by additive oxides, (11) 582.
of UP, as function of sintering temperature, (10) 543.
Density, bulk, of fireclays, as function of pressure and temperature, (2) 91.
bulk, of fireclay compacts, compressive strength as function of, (9) 481.
of CaO-SiO_2 glasses, (11) 583.
and composition of tantalian magnetites, (3) 171.
and electrical properties of crystallized glasses in system MgO-Al_2O_3-SiO_2-TiO_2, (1) 11.
etch-pit, for surfaces of sapphire crystals, (3) 124.
Eu^{3+} ion, in glass, transition wavelength as function of, (5) 263.
as function of sintering time and temperatures for shocked and control Al_2O_3, MgO, and $BaFe_{12}O_{19}$, (9) 506.
glass, dependence on composition, (12) 672.
maximum packing, of powder mixtures, theorems for calculation of weight ratios to produce, (6) 323.
measurements, at high temperatures, in PuO_{2-x}, (11) 624.
of PuP and PuS, (12) 662.
vs. temperature, for Ar-$K_2O \cdot 4SiO_2$ glasses, (12) 640.
Desulfurization, of pyrite, (11) 591.
Devitrification, in soda-lime glasses, absence at bubble surfaces, (7) 396; resistance of tellurite glasses to, (12) 670.
Dielectrics, constant, of $BaTiO_3$, effect of particle size and Ta_2O_5 additions, (6) 299.
devitrified $BaTiO_3$, (4) 210.
loss, in MgO, effect of water vapor, (7) 390.
properties of $BaTiO_3$ ceramics with controlled grain sizes, (6) 298.
of crystallized glass in system MgO-Al_2O_3-SiO_2-TiO_2, (1) 13.
in systems $BaTiO_3$-UO_2 and $BaTiO_3$-UO_2, (5) 276.
Diffraction. See *Electron diffraction; X rays.*
Diffusion, binary, in ceramics, extension of Darken's equation to, (5) 280.
cation, in single-crystal and polycrystalline BeO, (2) 94.
cationic, in $SrTiO_3$, dislocation dependence of, (10) 521.
coefficients, calculated from shrinkage of α-Cr_2O_3, (1) 25.
for creep in MgO, (11) 599.
for lead zirconate titanate + 2 at.% Bi, (3) 116.
grain-boundary, as function of pressure for sintering MgO, (10) 528.
for Th in ThO_2 calculated from creep data using Nabarro-Herring model, (8) 413.
couples, Al_2O_3-NiO, growth of $NiAl_2O_4$ in, (4) 199.
grain-boundary, of Ni^{2+} in MgO, (2) 112.
grain-boundary, origin in MgO, (8) 433.
in impure ionic solids, (7) 367.
lattice, grain boundary, as rate-controlling mechanism in deformation of dense polycrystalline SiC, (5) 267.
model, grain boundary vs. bulk, for sintering of Al_2O_3, (5) 249.
of O_2 in vitreous silica, correction, (4) 232.
oxygen, in CaO-stabilized ZrO_2, (3) 139.
self-, cationic, in CaO-stabilized ZrO_2, (5) 244.
studies, of Na_2O-SiO_2-Fe_2O_3 melts at 1200°C, (10) 547.
volume, as mechanism in sintering of BeO, (3) 163.
Diffusivity, thermal, of PuS and PuP, (12) 661.
Dislocations, in crystals. See *Crystals.*
configuration, of matching cleavage surfaces in $SrTiO_3$ crystals, (2) 111.

Dislocations (*continued*)
etch pits, on {110} planes of magnesium oxide, (6) 343.
etch pits, on single-crystal sapphire, relation to whisker growth sites, (3) 122.
interaction on oblique systems in MgO crystals, (2) 79.
in MgO cleavage foil, (4) 191.
in $SrTiO_3$ single crystals, density of, (10) 522.
Dispersion, frequencies, and number of electrons for oxide components of binary tellurite glasses, (12) 674.
Distributions, chain length, calculation in polyphosphoric acids and polyphosphate glasses, (2) 64.
Drilling, upward, simulative studies of, (8) 441.
Durability, chemical, of tellurite glasses, (12) 000.
Dysprosium, oxide, polycrystalline, temperature and porosity dependence of Young's modulus, (4) 227.

Elasticity, constants, of MgO, determination of pressure derivatives by pulse superposition, (8) 404.
of SiC, (6) 342.
of single-crystal BeO at room temperature, (3) 125.
of vitreous silica, (10) 532.
moduli, of ceramic powder, calculation from compressibility and Debye temperature data, (6) 318.
modulus, in tension, of zirconia with 15 mole % titanium, (6) 335.
properties, high-temperature, of polycrystalline MgO and Al_2O_3, (7) 355.
Young's modulus, at high temperatures, ratio to room temperature in chemically strengthened glass, (11) 616.
of Dy_2O_3 and Er_2O_3, temperature and porosity dependence, (4) 227.
of $5SrTiO_3 \cdot 3La_{2/3}TiO_3$, anomaly below 100°C, (11) 628.
Electric resistivity. See *Resistivity.*
Electrical properties, of alkali metal oxide-SiO_2 glasses, (2) 55.
of crystallized glasses in system MgO-Al_2O_3-SiO_2-TiO_2, (1) 10.
of system $SrFeO_3$-$BiFeO_3$, (12) 644.
of Y_2O_3, (8) 401.
Electrochemistry, processes, in formation of bubbles in glass, (10) 551; theory, for oxygen reboil, (10) 559.
Electron diffraction, patterns, for $CoNb_2O_6$-$CaTa_2O_6$ compounds, (5) 275; patterns of single-crystal and polycrystalline spinel films grown on MgO, (5) 238; of reaction products in system kaolin-lime-water, (7) 364.
Electrodes, electroless Ni-P alloy, for barium titanate ceramics, (8) 457; reference, definition of, (10) 552.
Electrolytes, effect on rheology and electrokinetics of glass-frit and quartz suspensions, (5) 252.
Electron probe, preparation of magnesia-chrome refractories for study by, I, (10) 535; study of grain-boundary reactions in MgO-Cr refractories, II, (11) 609.
Electrostatic charges, in study of glass surfaces, (9) 492.
Emittance, normal spectral, of Ti boronitride, BN, TiB_2, and TiN at 1300°K, (12) 630.
Energy, activation, of CaO-SiO_2 glasses, (11) 583.
for creep of dense MgO, effect of grain size, (11) 597.
for crystallization of stoichiometric SiO_2 glass in H_2O vapor atm, (2) 120.
in firebrick, (6) 315.
for initial sintering of MgO in low P_{H_2O} region, (10) 529.
vs. $Fe_{1-x}O$ concentration in MgO solid solutions, (2) 102.
for O_2 exchange and diffusion in CaO-stabilized ZrO_2 and in oxides, (3) 142.
for viscous flow as function of composition for aluminoborate melts above 1400°C, (1) 21.
of volume diffusion of ions in MgO, (1) 48.
adsorption, of hydroxyl ion over Mg ion, (11) 627.
electronic, levels of imperfections in doped Zr, (4) 216.
grain boundary, method, for measuring crack propagation in brittle materials, (6) 306.
radiant, from blackbody source, in determining thermal shock resistance of semitransparent ceramics, (2) 103.
standard free, of formation and reaction between SiO_2 and graphite, (7) 373.
Equations, for calculating chain length distributions in polyphosphoric acids and polyphosphate glasses, (2) 63; Darken's, extension to binary diffusion in ceramics, (5) 280; solid state reaction, numerical data for, (7) 379.
Equilibrium studies, of alkaline-earth tungstates, (7) 385.
in $CoAl_2O_4$-$MgAl_2O_4$ solid solutions, determination of stability of $MgAl_2O_4$ from, (2) 107.
manganous-manganic, in alkali borate glasses, (10) 565.
oxidation-reduction, in glass melts, ionic formulation, (4) 228.
oxidation-reduction, in $Na_2O \cdot 2SiO_2$ glass melts in contact with metallic Cu and Ag, (10) 562.
in systems KF-AlF_3, $KAlF_4$-$RbAlF_4$, and $KAlF_4$-$RbAlF_4$-KBF_4, (12) 631.
Equipment, for foaming experiments in silicate melts, (10) 569; for study of oxygen reboil, (10) 560.
Erbium, oxide, polycrystalline, temperature and porosity dependence of Young's modulus, (4) 227.
Etching, of magnesium oxide crystals, (6) 344; of single-crystal $SrTiO_3$, (2) 110.
Europium, glasses, preparation and Faraday rotation, (5) 261; see also *Systems.*
Eutectics, temperatures, carbide-carbon, (10) 574.
Evaporation, and condensation, CdS films deposited on glass by, (12) 681; flux, oxide crystal growth by, (10) 576; studies, of stannic oxide, (3) 128.
Expansion, bulk linear thermal, vs. temperature for $PbZrO_3$, (9) 484.
coefficients, molar volume, as function of composition for aluminoborate melts, (1) 21.
thermal, of clay-cristobalite bars, (9) 515.
of nonstoichiometric zirconium carbides, (8) 456.
of PuS and PuP, (12) 665.
of uranium monophosphide, (10) 545.
of zirconia with 15 mole % titanium, (6) 335.

Faraday rotation, room-temperature, of Eu^{2+} glasses, (5) 262.
Ferric, Ferrous, etc. See *Iron.*
Ferrites, magnesium, temperature dependence of properties, (5) 257; nickel, O_2 content at 1300°C, discussion of paper, (5) 288; reply to discussion, (12) 680; nonstoichiometric NiZn, magnetic properties of, (8) 459.
Ferroelectric materials, sodium-strontium niobates, dielectric properties and phase transitions of, (7) 376; ultrafine particle size, I, (6) 291; II, (6) 295; III, (6) 299.
Fibers, high-strength, high-modulus, nonlinear behavior in three-point bending, (3) 169.
Films. See *Coatings.*
Fireclay. See also *Refractories.*
constitution, at high temperatures, I, (2) 83; II, (2) 87; III, (2) 90; see also *Refractories.*
Flow, characteristics for $PbZrO_3$-$PbTiO_3$ + 2 at.% Bi, as function of pressure, (3) 116; rate, of glass through nozzle, effect of beading on, (3) 147; viscous, in dense polycrystalline SiC, (5) 267.
Fluoaluminates, stability relations in, (12) 631.
Fluorides, effect on grain growth of $PbTiO_3$, (4) 230.
Flux, equations, for binary diffusion in ionic systems, (5) 281; growth, and characterization of β-Ga_2O_3 single crystals, (3) 168.
Formulas, for determining minimum grain size and temperature for a fixed porosity, (3) 164.
Fracture, method, for preparation of foils for transmission electron microscopy, (4) 190.
origin, distribution of hackle about, (1) 7.
surfaces, of hot-pressed CrO_2, (1) 53.
theory, of dispersion-strengthened glass matrix, (2) 68.
Friction, internal, of $5SrTiO_3 \cdot 3La_{2/3}TiO_3$ below 100°C, (11) 628; internal, in TiO_2 single crystals, (1) 16.
Furnaces, high-temperature, for determining electrical resistivity of Al_2O_3, (4) 195.

Gallium, β-Ga_2O_3, single crystals, flux growth and characterization, (3) 168.
Garnets, crystals, yttrium-iron, grown from flux, influence of NiO on yield, (12) 678.
Y-Al, effect of deviations in composition on transmission properties, (4) 206.
Y-Ga, Czochralski growth of, (1) 51.
YFe, crystals, vaporization of PbO-PbF_2 melt during solution growth, (2) 104.
Gases, analysis, apparatus for, (8) 448; physical solubility of, in fused silica, (9) 461.
Germanium. See *Systems.*
Glass, alkali borate, manganous-manganic equilibrium, (10) 565.
alkali borate, solubility of water vapor in, (9) 476.
alkali metal oxide-silica, physical and electrical properties, (2) 57.
aluminoborosilicate fibers, failure under combined loadings of tension and torsion, (9) 508.
arsenic borate, gamma-induced absorption and structural studies of, (8) 423.
$BaTiO_3$, devitrification to tetragonal $BaTiO_3$, (4) 210.
borate, time and temperature effects on SiO_2 distribution in, (2) 105.
bubbles, corrosion resulting from, (8) 443.
in fining of glass, (8) 439.
formation by electrochemical processes, (10) 551.
spontaneous formation in silicate melts at high temperature, (10) 568.
calcium silicate, ionic conductivity for, (11) 582.
chemically strengthened, mechanical properties at high temperatures, (11) 613.
crystallized, in system MgO-Al_2O_3-SiO_2-TiO_2, electrical properties of, (1) 10.
europium, divalent, preparation and Faraday rotation, (5) 261.
fibers, relation of strength to melt treatment, (3) 144.
fining kinetics and mechanisms of, (8) 436.
-frit suspension, rheological and electrokinetic properties, (5) 252.
galvanic oxygen reboil in, (10) 560.
GeO_2-P_2O_5-V_2O_5, relation of infrared spectra to structure and electronic conduction, (11) 605.
hackle, effect of stress and strain on producing in plates, (1) 6.
Glass (*continued*)
lead borate, microseparation in, (2) 80.
lead silicate, electrode potential vs. time for, (9) 494.
lithium-cesium phosphate, constitution of, (6) 310.
matrix, dispersion-strengthened, fracture theory, (2) 68.
melts, formulation of oxidation-reduction reactions in, (9) 513.
ionic formulation of redox equilibria in, (4) 228.
physical and chemical solubility of nitrogen in, (9) 462.
-metal interfaces, "adherence oxides" in development of chemical bonding, (1) 1.
mixed-alkali phosphate, constitution of, IV, (6) 310.
optical, flint-type, (12) 670.
outgassing of, caused by thermal neutrons and gamma radiation, (8) 446.
polyphosphate, equations for calculating chain length distributions in, (2) 63.
porous, surface composition of, (12) 651.
SiO_2, stoichiometric, kinetics of crystallization in H_2O atm, (3) 118.
silicate, bubble formation in, (10) 568.
soda-lime, absence of devitrification at bubble surfaces, (7) 396.
soda-lime-silica, solubility of nitrogen in, (9) 463.
Na_2O-GeO_2, acoustic spectra, (3) 134.
Na_2O-SiO_2-FeO, diffusion studies at 1200°C, (10) 547.
$Na_2O \cdot 2SiO_2$, molten, in contact with Cu and Ag, oxidation-reduction equilibria in, (10) 562.
sodium silicate melts, O^{2-} activity and solubility of SO_2 in, (9) 467.
solubilities of Ar, N_2, CO_2, and He in, at pressures to 10 kbars, (12) 638.
sorption of argon by, in gas-discharge lamp, (8) 450.
surfaces, strengthening by SO_3 treatment, (11) 585.
surfaces, study by generation of electrostatic charges, (9) 492.
tellurite, (12) 670.
upward drilling in, simulative studies of, (8) 441.
viscosity, in fireclays and kaolin at hot-pressing temperatures, (2) 93.
Gold, as overlay for CdS films, (12) 681.
Grain boundaries, energies, in brittle materials, crack propagation method for measuring, (6) 306; reactions, in magnesia-chrome refractories: application of electron probe, I, (10) 535; II, (11) 609; sliding, without void formation, flow pattern in magnesia, (7) 350.
Grain growth, of $BaTiO_3$, inhibition studies, (6) 295.
in BeO compacts, (3) 161.
of hot-pressed $PbZrO_3$-$PbTiO_3$ ceramics containing Bi, (3) 113.
of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, (11) 582.
of $PbTiO_3$, effect of additives, (4) 230.
in MgO containing Fe_2O_3 or TiO_2, (1) 47.
of oxides, effects of inclusions on, (11) 621.
of zirconia, effect of titanium additions on, (6) 339.
Grain size, average, nomograph for converting average intercept size to, (7) 399; effect on microcracking in $PbTiO_3$ ceramics, (4) 229.
Graphite, crucible, for determining metal carbide-carbon eutectic temperatures, (10) 574; and silica, reactions between, (7) 369.
Grit, angular and ball-milled, packing efficiency in vibrating compaction, (4) 208.

Hackle. See *Glass.*
Hafnia. See *Hafnium, oxide.*
Hafnium, oxide, grain growth studies, (11) 621; oxide, permeability to O_2, (5) 240.
Hardness, of borides at 1625°C, (4) 231; micro-, of MgO, (9) 501; micro-, of PuS and PuP, (12) 666.
Heat, capacity, of PuS and PuP, (12) 661.
capacity, of zirconia with 15 mole % titanium, (6) 334.
effect on resistance of gold films deposited on CdS films, (12) 681.
treatment, effect on microstructure of MgO, (1) 40.
treatment, of UP in vacuum, effect on lattice constant and stoichiometry, (10) 544.
Heating, radiation, of semitransparent ceramics, effect on thermal shock resistance, (2) 103.
Helium, calculated and observed, from neutron-irradiated glass, (8) 449; solubility in glasses, (12) 638.
Hydration, of $3CaO \cdot Al_2O_3$, (5) 268.
Hydrogen, sublimation of Al_2O_3 in, (1) 26.
Hydrolysis, of titanate esters in barium hydroxide, (6) 291.
Hydroxyl, surface, in MgO, (11) 626.

Ice, upward drilling by bubbles in, refrigerated apparatus for observation of, (8) 443.
Immiscibility, metastable liquid, in alkali metal oxide-silica systems, (2) 55.
Impurities, distribution, in hot-pressed polycrystalline MgO, (9) 498.
Inclusions, effects on grain growth of oxides, (11) 621.
Infrared, radiation, of Ti boronitride, (12) 629; see also *Phase diagrams; Systems.*
Intensity, relative radiant, of Ti boronitride, BN, TiN, and TiB_2 at 1300°K, (12) 630.
Interferometry, ultrasonic, in determining isotropic elastic properties of polycrystalline ceramics, (4) 184.

Ions, bombardment, apparatus for, (8) 455.
Iridium, IrO_2 and Cr_2O_3, phase relations in air, (5) 285; see also *Phase diagrams; Systems.*
Iron. See also *Phase diagrams; Systems.*
activity, hypothetical, vs. penetration distance for oxidized Fe-glass contact zone, (1) 1.
-glass composites heated in Pt or Al_2O_3 crucibles, net weight gain vs. time for, (1) 2.
-niobium oxides, phase relations at 1180°C, (4) 177.
oxide, effect on electrical conductivity of MgO solid solutions, (2) 100.
ferric, in plastic and flint fireclays and kaolin, effect of firing temperature, (2) 89.
ferric, and silica, interdiffusion coefficients in soda-silica-ferric oxide melts, (10) 547.
in MgO, effect on grain growth, (1) 47.
tetra- and trivalent, preparation by equilibration of perovskite phases containing, (12) 644.
Irradiation, dose, effect on UP lattice constant, (10) 545; γ-, of glass, gases in, (8) 448; see also *Radiation.*

Kaolin. See *Systems.*
calcined, electrodes, effect of temperature on polarization, (10) 556.
composition of liquid phase, (2) 88.
hot-pressing characteristics, (2) 90.
Kinetics, electro-, properties, of glass-frit and quartz suspensions, (5) 252.
equations based on concept of an order of reaction, (7) 380.
of crystallization of stoichiometric SiO_2 glass in H_2O atm, (3) 118.
of fining glasses, (8) 436.
of sublimation of Al_2O_3, (1) 27.
thermal decomposition, of boehmite, (8) 419.

Lamps, gas-discharge, sorption of argon by glass in, (8) 450.
Lanthanum, ions, as habit modifiers for corundum crystals, (5) 233; see also *Systems.*
Lead. See also *Systems.*
PbO-PbF_2 melt, vaporization during solution growth of YIG crystals, (2) 104.
titanate, ceramics, effect of grain size on microcracking, (4) 229.
zirconate, high-temperature phase transitions in, (9) 483.
zirconate and titanate, containing Bi, hot-pressed, grain growth and densification, (3) 113.
Lime. See *Systems.*
Lithium, cesium phosphate glasses, constitution of, (6) 310; concentration in ZnO crystals, (6) 302; see also *Systems.*
Luminescence, cathodo-, in determination of solid solution limit of TiO_2 in Al_2O_3, (12) 637.

Magnesia. See *Magnesium, oxide; Phase diagrams; Systems.*
Magnesium. See also *Phase diagrams; Systems.*
carbonate, MgO prepared by thermal decomposition of, (12) 677.
ferrite, temperature dependence of properties, (5) 257.
oxide, containing Fe_2O_3 or TiO_2, grain growth in, (1) 47.
dense, polycrystalline, creep of, (11) 594.
dislocation etch pits on {110} planes, (6) 343.
effect of crystal orientation on mechanical behavior at high temperatures, (2) 72.
effect of water vapor on dielectric loss in, (7) 390.
effect of water vapor on initial sintering of, (10) 526.
formed during decomposition of brucite, (12) 660.
grain-boundary diffusion of Ni^{2+} in, (2) 112.
grain growth studies, (11) 623.
growth of $MgAl_2O_4$ and $MgFe_2O_4$ single-crystal and polycrystalline thin films on, (5) 237.
impurity distribution in, (9) 498.
lattice parameter, dependence on crystallite size, (3) 152.
origin of grain-boundary diffusion in, (8) 433.
polycrystalline, elastic moduli as function of porosity, (6) 320.
polycrystalline, high-temperature elastic properties, (7) 355.
polycrystalline, mechanical behavior at high temperatures, (7) 345.
precursor and sintering study, (12) 676.
production of cleavage foils of, for electron microscopy, (4) 192.
single crystal, pressure derivatives of elastic constants of, (8) 405.
single crystals, thermal-mechanical history and strength, II, (1) 39.
solid solutions, effect of iron oxide on electrical conductivity in, (2) 100.
surface hydroxyl in, (11) 626.
very pure, and containing vanadium, sintering in, comment on paper, (7) 400.
Magnetic properties, of $CaCoSiO_4$ and $CaFeSiO_4$, (5) 284.
of nonstoichiometric NiZn ferrites, (8) 459.
of system $SrFeO_3$-$BiFeO_3$, (12) 644.
of YIG, effect of NiO on, (12) 678.
Magnetites, niobian, cell dimensions and properties, (4) 179; tantalian, nonstoichiometric, (3) 170.
Manganese, Mn^{3+}, deviation from stoichiometry in system Mn_xO-MgO, (10) 572; Mn^{3+}-Mn^{2+} equilibrium in alkali borate glasses, (10) 567; oxides, nonstoichiometry at 1200°C, (7) 383; see also *Systems.*
Mass transport, in impure ionic solids, (7) 366.
Materials, brittle, crack propagation method for measuring grain boundary energies in, (6) 306.
Mechanical properties, of chemically strengthened glasses at high temperatures, (11) 613; of MgO, as function of thermal history, II, etch pit and electron transmission studies, (1) 39.
Melting, point, of hypostoichiometric UO_2, (7) 395; point, of PuS and PuP, (12) 665.
Melts, glass, effect of treatment on fiber strength, (3) 146.
PbF_2-Bi_2O_3, habit modification of corundum crystals grown from, (5) 233.
silicate, at high temperatures, spontaneous bubble formation in, (10) 568.
Na_2O-SiO_2-Fe_2O_3, diffusion studies at 1200°C, (10) 547.
Metal, oxides, effect on high-temperature electrical conductivity of Al_2O_3, (4) 194.
Metallizing. See *Coatings.*
Micrographs, of Al_2O_3 heated in H_2, (1) 29.
of development of two phases in $50SiO_2$:$50Na_2B_8O_{13}$ at 603°C, (1) 33.
of dislocation etch pits in MgO, effect of heat treatment on appearance, (1) 42.
electron, of disrupted $PbTiO_3$ compact, (4) 230.
of fracture surfaces of hot-pressed CrO_2, (1) 53.
of glass-metal interfaces, (1) 3.
of polished cross section of carburized Ta, (2) 109.
of stannic oxide Langmuir specimen after thermal etching, (3) 130.
transmission electron, of MgO, (11) 595.
of wear surface of single-crystal sapphire, (4) 222.
Microscopy, electron, in study of microstructure of lead borate glass, (2) 82.
in study of plastic fireclay at high temperatures, (2) 85.
of system kaolin-lime-water, (7) 365.
of thermal decomposition of brucite, I, (12) 656.
transmission, fracture method for preparation of foils for, (4) 190.
transmission, preparation by ion bombardment of near-stoichiometric TiO_2 for, (8) 454.
replica, SiO, for observing surface microtopography, (1) 54.
Microtopography, surface, SiO technique for observing, (1) 53.
Mineralogy, composition, of refractory clays heated at 1150° to 1500°C, (2) 87.
Models, imperfection, for donor-doped stabilized ZrO_2, (4) 217; for origin of internal stress in fine-grained $BaTiO_3$, (1) 34; showing two-dimensional stress system in ceramic body, (1) 38.
Modulus of elasticity. See *Elasticity.*
Modulus of rupture. See *Rupture.*
Molybdenum, disilicide, high-temperature oxidation, (4) 173; dispersion in Al_2O_3 to inhibit grain growth and recrystallization during sintering, (9) 488.
Mullite, content, in fireclays, effect of quenching, (2) 86.

Neon, variation of intensity with time, in discharge from gas-discharge lamp, (8) 451.
Nickel. See also *Phase diagrams; Systems.*
ferrites, O_2 content at 1300°C, discussion of paper, (5) 288; reply to discussion, (12) 680.
flash, function of, (1) 5.
Ni^{2+}, grain-boundary diffusion in MgO, (2) 112.
Ni^{2+}, preferential diffusion along grain boundaries in MgO bicrystals, (8) 433.
$NiAl_2O_4$, formation by solid state reaction, (4) 199.
oxide, influence on yield of YIG crystals grown from flux, (12) 678.
-phosphorus, electroless, alloy electrode for semiconductive $BaTiO_3$, (8) 457.
-zinc ferrites, magnetic properties of nonstoichiometric, (8) 459.
Niobium, -iron oxides, phase relations at 1180°C, (4) 177; Nb^{5+}, introduction into magnetite spinel lattice, (3) 170; see also *Phase diagrams; Systems.*
Nitrides, transition metal, high-temperature thermal conductivity of, (3) 156.
Nitrogen, gas, method, for removing H_2O from B_2O_3, (12) 679; physical and chemical solubility, in glass melts, (9) 462; solubility in glasses, (12) 638.
Nomographs, for converting average intercept size to average grain size, (7) 398.
Nuclear materials, fuel rods, with U and Pu carbides, forming by vibratory compaction, (4) 210.
Nucleation, gaseous, during short-circuiting of two electrodes, (10) 557; and growth, of MgO in brucite, (12) 654.
Neutrons, thermal, in outgassing of glass, (8) 446.

Optical properties, of MgO-GeO_2-MgF_2 compounds, (11) 619.
Orientation, vs. Young's modulus for BeO single crystal, (3) 127.
Oxidation, of $MoSi_2$, (4) 173; -reduction equilibria, ionic formulation in glass melts, (4) 228; -reduction reactions, in glass melts, (9) 513.
Oxides, adherence, in development of chemical bonding at glass-metal interfaces, (1) 1.
crystals, growth by flux evaporation, (10) 576.
effect on grain growth of $PbTiO_3$, (4) 230.
grain growth of, effects of inclusions, (11) 621.
mixed, single-crystal growth, deviations in molar composition, (4) 204.
redox, oxidation potential in glass, (10) 565.
Oxygen. See also *Phase diagrams; Systems.*
exchange and diffusion in CaO-stabilized ZrO_2, (3) 139.
Oxygen (*continued*)
ion activity in sodium silicate melts, (9) 467.
permeability of ZrO_2, HfO_2, and ThO_2, (5) 240.
reboil, electrochemical theory for, (10) 559.
solubility in various glass compositions, (12) 638.

Packing, density, maximum, in powder mixtures, calculation of weight ratios for, (6) 323; efficiency, of angular and ball-milled grits and spheres, (4) 208.
Particle size, and aging, effect on flocculated quartz, (5) 256.
in calculation of weight ratios for maximum packing density in powder mixtures, (6) 323.
of shocked and unshocked SiC after ball milling, (9) 505.
ultrafine, ferroelectrics of, I, (6) 291; II, (6) 295; III, (6) 299.
Periclase, grains, in magnesia-chrome brick, migration of ions into, (10) 537.
Permeability, initial, vs. reciprocal of coercive force for NiZn ferrites, (8) 460; rate of permeation in glass exposed to neutrons, (8) 449; of zirconia, hafnia, and thoria to O_2, (5) 240.
Perovskite, phases, containing Fe in tetra- and trivalent states, preparation of, (12) 644.
Phase diagrams, condensed, for portion of join Ca_2SiO_4-$CaMgSiO_4$, (8) 431.
MgO-Fe_2O_3, addendum to subsolidus region, (5) 259.
solid-state, for solid solution region in the system $Na_{1-x}Sr_{x/2}NbO_3$, (7) 378.
for system, $BaTiO_3$–$CaTiO_3$, (12) 648.
CaO–Yb_2O_3, (12) 669.
Cr_2O_3-IrO_2 in air, (5) 286.
$CoNb_2O_6$-$CoTa_2O_6$, pseudobinary, (5) 274.
Fe-Ni-O, (12) 680.
KF-AlF_3, (12) 633.
SiO_2-Na_2O·$4B_2O_3$, (1) 31.
Ti-O_2, (4) 181.
Phenacite, -spinel, transition in $LiAlGeO_4$, (9) 516.
Phosphides, uranium, crystallographic properties, (10) 541.
Phosphorus, electroless nickel-, alloy electrode, for semiconductive barium titanate ceramics, (8) 457.
Piezoelectricity, properties, of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics modified with oxides, (11) 577; of Na Sr niobates, effect of temperature on, (7) 379.
Platinum, crucible, effect on reboil of glass, (10) 559; electrode, in determination of electroactivity range of soda-lime-silicate glass in air, (10) 556.
Plutonium, dioxide, density measurements at high temperatures, (11) 624; monophosphide and monosulfide, sintering characteristics and properties, (12) 661.
Polishing, chemical, of single-crystal $SrTiO_3$, (2) 110.
Polymerization, of SiO_2, effect of crystallization on, (2) 106.
Pores, size distribution, in basic brick, effect of temperature, (7) 363; -size distribution, for hydrated $3CaO·Al_2O_3$ compacts, (5) 269.
Porosity, of boehmite compacts, as function of temperature, (9) 479.
dependence, of elastic moduli for SiC, (6) 342.
dependence, of Young's modulus of polycrystalline Dy_2O_3 and Er_2O_3, (4) 227.
permeable, of refractories, determinations by texture analysis, (7) 360.
Porous materials, MgO, effect of pressure on dissipation factor of, (7) 391.
Potassium. See also *Phase diagrams; Systems.*
chloride, cleavage technique for measuring surface free energy and grain boundary energy in, (6) 306.
metaniobate, single crystals, preparation of, (9) 517.
$KAlGeO_4$, X-ray powder data, (3) 149.
tantalum niobate crystals, growth of, (8) 415.
Powders, ceramic, effect of explosive shock waves on, (9) 502.
Precipitation, of dispersed $CaTiO_3$-rich phase, effect on ferroelectric domains in $BaTiO_3$, (12) 648; of $MgMn_2O_4$ phase in MgO-MnO alloys, (1) 41.
Pressing, cold-, characteristics of shocked and unshocked ceramic powders, (9) 506.
hot, characteristics, of kaolin, fireclay, and plastic fireclay, (2) 90.
of CrO_2, (1) 52.
of polycrystalline magnesium oxide, effect on high-temperature tensile deformation, (7) 345.
reactive hot-, of clays and alumina, (9) 477.
Pressure, applied, of fireclay, compressive strength as function of, (9) 479.
derivatives, of elastic constants of single-crystal MgO at 23° to −195.8°C, (8) 404.
derivatives, of sound velocities of polycrystalline Al_2O_3, (4) 184.
effect on refractive index of vitreous silica, (10) 531.
oxygen, vs. composition stability field of niobian magnetites at 1180°C, (4) 178.
effect on concentration of imperfections in CaO-stabilized ZrO_2, (4) 217.
partial, effect on foaming temperature, (10) 570.
partial, H_2O, effect on ac conductivity of MgO, (7) 392.
shrinkage as function of, in magnesium oxalate, (10) 527.
-temperature diagram for system $LiAlGeO_4$, (9) 516.
to 10 kbars, solubilities of Ar, N_2, CO_2, and He in glasses at, (12) 638.

Pressure (*continued*)
two-dimensional, effect on permittivity of fine- and coarse-grained $BaTiO_3$, (1) 36.
water vapor, effect on crystallization rate of SiO_2 glass, (3) 120.
water vapor, effect on decomposition of boehmite, (8) 420.
Pycnometer, gas, high-temperature, schematic diagram, (11) 624.
Pyrite, desulfurization of, (11) 590.
Pyrolysis, isothermal, of barium titanyl oxalate, (6) 291.

Quartz, crystals, infrared transmission of, discussion of paper, (12) 682; suspension, rheological and electrokinetic properties, (5) 252.
Quenching, effect on mullite and cristobalite content of fireclays, (2) 85.

Radiation, gamma, outgassing of glass caused by, (8) 446.
Radiographs, auto-, for ^{95}Zr diffusion into $Zr_{0.85}Ca_{0.15}O_{1.85}$, (5) 245.
Reactivity, solid state, of alkali aluminogermanates, (3) 148.
Reboil, oxygen, electrochemical theory for, (10) 559.
Reflectance. See *Reflection.*
Reflection, diffuse, spectra, for Al_2O_3 doped with TiO_2, (12) 636.
Refractive index, of glasses in system SiO_2-Na_2O-$4B_2O_3$, (1) 31; of glasses in systems TeO_2-WO_3 and TeO_2-BaO, (12) 674; of vitreous silica, nonlinear variation with pressure, (10) 531.
Refractories, basic, texture analysis, (7) 360.
chrome-magnesia, grain-boundary reactions in, I, (10) 535; II, (11) 609.
fireclay, analysis of deformation, (6) 312.
fireclay, high and superduty, mineralogical composition, (2) 88.
magnesia-chrome, grain-boundary reactions in, I, (10) 535; II, (11) 609.
upward drilling in, caused by bubbles, (8) 443.
Resistance, electric, circuit diagram for measurement of, (11) 606.
Resistivity, electrical, of Al_2O_3, effect of metal oxide additions, (4) 197.
of CaO-SiO_2 compounds, (11) 583.
of electroded barium titanate ceramics, (8) 457.
low and intermediate, in hydrothermally grown ZnO crystals, (6) 302.
measurements, in $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, (11) 577.
of PuS and PuP, (12) 666.
of rutile, (1) 16.
in sintered VO_2, temperature dependence, (1) 47.
vs. temperature, for CdS films heated in Cd vapor, (12) 682.
vs. temperature, for Sr ferrates with Bi additions, (12) 645.
of TiN, ZrC, and TiC, (3) 157.
of VO_2 powder, temperature dependence of, (9) 519.
Rheology, properties, of glass-frit and quartz suspensions, (5) 252.
Rubidium, $RbAlGeO_4$, X-ray powder data, (3) 149; see also *Systems.*
Ruby, crystals, effect of La_2O_3 on growth, (5) 234.
Rupture, modulus, of alumina and lime glasses after SO_3 treatment, (11) 588.
in bending, of zirconia with 15 mole % titanium, (6) 335.
of chemically strengthened glass, (11) 615.
strengths, transverse, of Al_2O_3 as function of Mo content, (9) 488.
Rutile, near-stoichiometric, preparation by ion bombardment for transmission electron microscopy, (8) 454; single crystals, dislocation damping in, (1) 15; tri-, structure, relation to rutile structure, (5) 273; see also *Titanium, dioxide.*

Sapphire, crystals, effect of La_2O_3 on growth, (5) 234; single-crystal, comparison of whisker growth sites and dislocation etch pits on, (3) 122; wear on steel, chemical and mechanical mechanisms in, (4) 221.
Separation, micro-, in lead borate glasses, (2) 80.
Shale, -pyrite mixtures, reactions during heating, (11) 590.
Shear, moduli, of polycrystalline MgO, Al_2O_3, BeO, and TiO_2 computed from compressibility and Debye temperature data, (6) 318.
Shock resistance, thermal, of semitransparent ceramics under radiation heating, theory of, (2) 103; of zirconia, mechanism by which metal additions improve, (6) 339; of ZrO_2 with 15 mole % Ti, (6) 335.
Shock waves, explosive, effect on ceramic powders, (9) 502; explosive, formation of zinc orthosilicate by, (9) 519.
Shrinkage, of α-Cr_2O_3 compacts at several temperatures, isothermal time dependence of, (1) 24.
of Al_2O_3 and Al_2O_3-Mo at 2800°F in vacuum, (9) 489.
diametral, of BeO compacts, relation to time, (3) 162.
as function of P_{H_2O} at 875°C in MgO, (10) 527.
initial, of Al_2O_3 powder compacts containing TiO_2, (12) 635.
Silica. See also *Phase diagrams; Systems.*
distribution in borate glasses, (2) 105.
and ferric oxide, interdiffusion coefficients in soda-silica-ferric oxide melts, (10) 550.
fused, physical solubility of gases in, (9) 461.
Silica (*continued*)
glass, stoichiometric, kinetics of crystallization in H_2O atm, (3) 118.
and graphite, reactions between, (7) 369.
transformations, hydrothermal, (7) 397; comment on note, (12) 677; reply to comment, (12) 678.
vitreous, refractive index, nonlinear variation with pressure to 7 kbars, (10) 531.
Silicates, pockets, in MgO-Cr refractories, concentration of Mg-rich phases in, (11) 612.
Silicon, carbide, effect of explosive shock waves on, (9) 504.
elastic constants of, (6) 342.
polycrystalline, deformation behavior, (5) 264.
dioxide, infrared absorption spectrum of, discussion of paper, (12) 682.
monoxide, technique, for observing surface microtopography, (1) 53.
on surface of porous glass, (12) 651.
Silver, effect on oxidation-reduction equilibria in molten Na_2O·$2SiO_2$ glass, (10) 562; permeability to O_2, (5) 241.
Sintering, of Al_2O_3, inhibition of grain growth and recrystallization during, (9) 487.
behavior, of UP, (10) 542.
effect on PuS and PuP, (12) 662.
in impure ionic solids, (7) 366.
initial, of α-Cr_2O_3, (1) 23.
initial, of MgO, effect of water vapor on, (10) 526.
kinetics, of BeO, (3) 159.
of magnesia, (12) 676.
in MgO and MgO with V, and in CaO and CaO with Sr, comment on papers, (7) 400.
parameters, effect on grain size of $BaTiO_3$, (6) 296.
partial, of Al_2O_3 compacts, effect on strength, (5) 249.
of VO_2, (1) 46.
Slags, blast-furnace, phase T in, (8) 432.
Soda. See also *Sodium, carbonate.*
Sodium. See also *Phase diagrams; Systems.*
fluoride, as dopant, in CaF_2, (8) 458.
germanate, glasses, acoustic spectra, (3) 134.
oxide, -depleted layer, relation of depth in glass to Al_2O_3 content, (11) 588.
$NaAlGeO_4$, X-ray powder data, (3) 150.
-strontium niobates, dielectric properties and phase transitions, (7) 376.
Solids, ionic, impure, mass transport and sintering in, (7) 366.
Solid solution. See *Solutions, solid.*
Solid state, reaction, in formation of $NiAl_2O_4$, (4) 199.
reaction equations, numerical data for, (7) 379.
reactivity, and glass crystallization of alkali aluminogermanates, (3) 148.
sintering, review of theory of, (3) 159.
Solidus, sub-, equilibria, in system MgO-GeO_2-MgF_2, (11) 618.
Solubility, of Ar, N_2, CO_2, and He in glasses at pressures to 10 kbars, (12) 638.
of β-spodumene as function of temperature, (5) 290.
crystalline, of Yb_2O_3 in CaO, (12) 667.
of gases in glass, electrochemical determination of mechanisms of, (10) 552.
physical and chemical, of nitrogen in glass melts, (9) 462.
physical, of gases in fused silica, (9) 461.
solid, limit of TiO_2 in Al_2O_3, (12) 634.
of SO_3 in sodium silicate melts, (9) 467.
of water vapor in alkali borate melts, (9) 473.
Solutions, solid, $BaTiO_3$-$CaTiO_3$, effect of hot-pressing, (12) 648.
$CoAl_2O_4$-$MgAl_2O_4$, equilibrium measurements in, to determine stability of $MgAl_2O_4$, (2) 107.
Co_2SiO_4-Fe_2SiO_4, activity-composition relations, (6) 328.
$Fe_{1-x}O$-MgO, electrical conductivity in, (2) 100.
of MgO-Mn_xO in air at high temperatures, (10) 572.
of $KAlF_4$ and $RbAlF_4$ compounds, (12) 631.
series $FeCr_2O_4$-$MgCr_2O_4$, chromous ion in, (1) 50.
of TiO_2 in Al_2O_3, (12) 634.
Sound, velocity, isotropic elastic constants in terms of, (4) 184; velocity, relation to bulk modulus as function of Poisson's ratio and of Young's modulus, (6) 319.
Spectra, absorption, of Cr^{3+} ions in spinel in near-infrared region, (9) 518.
acoustic, of B_2O_3 glass, effect of OH content, (3) 171.
acoustic, of Na_2O-GeO_2 glasses, (3) 134.
diffuse reflectance, of spinels produced at various p_{O_2}, (1) 51.
infrared, of GeO_2-P_4O_{10}-V_2O_5 glasses, relation to structure and electronic conduction, (11) 605.
of porous glass, (12) 652.
of sodium borate glasses, (9) 474.
Spectrophotometry, of γ-induced absorption of arsenic borate glasses, (8) 423.
Spheres, packing efficiency in vibratory compaction, (4) 208.
Spinels, Co-Al, and Mg-Al, determination of free-energy change in formation of, (2) 107.
FeO·Al_2O_3, formation on wear surface of sapphire, (4) 223.
Jahn-Teller distortion induced by tetrahedral-site Cr^{3+} ions in, (9) 518.
$MgAl_2O_4$ and $MgFe_2O_4$, growth as single-crystal and polycrystalline films on MgO, (5) 237.
$NiAl_2O_4$, formation by solid state reaction, (4) 199.
solid solution series $FeCr_2O_4$-$MgCr_2O_4$, chromous ion in, (1) 50.
Spodumene, β-, crystal growth of, (5) 290.
Spraying, flame, of $BaTiO_3$ to form glass, (4) 210.
Stannic oxide. See *Tin, oxide.*
Steel, wear of sapphire on, mechanisms of, (4) 221.
Stoichiometry, of MgO-Mn_xO solid solutions in air at high temperatures, (10) 572; of UP, relation to structure, (10) 543.
Strain, -creep rate for dense MgO, (11) 596.
effect on producing hackle in a glass plate, (1) 6.
-optical constants of vitreous silica, (10) 533.
-tensile stress curves, for (110) and (001) specimens of MgO crystals, (2) 78.
Strength, compressive, of fireclays, as function of temperature, (9) 478.
crushing, for α-Al_2O_3, (1) 49.
glass fiber, relation to melt treatment, (3) 144.
of glass surfaces, effect of Al_2O_3 after SO_3 treatment, (11) 588.
of MgO single crystals, II, (1) 39.
of partly sintered Al_2O_3 compacts, (5) 249.
of sodium borosilicate glass matrices, effect of dispersed Al_2O_3 spheres, (2) 69.
tensile fracture, of hot-pressed polycrystalline magnesia at high temperatures, (7) 351.
Strengthening, chemical, of polycrystalline ceramics, (6) 330.
Stress, dimensionless shear, dependence on flaw density exponent according to Weibull theory of failure, (9) 512.
distribution in firebrick with heating, (6) 316.
effect on creep of dense MgO, (11) 598.
effect on producing hackle in a glass plate, (1) 6.
effect of temperature-compensated creep rate of fine-grained Al_2O_3, (3) 167.
induced, in surface layer of polycrystalline ceramics, relation to surface layer composition, (6) 331.
internal, in ceramics containing cristobalite, (9) 515.
internal, in fine-grained $BaTiO_3$, model showing origin, (1) 34.
orientation factors for resolving onto principal slip systems, (1) 15.
-strain curves, for recrystallized polycrystalline magnesia as function of temperature, (7) 347.
vs. strain rate for polycrystalline SiC, (5) 266.
tensile, -strain curves, for (110) and (001) specimens of MgO crystals, (2) 78.
tensile, and torsion, distribution in E glass fibers, (9) 510.
Strontium. See also *Phase diagrams; Systems.*
ferrate, electrical and magnetic properties, effect of Bi on, (12) 644.
-sodium niobates, dielectric properties and phase transitions, (7) 376.
titanate, dislocation dependence of cationic diffusion in, (10) 521.
titanate, single-crystal, etching and polishing, (2) 110.
Structure, band, in MgO cleavage foil, (4) 193.
of $BaTiO_3$ glass spheres, (4) 211.
of BeO crystal, (2) 97.
of B_2O_3 and binary aluminoborate melts at 1600°C, (1) 19.
cellular, in $3Y_2O_3$·$5Al_2O_3$ crystal, (4) 205.
defect, of Y_2O_3, (8) 401.
of GeO_2-P_4O_{10}-V_2O_5 glasses, relation of infrared spectra to, (11) 605.
micro-, of Al_2O_3, effect of firing in Cr_2O_3, (6) 332.
of hot-pressed polycrystalline magnesium oxide, (7) 346.
of lead borate glasses, electron microscopy and X-ray studies of, (2) 81.
of polycrystalline SiC electrically etched, (5) 265.
of press-forged Y_2O_3, (3) 166.
of sintered Al_2O_3, effect of Mo particles, (9) 488.
in system $BaTiO_3$-$CaTiO_3$, (12) 648.
perovskite, in barium orthoferrate, (11) 600.
studies, of arsenic borate glasses, (8) 423.
sub-, dislocation, during creep in MgO, (11) 597.
of trirutile, relation to rutile, (5) 273.
of UP, relation to stoichiometry, (10) 543.
Sulfates, addition to silicates, effect on foaming temperature, (10) 571.
Sulfur. See also *Systems.*
trioxide, solubility in sodium silicate melts, (9) 467; trioxide, in strengthening glass surfaces, (11) 585.
Synthesis, of MgO-GeO_2-MgF_2 compounds by solid state reactions, (11) 618.
Systems, alkali metal oxide-silica, metastable liquid immiscibility in, (2) 55.
aluminum-silicon oxide, crystal growth of β-spodumene, (5) 290.
$BaTiO_3$-$CaTiO_3$, dielectric aging and microstructure in, (12) 648.
$BaTiO_3$-UO_2, and $BaTiO_3$-$BaUO_3$, crystal chemistry and dielectric properties in, (5) 276.
BeO-WO_3, MgO-WO_3, CaO-WO_3, SrO-WO_3, BaO-WO_3, phase relations in, (7) 386.
CaO-MgO-SiO_2, Ca_2SiO_4-$CaMgSiO_4$ join, (8) 430.
CaO-SiO_2, ionic conductivity in, (11) 582.
CaO-Yb_2O_3, phase equilibria in, (12) 667.
$CoNb_2O_6$-$CoTa_2O_6$, phase relations in, (5) 273.
Cr_2O_3-IrO_2, in air, (5) 285.
EuO-Al_2O_3-B_2O_3, glass-forming region, (5) 261.
Fe-Nb-O, isothermal polybaric section, (4) 177.
Fe-Ni-O, phase equilibria at 1300°C, (5) 288.
Fe-Ni-O, phase equilibria in, (12) 680.
kaolin-lime-water, microtexture and composition of reaction products in, (7) 364.
$0.25Pb(Mg_{1/3}Nb_{2/3})O_3$-$yPbTiO_3$-$zPbZrO_3$, dielectric coefficient for, (11) 579.
$LiAlGeO_4$, pressure-temperature diagram for, (9) 516.
LiO_2-Na_2O-SiO_2, relation between liquidus surface and metastable immiscibility volume, (2) 59.
MgO-Al_2O_3-SiO_2-TiO_2, electrical properties of crystallized glasses in, (1) 10.

Systems (*continued*)
MgO-GeO_2-MgF_2, subsolidus equilibria in, (11) 618.
Mg-W-O, Ca-W-O, Sr-W-O, and Ba-W-O phase relations at 1700°C, (7) 389.
Mn_2O-MgO, interdiffusion in, (10) 572.
Mn-Ta-O, isothermal polybaric projection, (7) 383.
M-W-O, equilibrium and stability in, (7) 385.
$KAlF_4$- containing, equilibria in, (12) 631.
KF-AlF_3, $KAlF_4$-$RbAlF_4$, and $KAlF_4$-$RbAlF_4$-KBF_4, stability relations in, (12) 631.
SiO_2-$Na_2O \cdot 4B_2O_3$ phase relations, (1) 30.
Na_2O-B_2O_3, solubility of Ar in glasses in, (12) 640.
$Na_2O \cdot nSiO_2$-Na_2SO_4, hypothetical activity plot for Na_2SO_4 in, (9) 468.
Na_2O-SiO_2-SO_3, solution of SO_3 and Na_2SO_4 in, (9) 468.
$Na_{1-x}Sr_{x/2}NbO_3$, effect of temperature on dielectric constant of compositions from, (7) 377.
$SrFeO_3$-$BiFeO_3$, electrical and magnetic properties of, (12) 644.
$SrTiO_3 \cdot La_{2/3}TiO_3$, anomaly in Young's modulus and internal friction of, (11) 628.
Ta-C, zeta phase in, (2) 109.
TeO_2-WO_3-Ta_2O_5, TeO_2-WO_3-BaO, TeO_2-WO_3-Bi_2O_3, and TeO_2-WO_3-Tl_2O, boundaries of regions of glass-forming compositions in, (12) 670.
Ti-O_2, reinvestigation of phase diagram for, (4) 180.
Y_2O_3-ZrO_2, search for binary compounds, (11) 625.

Tantalum. See also *Phase diagrams; Systems.*
carbide, carbide-carbon eutectic in, (10) 574.
carburized, zeta phase in, (2) 109.
fraction, in $KTaO_3$ crystal, as function of Ta in melt, (8) 417.
oxide, effect on grain growth of $BaTiO_3$ containing 0.5 wt% SiO_2, (6) 297.
effect of Mn on phase relations, (7) 384.
molar refractions for different wavelengths, (12) 674.
Ta^{5+}, introduction into magnetite spinel lattice, (3) 170.
Tellurium, oxides, molar refractions for different wavelengths, (12) 674; see also *Systems.*
Temperature, dependence of adiabatic bulk modulus, for MgO and Al_2O_3, (7) 358.
of loss peaks in CaF_2 doped with NaF, (8) 458.
of Sr dislocation pipe diffusion in single-crystal $SrTiO_3$, (10) 525.
of Young's modulus of polycrystalline Dy_2O_3 and Er_2O_3, (4) 227.
effect on dissipation factor of MgO, (7) 394.
high-, phase transitions in $PbZrO_3$, (9) 483.
vs. magnetization, for $SrFeO_3$ with low and intermediate Bi concentration, (12) 646.
and time, in hydration of $3CaO \cdot Al_2O_3$, (5) 270.
vs. viscosity, for B_2O_3, (12) 679.
Tension, creep in, prediction from bending tests, (4) 218; failure of aluminoborosilicate glass fibers under, (9) 508.
Testing, apparatus, tensile, (3) 145.
Texture, analysis, of basic refractory brick, (7) 360.
Thallium. See *Systems.*
Thermal analysis, differential, of alkali aluminogermanates, (3) 149.
of alkaline-earth tungstates, (7) 385.
of barium orthoferrate, (11) 602.
of $MgFe_2O_4$, (5) 259.
phase relations in fluoaluminates established by, (12) 631.
of pyrite reactions, (11) 591.
Thermal conductivity. See *Conductivity, thermal.*
Thermal decomposition. See *Decomposition.*
Thermal expansion. See *Expansion.*
Thermal neutrons. See *Neutrons.*
Thermal shock resistance. See *Shock resistance, thermal.*
Thermodynamics, of reaction between silica and graphite, (7) 372; treatment, use of modified Devonshire, (1) 36.
Thermogravimetry, of barium orthoferrate, (11) 602.
Thoria. See *Thorium, oxide.*
Thorium, dioxide, polycrystalline, creep of, (8) 410; dioxide, crystal, and inclusion, after exposure to temperature gradient, (8) 460; oxide, permeability to O_2, (5) 240.
Tin, oxide, electrode, electrochemical behavior in soda-lime-silicate glass, (10) 556; oxide, stannic, Knudsen and Langmuir evaporation studies, (3) 128.
Titanates, powders, of ultrafine particle size, synthesis of, (6) 291.
Titania. See *Titanium, dioxide.*
Titanium, dioxide. See also *Rutile; Systems.*
boronitride, infrared radiation, (12) 629.
diffusion coefficient of, as function of dislocation density in single-crystal $SrTiO_3$, (10) 524.
dioxide, in MgO, effect on grain growth, (1) 47.
in plastic and flint fireclays and kaolin, effect of firing temperature, (2) 89.
solid solution limit in Al_2O_3, (12) 634.
effect on grain growth of ZrO_2, (6) 339.
nitride and carbide, high-temperature thermal conductivity, (3) 156.
oxide, ceramics, strengthened by TiO_2-SnO_2 surface layers, (6) 330.
Torsion, failure of aluminoborosilicate glass fibers under, (9) 508.
Transformations, hydrothermal, silica, (7) 397; comment on note, (12) 677; reply to comment, (12) 678; rutile-trirutile, continuous, hypothetical phase diagrams of, (5) 275.
Tridymite, hydrothermal conversion at 400° ± 5°C, (7) 398; comment on note, (12) 677; reply to comment, (12) 678.
Transmission, electron, of Mg oxide single crystals, (1) 39; electron micrographs, of MgO crystals, (12) 677; spectrum, of α-quartz and fused silica, discussion of paper, (12) 682.
Tungstates, alkaline-earth, equilibrium and stability in the M-W-O systems, (7) 385.
Tungsten, oxides, molar refractions for different wavelengths, (12) 674; see also *Systems.*

Uranium, additions to polycrystalline $BaTiO_3$, effect on structure, (5) 276; dioxide, hypostoichiometric, melting points of, (7) 395; monophosphide, properties of, (10) 541; see also *Systems.*

Vanadium, dioxide, sintering of, (1) 46.
dioxide, powder and crushed single crystals, temperature dependence of electrical resistivity of, (9) 519.
oxides, crystal growth of, (2) 106.
spinels, crystalline, infrared spectra of, (11) 607.
Vaporization, of PbO-PbF_2 melt during solution growth of YIG crystals, (2) 104.
Velocity, application to binary ceramic systems, (5) 283; longitudinal and shear, as function of pressure, (4) 187; wave, in single-crystal MgO at 23°C, (8) 405.
Viscosity, of glass, see *Glass;* of molten B_2O_3, (12) 679; vs. reciprocal temperature for pure molten B_2O_3, (1) 21.
Volume, change, in polycrystalline Al_2O_3, relation to shock wave data, (4) 189; ion, and partial gram atom, for alkali metal cations in SiO_2 glasses, (2) 61.
Water, vapor, effect on dielectric loss in MgO, (7) 390; vapor, solubility in alkali borate melts, (9) 473; see also *Systems.*
Wear, of sapphire on steel, mechanisms of, (4) 221.
Weight, loss, during YIG crystal growth, (2) 105; ratios, for maximum packing density of powder mixtures, theorems for calculation, (6) 323.
Whiskers, growth sites, relation to dislocation etch pits on single-crystal sapphire, (3) 122; and plates grown on Al_2O_3 rods heated in H_2, (1) 29.
Wustite, electrical conductivity, effect of dilution with MgO, (2) 102.

X rays, data, for MgO-GeO_2-MgF compounds, (11) 620.
data, from striated zone of carburized Ta specimen, (2) 110.
diffraction, and fluorescence in determining mineralogical composition of refractory clays heated at 115° to 1500°C, (2) 88.
diffraction, of precipitated films of $BaTiO_3$, (6) 300.
flash, of mechanism of explosive shock treatment of ceramic powders, (9) 503.
linear thermal expansion, calculated, for $PbZrO_3$, (9) 485.
powder diffraction data, for alkali aluminogermanates, (3) 148.
for high-temperature form of $MgWO_4$, (7) 387.
for submicron ZrO_2, (5) 287.
powder diffraction patterns, for crystalline and flame-sprayed $BaTiO_3$, (4) 211.
for MgO calcined in air at 700°C, (3) 154.
of Mn-Ta oxides, (7) 384.
of $MoSi_2$ oxidized in air, (4) 174.
of superduty firebrick at high temperatures, (2) 84.
for system CaO-Yb_2O_3, (12) 668.
scattering techniques, in study of microstructure of lead borate glass, (2) 82.
study, of development of grain-boundary reactions in magnesia-chrome brick, (10) 536.
transmission patterns, of $CaSO_4 \cdot 2H_2O$ and its dehydration products, (6) 343.

Young's modulus. See *Elasticity.*
Ytterbium. See *Phase diagrams; Systems.*
Yttrium, oxide, as pure electronic conductor from 1200° to 1600°C, (8) 404; oxide, thermomechanically deformed, (3) 165; zirconate, nonexistence of, (11) 625; see also *Systems.*

Zinc, orthosilicate, formation by explosive shock, (9) 519; oxide, crystals, of low and intermediate resistivity, hydrothermally grown, (6) 302.
Zirconia. See *Zirconium, dioxide.*
Zirconium. See also *Systems.*
carbide, high-temperature thermal conductivity, (3) 156.
carbides, nonstoichiometric, thermal expansion of, (8) 456.
dioxide, CaO-stabilized, electronic conductivity of, (4) 215.
CaO-stabilized, O_2 exchange and diffusion in, (3) 139.
grain growth studies, (11) 621.
oxide, CaO-stabilized, cationic self-diffusion in, (5) 244.
from decomposition of alkoxides, metastable transitions of, (5) 286.
electrode, stabilized, electrochemical behavior in soda-lime-silicate glass, (10) 555.
permeability to O_2, (5) 240.
thermal shock resistance, mechanism of improvement by metal additions, (6) 339.
with 15 mole % Ti, thermal shock resistance of, (6) 334.

Standing Committees for 1966–1967

The American Ceramic Society

Executive

GEORGE J. BAIR, *chairman (ex officio)*
Corning Glass Works, Technical Staffs Services
Corning, N. Y. 14830
HOWARD P. BONEBRAKE
5250 S.W. 62nd Ave., Miami, Fla. 33155
ELBURT F. OSBORN, Pennsylvania State University
207 Old Main, University Park, Pa. 16802
ALFRED W. ALLEN, University of Illinois
Ceramic Engineering Dept., Urbana, Ill. 61801
JAMES S. OWENS, Champion Spark Plug Co., Ceramic Div.
8525 Butler Ave., Detroit, Mich. 48211

Rules

JOHN F. MCMAHON, *chairman*
13 Sayles St., Alfred, N. Y. 14802
KENNETH C. LYON, 317 E. Washington St.
Dunkirk, Ind. 47336 (Ball Brothers Research Corp.)
JOHN S. NORDYKE, 440 Sulgrave Rd.
Pittsburgh, Pa. 15211 (Hammond Lead Products, Inc.)

Publications

W. J. SMOTHERS, *chairman;* Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016
HOWARD F. MCMURDIE
National Bureau of Standards, Washington, D. C. 20234
SEYMOUR L. BLUM, IIT Research Institute
10 West 35th St., Chicago, Ill. 60616
CLARENCE L. BABCOCK, 1718 Potomac Drive
Toledo, Ohio 43607 (Owens-Illinois, Inc.)
F. P. REID (ex officio)

Finance

LORAN S. O'BANNON, *chairman;* Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
ARTHUR J. BLUME, American Olean Tile Co.
Lewisport, Ky. 42351
JOHN MCLAREN, Box 75, East Liverpool, Ohio 43920
(Sales Representative)

Classes and Divisions

RALPH L. COOK, *chairman;* University of Illinois
209 Ceramics Bldg., Urbana, Ill. 61801
(With the presiding officer of each Class and the chairman of each Division)

Sections

LORAN S. O'BANNON, *chairman;* Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
(With the counselor of each active Section)

Student Branches

L. D. HART, *chairman;* 8909 Redoak Drive
Crestwood, Mo. 63126 (Alcoa Research Labs.)
GEORGE J. MIDDLETON, 328 Fifth St.
Manhattan Beach, Calif. 90266 (Paul W. Wood Co.)
PHILIPPE D. S. ST. PIERRE, General Electric Research & Development Center, Box 8, Schenectady, N. Y. 12301

Trustees Nominating

GEORGE J. BAIR, *chairman;* Corning Glass Works
Technical Staffs Services, Corning, N. Y. 14830
HOWARD P. BONEBRAKE
5250 S.W. 62nd Ave., Miami, Fla. 33155
ELBURT F. OSBORN, Pennsylvania State University
207 Old Main, University Park, Pa. 16802

Programs and Meetings

WILLARD E. HAUTH, Jr., *chairman;* 1218 Blanchard Ave.
Flint, Mich. 48503 (AC Spark Plug Div., General Motors)
EDWIN RUH, 892 Old Hickory Rd., Pittsburgh, Pa. 15216
(Harbison-Walker Refractories Co., Garber Research Lab.)
WINSTON DUCKWORTH, Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
STEPHEN D. STODDARD, 1460 Myrtle St.
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
F. P. REID (ex officio)

Classification, Nomenclature and Standards

WALTER H. GITZEN, *chairman*
One Wesley Dr., Belleville, Ill. 62223
(With the chairman of the Classification and Nomenclature Committee of each Division)

Ross Coffin Purdy Award

EDWIN RUH, *chairman* (1967); 892 Old Hickory Rd.
Pittsburgh, Pa. 15216
(Harbison-Walker Refractories Co., Garber Research Lab.)
JAMES S. OWENS (1968), Champion Spark Plug Co., Ceramic Div.
8525 Butler Ave., Detroit, Mich. 48211
DWIGHT G. MOORE (1969), University of Denver, Metallurgy Div., D.R.I., Denver, Colo. 80210
WILLIS E. MOODY (1970), Georgia Institute of Technology
School of Ceramic Engineering, Atlanta, Ga. 30332
FLOYD A. HUMMEL (1971), Pennsylvania State University
Mineral Industries Bldg., University Park, Pa. 16802

Orton Memorial Lecture

W. D. KINGERY, *chairman* (1967); Massachusetts Institute of Technology, Ceramics Div., Rm. 13-4090, Cambridge, Mass. 02139
RALSTON RUSSELL, Jr. (1968) Ohio State University
Dept. of Ceramic Engineering, 2041 N. College Rd., Columbus, Ohio 43210

John Jeppson Award

ALEXIS G. PINCUS, *chairman* (1967); IIT Research Institute
10 West 35th St., Chicago, Ill. 60616
MICHAEL P. FEDOCK (1967), 7144 Seven Hills Dr.
Cleveland, Ohio 44131 (Republic Steel Corp.)
ALAN T. PRINCE (1967), Dept. of Mines & Technical Surveys, Water Research Branch, Ottawa, 4, Ont., Canada
WAYNE E. BROWNELL (1968) State University of New York
College of Ceramics at Alfred University, Alfred, N. Y. 14802
GRANT E. MILLER (1968), Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
A. E. R. WESTMAN (1968), 35 Glenayr Rd.
Toronto 10, Ont., Canada
HARRY W. THIEMECKE (1969), Homer Laughlin China Co.
Newell, W. Va. 26050
FRANK J. ZVANUT (1969), Two Country Club Acres
St. Charles, Mo. (Frank Zvanut Co.) 63301
RICHARD M. FULRATH (1969) University of California
264 Hearst Mining Bldg., Berkeley, Calif. 94720

Honorary Members

OSCAR G. BURCH, *chairman* (1967)
1400 Bluebell Ave., Boulder, Colo. 80302
JOHN S. NORDYKE (1968), 440 Sulgrave Rd.
Pittsburgh, Pa. 15211 (Hammond Lead Products, Inc.)
JOHN H. KOENIG (1969), Rutgers, the State University
School of Ceramics, New Brunswick, N. J. 08903
PAUL V. JOHNSON (1970), Structural Clay Products Research Foundation, Geneva, Ill. 60134
ELBURT F. OSBORN (1971) Pennsylvania State University
207 Old Main, University Park, Pa. 16802

JOURNAL
of the
American Ceramic Society

A MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO THE SILICATE INDUSTRIES

VOLUME 49, 1966

F. P. Reid, *Editor*
Herbert Insley, *Consulting Editor*
Margie K. Reser, *Technical Editor*
M. Geraldine Smith, *Associate Editor*
Barbara L. White, *Assistant Editor*
Olive Scott, *Editorial Assistant*

Committee on Publications: W. J. Smothers, *Chairman;*
Howard F. McMurdie, Seymour L. Blum, Clarence L. Babcock, Edward E. Mueller

Executive, Editorial, and Advertising Offices: **4055 North High Street, Columbus, Ohio 43214**
Publication Office: **Easton, Pennsylvania**

Officers of The American Ceramic Society, 1966–67

Society Officers

President: GEORGE J. BAIR, Corning Glass Works
Technical Staffs Services, Corning, N. Y. 14830
President-Elect: JAMES S. OWENS, Champion Spark Plug Co.
Ceramic Div., 8525 Butler Ave., Detroit, Mich. 48211
Vice Presidents:
ARTHUR J. BLUME, American Olean Tile Co.
Lewisport, Ky. 42351
EDWARD C. HENRY, General Electric Co.
Valley Forge Space Technology Center, King of Prussia, Pa.
HARRY W. THIEMECKE, Homer Laughlin China Co.
Newell, W. Va. 26050
Treasurer: LORAN S. O'BANNON, Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
Past-President: HOWARD P. BONEBRAKE
5250 S.W. 62nd Ave., Miami, Fla. 33155
Past-President: ELBURT F. OSBORN
Pennsylvania State University
207 Old Main, University Park, Pa. 16802

Division Officers

Basic Science Division

Trustee: FLOYD A. HUMMEL (1969)
Pennsylvania State University
Mineral Industries Bldg., University Park, Pa. 16802
Chairman: LAWRENCE H. VAN VLACK, University of Michigan
Dept. of Chemical & Metallurgical Engineering
Ann Arbor, Mich. 48104
Chairman-Elect: RUSTUM ROY, Pennsylvania State University
Research Bldg. 1-112, University Park, Pa. 16802
Vice Chairman: ALBERT E. PALADINO, JR., Raytheon Co.
Research Div., 28 Seyon St., Waltham, Mass. 02154
Secretary: RALPH CARTER, General Electric Research and
Development Center, Box 1088, Schenectady, N. Y. 12301

Ceramic-Metal Systems Division

Trustee: DWIGHT G. MOORE (1967)
University of Denver, Metallurgy Div., Denver, Colo. 80210
Chairman: HAROLD C. WILSON
Vitreous Steel Products Co., Box 150, Nappanee, Ind. 46550
Vice Chairman: JACK E. BURROUGHS, SR.
General Dynamics Corp., Grant Lane, Fort Worth, Texas 76101
Secretary: CLIFTON G. BERGERON, University of Illinois
203 Ceramics Bldg., Urbana, Ill. 61801
Counselor: JESSE D. WALTON, JR., Georgia Institute of
Technology, High Temperature Materials Branch
225 North Ave., N.W., Atlanta, Ga. 30332

Design Division

Trustee: JULES R. GULDEN (1968)
Syracuse China Corp., Syracuse, N. Y. 13201
Chairman: SAMUEL L. FAHNESTOCK
16048 Tupper St., Sepulveda, Calif. 91343
First Vice Chairman: DON SCHRECKENGOST
Design for Industry, Inc., 2617 St. Clair Ave. MC-19
East Liverpool, Ohio 43920
Second Vice President: JOEL P. MYERS
Blenko Glass Co., Inc., Milton, W. Va. 25541
Secretary: DONALD E. FRITH, 1109 W. Clark
Champaign, Ill. 61820 (University of Illinois)

Electronics Division

Trustee: ALEXIS G. PINCUS (1969) IIT Research Institute
10 West 35th St., Chicago, Ill. 60616
Chairman: SEYMOUR L. BLUM, IIT Research Institute
10 West 35th St., Chicago, Ill. 60616
Chairman-Elect: RAYMOND J. BROWN
Cesco Plant, Refractories Div., Ferro Corp.
Box 151, Crooksville, Ohio 43731
Vice Chairman: GILBERT GOODMAN, Vitramon, Inc.
Box 544, Bridgeport, Conn. 06601
Secretary: VICTOR J. TENNERY, University of Illinois
205 Ceramics Bldg., Urbana, Ill. 61801

Glass Division

Trustee: CLARENCE L. BABCOCK (1968)
1718 Potomac Dr., Toledo, Ohio 43607 (Owens-Illinois)
Chairman: WILLIAM R. PRINDLE, Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
First Vice Chairman: CHARLES L. MCKINNIS
Owens-Corning Fiberglas Corp., Technical Center
Granville, Ohio 43023
Second Vice Chairman: DELFORD A. MCGRAW
4117 Graceway, Toledo, Ohio 43606 (Owens-Illinois)
Secretary: Fay V. Tooley, 611 W. Oregon
Urbana, Ill. 61801 (University of Illinois)

Materials & Equipment Division

Trustee: JOHN MCLAREN (1969) Box 75
East Liverpool, Ohio 43920 (Sales Representative)
Chairman: GEORGE A. WIEAND, Pennsylvania Glass Sand Corp.
Two Gateway Center, Pittsburgh, Pa. 15222
Chairman-Elect: FRANK J. ZVANUT, Two Country Club Acres
St. Charles, Mo. 63301 (Frank Zvanut Co.)
Vice Chairman: WILLIAM K. BURRISS, International Minerals
& Chemical Corp., Industrial Minerals, Div.
5401 Old Orchard Rd., Skokie, Ill. 60076
Secretary: RICHARD O. HOMMEL, 1526 Valmont St.
Pittsburgh, Pa. 15217 (The O. Hommel Co.)

Nuclear Division

Trustee: STEPHEN D. STODDARD, 1460 Myrtle St.
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
Chairman: STEPHEN D. STODDARD, 1460 Myrtle St.
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
Vice Chairman: RICHARD M. FULRATH, University of Calif.
264 Hearst Mining Bldg., Berkeley, Calif. 94720
Secretary: JOSEPH H. HANDWERK, 1112 Black Rd.
Joliet, Ill. 60435 (Argonne National Lab.)

Refractories Division

Trustee: ALFRED W. ALLEN (1967) University of Illinois
Ceramic Engineering Dept., Urbana, Ill. 61801
Chairman: G. REGINALD RIGBY, Canadian Refractories Ltd.
Box 160, Grenville, Quebec, Canada
Vice Chairman: THEODORE J. M. PLANJE
University of Missouri at Rolla
School of Mines & Metallurgy, Rolla, Mo. 65401

Structural Clay Products Division

Trustee: GILBERT C. ROBINSON (1969)
Box 91, Clemson, S. C. 29631 (Clemson University)
Chairman: HAROLD W. EMRICH, 1740 S. Monaco St.
Denver, Colo. 80222 (Denver Brick & Pipe Co.)
Chairman-Elect: H. HOWARD LUND, Pomona Pipe Products Co.
Winston-Salem Rd., Greensboro, N. C. 27407
Vice Chairman: ROBERT B. HOCKADAY
Acme Brick Co., Box 1189, Denton, Texas 76202
Secretary: ROBERT W. RICHARDS, Richards Brick Co.
234 Springer, Edwardsville, Ill. 62025

White Wares Division

Trustee: RALPH L. GIBSON (1968) 520 Hill Blvd.
East Liverpool, Ohio 43920 (Taylor, Smith & Taylor Co.)
Chairman: GEORGE J. HUND, 221 Poplar Ave., N. W.
Canton, Ohio 44708 (Sparta Ceramic Co.)
Chairman-Elect: FRED G. SIMMEN, R.R. 3, Oakmont
East Liverpool, Ohio 43920 (Hall China Co.)
Vice Chairman: MILAN VUKOVICH, JR.
Edward Orton, Jr., Ceramic Foundation, 1445 Summit St.
Box 8007, Sta. A, Columbus, Ohio 43201
Secretary: WILLIAM B. CAMPBELL, 1892 Inchcliff Rd.
Columbus, Ohio 43221 (Ohio State University)

Ceramic Educational Council

Trustee: WILLIS E. MOODY (1968) School of Ceramic Engineering
Georgia Institute of Technology, Atlanta Ga. 30332
President: PAUL R. JONES, West Virginia University
Dept. of Chemical Engineering, Morgantown, W. Va. 26506
President-Elect: DAVID R. WILDER
1212 S. Third St., Ames, Iowa 50010 (Iowa State University)
Vice President: ALFRED W. ALLEN, University of Illinois
Ceramic Engineering Dept., Urbana, Ill. 61801
Secretary-Treasurer: WILLIS G. LAWRENCE
State University of New York College of Ceramics at
Alfred University, Alfred, N. Y. 14802

National Institute of Ceramic Engineers

Trustee: RALPH L. COOK (1968) University of Illinois
209 Ceramics Bldg., Urbana, Ill. 61801
President: WILLIAM O. BRANDT, 1350 S. Monroe St.
Denver, Colo. 80210 (Consultant)
President-Elect: WILLARD E. HAUTH, JR., 1218 Blanchard Ave.
Flint, Mich. 48503 (AC Spark Plug Div., General Motors Corp.)
Vice President: ROBERT J. BEALS, Argonne National Lab.
9700 S. Cass Ave., Bldg. 212, Argonne, Ill. 60439
Secretary-Treasurer: MURRAY C. GAUTSCH, M & T Chemicals Inc.
100 Park Ave., New York, N. Y. 10017

TABLE OF CONTENTS

VOLUME 49, 1966

January [No. 1], pp. 1–54

1. Marcus P. Borom and Joseph A. Pask: Role of "Adherence Oxides" in the Development of Chemical Bonding at Glass-Metal Interfaces 1
2. John M. Barsom: Effect of Stress and Strain on Producing Hackle in a Glass Plate 6
3. S. Kumar and B. B. Nag: Electrical Properties of Crystallized Glasses in the System MgO–Al_2O_3–SiO_2–TiO_2 10
4. R. D. Carnahan and J. O. Brittain: Dislocation Damping in Rutile Single Crystals 15
5. E. F. Riebling: Structure of B_2O_3 and Binary Aluminoborate Melts at 1600°C 19
6. William C. Hagel, P. J. Jorgensen, and D. S. Tomalin: Initial Sintering of α-Cr_2O_3 23
7. D. W. Readey and G. C. Kuczynski: Sublimation of Aluminum Oxide in Hydrogen 26
8. T. J. Rockett and W. R. Foster: The System Silica–Sodium Tetraborate 30
9. W. R. Buessem, L. E. Cross, and A. K. Goswami: Phenomenological Theory of High Permittivity in Fine-Grained Barium Titanate 33
10. W. R. Buessem, L. E. Cross, and A. K. Goswami: Effect of Two-Dimensional Pressure on the Permittivity of Fine- and Coarse-Grained Barium Titanate 36
11. R. J. Stokes: Thermal-Mechanical History and the Strength of Magnesium Oxide Single Crystals: II, Etch Pit and Electron Transmission Studies 39

Discussions and Notes

Tokuyoshi Ohashi and Akinori Watanabe: Sintering of Vanadium Dioxide 46
G. C. Nicholson: Grain Growth in Magnesium Oxide Containing Iron Oxide or Titanium Dioxide 47
D. Lewis and M. W. Lindley: Enhanced Activity and the Characterization of Ball-Milled Alumina 49
Gene C. Ulmer and William B. White: Existence of Chromous Ion in the Spinel Solid Solution Series $FeCr_2O_4$–$MgCr_2O_4$ 50
A. E. Paladino and B. D. Roiter: Czochralski Growth of Yttrium-Gallium Garnet 51
Nobuo Nakayama, Eiichi Hirota, and Tomozo Nishikawa: Hot-Pressing of CrO_2 52
H. L. Bourne: Silicon Monoxide Technique for Observing Surface Microtopography 53

February [No. 2], pp. 55–112

12. R. J. Charles: Metastable Liquid Immiscibility in Alkali Metal Oxide–Silica Systems 55
13. A. E. R. Westman and R. Beatty: Equations for Calculating Chain Length Distributions in Polyphosphoric Acids and Polyphosphate Glasses 63
14. D. P. H. Hasselman and R. M. Fulrath: Proposed Fracture Theory of a Dispersion-Strengthened Glass Matrix 68
15. R. B. Day and R. J. Stokes: Effect of Crystal Orientation on the Mechanical Behavior of Magnesium Oxide at High Temperatures 72
16. D. J. Liedberg, R. J. Smid, and C. G. Bergeron: Microseparation in Lead Borate Glasses 80
17. Thomas D. McGee: Constitution of Fireclays at High Temperatures: I, Methods of Analysis 83
18. Thomas D. McGee: Constitution of Fireclays at High Temperatures: II, Mineralogical Composition 87
19. Thomas D. McGee: Constitution of Fireclays at High Temperatures: III, Deformation Characteristics 90
20. Stanley B. Austerman and J. W. Wagner: Cation Diffusion in Single-Crystal and Polycrystalline BeO 94
21. Kent W. Hansen and Ivan B. Cutler: Electrical Conductivity in $Fe_{1-x}O$-MgO Solid Solutions 100

Discussions and Notes

D. P. H. Hasselman: Theory of Thermal Shock Resistance of Semitransparent Ceramics Under Radiation Heating 103
E. A. Giess: Vaporization of PbO-PbF_2 Melt During Solution Growth of YIG Crystals 104
Kenneth E. Kolb and Kent W. Hansen: Time and Temperature Effects on Silica Distribution in Borate Glasses 105
Leon E. Sobon and Paul E. Greene: Crystal Growth of Some Vanadium Oxides 106
Erik Rosén and Arnulf Muan: Stability of $MgAl_2O_4$ at 1400°C as Derived from Equilibrium Measurements in $CoAl_2O_4$-$MgAl_2O_4$ Solid Solutions 107
I. Zaplatynsky: Observations on Zeta Phase in the System Ta–C 109
W. H. Rhodes: Etching and Chemical Polishing of Single-Crystal $SrTiO_3$ 110
M. Wuttig: Grain-Boundary Diffusion of Ni^{2+} in MgO 112

March [No. 3], pp. 113–72

22. G. H. Haertling: Grain Growth and Densification of Hot-Pressed Lead Zirconate-Lead Titanate Ceramics Containing Bismuth 113
23. F. E. Wagstaff and K. J. Richards: Kinetics of Crystallization of Stoichiometric SiO_2 Glass in H_2O Atmospheres 118
24. P. L. Edwards and S. Huang: Comparison of Whisker Growth Sites and Dislocation Etch Pits on Single-Crystal Sapphire 122
25. G. G. Bentle: Elastic Constants of Single-Crystal BeO at Room Temperature 125
26. C. L. Hoenig and Alan W. Searcy: Knudsen and Langmuir Evaporation Studies of Stannic Oxide 128
27. C. R. Kurkjian and J. T. Krause: Acoustic Spectra of Na_2O-GeO_2 Glasses 134
28. L. A. Simpson and R. E. Carter: Oxygen Exchange and Diffusion in Calcia-Stabilized Zirconia 139
29. N. M. Cameron: Relation Between Melt Treatment and Glass Fiber Strength 144
30. Herbert D. Kivlighn, Jr.: Solid State Reactivity and Glass Crystallization Behavior of Some Alkali Aluminogermanates 148
31. A. Cimino, P. Porta, and M. Valigi: Dependence of the Lattice Parameter of Magnesium Oxide on Crystallite Size 152
32. Wendell S. Williams: High-Temperature Thermal Conductivity of Transition Metal Carbides and Nitrides 156
33. T. E. Clare: Sintering Kinetics of Beryllia 159

Discussions and Notes

L. A. Brissette, P. L. Burnett, R. M. Spriggs, and T. Vasilos: Thermomechanically Deformed Y_2O_3 165
E. M. Passmore and T. Vasilos: Creep of Dense, Pure, Fine-Grained Aluminum Oxide 166
Gerald Katz and Rustum Roy: Flux Growth and Characterization of β-Ga_2O_3 Single Crystals 168
R. L. Mehan and J. M. Berry: Nonlinear Behavior in Three-Point Bending of High-Strength, High-Modulus Fibers 169
Norman F. H. Bright and A. C. Turnock: Nonstoichiometric Tantalian Magnetites 170
C. R. Kurkjian and J. T. Krause: Effect of OH Content on the Acoustic Spectra of B_2O_3 Glass 171

April [No. 4], pp. 173–232

34. C. D. Wirkus and D. R. Wilder: High-Temperature Oxidation of Molybdenum Disilicide ... 173
35. A. C. Turnock: Fe-Nb Oxides: Phase Relations at 1180°C ... 177
36. Phillip G. Wahlbeck and Paul W. Gilles: Reinvestigation of the Phase Diagram for the System Titanium–Oxygen ... 180
37. Edward Schreiber and Orson L. Anderson: Pressure Derivatives of the Sound Velocities of Polycrystalline Alumina ... 184
38. C. O. Hulse and W. K. Tice: General Fracture Method for Preparation of Foils for Transmission Electron Microscopy ... 190
39. R. A. Vernetti and R. L. Cook: Effect of Metal Oxide Additions on the High-Temperature Electrical Conductivity of Alumina ... 194
40. F. S. Pettit, E. H. Randklev, and E. J. Felten: Formation of $NiAl_2O_4$ by Solid State Reaction ... 199
41. B. Cockayne: Observation and Control of Deviations in Molar Composition in Single-Crystal Growth of Mixed Oxides ... 204
42. J. E. Ayer and F. E. Soppet: Vibratory Compaction: II, Compaction of Angular Shapes ... 207
43. Donald R. Ulrich and Edward J. Smoke: Devitrified Barium Titanate Dielectrics ... 210
44. F. A. Kröger: Electronic Conductivity of Calcia-Stabilized Zirconia ... 215
45. Iain Finnie: Method for Predicting Creep in Tension and Compression from Bending Tests ... 218
46. Norman S. Eiss, Jr., and Richard C. Fabiniak: Chemical and Mechanical Mechanisms in Wear of Sapphire on Steel ... 221

Discussions and Notes

W. R. Manning, M. O. Marlowe, and D. R. Wilder: Temperature and Porosity Dependence of Young's Modulus of Polycrystalline Dysprosium Oxide and Erbium Oxide ... 227
S. B. Holmquist: Ionic Formulation of Redox Equilibria in Glass Melts ... 228
Yoshihiro Matsuo and Hiromu Sasaki: Effect of Grain Size on Microcracking in Lead Titanate Ceramics ... 229
W. A. Sanders and H. B. Probst: Hardness of Five Borides at 1625°C ... 231
Eugene W. Sucov: Correction: Diffusion of Oxygen in Vitreous Silica (January issue, 1963) ... 232

May [No. 5], pp. 233–90

47. A. B. Chase: Habit Modification of Corundum Crystals Grown from Molten PbF_2-Bi_2O_3 ... 233
48. J. J. Comer, N. C. Tombs, and J. F. Fitzgerald: Growth of Single-Crystal and Polycrystalline Thin Films of $MgAl_2O_4$ and $MgFe_2O_4$ ... 237
49. A. W. Smith, F. W. Meszaros, and C. D. Amata: Permeability of Zirconia, Hafnia, and Thoria to Oxygen ... 240
50. W. H. Rhodes and R. E. Carter: Cationic Self-Diffusion in Calcia-Stabilized Zirconia ... 244
51. Paul D. Wilcox and Ivan B. Cutler: Strength of Partly Sintered Alumina Compacts ... 249
52. Donald H. DeClerck and Gouq-Jen Su: Rheological and Electrokinetic Properties of Glass-Frit and Quartz Suspensions ... 252
53. Walter C. Allen: Temperature Dependence of Properties of Magnesium Ferrite ... 257
54. M. W. Shafer and J. C. Suits: Preparation and Faraday Rotation of Divalent Europium Glasses ... 261
55. P. L. Farnsworth and R. L. Coble: Deformation Behavior of Dense Polycrystalline SiC ... 264
56. R. F. Feldman and V. S. Ramachandran: Character of Hydration of $3CaO \cdot Al_2O_3$ ... 268
57. E. J. Felten, P. G. Sprang, and S. Rosen: Phase Relations in the System $CoNb_2O_6$–$CoTa_2O_6$ ... 273
58. Paul R. Van Loan and M. R. Chakrabarty: Crystal Chemistry and Dielectric Properties in the Systems $BaTiO_3$–UO_2 and $BaTiO_3$–$BaUO_3$ ... 276
59. Alfred R. Cooper, Jr., and James H. Heasley: Extension of Darken's Equation to Binary Diffusion in Ceramics ... 280

Discussions and Notes

R. E. Newnham, L. G. Caron, and R. P. Santoro: Magnetic Properties of $CaCoSiO_4$ and $CaFeSiO_4$ ... 284
C. L. McDaniel and S. J. Schneider: Phase Relations Between Cr_2O_3 and IrO_2 in Air ... 285
K. S. Mazdiyasni, C. T. Lynch, and J. S. Smith: Metastable Transitions of Zirconium Oxide Obtained from Decomposition of Alkoxides ... 286
A. E. Paladino: Discussion of Paper "Oxygen Content of Nickel Ferrites at 1300°C" ... 288
W. E. Kramer and R. Mazelsky: Crystal Growth of β-Spodumene ... 290

June [No. 6], pp. 291–344

60. Klara Kiss, Jules Magder, Mark S. Vukasovich, and Robert J. Lockhart: Ferroelectrics of Ultrafine Particle Size: I, Synthesis of Titanate Powders of Ultrafine Particle Size ... 291
61. Theodore M. Harkulich, Jules Magder, Mark S. Vukasovich, and Robert J. Lockhart: Ferroelectrics of Ultrafine Particle Size: II, Grain Growth Inhibition Studies ... 295
62. Robert J. Lockhart and Jules Magder: Ferroelectrics of Ultrafine Particle Size: III, Thin Barium Titanate Layers for Capacitors ... 299
63. E. D. Kolb and R. A. Laudise: Hydrothermally Grown ZnO Crystals of Low and Intermediate Resistivity ... 302
64. W. H. Class and E. S. Machlin: Crack Propagation Method for Measuring Grain Boundary Energies in Brittle Materials ... 306
65. M. K. Murthy and A. E. R. Westman: Constitution of Mixed-Alkali Phosphate Glasses: IV, Constitution of Lithium-Cesium Phosphate Glasses ... 310
66. C. O. Hulse and Joseph A. Pask: Analysis of Deformation of a Fireclay Refractory ... 312
67. Naohiro Soga and Orson L. Anderson: Simplified Method for Calculating Elastic Moduli of Ceramic Powder from Compressibility and Debye Temperature Data ... 318
68. H. D. Lewis and A. Goldman: Theorems for Calculation of Weight Ratios to Produce Maximum Packing Density of Powder Mixtures ... 323
69. D. P. Masse, Erik Rosén, and Arnulf Muan: Activity-Composition Relations in Co_2SiO_4-Fe_2SiO_4 Solid Solutions at 1180°C ... 328
70. H. P. Kirchner and R. M. Gruver: Chemical Strengthening of Polycrystalline Ceramics ... 330
71. Alan Arias: Thermal Shock Resistance of Zirconia with 15 Mole % Titanium ... 334
72. Alan Arias: Mechanism by Which Metal Additions Improve the Thermal Shock Resistance of Zirconia ... 339

Discussions and Notes

Edward Schreiber and Naohiro Soga: Elastic Constants of Silicon Carbide ... 342
K. J. Richards: Oriented Growth of Dehydration Products of Calcium Sulfate Dihydrate ... 342
T. R. Cass and J. Washburn: Dislocation Etch Pits on {110} Planes of Magnesium Oxide ... 343

July [No. 7], pp. 345–400

73. R. B. Day and R. J. Stokes: Mechanical Behavior of Polycrystalline Magnesium Oxide at High Temperatures ... 345
74. Naohiro Soga and Orson L. Anderson: High-Temperature Elastic Properties of Polycrystalline MgO and Al_2O_3 ... 355
75. Peter Jeschke: Texture Analysis of Basic Refractory Brick ... 360
76. W. C. Ormsby and L. H. Bolz: Microtexture and Composition of Reaction Products in the System Kaolin–Lime–Water ... 364
77. D. W. Readey: Mass Transport and Sintering in Impure Ionic Solids ... 366
78. N. Klinger, E. L. Strauss, and K. L. Komarek: Reactions Between Silica and Graphite ... 369
79. Victor J. Tennery: Dielectric Properties and Phase Transitions of Ferroelectric Sodium-Strontium Niobates ... 376
80. J. H. Sharp, G. W. Brindley, and B. N. Narahari Achar: Numerical Data for Some Commonly Used Solid State Reaction Equations ... 379
81. A. C. Turnock: Mn-Ta Oxides: Phase Relations at 1200°C ... 382

82. Luke L. Y. Chang, Margaret G. Scroger, and Bert Phillips: Alkaline-Earth Tungstates: Equilibrium and Stability in the M–W–O Systems 385
83. Howard B. Johnson, Owen W. Johnson, and Ivan B. Cutler: Effect of Water Vapor on Dielectric Loss in MgO 390

Discussions and Notes

J. Lambert Bates: Melting Points of Hypostoichiometric Uranium Dioxide 395
James E. Neely and F. M. Ernsberger: Absence of Devitrification at Bubble Surfaces in Soda-Lime Glasses 396
S. B. Holmquist: Hydrothermal Silica Transformations 397
John W. Lennon: Nomograph for Converting Average Intercept Size to Average Grain Size 398
K. D. Reeve and T. E. Clare: Comments on Papers "Sintering in Very Pure Magnesium Oxide and Magnesium Oxide Containing Vanadium" and "Sintering in Calcium Oxide and Calcium Oxide Containing Strontium" 400

August [No. 8], pp. 401–60

84. N. M. Tallan and R. W. Vest: Electrical Properties and Defect Structure of Y_2O_3 401
85. Orson L. Anderson and P. Andreatch, Jr.: Pressure Derivatives of Elastic Constants of Single-Crystal MgO at 23° and −195.8°C 404
86. L. E. Poteat and C. S. Yust: Creep of Polycrystalline Thorium Dioxide 410
87. W. R. Wilcox and L. D. Fullmer: Growth of $KTaO_3$-$KNbO_3$ Mixed Crystals 415
88. William D. Callister, Jr., Ivan B. Cutler, and Ronald S. Gordon: Thermal Decomposition Kinetics of Boehmite 419
89. A. M. Bishay and S. Arafa: Gamma-Induced Absorption and Structural Studies of Arsenic Borate Glasses 423
90. C. M. Schlaudt and Della M. Roy: The Join Ca_2SiO_4-$CaMgSiO_4$ 430
91. B. J. Wuensch and T. Vasilos: Origin of Grain-Boundary Diffusion in MgO 433
92. Michael Cable: Kinetics and Mechanisms of Fining Glasses 436
93. T. S. Busby and J. Barker: Simulative Studies of Upward Drilling 441
94. V. O. Altemose: Outgassing of Glass Caused by Thermal Neutrons and Gamma Radiation 446
95. A. J. Burggraaf: Sorption of Argon by Glass in a Gas-Discharge Lamp 450

Discussions and Notes

W. M. Hirthe, A. T. Meiville, and P. H. Wackman: Preparation by Ion Bombardment of Near-Stoichiometric Rutile (TiO_2) for Transmission Electron Microscopy 454
S. Aronson, E. Cisney, and A. B. Auskern: Thermal Expansion of Nonstoichiometric Zirconium Carbides 456
Tsuneharu Nitta, Kaneomi Nagase, and Shigeru Hayakawa: Electroless Nickel-Phosphorus Alloy Electrode for Semiconductive Barium Titanate Ceramics 457
Howard B. Johnson, Neal J. Tolar, G. R. Miller, and Ivan B. Cutler: Dipole Relaxation in CaF_2 Doped with NaF 458
A. H. Agajanian and H. L. Turk: Magnetic Properties of Nonstoichiometric NiZn Ferrites 459
A. B. Chase and W. R. Wilcox: Elimination of Inclusions from Flux-Grown Crystals 460

September [No. 9], pp. 461–520

96. Robert H. Doremus: Physical Solubility of Gases in Fused Silica 461
97. Hans-Otto Mulfinger: Physical and Chemical Solubility of Nitrogen in Glass Melts 462
98. Stig Holmquist: Oxygen Ion Activity and the Solubility of Sulfur Trioxide in Sodium Silicate Melts 467
99. Helmut Franz: Solubility of Water Vapor in Alkali Borate Melts 473
100. A. C. D. Chaklader and L. G. McKenzie: Reactive Hot-Pressing of Clays and Alumina 477
101. Victor J. Tennery: High-Temperature Phase Transitions in $PbZrO_3$ 483
102. C. O. McHugh, T. J. Whalen, and M. Humenik, Jr.: Dispersion-Strengthened Aluminum Oxide 486
103. F. J. Shonebarger and Henry H. Blau: Study of Glass Surfaces by Generation of Electrostatic Charges 492
104. Martin H. Leipold: Impurity Distribution in MgO 498
105. Oswald R. Bergmann and Jonathan Barrington: Effect of Explosive Shock Waves on Ceramic Powders 502
106. William J. Kroenke: Mechanical Test for Anisotropy; Failure of Aluminoborosilicate Glass Fibers Under Combined Loadings of Tension and Torsion 508

Discussions and Notes

W. D. Johnston: Formulation of Oxidation-Reduction Reactions in Glass Melts 513
P. K. Foster and I. R. Hughes: Internal Stress in Ceramics Containing Cristobalite 515
A. M. Gaines, A. J. Perrotta, and D. A. Stephenson: Phenacite-Spinel Transition in $LiAlGeO_4$ 516
M. Kestigian, F. D. Leipziger, J. R. Carter, and F. G. Garabedian: Preparation of $K_4Nb_6O_{17}$ Single Crystals 517
V. S. Stubican and C. Greskovich: Jahn-Teller Distortion Induced by Tetrahedral-Site Cr^{2+} Ions in Spinels 518
Yoshikazu Horiguchi: Formation of Zinc Orthosilicate by Explosive Shock 519
Tokuyoshi Ohashi and Akinori Watanabe: Temperature Dependence of Electrical Resistivity of VO_2 Powder 519

October [No. 10], pp. 521–76

107. W. H. Rhodes and W. D. Kingery: Dislocation Dependence of Cationic Diffusion in $SrTiO_3$ 521
108. Paul F. Eastman and Ivan B. Cutler: Effect of Water Vapor on Initial Sintering of Magnesia 526
109. K. Vedam, E. D. D. Schmidt, and Rustum Roy: Nonlinear Variation of Refractive Index of Vitreous Silica with Pressure to 7 Kbars 531
110. V. S. Stubican and I. de Menezes: Grain-Boundary Reactions in Magnesia-Chrome Refractories: Application of the Electron Probe, I 535
111. Y. Baskin: Properties of Uranium Monophosphide 541
112. M. L. Pearce and J. F. Beisler: Diffusion Studies of Na_2O-SiO_2-Fe_2O_3 Melts at 1200°C 547
113. E. Plumat, F. Toussaint, and M. Boffe: Formation of Bubbles by Electrochemical Processes in Glass 551
114. J. H. Cowan, W. M. Buehl, and J. R. Hutchins, III: An Electrochemical Theory for Oxygen Reboil 559
115. W. D. Johnston and A. Chelko: Oxidation-Reduction Equilibria in Molten $Na_2O \cdot 2SiO_2$ Glass in Contact with Metallic Copper and Silver 562
116. A. Paul and D. Lahiri: Manganous-Manganic Equilibrium in Alkali Borate Glasses 565
117. C. G. Rasul and M. Cable: Spontaneous Bubble Formation in Silicate Melts at High Temperatures 568

Discussions and Notes

John T. Jones and Ivan B. Cutler: Stoichiometry of MgO-Mn_xO Solid Solutions in Air at High Temperatures 572
L. M. Adelsberg, L. H. Cadoff, and J. M. Tobin: Group IVB and VB Metal Carbide-Carbon Eutectic Temperatures 573
N. G. Dave and S. K. Chopra: Preparation and Thermal Decomposition of Calcium Hydroxide Crystals 575
W. H. Grodkiewicz and D. J. Nitti: Oxide Crystal Growth by Flux Evaporation 576

November [No. 11], pp. 577–628

118. Hiromu Ouchi, Masamitsu Nishida, and Shigeru Hayakawa: Piezoelectric Properties of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ Ceramics Modified with Certain Additives 577

119. Michael Schwartz and J. D. Mackenzie: Ionic Conductivity in Calcium Silicate Glasses 582
120. Ellen L. Mochel, Martin E. Nordberg, and Thomas H. Elmer: Strengthening of Glass Surfaces by Sulfur Trioxide Treatment 585
121. J. R. Blachere: Desulfurization of Pyrite 590
122. E. M. Passmore, R. H. Duff, and T. Vasilos: Creep of Dense, Polycrystalline Magnesium Oxide 594
123. Saburo Mori: Phase Transformation in Barium Orthoferrate, $BaFeO_{3-x}$ 600
124. Bh. V. Janakirama-Rao: Infrared Spectra of GeO_2-P_4O_{10}-V_2O_5 Glasses and Their Relation to Structure and Electronic Conduction 605
125. I. de Menezes and V. S. Stubican: Grain-Boundary Reactions in Magnesia-Chrome Refractories: Application of the Electron Probe, II 609
126. M. J. Kerper and T. G. Scuderi: Mechanical Properties of Chemically Strengthened Glasses at High Temperatures 613
127. George Robert McCormick: Subsolidus Equilibria in the System MgO–GeO_2–MgF_2 618
128. Alan Arias: Effect of Inclusions on Grain Growth of Oxides 621

Discussions and Notes

L. M. Atlas, G. J. Schlehman, and D. W. Readey: Defects in PuO_{2-x}: Density Measurements at High Temperature 624
D. K. Smith: The Nonexistence of Yttrium Zirconate 625
T. H. Nielsen and M. H. Leipold: Surface Hydroxyl in MgO 626
R. W. Dickson: Anomaly in Young's Modulus and Internal Friction of $5SrTiO_3 \cdot 3La^{2}/_{3}TiO_3$ Below 100°C 628

December [No. 12], pp. 629–91

129. Albert F. Grenis and Albert P. Levitt: Infrared Radiation of Titanium Boronitride 629
130. Bert Phillips, C. M. Warshaw, and I. Mockrin: Equilibria in $KAlF_4$-Containing Systems 631
131. E. R. Winkler, J. F. Sarver, and Ivan B. Cutler: Solid Solution of Titanium Dioxide in Aluminum Oxide 634
132. S. P. Faile and Della M. Roy: Solubilities of Ar, N_2, CO_2, and He in Glasses at Pressures to 10 Kbars 638
133. J. B. MacChesney, J. J. Jetzt, J. F. Potter, H. J. Williams, and R. C. Sherwood: Electrical and Magnetic Properties of the System $SrFeO_3$–$BiFeO_3$ 644
134. F. W. Cooke, R. C. Bradt, R. C. DeVries, and G. S. Ansell: Dielectric Aging and Microstructure in the System $BaTiO_3$–$CaTiO_3$ 648
135. Michael L. Hair and Ian D. Chapman: Surface Composition of Porous Glass 651
136. Ronald S. Gordon and W. D. Kingery: Thermal Decomposition of Brucite: I, Electron and Optical Microscope Studies 654
137. O. L. Kruger and J. B. Moser: Sintering Characteristics and Properties of PuS and PuP 661
138. Thomas L. Barry, V. S. Stubican, and Rustum Roy: Phase Equilibria in the System CaO–Yb_2O_3 667
139. A. K. Yakhkind: Tellurite Glasses 670

Discussions and Notes

A. F. Moodie, C. E. Warble, and L. S. Williams: Magnesia Precursor and Sintering Study 676
E. F. Osborn: Comment on Note "Hydrothermal Silica Transformations" 677
S. B. Holmquist: Reply to Comment on Note "Hydrothermal Silica Transformations" 678
R. Krishnan: Influence of NiO on the Yield of Yttrium Garnet Crystals Grown from Flux 678
R. A. Eppler: Viscosity of Molten B_2O_3 679
H. M. O'Bryan, F. R. Monforte, and R. Blair: Reply to Discussion of Paper "Oxygen Content of Nickel Ferrite at 1300°C" 680
D. W. Readey: Nonstoichiometry of Cadmium Sulfide Thin Films 681
D. Bloor: Discussion of Paper "Infrared Absorption Spectrum of Silicon Dioxide" 682
R. L. Mehan and J. M. Berry: Correction: Nonlinear Behavior in Three-Point Bending of High-Strength, High-Modulus Fibers 683
Author Index to *The Journal* 684
Subject Index to *The Journal* 686

Instructions for Preparation of Papers and Notes ..... Back Cover, November Journal

CERAMIC ABSTRACTS

December 1966 *SECTION*

Compiled by the American Ceramic Society

AUTHOR INDEX FOR 1966

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates the position of the abstract on the page.

Aagaard, L. Alkali metal titanium phosphate glass, P (4) 96*e*.

Aamodt, R. L., Brown, L. J., and Nichols, B. D. Method and means for improving the electron emission from a refractory conducting material, P (7) 193*g*.

Abbakumov, V. G. Thermotechnical comparison of various types of setting on tunnel kiln cars, (5) 125*d*.

Abbey, S. Determination of potassium, sodium, and calcium in feldspars, (3) 75*h*.

Abbott, R. B., and Olson, R. H. Neck mold [inverting] apparatus for glass forming machine, P (6) 150*d*.

Abdullah, M. I., and Riley, J. P. Titrimetric determination of calcium and magnesium in silicate rocks, (2) 45*e*.

Abdurazakov, A. A. See Bezborodov, M. A.

Abe, K. See Takeuchi, H.

Abe, M. See Kida, K.

Abe, S. See Mihara, Y.

Abe, T. See Moriyama, T.

Abeck, W. See Hoch, W.

Abel'chuk, N. A., Malyshev, S. I., and Lukonin, G. A. Equipment for horizontal softening and hardening of automobile glasses, (10) 264*i*.

Aber, J. I. Size composition for glass, treated glass structures, and method for manufacturing same, P (10) 270*a*.

Abernethy, I. A. Apparatus for securing a plurality of units in abutting relationship with one another, P (1) 13*c*.

Abler, R. L. Urea-formaldehyde resin bonded abrasive sheet, P (8) 205*h*.

Abowitz, G. See Mountvala, A. J.

Abraham, D., and Rauschenfels, E. Rocks and minerals in the Transvaal, (6) 164*i*.

Abramovici, R., Velica, P., and Olah, I. Effect of previously melted feldspar on the porcelain body, (2) 39*g*.

Abrasive Dressing Tool Co. Inspecting abrasive grinding wheels, P (2) 27*g*.

Abrecht, H., and Balb, A. Process for preparation of refractory substances in the form of hollow spheres starting from silicates containing magnesium, P (7) 189*a*.

Abrecht, H., and Lukacs, J. Effect of oxygen deficiency on the properties of ceramically bonded silicon carbide refractories, (10) 271*a*.

Abrikosov, N. Kh. See Glukhikh, L. E.; Poretskaya, L. V.

Acara, N. A. See Breck, D. W.

Accary, A. See Magnier, P.; Rousset, P.

Accary, A., Dubuisson, J., and Rousset, P. Process for the preparation of a uranium compound in powder form, P (4) 101*d*.

Accary, A., Magnier, P., and Marchal, M. Mechanical behavior at elevated temperatures of U-C alloys close to the monocarbide and their fabrication by extrusion, (11) 301*g*.

Achar, B. N. N. See Sharp, J. H.

Achey, N. Drainage tile, P (3) 65*e*.

Achilles, M. See Gebhardt, F.

Acieries Reunies de Burbach-Eich-Dudelange, Soc. Anon. Manufacture of refractory materials, P (6) 154*f*. Process for making converter bottoms, brick, and electrodes based on refractory materials or carbon and organic binders and the products obtained, P (10) 274*b*. Process for making refractory articles, P (7) 189*j*. Refractory composition and process for making same, P (3) 70*j*.

Acker, E. G., Sanchez, M. G., and Vanik, M. C. Fine sized powders of thoria, urania, and mixtures thereof and methods for their preparation, P (1) 11*d*.

Ackerman, S. C. Base end structure for electric lamps or similar devices, P (8) 220*j*.

Ackermann, R. J., and Thorn, R. J. Thermodynamic properties of compounds of actinide elements, B (6) 175*f*. Vaporization properties of thorium, uranium, and plutonium metals and oxides, B (6) 175*b*.

Acloque, P. H. Differential thermal treatment of glass objects, P (8) 212*d*. Sheet of structural tempered glass, P (8) 214*c*.

Adair, J. E. Ornamented drinking glass, P (9) 236*h*.

Adam, J. Dry process enameling, (10) 263*e*. See Gergely, G.; Thorpe, T.

Adam, T. See Harding, A. G.

Adametz, O., and Myl, J. Further possibilities of the use of acoustic thermal analysis, (10) 286*j*.

Adamjan, R. G. See Nabiullin, F. H.

Adams, C. P. Dinnerware must gear for impulse, (8) 219*a*.

Adams, I., Nielsen, J. W., and Story, M. S. Growth of broad line width ruby crystals, (7) 199*i*.

Adams, J. W. Visible region absorption spectra of rare-earth minerals, (3) 87*c*.

Adams, R. V., Rawson, H., Fisher, D. G., and Worthington, P. Use of the electron probe X-ray microanalyzer for the identification of inhomogeneity in glass, (9) 235*g*.

Adams, W. J. Drain line coupling for plain end glass pipe, P (5) 122*e*.

Adamski, T. Gravity flow furnace, (5) 132*d*.

Adamski, T. W., and Kalinowski, B. Method of and apparatus for grinding hard materials, P (4) 109*b*.

Adamson, G. M., Jr. See Hammond, J. P.

Adelsberg, L. M., Cadoff, L. H., and Tobin, J. M. Group IVB and VB metal carbide-carbon eutectic temperatures, (11) 317*h*.

Adkins, F. E., Jr. See Carithers, V. G.

Adwick, A. G. See Garrett, K. H.

A. E. I. John Thompson Nuclear Energy Co., Ltd. Method of constructing a nuclear reactor core from graphite blocks, P (2) 38*c*.

Aerojet-General Corp. High temperature [graphite] nozzle for rocket motor, P (3) 70*j*. Material handling apparatus for pulverulent materials, P (4) 109*a*.

Aerological Research, Inc. Electrical hygrometer, P (7) 195*b*.

Aeronca Mfg. Corp. Foamed zirconia insulating materials, P (3) 70*h*. Method for preparing foamed insulating material, P (3) 70*e*. Zirconia based foam insulating material and method, P (9) 241*e*.

Aerovox Corp. Electric capacitor and method for producing the same, P (11) 305*h*. Process for manufacturing multilayer ceramic capacitors, P (5) 129*d*.

Afanas'ev, A. N., and Andreev, S. I. Use of heat resistant steels for [glass] press molds, (4) 95*i*.

Afanas'ev, I. I. See Mokievskii, V. A.

Affleck, J. H., III. Dispenser cathode, P (6) 159*b*. Thermionic emitter and method of making same, P (4) 106*e*.

Affleck, J. H., III, and Hawkins, N. J. Electron emitter with activator of silicide, boride, or carbide of solid solution of barium and at least one other alkaline earth metal, P (9) 243*d*.

Affleck, J. H., III, and Paley, J. J. Dispenser cathode and method for the production thereof, P (11) 305*f*.

Afinogenov, Yu. P. See Palkin, A. P.

Afrange, O. D. C. Brazilian sodium carbonate as a glass component, (6) 146*j*.

Agajanian, A. H., and Turk, H. L. Magnetic properties of nonstoichiometric NiZn ferrites, (9) 242*e*.

Agency of Industrial Science and Technology. Process for manufacturing ceramiclike products from glass by microscopic crystallization, P (5) 124*c*.

Agnie, J. Material of construction and process for obtaining it, P (7) 188*f*.

Agnihotri, S. K. See Pamnani, K.

Agranovskaya, A. I. See Smolenskii, G. A.

Agron, A. M. See Kropp, D. E.

Agullo-Lopez, F. See Alvarez Rivas, J. L.

Ahn, J., and Geldermans, P. Method for producing square loop nickel ferrous ferrite, P (5) 129*j*.

Ahnstrom, G. Physical and chemical processes accompanying the dissolution of irradiated substances, studied by luminescence measurements, (1) 24*f*.

Ahrens, L. H. Chemical bond and the geochemical distribution of the elements, (4) 109*j*.

Aigrain, P. Properties of semiconductor surfaces—relation to adsorption, catalysis, and adherence, B (6) 175*c*.

Aihara, M. Results of using castable and plastic refractories for joining runner brick, (1) 10*d*.

Aihara, M., and Yamashita, I. Improvement of the bottom lining for the teeming ladle, (1) 9*e*.

Aiken, J. P. Method and apparatus for the production of hardened clay products, P (11) 300*c*.

Ainsley, R., Wood, D. C., and Sowden, R. G. Some aspects of the preparation of uranium and plutonium carbides from oxides, B (6) 172*c*.

Air Reduction Co., Inc. Flashless encapsulated sphere manufacture, P (8) 217*a*. Fuel element manufacture, P (8) 217*b*. Method for extrusion of a graphite matrix containing coated particles, P (8) 217*e*. Oxidation resistant carbonaceous bodies and method for making, P (9) 241*a*. Resistor composition, P (5) 129*h*. Semiconductor film resistor, P (6) 160*h*.

Airtron, Inc. High power microwave components, P (4) 104*j*. Method of making a microwave element, P (3) 73*b*.

Ajem Laboratories, Inc. Method for handling grit, P (5) 131*c*.

Akao, Y. See Moriya, T.

Akashi, T. Effect of impurities on grain boundary of ferrites and their electrical resistivities (II), (9) 242*g*.

Akerman, K., Hoffman, P., and Zablotny, W. Mechanism and rate of passage of materials in rotary kilns, (4) 108*c*.

Akhtar, S. M., and Siddiqi, F. A. Mineralogy of alluvial sand of the Kabul River near Charsadda, (11) 312*e*.

Aktiebolaget Hoganasmetoder. Pulsed oil feeding system for industrial furnaces, P (2) 46*e*.

Aktiebolaget Installationsmateriel. Method of mass producing resistors, P (3) 73*f*.

Aktiebolaget Kamyr. Apparatus for the classification of finely divided materials, P (2) 47*b*.

Aktiebolaget Kanthal. Electric resistance elements of silicon carbide and metal silicide, P (7) 195*i*. Heat-resistant and oxidation-proof material containing molybdenum disilicide, P (7) 195*j*.

Aktiebolaget Separator. Method and apparatus for [successive] centrifugal separation of suspensions, P (11) 309*c*.

Aktiebolaget Svenska Fiaktfabriken. Device for filtering air in spray-painting booths, P (2) 43*e*.

Aladdin Industries, Inc. Automatic flame regulator for glass forming and welding machine, P (10) 267*d*.

Alakin, A. I., Nikitin, B. N., and Tsarevskaya, N. P. Use of rare earths for coloring glass, (9) 235*h*.

Albert, D. Pneumatic fluidizing means, P (3) 75*b*.

Albert, H. J. See Hill, J. S.

Albert, J., and Naray-Szabo, I. Composition and structure study of brick and tile clays, (2) 35*c*.

Albert Air Conveyor Corp. Pneumatic fluidizing means, P (3) 75*b*.

Alberts, L., Bohlmann, M., and Meiring, G. L. Influence of low moisture content on the conductivities of a granular substance such as sand, (9) 250*g*.

Albon, D. Joints for sewer pipes and the like, P (7) 185*d*.

Albrecht, W. Properties and testing of plaster and gypsum, (2) 29*b*.

Albrecht, W., and Schneider, H. Effect of absorptive capacity of building brick on the bearing strength of masonry, (10) 270*d*.

Alcock, C., and Grieveson, P. Study of uranium borides and carbides by means of the Knudsen effusion technique, B (6) 175*d*.

Alcock, C. B. See Steele, B. C. H.

Alcock, N. W., and Kjekshus, A. Crystal structure of ReSe$_2$, (3) 80*d*.

Aldinger, R. Sulfur in enamels, (3) 59*h*. White ground enamel, (10) 263*f*.

Aleinikov, F. K. See Parfenov, V. A.; Vaitkus, J.; Zitkeviciute, I.

Aleinikov, F. K., and Parfenov, V. A. Effect of catalysts on the crystallization process of silicate glasses (I) platinum catalyst in the Li$_2$O–MgO–SiO$_2$ system, (7) 179*g*.

Aleinikov, F. K., and Paulavicius, R. Effect of heat treatment on some physical-mechanical properties and structure of silicate glasses (III) structure, (7) 179*i*. Stresses in the glass surface, (7) 181*j*.

Aleinikov, F. K., Paulavicius, R., and Parfenov, V. A. Use of ultrathin glass sections for structure investigations by electron microscope, (7) 182*b*.

Aleinikov, F. K., Paulavicius, R., Parfenov, V. A., and Slizys, V. Effect of heat treatment on some physical-mechanical properties and structure of silicate glasses (I) mechanical properties, (7) 179*i*.

Aleixandre Ferrandis, V., and Fernandez Navarro, J. M. Clays for tile manufacture, (2) 35*g*. Effects of the substitution of lithium oxide for lead oxide in ceramic glazes (III), (2) 39*j*.

Aleixandre Ferrandis, V., and Gonzalez Pena, J. M. Forsterite from Spanish serpentines (II) effect of mineralizers on reaction speed, (8) 225*b*.

Aleksandrov, L. N., and Shchelkonogov, V. Ya. Diffusion of carbon into tungsten and molybdenum at low carbon concentrations, (10) 284*d*.

Aleksandrova, V. A. See Kossovskaya, A. G.

Alekseev, V. I., and Shvartsman, L. A. Free energy of formation of certain carbides of vanadium and chromium, (11) 317*b*.

Alekseeva, Z. D. Phase diagram of the system Rb$_2$SiO$_3$–SiO$_2$, (10) 289*j*.

Aleksejunas, B. See Sirvaitis, A.

Alekseyeva, H. A. See Kreimer, G. S.

Alexander, B. T. See Pedigo, C. L.

Alexander, C. A., Ward, J. J., Ogden, J. S., and Cunningham, G. W. Thermodynamics for compatibility studies of metal-clad uranium carbide, B (6) 171*h*.

Alexander, D. E., and Foti, A. Alumina porcelain insulators for electrical apparatus, P (4) 103*a*.

Alexander, E. G., and Runyan, W. R. Factors affecting silicon growth on amorphous SiO$_2$ surfaces, (11) 316*h*.

Alexander, G. B., Iler, R. K., and Meadows, G. W. Cemented carbide bodies containing a dispersed oxide in the matrix metal and a process of making, P (7) 177*g*.

Alexander, G. B., West, S. F., and Yates, P. C. Powder metal compositions containing dispersed refractory oxide, P (2) 38*b*.

Alexander, H. M., and Ryan, J. D. Glass polishing compositions of rare earth nitrates, P (6) 150*b*.

Alexander, J. G., Wagner, P. W., and Bean, X. L. Molding composition and method, P (8) 218*a*.

Alexander, M. R. See Horton, R. C.

Alexander, R. E. See Yen, L. C.

Alfilie, L., Bocquet, J. P., Chaignon, R., Pramaggiore, A., and Valentin, G. Closure method and means for the ends of nuclear fuel rods having a very thin sheath, P (10) 273*c*.

Alford, H. E. Glass microsphere and fiber filled polyester resin composition, P (4) 96*j*. See Veatch, F.

Alford, H. E., and Veatch, F. Ceramic molding composition, articles made from same and process for making such articles, P (8) 217*k*.

Alford, W. J. See Campbell, W. B.

Alias Perez, L. J. See Martin-Vivaldi, J. L.

Aliev, A. I. See Chernyak, M. G.

Alikhanov, R. A. Study by neutron diffraction of solid oxygen, B (2) 55*f*.

Aling, P. See Cordfunke, E. H. P.

Aliprandi, G. See Savioli, F.

Allaire, R. P. Operation of the microwave oven, (8) 224*h*.

Allam, I. W. See MacHutchin, J. G.

Allegheny Ludlum Steel Corp. Ladles, P (2) 38*b*.

Allegretti, J. E., Gutsche, H., and McAleer, W. J. Monocrystalline elongate polyhedral semiconductor material, P (4) 105*i*.

Allegrini, A. P., and Cecil, T. A. Agglomeration of bauxite fines, P (3) 78*e*.

Alleman, C. E. Radiant drying of particulate material, P (8) 224*g*.

Aliemann, R. T., Moore, R. L., and Upson, U. L. Electrostatic apparatus for removal of dust particles from a gas stream, P (2) 43*e*.

Allen, A. C. Ceramic cutting tools, (8) 214*i*. Custom glass manufacturer offers variety of decoration and design, (8) 209*a*. Electrostatic spraying trims porcelain enamel overspray, (8) 207*i*. How to make thick film resistors and capacitors, (8) 220*a*. Luminous wall doubles porcelain enamel furnace efficiency, (3) 59*j*. Remarkable growth of tile plant due to design and innovation, (8) 214*h*. Tunnel kiln improves beryllia product, (8) 219*b*.

Allen, A. C., and Houck, R. L. First West Coast high tension insulators made by Gladding, (2) 39*a*.

Allen, A. W. Gettering means in a vacuum deposition device, P (5) 128*f*.

Allen, E. M., and Benner, F. E., Jr. Process for producing titanium oxide pigments, P (3) 79*a*.

Allen, J. W., Shyam, M., Chen, Y. S., and Pearson, G. L. Microwave oscillations in GaAs$_x$P$_{1-x}$ alloys, (1) 23*i*.

Allen, L. R., Das, D. K., and Stauffer, R. A. Process of making niobium stannide superconductors, P (2) 42*d*.

Allen, R. E. Cold diffusion bond between acoustic delay line and back electrode or acoustic absorber, P (7) 192*d*. Delay line bond, P (8) 220*e*.

Allen, W. C. Temperature dependence of properties of magnesium ferrite, (6) 170*b*.

Allen-Bradley Co. Capacitive component, P (7) 192*i*.

Allendorf, H. D. See Rosner, D. E.

Allerton, G. L., and Seifert, J. R. Method and [high frequency] apparatus for measuring semiconductor volume resistivity by transmission loss in a resonant cavity, P (2) 42*a*.

Allerton, G. L., Seifert, J. R., and Stark, L. T. Methods of determining semiconductor thickness and resistivity by loss in a transmission line, P (2) 42*g*.

Alley, J. K. See Johnson, R. C.

Allied Chemical Corp. Anhydrous dense soda ash, P (5) 133*a*. Apparatus for ultrahigh pressures, P (6) 161*f*. Beneficiation of chromium ore, P (2) 47*c*. Production of ultrafine alpha alumina and such alpha alumina, P (10) 283*b*.

Allio, R. J. See Biancheria, A.

Allis-Chalmers Mfg. Co. Coated graphite and method of coating, P (11) 302*b*. Head control for particle counter, P (3) 77*a*. High temperature material, P (8) 217*c*. Method of preparing cubic boron phosphide, P (8) 217*e*. Method of preparing hexaboron silicide (B$_6$Si), P (11) 302*e*. Refractory materials and method of making same, P (9) 241*f*.

Allman, O. H. Glass stirring apparatus, P (5) 122*i*.

Allman, O. H., Brumm, C. E., and Pither, L. F. Apparatus for homogenizing molten glass in a forehearth, P (3) 62*j*.

Allmanna Svenska Elektriska Aktiebolaget. Heating means, P (7) 158*d*.

Alloyd Electronics Corp. High temperature apparatus, P (1) 17*i*. Systems and processes for coating by evaporation, P (10) 279*g*.

Allsopp, P. J. Apparatus [electrolytic] for oxygen analysis of gases, P (7) 195*a*.

Almasfuzitoi Timfoldgyar. Filter presses for separating solids from liquids, P (11) 308*i*.

Almodovar, I. Method for the isolation of thorium from siliceous materials, (2) 44*c*.

Almodovar, I., Bielen, H. J., Frazer, B. C., and Kay, M. I. Neutron diffraction studies at Puerto Rico Nuclear Center, B (2) 55*i*.

Almond, J. C. See Bengtson, K. B.

Almqvist, E. See Ollerhead, R. W.

Alper, A. M., and McNally, R. N. Fused cast refractory and method of making, P (4) 100*b*, P (7) 188*b*, P (10) 273*h*. Refractory and furnace lining, P (7) 189*i*.

Alperin, H. A. See McGuire, T. R.

Alphen, P. M., van. See Wal, J. van der.

Altemose, V. O. Outgassing of glass caused by thermal neutrons and gamma radiation, (9) 234*h*.

Altmann, B. G. See Van Dreser, M. L.

Aluminum Co. of America. Agglomerating alumina, P (10) 282*i*. Fibrous refractory, P (11) 302*d*. Method of preparing alumina casting slips, P (9) 240*c*. Method of preparing casting slips from alumina hydrate, P (9) 240*d*. Refractory composition, P (11) 303*a*.

Aluminium Laboratories, Ltd. Method of making low soda alumina of small crystal size, P (10) 283*c*. Prebake anodes for electrolytic production of aluminum and coating therefor, P (5) 126*d*. Refractory compositions and methods of preparation, P (11) 303*c*.

Alvarez-Estrada, D. Lightweight refractories, (2) 36*c*.

Alvarez-Estrada, D., and Aza Pendas, S. de. Reaction between boric acid and sintered magnesia, (10) 272*h*.

Alvarez-Estrada, D., and Duran Botia, P. Spanish magnesites, (3) 78*b*.

Alvarez Rivas, J. L., and Agullo-Lopez, F. Plastic flow induced by partial X-ray irradiation of NaCl, (1) 24*h*.

Alvargonzalez, J. M. N. See Navarro Alvargonzalez, J. M.

Alves, V. F. See Ferreira Alves, V.

Alyamovskii, S. I. See Shveikin, G. P.

Amata, C. D. See Smith, A. W.

Amato, I., Colombo, R. L., and Frigerio, G. Fission gas retention ability of uranium dioxide pellets produced with different techniques, (3) 67*i*.

Amato, I., Colombo, R. L., and Protti, A. M. UO$_2$–ZrO$_2$–CaO ceramic nuclear fuels, (7) 188*a*.

Amberg, S. Heat-resistant and oxidation-proof material containing molybdenum disilicide, P (7) 195*j*.

Ambrozhii, M. N., and Dvornikova, L. M. Thermal decomposition of the hydroxides of samarium and quadrivalent cerium, (10) 291*b*.

American Air Filter Co., Inc. Fabric tube type dust collector and method of operating the same, P (2) 43*f*.

American Can Co. Zirconium silicate opacified ceramic glaze compositions, P (1) 13*e*.

American Cement Corp. Rotary kiln lining, P (7) 196*d*.

American Cyanamid Co. Impregnated porous photochromic glass, P (11) 298*j*. Method for cooling a gaseous suspension of titanium dioxide, P (2) 47*h*. Photochromic cement, P (2) 29*i*. Plasma production of titanium dioxide, P (11) 312*g*. Process of preparing gallium sulfide flakes and photoconductive device using same, P (10) 279*j*. Production of oxides by plasma process, P (11) 303*h*. Semiconducting materials, P (1) 15*h*. Therapeutic dental cement and a method for treating carious teeth, P (8) 219*f*.

American Felt Co. Polishing pads, P (6) 150*i*, P (9) 236*i*.

American Instrument Co., Inc. Radio frequency cell for gas chromatography, P (3) 77*d*.

American Olean Tile Co., Inc. Apparatus for stacking tiles in magazines, P (3) 71*j*. Blending apparatus comprising weighing-scale hoppers discharging tiles upon a conveyor, P (7) 190*h*. Blending apparatus and method, especially for tiles, P (4) 103*b*.

American Optical Co. Composite image display device formed of fiber ribbons, P (7) 182*d*. Doubly clad light-conducting fibers with the outer cladding being partially light absorbing, P (8) 212*e*. Electronic read-out device embodying glass coated metal wires, P (5) 128*d*. Energy conducting fibers formed of sapphire cladded with quartz, P (4) 96*g*. Fiber optical faceplates having different numerical aperture values in two different directions, P (11) 298*d*. Fiber optical image transfer devices and method of making the same, P (2) 33*h*. Fiber optical image transfer device having a multiplicity of light absorbing elements, P (7) 182*i*. Fiber type light transferring devices and method of making the same, P (4) 96*g*. Infrared transmitting fibers formed of arsenic and sulfur, P (1) 6*g*. Lens aligning and blocking apparatus, P (9) 236*e*. Method and apparatus for forming a lens surface, P (4) 97*g*. Method and apparatus for fusing fiber optical image transfer devices, P (1) 6*i*. Method of forming a fused energy-conducting device, P (3) 64*d*. Method of making cathode ray tube faceplates, P (8) 213*g*. Method for making fiber optical devices, P (2) 34*h*. Method of making a fiber-optical image transmitting device, P (7) 184*f*. Method of making glass clad energy-conducting fibers, P (8) 213*h*. Method of making honeycomb structure, P (11) 299*c*. Solder sealing glass members, P (3) 64*j*. See Textron, Inc.

American Radiator & Standard Sanitary Corp. Bathroom structure and fixture, P (11) 304*f*. Coated mold and method of coating same, P (10) 273*e*. Coatings, P (1) 13*f*. Molding methods and associated apparatus, P (6) 157*b*. Porous normally dry nonconductive mold, P (4) 103*e*. Thermistor, P (4) 106*e*.

American-Saint Gobain Corp. Apparatus for drawing glass sheet with control device, P (3) 62*f*. Glass pallet package, P (11) 298*h*. Window construction and glass block for use therein, P (3) 65*a*.

American Tansul Co. Vinyl amine modified clay process, P (10) 283*e*.

American Thermocatalytic Corp. Method of molding a combustion element of ceramic fibers on a porous support, P (11) 302*c*.

Ames, I. Method of fabricating high gain cryotrons, P (6) 159*g*.

Ames, I., and Simmons, R. G. Method and apparatus for [vapor] depositing films of refractory metal oxides and refractory metals, P (1) 14*h*.

Ames, L. L. See White, D.

Ametek, Inc. Rotary leaf filter, P (11) 309*b*.

Amey, M. E. F. See Haggett, R. O.

Amiran, R. Beginnings of pottery-making in the Near East, B (6) 172*f*.

Ammon, R. See Polhemus, J. H.

Amos, H. C. See Strickland, F. T.

Amosov, N. I. Development of terminology and classification of glass defects, (8) 209*d*.

Ampex Corp. Nickel-manganese-ferrous ferrite, P (5) 129*c*.

Amphenol Corp. Waveguide dissipating section using glass-iron composition absorber and method of making same, P (5) 130*d*.

Amrhein, E. M. Stress optical studies on opaque glass at wavelengths between 1 and 3μ, (8) 211*d*.

Amsted Industries, Inc. Method for preparing shell molding compositions, P (9) 240*f*.
Anaconda Co. Automatic burner control system for rotary kilns, P (5) 132*f*.
Anaconda Wire & Cable Co. Electrical insulating glass composition and apparatus encapsulated therewith, P (3) 73*b*. Method of making electromagnetic structures for high temperature service, P (11) 296*b*.
Ananich, N. I., and Botvinkin, O. K. Orientation effect and form birefringence in sodium borosilicate glasses, (4) 94*c*.
Anazawa, S. See Hayashi, T.
Anbo, E. X-ray study of behavior of sesquioxides deposited in chromite grains, (5) 142*b*.
Anda, L. A. A. de. See Arroyo de Anda, L. A.
Anderberg, B. I., and Claesson, S. H. Apparatus for making pipe insulating shells from mineral wool, P (8) 211*f*.
Andermann, G. Semitheoretical approach to interelement correction factors in secondary X-ray emission analysis, (3) 76*b*.
Anders, H. Molds for the production of pressed tile, (11) 308*h*.
Andersen, J. C. See Rose, C. G.; Taylor, K. M.
Andersen, W. Windbox cooler for a bottle machine split mold, P (5) 124*d*.
Anderson, D. E. See Nelson, O. L.
Anderson, E. E. See Zumwalt, L. R.
Anderson, I. Polyurethane for clay pipe joints, (4) 98*j*.
Anderson, J. C. See Dey, S. K.
Anderson, J. C., Dey, S. K., and Halpern, V. Magnetic susceptibilities of $LiFeO_2$, (5) 138*f*.
Anderson, K. A. Rotary leaf filter, P (11) 309*b*.
Anderson, L. M. Head control for particle counter, P (3) 77*a*.
Anderson, N. G. System for separating particulate substances by reorienting gradients, P (6) 161*g*.
Anderson, O. L. See Schreiber, E.; Soga, N.; White, G. K.
Anderson, O. L., and Andreatch, P., Jr. Pressure derivatives of elastic constants of single-crystal MgO at 23° and −195.8°C, (9) 253*i*.
Anderson, O. L., and Glynn, P. Measurement of compressibility in polycrystalline MgO using the reflectivity method, (9) 251*i*.
Anderson, R. C. See Simmers, C. D.
Anderson, R. E. Method of forming a *pn* junction, P (9) 243*j*.
Anderson, R. L. Semiconductor heterojunction device, P (5) 130*b*.
Anderson, W. L., and Rosen, G. Refractory dust method, (5) 140*j*.
Anderson, W. W. Nd ion bombarded CdS, (10) 288*g*.
Anderson, Y. R. Preparation of clays and shales—theory and practice, (6) 164*h*.
Andersson, S. Crystal structure of $NaNb_{11}O_{30}$ and the geometrical principles of the homologous series $NaM_{3n+1}O_{8n+1}$, (2) 49*a*. Hydrothermally grown crystals of silver vanadium oxide bronzes, (1) 22*f*.
Ando, J., Matsuno, S., and Watanabe, T. Constitution and citric solubility of phosphate rocks, (9) 247*c*.
Ando, K. See Steele, M. C.
Ando, T. See Funasaka, W.
Andreatch, P., Jr. See Anderson, O. L.; Thurston, R. N.
Andreev, S. I. See Afanas'ev, A. N.
Andres, R. J., and Heller, P. V. N. Method of making a ceramic supported semiconductor device, P (8) 221*j*.
Andrievskii, A. I. See Sandulova, A. V.
Andrusieczko, A. Problems of electric melting and boosting of glass, (4) 94*j*.
Andryukhina, T. D., and Nikolaev, N. A. Production and control of hardened glass parts for line suspension insulators, (7) 181*d*.
Andryushchenko, Yu. I. See Bergman, A. G.
Anfinogenov, A. I., Belyaeva, G. I., Smirnov, M. V., and Ilyushchenko, N. G. Structure and phase composition of beryllium plating on copper obtained by electrolysis of molten salts, B (1) 26*a*.
Anfinogenov, A. I., Smirnov, M. V., and Ilyushchenko, N. G. Electrolytic plating of beryllium onto copper from fused salts, B (1) 26*a*.
Angeleri, F. B., and Manzo, J. Slips for clay sanitary ware, (2) 39*i*.
Angeleri, F. B., Souza Santos, P. de, Paiva Netto, J. E., Nascimento, A. C., and Souza Santos, H. L. de. Physicochemical properties of kaolins and clays used in the Sao Paulo ceramic industry (IV) rose kaolin of Fazenda Floresta; (V) refractory clays from Suzano, (11) 312*g*.
Angelov, B. See Zagorcheva, E.
Angress, J. F., and Smith, S. D. Observation of defect-activated one-phonon infrared absorption in diamond coat, (3) 84*e*.
Annable, P. G., and Dasher, W. G. Block stacking apparatus, P (9) 237*h*. Block stacking method, P (9) 237*f*. Method of assembling interfitting block arrays, P (8) 214*e*.
Annamamedov, R. See Skudnova, E. V.
Anosov, V. Ya. See Dubrovskii, S. M.
Anscherlik, A. Automatic analyzing device and method, P (9) 246*c*.
Anselin, F., Dean G., Lovenselli, R., and Pascard, R. The system U–Pu–(C,N,O) as applied to sintered carbides, carbonitrides, and oxycarbides, B (6) 171*g*.
Antaki, E. E. Effect of alkali content on expansion coefficient of porcelain, (10) 275*h*.
Antelme, G. See Deiss, W. J.
Anthony, A. M. Electrical conductivity measurements of some oxides for magnetohydrodynamic systems, B (6) 173*d*.
Antill, J. E. See Peakall, K. A.
Antill, J. E., and Peakall, K. A. Electrochemical aspects of the hydrolysis of UC-10%Fe, (10) 285*f*.
Antonova, L. I. See Yarembash, E. I.
Antonova, V. F. See Kuz'mina, I. P.
Antonowicz, K. Interaction of strongly absorbed oxygen with free spin centers in carbon, (4) 111*j*.
Anzai, S. See Kunitomi, N.
Ao, T., Oyama, T., and Ito, T. Corrosion of open-hearth furnace and pouring-pit refractories and nonmetallic inclusions in steel, (10) 271*e*.
Aoki, I. Tetragonal distortion of the oxide spinels containing cobalt and manganese, (10) 291*a*.
Aoki, Y., Emoto, M., and Tanaka, T. Treatment of phosphors, P (11) 308*c*.
Apininskaya, L. M., and Radomysel'skii, I. D. Corrosion of cermet construction materials and method of applying protective and decorative electroplated and chemical coatings, (1) 8*a*.
Apker, L. Solid-state electron source, P (2) 42*j*.
Appen, A. A. Method for calculating the properties of glass, (10) 265*j*.
Apple, J. M., and Coombs, J. A. Method of feeding to and melting in a glass furnace, P (6) 150*a*.
Apple, J. M., and Mooney, C. F. Glass furnace fining means, P (6) 149*j*.
Apple, J. M., and Zak, T. J. Glass containing pot furnace, P (7) 183*c*. Regulated flow glass melting furnace, P (6) 151*b*.
Appleman, D. E., and Clark, J. R. Crystal structure of reedmergerite, a boron albite, and its relation to feldspar crystal chemistry, (11) 314*g*.
Arabadzhan, A. S. See Bergman, A. G.
Arabadzhan, A. S., and Bergman, A. G. Fusibility diagram of the ternary system of the bromides of lithium, sodium, and potassium, (9) 250*e*.
Arabei, B. G., Salibekov, S. E., and Levinskii, Yu. V. Ignitability of certain powder materials, (3) 67*e*.
Arabei, B. G., Shtrom, E. N., and Lapitskii, Yu. A. Characteristics of the manufacture of dense parts from, and the mechanical properties of, some hexaborides of the rare earth metals, (10) 270*f*.
Arafa, S. See Bishay, A. M.
Arai, T. Optical absorption of heat treated silicon, (10) 289*c*.
ARBED. See Acieries Reunies de Burbach-Eich-Dudelange, Soc. Anon.
Archdale Belt Co., Inc. Sandpaper cot, P (3) 57*g*.
Archer-Daniels-Midland Co. Mold and core binder for foundry use, P (1) 11*g*.
Arcos Corp. Electric arc welding flux and method, P (1) 3*g*.
Arcuri, F., and Grosskopf, K. Determination of combustion characteristics of an oil-fired tunnel kiln, (2) 46*b*.
Areskoug, C. O. Method of mass producing resistors, P (3) 73*f*.
Argay, G. See Naray-Szabo, I.
Argon, A. S. Deformation and fracture of solids, B (9) 259*e*.
Argueso, L. M., Jr., and Treacy, C. S. Composition for preparing thin-walled cored objects preparatory to performing machining operations thereon, P (10) 273*g*.
Argueso, M., & Co., Inc. Composition for preparing thin-walled cored objects preparatory to performing machining operations thereon, P (10) 273*g*.
Argyle, J. F., and Hummel, F. A. System PbO–BaO–MgO–SiO_2 (I) phase studies in subsidiary ternary systems; (II) dielectric studies, (8) 211*a*.
Argyle, P. See Lagally, P.
Arias, A. Mechanism by which metal additions improve the thermal shock resistance of zirconia, (7) 187*b*. Thermal shock resistance of zirconia with 15% (mole) titanium, (7) 187*i*.
Arifi, M. R. See Ashraf, M.
Ariga, K. See Tomita, Y.
Arimori, T. See Ihara, M.
Ariya, S. M. See Bogdanova, N. I.; Grossmann, G.; Vasil'ev, Ya. V.
Arizumi, T., Umeno, M., and Iwai, S. Doppler effects of the drifting plasma in semiconductors, (6) 157*h*.
Arkless, K. See Evans, A. W.
Arkless, K., and Herriman, J. D. Process for producing silica by oxidizing silicon tetrahalides, P (9) 247*h*.
Armant, D. L. Frit compositions for vitreous enamels, P (2) 30*f*.
Armbrust, B. F., Jr., Carithers, V. G., Hrishikesan, K. G., and Drown, H. L. Alumina hydrate and its method of preparation, P (10) 273*h*.
Armco Steel Corp. Elimination of enamel fishscaling in iron and steel sheets, P (11) 295*h*.
Armington, A. F. See Mitchell, R. F.
Armitage, C. H. See Revolinsky, E.
Armitage Ware, Ltd. Flushing cistern and water-closet suite of the double trap type, P (5) 127*g*.
Armrock Products, Inc. Kiln for rapid firing single layers of ceramic articles, P (11) 311*g*.
Armstrong, L. D. Method of making a tunnel diode assembly, P (6) 160*a*.
Armstrong, L. D., and Buckley, E. G. Ohmic contact to III–V semiconductive compound bodies, P (2) 42*a*.
Armstrong Cork Co. Mineral wool quality test, P (3) 77*c*.
Arnheim, W. M., Kwei, T. K., and Kumins, C. A. Effect of water vapor on glass-resin interface, (2) 31*h*.
Arni, H. T. See Blaine, R. L.
Arnold, S. R., and Nelson, J. T. Method of fabricating semiconductor [planar transistor] devices, P (5) 128*j*.
Arnold, V. E., and Holmes, S. D. Humidity resistance tester, P (10) 281*g*.
Arnott, R. J. Particle sizes of clay minerals by small-angle X-ray scattering, (6) 162*i*. See Rogers, D. B.
Aro Corp. Air atomizer for airless spray gun, P (1) 16*e*.
Aronson, H., and Schaeffler, L. How to make your own glazes (III) recipe for a basic glaze, (8) 206*b*.
Aronson, S. See Auskern, A. B.
Aronson, S., Cisney, E., and Auskern, A. B. Thermal expansion of nonstoichiometric zirconium carbides, (9) 257*h*.
Arrandale, R. S. Furnace design and glass melting (VI) port and checker details, (11) 296*e*.
Arroyo de Anda, L. A. Pre-Columbian art in the new National Museum of Anthropology in Mexico City, (3) 58*a*.
Artama, A. Apparatus for making laminated glass panes, P (7) 182*h*.
Artamonova, M. V. See Kitaigorodskii, I. I.
Artamonova, N. V., and Ignatova, V. A. Effect of heat treatment of silica gel on the properties of high-silica foam materials, (6) 147*b*.
Artelt, P., and Bueschenfeld, H. Evaluation of ceramic recuperator tubes, (3) 67*e*. Measuring the workability of tar-bonded blast-furnace taphole materials, (9) 238*b*.
Arthur D. Little, Inc. Silicon carbide recovery, P (9) 229*h*.
Arthur, E. P. See Leonard, J. E.
Arthur, E. P., and Nolan, R. W. Ion sensitive glass, P (5) 123*e*.
Arthur, G. Compatibility of some refractory materials with cesium vapor, B (6) 173*c*. Manufacture of cermets with metal members bonded thereto, P (5) 126*b*.
Arthur G. McKee & Co. Hammer mill, P (2) 47*f*.
Arzumanov, M. A. See Zegzhda, D. P.
Asada, C. Observation of slag melting conditions by the hot-stage microscope, (9) 238*e*.
Asada, C., and Onishi, M. Proceedings of the Pouring Pit Refractory Subcommittee Meeting (III) correlation of results of erosion tests on brick with the submitted slag and the results of actual use of the brick, (4) 99*h*.
Asada, E. Suzuki, Y.
Asaki, S. See Watanabe, H.
Asanabe, S. Semiconducting properties of SnSe and GeSe, (4) 104*e*.
Asano, T., Masuda, S., and Ito, T. Vertical kiln and a method for preparation of calcined products, P (9) 231*e*.
Ashbee, K. H. G. See Smallman, R. E.
Asher, R. R. Volcanic construction materials in Idaho, (7) 196*f*.
Ashraf, M., Qureshi, M. H., and Ariff, M. R. Production of grog fireclay bricks, (4) 99*f*.
Askew, W. S., and Beckmann, R. B. Velocity profiles and transfer operations at the wall of an agitated vessel, (9) 244*i*.
Aslam, M. See Hasan, S. T.
Aslanov, L. A., and Novoselova, A. V. Synthesis of barium zirconyl carbonate and production of barium zirconate, (10) 291*d*.
Aslanov, L. A., Ukrainskii, Yu. M., and Simanov, Yu. P. Diselenide and triselenide of tantalum, (11) 315*f*.
Aslanov, S. M. See Zakharchenko, M. A.
Aslanova, M. S., and Khazanov, V. E. High strength of glass and quartz fibers at −196° (in liquid nitrogen), (8) 209*b*.
Associated Electrical Industries, Ltd. Bonding of metal plated to semiconductor materials, P (2) 41*a*. Four-region switching transistor comprising a controlled current path in the emitter, P (10) 278*b*. Manufacture of silicon controlled rectifiers, P (6) 159*e*. Method of preparing indirectly heated cathodes, P (2) 42*d*. Method of using protective coating over layer of lithium being diffused into substrate, P (1) 14*j*.
Associated Lead Mfrs., Ltd. Method of preparing zirconium silicate ceramic stains, P (9) 242*c*.
Associated Minerals Consolidated, Ltd. Process for extraction of thoria and ceria from rare earth ores, P (8) 225*f*.
Associated Portland Cement Manufacturers, Ltd. Mechanical air classifier, P (5) 131*c*.
Astbury, N. F., and Moore, F. Torsional hysteresis in plastic clay and its interpretation, (1) 13*b*.
Aster, H., Forman, I., and Hajman, J. Analog computers solve the calculation of the composition of cement raw mixes, (8) 206*e*.
Asti, G., Colombo, M., Giudici, M., and Levialdi, A. Magnetization dynamics in $BaO \cdot 6Fe_2O_3$ single crystals using pulsed magnetic fields, (4) 112*j*.
Atalla, M. M. Semiconductor devices having dielectric coatings, P (2) 42*h*.
Atkins, A. G., Brookes, C. A., and Murray, M. J. Recent studies of the mechanical properties of solids at high temperatures, (11) 301*a*.
Atkins, J. H. Measurement of surface areas of solids, P (1) 17*d*.
Atkinson, B. D. See Durrant, G. G.
Atlantic Research Corp. Process for producing finely divided rounded particles, P (3) 75*b*.
Atlas Copco AB. Electrostatic spray coating apparatus, P (1) 3*h*.
Ato, Y., Huzimura, R., and Oishi, M. Radioactive self-luminous compounds (IV) comparison of relative luminescence efficiencies of radioluminescence and photoluminescence of various phosphors, (11) 304*j*.

Atoda, T., Kobayashi, M., Sasa, Y., Takahashi, Y., and Higashi, I. Preparation and chemical properties of uranium carbides, B (6) 172*b*.

Atomic Energy of Canada, Ltd. Plutonium enriched uranium fuel for nuclear reactors, P (8) 218*b*. Preparation of dense uranium oxide, P (9) 241*b*.

Aton G.m.b.H. Process for the continuous production of thin-walled ceramic tiles, P (10) 276*c*.

Atterberg, I. Lisa Larson—a Swedish architectural ceramist, (3) 58*a*.

Atteridge, T. L. See Shulver, W.

Atwell, E. C. Process for dulling glass fibers with oxalic acid, P (9) 237*b*.

Auchter, G. See Schwiete, H. E.

Audet, H. J. See Harris, J. M.

Audzijonis, A., Bataranas, J., Karpus, A., and Kudzmauskas, S. Optical properties and zone structure of single Sb_2S_3 crystals, (9) 252*e*.

Auerbach, A. Apparatus for the rapid determination of the thermal conductivity of refractory materials, (6) 161*i*. Testing method for refractories used in pusher-type furnaces, (9) 239*i*.

Augsburger, C. Apparatus for filling structural clay tile, P (4) 98*g*.

Aukrust, E., Forland, T., and Hagemark, K. Equilibrium measurements and interpretation of nonstoichiometry in $UO_{2\pm x}$, B (6) 175*f*.

Auleytner, J. See Litwin, J.

Aulock, W. H. von (editor). Handbook of Microwave Ferrite Materials, B (4) 115*c*.

Auskern, A. B. See Aronson, S.

Auskern, A. B., Aronson, S., Sadofsky, J., and Salzano, F. J. Electrical properties of thorium carbide, (11) 316*b*.

Austerman, S. B. Degradation of growth perfection in BeO crystals by silica, (1) 20*c*.

Austerman, S. B., Newkirk, J. B., and Smith, D. K. Study of defect structures in BeO single crystals by X-ray diffraction topography, (5) 141*a*.

Austerman, S. B., and Wagner, J. W. Cation diffusion in single-crystal and polycrystalline BeO, (3) 79*j*.

Autenrieth, H. Electrostatic separation of minerals, P (2) 47*e*.

Automatic Control Devices, Inc. Magnetic and optical differential thickness measuring instrument, P (9) 246*d*.

Automation Industries, Inc. Electromechanical transducers and the fabrication thereof, P (6) 159*e*.

Auzins, P. See Kirklin, P. W.

Avco Corp. Method of making a ceramic platen for a brazing fixture, P (10) 274*h*. Process of making an impregnated ceramic, P (7) 189*f*.

Avdasev, V. I., Lemeshonok, V. D., and Kovzel, N. I. Broaching of porous cermets, (3) 65*j*.

Aven, M. Efficient visible injection electroluminescence from *pn* junctions in $ZnSe_xTe_{1-x}$, (10) 285*i*.

Averbach, B. L. Solid solution formation, B (7) 204*d*.

Aver'yanova, L. N. See Belyaev, I. N.

Aves, W. L., Jr. Heat-resistant article, P (6) 146*f*.

Avgustinik, A. I. Interactions of oxides and carbides with metals, (7) 178*j*.

Avgustinik, A. I., Vigdergauz, V. Sh., Gropyanov, V. M., and Drozdetskaya, G. V. Effect of particle dispersion on the densification of parts from columbium carbide powder at different sintering temperatures, (1) 8*d*.

Avizonis, P. V., and Farrington, T. Internal self-damage of ruby and Nd-glass lasers, (10) 287*d*.

Axler, M. F. Residual argon partial pressure changes due to an intermittently operated Bayard-Alpert ionization gage in ultrahigh vacuum, (10) 281*b*.

Axmann, M. Combustion chamber pressure regulation by electric or hydraulic transmission, (7) 179*i*.

Ayer, J. E., and Soppet, F. E. Vibratory compaction (II) compaction of angular shapes, (5) 125*f*.

Ayer-McCarel Clay Co., Inc. Method of preparing tile surfaces, P (4) 98*h*.

Ayers, P. See Ball, D.

Aylett, B. J. Silicon-nitrogen polymers, B (11) 320*f*.

Aylward, G. H., and Findlay, T. J. V. (editors). Chemical Data Book, B (9) 258*b*.

Aza Pendas, S. de. See Álvarez-Estrada, D.

Azam, F. See Hashmi, M. H.

Azarov, K. P. See Budnikov, P. P.

Azarov, K. P., and Gorbatenko, V. E. Effect of composition of iron-containing enamels on the whiteness of the coating, (2) 30*d*.

Azegami, K. Mirror having a magnifying portion, P (10) 269*e*.

Azelitskaya, R. D. See Budnikov, P. P.

Azzarello, C. A. Making air dryers work efficiently, (1) 17*i*.

Azzi, V. D. See Tsai, S. W.

Baab, K. A. See Osterholtz, C. E.

Baak, T. Redox reactions in glass, (4) 95*c*.

Baas, G., and La Grouw, C. M. Devitrified glass-to-metal compression seal, P (3) 63*d*.

Babachev, G. N. Methods of estimating the activity of mineral admixtures for cement, (4) 90*g*.

Babachev, G. N., Markova, M., and Todorova, R. Determining the cement content of concrete and mortar, (10) 262*g*.

Babad-Zakhryapin, A. A. See Izvekov, V. I.

Babatschew, G. N. See Babachev, G. N.

Babcan, J. Thermal decomposition of kaolinite from the standpoint of solid phase reactions, (8) 227*i*.

Babcock, C. L. High expansion glass and seals, P (6) 150*c*.

Babcock, H. N. See Small, A. B.

Babcock, S. W. See Hotine, W.

Babcock & Wilcox Co. Graphite-plate heat exchange apparatus, P (4) 100*d*. Tapping nozzle for molten refractories, P (2) 38*i*.

Babonas, G., Girciene, V., Zakarka, A., Kavaliauskas, J., and Sileika, A. Effect of pressure and temperature on the absorption edge of CdTe, (3) 81*f*.

Babonas, G., Kavaliauskas, J., and Sileika, A. Intrinsic absorption edge of CdTe under hydrostatic pressure up to 6600 kg/cm², (9) 251*f*.

Babushkin, V. I., and Mchedlov-Petrosyan, O. P. Corrosion of concrete and reinforced concrete and its prevention, (7) 178*a*.

Bacchella, G. L., and Pinot, M. Study on magnetic structure of $FeCr_2O_4$, B (2) 55*c*.

Bach, R. O. Production and recovery of beryllium chloride, P (7) 196*j*.

Bachler, C. L. See Shepherd, J. F.

Bachvarov, S. See Levcheva, K.

Bachvarov, S., and Kukusheva, M. Improving the quality of glazes for earthenware tile, (6) 156*e*.

Back, L. See Bergstein, F. D.

Backlin-Landman, H., and Shapiro, E. Story of Porcelain, B (1) 26*d*.

Bacmann, M., and Bertaut, E. F. Structure of UCr_2O_4, (7) 203*a*.

Bacon, F. R. Method of increasing the chemical resistance of glass surfaces, P (2) 34*f*.

Badger, A. E. Method of controlling temperatures in sheet glass with heat absorptive material, P (9) 236*j*. See O'Connell, T. B.

Badger, A. E., Lehr, G. J., and Woods, J. A. Treatment of glass batch materials, P (3) 65*b*.

Badische Anilin- & Soda-Fabrik Akt.-Ges. Apparatus for continuous drying of powdery or granular materials in a high-frequency field, P (3) 77*i*. Process for making heat insulating refractory slabs, P (8) 218*d*.

Badoz, J. See Briat, B.

Baer, C. A., Clough, P. J., and Steeves, R. W. Crucible coated with reaction product of aluminum and boron nitride coating, P (7) 188*j*.

Baernighausen, H., Knausenberger, M., and Brauer, G. Crystal structure of $TiP_{0.43}$, (3) 80*g*.

Baerns, M. G. See Gabor, J. D.

Bagdasarov, Kh. S. See Belyaev, L. M.

Baglietto, M. Relation between technology and ceramic art, (10) 261*j*.

Bagwell, W. W. Apparatus for the manufacture of asbestos-cement tubes, P (7) 188*h*.

Bahl, O. P. See Patel, A. R.

Baier, E., Doerr, F. H., and Lotz, K. E. Quantitative determination of crystalline substances from the system ZrO_2–Al_2O_3–SiO_2, (2) 32*g*.

Baier, E., and Hausmann, P. Research on glass surfaces with radioactive phosphorus, (2) 32*h*.

Bailey, B. L. See Juel, L. H.

Bailey, B. L., Karagoz, B. Y., and Peller, P. Fabrication of carbon and graphite bodies, P (11) 302*c*.

Bailey, F. M. Electrothermal fragmentation [of rock], P (1) 18*e*.

Bailey, J. S., and Schmalz, H. H. Electron discharge devices, P (6) 159*e*.

Bailey, R. T. China clay for ceramic uses, (6) 164*b*, (11) 312*b*.

Baird-Atomic, Inc. High temperature furnace, P (5) 132*e*.

Bairiat, H., Lafontaine, I., and Pizziolo, A. Description of the Belgo nucleaire–C.E.N. work on plutonium-bearing carbides, B (6) 172*b*.

Bakalar, D. Crystal diode, P (1) 14*h*.

Baker, C. L., and Holloway, P. W. Spherical particles of anhydrous sodium metasilicate and method of manufacture thereof, P (1) 13*d*.

Baker, G. S. See Vanfleet, H. B.

Baker, H. W. Methods of and apparatus for toughening curved sheets of glass, P (2) 34*b*.

Baker, J. H. See Wahlberg, J. S.

Baker, J. J. See Cook, C. M.

Baker, J. M., Chadwick, J. R., Garton, G., and Hurrell, J. P. EPR and endor of Tb^{4+} in thoria, (1) 21*g*.

Bakker, M. A. M., and Van Vulpen, A. Semiconductor devices and methods for their manufacture, P (3) 74*g*.

Bakker, W. T., and Bartok, D. Particle size measurement of alumina by centrifuging, (7) 195*d*.

Balb, A. See Abrecht, H.

Baldauf, G. A., and Elkind, M. J. Barium oxide moisture getter preparation, P (2) 41*a*.

Balduin, H. Water absorption of granular materials, (9) 246*a*.

Baldwin, D. H., Co. Semiconductive films and method of producing them, P (4) 106*f*.

Balfet, H. Ethnographical observations in North Africa and archeological interpretation, B (6) 172*e*.

Balinkin, I. See Illing, A. M.

Ball, C. J. Estimation of the dihedral angle between spherical grains from measurements in a plane section, (7) 199*a*.

Ball, D., and Ayers, P. Methods of breaking up sintered compacted metal bodies, P (9) 240*h*.

Ball, D. F. Saponite and lizardite veins on the Isle of Rum, (5) 133*h*.

Ball, F. C. Slab project for children, (8) 206*c*.

Ball, M., Leask, M. J. M., Wolf, W. P., and Wyatt, A. F. G. Thermal properties of dysprosium aluminum garnet near the Neel temperature, (2) 53*c*.

Ball, R., and Putner, T. Coating cold mirrors on a high-production basis, (5) 134*i*.

Ball Brothers Co., Inc. Flaw detection method and apparatus, P (7) 182*i*. Inspection apparatus, P (7) 183*a*. Method and apparatus for detecting surface unevenness, P (7) 183*g*. Mold patch support, P (1) 7*a*. Treatment of newly formed glass articles, P (7) 184*h*.

Balla, B., Csetenyi, J., and Nagy, K. Studies of glass batch mixing, (3) 62*h*.

Ballard, J. W. Ceramic diode pressure transducer and system, P (6) 158*j*.

Ballastracci, R. See Broquetas Colominas, C.

Ballman, A. A. See Laudise, R. A.; Wood, D. L.

Ballman, A. A., Linares, R. C., and Van Uitert, L. G. Growth of beryl crystals, P (5) 128*f*.

Balmer, H., and Gasparac, R. J. Seal for gyratory crushers, P (11) 312*j*.

Balog, M. J. Automatic glass area measuring device, P (10) 267*d*.

Baltrusaitis, R., and Brazdziunas, P. Conductivity of cadmium oxide in the high-frequency electromagnetic field, (3) 80*f*.

Bambauer, H. U., Corlett, M., Eberhard, E., Gubser, R., Laves, F., Nissen, H. U., and Viswanathan, K. Variations in X-ray powder patterns of low structural state plagioclases, (6) 171*b*.

Banashek, E. I. See Sokolov, V. A.

Bandyopadhyay, T., and Saha, P. Observations on hydrothermal growth of quartz, (7) 201*a*.

Banerjee, B. See Sienko, M. J.

Banerjee, J. C., De, S. K., and Nandi, D. N. Pyrophyllite refractories, (4) 99*j*.

Bange, G. R., Jones, M. J., and Young, H. F. Apparatus and method for healing glass lined pipe, P (7) 179*a*.

Banks, E. See Robbins, M.

Banks, E., and Kostiner, E. Growth of crystals and magnetic properties of β-Mn_2O_3 solid solutions, (11) 317*f*.

Banus, M. D. See Hanneman, R. E.

Bapat, N. J. See Bhide, V. G.

Baraboshkin, A. N., and Sazhnov, V. K. Behavior of vanadium trioxide + carbon anodes during electrolysis of molten chlorides, B (1) 26*i*.

Barag, D. Note on a Mesopotamian bottle, (4) 90*b*.

Barantseva, I. G. See Neshpor, V. S.

Barch, H. W. See Malobicky, R. L.

Barch, H. W., Kelly, J. D., and Malobicky, R. L. Method and apparatus for supporting glass sheets, P (3) 63*j*.

Barclay, J. See Orlandini, K. A.

Bardin, P. C. Molding, finishing products made of fiber glass, (9) 234*d*.

Bargel, G., and Eggert, R. Bottles and the like, P (1) 6*e*.

Bariand, P., Chantret, F., Pouget, R., and Rimsky, A. New mineral—chervetite, lead pyrovanadate, $Pb_2V_2O_7$, (6) 169*d*.

Barinov, Yu. D. See Belyaev, G. I.

Barkemeyer, H. R., McAleer, W. J., and Pollak, P. I. Apparatus for the preparation of semiconductor material, P (4) 104*h*.

Barker, J. See Busby, T. S.

Barker, R. E., Jr. Approximate relation between elastic moduli and thermal expansivities, (2) 48*g*.

Barkman, E. F., and Barnes, H. C., Jr. Color finishing of aluminum, (1) 3*d*.

Barmore, W. L. See Vandervoort, R. R.

Barna, J. Preparation of a lean kaolin of Mad-Kiralyhegy and study of the slip, (2) 47*c*. See Nemecz, E.

Barna, J., and Marschalko, B. Rheological properties of aqueous bentonite dispersions (II), (6) 169*h*.

Barnard, W. M. See Wright, H. D.

Barnes, B. T. Cathodic glow gaseous discharge device, P (5) 128*a*.

Barnes, D. W. See Mezaki, R.

Barnes, H. C., Jr. See Barkman, E. F.

Barnes Engineering Co. Black coating for fragile infrared radiation detectors, P (10) 277*i*.

Barnett, J. D., and Hall, H. T. High pressure-high temperature X-ray diffraction apparatus, P (7) 195*c*.

Barnett, R. L., and McGuire, R. L. Statistical approach to analysis and design of ceramic structures, (7) 202*e*.

Barogenics, Inc. High pressure apparatus, P (5) 131*a*. Hydrostatic pressure device, P (3) 75*a*.

Barone, F. J. See Greener, E. H.

Barr, G. W. Bag house facility, P (10) 262*h*.

Barr, H. N., and Sundquist, L. A. Method of making hollow spherical UO_2 particles, P (11) 302*b*.

Barr, L. C., Quaas, J. F., Broderick, J. P., and Wishnie, F. T. Flame spraying torch, P (7) 179*c*.

Barr, R. A. Progress in refractories, (9) 239*a*.

Barr & Stroud, Ltd. Blooming of optical components with a complex aluminosilicate compound, P (10) 267*f*.

Barradell-Smith, R. Snapping of sheets of glass, P (10) 270*a*.

Barradell-Smith, R., and Silverwood, F. W. Apparatus for the manufacture of flat glass, P (3) 63*a*. Manufacture of flat glass, P (3) 63*e*.

Barrante, J. R. See Galasso, F.

Barrer, R. M. Mineral synthesis by the hydrothermal technique, (11) 318*b*.

Barrington, J. See Bergmann, O. R.

Barron, L. H., and Martin, D. C. Aspheric lens grinder, P (6) 149*c*.
Barrot, J. C. Process for separating liquids and solids and device therefor, P (8) 222*f*.
Barsauskas, K., Bendorius, R., Semenov, Ya. A., and Sileika, A. Effect of hydrostatic pressure on the lead sulfide transmission spectrum, (6) 167*a*.
Barsom, J. M. Effect of stress and strain on producing hackle in a glass plate, (2) 31*h*.
Barson, F., and Gow, J., III. *Pnpn* semiconductor translating device and method of construction, P (2) 42*b*.
Barsukova, N. F. See Zheleztsov, V. A.
Barsukova, N. F., and Zheleztsov, V. A. Method of determining the geometry of drawn-glass surfaces, (9) 234*a*.
Barta, R. Theory of solid phase reactions in the silicate industry, (7) 203*c*.
Bartels, B. E. See Burdick, G. A.
Bartenev, G. M. See Vitman, F. F.
Bartenev, G. M., and Chernyakov, R. G. Strength of fibers coated with an alkali-free aluminoborosilicate glass, (10) 266*j*.
Barth, B. P. See Daniels, R. S.
Bartha, P. Behavior of high alumina brick in a rotary cement kiln, (1) 2*b*.
Barthel, H. Effect of carbon in tar-impregnated burned magnesite brick on the wear of basic oxygen furnace linings, (11) 301*d*.
Bartholomew, G. L. See Sturges, D. G.
Bartlett, A. F. See Eyre, B. L.
Bartlett, R. W., McCamont, J. W., and Gage, P. R. Structure and chemistry of oxide films thermally grown on molybdenum silicides, (1) 25*f*.
Bartok, D. See Bakker, W. T.
Barton, G. W., Jr. See Jackson, D. D.
Bartow, W. T., and Head, B. L. Heat-treating method for modifying permeability and quality factor of nickel-zinc-cobalt ferrite, P (6) 159*i*.
Bartushka, M., and Batrakov, N. A. Properties of zinc oxide-zirconium dioxide sinters, (5) 140*e*.
Barzac, G. Comparative study of atomization and traditional processes for the preparation of wall-tile dust, (7) 190*f*.
Barzaghi, L., and Ferreira, W. Flow of refractory materials at high temperatures, (2) 36*g*.
Basic, Inc. Kiln gun projectile, P (5) 132*g*. Pitch-bonded refractory composition, P (5) 126*c*. Refractory block molding machine, P (6) 155*b*. Refractory bonded with pitch, P (1) 12*b*.
Baskin, M. L. See Pivovarov, L. Kh.
Baskin, M. L., Tret'yakov, V. I., and Chaporova, I. I. Diffusion of niobium in titanium carbide and in the equimolar composition solid solution TiC-NbC, (10) 284*f*.
Baskin, Y. Phase studies in the system UP–UO_2, (1) 24*f*. Properties of uranium monophosphide, (11) 319*b*.
Baskin, Y., and Shalek, P. D. Uranium monosulfide-uranium monophosphide solid solutions, P (10) 275*c*.
Bass, M. See Riley, L. W.
Bassett, W. A., and Takahashi, T. Silver iodide polymorphs, (9) 255*c*.
Bassi, A., Brutto, E., Perona, G., Screm, G., and Sesini, R. Sintering of urania and thoria, (6) 153*g*.
Bassi, G. See Bertaut, E. F.
Bast, C. H. See Veo, L. E.
Bast, J. de, and Gilard, P. Rheology of Glass Under Stress in the Transformation Range, B (9) 259*j*.
Bastiaanse, E. Apparatus for evacuating an electric filament lamp or discharge tube through a protruding exhaust tube and for sealing off the exhaust tube, P (5) 128*f*.
Basty, W. du, Jacquin, C., and Simandoux, P. Study of some interfacial properties of montmorillonite, (8) 227*g*.
Batarunas, J. See Audzijonis, A.
Batchelor, E. R. See Garrett, K. H.
Bates, J. L. Melting points of hypostoichiometric uranium dioxide, (8) 226*i*. Visible and infrared absorption spectra of uranium dioxide, (2) 53*i*.
Bateson, S., Hunt, J. W., Dalby, D. A., and Sinha, N. K. Stress measurements in tempered glass plates by scattered light method with a laser source, (3) 62*g*.
Batey, W., Bolton, K., Donaldson, D. M., and Yates, G. Compatibility of (U, Pu) carbides with cladding materials, B (6) 172*a*.
Batigne, J., and Didier, R. Equipment for burning refractory products, P (4) 108*g*.
Batrakov, N. A. See Bartushka, M.
Batteau, D. W. See Lees, S.
Battelle Development Corp. Method of explosively compacting powders to form a dense body, P (3) 75*a*.
Battelle Memorial Institute. Resistance devices, P (11) 307*b*.
Battey, M. H., and Tomkieff, S. I. (editors). Aspects of Theoretical Mineralogy in the U.S.S.R., B (8) 228*e*.
Battista, O. A. Colloidal macromolecular phenomena, (5) 120*d*.
Bauer, D., Schnering, H. G., and Schaefer, H. Chemistry of the elements niobium and tantalum (XLV) Ta_6I_{14}—preparation, properties, and structure, (11) 314*i*.
Bauer, E. See Green, A. K.
Bauer, G. T. See Gergely, G.
Bauer, K. E. Gas fired infrared heaters, P (4) 108*e*. See Patrick, M. W.
Bauer, P. A. Solid delay line, P (8) 222*a*.
Bauer, P. J. A. See Etzel, K. W. F.
Bauer, R. See Hartman, T. E.
Bauer, W., Singer, E., and Koenig, A. Titanium nitride ceramics, (9) 239*c*.
Bauer, W. C. See Conroy, A. R.
Baum, M. Konopicky, K.
Bauman, H. D. See Casciani, F.
Bauman, H. D., and Williams, R. S. Manufacture of calcium carbonate, P (10) 283*b*.
Baumann, J., and Lax, L. Rapid complexometric determination of zirconia and the oxides of aluminum, iron, and titanium (works analysis), (6) 163*b*.
Baumer, H. Oil firing in glassworks, (10) 265*e*.
Baur, J. A., and Bricker, C. E. Hexamminecobalt (III) tricarbonatocobaltate (III)—a new analytical titrant, (2) 44*i*.
Bausch & Lomb, Inc. Apparatus for forming optical elements, P (3) 62*i*. Apparatus for processing a vitreous composition, P (5) 122*h*. Glass containing pot furnace, P (7) 183*c*. Glass furnace fining means, P (6) 149*j*. Glass press mold structure with temperature regulation, P (6) 150*c*. Lens blocking method and device, P (3) 63*b*. Method of feeding to and melting in a glass furnace, P (6) 150*a*. Method of forming apertured optical disks, P (6) 150*a*. Method of lens grinding, P (5) 123*g*. Method of making lenses, P (7) 184*g*. Method of making multifocal lenses, P (7) 184*g*. Method of shearing glass, P (4) 97*g*. Process and apparatus for making homogeneous gas-free optical glass, P (6) 150*i*. Reflecting diffraction grating for minimizing anomalies, P (5) 132*c*. Regulated flow glass melting furnace, P (6) 151*b*.
Bauschmann, W., and Pascard, R. Method of manufacture of uranium dioxide having a high density, P (4) 101*f*.
Bayer, G. Alumina refractories and preparation, P (6) 154*g*. Inorganic metal oxides containing cobalt, antimony, and tantalum and method of preparing same, P (7) 193*e*. Isomorphic and morphotropic relations of oxides with TiO_3-type and related structures, (7) 200*f*. Vanadates $A_3B_2V_3O_{12}$ with garnet structure, (1) 25*j*.
Bayer, G., and Hoffmann, W. Primary crystallization of glasses in the system Na_2O–TiO_2–SiO_2 and its relation to immiscibility, (9) 234*a*.
Bayler, H. Ingenious handling ups concrete block production, (9) 230*j*.
Bazinet, W. P., Jr. See Woodcock, R. F.
Beale, J. R. A., and Beer, A. F. Method of manufacturing semiconductor devices, P (5) 129*g*.
Beall, G. H. Glass-ceramic bodies and method of making them, P (8) 212*g*.
Bean, C. H. Process of making a sintered homogeneous dispersion of nuclear fuel and burnable poison, P (10) 274*c*.
Bean, L. See Blaine, R. L.
Bean, Morris, & Co. See Morris Bean & Co.
Bean, X. L. See Alexander, J. G.
Beasley, G. A. See Rudd, M. O.
Beattie, J. R. Radiant type cooler in apparatus for producing glass in ribbon form, P (11) 299*f*.
Beattie, J. R., and Wolfe, K. J. B. Method of producing toughened glass, P (4) 97*e*.
Beatty, R. See Westman, A. E. R.
Beauzee, C. Method of manufacturing photoelectric semiconductor devices, P (9) 243*c*.
Beazley, K. M. Factors influencing dilatant behavior in china clay suspensions, (7) 190*g*.
Bebbington, P. J., Feagin, R. C., McConnell, L. W., and Thompson, C. W. Discoloration of mortar joints by manganese-colored brick, (4) 98*g*.
Becherer, H. K. Semiconductor device and method of fabricating the same, P (6) 160*e*.
Bechtold, M. F. High temperature-resistant materials of aluminum, nitrogen, boron, carbon, and silicon and preparation thereof, P (10) 273*j*, 274*a*.
Beck, P. W. See Brockman, F. G.
Beck, R. A. Method of forming a patterned electroconductive coating, P (6) 159*i*.
Becke, H. W. See Flatley, D. W.
Becker, A. See Nauroth, P.
Becker, H. Dissolution of silica schlieren in glass by diffusion and flow, (8) 209*d*.
Becker, R. M. Some generalized probability distributions with special reference to the mineral industries (II) sampling to λ amount of items per sample; (III) computer programs of distribution moments; (IV) experimental confirmation, (4) 108*j*.
Beckius, K., and Davidson, P. Use of basic linings for steel in melting in large induction furnaces in Sweden, (3) 69*f*.
Beckman Instruments, Inc. Encapsulated transducer, P (1) 6*i*. Ion sensitive glass, P (5) 123*e*. Method of making electrical resistance element, P (11) 306*d*. Method of making glass electrode, P (1) 7*b*.
Beckmann, R. B. See Askew, W. S.
Beech, D. G. See West, H. W. H.
Beer, A. F. See Beale, J. R. A.
Beerman, H. P. Thermoelectric cooling of infrared detectors, (2) 40*j*.
Beerntsen, D. J. See Revolinsky, E.
Beese, N. C. Improving efficiency of infrared radiation generation by alkali metal vapor lamps and prolonging their useful lives, P (9) 243*g*.
Behrens, H. See Schwamborn, P.
Behringer, A. J., and Corrsin, L. Photoconductive cadmium sulfide powder and method for the preparation thereof, P (5) 129*c*.
Behrndt, K. H. Angle-of-incidence and stress effects on rotating and stationary substrates, (10) 276*b*.
Beine, H. See Trier, W.
Beisler, J. F. See Pearce, M. L.
Beke, B. Cement grinding problems, (3) 58*d*. Principles of Comminution, B (4) 115*d*.
Bekkering, H. M., Stapel, C., and Wiegman, F. B. J. Apparatus for working glass tubing, P (4) 96*j*.
Belardi, R. J., and Moles, L. Thermocompression bonding chisel, P (1) 15*d*.
Belasco, M. See Ratcliff, G. J.
Belasco, M., and Ratcliff, G. J. Transistors and the fabrication thereof, P (9) 244*d*.
Belcher, G. W. Casting process using borax-silica slag, P (4) 100*g*. Process for casting metals into asbestos-containing mold coating, P (7) 189*f*.
Belevantsev, V. S. See Budnikov, P. P.
Belikov, A. M., Lisnyak, S. S., and Morozov, A. N. Chromium spinellids and the crystallochemical transformations which occur when they are calcined, (10) 284*a*.
Belitskii, M. E. See Kostetskii, B. I.
Belknap, D. J. Apparatus for making microminiature incandescent lamps, P (4) 96*h*.
Bell, J. A. E., and Winegard, W. C. Constitutional undercooling and the growth of eutectics, (3) 80*g*.
Bell, K. R., Staunton, J. J. J., Horn, A. J., Sinclair, J. H., and Bull, R. W. System for processing and analysis of liquid samples, P (6) 163*d*.
Bell, T. See Pugh, N.
Bell Telephone Laboratories, Inc. Barium oxide moisture getter preparation, P (2) 41*a*. Diffusion technique for making composite optical maser crystals, P (2) 41*d*. Electrodes to semiconductor wafers, P (6) 159*d*. Fabrication of semiconductor bodies, P (2) 41*a*. Ferrite compositions and method of manufacture, P (4) 104*f*. Ferromagnetic compound and devices including elements thereof, P (5) 128*e*. Gallium arsenide semiconductor diode and method, P (11) 306*g*. Growth of beryl crystals, P (5) 128*f*. [Hydrothermal] crystal growth container, P (11) 306*h*. Laser utilizing rare earth activated yttrium and lanthanum trifluoride active media, P (5) 128*h*. Method of fabricating semiconductor contacts, P (2) 41*j*. Method of fabricating semiconductor [planar transistor] devices, P (5) 128*j*. Method for the fabrication of tantalum film resistors, P (9) 243*i*. Method of forming metal carbide coating on carbon base, P (10) 274*g*. Method of making integrated semiconductor devices, P (5) 129*d*. Method of making low resistance contact to silicon semiconductor device, P (8) 221*a*. Multiple resistance semiconductor elements, P (6) 160*g*. Nb–Zr superconductor and process of making the same, P (8) 221*f*. Nd^{3+}–YAG laser amplifier and oscillator, P (8) 221*e*. Optical masers comprising the active media $SrMoO_4$:Nd, $CaMoO_4$:Nd, and $PbMoO_4$:Nd, P (9) 243*i*; CaF_2:Nd, P (9) 243*h*; $CaWO_4$:Ho, P (7) 194*a*; $CaWO_4$:Pr, P (9) 243*i*; $CaWO_4$:Tm^{3+}, P (7) 193*j*. Optical maser using internal reflection, P (2) 42*a*. Optical maser using single crystal molybdate composition, P (6) 160*i*. Optical maser using trivalent neodymium ions in a calcium tungstate host lattice, P (3) 74*b*. Oxide underlay for printed circuit components, P (3) 74*c*. Piezoresistive material, P (8) 221*f*. Preanodization of tantalum electrodes, P (3) 74*d*. Process for growing neodymium doped single crystal divalent metal ion tungstates, P (9) 244*a*. Radiation insensitive quartz crystal devices, P (10) 279*a*. Selective removal of material using cathodic sputtering, P (11) 307*d*. Semiconductor contact, P (4) 106*f*, P (11) 307*e*. Semiconductor devices having dielectric coatings, P (2) 42*h*. Semiconductor encapsulation, P (11) 307*i*. Semiconductor surface cleaning, P (3) 74*g*. Support assembly for materials processing and method, P (5) 130*a*. Tantalum nitride film resistor, P (6) 161*b*. Temperature sensitive element, P (9) 244*a*. Vanadium-containing garnets, P (10) 279*i*. Vapor deposition method and apparatus, P (4) 106*g*.
Bellaire, M. Basic brush exercises for the underglaze decorator, (8) 205*j*.
Beloit Corp. Liquid flow control device having improved surface for operative engagement with relatively moving paper machine forming wire, P (7) 190*i*.
Belopol'skii, M. S. Quantitative evaluation of the sensitivity of clays to drying, (5) 130*h*.
Belorukova, L. P. See Efimov, A. I.
Belostotskaya, N. S. Study of the fine fractions of clays and kaolins with supercentrifugal dispersion analysis, (2) 45*c*.
Belous, V. M. Effect of thermal treatment on the formation of the trapping level spectrum in silver chloride, (2) 49*g*.
Belov, N. V. See Kuz'min, E. A.; Mamedov, Kh. S.
Belyaev, G. I., and Barinov, Yu. D. Effect of composition on whiteness and water resistance of zirconium enamels, (6) 145*h*.
Belyaev, I. N. See Smolyaninov, N. P.
Belyaev, I. N., Aver'yanova, L. N., and Belyaeva, I. I. X-ray-phase analysis of the systems MeTiO_3–MeWO_4(MoO_4), (3) 87*g*.
Belyaev, I. N., and Chikova, N. N. Ternary systems K_2SO_4–Li_2SO_4–Ca_2SO_4 and Li_2SO_4–Rb_2SO_4–$PbSO_4$, (10) 291*j*.
Belyaev, I. N., and Golovanova, T. G. Interactions of the titanates and vanadates of sodium in melts, (1) 22*j*.

Belyaev, I. N., Smolyaninov, N. P., and Kal'nitskii, N. R. Investigation of the system Bi_2O_3–TiO_2–PbO, (1) 23*b*.

Belyaev, L. M., Dobrzhanskii, G. F., and Bagdasarov, Kh. S. Some changes in a method of growing crystals from melts, B (11) 319*j*.

Belyaeva, G. I. See Anfinogenov, A. I.

Belyaeva, I. I. See Belyaev, I. N.

Belyustin, A. V. Relation of impurity effects in crystal growth to pH of solution, B (11) 319*h*.

Belyustin, A. V., and Portnov, V. N. Effects of borax on the rate of growth of alum crystals from solution, B (11) 319*i*.

Belyustin, A. V., and Rogacheva, E. D. Production of crystallization nuclei in the presence of a seed crystal, B (11) 319*h*.

Benard, E. J. J. Method of making hollow glassware with a stem and a foot, P (11) 299*b*.

Bender, B. G. Advances in applying circuitry to ceramic substrates, (10) 276*h*. Method of making semiconductor devices, P (4) 105*a*.

Bender, R. E. See Fischer, J. J.

Bendix Corp. Prestressed ceramic transducer, P (4) 106*c*. Semiconductor triode, P (3) 74*h*.

Bendorius, R. See Barsauskas, K.

Benecki, W. T. Control of the dry-pressing process, (10) 276*i*.

Benesovsky, F. Importance of powder metallurgy for developing and producing new types of nuclear fuel materials, (3) 67*g*.

Benesovsky, F., and Rudy, E. High-temperature nuclear fuel structures and their production, P (1) 11*f*.

Bengtson, K. B., Johanson, L. N., and Almond, J. C. Method and apparatus for the preparation of magnesium oxide by a spouting bed technique, P (8) 217*d*.

Benjamin, E. A. See Duffek, E. F.

Benjamin Lassman & Son. Pressure molding of dry material, P (1) 16*b*.

Benjamin, W. O., and Jaeger, A. R. Prismatic light transmitting panel, P (2) 34*e*.

Benjaminson, A. See Hammond, D. L.

Bennahmias, D. Bright pastel compositions containing daylight fluorescent pigments, P (4) 104*c*.

Benner, F. E., Jr. See Allen, E. M.

Bennett, A. I. Apparatus for producing crystalline semiconductor material, P (8) 220*j*.

Bennett, A. I., Jr., Church, C. H., Coleman, J. J., O'Hara, S., Smith, W. J., and Stewart, R. C. Apparatus for producing crystals, P (6) 158*e*.

Bennett, D. C. Continuous growth of crystalline materials, P (7) 192*d*. Cost reduction through kiln car engineering, (6) 163*g*.

Bennett, H. Some aspects of the analysis of alumina ceramics, B (11) 320*f*.

Bennett, H., and Hawley, W. G. Methods of Silicate Analysis, B (6) 173*b*.

Bennett, P. E. See Browning , J. S.

Benson, G. E. See Doob, H., Jr.

Benthien, E. Reversible temperature dependence of electric resistors, (8) 220*f*.

Bentle, G. G. Elastic constants of single-crystal BeO at room temperature, (4) 110*i*.

Bentle, G. G., and Kniefel, R. M. Brittle and plastic behavior of hot-pressed BeO, (1) 19*f*.

Bentley, G. P., and Lovins, G. H. Method of producing aspheric surfaces on mirrors or lenses, P (1) 7*c*.

Bentley, W. Glass bending mold positioning and orienting apparatus, P (7) 183*a*.

Benton, K. R. Feeder for producing fibers, P (11) 298*c*.

Ben-Yair, M. See Heller, L.

Beranek, M. Automatic substitution thermobalance with graphic recording and digital indication, (8) 222*j*.

Berdonosov, S. S., Berdonosova, D. G., Lapitskii, A. V., and Vlasov, L. G. X-ray study of hafnium tetrabromide, (2) 54*b*.

Berdonosova, D. G. See Berdonosov, S. S.

Berenshtein, P. I. Rational schedule for firing large diameter drain tile, (2) 35*h*.

Berezhnaya, V. T. See Bukhalova, G. A.

Berezhnoi, A. S., and Gul'ko, N. V. Subsolidus structure of the four-component systems MgO–Cr_2O_3–Al_2O_3–SiO_2, MgO–Cr_2O_3–Al_2O_3–TiO_2, and MgO–Cr_2O_3–Al_2O_3–ZrO_2, (3) 86*j*.

Berezkina, L. G., and Chizhikov, D. M. X-ray investigation of the compound in the system PbO–SiO_2, (3) 87*e*.

Berg, A. See Khershel'mann, V.

Berg, D., and Malinaric, P. J. Electrical stress-grading coatings, P (1) 11*c*.

Berg, R. H. Peripherally locked and sealed orifice disk and method, P (10) 269*g*.

Berger, J. A., and Blankenship, M. G. Image recording, P (10) 278*a*.

Bergeron, C. G. See Liedberg, D. J.

Bergh, S. S. See Nielsen, A.

Berghuis, P. J. See Gie, O. T.

Bergman, A. G. See Arabadzhan, A. S.; Il'yasov, I. I.

Bergman, A. G., and Andryushchenko, Yu. I. Fusibility diagram of the reciprocal system of the chlorides and bromides of lithium and lead, (9) 250*d*.

Bergman, A. G., Andryushchenko, Yu. I., and Bineeva, R. K. Fusibility in the ternary system of the chlorides of lithium, potassium, and lead, (11) 317*c*.

Bergman, A. G., and Arabadzhan, A. S. Effect of a displacement of equilibrium on the fusibility diagrams of systems with solid solutions, (9) 249*c*. Fusibility diagram of the ternary system Li ‖ F,Cl,Br, (10) 286*b*. Reciprocal system of the chlorides and bromides of lithium and thallium, (10) 290*e*.

Bergman, A. G., and Goryacheva, V. P. Fusibility diagram of the system of the pyrophosphates of lithium and potassium and sodium fluoride, (1) 21*e*.

Bergman, A. G., Kaznacheeva, K. F., Goryacheva, V. P., and Salovskii, A. P. Reciprocal system of the pyrophosphates and fluorides of sodium and potassium, (10) 290*f*.

Bergman, A. G., and Misler, Zh. V. Ternary system of the chlorides of lithium, potassium, and cadmium, (1) 25*i*.

Bergman, A. G., Salovskii, A. P., and Misler, Zh. V. Ternary system of the chlorides of lead, lithium, and cadmium, (9) 257*g*.

Bergmann, O. R. Aluminum-bonded titanium carbide cermets, (8) 214*i*.

Bergmann, O. R., and Barrington, J. Effect of explosive shock waves on ceramic powders, (10) 285*f*.

Bergquist, H. R. See Dunlap, J. C.

Berganov-Hansen, B., Endow, N., and Pasternak, R. A. Ion gage calibration at low pressures using a leak detector, (10) 281*d*.

Bergstein, A. DTA of tetragonally deformed spinels, (2) 49*b*.

Bergstein, A., and Kleinert, P. Oxygen deficient spinels in the Li–Mn–O system, (5) 139*g*.

Bergstein, A., Sestak, J., and Kitzinger, E. Phases in the spinel region of the system CuO_x–Mn–O_y–FeO_z, (3) 84*j*.

Bergstein, F. D., Kleingers, A. B., Jr., and Back, L. Method and means for controlling foaming of clay coating composition during application, P (11) 309*c*.

Bergstein Packaging Trust. Method and means for controlling foaming of clay coating composition during application, P (11) 309*c*.

Bergstrom, B. H. See Gilvarry, J. J.

Berkelhamer, L. H. Small electrical unit with molded ceramic coating, P (4) 106*h*.

Berkes, J. S., White, W. B., and Roy, R. Growth of rutile of controlled composition from borate fluxes, (3) 82*f*.

Berkhin, S. I. See Chukhrov, F. V.

Berkowitz, J. Reaction of graphite with nitrogen at elevated temperatures, B (6) 175*c*.

Berlinov, Kh. Polarographic determination of aluminum in silicate materials with the use of Eriochrome Black T, (2) 44*i*.

Berman, S. S. See Goto, K.

Bernard, B. Infrared temperature sensing of transparent objects, (7) 195*g*.

Bernath, J. Thermal radiant energy detecting device, P (9) 244*b*.

Berner, L., and Edwards, I. A. Material handling apparatus for pulverulent materials, P (4) 109*a*.

Bernett, F. E. Construction material, P (1) 13*a*.

Bernier, C. J., and Menelly, R. A. Electric discharge lamp with integral pressure regulator, P (4) 104*e*.

Bernstein, B. T. Elastic constants of synthetic sapphire at 27°C, (2) 49*h*.

Bernstein, H. See Craven, J. P.

Bernstein, J. L. Unit cell and space group of gadolinium molybdate and of scandium tungstate, (8) 228*a*.

Bernstein, L. Gold bonded boron containing semiconductor devices, P (2) 41*d*. Gold boron alloy and method of making the same, P (1) 11*e*. *P*-type alloy bonding of semiconductors using a boron-gold alloy, P (2) 42*c*.

Bernt, E. Refractories in the ceramic industry (II), (2) 36*h*.

Berohn, A. See Curran, D. R.

Berringe, L. B. Mass spectrometer survey, (10) 281*e*.

Berry, J. M. See Mehan, R. L.

Berry, K. L. Process for preparing fibrous titanium dioxide and compositions useful in production therefor, P (6) 164*i*.

Berry, L. G., and Rao, S. V. L. N. Method for taking back reflection oscillation photographs of single crystals, (6) 162*e*.

Berstein, G., and Nuttle, R. G. Titanium dioxide pigments, P (1) 19*b*.

Bertaut, E. F. See Bacmann, M.; Chazalon, R.

Bertaut, E. F., Delapalme, A., Bassi, G., Durif-Varambon, A., and Joubert, J. C. Crystal structure of γ-$LiAlO_2$, (7) 198*c*.

Bertaut, E. F., and Forrat, F. Preparation of monocrystals of rare earth manganites, P (4) 106*b*.

Bertaut, E. F., Van Qui, V., Pauthenet, R., and Murasik, A. Magnetic structure and magnetic properties of $GeNi_2O_4$, B (2) 55*j*

Berthold, C. E. Process for preparing cesium compounds from cesium alum, P (1) 19*a*.

Berthold, H. J. See Geilmann, W.

Bertolini, W. A., and Davison, D. G. Pneumatic apparatus for handling pulverulent materials, P (4) 107*a*.

Bertulis, K., and Tolutis, V. Dielectric properties of praseodymium, cerium, and neodymium thin films, (11) 315*b*. Dielectric properties of thin praseodymium fluoride films, (6) 157*j*.

Berul, S. I. See Voskresenskaya, N. K.

Berul, S. I., and Voskresenskaya, N. K. Interaction of CeO_2, Md_2O_3, and Sm_2O_3 with fluoride melts, (10) 287*a*.

Beryllium Metals & Chemicals Corp. Production and recovery of beryllium chloride, P (7) 196*j*.

Berzon, S. A., Meitina, V. A., and Shtaveman, A. V. New effective coagulant, (6) 156*c*.

Beskow, G. Some geopractical effects of variable particle surface constitution in mineral soils, B (7) 204*e*.

Besse, L. L. Reversible roof tiles [design], P (3) 65*c*.

Besson, H. See Caillere, S.

Besson, J., Blum, P., and Spitz, J. Hydrolysis of uranium carbide in aqueous solution, B (6) 172*h*.

Besson, J. M., Butler, J. F., Calawa, A. R., Paul, W., and Rediker, R. H. Pressure-tuned PbSe diode laser, (10) 289*i*.

Bessonov, A. F. See Strekalovskii, V. N.

Bessonov, A. F., Borisov, B. S., and Vlasov, V. G. Investigation of the structure of the primary oxide layer on uranium, (11) 318*b*.

Bessonov, A. F., and Vlasov, V. G. Interaction of uranium with nitrogen, (11) 317*g*.

Bessonova, E. S. See Vorob'eva, O. V.

Best, B. Thermal pressing analysis, (8) 216*e*.

Best, J. R. Fibrous glass air filters, P (6) 149*i*.

Best, W. H. Radiant burner with vented [ceramic plate] burner surface, P (5) 132*h*.

Betar, V. G. Metallizing filament, P (7) 193*i*.

Bethlehem Steel Corp. Blast furnace hot stove checkers, P (5) 125*h*. Dilatometer for heated specimens under external stress, P (5) 132*d*. Mold for steel casting, P (8) 218*a*.

Bettens, A. H. See Goodman, R. H.

Beus, M. D. See Kitaigorodskii, I. I.

Beutelspacher, H., and Marel, H. W. van der. Electron microscopy in the identification of clay minerals in delta sediments, B (2) 56*g*.

Beyersdorfer, K. Differences between glass melting and glaze melting, (4) 92*g*.

Beyersdorfer, P. Effect of permanent mechanical strains on a glass sheet, (4) 93*b*.

Bezborodov, M. A., and Abdurazakov, A. A. Newly excavated glassworks in the U.S.S.R., 3rd to 14th century A.D., (4) 80*j*.

Bezirjian, O. H. See Gabrysh, A. F.

Bezpalov, K. M., and Tarunin, A. A. Automation of glass tank furnaces, (7) 179*g*.

Bezpalov, K. M., and Vakhrameev, V. S. New nonstaged electric drive for the VVS [glass drawing] machine, (9) 234*e*.

Bhagwat, W. V. See Poonia, N. S.

Bhappu, R. B. See Roman, R. J.

Bhattacharya, R. Hall effect in single crystals of graphite, (2) 50*f*. Magnetoresistance in single crystals of graphite, (7) 201*b*.

Bhattacharyya, B. N., and Sen, S. Aluminum titanate—formation and properties, (7) 197*b*.

Bhatye, S. V. Effect of small addition of alumina, boric oxide, and titania on the properties of a soda-lime-silica glass, (7) 180*d*.

Bhide, V. G., and Bapat, N. J. Interferometric study of the microtopography arising out of 90° domain walls in single crystals of barium titanate, (3) 82*h*.

Bhide, V. G., and Chinmulgund, N. D. Interferometric studies of domain structure in ferroelectric barium titanate, (3) 82*f*.

Bhide, V. G., Gondhalekar, R. T., and Shringi, S. N. Surface layers on ferroelectric $BaTiO_3$ crystals, (5) 141*d*.

Bhide, V. G., and Shringi, S. N. Polarization reversal electroluminescence at low frequencies in barium titanate crystals, (8) 226*j*.

Bhuiyan, A. L. Extraction of stibnite with sodium sulfide solutions, (11) 312*c*.

Bhuiyan, M. M., and Cable, M. Refining of two soda-lime-silica glasses with sodium sulfate, (3) 62*c*.

Bhushan, B., and Sen, S. Zircon glazes, (2) 40*c*.

Biancheria, A., and Allio, R. J. Fabricating PuO_2–UO_2 fuels—how leading processes compare, (6) 152*c*.

Bickerdike, R. L., and Brown, A. R. G. Method for producing a composite carbon article and articles produced thereby, P (5) 126*a*.

Bickerdike, R. L., and Hughes, G. Method of forming fibrous carbon articles, P (5) 126*c*.

Bickley Furnaces, Inc. Burner means for furnaces, P (7) 195*g*.

Bidault, G. Use of electrocast refractories in reheating furnaces, (11) 301*f*.

Bidnaya, D. S. See Sysoev, L. A.

Bidnaya, D. S., Obukhovskii, Ya. A., and Sysoev, L. A. Search for methods of growing crystals of CdS from solution, (1) 24*j*.

Biedron, M. Intensification of the glass melting process in pot furnaces, (4) 93*j*.

Biehl, A. T. Low power nuclear reactors, P (3) 70*c*.

Bielanski, A., Deren, J., and Duczyminska, E. Electrical conductivity in MgO–Cr_2O_3 mixtures of varying composition and at different stages of sintering, (3) 81*b*.

Bielanski, A., Deren, J., Haber, J., and Sloczynski, J. Studies on the properties of doped nickel oxide, (8) 227*d*.

Bielen, H. J. See Almodovar, I.

Bieler, B. H. Aqueous slips of tantalum pentoxide and calcium fluoride, (6) 155*j*.

Biemans, L. J. M. See Gie, O. T.

Bien, F. See Green, A. K.

Bierlich, K. G. Tile construction, P (5) 127*i*.

Biglin, J. M., and Greaves, J. J. Cold press method of making abrasive articles, P (1) 1*h*.

Bihari, J. K. Use of combustible materials in heavy clay products, (11) 300*c*.

Bilby, B. A., and Crocker, A. G. Theory of the crystallography of deformation twinning, (3) 86*g*.

Billardon, M. See Briat, B.

Billco. Flat glass washer, P (10) 267*j*.

Billington, S. R., Chown, J., and White, A. E. S. Sintering of silicon carbide, B (11) 320*e*.

Bil'tyukova, E. P. See Syritskaya, Z. M.

Bil'tyukova, E. P., Prokopets, V. F., and Esechko, A. M. Methods of chemical analysis of high-alumina refractories of the bakor and Corhart types, (8) 216*b*.

Bimson, M., and Werner, A. E. Danger of heating glass objects, (4) 89*i*.
Bineeva, R. K. See Bergman, A. G.
Bingham, K., and Parke, S. Absorption and fluorescence spectra of divalent manganese in glasses, (3) 60*d*.
Binkert, C. F., and Laine, L. H. Apparatus for bending glass sheets or plates, P (4) 96*f*.
Binkowski, E. J. Pyrometric lance apparatus, P (11) 311*d*.
Binks Mfg. Co. Spray gun having vent member for spray material and air, P (5) 131*b*.
Binks-Bullows, Ltd. Liquid spraying apparatus, P (5) 131*b*.
Birch, R. E. Fused cast articles and method of making the same, P (5) 125*i*.
Birch, R. E., King, D. F., and Davies, B. Silica refractories, P (2) 38*g*.
Bird, G. O. Design relationships in nineteenth century American glass, (3) 57*j*.
Bird, G. R. Method of forming [Ta] carbide coated coiled filaments for lamps, P (5) 129*b*.
Bird, G. R., Brewer, L., and Gray, W. E., Jr. Method of preparing a tantalum carbide crystal, P (8) 217*f*.
Bird, R. See Konopicky, K.
Bird Machine Co. Solid bowl centrifuge with air circulation control, P (11) 309*c*.
Birks, F. T. See Taylor, B. L.
Birks, L. S., Hurley, J. W., and Sweeney, W. E. Perfection of ruby laser crystals, (4) 104*b*.
Bisch, J. Process of making ceramic objects, P (8) 222*e*.
Bischoff, F., and Krueppel, A. Measurement of porosity (apparent density) of granular material, (3) 76*c*.
Bishay, A. M., and Arafa, S. Gamma-induced absorption and structural studies of arsenic borate glasses, (9) 233*e*.
Bishop, D. L. Calcium silicate insulating material and method of producing same, P (4) 100*e*. See Kalousek, G. L.
Bishop, F. L. Method and apparatus for severing mold charges of molten glass, P (10) 268*c*.
Bishop, F. L., and Pinotti, A. D. Neutron-absorptive glass, P (2) 34*b*.
Bishop, G. W. Method of removing surface irregularities from metal articles, P (6) 143*h*.
Bishop, S. G., and Bray, P. J. Nuclear magnetic resonance studies of calcium boroaluminate glasses, (9) 234*e*.
Bishui, B. M. See Prasad, J.
Bishui, B. M., and Prasad, J. Physicochemical properties of some Indian clays (IV) infrared absorption spectra study; (V) electron microscope study, (3) 84*d*; (VI) their occurrence and ceramic characteristics, (6) 169*f*.
Biskupski, V. S. Fast and complete decomposition of rocks, refractory silicates, and minerals, (1) 16*i*.
Bitsianes, G. See Gorton, A. T.
Bittencourt, P. R. H. M. Kinetics of the aluminum-silica reaction, (9) 251*h*.
Bixby, H. D. Method and product for the disposal of radioactive wastes, P (7) 190*j*.
Bjerkelund, E., and Kjekshus, A. Crystal structure of $TaSe_3$, (2) 49*c*.
Black, I. A. See Glaser, P. E.
Black, L. V., and Golightly, J. S. Glass bending mold with pivoted end sections, P (7) 183*a*.
Black, L. V., and McKelvey, H. E. Apparatus for bending glass, P (7) 182*f*.
Blackburn, A. R. See Emmel, D. R.
Blade, J. W., and Kagan, C. A. R. Apertured thin-film circuit components, P (10) 277*g*.
Blaha, E. Method of furnace operation, P (1) 17*j*.
Blain, B. J., and Douglas, R. W. Infrared optical constants of glasses, (3) 61*j*.
Blaine, J. C. Apparatus for delivering fusible material to a glass melting furnace, P (2) 32*i*.
Blaine, R. L., and Arni, H. T. Heat of hydration of portland cements, (11) 294*h*. Variables associated with small autoclave expansion values of portland cements, (11) 294*j*.
Blaine, R. L., Arni, H. T., and Clevenger, R. A. Water requirements of portland cement, (11) 294*c*.
Blaine, R. L., Arni, H. T., and Evans, D. N. Interrelations between cement and concrete properties (II) sulfate expansion, heat of hydration, and autoclave expansion, (11) 294*e*. Variables associated with expansion in the potential sulfate expansion test, (11) 294*f*.
Blaine, R. L., Arni, H. T., and Foster, B. E. Materials and techniques, (11) 294*b*.
Blaine, R. L., Arni, H. T., Foster, B. E., et al. Interrelations between cement and concrete properties (I) materials, techniques, water requirements, and trace elements, (11) 293*j*.
Blaine, R. L., Bean, L., and Hubbard, E. K. Occurrence of minor and trace elements in portland cement, (11) 294*d*.
Blainey, A., and Custers, J. F. H. Diamond abrasive particles in a metal matrix, P (6) 143*h*.
Blair, G. E., and Urnes, S. Glass formation in the system Li_2O–SiO_2, (4) 93*c*.
Blair, J. C. See Hartman, T. E.
Blair, L. R. See Redican, F. W.
Blair, R. See O'Bryan, H. M., Jr.
Blair, R. C. Process and apparatus for continuous calcining of powdered gypsum rock, P (5) 119*d*.
Blake, F. L. Method of forming semiconductors, P (4) 105*e*.
Blake, G. D. See Holzinger, R. J.
Blakely, J. M. See Maiya, P. S.
Blakemore, G., and Hillman, G. E. Comprehensive fuel-gas analysis by gas chromatography, (4) 107*e*.
Blanchard, M. See Budd, S. M.
Blanck, D. Glass finishing by impact lapping at ultrasonic frequency, (4) 93*c*.
Bland, C. C. Apparatus for production of glass beads by dispersion of molten glass, P (8) 211*i*. Method and apparatus for production of glass beads by dispersion of molten glass, P (6) 150*h*.
Blank, J. M., and Shafer, H. J., Jr. Method and apparatus for decorating glassware, P (8) 212*j*.
Blank, M., and Britten, J. S. Transport properties of condensed monolayers, (4) 114*f*.
Blankenburg, H. J. German and foreign quartz sand deposits (comparative survey), (10) 282*j*.
Blankenship, A. C., and Huntt, R. L. Microwave characteristics of fine-grain high-power garnets and spinels, (9) 252*e*.
Blankenship, M. G. See Berger, J. A.
Blasiak, E., and Haba, A. Influence of liquid phase in fluidized bed on calcium carbide nitriding, (5) 137*i*.
Blasov, V. G. See Strekalovskii, V. N.
Blasse, G. Antiferromagnetism of the spinel $LiCuVO_4$, (11) 313*c*. Ferromagnetic interactions in nonmetallic perovskites, (11) 316*j*. Ferromagnetism and ferrimagnetism of oxygen spinels containing tetravalent manganese, (11) 317*a*. Vanadium-containing ferrimagnetic material, P (1) 15*g*.
Blau, H. H. See Shonebarger, F. J.
Blaugher, R. D., and Hulm, J. K. Superconducting phosphides of the transition metals, (9) 257*a*.
Blaus, J. See Rydinger, M.
Blavat, H. See Lacroix, R.
Blazek, W. S. See Chandley, G. D.
Blazey, K. W. See Burns, G.
Bleukens, P. C. M., and Schuitemaker, J. J. Method of applying an alkaline earth metal getter, P (10) 278*e*.
Blinc, R., Jovanovic, A., Levstik, A., and Prelesnik, A. Dielectric properties of $NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$ single crystals, (5) 135*d*.
Bliton, J. L., Rechter, H. L., and Griffith, J. S. Method of making fuel cell elements, P (2) 38*d*.
Blocher, J. M., Jr. Nuclear fuel particles coated with mixture of pyrolytic carbon and silicon carbide, P (7) 189*b*.
Blocher, J. M., Jr., Browning, M. F., Wilson, W. J., Secrest, V. M., Secrest, A. C., Landrigen, A. B., and Oxley, J. H. Properties of ceramic-coated nuclear fuel particles, (2) 36*e*.
Block, A. Abrasive article, P (10) 261*f*. Flap-type abrasive wheel, P (3) 57*h*.
Block, A., and Nelson, R. M. Abrasive device and method of fabrication, P (6) 143*g*.
Block, S. See Weir, C.
Blocker, T. G., III. See Heeger, A. J.
Blodgett, W. E. Research in sanitary ware, (1) 12*j*.
Blodgett, W. E., Keeling, P. I., and Robertson, J. M. Thermistor, P (4) 106*e*.
Blokh, K. I. See Chernyak, M. G.
Blokh, S. A. See Zakharikov, N. A.
Blomdahl, F. A. See Schlicke, H. M.
Bloom, M. Lead glass skin on silica, (1) 4*d*.
Bloomster, C. H. See Mills, L. E.
Bloomster, C. H., and Hauth, J. J. Nuclear [ceramic] fuel element incorporating helical fissionable wire, P (11) 302*j*.
Bluemel, F. Renaissance stoves of the castle at Eferding (Upper Austria), (8) 206*a*.
Blum, P. See Besson, J.
Blum, P., and Devillard, J. Some aspects of the fabrication of uranium monocarbide by electron bombardment, B (6) 172*f*.
Blum, P., and Guinet, P. Actinide oxide-actinide nitride eutectic compositions and their method of manufacture, P (4) 99*i*.
Blum, P., and Moreau, C. Process for the preparation of uranium monocarbide powder, P (3) 70*e*.
Blum, W. A. Dry film lubricants for cold forming of steel, (4) 91*f*.
Blume, W. S. Method of making machinable high energy permanent magnets, P (7) 193*d*.
Blumenfeld, M. A. See Triggs, W. M.
Blumenthal, J. L., Santy, M. J., and Burns, E. A. Kinetic studies of high-temperature carbon-silica reactions in charred silica-reinforced phenolic resins, (8) 215*e*.
Blumenthal, R. N., Moser, J. B., and Whitmore, D. H. Thermodynamic study of nonstoichiometric niobium pentoxide, (1) 25*g*.
Blundell, A., Brooks, L. H., Clarke, J. C., Gillies, G. M., and Saum, C. J. Manufacture of uranium dioxide, P (5) 126*c*.
Blust, H. L. Apparatus for manufacturing reed switches, P (10) 267*a*.
Bluvshtein, M. N., Tsikolin, G. I., and Zykova, Z. K. Dynamic method for determining the modulus of elasticity of refractories at high temperatures and automation of the test, (6) 152*f*.
Blytas, G. C. See Peterson, D. L.
Bobovich, Ya. S. Raman scattering spectrum of barium orthotitanate, (2) 51*j*.
Bobrova, T. N., Zolotarev, I. S., Plotnikova, V. V., and Girshgorn, P. B. Method of manufacturing crucibles from cermet alloy TsM-332 and their use for chemical analysis, (8) 215*i*.
Bobrowsky, A. R. Compacting of particulate materials, P (4) 106*j*.
Bocquet, J. P. See Alaille, L.
Bocquet, M. See Rappeneau, J.
Bodenheimer, W., Heller, L., Kirson, B., and Yariv, Sh. Organometallic clay complexes (III) copper-polyamine-clay complexes, B (2) 56*j*.
Bodenseewerk Perkin-Elmer & Co. G.m.b.H. Method and means for producing chromatographic capillary columns, P (6) 150*b*.
Boehm, H. P., Clauss, A., Fischer, G. O., and Hofmann, U. Adsorption behavior of extremely thin carbon films, (3) 79*f*.
Boehme, J. Silo control in the preparation and working of ceramic bodies, (1) 16*a*.
Boeing Co. Method of bonding sheets of metal, P (3) 60*a*.
Boell, G. R. See Ridge, M. J.
Boelsterli, H. U. See Mooser, E.
Boer, F. de, and Broos, J. Some observations on the discoloration of green-emitting zinc-cadmium sulfide phosphors in color tubes, (11) 305*b*.
Boesen, G. Seventeenth-century cup in the Danish Royal Collection, (2) 28*a*.
Boffe, M. See Plumat, E.
Bogardus, E. H. Third-order elastic constants of Ge, MgO, and fused SiO_2, (3) 87*i*.
Bogdanova, N. I., Pirogovskaya, G. P., and Ariya, S. M. Higher oxides of titanium, (9) 250*a*.
Boggs, L. R. Equipment for making articles composed of fiber reinforced resin materials, P (9) 235*i*.
Boggum, P. See Glaser, W.
Boggum, P., and Glaser, W. Basic material—why and where? Technically sensible use of basic refractories in glass melting furnaces, (1) 8*a*.
Boghen, J., Herenguel, J., Salesse, M., Caillat, R., and Darras, R. Preparation of materials of composite structure, P (2) 30*h*.
Bognar, L. L. Method and apparatus for scoring [micro] sheet material, P (6) 150*i*.
Bogoslovskii, V. N. See Leont'ev, L. I.
Boguslavskii, I. A. Obtaining high-strength glasses, (4) 94*b*.
Bohlmann, M. See Alberts, L.
Boicey, J. H. Automobile windshield of laminated glass having embedded antenna wires, P (1) 6*e*. Pressing glass-plastic sandwiches, P (7) 184*e*.
Boikova, A. I., and Toropov, N. A. Stoichiometry and polymorphism of tricalcium silicate, (9) 256*c*.
Boirat, M., Maretheu, M., and Tanguy, M. Use of radioactive elements for the automatic determination of moisture in the ceramic industry, (3) 76*h*.
Bokin, P. Ya. Grain strength of abrasive powders, (5) 117*g*.
Bokov, V. A., and Myl'nikova, I. E. Ferroelectric properties of monocrystals of new perovskite compounds, (4) 111*i*.
Boksay, Z. See Lengyel, B.
Boksay, Z., Bouquet, G., and Csakvari, B. Interpretation of Jordan's equation for calculating the alkali error of glass electrodes, (8) 209*e*.
Bolidens Gruvaktiebolag and Skelleftea Gummifabriks AB. Screening device in a rotatable drum intended for grinding and/or mixing material, P (2) 48*b*.
Bol'shakov, K. A., Fedorov, P. I., and Il'ina, N. I. Binary systems of sodium sulfate with the sulfates of copper(II) and iron(III), (11) 314*a*.
Bolton, K. See Batey, W.
Bolz, L. H. See Ormsby, W. C.
Bomar, E. S. See Carlsen, F. L., Jr.
Bonazoli, R. P. See Scoledge, R. F.
Bonazoli, R. P., Scoledge, R. F., and Palermo, J. J. Incandescent lamp containing iodine, oxygen, and inert gas, P (6) 159*a*.
Bond, W. L. Method of forming metal carbide coating on carbon base, P (10) 274*g*.
Bondar, I. A. See Lazarev, A. N.
Bondarev, D. E., and Solov'ev, O. A. Low-induction ferrites for use in computer memories, (3) 72*g*.
Bondarev, K. T. Stresses originating during the leaching of sodium borosilicate glasses, (9) 234*j*.
Bondarev, K. T., Kariyuk, V. N., and Minakov, V. A. Nucleation of catalyst and origin of crystals in some sitalls, (10) 265*a*.
Bondarev, V. N., and Samsonov, G. V. Preparation of the germanides Mo_3Ge and Cr_3Ge, (8) 220*e*.
Bondi, A. See Hassell, H. L.
Bondi, H. S. Glazed ceramic articles, P (1) 13*a*.
Bondley, R. J. Manufacture of helium separation apparatus, P (11) 298*d*. Metal to ceramic sealing structure, P (1) 14*b*.
Boneff, S., and Schwiete, H. E. Formation of chip cavities in the scratching of glass surfaces, (2) 31*c*.
Bonetti, G. See Gottardi, V.
Bonin, G. E. Edge grinding, P (10) 267*g*.
Bonis, L. J., and Hausner, H. H. (editors). Fundamental Phenomena in the Material Sciences (Vol. I) Sintering and Plastic Deformation—Proceedings of the First Symposium, Boston, February 1963, B (7) 204*e*.
Bonnaud, M. See Paymal, J.
Bonnetti, G., Locardi, B., and Tornati, M. Structural anomalies in SiO_2–Al_2O_3–Na_2O–Li_2O glasses determined by physical measurements and chemical resistance, (6) 148*j*.
Bonnke, M., and Fitzer, E. Pyrolytic silicon carbide, (9) 254*f*.
Bonstedt, K. P. See Lauer, G. G.
Boon, G. C. Roman window glass from Wales, (9) 230*a*.
Boon, W. Pneumatic conveying system for bulky materials, P (1) 16*b*.
Booth, C. See Lynam, T. R.
Booth, C. F., and Whitehurst, B. M. Aluminous cement slag composition and method of increasing compressive strength of same, P (10) 262*g*.

Booth, M. L. Molds and dies by Shaw casting, (3) 68*i*.
Boparai, K. S. See Poonia, N. S.
Borchardt, H. J. Luminescent materials, P (1) 14*g*. Luminescent solid solutions of europium compounds with at least one other rare earth compound, P (7) 193*f*.
Borchardt, H. J., and Thompson, B. A. Reactions of solid alkaline earth oxides (I) BaO and SrO; (II) CaO and MgO, (9) 254*b*.
Borden Co. Cold press method of making abrasive articles, P (1) 1*h*.
Boreiko, B. M. See Slavyanskii, V. T.
Borgstedt, H. U., Eichkorn, G., and Heim, E. Research on the elimination of stress in glass by ultrasonics, (4) 95*d*.
Borisenko, V. B. Accuracy of hardness determinations at high temperatures, (11) 313*c*.
Borisov, B. I. See Brekhovskikh, S. M.
Borisov, B. I., Ignatova, V. A., Kabanov, N. P., Terman, V. B., Shumilina, V. I., Nazarova, N. A., Okal'nik, G. N., and Popov, M. I. Improving the surface of sheet glass by electrically heating the air in the drawing chamber, (10) 265*f*.
Borisov, B. S. See Bessonov, A. F.
Borisova, I. I. See Brekhovskikh, S. M.
Borom, M. P., and Pask, J. A. Role of adherence oxides in the development of chemical bonding at glass-metal interfaces, (2) 30*c*.
Borovik, E. S., and Mamalui, Yu. A. Magnetic susceptibility of granular hexagonal ferrites, (11) 318*a*.
Borovik, E. S., and Usikova, N. E. Properties of mixed barium and strontium ferrites, (10) 290*c*.
Borovik, E. S., and Yakovleva, N. G. Influence of texture on the magnetic properties of mixed barium and strontium ferrites, (11) 317*d*.
Borrajo, E. P. Pyrographic process and products for operation of the process, P (9) 242*c*. Vitrifiable decalcomania, P (11) 304*e*.
Borrelli, N. F. See Summitt, R.
Borrelli, N. F., Herczog, A., and Maurer, R. D. Electrooptic effect of ferroelectric microcrystals in a glass matrix, (10) 285*j*.
Bortz, S. A. Increasing the strength of structural clay products, (6) 151*f*.
Bortz, S. A., and Nagao, H. Nondestructive quality control of tar-bonded basic brick, (3) 68*a*.
Bose, A. K. See Yedavalli, B. V. S.
Bosman, M. See Koning, J. de.
Bossetti, A. Continuous kiln for firing ceramic materials, P (10) 282*b*.
Bosso, J. F. See Wismer, M.
Botia, P. D. See Duran Botia, P.
Bottomley, S. C. See Bradsell, R. H.
Botton, R. See Steinmetz, A.
Botvinkin, O. K. See Ananich, N. I.
Botvinkin, O. K., and Demichev, S. A. Investigation of certain properties of glasses in the system Na_2O–ZrO_2–SiO_2 (I) investigation of the index of refraction and the density of glasses as a function of their composition; (II) thermal expansion of glasses and its dependence on the composition; (III) microhardness and surface energy of glasses; (V) investigation of the structure with the help of an electron microscope, (1) 4*e*.
Botvinkin, O. K., Krogius, E. A., Demichev, S. A., and Vlasov, V. A. Investigation of certain properties of glasses in the system Na_2O–ZrO_2–SiO_2 (IV) reflection spectra in the infrared region, (1) 4*i*.
Botvinkin, O. K., and Lyasin, V. F. Study of the viscosity of quartz glass, (10) 266*j*.
Botvinkin, O. K., Mironova, M. L., and Mezhekova, L. I. Study of possibility of submicroscopic compatibility of porous glass with polymers and metals, (8) 211*g*.
Botvinkin, O. K., Oshchipkov, F. P., and Solinov, E. F. Investigation of the permeation of helium through certain commercial electron tube glasses, (1) 4*b*.
Botvinkin, O. K., and Solinov, E. F. Study of effect of different oxides on the diffusion of helium through silicate glasses, (7) 181*g*.
Botvinkin, O. K., and Vorob'eva, O. V. Effect of γ-radiation on certain properties of conducting films, (10) 264*g*.
Botvinkin, O. K., Vorob'eva, O. V., and Portnova, V. A. Insulating electroconducting films on glass, (9) 233*f*.
Boucher, B., Herpin, A. G., and Oles, A. Antiferromagnetism of the spinel $MnGa_2O_4$, (11) 313*d*.
Bouchet, G. Optical pyrometer having a cyclically moving detector, P (1) 17*a*.
Bough, M. O., Jr. See Zappia, A. T.
Bouquet, G. See Boksay, Z.
Bour, T. C. Method for the production of glass fibers, P (8) 213*c*.
Bourgeois, M., and Faugeras, P. F. Process of preparation of uranium compounds from uranium-molybdenum alloys, P (1) 19*a*.
Bourne, H. L. Silicon monoxide technique for observing surface microtopography, (2) 45*j*.
Bousky, S. Fiber optics code apparatus, P (9) 235*j*.
Bouteille, C. Y. J. Method and apparatus for electrostatic separation of fine powders, P (11) 309*b*.
Bouvier, G., Nemec, F., and Ulbert, P. Magnetic susceptibility of chromites, (6) 168*b*.
Bovone, L. Roller device for the painting of glass or crystal plates and of flat surfaces in general, P (5) 124*e*.
Bowdish, D. D. See McGuire, J. C.
Bowen, D. H. See Matkin, D. I.
Bower, C. See Cable, M.
Bowerston Shale Co. Palletized structure of cylindrical products, P (5) 124*i*.
Bowkett, K. M. See Ralph, B.; Ranganathan, S.
Bowler, D. L. See Pollard, J. H.
Bowman, A. L., Wallace, T. C., Yarnell, J. L., Wenzel, R. G., and Storms, E. K. Crystal structures of V_2C and Ta_2C, (3) 80*h*.
Bowman, D. C. Stress as related to physical properties of titania cover coats, (6) 146*a*.
Bowman, E. W. Annealing and decorating lehrs, P (9) 235*a*.
Bowman, J. Recent developments in basic gunning of electric furnaces, (9) 239*b*. See Neely, J. E.
Bowman, M. G. See Farr, J. D.
Bowman, R. G. Method for ceramic work in prosthetic dentistry, P (4) 103*c*.
Boyadzhieva, P. Lusters as decoration for porcelain, (2) 39*f*. Physicochemical and technological properties of clays from the Elov Dol and Svetlya (near Pernik) regions, (5) 139*g*.
Boyce, G. B. Liquid spraying apparatus, P (5) 131*b*.
Boyd, D. R., Sihvonen, Y. T., and Woelke, C. D. Method of producing ohmic contacts on semiconductors, P (5) 129*i*.
Boyd, H. Particle size reduction (III) jet pulverization, (1) 15*i*.
Boyer, N. E. Hammer press, P (4) 106*j*. See Crookston, J. A.
Boykin, O. F. Electrical resistance element and method of making the same, P (11) 305*j*.
Boynton, D. R. See Ross, J. W.
Boynton, R. S. Chemistry and Technology of Lime and Limestone, B (8) 228*e*.
Bozich, M. J. Valve construction for pneumatic handling of granular materials, P (8) 222*g*.
Bozsin, M. Air pollution abatement in the ceramic industry, (10) 292*b*.
Braat, W. C. Two Near Eastern glasses recently acquired by the Rijksmuseum van Oudheden at Leiden, (9) 230*d*.
Brace, W. F. See Walsh, J. B.
Bracker, J. See Egan, J. J.
Bradbury, B. T., Cole, J. E., Frost, B. R. T., and Lambert, J. D. B. Irradiation effects in U-C and (U-Pu)C fuel pellets, B (6) 172*b*.
Bradley, M. J. See Ferris, L. M.
Bradley, M. J., and Ferris, L. M. Hydrolysis of uranium carbides between 25° and 100° (III) uranium sesquicarbide and mixtures of the sesquicarbide with monocarbide or dicarbide, (7) 200*f*.
Bradley, M. J., Goode, J. H., Ferris, L. M., Flanary, J. R., and Ullmann, J. W. Reactions of reactor-irradiated uranium monocarbide with water and aqueous solutions of NaOH, HCl, and H_2SO_4, (3) 68*h*.
Bradley, M. J., Pattengill, M. D., and Ferris, L. M. Reactions of thorium carbides with aqueous sodium hydroxide solutions, (8) 227*h*.
Bradley, W. F. Crystal chemistry of the laminar silicates, (9) 249*a*.
Bradsell, R. H., and Bottomley, S. C. Development of the photoelectric microscope, (3) 75*j*.
Bradt, R. C. Microstructure in ceramic cutting tools, (1) 1*h*.
Brafman, O., and Steinberger, I. T. Determination of the absorption edges of ZnS polytypes by contact photography with UV, (1) 20*g*.
Bragg, R. H., Crooks, D. D., Fenn, R. W., Jr., and Hammond, M. L. Effect of applied stress on the graphitization of pyrolytic graphite, (5) 135*j*.
Brailovskii, V. B. Regularity in the change of dielectric properties of commercial electronic glasses in a wide range of temperatures and frequencies, (6) 148*f*.
Brajkowa, P. See Symowa, W.
Bramer, H. C., and Hoak, R. D. Measuring sedimentation-flocculation efficiencies, (9) 245*e*.
Bramming, C. Automatic flame regulator for glass forming and welding machine, P (10) 267*d*.
Branch, A. P. Adobe-making machine, P (4) 98*f*.
Brand, H. See Weiss, H.
Brandes, E. A. See Robiette, A. G. E.
Brandmayr, R. J., Brown, A. E., Di Vita, S., and Fischer, R. J. Method of processing ceramic type ferroelectric materials, P (10) 279*b*.
Brandt, F. R., De Glas, A. J., and Mann, C. W. Ceramic ruggedized low frequency crystal unit, P (3) 72*g*.
Brandt, M. O. Method and apparatus for forming a lens surface, P (4) 97*g*.
Brandt, W. O. Testing of frits for fast firing of glazes—progress report, (6) 157*e*.
Brandt, W. W., and Rudloff, W. Diffusion of ethane in modified synthetic zeolites, (5) 135*h*.
Branson, D. L. Kinetics and mechanism of the reaction between zinc oxide and aluminum oxide, (1) 23*f*.
Branstetter, M. W. See Sauber, C. A.
Brashnarova, A., Radkova, A., Vodenicharov, M., Karaivanov, I., and Damyanov, N. Use of quartz sands from the Elene [Bulgaria] region for glass manufacture, (2) 32*g*.
Bratton, R. E. Machine and method for making perforated brick, P (1) 11*g*.
Brau, M. See Hilton, A. R.
Brauer, G. See Baernighausen, H.; Knausenberger, M.
Brauer, J. B. Method of fabrication of a microwave delay line, P (10) 278*h*.
Braun, A. B. See Fitch, F. T.
Braun, J. H. See Lewis, E. D.
Braunwarth, V. A., Nickle, A. G., and Phillips, N. W. F. Refractory compositions and methods of preparation, P (11) 303*c*.
Bray, J. See Leger, L.
Bray, P. J. See Bishop, S. G.; Greene, A. C.; Kline, D.; Knutson, C. D.; Leventhal, M.
Bray, R. S. Dispersion hardened materials and processes therefor, P (6) 154*b*.
Brayman, J. High pressure apparatus, P (5) 131*a*.
Brazdziunas, P. See Baltrusaitis, R.
Bre, M. Vitreous body including mica in finely divided state, P (2) 43*a*.
Bre, M., and Ferault, G. Bearing, P (9) 235*f*.
Brearton, D. S. Preparation of dense uranium oxide, P (9) 241*b*.
Breck, D. W., and Acara, N. A. Crystalline zeolite L, P (2) 47*e*.
Breck, W., Cadenhead, G., and Hammerli, M. Thermoelectric powers and entropies of the hydrogen ion, (3) 87*e*.
Bredsdorff, P., Poulsen, E., and Spohr, H. Experiments on mortar bars prepared with selected Danish aggregates, (8) 207*a*.
Bredt, J. H. See Kendall, L. F., Jr.
Breedveld, C. Package for glasses or such fragile objects, P (1) 7*b*.
Breit, K. History of the Jablonec industry, (6) 144*b*.
Brekhovskikh, S. M. Methods of increasing the mechanical strength of glass, (9) 234*c*. Prospective uses of radioactive isotopes and nuclear radiation in the glass industry, (4) 95*b*.
Brekhovskikh, S. M., and Borisov, B. I. Facing materials from glass, (9) 233*a*.
Brekhovskikh, S. M., and Borisova, I. I. Resistance of metal oxide films on glass to ionizing radiation, (10) 266*f*.
Brekhovskikh, S. M., and Grinshtein, Yu. L. Melting glass under the action of gamma rays, (7) 180*i*.
Brekhovskikh, S. M., Landa, L. M., Viktorova, Yu. N., and Shelyubskii, V. I. Radiation-optical stability of quartz glass at different temperatures of irradiation with γ rays, (8) 210*i*.
Brekhovskikh, S. M., and Solinov, V. F. Faraday effect in diamagnetic glasses, (9) 233*b*.
Brekhovskikh, S. M., and Zhitomirskaya, E. Z. Radiation resistance of foam glass, (7) 181*d*.
Bretsch, M. A. Spark plug with insulator nose spaced from center electrode, P (8) 222*c*.
Bretsznajder, S., and Ziolkowski, D. Effective thermal conductivity of granular beds, (1) 8*f*.
Brett, H. H., Harper, E. A., Hedger, H. T., and Pottinger, J. S. Substitutional solubility of oxygen in UC, $(U_{0.85}\ Pu_{0.15})C$, and PuC, B (6) 171*h*.
Brett, J., and Seigle, L. Diffusion-controlled oxidation of several lanthanides, (11) 315*d*.
Breu, R. See Gaeth, R.
Brewer, L. Prediction of high temperature metallic phase diagrams, B (2) 55*g*. See Bird, G. R.
Brewer, P. G., and Riley, J. P. Automatic determination of silicate-silicon in natural waters with special reference to seawater, (11) 309*i*.
Brezina, B., and Fousek, J. Domain structure of ferroelectric barium titanate and its influence on dielectric properties, (7) 198*j*.
Brezny, B. Formation of magnesium ferrites in $MgCO_3$–$FeCO_3$ solid solutions, (6) 167*e*. System MgO–FeO–Fe_2O_3, (2) 52*j*.
Brezny, B., and Cerven, I. Quantitative determination of magnesium ferrite by measuring the magnetic moment, (11) 319*d*.
Brian, P. L. T. See Reti, A. R.
Briat, B., Billardon, M., Badoz, J., and Loriers, J. Qualitative and quantitative analysis of rare earth mixtures by means of magneto-optical rotation, (6) 162*j*.
Brice, J. C. Growth of Crystals from the Melt, B (8) 228*i*.
Brichard, E. Method of and apparatus for the thermal conditioning of molten glass before its shaping, P (4) 97*i*. Process and device for improving the thermal uniformity of molten glass, P (6) 150*j*. See Henry, G.
Bricker, C. E. See Baur, J. A.
Bricker, O. Some stability relations in the system Mn–O_2–H_2O at 25° and one atmosphere total pressure, (9) 256*a*.
Briggs, C. W. Infrared sensors aid glass melting control, (8) 209*e*.
Briggs, G., Dutta, S. K., and White, J. Phase relations in the systems U–Cr–C, U–Ni–C, and U–Fe–Cr–C, B (6) 172*a*.
Briggs, H. D. See Schultz, W. W.
Bright, N. F. H., and Turnock, A. C. Nonstoichiometric tantalian magnetites, (4) 112*d*.
Bril, A., and Laat, C. D. J. C. de. Light output of color television screens with europium-activated phosphors as a red component, (8) 220*c*.
Brill, R. H. Corinth *diatretum*, (4) 80*i*.
Brill, R. H., Fleischer, R. L., Price, P. B., and Walker, R. M. Fission-track dating of manmade glasses—preliminary results, (4) 89*h*.
Brindley, G. W. Clay-organic studies (X) complexes of primary amines with montmorillonite and vermiculite, (9) 248*i*. See Sharp, J. H.
Brindley, G. W., and Hayami, R. Kinetics and mechanism of formation of forsterite (Mg_2SiO_4) by solid state reaction of MgO and SiO_2, (3) 83*c*.
Brindley, G. W., and Moll, W. F., Jr. Clay-organic studies (IX) complexes of natural and synthetic Ca montmorillonites with fatty acids, (9) 248*f*.
Briones, R. A. See Brooks, R. E.
Brisse, F. See Knop, O.
Brissette, L. A., Burnett, P. L., Spriggs, R. M., and Vasilos, T. Thermomechanically deformed Y_2O_3, (4) 114*e*.
Brite, D. W., and Sump, K. R. Fabrication of shapes by pneumatic impaction, P (1) 11*d*.

British Aluminium Co., Ltd. Methods of breaking up sintered compacted metal bodies, P (9) 240*b*.
British Oxygen Co., Ltd. Method and electrode for electric arc welding, P (3) 60*b*.
British Plaster Board (Holdings), Ltd. Process and apparatus for continuous calcining of powdered gypsum rock, P (5) 119*d*.
British Titan Products Co., Ltd. Process for producing metal oxides, P (2) 48*c*. Process for producing silica by oxidizing silicon tetrahalides, P (9) 247*h*. Production of metal oxides, P (1) 19*b*. Vapor phase oxidation, P (7) 190*b*. Vapor phase oxidation of titanium tetrachloride, tetrabromide, or tetraiodide in the presence of a thorium source, P (9) 247*j*.
Brittain, J. O. See Carnahan, R. D.
Britten, J. S. See Blank, M.
Brixner, L. H. Stabilized zirconia composition, P (10) 275*c*. Thermoelectric compositions and methods of preparing same, P (1) 15*e*, P (3) 74*c*.
Brock, T. W., and Carter, D. L. Analysis of cords in soda-lime-silica glasses, (7) 179*f*.
Brocklehurst, J. E. See Martin, W. H.
Brockman, F. G., and Beck, P. W. Temperature-independent transducer, P (1) 15*b*.
Brockman, J. J. See Rich, E. A. E.
Brockway Glass Co., Inc. Glass tubing severing machine, P (5) 123*a*. Strengthened glass article and method of producing same, P (2) 34*i*.
Broderick, J. P. See Barr, L. C.; Keys, D. L.; Quaas, J. F.; Schilling, D. C.
Broderick, J. P., Wishnie, F. T., Keys, D. L., and Neary, F. X. Flame spraying torch, P (8) 208*d*.
Brodie, I. Vacuum breakdown in the presence of thermionic cathodes, (10) 277*b*.
Broemer, H., and Meinert, N., Technical glass, P (10) 270*a*.
Broemer, H., and Preuss, H. J. Apparatus for the accurate location of streaks in optical glass blocks, (10) 264*d*.
Brolmann, H. See Toytot, R. de.
Brombach, H. See Tillmann, P.
Brookes, C. A. See Atkins, A. G.
Brookes, C. A., and Imai, M. Frictional properties of silicon nitride and silicon carbide, B (11) 320*g*.
Brooks, L. H. See Blundell, A.
Brooks, R. E., Heflinger, L. O., Wuerker, R. F., and Briones, R. A. Holographic photography of high-speed phenomena with conventional and *Q*-switched ruby lasers, (1) 13*j*.
Brooks, W. Electroluminescent phosphors and method for making same, P (10) 278*f*.
Brooks, W. P. Shock-induced luminescence in quartz, (3) 85*e*.
Broos, J. See Boer, F. de
Broquetas Colominas, C., Ballastracci, R., and Roult, G. Study by neutron diffraction of the spinel $FeCr_2S_4$, B (2) 55*b*.
Brotzmann, K. Reactions between magnesium oxide and molten iron under reduced pressures, (6) 153*c*.
Brous, J., Conrad, W. A., and Poelstra, W. G. Method for securing structures in precise geometric relationship, P (11) 307*c*.
Browarski, I., and Karesz, J. Static characteristics in the temperature control of the combustion chamber of a glass melting tank furnace, (8) 211*c*.
Brown, A. E. See Brandmayr, R. J.
Brown, A. R. G. See Bickerdike, R. L.
Brown, A. W., and Leary, D. E. Dielectric panels, P (9) 235*i*.
Brown, B. E. See Revolinsky, E.
Brown, C. J., Jr. Method and apparatus for mixing glass batch materials, P (2) 34*a*, P (9) 236*f*.
Brown, C. S. Glass coated member, P (2) 30*g*.
Brown, D., and Douglas, R. W. "Carbon-sulfur" amber glass, (3) 60*g*.
Brown, D. G., and Tymczak, R. W. Review of high temperature materials, (6) 171*e*.
Brown, D. J. Melting and casting of uranium carbide, B (6) 172*c*.
Brown, D. N. Method and apparatus for producing glass sheet, P (6) 150*h*.
Brown, F., Dennard, F., and Ellis, P. Preparation of Ru, U, and (PuU) carbides by the metal-hydrocarbon gas reaction, B (6) 172*e*.
Brown, G. Contribution to discussion on "Role of crystal structure in solid state reactions of clays and related minerals" by G. W. Brindley, B (2) 56*d*. Significance of recent structure determinations of layer silicates for clay studies, (8) 227*c*.
Brown, G., and Weir, A. H. Addition to "Identity of rectorite and allevardite," B (2) 56*c*.
Brown, G. M. Investment molding, P (1) 11*g*. Method and apparatus for making ceramic molds, P (10) 274*d*.
Brown, G. N. Solids flow equalizer, P (1) 16*c*.
Brown, H. L. Muffler manufacturing method, P (1) 3*f*.
Brown, J. A. See Fox, W. T.
Brown, J. D. Computer program for electron probe microanalysis, (1) 16*g*.
Brown, J. J., and Hummel, F. A. Dilatometric and X-ray data for zinc compounds (II) phosphates and vanadates, (2) 49*i*. Reactions between ZnO and selected oxides of elements of groups IV and V, (2) 51*j*.
Brown, J. R., Jr. See Horan, J. J.
Brown, L. H. Method for manufacturing foundry cores and molds, P (2) 38*f*.
Brown, L. J. See Aamodt, R. L.
Brown, R. Optical method for determination of glaze thickness and substrate surface warp, (3) 76*e*. Substrates for tantalum thin-film circuits, (9) 242*e*.
Brown, R. A. Sintering in active nickel oxide, (1) 25*a*.
Brown, R. L., and Sears, G. W., Jr. Forming inorganic fiber material containing cationic starch and colloidal silica, P (3) 70*i*.
Brown, T. O., Jr. Tile machine [conveyor], P (9) 242*d*.
Brown, W. F., Mook, G. C., Jarosi, J. J., and Cunningham, E. H. Recovery of waste grinding materials, P (9) 237*b*.
Brown, W. H. Production of alumina, P (6) 164*j*.
Brown, W. H., and Hrishikesan, K. G. Process for the production of alumina, P (6) 164*j*.
Brown, W. K. See Waddell, B. L.
Browne, C. M. Method of producing multiple sheet glazing units, P (3) 64*a*.
Browning, J. A. Method of flame working materials, P (1) 18*i*.
Browning, J. S., and Bennett, P. E. Flotation of California mica ore, (3) 78*e*.
Browning, M. F. See Blocher, J. M., Jr.
Brownlow, J. M. Magnetic [ferrite] memory element, P (10) 278*b*.
Brownrigg, G. K. A. Apparatus for preparing specimens for chromatographic analysis, P (10) 281*f*.
Bruce, J. A. See Mitchell, R. F.
Bruce, R. H., and Wilkinson, W. T. Fillers for whiteware bodies, (10) 275*i*.
Bruchhausen, C. See Konopicky, K.
Bruckmayer, F. Comparison of Austrian and foreign hollow brick forms in regard to heat insulation, (2) 35*b*.
Brueckner, R. Influence of inhomogeneities on the viscosity and flow homogenization of glass melts, (5) 120*i*. Kinetics of material exchange at the interface between silicate glass and molten salts and material transport in silicate glass melts with special consideration of the behavior of Na_2SO_4 and its decomposition products (I) interfacial energy equalization processes by material exchange processes; (II) material exchange between silicate glass and molten salts, (4) 94*d*. (III) thermal and chemical decomposition of Na_2SO_4 and the material exchange between silicate glass melts and atmospheres containing SO_3, (6) 148*e*.
Brueckner, R., and Kaes, H. H. Orientation induced birefringence and structural constitution of glass melts, (10) 265*e*.
Bruegger, W. Electrical tunnel kiln for firing hard porcelain in a reducing atmosphere, (8) 224*d*. See Taesler, W.
Bruegger, W., and Taesler, W. Electric tunnel kiln in the ceramic industry, (6) 163*h*.
Brumm, C. E. See Allman, O. H.
Brunet, A. See Brunet, M.
Brunet, M., Brunet, A., and Deyris, E. Device for floating zone melting, P (5) 128*b*.
Bruns, J. G. Method of cutting glass, P (7) 184*a*.
Brunswick Industries Research, Inc. Method and apparatus for producing filaments, P (8) 213*c*.
Brush Beryllium Co. Process for producing basic beryllium material of high purity, P (9) 247*g*.
Bruthans, Z., and Jakubekova, D. Use of thermography in the study of the hardening and setting of tufaceous binders, (2) 29*d*.
Brutto, E. See Bassi, A.
Bruun, H. H., and Julsrud, E. Study of contact angles of water on solid surfaces of rosin acids of the abietic and primary series and technical rosin acids, B (7) 204*f*.
Bryan, A. R. See Spence, G. M.
Bryant, A. M. See Hilton, A. R.
Bryant, E. E. Critical look at seam welding for porcelain enameling, (11) 295*c*. Method of porcelain enameling, P (9) 232*c*.
Brymer, A. E. Apparatus for forming glass articles, P (8) 211*e*. Method for mold release during glass forming, P (8) 213*j*.
Bubenicek, J. See Hoens, M. F. A.
Bubik, I. Ceramic materials in electronics, (10) 276*h*.
Buchanan, C. S. See Kleist, D.
Buchenkova, A. F. See Maslennikova, G. N.
Buchkremer, R. Development in ceramic kiln design with respect to automation and fast firing, (2) 46*c*.
Buchner, S. Firing of ceramic-bonded grinding wheels, (6) 143*f*.
Buchwald, R. High-pressure discharge lamp inlead construction, P (2) 33*b*.
Buck, A. D., and Dolch, W. L. Investigation of a reaction involving nondolomitic limestone aggregate in concrete, (9) 231*a*.
Buck, I. E., Jr. Electroluminescent lamp with built-in rearwardly disposed input terminals, P (8) 221*a*.
Buck, I. E., Jr., and Bullinger, H. Ceramic type electroluminescent device with moisture penetration prevention seal, P (11) 305*c*.
Buckley, E. G. See Armstrong, L. D.
Buckley, F. T., and Nelson, J. S. Safety laminates, P (7) 184*g*.
Buckley, M. J. Vibrating sieve, P (10) 280*e*.
Buckminster, L. A. Lens blocks [metallic alloy], P (11) 298*c*.
Budd, S. M., and Blanchard, M. Microinhomogeneity of glass as determined from measurement of refractive index distribution, (8) 210*f*.
Budd Co. Dehydrated mica products and method of making same, P (4) 104*d*.
Budde, M. C., and Zumaquero, F. J. Art of bonding ceramic to metal, P (4) 104*i*.
Buddery, J. H. See Hilton, D. A.
Budkiewicz, M. Kaolin deposits in Poland, (7) 196*j*.
Budnick, A. S. Semiconductive devices, P (11) 307*e*.
Budnikov, P. P., Azarov, K. P., et al. Evolution of gases during the reaction of phosphate enamels with aluminum, (2) 30*e*.
Budnikov, P. P., Arelitskaya, R. D., and Prikhodchenko, N. A. Effect of small additions of electrolytes on the rheological properties of a lime suspension, (4) 90*e*.
Budnikov, P. P., and Ginstling, A. M. Reactions of Mixtures of Solid Substances, B (9) 259*j*.
Budnikov, P. P., and Kantor, Ya. M. Effective method of grinding articles made of high-alumina ceramics, (2) 43*e*.
Budnikov, P. P., and Kroichuk, L. A. Intensification of the processes of clinker formation by the use of mineralizers, (7) 178*b*.
Budnikov, P. P., Kushakovskii, V. I., and Belevantsev, V. S. Study of the systems Gd_2O_3–Al_2O_3 and Sm_2O_3–Al_2O_3, (6) 170*h*.
Budnikov, P. P., Royak, S. M., and Kroichuk, L. A. Influence of the mineralizer on the production of highly active clinker from the tailings of the processing of nepheline rocks, (1) 2*d*.
Budnikov, P. P., and Sandulov, D. B. Whisker single crystals of refractory oxides and their use, (7) 188*f*.
Budnikov, P. P., Sochackaya, G. A., and Kulygin, I. P. Crystallization behavior and some properties of fusion-cast cordierite brick, (10) 271*e*.
Budnikov, P. P., and Zlochevskaya, K. M. Synthesis of mullite-spinel ceramic and study of its properties, (9) 257*c*.
Budo, Y. See Priest, J.
Budworth, D. W. Principles of ceramic density measurement, (5) 131*e*.
Buehl, W. M. See Cowan, J. H.
Buell, H. W. See Holland, C. J.
Buerger, M. J. See Burnham, C. W.
Buerklin, H. Glass level control in a tank with an electropneumatic probe, (7) 180*c*.
Bueschenfeld, H. See Artelt, P.
Buescher, W. E. Cathode base structure, P (6) 158*g*.
Buessem, W. R., Cross, L. E., and Goswami, A. K. Effect of two-dimensional pressure on the permittivity of fine- and coarse-grained barium titanate, (2) 49*h*. Phenomenological theory of high permittivity in fine-grained barium titanate, (2) 40*f*.
Buessing, D. Influence of surface damage on the internal pressure resistance of bottles, (4) 93*j*.
Buetter, H. Flexosmalt—a technique for enameling sheet steel without a ground coat, (10) 263*e*.
Bugl, J., and Keller, D. L. Uranium mononitride—a new reactor fuel, (3) 69*d*.
Building Research Institute, Building Materials Section. Relation between impermeability of activated slag concrete and its pore structure, (8) 207*g*.
Bukhalova, G. A. See Mateiko, Z. A.
Bukhalova, G. A., and Berezhnaya, V. T. Fusibility diagram of the ternary system of the chlorides of potassium, calcium, and barium, (4) 111*e*. Quaternary system—the fluorides and chlorides of potassium, calcium, and barium, (9) 254*h*.
Bukhalova, G. A., and Maslennikova, G. N. Stable cross sections of the tetrahedron of the system Na^+, K^+, Ca^{2+}, Ba^{2+}||F^-, Cl^-, (1) 25*e*.
Bukhalova, G. A., Maslennikova, G. N., and Rabkin, D. M. Ternary reciprocal system of the chlorides and hexafluoroaluminates of sodium and potassium, (4) 113*g*.
Bukhalova, G. A., and Mateiko, Z. A. Topological analysis of the quaternary reciprocal system Na,Ca,Ba,||F,Cl, (10) 291*e*.
Bukhalova, G. A., Mateiko, Z. A., and Berezhnaya, V. T. Fusibility diagram of the ternary systems of the fluorides of sodium, potassium, strontium, and barium, (4) 111*f*.
Bukhanevich, V. F. See Lyutaya, M. D.
Bukovszky, F. Elementary calculations of the Madelung constants of some cubic lattices, (6) 167*i*.
Buleza, D. S. Electroluminescent devices and materials, P (1) 14*j*.
Bull, G. H. See Wood, A. A.R.
Bull, G. H., Timms, P. L., and Wood, A. A. R. Abrasion resistant materials, P (8) 216*j*. Abrasion resistant material bonding process using boron alloys, P (8) 216*j*.
Bull, R. W. See Bell, K. R.
Bullinger, H. See Buck, I. E., Jr.
Bundy, A. J. Glass pallet package, P (11) 298*h*.
Bundy, F. P. Method for converting hexagonal boron nitride to a new structure, P (1) 11*h*.
Bundy, F. P., and Wentorf, R. H., Jr. Boron nitride having a new structure, P (1) 10*h*.
Bunge, R. A. Cantilever structure for furnace roof, P (6) 154*i*.
Bunger, W. See Maeder, H. J.
Bunn, J. P., and Ward, L. Effect of pipeline outgassing in the vacuum pumping equation, (2) 44*e*.
Buntpapierfabrik, A. G. Decoration of ceramic ware, P (2) 40*d*.
Bunzen, K. Examination of various opacification systems in powdered white enameling frits, (7) 178*h*.
Burak, N., and McAnespie, P. Method of making calcium silicate materials, P (5) 126*g*.

Burch, O. G. Apparatus for melting glass, P (1) 6*d*.

Burdick, G. A., Miller, R. C., and Bartels, B. E. Performance of europium-activated phosphors in color picture tubes, (8) 220*d*.

Burdick, M. D. Progress report on a test for cleanability, (7) 179*b*. Standard test for determining alkali resistance of porcelain enamels, (6) 146*d*. See Rushmer, M. A.

Bureau d'Etudes Industrielles Fernand Courtoy S.A. Improvements in the joining of ceramics, cermets, alloys, and metals having different coefficients of expansion, P (9) 243*g*.

Burfoot, J. C. See Parker, T. J.

Burfoot, J. C., and Parker, T. J. Movements of transition fronts in barium titanate, (5) 139*a*.

Burg, F. J. Banded glass container constructions, P (6) 149*d*.

Burggraaf, A. J. Sorption of argon by glass in a gas-discharge lamp, (9) 234*f*.

Burgman, J. A., and Margason, L. L. Method and apparatus for forming hollow glass fibers, P (10) 268*f*.

Burgos, M. E. See Gergely, G.

Burgyan, A., and Votava, W. Gray ceramics containing a calcined mixture of aluminum and vanadium compounds, P (11) 304*b*.

Burian, R. J. See Townley, C. W.

Burke, O. W., Jr. Silica pigments and preparation thereof, P (7) 197*a*.

Burke, O. W., Jr., and Jackson, C. B. Apparatus for the production of silica pigments, P (8) 225*a*. Silica pigments and preparation thereof, P (7) 197*a*.

Burke, W. J. Apparatus for drawing glass sheet, P (5) 122*e*.

Burkert, G. M. See Nickerson, J. D.

Burko, J., Pigeot, A., Jouannaud, C., and Nollet, P. Method of preparing uranic oxide in granulated form, P (1) 11*d*.

Burley, G. Experimental atomic scattering factors for magnesium oxide, (10) 286*c*.

Burlington Industries, Inc. Process for dulling glass fibers with oxalic acid, P (9) 237*b*.

Burma, M. Spark machining electrode, P (1) 12*d*.

Burnett, J. L. Expansible shale resources of the San Jose-Gilroy area, California, (7) 196*h*.

Burnett, P. L. See Brissette, L. A.

Burnett, R. W., and Turnbull, W. T. Industrial applications of molecular sieves, (7) 190*d*.

Burnham, C. W. See Hamilton, D. L.

Burnham, C. W., and Buerger, M. J. Refinement of the crystal structure of andalusite, (3) 85*i*.

Burnham, J. B., Skavdahl, R. E., and Chikalla, T. D. Plutonium bearing refractory carbides, B (6) 171*j*.

Burns, E. A. See Blumenthal, J. L.

Burns, G., Giess, E. A., and Blazey, K. W. *a-c* exchange in the garnets, (11) 313*b*.

Burns, G. W., and Gallagher, J. S. Reference tables for the Pt-30 percent Rh versus Pt-6 percent Rh thermocouple, (9) 245*h*.

Burns, J. H. Crystal structure of hexagonal sodium neodymium fluoride and related compounds, (6) 166*b*.

Burns, N. H. See Perry, E. S.

Burov, G. V. See Neuimin, A. D.

Burrage, L. M., and McStrack, D. D. Fuse with hydrated arc extinguishing material, P (4) 104*i*. Lightning arrester valve element and method for making the same, P (1) 14*f*.

Burroughs, F. H. Composite adsorbent filter body, P (5) 127*e*.

Burroughs, J. E. See Howeth, M. S.

Burroughs, J. E., and Thornton, H. R. Refractory aerospace structural components by plastic molding process, (3) 68*j*.

Burrowes, C. Method of aligning fibers of a multiple fiber bundle, P (8) 212*h*.

Bursich, J. M. See Shorr, N.

Burton, E. Ceramic industry in Sweden, (10) 292*c*. Designers of Swedish ceramics, (10) 261*h*. Far Eastern Museum in Stockholm, (8) 206*a*.

Burvys, J., and Buskunas, P. Effect of dispersed additives on the quality of dolomitic limestone concrete, (6) 144*d*.

Burwell, B. Flotation concentration of nonmetallic minerals containing calcite, P (7) 196*i*.

Burwell, R. L., Jr., Pearson, R. G., Haller, G. L., Tjok, P. B., and Chock, S. P. Adsorption and reaction of coordination complexes on silica gel, (3) 79*g*.

Burykina, A. L., and Evtushenko, O. V. Vacuum diffusion welding of metallic carbides to high-melting metals, (7) 179*d*.

Burykina, A. L., and Evtushok, T. M. Contact interaction of metal-like carbides with graphite at high temperatures in a vacuum, (3) 65*j*.

Burzynski, A. J., and Martin, R. E. Process for forming spherical silica beads, P (9) 241*d*.

Busby, T. S., and Barker, J. Simulative studies of upward drilling, (9) 234*e*.

Busche, M. G. New materials applications, (4) 108*i*.

Busen, K. M., and Linzey, R. Removal of thin layers of *n*-type silicon by anodic oxidation, (7) 192*e*.

Bush, E. G. W. Cementitious composition and method of preparation, P (5) 119*e*.

Bush, H. D. Bonding of refractory materials by means of cerium oxide-cerium sulfide mixtures and product. P (5) 125*h*.

Bush, P. W. Reduce major appliance shipping damages, (8) 208*c*.

Buskunas, P. See Burvys, J.

Buslaev, Yu. A. Constants of instability of complex fluorides of zirconium, (4) 110*c*.

Buss, W. Hot-stage microscope study of processes in glass melting with and without sulfate, (6) 148*a*.

But, A. I. See Rabinovich, A. E.

Buteau, L. J., Jr. See Kronsbein, J.

Butler, J. F. See Besson, J. M.

Butler, M. F. Strengthened cathode ray tube, P (4) 98*b*.

Butler, R. S. Method and apparatus for separating conducting and nonconducting particles, P (6) 161*e*.

Butt, Yu. M., and Timashev, V. V. Portland cement clinkers with given crystalline structure and the production of high-quality cements from them, (7) 178*d*.

Butterworth, B. Absorption of water by clay building bricks (IV) effect of weathering on rate of absorption, (7) 184*j*.

Buxton, K. See Childs, B. G.

Buyers, A. G., and Mohr, A. J., Jr. Ceramic-metal seal, P (8) 220*c*.

Buzdov, K. A., and Vlasov, V. V. Nature of the products of thermal dissociation of the solid solutions of the carbonates of iron and manganese, (1) 23*b*.

Buzhinskaya, A. V. See Gul'din, I. T.

Buzzell, B. R. Wear indicating surfacing device, P (6) 143*j*.

Bychkov, V. Z. See Timofeeva, V. A.

Byers, A. M., Co. Gaseous and liquid fuel industrial furnace burner, P (6) 164*a*.

Byfield, D. R. See Reintjes, G. P.

Byington, R. L. Kiln for rapid firing single layers of ceramic articles, P (11) 311*g*.

Bykov, V. V. See Dyatlova, O. N.; Savonichev, G. V.

Byler, W. H. See MacHutchin, J. G.

Byrne, T. J. See Wiegert, R. E.

Byteva, I. M. Effects of pH on the shape of ammonium dihydrogen phosphate crystals, B (11) 319*k*.

Cable, M. Kinetics and mechanisms of fining glasses, (9) 233*i*. See Bhuiyan, M. M.; Rasul, C. G.; Varshneya, A. K.

Cable, M., and Bower, C. Homogeneity of small-scale laboratory glass melts, (3) 61*g*.

Cabot Corp. Measurement of surface areas of solids, P (1) 17*d*. Titanium dioxide pigments, P (1) 19*b*.

Cade, P. J. Ultraviolet detector, P (2) 43*c*.

Cadenhead, G. See Breck, W.

Cadle, R. D. Particle Size—Theory and Industrial Applications, B (9) 259*h*.

Cadoff, I. B. See Manasevit, H. M.

Cadoff, L. H. See Adelsberg, L. M.

Cady, W. G. Piezoelectricity, an Introduction to the Theory and Applications of Electromechanical Phenomena in Crystals (Vols. I, II), B (8) 228*j*.

Caggiano, A. J. Fabrication of barrier material devices, P (3) 73*c*.

Cahn, J. W., and Charles, R. J. Initial stages of phase separation in glasses, (2) 31*h*.

Caillat, R. See Boghen, J.

Caillere, S., Henin, S., and Besson, H. Formation of phyllites by direct attack of different minerals, (7) 199*g*.

Cala, C. F. Apparatus for homogenizing glass, P (10) 267*j*. Process and apparatus for making homogeneous gas-free optical glass, P (6) 150*i*.

Calabra, A. E. Mounting metallographic specimens for edge retention, (9) 245*f*.

Calabria, G. Process and apparatus for improving the resistance of porous refractory materials to corrosive action, P (8) 218*c*.

Calawa, A. R. See Besson, J. M.

Caldwell, O. G. Ceramic adhesive composition, P (11) 302*a*.

California Portland Cement Co. Cement sack pallet and handling equipment, P (4) 91*a*.

California Research Corp. Method of preparing improved magnetic material of controlled particle size, P (2) 42*d*.

Callaby, D. R. Domain wall velocities and the surface layer in $BaTiO_3$, (3) 81*e*. Surface layer of $BaTiO_3$, (9) 257*b*.

Callard, C. See Magnier, P.

Callister, W. D., Jr., Cutler, I. B., and Gordon, R. S. Thermal decomposition kinetics of boehmite, (9) 257*h*.

Calvet, R., Chaussidon, J., Cloos, P., Kimpe, C. de, Fripiat, J. J., Gastuche, M. C., Helsen, J., Jelli, A., Leonard, A., Poncelet, G., and Uytterhoeven, J. Protons of constitution, free protons, and adsorbed water, (8) 227*d*.

Calvi, M. C. Glass cup by Aristeas in the Strada collection, (5) 118*c*.

Camagni, P., and Manara, A. Steady-state excess conductivity during plastic deformation of alkali halides, (7) 202*e*.

Camarda, F. V. See Kalousek, G. L.

Camazano, M. S. See Sanchez Camazano, M.

Cameron, E. N., and Carpenter, R. H. Photometric measurement of rotation properties, (9) 253*i*.

Cameron, N. M. Influence of tensile stress during heat treatment on the thermal weakening of glass fibers, (2) 31*h*. Relation between melt treatment and glass fiber strength, (4) 95*d*.

Campana-Ros, J. See Kroeger, C.

Campbell, F., Jr. See Ulmer, G. C.

Campbell, F. A. See Maiklem, W. R.

Campbell, I., and Loofbourow, J. S., Jr. Geology of the magnesite belt of Stevens County, Washington, (9) 247*e*.

Campbell, J. G., and Ford, A. R. Graphite for hot-pressing dies, (5) 130*f*.

Campbell, J. K. Glass cloth, P (10) 268*a*. Method of pigmenting glass cloth with silanes, P (6) 150*c*.

Campbell, W. B., Alford, W. J., and Hobbs, H. A. Preliminary investigation of nonreactive body compositions, (6) 156*f*.

Campbell, W. W. See Pack, A. H.

Campion, P. See Walker, J. A. J.

Canadian Refractories, Ltd. Grooved refractory brick construction, P (8) 217*c*.

Candelise, A., and Whaley, J. A. Spark plug with visual indicating discharge bulb, P (6) 161*c*.

Canfield, S. A. Feeder for melting glass spheres for fiber drawing, P (7) 182*h*. Method and apparatus for producing bonded fibrous products, P (11) 298*g*. See Roberson, C. L.

Cannaday, S. S. Wire coating apparatus, P (9) 232*f*.

Canrad Precision Industries, Inc. Electroluminescent zinc sulfide of optimum luminosity per gram, P (9) 243*c*.

Cape, A. T. Powder melting torch, P (3) 60*b*.

Capell, R. G., and Granquist, W. T. Cracking catalyst and process of cracking, P (8) 225*b*.

Capellaro, D. F. See Kapany, N. S.

Capita, E. R. Apparatus for vapor plating, P (5) 128*f*.

Capps, F. R. Sand molds for metal casting and methods therefor, P (1) 12*c*.

Caprio, M. J., and Krisleit, R. F. Fibrous refractory, P (11) 302*d*.

Caracciolo, E. A. Packaged electronic device, P (9) 243*j*.

Carborundum Co. Abrasive articles with iron sulfide and potassium aluminum fluoride filler, P (7) 177*h*. Bonded boron nitride, P (6) 158*f*. Flexible abrasive coated cloth, P (5) 117*f*. Method of making submicron size nitrides and carbides, P (5) 126*j*. Method of removing surface irregularities from metal articles, P (6) 143*h*. Neutron shielding using a composition comprising graphite, boron carbide, and carbonized residue, P (4) 101*a*. Refractory bodies and method of making same, P (7) 189*h*. Refractory carbide bodies and method of making them, P (8) 224*h*. Refractory composition, P (4) 102*b*. Resilient-backed abrasive stone, P (4) 89*g*.

Carden, R. L. Thermal stress effects in enameled cast iron, (10) 263*e*.

Cardwell, J. G. Electric incandescent lamp with integral fuse, P (1) 6*g*.

Carithers, V. G. See Armbrust, B. F., Jr.

Carithers, V. G., Adkins, F. E., Jr., Lippman, A., Jr., Royce, D. V., Jr., and Hrishikesan, K. G. Process for producing substantially kappa-phase alumina, P (4) 109*f*.

Carl Strutz & Co., Inc. Bottle decorating apparatus, P (8) 212*b*. Method and apparatus for decorating bottles, P (3) 63*f*.

Carley-Macauly, K. W., Myles, J. W., and Williams, G. H. Coating of uranium carbide particles in a fluidized bed, B (6) 172*h*.

Carlsen, F. L., Jr., Bomar, E. S., and Harms, W. O. Development of fueled graphite containing pyrolytic-carbon-coated carbide particles for nonpurged gas-cooled reactor systems, (3) 66*g*.

Carlson, E. T. Some properties of the calcium aluminoferrite hydrates, (11) 294*c*.

Carlson, R. J., Porembka, S. W., and Simons, C. C. Explosive compaction of ceramic materials, (4) 106*i*.

Carlson, W. G. See Tien, Tseng-ying.

Carman, J. N. Semiconductor device, P (9) 244*b*.

Carman Laboratories, Inc. Semiconductor device, P (9) 244*b*.

Carnahan, R. D., and Brittain, J. O. Dislocation damping in rutile single crystals, (2) 49*j*. Low-temperature internal friction peak in rutile, (9) 251*b*.

Carnall, E., Jr., and Hatch, S. E. Magnesium oxide infrared transmitting optical elements, P (5) 123*g*.

Carney, D. E. See Davis, C. W., Jr.; O'Connell, T. B.

Carney, D. E., and Gartz, C. A., Jr. Method and apparatus for melting glass, P (10) 268*j*.

Carniglia, S. C. Petch relation in single-phase oxide ceramics, (1) 24*b*. Single crystal and dense polycrystal uranium carbide—thermal, mechanical, and chemical properties, B (6) 172*a*.

Caron, L. G. See Newnham, R. E.

Caron, L. G., Santoro, R. P., and Newnham, R. E. Magnetic structure of $CaMnSiO_4$, (5) 138*d*.

Carpenter, F. D., and Yang, L. Refractory material, P (10) 274*j*.

Carpenter, J. C. Hot top refractory and/or exothermic unit, P (2) 38*a*.

Carpenter, J. H. Slotted cylindrical electrode electrostatic separator, P (9) 245*a*.

Carpenter, R. H. See Cameron, E. N.

Carpenter, W. E. Colored sealed beam lamp and method of making the same, P (11) 297*i*.

Carr, B., Guidry, H. L., and Hyde, J. R. Process for preparing microspheroidal silica, P (6) 164*j*.

Carr, K., Evans, J. L., Leonard, L. A., and Richardson, H. M. Study of oxygen converter linings (I) lining performances and steelmaking processes; (II) laboratory examination of refractory materials, (3) 69*d*.

Carrier, R. M., Jr. Apparatus for transporting material by compound motion, P (5) 130*h*.
Carrier Corp. Method of assembling a ceramic lined water heater, P (11) 296*d*.
Carrier Mfg. Co. Apparatus for transporting material by compound motion, P (5) 130*h*. Vibratory screw feeder, P (1) 16*e*.
Carrison, L. C. See Sclar, C. B.
Carroll, D. F. See Mills, L. E.
Carroll, J. W. Effect of synthetic wetting agents on subsequent pickling operations, (8) 207*h*.
Carroll, R. M., and Sisman, O. In-pile fission-gas release from single crystal UO_2, (3) 67*j*.
Carson, F. J. Method for bending and tempering glass sheets, P (10) 268*e*. See Caswall, R. D., Jr.; Leflet, H. A., Jr.; Ritter, G. F., Jr.
Carson, F. J., and Leflet, H. A., Jr. Apparatus for bending glass sheets, P (4) 96*f*. Apparatus for bending glass sheets with an outrigger support, P (3) 62*e*. Method for bending glass sheets, P (9) 236*i*. Method of bending glass sheets with a compressional zone, P (4) 97*j*.
Carson, F. J., and Stickel, A. Glass sheet bending apparatus with guide means, P (4) 96*j*.
Carson, F. J., and Wampler, D. M. Bending mold for bending glass sheets with heat distributor, P (11) 297*f*.
Carson, R. W. Plasma arc jet—hottest thing in testing, (5) 131*d*.
Carter, D. L. See Brock, T. W.
Carter, G. See Erents, K.; Grant, W. A.
Carter, G., and Grant, W. A. Ion bombardment of glass, (9) 233*g*.
Carter, G., and Hodgkins, C. E. Ceramic capacitor and method of making the same, P (3) 72*g*.
Carter, J. A. Permeable mold materials, (4) 102*e*.
Carter, J. R. See Kestigian, M.
Carter, J. W. Adsorption, solids drying, and membrane penetration, (11) 308*f*.
Carter, R. E. Process for sealing vacuum-tight spinel bodies, P (6) 160*b*. See Rhodes, W. H.; Simpson, L. A.
Carter, W. B. Preparation of eta alumina by water hydrolysis, P (10) 283*d*.
Carvelas, J., Vesper, R. M., and Weichardt, H. H. Microwave modulator using single crystal ferrite [sphere], P (5) 129*b*.
Casciani, F., Bauman, H. D., and Williams, R. S. Manufacture of calcium carbonate, P (10) 283*b*.
Caserta, R. T. Grinding wheel, P (7) 177*h*.
Cass, T. R., and Washburn, J. Dislocation etch pits on {110} planes of magnesium oxide, (7) 198*g*.
Cassaday, H. L., House, O. F., and Ryley, J. F. Method of strengthening delivery points and stems of laboratory glassware, P (9) 236*g*.
Casson, M. New gas kiln, (9) 230*e*.
Castellion, G. A. Semiconducting materials, P (1) 15*h*.
Castelliz and Sutarno, L. See Knop, O.
Castells, A. F. Particle size control of nonplastic materials, (2) 44*g*.
Caswall, R. D., Jr., and Carson, F. J. Apparatus for bending and tempering glass sheets, P (5) 122*c*.
Caswell, H. L. See Priest, J.
Catalano, E. See Lee, K.
Catchpole, C. Isostatic pressing, (5) 130*g*.
Cater, E. D., Rank, E. G., and Thorn, R. J. Vaporization and thermodynamic properties of uranium sulfide and oxysulfide, B (6) 175*c*.
Caterpillar Tractor Co. Mold wash composition and casting mold coated therewith, P (1) 11*h*.
Catherall, D., Stewartson, K., and Williams, P. G. Viscous flow past a flat plate with uniform injection, (7) 203*f*.
Caveney, R. J. Experimental study of vapor-grown CdS crystal platelets, (3) 81*h*.
Cecil, T. A. See Allegrini, A. P.
Celotex Corp. Method of making a porous ceramic product, P (11) 300*e*. Molded mineral fiber acoustical tile, P (7) 189*a*.
Central National de la Recherche Scientifique. Methods of using plasma torches for treating powdery refractory materials, P (9) 246*i*. Spark machining electrode, P (1) 12*d*.
Cepulyte, V. Stratigraphic arrangement of quaternary deposits in Kaunas [Lithuania] area, (6) 164*c*.
Certa, A. J., and Watkins, A. E. Method for fabricating a rectifying connection to a body of *n*-type germanium, solder, and semiconductor device, P (6) 159*h*.
Certain-Teed Fiber Glass Corp. Oven for curling resin impregnated fibrous mat, P (6) 150*f*.
Cerven, I. See Brezny, B.
Cesa, B. Steam dryer for brick with recovery of hot and humid air for preliminary treatment of clay, P (9) 246*j*.
Cesbron, F. New data on chervetite, (9) 252*b*.
Chabelska, E. Possibility of purifying domestic glass sands by flotation, (4) 94*f*.
Chadwick, J. R. See Baker, J. M.
Chaignon, R. See Alfille, L.
Chain Belt Co. Apparatus for conveying powdery material [by vibration], P (4) 106*i*.
Chaklader, A. C. D., and McKenzie, L. G. Reactive hot-pressing of clays and alumina, (10) 290*e*.
Chakrabarty, M. R. See Van Loan, P. R.
Challis, L. J., and Williams, D. J. Phonon scattering by paramagnetic ions in magnesium oxide, (8) 226*g*.
Chamberlin, R. R. Effects of substrate on films of chemical spray deposited CdS, (9) 242*h*.
Champion, A. R., and Drickamer, H. G. Effect of high pressure on the compressibility of four cubic carbides, (11) 316*c*.
Champion Spark Plug Co. Spark plug with conical seat sealing washer, P (4) 106*a*. Spark plug with insulator nose spaced from center electrode, P (8) 222*c*. Spark plug seal, P (7) 194*c*.
Chan, K. M., and Riley, J. P. Automatic determination of fluoride in seawater and other natural waters, (11) 309*h*. Determination of vanadium in sea and natural waters, biological materials, and silicate sediments and rocks, (6) 166*f*.
Chandler, W. T. See Walter, R. J.
Chandley, G. D. Method for improving grain structure and soundness in castings, P (7) 188*g*.
Chandley, G. D., and Blazek, W. S. Method and pattern material [Se + S] for precision investment casting, P (9) 240*c*.
Chandrashekhara, K. See Iyengar, K. T. S. R.
Chang, Chi-yuan. See Ke, Wen-min.
Chang, H. C., and Kroko, L. J. Apparatus for and preparation of silicon carbide single crystals P (11) 311*h*.
Chang, Hwei-min, Liu, Fu-yu, and Hsu, Hsiao-pai. Comparison of methods for preparing Ce_2S_3 and CeS, (6) 164*f*.
Chang, Kung-jui, and Liu, Chu-lin. Flint-containing limestone used as a raw material for portland cement, (2) 28*f*.
Chang, L. L., and Howard, W. E. Surface inversion and accumulation of anodized InSb, (10) 291*d*.
Chang, L. L. Y. Subsolidus phase relations in the systems $BaCO_3$–$SrCO_3$, $SrCO_3$–$CaCO_3$, and $BaCO_3$–$CaCO_3$, (2) 52*d*. See Phillips, B.
Chang, L. L. Y., Scroger, M. G., and Phillips, B. Alkaline-earth tungstates—equilibrium and stability in the M–W–O systems, (8) 226*a*.
Chang, R. Conductivity anomaly associated with the glass transition in vitreous selenium, (6) 165*e*. See Graham, L. J.
Chang, Ru-chao. See Shen, Chi-yu.
Chang, Sheng-yuan, Thu, Tien-min, Chiang, Pai-ming, and Ku, Gen-sheng. Fluorescent uranium glasses, (6) 147*h*.
Chantrell, P. G., and Popper, P. Inorganic polymers and ceramics, B (11) 320*c*.
Chantret, F. See Bariand, P.
Chapman, G. C. Apparatus for forming solid glassware in a carbon die, P (10) 267*i*.
Chaporova, I. I. See Baskin, M. L.
Charles, R. J. Glass bodies and methods of treatment thereof, P (11) 298*e*. Metastable liquid immiscibility in alkali metal oxide-silica systems, (3) 83*e*. See Cahn, J. W.; Hillig, W. B.
Charleston, R. J. Glass "cakes" as raw material and articles of commerce, (2) 27*i*. Wheel engraving and cutting—some early equipment (I) engraving, (4) 90*c*; (II) waterpower and cutting, (5) 118*d*.
Charlesworth, D. Roman square bottles, (9) 230*f*.
Charlton, R. J. See Hockin, J.
Charpentier, M. See Levecque, M.
Charvat, F. R. Spall resistant refractory brick, P (5) 127*a*.
Chase, A. B. Habit modification of corundum crystals grown from molten PbF_2–Bi_2O_3, (6) 167*i*. See Janowski, K. R.; Lefever, R. A.
Chase, A. B., and Wilcox, W. R. Elimination of inclusions from flux-grown crystals, (9) 247*d*.
Chatterjee, B. K. New technique for preparing polished thin sections of heavy mineral residue, (8) 223*c*.
Chaussidon, J. See Calvet, R.
Chazal, L. E. M. de. See Hyun, Kun Sup.
Chazalon, R., Bertaut, E. F., and Duc, Tran Qui. Structural parameters of orthorhombic rare earth rhodites, (6) 170*e*.
Chebotin, V. N. See Neuimin, A. D.
Cheever, G. D., Rummery, F. O., and Richards, J. D. Manufacture of rutile TiO_2, P (2) 47*g*.
Chegwidden, R. A. See Cohen, H. M.
Chelini, J. M., Smith, R. I., and Lawson, D. C. Progress report on clays and shales of Montana 1962–1964, (8) 225*g*.
Chelko, A. See Johnston, W. D.
Chemetron Corp. Method of preparing an extended catalyst composition consisting of cobalt oxide, molybdenum oxide, and alumina, P (1) 18*j*.
Chemical and Aerospace Products, Inc. Method and means for etching glass and glass reinforced plastics, P (10) 269*g*.
Chemically Prestressed Concrete Corp. Expansive and shrinkage-compensated cements, P (8) 207*d*.
Chemicals & Phosphates, Ltd. Process for the production of magnesium fluoride, P (9) 247*i*.
Chem-Met-Andersen Engineering Co. Windbox cooler for a bottle machine split mold, P (5) 124*d*.
Chemtree Corp. Radiation shielding composition comprising carbon and lead dispersed in cement, P (1) 3*c*.
Chen, Jia-ping, Fan, Ming, and Huang, Ching-kuen. Preparation and determination of immersion liquids of high refractive indices between 1.74 and 2.50, (6) 162*e*.
Chen, Sho-hsian, and Huang, Hsi-huai. Yellowish orange glass colored by CeO_2 and TiO_2, (3) 62*c*.
Chen, W. K., and Swalin, R. A. Studies on the defect structure of α-Nb_2O_5, (9) 256*h*.
Chen, Y. S. See Allen, J. W.
Chen, Yu-ying. See Wang, Chang-wen.
Cheng, Chang-ying. Electrical properties of glasses in the ternary system Na_2O–RO–SiO_2, (3) 61*e*.
Cheng, D. C. H. Cone-and-plate viscometry—explicit formulas for shear stress and shear rate and the determination of inelastic thixotropic properties, (5) 134*c*.
Cheng, D. C. H., and Evans, F. Phenomenological characterization of the rheological behavior of inelastic reversible thixotropic and antithixotropic fluids, (3) 84*a*.
Cheng, Jie-jian, Sun, Fan-min, and Huo, Gun-tsuan. Effect of heat treatment on the elastic properties of glasses, (6) 147*i*.
Cheng, Kai-jia, and Deng, Hsien-yuan. Influence of La^{3+} on the properties of barium titanate ceramics, (8) 220*b*.
Cheng, Shue-hai. Constitution and properties of glass-bonded mica, (2) 40*f*.
Cheng, Sun, and Min, Syu-kwei. Study of glass-ceramics in the system ZnO–Al_2O_3–SiO_2, (8) 211*e*.
Cheng, Tie-jian, and Fan, Chi-yao. Silicone treatment of glass surfaces, (5) 121*a*.
Chepizhnyi, K. I. Dislocations in quartz crystals, (11) 315*g*.
Cherepanov, A. M. High temperature inorganic coatings for modern technology, (7) 178*i*.
Cherepova, O. V., Sakharova, N. A., Golik, E. M., Parnovskii, L. K., and Gumenyuk, E. L. Colored glazed tile with light shades, (2) 39*d*.
Chernin, M. A., and Leppelmeier, E. T. Reflector fluorescent lamp, P (11) 307*b*.
Chernyak, M. G., Blokh, K. I., Aliev, A. I., and Kapustkin, D. M. Study of glass currents in electric furnaces for producing glass fiber, (9) 235*a*.
Chernyak, M. G. and Zubova, S. K. Change in strength of glass filaments during aging, (6) 147*c*.
Chernyakov, R. G. See Barteney, G. M.
Cherpak, A. G. and Kamyshanskii, I. P. Typical plant layout for the production of keramzit, (11) 294*i*.
Chervenkova, N. See Gerasimov, E.
Chevron Research Co. Combustion chamber liner for well gas and air burner, P (3) 70*f*.
Chiang, Chung-hung. See Kan, Fu-hsi.
Chiang, Pai-ming. See Chang, Sheng-yuan.
Chiao, Hung-ke. See Shen, Chi-yu.
Chiba, H. See Kubota, B.
Chicago Aerial Industries, Inc. Composite supported fiber optic strip, P (11) 298*a*.
Chicago Fire Brick Co. Cantilever structure for furnace roof, P (6) 154*i*. Power press process for forming lightweight refractory articles and articles so made, P (10) 274*a*.
Chicago Pottery Co. Toilet construction, P (5) 127*j*.
Chien, Ju-chung, Hu, Hui-chung, and Wang, Chao. Research on the resonant motion of grinding media in a vibration mill, (5) 130*i*.
Chikalla, T. D. See Burnham, J. B.
Chikawa, Jun-ichi. X-ray observation of moire patterns with superposed CdS crystals, (10) 291*j*.
Chikova, N. N. See Belyaev, I. N.
Childree, H. T. Burner assembly, P (11) 311*j*.
Childs, B. G., Ruchman, J. C., and Buxton, K. Radiation damage in UC, UC_2, and U_2C_3, B (6) 172*b*.
Ch'in, N. C. H., Reeg, C. P., and Waldorf, D. M. Pretreatment of pelleted zeolites to improve crushing strength, P (6) 155*g*.
Chinmulgund, N. D. See Bhide, V. G.
Chirnside, R. C., and Proffitt, P. M. C. Rothschild Lycurgus cup—analytical investigation, (2) 27*j*.
Chiron, B. P. Temperature compensated reciprocal ferrite phase shifter, P (11) 308*a*.
Chironis, N. P. Changes in strain gages, (2) 30*b*.
Chisholm, C. G., Fritzlen, G. A., and Leach, E. M. Gas turbine nozzle vane and like articles, P (2) 37*g*.
Chisholm, H. E. Method of producing magnesium hydroxide having variable particle sizes, P (5) 133*i*.
Chistyakov, Yu. D., and Lainer, B. D. Oriented overgrowth (epitaxis) of crystalline materials, B (11) 320*e*.
Chitayat, A. K. Fiber optical image enhancement device utilizing polarized synchronous motors, P (2) 33*h*. Fiber optics image enhancement means with image rotation, P (2) 33*i*.
Chizhikov, D. M. See Berezkina, L. G.
Chizhova, A. S. See Demkina, L. I.
Chloride Electrical Storage Co., Ltd. Lead oxide mills, P (1) 18*g*.
Cho, S. Comparative study of four kinds of SiC nozzles, (9) 237*j*. Prolongation of the life of basic brick for open-hearth furnace roofs by decreasing its porosity, (8) 216*e*. Results of using cased brick made of waste basic brick in the hearth of an open-hearth furnace, (7) 187*e*.
Chock, S. P. See Burwell, R. L., Jr.
Choh, Hsien Li. Low friction material, P (3) 70*a*.
Choi, D. M. See Kriegel, W. W.
Chopoorian, J. A. Photochromic cement, P (2) 29*i*.
Chopoorian, J. A., and Loeffler, K. O. Impregnated porous photochromic glass, P (11) 298*j*.
Chopra, S. K. See Dave, N. G.
Chopra, S. K., Lal, K., and Ramachandran, V. S. Gas producing agents in the production of lightweight aggregates, (9) 237*f*.
Choshi, I. See Kato, E.
Chou, Tsai-lu. See Wei, Fan-chun.
Chou, Yu-hwa, and Huang, Hsi-huai. Colors of glasses produced by Cu_2O, (3) 60*e*.
Choudhuri, A. K., and Roy, S. K. D. Hall mobility of tellurium films deposited on $BaTiO_3$ crystals, (2) 50*g*.

Chown, J. See Billington, S. R.

Christen, D. L., Cipriani, C. C., and Russell, R. G. Method of forming small glass envelopes, beads, and the like, P (2) 34*f*.

Christensen, A. N., and Rasmussen, S. E. Ferroelectric chloride - of perovskite type-crystal structures of $CsGeCl_3$, (1) 21*a*.

Christensen, F. L., and Frear, L. Abrasive cutting devices and method of making the same, P (3) 57*f*.

Christensen Diamond Products Co. Abrasive cutting devices and method of making the same, P (3) 57*f*.

Christian, S. M. Semiconductor devices, P (2) 42*h*.

Christmann, L. J. See Roberts, E. S.

Christova, R., and Ilkova, P. Chromatographic separation of calcium and strontium by elution with ammonium sulfate solution, (2) 43*j*.

Christy, R. S. Apparatus for panel lamp manufacture, P (8) 211*g*. Fluorescent panel lamp, P (4) 104*g*. Panel lamp seal, P (6) 150*f*.

Chromy, S. Microautoclave, (11) 310*j*.

Chrysler Corp. Glass treatment tempering nozzle arrangements and method of tempering, P (4) 97*a*.

Chu, Er-chang. See Wang, Chang-wen.

Chubb, W., and Keller, D. L. Constitution of the systems of uranium and carbon with molybdenum, niobium, rhenium, tungsten, and yttrium, B (6) 171*h*.

Chudzinski, J. Results of studies on the microstructure of electrotechnical porcelain by the electron microscope, (11) 304*d*.

Chufarov, G. I. See Leont'ev, L. I.

Chukhrov, F. V., Berkhin, S. I., Ermilova, L. P., Moleva, V. A., and Rudnitskaya, E. S. Allophanes from some deposits of the USSR, B (2) 56*b*.

Church, C. H. See Bennett, A. I., Jr.

Church, G. L. Attrition resistant siliceous catalysts and method of preparation thereof, P (4) 100*d*.

Chursina, L. S. See Tsigler, V. D.

Chzhan, Tsin-Chun. See Keler, E. K.

Ciapetta, F. G. See Wilson, C. P., Jr.

Cilker, W. H., and Shrode, W. A. Method of treating glass roving, P (6) 150*c*.

Cimino, A., Porta, P., and Valigi, M. Dependence of the lattice parameter of magnesium oxide on crystallite size, (4) 110*e*.

Cincinnati Milling Machine Co. Abrasive article containing zirconium tetrafluoride filler, P (11) 293*f*.

Ciocoiu, P., et al. Synthesis and applications of molecular sieves—synthesis of kaolin molecular sieves, (2) 47*g*.

Ciotti, J. A. See Schwabe, W. E.

Cipriani, C. C. See Christen, D. L.

Cipriano, N. A. Toilet flush tanks, P (9) 230*f*.

Cisney, E. See Aronson, S.

Clabaugh, W. S. See Swiggard, E. M.

Claesson, S. H. See Anderberg, B. I.

Clancy, T. M. See Watson, P. K.

Clare, T. E. Sintering kinetics of beryllia, (4) 113*b*. See Reeve, K. D.

Clarenburg, L. A., and Van der Wal, J. F. Aerosol filters, (5) 120*c*.

Claridge, R. F. C. Chemical effects of thermal neutron capture—mixed crystals of phosphates and arsenates, (3) 79*j*.

Clark, C. B. See Ryan, J. R.

Clark, C. H. W. Insulator having semiconductive layers to increase the capacitance thereof, P (6) 159*b*.

Clark, J. E. Semiconductor encapsulation, P (11) 307*i*.

Clark, J. R. See Appleman, D. E.

Clark, J. W., and Rectenwald, C. E. Catalyst composition consisting essentially of the oxides of iron, rare earth, and zirconium, P (4) 100*h*.

Clark, L. D. See Zapp, A. D.

Clark, M. B., Darland, W. G., and Kordesch, K. V. Composite carbon-metal electrodes for fuel cells, (7) 191*d*.

Clark, R. E. See Gaskill, A. T.

Clark, S. P., Jr. (editor). Handbook of Physical Constants, B (10) 292*g*.

Clarke, B. H. Resonance relaxation in $Mn_2Fe_2O_4$ by slow relaxing manganic and ferrous ions, (9) 254*i*.

Clarke, J. C. See Blundell, A.

Clarkson, T. C. S. Ceramic receptacle having rubber impact layer, P (8) 219*c*.

Class, W. H., and Machlin, E. S. Crack propagation method for measuring grain boundary energies in brittle materials, (7) 198*a*.

Clauser, H. R., Fabian, R. J., and Mock, J. A. How materials are selected, (2) 46*h*.

Clauss, A. See Boehm, H. P.

Clay, D. B. Factors affecting the adhesion of porcelain enamel on steel, (6) 145*d*.

Clayburn-Harbison, Ltd. Joints for sewer pipes and the like, P (7) 185*d*.

Claypool, C. V., Jr Electric discharge device, P (8) 220*c*.

Clayton, (Mrs.) H. See Gross, P.

Clayton, R. N. See Sharma, T.

Clearfield, A. Process for the production of zirconia, P (8) 225*g*.

Clemens, E. C. Clay pipe needs improvements, (9) 237*e*.

Clements, J. F., Housley, F., and Moffat, A. R. L. Prediction of pyroplastic deformation by a mechanical analogy, (7) 187*g*.

Clements, J. F., and Vyse, J. Creep measurements on some high-alumina refractories, (7) 186*e*.

Clemtex, Ltd. Abrasive tester, P (4) 108*b*.

Cleveland, T. K. Soluble silicates in ceramics, (1) 16*c*.

Clevenger, R. A. See Blaine, R. L.

Clevite Corp. Ferroelectric ceramic compositions, P (10) 278*g*. Ferroelectric ceramic and transducer embodying same, P (2) 41*b*. Method of preparing lead titanate ferroelectric ceramics, P (2) 42*e*. Piezoelectrically powered X-ray equipment, P (2) 45*j*. Piezoelectrically powered X-ray tube, P (2) 45*j*. Semiconductive device and method of making the same, P (5) 130*b*. Wave filter comprising piezoelectric wafer electroded to define a plurality of resonant regions independently operable without significant electromechanical interaction, P (3) 74*g*.

Clifford, J. S. Toilet construction, P (5) 127*j*.

Clinton, S. D. See Haas, P. A.

Cloos, P. See Calvet, R.

Clough, A. R. J. Plastic forming by roller machine, (5) 130*h*.

Clough, P. J. See Baer, C. A.

Cobb, H. R. W. Vibratory compaction of uranium carbide, B (6) 172*g*.

Coble, R. L. Deformation behavior of refractory compounds, B (2) 55*h*. See Farnsworth, P. L.

Coby, G. Package for frangible articles, P (4) 98*a*.

Coby Glass Products Co., Inc. Package for frangible articles, P (4) 98*a*.

Cocco, G., Corazza, E., and Sabelli, C. Crystal structure of glauberite, $CaNa_2(SO_4)_2$, (7) 198*d*.

Cochran, J. K. Method and apparatus for forming fibers, P (8) 213*b*.

Cochran, M. C., and Jensen, J. R. Improved holder for grinding thin sections, (7) 195*b*.

Cockayne, B. Nonuniform impurity distributions in yttrium aluminum garnet single crystals, (3) 84*c*. Observation and control of deviations in molar composition in single-crystal growth of mixed oxides, (5) 139*f*.

Cocks, E. H. Solenoid airless spray gun, P (1) 16*c*.

Coekelbergs, R., Crucq, A., Decot, J., Degols, L., Randoux, M., and Timmerman, L. Adsorption under irradiation (I) adsorption of oxygen and carbon monoxide on alumina, (11) 313*f*.

Coen Co., Inc. Apparatus and method for providing constant-heat variable-pattern burner flame, P (2) 46*c*.

Coenen, M. Density measurements on borate glasses, (5) 120*g*. Vibration damping and structure of glasses in the system $LiF–BeF_2$, (8) 211*c*. See Dietzel, A.

COFELEC. See Compagnie des Ferrites Electroniques.

Coffey, F. F. Coated abrasives and grinding for porcelain enameling, (4) 91*c*.

Coffman, R. E. See Wertz, J. E.

Cogan, M. R. Piezoelectrically powered X-ray equipment, P (2) 45*j*.

Coghill, H. D. Radiation sensitive electroluminescent devices, P (1) 15*e*.

Cohen, A. J. Phototropic glass and methods, P (11) 299*c*.

Cohen, H. M., and Chegwidden, R. A. Control of the electromagnetic properties of the polycrystalline garnet $Y_3Fe_{3.78}Al_{1.32}O_{12}$, (11) 314*e*.

Cohen, H. M., and Roy, R. Densification of glass at very high pressure, (2) 31*e*.

Cohen, S. Heat and infrared responsive glass composition and method of making it, P (8) 212*e*.

Cohen, S. T. See Cowley, A. H.

Cohen-Adad, R. See Rollet, A. P.

Cohn, H. Electrical capacitors and method of making the same, P (11) 305*j*.

Cohn, M. I., and Perdue, R. D. Apparatus for delaminating laminar minerals, P (5) 133*b*. Method of treating kaolin, P (8) 225*e*.

Cole, D. I. See Gaskill, A. T.

Cole, H. Analyses and discussion of the Caerleon window glass, (9) 229*i*.

Cole, H. B. Method and apparatus for fusing fiber optical image transfer devices, P (1) 6*i*.

Cole, J. C. Hammer mill, P (2) 47*f*.

Cole, J. E. See Bradbury, B. T.

Cole, L. G., and Cook, R. L. Ceramic material, P (8) 220*b*.

Coleman, J. Car top, P (4) 108*e*.

Coleman, J. J. See Bennett, A. I., Jr.; Smith, W. J.

Coleman, J. J., Fekete, J. M., and Smith, W. J. Furnace with means for adjusting a crucible in growing crystals, P (5) 132*h*.

Coleman, J. J., Smith, W. J., Stewart, R. C., and Fekete, J. M. Dendrite pulling and reeling mechanism, P (1) 14*j*.

Coleman, J. W. See Inkley, F. A.

Coleman Instruments Corp. System for processing and analysis of liquid samples, P (6) 163*d*.

Collings, R. K. Industrial minerals, (1) 18*d*, (6) 164*h*.

Collins, F. M. Semiconductor film resistor, P (6) 160*h*.

Collins, J. D., and Shriver, E. L. High strength concrete from hydraulic cement, aggregate, an aldehyde (formaldehyde, glyoxal), and a phenol (resorcinol, phloroglucinol), P (2) 29*h*.

Collins, O. D., III. Boron nitride incorporated in polymer products, P (9) 239*i*.

Collins, R. J. See Mocker, H. W.

Collins, T. See Wade, W. L.

Collongues, R. Order-disorder phenomena in mineral chemistry, B (6) 175*c*. See Perez y Jorba, M.

Colombo, M. See Asti, G.

Colombo, R. L. See Amato, I.

Colominas, C. B. See Broquetas Colominas, C.

Colton, E. Coated graphite and method of coating, P (11) 302*b*. High temperature material, P (8) 217*c*. Method of preparing hexaboron silicide (B_6Si), P (11) 302*e*. See Matkovich, V. I.

Columbian Carbon Co. Process for producing pigmentary silica, P (5) 134*a*. Treatment of pigmentary silica, P (11) 313*a*.

Combe, E. C., and Smith, D. C. Effects of some organic acids and salts on the setting of gypsum plaster (I) acetates, (9) 230*i*.

Combined Optical Industries, Ltd. Mold for the manufacture of lenses, P (11) 299*i*.

Comer, J. J., Tombs, N. C., and Fitzgerald, J. F. Growth of single-crystal and polycrystalline thin films of $MgAl_2O_4$ and $MgFe_2O_4$, (6) 167*h*.

Commissariat a l'Energie Atomique. Actinide oxide-actinide nitride eutectic compositions and their method of manufacture, P (4) 99*i*. Apparatus for producing very high static pressures within a hexahedral solid, P (9) 244*j*. Device for measuring doses of thermal neturons, P (3) 77*c*. Filtration-desiccation method and apparatus, P (10) 280*a*. Method and apparatus for continuously obtaining uranium dioxide with predetermined characteristics from uranium trioxide, P (4) 100*j*. Method of manufacture of uranium dioxide having a high density, P (4) 101*f*. Method of preparing uranic oxide in granulated form, P (1) 11*d*. Methods for the preparation of granular products and in particular of uranium oxide, P (8) 217*h*. Porous ceramic of low thermal conductivity and process for its manufacture, P (8) 219*d*. Preparation of materials of composite structure, P (2) 30*k*. Process of preparation of uranium compounds from uranium-molybdenum alloys, P (1) 19*a*. Process for the preparation of uranium monocarbide powder, P (3) 70*e*. Process for preparing nuclear radiation protective materials and the material obtained, P (10) 274*e*.

Compagnie des Ateliers et Forges de la Loire. Method of casting and firing a layered ceramic article, P (11) 302*h*.

Compagnie des Ferrites Electroniques. Fabrication of ferrite cores, P (6) 159*f*.

Compagnie Francaise Thomson-Houston. Metallized ceramic members, P (10) 278*b*. Metallized facing of ferrites and ferrite devices using them, P (10) 278*c*. Semiconductor materials, P (7) 194*a*.

Compagnie Generale d'Electricite. Semiconductor device having self-protection against overvoltage, P (9) 244*c*.

Compagnie Generale de Telegraphie Sans Fil. Electrode structure, P (8) 220*i*. Electron-emissive structure, P (9) 243*c*. Field-effect transistor devices, P (11) 306*c*. Method of manufacturing cathodes, P (10) 279*a*. Methods for manufacturing semiconductor devices, P (9) 243*g*. Ni-Mn-Al-Co ferrite, P (7) 193*i*. Nickel ferrite containing cobalt and manganese, P (5) 129*b*.

Compagnie de Saint-Gobain. Apparatus for the manufacture of fibers, particularly glass fibers, P (8) 211*g*. Apparatus for press bending glass, P (8) 211*h*. Apparatus for tracing and breaking glass sheets, P (2) 32*b*. Bearing, P (9) 235*f*. Burner for producing gaseous mixtures in centrifugal fiber attenuating apparatus, P (8) 212*b*. Differential thermal treatment of glass objects, P (8) 212*d*. Electroprotection of refractories, P (6) 146*c*. Glass compositions, P (2) 33*j*, P (7) 183*b*, P (8) 212*h*. Glass tank furnaces with submerged heating and cooling means, P (2) 33*a*. Heat and infrared responsive glass composition and method of making it, P (8) 212*e*. Iron oxide pigments, P (10) 283*a*. Manufacture of flat glass, P (8) 212*f*. Method of analyzing glass sheets for cutting, P (2) 33*g*. Method of and apparatus for cutting glass, P (11) 298*e*. Method of and apparatus for making thermoplastic sheet material, P (2) 33*i*. Method and apparatus for the manufacture of armored glass, P (2) 33*j*. Method and apparatus for the manufacture of fibers from glass, P (7) 183*i*. Method and apparatus for polychrome striped screens for color television receiver, P (8) 213*b*. Method of and apparatus for producing fibers from thermoplastic material, P (2) 34*b*. Method and apparatus for the protection of glass sheet in contact with metal bath, P (7) 183*j*. Method and apparatus for removing impurities in manufacture of glass, P (3) 63*h*. Method for producing in a glass article stresses heterogeneously distributed, P (9) 236*d*. Method of strengthening glass articles, P (2) 34*a*. Optical pyrometer having a cyclically moving detector, P (1), 17*a*. Process and apparatus for dividing glass, P (9) 236*i*. Process and apparatus for drawing glass, P (2) 34*f*. Process and apparatus for production of fibers from thermoplastic material, particularly glass fibers, P (8) 213*f*. Process for the manufacture of flat glass, P (2) 34*f*. Process for treating glass to produce reverse stresses and product, P (9) 237*d*. Self-gripping tongs, P (11) 299*g*. Shaping glass sheet on molten metal bath, P (8) 214*a*. Sheet of structural tempered glass, P (8) 214*c*. Surfacing of glass, P (2) 34*j*. Vitreous body including mica in finely divided state, P (2) 43*a*. Vitreous compositions of matter, P (8) 214*a*.

Comptoir Lyon-Alemand Louyot & Cie. Metallic appliances and components subjected to contact with molten materials at high temperature, P (5) 132*a*.

Compton, L. A. See Hall, H. T.
Conair, Inc. Material transporting device, P (11) 309*a*.
Conde, C. S. See Sanchez Conde, C.
Conde, F. L. See Lucena Conde, F.
Conder, N. H., and Harris, H. C. Method of precasting [brick] masonry panels, P (4) 98*k*.
Condon, H. F. Glass pipe coupling, P (5) 122*i*. Method for forming apertures in hollow glass articles, P (1) 7*a*.
Congleton, J., and Petch, N. J. Surface energy of a running crack in Al_2O_3, MgO, and glass from crack-branching measurements, (6) 170*i*.
Conley, K. H., and Tenner, A. J. Centrifugal impacting apparatus, P (4) 109*c*.
Conn, W. M. Use of electric wire explosions in investigating the fracture process in glass, (6) 149*i*.
Connecticut Research Associates, Inc. Block stacking apparatus, P (9) 237*h*. Block stacking method, P (9) 237*f*. Method of assembling interfitting block arrays, P (8) 214*e*.
Connell, J. G. Method and apparatus for making aggregate, P (9) 237*f*.
Connett, B. E., and Frost, J. A. Simply constructed stirrer guide, (4) 95*g*.
Connolly, J. D. See Hume, W. G.
Connolly, J. R. Clay mineralogy of some Upper Devonian sediments from central New South Wales, (4) 108*h*.
Connor, J. H. Mechanization of pugging processes, (3) 74*i*.
Conrad, E. E. See Pliskin, W. A.
Conrad, P. G., and Darms, F. J. Glass-resin interaction of filament-wound composites, (5) 120*g*.
Conrad, W. A. See Brous, J.
Conroy, A. R., Manring, W. H., and Bauer, W. C. Role of sulfate in the melting and fining of glass batch (I, II), (6) 148*g*.
Conroy, L. E., and Yokokawa, T. Preparation and properties of a barium tungsten bronze, (7) 202*e*.
Consett Iron Co., Ltd., and Freebury, L. S. Improvement in brick presses, P (8) 222*e*.
Consolidated Electrodynamics Corp. Ceramic material, P (8) 220*b*. Method for making ball valves, P (10) 276*c*.
Consolidated Electronics Industries Corp. Small electrical unit with molded ceramic coating, P (4) 106*k*.
Consolidated Foundries & Mfg. Corp. Monolithic investment shell casting, P (1) 11*k*.
Constabaris, G., Lindquist, R. H., and Kuendig, W. Moessbauer effect for finely divided iron oxide on porous γ-alumina, silica, and silica-alumina, (1) 23*a*.
Continental Device Corp. Method for controlling diffusion of an active impurity material into a semiconductor body, P (7) 193*i*.
Continental Oil Co. Preparation of eta alumina by water hydrolysis, P (10) 283*d*.
Contre, M. Apparatus for producing very high static pressures within a hexahedral solid, P (9) 244*j*.
Controls Co. of America. Moisture sensing control, P (11) 311*b*.
Coobs, J. H. See Sayers, J. B.
Cook, C. G. See Wilson, J.
Cook, C. M., Baker, J. J., and Walberg, A. C. New concept in electrostatic application of porcelain enamel, (5) 119*j*.
Cook, C. W. See Doud, W. O.
Cook, D. C. See Nobles, E. L.
Cook, J. S. See Dryden, J. S.
Cook, R. L. See Cole, L. G.; Vernetti, R. A.
Cook, W. R., Jr., and Jaffe, H. Ferroelectric ceramic and transducer embodying same, P (2) 41*b*.
Cooke, L. Control of ferrous sulfate in the nickel tank using barium peroxide, (6) 145*c*.
Cool, B. Segregation of glaze suspensions during application and defects arising therefrom, (6) 156*i*.
Coombs, J. A. See Apple, J. M.
Cooper, A. R., Jr. Effect of variable properties on mass and heat transfer with forced convection (II) dissolution of fused silica in a CaO-Al_2O_3-SiO_2 melt, (4) 93*b*. Kinetics of mixing in continuous glass melting tanks, (5) 121*b*. Model for multicomponent diffusion—correction, (9) 234*d*. See Varshneya, A. K.
Cooper, A. R., Jr., and Heasley, J. H. Extension of Darken's equation to binary diffusion in ceramics, (6) 167*e*.
Cooper, M., and Leake, J. A. Electron binding energy effects in Compton scattering from graphite, (9) 249*h*.
Cooper, N. W. See Oliver, T. A.
Cooper, R. H. Carbon dioxide cured sand molds employing dry sodium silicate binder, P (4) 100*f*.
Cooper, R. H., Goodenough, R. D., and Corbett, G. M. Thermosetting composition for exothermic hot tops, P (8) 218*g*.
Cooper, R. S., and Winklepleck, R. G. Electrostatic precipitator power connection, P (2) 43*e*.
Cooper, T. W. Bonds for oxidized materials, P (6) 158*g*. Method of making alloy connections to semiconductor bodies, P (4) 105*h*.
Coors Porcelain Co. Snow tire and insert therefor, P (11) 303*i*.
Copeland, C. R. Glass press mold structure with temperature regulation, P (6) 150*c*. Method of shearing glass, P (4) 97*g*.
Copeland, D. A. Simple apparatus for trimming thin sections, (6) 163*e*.
Copley, S. M. See Hulse, C. O.
Copley, S. M., and Pask, J. A. Deformation of polycrystalline MgO at elevated temperatures, (1) 20*c*.
Copper Range Co. Dispersion hardened materials and processes therefor, P (6) 154*b*.
Copson, R. L. See Lauder, W. B.
Corazza, E. See Cocco, G.
Corbeek, B. F. H. Method of manufacturing a bulb [from glass tubing], P (1) 7*b*.
Corbett, G. M. See Cooper, R. H.
Corbett, P. M. Instrumentation in porcelain enamel research and development, (6) 145*i*.
Corbin, D., and Mundell, J. M. Wearing elements for blast furnace stockline, P (7) 190*a*.
Corbitt, B. J. See Kiffer, A. D.
Cordfunke, E. H. P. Volatile oxides of some important materials used in nuclear technology, B (6) 175*b*.
Cordfunke, E. H. P., and Aling, P. System UO_3–U_3O_8—dissociation pressure of γ-UO_3, (1) 10*c*.
Corhart Refractories Co. Ceramic refractory and method, P (2) 37*d*. Fused cast refractory and method of making, P (4) 100*b*, P (7) 188*b*, P (10) 273*h*. Refractory and furnace lining, P (7) 189*i*. Steelmaking furnace, P (11) 303*i*.
Corlett, M. See Bambauer, H. U.
Corn, A. Fixing wall and floor tile, (2) 39*b*.
Cornelissen, J., Kruithof, A. M., and Meyer, H. W. J. H. Method of manufacturing reinforced cathode-ray tube for television display, P (3) 64*i*.
Cornell-Dubilier Electric Corp. Ceramic capacitor and method of making, P (3) 72*g*. Dielectric-coated foil capacitors, P (2) 41*c*. Method of capacitor manufacture, P (2) 41*i*.
Cornely, K. W. See Weiss, G.
Corning Fibre Box. Impact-resistant glass-lined containers, P (3) 63*b*.
Corning Glass Works. Apparatus for forming glass articles, P (4) 96*g*. Axially separable neck ring mold assembly, P (6) 149*d*. Blow mold with movable support, P (8) 211*i*. Bone china and method of making it, P (6) 149*d*. Bubblers, P (2) 33*d*. Ceramic burner plate, P (8) 224*e*. Ceramic heat exchanger structures, P (8) 217*g*. Ceramic muffler with resilient sealing gaskets, P (4) 96*a*. Ceramic mufflers, P (4) 96*b*. Cold diffusion bond between acoustic delay line and back electrode or acoustic absorber, P (7) 192*d*. Containers [paperboard] for TV bulbs, tubes, and the like, P (4) 96*b*. Continuous cylinder spinning of glass, P (7) 182*d*. Continuous strip forming apparatus with heater unit, P (5) 122*a*. Coupling for joining pipe sections of differing diameter, P (5) 122*b*. Delay line bond, P (8) 220*e*. Edge grinding, P (10) 267*g*. Electrical capacitor, P (10) 278*d*. Electrical resistor, P (2) 41*f*. Electroconductive coating patterning, P (6) 159*c*. Flux free bonded article, P (7) 182*j*. Fusion seals and their production, P (9) 235*j*. Glass article inspecting, P (4) 96*h*. Glassblowing machine blowhead and article cooling tube combination, P (5) 123*b*. Glass body having a semicrystalline surface layer and method of making it, P (8) 212*f*. Glass body having surface crystalline layer thereon and method of making it, P (11) 298*f*. Glass-ceramic bodies and method of making them, P (8) 212*g*. Glass delivery method, P (10) 268*a*. Glass electrode and method of making the same, P (4) 96*i*. Glass for incandescent discharge lamps, P (8) 221*b*. Glass stream feeder, P (11) 298*i*. Glass tube forming, P (7) 183*g*. Glass working conveying apparatus, P (2) 33*b*. Image recording, P (10) 278*a*. Laminated glass, P (9) 236*e*. Lamp having a colored envelope, P (8) 212*f*, P (9) 243*h*. Luminaire, P (11) 298*c*. Means for controlling the light transmission of a phototropic glass structure, P (8) 212*g*. Method and apparatus for electrolytically determining a species in a fluid, P (9) 246*d*. Method and apparatus for producing glass sheet, P (6) 150*h*. Method and apparatus for scoring [micro] sheet material, P (6) 150*i*. Method of applying electroconductive coatings and resulting article, P (10) 268*c*. Method of determining the dielectric constant of a material using calibrated standards, P (5) 132*b*. Method for finishing glass surfaces, P (5) 123*e*. Method of fire-polishing edges of hollow articles, P (8) 213*f*. Method for forming balls from thermoplastic materials, P (8) 213*g*. Method of forming a devitrified glass seal with tungsten or molybdenum, P (10) 269*b*. Method of forming an electrical capacitor, P (11) 306*c*. Method for forming enclosures for semiconductor devices, P (3) 73*j*. Method of forming glass ribbons, P (4) 97*b*. Method of forming metallic films on glass, P (7) 184*c*. Method of forming a patterned electroconductive coating, P (6) 159*i*. Method of introducing material into molten glass, P (7) 184*e*. Method of making ceramic article, P (7) 184*e*. Method of making an encapsulated impedance element, P (3) 73*b*. Method of making a flux free bonded article, P (5) 129*c*. Method of making gamma-alumina fibers, P (6) 154*j*. Method of making glass-to-metal seals, P (3) 64*g*. Method of making high strength devitrified glass bodies, P (11) 299*a*. Method of manufacturing a capacitor, P (4) 105*a*. Method of molding ceramic articles, P (5) 131*c*. Method for molding cup-shaped bodies, P (9) 243*c*. Method for sealing cavities in articles, P (10) 269*c*. Method of shaping a glass article, P (1) 7*c*. Method of sorting out defective metallic resistors by sensing the current noise index thereof, P (7) 193*i*. Mold charge delivering means, P (2) 34*b*. Neodymium glass laser having an output at about 9180 A, P (11) 299*i*. Phototropic glass composition, P (8) 213*d*. Pipe coupling, P (4) 98*a*. Pneumatic sensing device with digital readout, P (6) 150*g*. Press forming apparatus for forming wafers from drips of glass, P (11) 299*d*. Prismatic light transmitting panel, P (2) 34*e*. Protection and lubrication of metals at high temperatures, P (8) 213*h*. Radiant energy measuring device and method, P (10) 281*i*. Semicrystalline body and method of making it, P (5) 124*a*. Semicrystalline ceramic bodies and method, P (4) 98*d*. Solid delay line, P (8) 222*a*. Spacer retaining clip [for packaging], P (4) 98*b*. Strengthened cathode ray tube, P (4) 98*b*. Structural ceramic bodies and method of making same, P (11) 304*d*. Traveling wave laser amplifier with glass filter, P (2) 34*j*. Tubulated hollow article forming and molding apparatus therefor, P (9) 237*d*. Wareholder shaker, P (2) 35*b*.
Cornish, A. J. Thermoelectric materials, P (9) 244*b*.
Corrsin, L. See Behringer, A. J.
Corsi, R. J. Pivoted glass sheet bending mold, P (7) 184*d*.
Corsini, A., and MacFarlane, R. D. Some recent scientific developments and their effect on analytical chemistry, (1) 17*c*.
Corson, B. L., and Danforth, C. A. Vibratory kiln, P (7) 196*c*.
Corson, G. & W. H., Inc. Nonplastic composition containing pozzolan, lime, and blast furnace slag, P (4) 101*b*. Vibratory kiln, P (7) 196*c*.
Cortright, S. A., Howitt, T., Jr., and Shay, G. C. Continuous cylinder spinning of glass, P (7) 182*d*.
Corwin, W. C. See Wachtman, J. B., Jr.
Costa, J. E. P. da. See Pereira da Costa, J. E.
Costain, T. S., Weinberg, E. L., Luley, A. H., and Danielson, R. R. Zirconium silicate opacified ceramic glaze compositions, P (1) 13*e*.
Cotter, G. H., and Ludwig, H. C. Welding electrode, P (1) 3*g*.
Cotton, F. A., and Wing, R. M. Properties of metal-to-oxygen multiple bonds, especially molybdenum-to-oxygen bonds, (8) 227*c*.
Cottrell, A. H. Mechanical Properties of Matter, B (5) 142*h*.
Cotts, R. F. Molded mineral fiber acoustical tile, P (7) 189*a*.
Coulter, W. H. Particle analyzing device, P (11) 311*c*.
Coulter Electronics, Inc. Particle analyzing device, P (11) 311*c*. Particle studying device control circuit, P (11) 311*c*.
Coumans-Schepers, N. V. Method of controlling the pyrochemical bonding of a clay-carbon system, P (6) 164*a*.
Counts, W. E., Smith, R. W., and Schwartzwalder, K. Resistor composition and devices embodying same, P (5) 129*i*.
Courtault, B. Reactivity of cement products, (5) 118*f*.
Courtney, J. W. Rotational method for making a metal melting crucible, P (3) 70*j*.
Cowan, C. I. See Frei, J. F.
Cowan, D. B. See MacHutchin, J. G.
Cowan, J. H., Buehl, W. M., and Hutchins, J. R., III. Electrochemical theory for oxygen reboil, (11) 296*i*.
Cowan, J. V. Electromechanical transducers and the fabrication thereof, P (6) 159*e*.
Cowan, R. E., and Ehart, E. P. Epoxy resins as temporary binders for ceramics, (6) 156*b*.
Cowles, R. J. Ceramic capacitor, P (8) 220*a*.
Cowley, A. H., and Cohen, S. T. Iodides of phosphorus (I) Lewis basicity and structure, (3) 83*c*.
Cowley, C. H. Method and apparatus for producing all-glass multiple sheet glazing units, P (1) 6*j*. See Montgomery, E. C.
Cowley, E. R., and Cowley, R. A. Anharmonic interactions in alkali halides (1), (3) 79*i*.
Cowley, R. A. See Cowley, E. R.
Cox, G. A., Roberts, G. C., and Tredgold, R. H. Optical absorption edge of barium titanate, (9) 252*d*.
Cox, J. E., and Farr, A. E. Surface tension measurement of porcelain enamel glasses, (1) 3*f*.
Cox, S. F., McKelvey, H. E., and Reese, T. J. Bending glass sheets, P (5) 122*a*.
Cox, S. M., and Ferry, R. Electrical connection, P (7) 192*f*.
Cox, W. K. Wareholder shaker, P (2) 35*b*.
Craddock, C. H. Mold for the manufacture of lenses, P (11) 299*i*.
Craggs, J. W. Dislocations as sources of fracture, (1) 20*b*.
Craig, L. C. See Dunlap, J. C.
Craig, L. S. Electrical hygrometer, P (7) 195*b*.
Craig, R. A. Hardcoated mold press die, P (2) 43*g*. Process for forming a uranium mononitride-uranium dioxide nuclear fuel, P (1) 12*d*.
Craig, R. D., and Harden, E. H. Interpretation of mass spectra in vacuum measurement, (9) 245*j*.
Crane, J., and Gordon, E. Effects of fabrication and composition on the irradiation stability of uranium carbide, B (6) 172*b*.
Craven, J. P., and Bernstein, H. Materials for deep submergence—a development dilemma, (2) 54*i*.
Crawford, J. C., and Dragsdorf, R. D. Surface-charge layers in $BaTiO_3$ whiskers, (3) 86*b*.
Crawford, J. H., Jr. Radiation damage in solids—a survey, (1) 9*g*.
Crawford, P. B. See Talash, A. W.

Crawley, D. J., and Miller, J. M. Air-cooled diffusion pump and thermoelectrically cooled baffle to reach 10^{-9} torr, (1) 16*f*.
Creamer, R. H. See Dawson, D. K.
Cremer, G. Process for the continuous production of thin-walled ceramic tiles, P (10) 276*c*. See Schwamborn, P.
Cremer, J., and Rodis, F. Mineral-bound material, P (8) 217*i*.
Creuse, R. See Dubois, A.
Crichton, B. T. Refractory roof, P (2) 38*g*.
Crishal, J. M., La Chapelle, T. J., Wilcox, W. R., and Sandstrom, J. P. Impurity diffusion method, P (6) 159*a*.
Criss, F. F. Carbide coatings for graphite, P (1) 10*i*.
Criss, F. F., and Wohlberg, C. Carbide coatings on graphite, P (1) 10*j*.
Crocker, A. G. See Bilby, B. A.
Croegaert, J., and Vantournhoudt, M. Application of X-ray fluorescence in the flat glass industry, (4) 92*a*.
Croft, R. D. See Veatch, F.
Croft, W. J. Low-temperature thermal expansion of yttrium aluminum garnet, (9) 251*b*.
Cronemeyer, D. C. Semiconductor triode, P (3) 74*b*.
Cronin, J. See Rodriguez, A. R.
Crooks, D. D. See Bragg, R. H.
Crookston, J. A., Boyer, N. E., and Hodges, C. M. Suspended metal clad refractory, P (1) 12*d*.
Cropp, D. I., Jordan, C. C., and Lingo, R. W. Method of assembling a glass bead on a wire, P (11) 298*h*.
Crosfield, Joseph, & Sons, Ltd. See Joseph Crosfield & Sons, Ltd.
Cross, F. G. Prefab brick panels anyone can make, (8) 214*g*.
Cross, L. E. See Buessem, W. R.
Cross, M. M. Rheology of non-Newtonian fluids—a new flow equation for pseudoplastic systems, (1) 24*i*.
Crossley, D. See Milner, G. W. C.
Crossley Machine Co., Inc. Tile press mechanism, P (3) 72*a*.
Crothers, C. C. See Neimark, L. A.
Crowder, G. A., and Scott, D. W. Infrared spectra of 27 compounds in the regions 15 to 35 and 15 to 200 microns, (1) 22*a*.
Crowe-Gulde Cement Co. Kiln for making [concrete] blocks, P (8) 207*e*.
Crowley, M. S. Calcium aluminate cement composition, P (4) 90*j*. Metal anchors for refractory concrete, (8) 215*i*.
Crownover, J. W. Multilayer ceramic body, P (3) 74*a*.
Crozier, D., and Douglas, R. W. Study of sodium silicate glasses in the infrared by means of thin films, (3) 62*j*.
Crucq, A. See Coekelbergs, R.
Crump, E. E. See Demarest, P. C.
Crump, J. G. Industrial-process-type measurements employing gamma-ray backscattering, P (1) 311*e*.
Csagoly, Z. Surface construction materials in Iraq, (2) 29*a*.
Csakvari, B. See Boksay, Z.; Lengyel, B.
Csakvari, T. Method of making semiconductor devices, P (6) 159*j*.
Csetenyi, J. See Balla, B.
C.S.F. See Compagnie Generale de Telegraphie Sans Fil.
CTS Corp. Electrical resistance element and method of making the same, P (11) 305*j*.
Cuadrado, E. Note on the glass medallions of Tomb 204 at Cigarralejo, (4) 90*a*.
Culbertson, J. B. See Lamprey, H.
Culbertson, J. B., Lamprey, H., and Ripley, R. L. Ultrafine titanium boride, P (6) 155*h*.
Cullen, F. S. Spinner for producing mineral fibers, P (5) 124*c*.
Cullinan, D. M. Method of lining furnaces and like vessels, P (9) 240*j*. Refractory brick, P (2) 38*e*.
Cullinan Refractories, Ltd. Method of lining furnaces and like vessels, P (9) 240*j*. Refractory brick, P (2) 38*e*.
Cunningham, E. E. Apparatus for heat control of forehearths, P (7) 182*g*.
Cunningham, E. H. See Brown, W. F.
Cunningham, G. W. See Alexander, C. A.
Curran, D. R., and Berohn, A. Wave filter comprising piezoelectric wafer electroded to define a plurality of resonant regions independently operable without significant electromechanical interaction, P (3) 74*g*.
Curran, R. E. See Mendelsohn, L. I.
Currie, T. E. Metal pretreatment and one coat enamel bond, (6) 146*b*.
Curry, N. A. See Timmer, W. F.
Curry, N. A., and Johnston, G. B. Neutron diffraction measurements on pure and doped synthetic hematite crystals, (3) 84*a*.
Curtis, J. G. Method of sorting out defective metallic resistors by sensing the current noise index thereof, P (7) 193*i*.
Curtiss, L. E. Method and apparatus for making fibrous light-conducting devices, P (5) 123*j*.
Curtze, E. W., Mikus, C. A., and Huffman, C. O. Apparatus and method for scoring continuously moving glass sheets, P (6) 149*a*.
Cusano, D. A. Identification of laser transitions in electron-beam-pumped GaAs, (10) 286*g*.
Custers, J. F. H. See Blainey, A.
Cutler, I. B. See Callister, W. D., Jr.; Eastman, P. F.; Hansen, K. W.; Johnson, H. B.; Jones, J. T.; Keski, J. R.; Wilcox, P. D.
Cypher, J. H. See Stilley, G. W.
Cypher, J. H., and Davidson, C. R., Jr. Method of heat treating glass sheets while being conveyed, P (3) 64*b*, P (7) 184*d*.
Cypher, J. H., and Valchar, C. E. Method of bending glass sheets, P (3) 64*c*.
Czerlinsky, E. R. Method of determining the dielectric constant of irregularly shaped crystals, P (11) 306*c*.
Czerwinski, Z. Study of the relation between the specific resistance and the temperature of foam glasses, (11) 297*j*.

Daane, A. H. See Johnson, R. W.
Daemmer, H. See Meister, R.
Dahlberg, B. I. Method and apparatus for [successive] centrifugal separation of suspensions, P (11) 309*c*.
Dahlberg, R. Method of making masks for vapor deposition of electrodes, P (11) 306*h*.
Daines, G. A. Fabricating apparatus for a vitreous lamp member, P (1) 6*j*.
Dainis, J. A. Method of making electric lamps, P (2) 42*b*.
Dalby, D. A. See Bateson, S.
Dale, R. S. Screen printing on porcelain enamels, (5) 110*j*.
Daley, E. J. Bathroom and kitchen molding, P (3) 71*j*.
Daley, R. E. Hot top with dead air space, P (2) 38*a*.
Dallmann, W. E. See Fassel, V. A.
Dalton, J. T. Equilibria in the system uranium–plutonium–carbon, B (6) 171*j*.
Dalton, R. H., and Grego, P. Protection and lubrication of metals at high temperatures, P (8) 213*h*.
Damyanov, N. See Brashnarova, A.
Dancy, E. A., Pastorek, R. L., and Derge, G. J. Absolute Seebeck coefficient of the molten Ni–S system, (1) 19*d*.
Danforth, C. A. See Corson, B. L.
Daniel, V., and Rogers, M. G. Electrode effects in the degradation of ceramics at high temperature, B (11) 320*f*.
Daniels, R. S., and Barth, B. P. Epoxy resin abrasive structures and method therefor, P (4) 89*f*.
Danielson, R. R. See Costain, T. S.
Danilin, A. S. See Voronov, N. M.
Danjo, K. See Kawakita, K.
Danko, G. K. Electric lamp with single ended pinch seal, P (11) 298*c*.
Dantos, S. See Ellwood, P.
Darken, L. S. See Schwerdtfeger, K.
Darland, W. G. See Clark, M. B.
Darley, E. F. Studies of the effect of cement kiln dust on vegetation, (11) 294*g*.
Darling, A. S. See Selman, G. L.
Darmitzel, R. W. See Davies, J. H.
Darms, F. J. See Conrad, P. G.
Darras, R. See Boghen, J.
Das, C. R. Effect of different constituents on the opacity of phosphate opal glasses, (3) 61*a*. Review of the chemical resistance of glass, (2) 32*h*.
Das, D. K. See Allen, L. R.
Das, M. B., and Hossain, M. A. Transient methods of measuring thermal properties of solids, (4) 108*a*.
Dasgupta, D. R. Oriented transformation of magnesite, (7) 201*f*.
Dasgupta, S. Dc conductivity of alumina single crystals, (5) 134*f*.
Dasher, W. G. See Annable, P. G.
Dass, L., Saxena, S. C., and Kachhava, C. M. Interatomic forces and binding energy of diatomic ionic molecules, (7) 200*b*.
Date, M., Kanamori, J., and Tachiki, M. Origin of magnetoelectric effect in Cr_2O_3, (10) 289*e*.
Dates, H. F. Method of applying electroconductive coatings and resulting article, P (10) 268*c*.
Datta, R. K., and Roy, R. Stability of Ni_2TiO_4, (7) 202*d*.
Dau, G. J., and Davis, M. V. Electrical conductivity of alumina at temperatures in a reactor environment, (2) 49*i*.
Daubenspeck, J. M. Method for producing titanium dioxide of pigment quality, P (8) 225*d*.
Daumantas, E., and Martynaitis, M. Effect of Na_2SO_4 and NaCl on the solubility and hydration of anhydrite, (1) 2*h*.
Dave, N. G., and Chopra, S. K. Preparation and thermal decomposition of calcium hydroxide crystals, (11) 294*b*.
Davidse, P. D., and Maissel, L. I. Dielectric thin films through rf sputtering, (7) 198*b*.
Davidson, C. R., Jr. Heat treatment of conveyed glass and apparatus therefor, P (3) 63*a*. See Cypher, J. H.; Golightly, J. S.
Davidson, P. Hot top casing for casting molds, P (2) 38*a*. Method of making hot tops for ingot molds, P (2) 38*e*. See Beckius, K.
Davies, A. See Harper, H. F.
Davies, B. Method of making monolithic refractory lining in metallurgical vessels, P (5) 126*i*. Refractory shapes, P (10) 275*b*. See Birch, R. E.; Havranek, P. H.; Henry, G. R.; Miller, E. D., Jr.; Weaver, E. P.; Wilson, A. B.
Davies, B., and Havranek, P. H. Refractory, P (11) 303*j*.
Davies, B., and Henry, G. R. Prevention of hydration in magnesia refractories, P (5) 126*g*.
Davies, B., and McCreight, D. O. Mortar, P (1) 11*i*.
Davies, B., and Miller, E. D., Jr. Refractory, P (4) 101*j*.
Davies, B., and Weaver, E. P. Burned brick, P (3) 70*b*. Burned brick particularly suited for use in oxygen steelmaking, P (9) 239*j*.
Davies, B., Weaver, E. P., and Havranek, P. H. Basic fused refractories, P (10) 273*i*.
Davies, B., Woodruff, R. W., and Hanson, D. C. New brick composition, P (1) 11*j*.
Davies, G. L. Growth of fiber structures from the melt, B (2) 55*g*.
Davies, J. H., and Darmitzel, R. W. Alpha autoradiographic technique for irradiated fuel, (3) 65*f*.
Davies, J. M. See Paris, R.
Davis, C. W., Jr., Carney, D. E., Kurick, J. F., Schultz, D. A. Polishing composition feed system, P (6) 150*h*.
Davis, E. K. See Melamed, N. T.
Davis, J. L. Method of lowering the surface recombination velocity of indium antimonide crystals, P (1) 14*i*.
Davis, M. V. See Dau, G. J.
Davis, O. A., Sr., and Walsh, B. R. Aspirating [oil] spray nozzle, P (11) 311*j*.
Davis, R. A., and Quist, W. E. Designing for fracture toughness, (4) 114*i*.
Davis, S. S. Filter apparatus, P (10) 280*f*.
Davison, D. G. See Bertolini, W. A.
Davohn Corp. Cathode ray tube with transparent color screen, P (3) 72*f*.
Davy, J. R., and Hope, A. J. N. Glass sandwiches primarily for windows of optical instruments, P (3) 63*j*.
Davy, J. R., and Orr, J. S. Blooming of optical components with a complex aluminosilicate compound, P (10) 267*f*.
Davydov, A. A. See Maslov, V. N.
Davydov, A. M. See Gul'din, I. T.
Dawihl, W., and Doerre, E. Shear strength of sintered alumina as a basis for the interpretation of friction processes, (9) 229*g*.
Dawihl, W., and Klingler, E. Influence of compressive stress on the creep behavior of sintered alumina bodies around 1200°C, (2) 39*c*. Temperature dependence of the fatigue strength of sintered alumina bodies, (2) 40*c*.
Dawson, D. K., and Creamer, R. H. Electrical conductivity of zirconium dioxide films at intermediate temperatures, (3) 81*c*.
Dawson, H. H. See Emmel, D. R.
Dawson, J. W. See Long, M. J.
Day, D. E. Substitution of alkali oxides in tricalcium aluminate, (11) 293*i*.
Day, D. P. See Dobell, J. P.
Day, F., Froberg, M. L., and Holschlag, J. B. Method, system, and apparatus for processing filament-forming mineral materials, P (11) 299*h*.
Day, R. B., and Stokes, R. J. Effect of crystal orientation on the mechanical behavior of magnesium oxide at high temperatures, (3) 81*f*. Mechanical behavior of polycrystalline magnesium oxide at high temperatures, (8) 226*i*.
De, S. K. See Banerjee, J. C.
Deal, B. E., and Grove, A. S. General relation for the thermal oxidation of silicon, (5) 136*c*.
Dean, G. See Anselin, F.
Dean, H. N. See Montgomery, E. C.
Dean, H. N., Morgan, J. C., Jr., and Flaherty, L. H. Apparatus for producing all-glass multiple sheet glazing units, P (11) 297*f*.
Dean, J. Apparatus for slip casting ceramic electrical ware, P (4) 103*a*. Method of forming highly bonded shrink resistant plaster coating, P (5) 119*c*.
Dean, S. A. Method of forming highly bonded shrink resistant plaster coating, P (5) 119*c*.
Deans, H. A. See Koonce, K. T.
Debenham, W. S. See Hubble, D. H.
De Bord, J. H. See Fox, J. S.
De Carli, P. S. Method of making diamond, P (5) 117*h*.
Decker, H. See Goluecke, K.
Decker, J. J. Sanitary ware, (2) 39*h*.
Decker, W. J. Decorative electric lamp with specular coating, P (2) 33*f*.
De Clerck, D. H., and Su, Gouq-Jen. Rheological and electrokinetic properties of glass-frit quartz suspensions, (6) 146*d*.
Decot, J. See Coekelbergs, R.
De Crescente, M. A. High temperature properties of uranium carbide, B (6) 172*j*.
Deeg, E. Calculation of the temperature distribution in multicomponent coaxial glass-metal combinations, (2) 31*a*. Thermal and elastic aftereffects of glass (I) thermal aftereffect and its structural significance, (5) 122*a*.
Deeren, T. J., and Lewis, A. D. Forming short-length glass tubes, rods, and the like, P (2) 33*i*.
De Glas, A. J. See Brandt, F. R.
Degols, L. See Coekelbergs, R.
Degtyareva, E. V. Growth of corundum crystals during sintering, (6) 167*g*. See Kainarskii, I. S.
Dehenel, T. K. Optical flatness measurement, (9) 245*g*.
DeHoff, R. T. See Kronsbein, J.
Deiss, W. J., Michaud, H., and Antelme, G. Vacuum vaporization of uranium and carbides of uranium, B (6) 175*e*.
Deksnys, A., Paukste, J., and Tolutis, V. Properties of thin In-Te films containing 50 to 60% Te, (9) 254*d*.
Deksnys, A., Tolutis, V., and Simulyte, E. Photoelectric properties of CdTe thin film *pn* junctions, (3) 84*b*. Photoelectric properties of thin cadmium telluride film contacts with metals, (3) 72*i*.
De Lai, A. J. See Wentorf, R. H., Jr.
Delaney, R. A., Kaiser, H. D., and Mones, A. H. Decoupling capacitor, P (10) 278*b*.
Delange, M. See Vertes, P.
Delange, M., Huet, H., and Vertes, P. Methods for the preparation of granular products and in particular of uranium oxide, P (8) 217*h*.

Delapalme, A. See Bertaut, E. F.
Delarue, G. Behavior of oxides and metallic sulfides in molten eutectic LiCl–KCl, (5) 134*d*.
Delaune, L. J., Molstedt, B. V., and Waghorne, R. H. Cyclone separator for high temperature operations, P (11) 308*h*.
Delay, R. E. Hot top for ingot mold, P (6) 154*e*.
Delgrange, J. P. See Steinmetz, A.
Delimarskii, Yu. K. See Kolotii, A.
Delimarskii, Yu. K., and Grishchenko, V. F. Capacity of the double layer in binary $CdCl_2$–KCl and $CdCl_2$–NaCl melts, (6) 165*e*.
De Lisle, A. L. Synthetic stone bodies with controlled properties, P (6) 145*a*.
Delius, M. Refractory lightweight chamotte brick, (11) 301*c*.
Dellepiane, E., and Milanese, G. Direct-on enameling of decarburized steels, (7) 178*g*.
Delmotte, J. D. R. Porous normally dry nonconductive mold, P (4) 103*e*.
Delott, R. B. Survey of one-coat pickling processes, (7) 179*c*.
Demaison, R. J. Refractory slurry mixer and applicator, P (7) 189*j*.
Demarest, P. C. Method of making an electrical device comprising a glass capsule and a wire lead fused therein, P (3) 64*f*.
Demarest, P. C., Foster, H. R., and Crump, E. E. Capsulated bulb and method of making the same, P (11) 305*b*.
Dembovskii, S. A. Compound AsSe, (10) 284*d*. Study of the system As–Se, (2) 52*c*.
Dembovskii, S. A., Egorov, B. N., Pashinkin, A. S., and Polyakov, Yu. A. Phase transition of the second kind in SnSe, (9) 253*c*.
Demenkov, N. M. See Maslov, V. N.
Dement'eva, G. I., Shafranovskii, I. I., and Mokievskii, V. A. Conical structures on crystals, B (11) 319*j*.
Demichev, S. A. See Botvinkin, O. K.
De Mille, C. L., Quetsch, J. G., Jr., and Saia, F. J. Silicon bonding technology, P (6) 160*j*.
Demishev, G. K. Acoustic-dilatometric studies of simple silicate glasses (I) effect of composition on the structure, (9) 232*h*; (II) influence of composition on theoretical strength, (10) 264*b*. Calculation of theoretical and technical strength of inorganic glass from data of acoustic-dilatometric measurements, (6) 147*a*. Structural shear formation in glass during heating and cooling, (1) 5*c*. Thermal expansion and structure of glass, (1) 5*g*.
Demkina, L. I., Novozhilova, L. D., and Sinikas, R. I. Volatility of optical glasses, (7) 182*e*.
Demkina, L. I., Urusovskaya, L. N., and Chizhova, A. S. Volatilization of fluorine-titanium flint glasses, (4) 96*c*.
Dempsey, P. E. Method and apparatus for lining a hot top, P (5) 126*d*.
Dem'yanets, L. N. See Litvin, B. N.
DeNeufville, J. P. See Laudise, R. A.
Deng, Hsien-yuan. See Cheng, Kai-jia.
Denisenko, E. T. Macrokinetics of oxidation of porous substances, (10) 287*j*. See Miroshnikov, V. N.
Denker, S. P. Electronic properties of titanium monoxide, (5) 136*c*.
Denman, R. R. Glass forming apparatus, P (10) 268*c*. Pressing plunger for glass parisons, P (11) 299*d*.
Dennard, F. See Brown, F.
Dennen, W. H. See Ritter, C. J.
Dennerlein, D. A. Effect of fineness of grind on color and workability, (6) 145*i*.
Dennerlein, D. A., and Gazda, R. F. Versatility of extremely low temperature vitreous coatings with regard to base metal and fabrication, (5) 119*j*.
Dennert, H. Method of and apparatus for heat-treating granular materials in a gas current, P (2) 36*b*.
Dennis, J. See Henisch, H. K.
Dennis, J. A. Glass fiber filter tubes, P (10) 268*b*.
Dennis, W. J. Method of conditioning glass fiber strands, P (11) 298*h*. Polyvinyl acetate emulsion size for treating glass, P (7) 184*c*.
Denniston, D. W., and Helbing, C. H. Method for forming glass fibers, P (11) 298*j*.
Denson, N. M. See White, W. S.
Dent, J. W. See Mattare, L. A.
Dentzel, K. S. Contribution of [American] Indian ceramics, (2) 27*h*.
De Paolis, P. F., and Mauer, P. B. Borate glass for laser use, P (8) 212*a*. Phosphate glass for laser use, P (7) 184*c*.
DePerro, P. L. See Southgate, P. D.
De Pollier, F. A. Measuring apparatus for particulate material streams, P (1) 16*b*.
Deportes, C., Lorang, B., and Vitter, G. Improvement of the melting without crucible technique for refractory oxides, (8) 215*j*.
Derby, W. R., and Herzog, A. H. Process and apparatus for the production of single crystal compounds, P (6) 160*b*.
Deren, J. See Bielanski, A.
Derevyankin, V. A. See Kuznetsov, S. I.
Derge, G. J. See Dancy, E. A.
Deriemont, Y. Bubble structure—its effect on the physical and chemical properties of enamels, (2) 30*a*.
Derolf, M. R. See Weldes, H. H. W.
Derror, F. L. Mold and core construction, P (1) 13*d*.
Deschamps, A. Ferromagnetic materials and production methods, P (9) 243*e*.
Desmares, P. C. Ceramic microphone, P (8) 220*d*.
Dess, H. M. Phosphate bonded basic refractory articles, P (4) 101*c*.
Detrick, M. H., Co. Circular furnace roof and component refractory bricks, P (4) 100*i*. Means for mounting metallic members in brick molds, P (6) 154*i*. Refractory wall and nose construction, P (6) 155*f*.
Dettling, C. J., and Ramsay, R. C. Coating method and apparatus, P (4) 91*g*.
Deulina, Z. N. See Syritskaya, Z. M.
D'Eustachio, D. Sound absorbing systems, P (1) 7*c*.
Deutsch, T. Mode-locking effects in an internally modulated ruby laser, (2) 40*j*.
Deutsche Akademie der Wissenschaften zu Berlin. Manufacture of artificial paving block or brick, P (6) 151*f*.
Deutsche Edelstahlwerke Akt.-Ges. Pneumatic conveying, storing, and/or mixing apparatus, P (5) 126*d*. Production of hard metal powders, P (1) 12*a*.
Deutsche Gold- und Silber-Scheideanstalt vorm. Roessler. Method of producing finely divided siliceous pigments, P (5) 133*h*. Separation of zirconium, hafnium, niobium, and tantalum by introducing as a dry solid into the central step of a liquid-liquid partition system, P (10) 283*d*.
Deutsche Libbey-Owens Gesellschaft fuer Maschinelle Glasherstellung A.G. Heat-insulating glass pane and method of making same, P (10) 268*e*.
Deutscher, J. S. See Watson, D. R.
De Vaux, L. H., and Stopek, S. Method for making a gallium arsenide transistor, P (7) 193*d*.
Deventer, G. See Rubel, W.
Deventer Werke G.m.b.H. Casting mold and method of making it, P (4) 100*f*.
De Vilbiss Co. Spray gun using high pressure coating material, P (2) 43*h*.
Devillard, J. See Blum, P.
De Vries, E. R. Reflex reflective granule and marking material made thereof, P (8) 213*i*.
De Vries, E. R., and Ross, A. J. Retroreflective particles and reflective markers and compositions containing such particles, P (8) 213*j*.
Dewald, J. F., Northover, W. R., and Pearson, A. D. Multiple resistance semiconductor elements, P (6) 160*g*.
Dewar, R. S. See Wahlberg, J. S.
Dexco Corp. Abrading tool structure, P (7) 177*h*.
Dexel, W. Wolfenbuettel glass—a hitherto scarcely known type from about A.D. 1500, (2) 28*c*.
Dey, S. K. See Anderson, J. C.
Dey, S. K., and Anderson, J. C. Magnetic properties of cadmium manganite, (3) 83*b*.
Devris, E. See Brunet, M.
D'Harcour, J. C. See Rassel, P.
Diamond Alkali Co. Splitter blender apparatus, P (4) 107*b*.
Dichter, J. Apparatus for the manufacture of ampules, P (3) 62*j*.
Dickey, W. S., Clay Mfg. Co. Clay pipe take-out device, P (4) 98*g*.
Dickson, D. C., Jr. Rectifier assembly comprising series stacked *pn* junction rectifiers, P (10) 279*c*.
Dickson, D. J., Sanders, R. W., and Tseung, A. C. C. Ceramic materials for open-cycle MHD power generation, B (6) 173*c*.
Dickson, J. G., Katz, L., and Ward, R. Compounds with the hexagonal barium titanate structure, (6) 165*f*.
Dickson Electronics Corp. Method of forming semiconductors, P (4) 105*e*.
Didchenko, R. Thermoelectric materials, P (7) 194*d*.
Didchenko, R., Gortsema, F. P., and Dolloff, R. T. Thermoelectric conversion apparatus, P (8) 222*a*.
Didenko, E. D. Use of ammonium sulfate for intensifying glass melting, (10) 267*d*.
Didier, R. See Batigne, J.
Didier-Werke A. G. Manufacture of refractory bodies and brick, P (6) 154*f*. Process of making refractory and hydration resistant brick and magnesia material, P (8) 218*f*. Process for manufacturing metal cased basic or neutral refractory brick, P (10) 274*d*.
Diebold, E. J. Method of making a transistor containing a multiplicity of depressions, P (4) 105*a*.
Diefendorf, R. J. Resistance furnace, P (1) 18*a*.
Dienes, G. J. Point defects in metals, B (7) 204*d*.
Dienys, V., and Pozela, J. Electrical conductivity of *n*-type germanium and silicon in crossed electrical fields, (11) 316*i*.
Dieter, W. Automation of batch preparation at the Sighisoara glass factory, (2) 30*j*.
Dietert, H. W. Cylindrical screening apparatus, P (1) 16*a*.
Dietert, Harry W., Co. See Harry W. Dietert Co.
Dietert, R. L. Dryer and heater for granular material, P (4) 100*a*.
Dietrich, H. E. See Frick, O.
Dietrich, R. V. Mineral Tables—Hand Specimen Properties of 1500 Minerals, B (9) 258*c*.
Dietrich, V. E. Apparatus for spray analysis, P (11) 311*b*.
Dietzel, A. Effect of water vapor in the furnace atmosphere on the enameling of sheet steel, (9) 231*i*. See Hinz, I.; Konopicky, K.; Oel, H. J.
Dietzel, A., and Coenen, M. Trivalent cobalt in high alkali glasses, (2) 32*f*.
Dietzel, A., Floerke, O. W., and Williams, H. Formation of inhomogeneities during the melting process, (4) 93*h*.
Diggens, G. W. Hermetically sealed capacitor, P (10) 278*j*. Tantalum capacitor with glass-to-metal seal and resilient support for terminal, P (6) 161*b*.
Dill, F. H., Jr. Method for producing semiconductor articles, P (6) 160*c*. Surface protection for tunneling semiconductor devices, P (10) 279*f*. Switching transistors with controlled emitter-base breakdown, P (5) 130*b*.
Dill, F. H., Jr., Dumke, W. P., Lasher, G. J., and Nathan, M. I. Semiconductor laser with optical cavity, P (7) 194*a*.
Dill, F. H., Jr., and Rutz, R. F. Method of fabrication of crystalline shapes, P (7) 193*a*.
Dill, F. H., Jr., Rutz, R. F., and Sorokin, P. P. Lasers utilizing internal reflection techniques, P (7) 193*f*.
Diller, R. E., and Steiner, C. Machine for producing and handling elongated tubular items, P (6) 151*f*.
Dillon, J. F., Jr. See LeCraw, R. C.
Di Marco, H. A., Dorion, R. D., and Leaycraft, E. C. High iron magnesium manganese ferrite, P (3) 73*e*.
Dimov, D. See Petkov, P.
Dimov, D., Smoleva, D., P'nevski, I., Petkov, P., and Mashkin, L. Energy consumption norms in the glass industry, (2) 31*b*.
Dinh, C. Do, and Durif, A. Crystallographic study of some silicates and germanates of the type Al_2BaO_4, (6) 166*j*.
Dinsdale, A., and Wilkinson, W. T. Properties of whiteware bodies in relation to size of constituent particles, (10) 276*b*.
Dippel, T., and Kessler, W. Quantitative determination of Al_2O_3, Fe_2O_3, MgO, and CaO in sheet glass by photoelectric emission spectral analysis, (3) 62*b*.
Dismukes, J. P., and White, J. G. Rare earth sesquiselenides and sesquitellurides with the Sc_2S_3 structure, (8) 227*f*.
Distillers Co., Ltd. Inflatable former for the manufacture of hot tops, P (5) 126*a*. Process for producing a catalyst composed of tin and antimony oxides, P (6) 155*i*.
Ditrick, N. H. See Mitchell, M. M.
Dittrich, F. J., and Shepard, A. P. Flame spray clad powder composed of a refractory material and nickel or cobalt, P (8) 208*c*.
Di Vita, S. See Brandmayr, R. J.
Dixon, J. R., and Reeves, C. C., Jr. Representative carbonate petrography of some Lower and Middle Paleozoic rocks, West Flank Teton Mountains, Wyoming, (2) 47*e*.
Dixon, Joseph, Crucible Co. See Joseph Dixon Crucible Co.
Dixon Corp. Bearing composition, P (11) 301*i*.
Dmitriev, A. V. See Kuznetsov, V. G.
Dmitriev, Yu. G. See Revnivtsev, V. I.
Dobell, J. P., and Day, D. P. Preparation of thin sections of unconsolidated or friable sediments, (8) 223*d*.
Dobrott, R. D. See Hilton, A. R.
Dobrzhanskii, G. F. See Belyaev, L. M.
Dobrzhanskii, G. F., and Shaskol'skaya, M. P. Transfer of defects in a deformed seed to the grown crystal, B (11) 319*i*.
Doctorow, D. (editor). Red Book Directory Issue, B (10) 292*e*.
Dodd, D. M., and Fraser, D. B. The 3000 to 3900 cm^{-1} absorption bands and anelasticity in crystalline α-quartz, (6) 170*b*.
Dodson, V. H., Farkas, E., and Rosenberg, A. M. Noncorrosive accelerator for setting of cements, P (1) 3*b*.
Doehlert, D. H. See Golightly, J. S.
Doell, W. See Loh, E.
Doering, U. W. Fluorescent tube with mercury amalgam on tube wall, P (10) 278*h*.
Doerr, F. H. X-ray fluorescence methods for glass analysis, (2) 32*h*. See Baier, E.
Doerre, E. See Dawihl, W.
Doetzer, R. See Miederer, W.; Sandmann, H.
Dohm, Ltd. Composition based on a finely divided refractory oxide and a thermoplastic binder for the manufacture of molded articles, P (8) 217*i*.
Dohmann, K. D. See Schaefer, H.
Dohr, H. See Konopicky, K.
Doi, H. See Suehiro, Y.
Doi, M. Method of laying checker-brick, both basic and clay, for open-hearth furnace regenerator checker and of prolonging the life of checker, (10) 271*j*.
Doi, M., Takano, S., and Sakamoto, Y. Erosion of ladle brick used at converter mills and methods of reducing it, (9) 238*c*.
Doihara, T. See Hayashi, T.
Dolch, W. L. See Buck, A. D.; Mullen, W. G.
Dolf, H. R., and Marceau, W. E. Glass melting furnace with submerged gas burners, P (7) 183*e*. Method of melting glass with submerged combustion heaters and apparatus therefor, P (9) 236*d*.
Dolgina, L. V. See Eremenko, V. V.
Dolgov, V. M. See Nabiullin, F. H.
Dollase, W. A. Reinvestigation of the structure of low cristobalite, (8) 227*i*.
Dollimore, D., and Heal, G. R. Improved method for the calculation of pore size distribution from adsorption data, (11) 310*h*.
Dolloff, R. T. Method for growing crystals, P (4) 107*b*. See Didchenko, R.
Dolomie Francaise. Basic refractory composition for the support of basic refractory facings, P (8) 217*c*.
Dolomitwerke G.m.b.H. Process for making molded porous blocks of dolomite or magnesia, P (7) 189*i*.
Domaleski, J. V. Vapor deposition method and apparatus, P (4) 106*g*.
Dombkins, R. New type continuous furnace for Kelvinator-Australia, Ltd., (11) 295*j*.

Dombrovskaya, N. S. Sevenfold reciprocal system of 15 salts, (9) 255*h*. See Posypaiko, V. I.
Domicone, J. J., and Mounteer, J. E. Method for sealing cavities in articles, P (10) 269*c*.
Domingues, L. P. See Hyde, G. R.
Dominguez, G. See Travesi, A.
Dominguez, R. See Varadi, P. F.
Domokos, G., and Vajda, L. Simple photogrammetric method for surveying quarry walls, (2) 47*f*.
Domtar, Ltd. Incombustible board containing mineral and cellulosic fibers and metal oxide and method therefor, P (3) 70*f*.
Donahoe, F. J. Thermoelectric devices, P (1) 15*e*.
Donaldson, D. M. See Batey, W.
Donnelly, J. W. Apparatus for forming glassware, P (9) 235*b*. Long stroke single gob glassware forming machine, P (4) 97*b*.
Donohue, P. C., Longo, J. M., Rosenstein, R. D., and Katz, L. Preparation and structure of cadmium rhenium oxide, $CdRe_2O_6$, (1) 24*j*.
Doob, H., Jr., Philipps, T. E., and Benson, G. E. Method of preparing fibrous glass reinforcements, (P) (3) 64*j*.
Doppelfeld, O. Shell goblet and the new diatret glass of Cologne, (5) 118*c*.
Dore, B. V. See Hill, R. M.
Doremus, R. H. Physical solubility of gases in fused silica, (10) 265*j*.
Dorf, Z. P., Napara-Volgina, S. G., and Litovchenko, M. I. Determination of the range of parts for the cermet shop of a powder metallurgy plant, (3) 66*d*.
Dorion, R. D. See Di Marco, H. A.
Dorman, W. H. Luminaire, P (11) 298*c*.
Dorner, J. See Rummel, T.
Dorofeev, V. A. See Lipovskii, I. E.
Dorokhov, V. I. See Glushko, P. I.
Dorsey, F. E. See Fuller, R. A.
Doty, W. R. See Teeter, R. M.
Doud, W. O. Flaw detection method and apparatus, P (7) 182*i*.
Doud, W. O., and Cook, C. W. Inspection apparatus, P (7) 183*a*.
Douglas, D. L. Oxide plasticity in the oxidation mechanism of zirconium and its alloys, (7) 202*a*.
Douglas, G. See Levinson, S.
Douglas, R. W. Glasses and time, (6) 147*i*. See Blain, B. J.; Brown, D.; Crozier, D.; Nath, P.; Paul, A.; Steele, F. N.
Douglas, R. W., Nath, P., and Paul, A. Oxygen ion activity and its influence on the redox equilibrium in glasses, (3) 61*g*.
Dove, D. B. See Grigson, C. W. B.
Dow Chemical Co. Addition of melamine-formaldehyde to magnesium oxycement to improve the resistance to the passage of water of said cement, P (5) 119*a*. Carbon dioxide cured sand molds employing dry sodium silicate binder, P (4) 100*f*. Cement composition, P (5) 119*d*. Formable silicate composition, P (10) 273*h*. Lithium fluoride production, P (6) 164*f*. Method of concentrating fluorspar ores [by froth flotation], P (1) 18*h*. Recovery of lithium chloride from mixtures of other salts and metals, P (10) 283*c*. Thermosetting composition for exothermic hot tops, P (8) 218*g*.
Dow Corning Corp. Glass cleaning compositions, P (7) 183*b*. Glass cloth, P (10) 268*a*. Method of pigmenting glass cloth with silanes, P (6) 150*c*. Method of preparing paper from mica flakes and a silicone, P (6) 160*b*.
Dowley, A., and Roberts, H. Machines for finishing articles of ceramic ware, P (6) 157*a*. Manufacture of pottery, P (7) 190*j*.
Downing, J. H., Koerner, E. L., and Wells, J. E., III. High-temperature kiln, P (4) 108*e*.
Dowty Rotol, Ltd. Process and device for reducing the liquid content of a material containing a liquid and a solid, P (10) 280*d*.
Doyle, W. T. Method and apparatus for separating low micron size particles, P (2) 47*h*.
Doyle, W. T., and Drake, A. T. Pin grinding mechanism, P (2) 48*b*.
Drager, J. See Palmisano, R. R.
Dragsdorf, R. D. See Crawford, J. C.
Draignaud, P. Pressing of stoneware tile, (3) 71*e*.
Draiswerke G.m.b.H. Grinding method for interruptedly and continuously working mills and apparatus for practicing said method, P (2) 43*f*.
Drake, A. T. See Doyle, W. T.
Dreher, D. F. Brick package, P (7) 185*a*.
Dreier, F. A. Charpentier cut glass—Parisian cut glass of the Empire period, (3) 57*i*. Engravings and sketches on the glasses of Christian Gottfried Schneider, (5) 118*b*.
Dresher, W. H., and Reichard, H. F. Sulfur treated asbestos, P (8) 218*f*.
Dressler, P. d'H. Tunnel kiln system, P (7) 196*b*.
Dressler, W. Modern lighting in porcelain factories, (1) 15*j*.
Drexel Institute of Technology. Furnace for producing oriented graphite, P (4) 108*d*.
Dreyfus, B. A. Reusable transfer plate for making printed circuitry, P (4) 106*e*.
Dreyling, A. P. See Dreyling, L. J.
Dreyling, A. P., and Dreyling, L. J. High density, high refractory ceramic composition for open hearth furnace bottoms and method, P (6) 154*d*.
Dreyling, L. J. See Dreyling, A. P.
Dreyling, L. J., and Dreyling, A. P. Method of producing lightweight high temperature [acid] refractory products, P (1) 11*d*.
Drickamer, H. G. See Champion, A. R.
Drits, V. A. See Frank-Kamenetskii, V. A.; Kossovskaya, A. G.; Murav'ev, V. I.
Drobnyk, J. W. Petrology of the Paleocene-Eocene Aquia formation of Virginia, Maryland, and Delaware, (2) 47*a*.
Drobot, D. V. See Pashinkin, A. S.
Drobot, N. F. See Fedorov, P. I.
Dronyuk, M. I. See Sandulova, A. V.
Drost, W., and Dutchess, E. E. Hardened molecular sieve agglomerates and manufacture thereof, P (5) 127*g*.
Drown, H. L. See Armbrust, B. F., Jr.
Drozdetskaya, G. V. See Avgustinik, A. I.
Drucker, D. C. Engineering and continuum aspects of high-stength materials, B (2) 55*h*.
Drummond, W. W. Method and apparatus for forming fibers, P (8) 213*a*. Method and apparatus for producing fibers, P (5) 123*a*. Method for producing conductive glass fiber yarn, P (3) 64*a*. See Small, R. L.
Drushel, H. V. See Eberly, P. E., Jr.
Dryden, J. S., Morimoto, S., and Cook, J. S. Hardness of alkali halide crystals containing divalent ion impurities, (3) 82*h*.
Dryden, R. P. Occurrence of thermochromism in color standards, (1) 16*j*.
Dubinin, V. P. See Grigor'eva, V. V.
Dubois, A., and Creuse, R. Long duration tests of refractory materials usable for the construction of magneto-aerodynamic generators, B (6) 173*c*.
Dubois, A., and Hammar, M. Refractory corrosion in the presence of combustion gas seeded with potassium, B (6) 173*c*.
DuBois, H. Art pottery, (2) 27*h*.
DuBois, J. H. Glass bonded mica expands uses, (8) 220*a*.
Dubova, O. A., and Voloshinova, L. M. Service of refractories during high-temperature melting of glass, (2) 37*a*.
Dubovik, T. V. See Samsonov, G. V.
Dubrovo, S. K. Vitreous Lithium Silicates—Properties and Applications, B (4) 115*i*.
Dubrovskaya, L. B., and Gel'd, P. V. Boundaries of the region of homogeneity and the nature of chromium disilicide, (11) 314*d*.
Dubrovskaya, T. S. See Dubrovskii, V. A.
Dubrovskii, A. P. Influence of some factors on the permeability of porous materials, (9) 250*h*.
Dubrovskii, S. M., and Anosov, V. Ya. Relation between curves of the same property of a binary system, (9) 254*e*.
Dubrovskii, V. A. Relation between chemical and mechanical processes during glass polishing, (4) 95*c*.
Dubrovskii, V. A., Dubrovskaya, T. S., and Shkarlinskii, O. F. Potassium compounds—radioactive indicator for studying glassmaking processes, (4) 94*h*.
Dubuisson, J. See Accary, A.
Duc, Tran Qui. See Chazalon, R.
Duc, X. Nguyen, and Neant, D. Thermal conductivity of materials and structures of refractory materials used in MHD ducts, B (6) 173*e*.
Duchene, J. See Poirier, G.
Ducros, P. Mobility of hydrogen and mechanical properties of clays, (7) 201*e*. See Pare, X.
Ducros, P., and Dupont, M. Nuclear magnetic resonance study of the thermal evolution at low temperatures of the water of hydration of montmorillonite, (7) 201*h*.
Duczyminska, E. See Bielanski, A.
Dudareva, A. G. See Fedorov, P. I.
Dudek, J. A. See Mellen, E. J., Jr.
Duderstadt, E. C., and White, J. F. Sintering BeO to variable densities and grain sizes, (1) 10*j*.
Duerr, W. Method of producing a photoconductive layer, P (3) 73*i*.
Dufaure de Lajarte, S. See Lajarte, S. D. de.
Duff, R. D. Method of electrostatic screen printing, P (6) 150*j*.
Duffek, E. F., Benjamin, E. A., and Mylroie, C. A. Anodic oxidation of silicon in ethylene glycol solutions, (11) 313*j*.
Dugdale, R. A., and Ford, S. D. Etching of alumina and fused silica by sputtering, (8) 226*c*.
Dugnas, J. See Gaska, I.
Duke, J. B. Clay products and aqueous systems containing same, P (11) 312*d*. Method for producing spherical bauxite adsorbent granules, P (4) 101*j*. Sorbent products and method for making same from attapulgite clay, P (6) 155*g*.
Dulnev, G. N. Heat transfer through solid disperse systems, (6) 167*i*.
Duma, G. Survival of the pottery crown, an ancient building structure in Hungarian earthenware kilns, (2) 28*d*.
Dumesnil, M. E. See Snow, E. H.
Dumke, W. P. See Dill, F. H.
Dumke, W. P., and Haering, R. R. Semiconductor laser with optical cavity, P (7) 194*a*.
Duncumb, P. Method for the analysis of X-rays from an electron probe device, P (9) 246*d*.
Dundurs, J., and Mura, T. Interaction between an edge dislocation and a circular inclusion, (1) 22*e*.
Dundurs, J., and Sendeckyj, G. P. Edge dislocations inside a circular inclusion, (1) 20*b*.
Dundzys, P. See Mikailiene, E.
Dungan, R. H., and Golding, R. D. Polarization of $NaNbO_3$-$KNbO_3$ ceramic solid solutions, (1) 24*i*.
Dunipace, D. W., and McCown, W. E. Glass stream heating in a continuous ribbon furnace, P (8) 212*b*.
Dunlap, I. R., and Patchen, F. D. Cementing of high temperature wells, P (7) 178*d*.
Dunlap, J. C., Bergquist, H. R., Craig, L. C., and Overstreet, E. F. Bauxite deposits of Tennessee, (3) 77*j*.
Dunn, J. B. See Shaffer, W. R.
Dunning, J. W. See Soonpaa, H. H.
Dupont, M. See Ducros, P.
Du Pont de Nemours, E. I., & Co. Bonded alumina refractory, P (6) 154*h*. Boron nitride incorporated in polymer products, P (9) 239*i*. Cemented carbide bodies containing a dispersed oxide in the matrix metal and a process of making, P (7) 177*g*. Electrostatic decoration of hot glass, P (5) 122*e*. Extrusion of ferrous metals through dies of metal silicides, P (1) 11*c*. Forming inorganic fiber material containing cationic starch and colloidal silica, P (3) 70*i*. High alumina refractory bodies, P (6) 154*c*. High temperature-resistant materials of aluminum, nitrogen, boron, carbon, and silicon and preparation thereof, P (10) 273*j*, 274*a*. Impact pulverization-classification, P (3) 78*i*. Luminescent materials, P (1) 14*g*. Luminescent solid solutions of europium compounds with at least one other rare earth compound, P (7) 193*f*. Magnetic materials and their preparation, P (6) 159*d*. Mangano-chromia-manganite catalyst composition containing alkali metal and alkaline earth metal manganates, P (4) 100*f*. Method of preparing a catalyst composition consisting of manganese oxide-coated alumina with nickel or cobalt chromites and the product thereof, P (4) 101*g*. Method of preparing fine metal wires, P (2) 34*i*. Powder metal compositions containing dispersed refractory oxide, P (2) 38*b*. Preparation of fibrous titanium dioxide, P (6) 155*f*. Preparation of highly impervious refractories, P (7) 189*d*. Process for making a capacitor element for high temperature operation, P (8) 221*h*. Process for preparing fibrous titanium dioxide and compositions useful in production therefor, P (6) 164*i*. Process for the production of metal borides and nitrides, P (9) 241*e*. Process for the production of [turbostactic] boron nitride, P (6) 155*i*. Process for removing chloride impurity from TiO_2 product, P (8) 225*h*. Refractory product and process, P (8) 218*d*. Resistor compositions, P (1) 15*e*, P (5) 130*a*. Solids flow equalizer, P (1) 16*c*. Stabilized zirconia composition, P (10) 275*c*. Submerged arc welding process and flux composition utilizing fluorocarbon, P (11) 296*d*. Thermoelectric compositions and methods of preparing same, P (1) 15*e*, P (3) 74*c*. TiO_2 manufacture, P (1) 19*c*.
Dupuis, F., and Rousseau, A. Determination of the cost of individual articles of hollow ware, particularly bottles (I) general methods of calculation, rate of working, and production of the machine; (II) significance of volume of production, molds, machines, glass, annealing, sorting, and sales, (4) 92*d*.
Duquesnoy, A. Variations in the electrical conductivity of some transition metal oxides as a function of the equilibrium oxygen pressure at high temperature, (9) 242*g*.
Duran Botia, P. See Alvarez Estrada, D.
Durelli, A. J., and Parks, V. J. Make strain visible, (2) 44*a*.
Durham, J. L. See Wade, W. H.
Durif, A. See Dinh, C. Do; Grenier, J. C.; Joubert, J. C.; Martin, C.
Durif-Varambon, A. See Bertaut, E. F.; Durif, A.; Joubert, J. C.
Durkee, R. K, and Lucas, A. C. Thermoluminescent dosimeter shield, P (4) 106*f*.
Duro-Test Corp. Apparatus for controlled movement of flame heating means to form spiral lamp tubes, P (6) 149*j*. Reinforced envelope for light source and method of making, P (3) 64*i*.
Durrant, G. G., and Atkinson, B. D. Titanium dioxide pigments, P (8) 225*j*.
Dusenbery, E. B. Two fragments of a Roman cameo glass cup, (4) 90*b*.
Dutchess, E. E. See Drost, W.
Dutta, S. K. See Briggs, G.
Dutta, S. N., and Jeffrey, G. A. Structure of germanium selenide and related binary IV/VI compounds, (1) 25*h*.
Duweli, E. J., and Klein, W. A. Supersize film forming resins on coated abrasives, P (8) 205*g*.
Duwez, P. Metastable solid solutions, B (6) 171*g*.
Dvornikova, L. M. See Ambrozhii, M. N.
Dvorszky, M. See Millner, T.
Dwight, K. See Menyuk, N.
Dwyer, F. G., Schwartz, A. B., and Wilson, R. C., Jr. Aluminosilicate processing, P (8) 217*a*.
Dyakovska, Ts. Formation of the mullite phase in aluminosilicate refractory materials, (2) 36*h*.
Dyakovska, Ts., and Mikhova, M. Kaolin bodies of increased density for glass pot refractories, (6) 152*j*.
Dyatlova, O. N., and Bykov, V. V. Chemical polishing of glass, (10) 264*j*.
Dye, C. H. Method of delaminating mica crystals with sonic vibration, P (6) 159*f*.
Dynamics Corp. of America. Ceramic ruggedized low frequency crystal unit, P (3) 72*g*.
Dzeganovskii, V. P. See Zhurakovskii, E. A.
Dzhambazova, T., and Simova, M. Detection of imperfections in glass by a crystal-optical method, (6) 147*d*.
Dzhangov, G. Bulgarian glass factory of the 9th to 10th century, (5) 117*j*.
Dzotsenidze, G. S., and Matchabely, G. A. Genesis of bentonites of the Georgian SSR, B (2) 56*f*.

Dzotsenidze, G. S., and Skhirtladze, N. I. Paragenesis of the analcime and halloysite in the Bathonian sediments of Georgia, B (2) 56*f*.

Eagle Chemical Co. Siliceous dental filling, P (7) 191*a*.
Eales, H. V. Polarization figures as an aid to identification of polished isotropic minerals, (6) 162*b*.
Eargle, F. L., and Travis, C. J. Comparison study on bricklaying methods, (8) 214*d*.
Earl, J. A. Insulating coating compositions for electrical conductors, P (10) 263*h*.
Early, R. L., and Sorbie, T. B. Bottle gaging, P (11) 297*h*.
Eash, D. T. See Smith, M. C.
Eastman, D. E. Measurement of third-order elastic moduli of yttrium iron garnet, (9) 252*c*.
Eastman, P. F., and Cutler, I. B. Effect of water vapor on initial sintering of magnesia, (11) 316*i*.
Eastman Kodak Co. Borate glass for laser use, P (8) 212*a*. Magnesium oxide infrared transmitting optical elements, P (5) 123*g*. Optically immersed photoconductive cells, P (6) 150*e*. Phosphate glass for laser use, P (7) 184*c*.
Ebeling, M. Measurement and control procedures for glass melting tanks, (7) 180*i*.
Eberhard, E. See Bambauer, H. U.
Eberhart, J. P. Structure of the anhydrous phase of muscovite between 700° and 1000°C, (7) 202*h*.
Eberle, A. R., and Lerner, M. W. Differential spectrophotometric determination of boron with diaminochrysazin, (3) 75*d*.
Eberle, L., Nixdorf, J., Poeschel, E., and Rochow, H. Thermodynamic observations on reactions of high melting carbides at about 2000°C, (9) 257*c*.
Eberly, P. E., Jr., Kimberlin, C. N., Jr., Miller, W. H., and Drushel, H. V. Coke formation on silica-alumina cracking catalysts, (5) 125*d*.
Ebert, J. E. Waveguide dissipating section using glass-iron composition absorber and method of making, P (5) 130*d*.
Eberts, R. E. Stabilization of calcium carbonate slurries, P (7) 178*d*.
Ebina, O. Crushing of materials in theory and practice, (7) 186*g*.
Ebling, W. F., Jr., Huang, C. Y. D., and Immediata, T. M. Method of making electrical resistors, P (5) 129*b*.
Eck, R. D., and Lipp, G. D. Method of introducing material into molten glass, P (7) 184*e*.
Eckart, D. W. See Kohn, J. A.
Eckerlin, P. See Wollank, G.
Eckerlin, P., Langereis, C., Maak, I., and Rabenau, A. Preparation, structure, and properties of $LiPN_2$, B (11) 320*e*.
Eckerlin, P., and Rabenau, A. System Be_3N_2–Si_3N_4—crystal structure of a new modification of Be_2N_2, (3) 86*d*.
Eckert, J. S. Rotator, P (1) 16*c*. Saddle for treating tower, P (5) 127*h*.
Eckhardt, F. J. Influence of temperature on the crystallographic degree of order in kaolinite, B (2) 56*e*. Preparation and use of ultramicrotome sections for electron-microscopic investigations on clays, (3) 85*f*.
Eclipse Fuel Engineering Co. Tube-firing gas burner assembly, P (4) 108*g*.
Economy, J. See Giese, R. F., Jr.; Matkovich, V. I.
Economy, J., Matkovich, V. I., and Giese, R. F., Jr. Crystal chemistry of alpha-boron derivates, (7) 198*b*.
Eddleston, J. H. Semiconductor junction passivation, P (6) 160*i*.
Eden, C. Technical process advances in the melting of optical glass, (2) 32*d*.
Eden, J. S. Catalyst comprising molybdenum oxide, tellurium oxide, and a manganese phosphate, P (4) 100*h*.
Edens, A. H. Method and device for the mass production of glass rod and glass tube, P (2) 34*d*.
Edgecumbe, J. Thin film densities, (10) 281*c*.
Edgerton, Germeshausen & Grier, Inc. Thermoluminescent dosimeter shield, P (4) 100*f*. Triggered spark gap, P (2) 43*b*.
Edholm, B. B. Method of forming an [SiO_2] investment mold with potassium sulfate additive, P (5) 126*f*.
Edmundson, I. C. Calibration of a Fisher air permeability apparatus for determining specific surface, (8) 222*j*.
Edshammar, L. E. Crystal structures of Os_2Al_3 and $OsAl_2$, (2) 49*d*.
Edwards, G. J., and James, W. G. Electric incandescent lamp and manufacture thereof, P (8) 220*g*.
Edwards, I. A. See Berner, L.
Edwards, J. B. See Martin, J. J.
Edwards, P. L., and Huang, S. Comparison of whisker growth sites and dislocation etch pits on single-crystal sapphire, (4) 110*a*.
Edwards, S. P. See Harrell, B. R.
Efimenko, J. See Gingerich, K. A.
Efimov, A. I., Belorukova, L. P., and Ryndina, A. M. Complex compounds of the type Me_2MoCl_5, (10) 284*c*.
Efimov, A. I., and Pitirimov, B. Z. Fusibility diagrams of the systems RbCl–$CrCl_3$ and CsCl–$CrCl_3$, (11) 317*c*.
Egan, J. J., McCoy, W., and Bracker, J. Standard molar-free energy of formation of some chlorides of Mg, Ce, U, and Th by solid-state emf techniques, B (6) 175*a*.
Egawa, T. Study on coordination number of aluminum in allophane, (2) 52*j*.
Eggert, R. See Bargel, G.
Egorov, B. N. See Dembovskii, S. A.
Egyesult Izzolampa es Villamossagi Reszvenytarsasag. Method of manufacturing electrical heating elements with improved aluminum oxide coating, P (3) 73*d*. Shock and vibration resistant heater for indirectly heated cathodes of radio receiving tubes, P (10) 279*e*.
Ehart, E. P. See Cowan, R. E.
Ehrcke, U. See Schwiete, H. E.
Ehrenberg, W., Gutan, V. B., and Vodopyanov, L. K. Electrical bombardment induced conductivity in fused silica, (4) 110*j*.
Ehrich, R. W. Ceramics and man, B (6) 172*c*.
Eichbauer, R. N. See Markels, M., Jr.
Eichhorn, R., Reis, W. von, and Stoeckmann, G. Heat-insulating glass pane and method of making, P (10) 268*e*.
Eichkorn, G. See Borgstedt, H. U.
Eick, H., Rank, E., and Thom, R. Vaporization studies of the uranium dicarbide phase, B (6) 175*d*.
Eick, H. A. Plutonium borides, (1) 9*f*.
Eiduk, O. N. See Ivensen, V. A.
Eilerman, G. E. Glass fiber treatment, P (9) 236*a*. See Kolek, R. L.; McWilliams, D. E.; Triplett, B. L.
Eimco Corp. Filter apparatus, P (10) 280*f*.
Eipeltauer, E., and Schaden, K. Relation between viscosity and composition of binary sodium borate glasses, (9) 234*d*.
Eisenberg, A. Sound insulation of glass and glazing (I) single panes firmly mounted; (II) double glazing, (4) 95*a*.
Eisentrout, C. H. Gaseous and liquid fuel industrial furnace burner, P (6) 164*a*.
Eisenwerk Weserhuette A.G. Jaw crushing roller, P (4) 109*h*. Means for compensating the inertia forces in jaw crushers, P (2) 47*g*.
Eisler, C. Method of sealing glass tubes, P (9) 236*f*.
Eiss, N. S., Jr., and Fabiniak, R. C. Chemical and mechanical mechanisms in wear of sapphire on steel, (5) 119*g*.
Eitel-McCullough, Inc. Art of bonding ceramic to metal, P (4) 104*i*. Electron tube comprising beryllium oxide ceramic, P (4) 104*f*. Process for rendering ceramics slightly conductive, P (4) 106*c*. Tube having a heat conducting mount, P (3) 74*e*.
Eitingon, S. I. See Pavlushkin, N. M.
Ekholm, G. Scandinavian glass vessels of oriental origin from the first to the sixth century, (2) 28*a*.
Ekwall, P., Groth, K., and Runnstrom-Reio, V. (editors). Surface Chemistry—Proceedings of the Second Scandinavian Symposium on Surface Activity, Stockholm, November 1954, B (7) 204*e*.
El-Aggan, A. M. See El-Shamy, H. K.
Eland, A. J. Method of producing monocrystals of a semiconductor via the vapor phase, P (2) 42*f*.
Elbern, V. H. Late-Roman glass goblets from Cologne and their influence in early medieval times, (9) 230*c*
Eldred, J. W. Glassware sizing machine and method, P (1) 6*e*.
Electra Mfg. Co. Electrical resistor and method of producing, P (8) 220*h*. Precision electrical fuse, P (11) 307*f*.
Electro Materials Corp. Multilayer ceramic body, P (3) 74*a*.
Electro Refractories & Abrasives Corp. Radiant gas burner tile, P (2) 38*d*. Rotational method for making a metal melting crucible, P (3) 70*j*. Silicon aluminum boride complex, P (3) 57*g*.
Electronic Memories, Inc. Ferrite memory cores, P (5) 128*e*.
Electronics Corp. of America. Ultraviolet detector, P (2) 43*c*.
Elektroschmelzwerk Kempten G.m.b.H. Process for the continuous production of boron nitride, P (1) 12*d*.
Elgenstierna, R. M., and Ohlson, G. Method for producing wall units, P (11) 300*g*.
Elias, J. A. Elimination of enamel fish-scaling in iron and steel sheets, P (11) 295*h*.
Eliason, L. K. See Pentecost, J. L.
Elie, G. T. Method of fabricating semiconductor devices, P (10) 278*h*.
Elinek, V. I. See Kitaigorodskii, I. I.
Eliseev, A. A. See Yarembash, E. I.
Elkind, M. J. See Baldauf, G. A.
Ellies, P. See Schwiete, H. E.
Elliot, A. B. M. See Reynolds, F. H.
Elliot, M. N., and Grover, J. R. Measurement and control of gas temperature in the FINGAL process, (4) 94*f*.
Elliott, J. F. (editor). Steelmaking—The Chipman Conference, Dedham, Mass., June 1962, B (3) 88*a*. See Rawling, J. R.
Ellis, P. See Brown, F.
Ellwood, P., and Danatos, S. Process furnaces, (7) 195*h*.
Elmer, T. H., and Nordberg, M. E. Glass for incandescent discharge lamps, P (8) 221*b*. Lamp having a colored envelope, P (8) 212*f*, P (9) 243*h*.
El Rifai, M. Preparation of highly impervious refractories, P (7) 189*d*.
El-Shamy, H. K., El-Aggan, A. M., and Habashy, M. G. Oxidation-reduction potential of sexivalent and quadrivalent uranium ions (I) formulas of sexivalent and quadrivalent uranium ions in acid solutions, (7) 201*h*; (II) standard oxidation-reduction potential of U^{VI}–U^{IV} system (7) 20*j*.
Elton, W. L. See Mattimoe, P. T.
Elving, P. J. See Kolthoff, I. M.
El Waziri, A. H. Apparatus for measuring temperature differences P (7) 195*a*.
Elzbutas, H. See Sasnauskas, K.
Emblem, H. G., and Fothergill, E. W. Shell mold process, P (11) 303*e*.
Emeis, R. Method of attaching an electric connection to a semiconductor device, P (4) 105*c*. Method of etching Si and Ge semiconductor bodies, P (10) 278*g*. Method of producing electrically asymmetrical semiconductor device of symmetrical mechanical design, P (5) 129*h*. Method of producing a semiconductor member, P (11) 307*b*. Method for surface treatment of semiconductor devices of the junction type, P (4) 105*f*. See Rummel, T.
Emer, P. Geological-petrographic and physical properties of some glass raw materials, (3) 78*f*.
Emerson, R. B. See Osment, H. E.
Emhart Corp. Apparatus for moving newly formed glassware articles of unstable configuration onto a conveyor, P (7) 182*aj*. Conveyor drive mechanism for glassware forming machines, P (7) 182*e*. Glassware annealing lehr, P (9) 236*d*. Glassware forming machine, P (3) 63*j*. Mechanism for handling glass containers, P (8) 212*h*. Take-out mechanism for double gob glassware forming machine, P (3) 65*b*.
Emmel, D. R. Removal of scrap material incident to pressed ware production, P (5) 127*g*.
Emmel, D. R., Blackburn, A. R., Steele, R. E., and Dawson, H. H. Automatic production of pressed ware from plastic material, P (2) 40*a*.
Emoto, M. See Aoki, Y.
Emrich, B. R. Glass-ceramics—performance and use, (2) 31*d*.
Endebrock, R. W. Uranium mononitride fuel and method of making, P (1) 12*e*.
Endo, T. Erosion of center brick used for bottom casting, (1) 8*g*.
Endow, N. See Bergsnov-Hansen, B.
Engel, A, von. Electric discharges and excited species, B (9) 259*f*.
Engelhard, W. E. Portable pyrometer, P (4) 108*a*.
Engelhard Hanovia, Inc. Grinding of materials with hard abrasives, P (5) 117*g*. Surfacing of materials, P (6) 151*b*.
Engelhard Industries, Inc. Compacting of particulate materials, P (4) 106*j*. Method and composition for decorating glass-ceramics, P (10) 268*g*. Palladium decorating compositions, P (2) 48*a*. Production of metal-carbon compounds, P (10) 274*g*. Production of refractory silica articles, P (3) 70*h*.
England, A. W. See Walsh, J. B.
English, C. J. See Skantze, H.
English, J. F., and Zubler, E. G. Iodine cycle incandescent electric lamp, P (6) 159*b*.
English Electric Co., Ltd. Bonded metal-ceramic elements, P (5) 128*h*. Crystalline material and method of making, P (4) 96*b*. Process of bonding glass or ceramic to metal, P (3) 64*c*. Process of making a ceramic article by controlled devitrification of a glass, P (10) 269*h*.
Enomoto, S. See Mori, C.
Enomoto, S., and Furuta, T. Industrial applications of γ-ray radiography (III) intensification factor of lead screen, (11) 310*i*.
Enomoto, S., Furuta, T., and Mori, C. Analytical applications of beta-ray back-scattering (III) improvement of the sensitivity by pulse height analysis, (11) 309*e*.
Enomoto, S., and Ito, T. Analytical applications of beta-ray back-scattering (I) improvement of the sensitivity by the filter method, (11) 309*e*.
Enomoto, S., and Mori, C. Analytical applications of beta-ray back-scattering (II) improvement of the sensitivity by the spectroscopic method with magnetic field, (11) 309*e*. Industrial applications of beta-ray excited X-rays (X) quantitative X-ray spectrochemical analysis using ^{147}Pm beta-ray source, (4) 107*f*; (XI) new apparatus for X-ray spectrochemical [spectroscopic] analysis, (4) 107*f*. Nondispersive X-ray spectrochemical analysis using nuclear beta-ray source, (4) 107*g*.
Enos, W. K., Jr. See Prohaszka, P. J. H.
Ensslen, R. H., and Norgard, F. C. Mineral wool board, P (8) 217*j*.
Enssle, B. E. Spray gun having vent member for spray material and air, P (5) 131*b*.
Entis, A. Think big, (8) 206*c*.
Entoleter, Inc. Centrifugal impacting apparatus, P (4) 109*c*.
Entwisle, A. R. Account of the exhibits relating to Henry Clifton Sorby, B (6) 173*h*.
Epel'baum, M. B. Possible causes of the high strength of glass fiber, (7) 181*c*.
Epifanova, K. I. See Maslov, V. N.
Eppenberger, P. Mixing machine, P (10) 280*c*.
Eppler, R. A., and MacDowell, J. F. Method of making high strength devitrified glass bodies, P (11) 299*a*.
Epstein, D. J. Magnetization process, B (9) 259*e*. See Lovell, B. W.
Era, K. See Shionoya, S.
Erdey, L. See Inczedy, J.; Paulik, F.
Erdey, L., Paulik, F., Paulik, J., and Zagyvai, I. Method for the examination of the separation of suspensions and emulsions, P (6) 163*b*.
Erdman, W. C. Support assembly for materials processing and method, P (5) 130*a*.
Erdogan, M. E. Heat transfer in an incompressible viscous fluid between two concentric rotating spheres, (1) 22*d*.

Eremeeva, A. S. Method of thermomechanical testing and calculation of molecular weight of the network chain of inorganic glasses, (7) 180*j*.

Eremenko, V. N. See Naidich, Yu. V.; Tolmacheva, Z. I.

Eremenko, V. N., and Lukashenko, G. M. Thermodynamic properties of the higher antimonide of zinc, (1) 25*d*.

Eremenko, V. N., Lukashenko, G. M., and Sidorko, V. R. Thermodynamic properties of manganese silicides, (10) 291*c*.

Eremenko, V. N., and Tret'yachenko, L. A. Isothermal section of the system Ti–V–C at 1450°C, (11) 318*j*.

Eremenko, V. V., and Dolgina, L. V. New method of determining the sensitivity of clays to drying, (2) 44*e*.

Erenrich, E. H. See Klein, P. D

Erents, K., and Carter, G. Evolution of water vapor from glass after atmospheric exposure, (9) 233*i*.

Erents, K., Grant, W. A., and Carter, G. Thermal release of gas trapped in sites with a continuum of activation energies, (4) 113*j*.

Erenyi, P. P. Magnetic abrasive disk holder and disk, P (4) 89*g*.

Erfe, C. Semiporcelain dinnerware from local materials, (8) 219*e*.

Erickson, G. F. Ceramic to metal bonding process, P (2) 37*c*.

Erickson, H. See Sanford, R. A.

Ericson, B. S. J. Binding composition and method of making, P (2) 29*f*.

Erie Resistor, Ltd. Ceramic capacitor, P (6) 158*k*.

Eriksson, L. See Hansen, T. C.

Erlin, B. Methods used in petrographic studies of concrete, (11) 293*i*.

Ermilova, L. P. See Chukhrov, F. V.

Ernsberger, F. M. See Neely, J. E.

Ernst Leitz G.m.b.H. Technical glass, P (10) 270*a*.

Erskine, G. B. See Hess, F. B.

Ervin, J. M. See Lincoln, E. T.

Erwin, L. R., Gustavson, G. E., and McCallum, D. W. Method of assembling a ceramic lined water heater, P (11) 296*d*.

Erzen, F. C. See Wilbanks, W. H.

Eschenbach, R. C. See Lozier, W. W.

Esechko, A. M. See Bil'tyukova, E. P.

Esquivel, A. L. See Otte, H. M.

Esse, F. Theoretical design problems of continuous ceramic kilns, (2) 46*f*.

Esso Research & Engineering Co. Cementitious systems, P (5) 119*f*. Crystalline zeolite composition and method of preparation, P (11) 312*f*. Cyclone separator for high temperature operations, P (11) 308*h*. Porous carbon electrode preparation, P (1) 12*a*. Side-entry fluid fuel injection system for furnaces, P (1) 18*a*.

Esson, J. Radiometric-spectrophotometric determination of microgram amounts of niobium in rocks and minerals, (2) 45*i*.

Esteve, S. C. Machine for the manufacture of fibro [asbestos] cement pieces, P (5) 126*a*.

Estrada, D. A. See Alvarez Estrada, D.

Esveldt, C. J., Fluks, R., and Peloschek, H. P. Method for making lithium nickel ferrite having a rectangular hysteresis loop, P (4) 105*i*.

Etablissements Poliet & Chausson. Process and apparatus for thermal treatment of powdered or granulated materials, P (7) 194*h*.

Ethyl Corp. Carbonaceous solid bodies and processes for their manufacture, P (8) 217*f*.

Ettre, K. Accurate glass coatings applied from transfer tapes, (2) 30*a*.

Etzel, G. L., and Ryan, L. D. Article banding apparatus, P (6) 149*c*.

Etzel, H. W., Gandy, H. W., and Ginther, R. J. Laser with ytterbium activated glass sensitive element, P (1) 14*e*.

Etzel, K. W. F., and Bauer, P. J. A. Process for preparing porous shaped structures of carbon or graphite, P (2) 38*c*.

Eugster, H. P. See Wones, D. R.

Eurasbest A. G. Method of an apparatus for corrugating sheets of fibrous cement [by vacuum], P (4) 101*a*.

European Atomic Energy Community—Euratom. Closure method and means for the ends of nuclear fuel rods having a very thin sheath, P (10) 273*c*.

Eutectic Welding Alloys Corp. Carbide welding rod, P (8) 208*a*. Flame-spraying torch, P (4) 91*h*, P (7) 179*c*, P (8) 208*d*, P (10) 263*g*. Flux-coated carbide welding rod, P (11) 295*i*. Flux-coated welding electrode and composition, P (5) 120*b*, P (8) 208*e*. Hardfacing electrode, P (1) 3*d*. Method, filler alloy, and flux for brazing, P (9) 232*b*. Remote powder feed for flame spraying torch, P (11) 296*c*.

Evacuated Insulation Research, Ltd. Method of producing heat insulating panels, P (7) 184*j*.

Evans, A. W. See Hughes, W.

Evans, A. W., and Arkless, K. Vapor phase oxidation of titanium tetrachloride, tetrabromide, or tetraiodide in the presence of a thorium source, P (9) 247*j*.

Evans, A. W., Arkless, K., and Peacock, J. Vapor phase oxidation, P (7) 190*b*.

Evans, D. N. See Blaine, R. L.

Evans, E. H. Sampler, P (2) 45*j*.

Evans, F. See Cheng, D. C. H.

Evans, J. L. See Carr, K.

Evans, J. W., and Schwarz, K. E. Method for finishing glass surfaces, P (5) 123*e*.

Evans, T., and Noreika, A. J. Effect of gaseous environment on the structure of sputtered GaAs films on NaCl substrates, (9) 249*d*.

Evans, T., and Wild, R. K. Plastic bending of diamond plates, (3) 84*g*. Plastic deformation of diamond below 1800°C, (8) 226*i*.

Everglades, Ltd., and Wolstenholme, S., Treuherz, W., and Hallowell, S. Process for making sheets for sound insulating, P (9) 237*c*.

Everhart, T. E. See MacDonald, N. C.

Everill, J. B. See West, H. W. H.

Eves, R. A. Method for use in the manufacture of grinding wheel assemblies, P (10) 261*f*.

Evtushenko, O. V. See Burykina, A. L.

Evtushok, T. M. See Burykina, A. L.

Evzikova, N. Z. Principles of structural-geometrical analysis of crystal faces, (9) 253*j*.

Exley, C. S. Some factors bearing on the natural synthesis of clays in the granites of southwest England, (5) 133*i*.

Exner, H. E., and Fischmeister, H. F. Evaluation of methods of characterizing the particle size of powders in the subsieve range by statistical correlation analysis, (8) 223*e*.

Eyre, B. L., and Bartlett, A. F. Determination of the Burgers vector of dislocations in deformed uranium carbide, (9) 249*f*.

Eyre, B. L., and Sole, M. J. Electron microscope studies of uranium dicarbide in single crystals of uranium carbide, B (6) 171*j*.

Eyre, P. B., and Linkison, W. S. Process for hot pressing powder, P (4) 107*a*.

Eyring, H. See Gabrysh, A. F.

Faas, K. D., and Schrier, I. Lens blocking method and device, P (3) 63*b*. Method of lens grinding, P (5) 123*g*.

Faber, J. O. Mold charge delivering means, P (2) 34*b*.

Fabian, R. J. Materials problems, (4) 114*j*. See Clauser, H. R.

Fabiniak, R. C. See Eiss, N. S., Jr.

Fabricacion de Maquinas S.A. Blank mold means with pneumatic operated plunger for fabricating seamless high optical quality glass articles, P (2) 33*c*.

Fabricius, J. H. Ceramic capacitor, P (8) 220*a*. Mixed metal-ceramic capacitor, P (3) 73*j*. See Heron, J. B., Jr.

Fadeeva, V. S. Compounding ceramic batches according to their formability, (2) 54*h*.

Fahey, R. E. See Reed, T. B.

Fahlstrom, P. A. H. H., Wilhelmsson, E. I., and Svensson, A. N. Screening device in a rotatable drum intended for grinding and/or mixing material, P (2) 48*b*.

Fahn, R. Winning and processing of bentonite, (3) 78*c*, (6) 164*e*.

Fahrenberger, U., and Harkort, D. Synthetic wollastonite—conditions for its formation and use in the manufacture of wall tile, (8) 219*a*.

Faile, S. P. Ceramic product and process of producing it, P (6) 149*e*.

Fainberg, E. A. See Kitaigorodskii, I. I.

Fair, J. E. Mold wash composition and casting mold coated therewith, P (1) 11*h*.

Fairchild Camera & Instrument Corp. Fabricating semiconductor devices, P (2) 41*j*. Monocrystal transistors with region for isolating unit, P (9) 243*h*. Surface-potential controlled semiconductor device, P (2) 43*a*. Voltage regulator, P (6) 161*c*.

Fairman, E. T., Sr. Apparatus for forming hollow glass articles, P (4) 96*g*.

Falkenthal und Presser K. G. Process for obtaining a photoelectric resistant coating, P (10) 279*i*.

Falls, H. S. Heat cleaning of fibrous glass fabrics, P (8) 212*c*.

Falls Industries, Inc. Coated graphite products, P (10) 273*d*.

Fan, Chi-yao. See Cheng, Tie-jian.

Fan, Fu-Kan, Kuznetsov, A. K., and Keler, E. K. Phase relations in the system Y_2O_3–ZrO_2 (I) yttrium zirconate and its physicochemical properties; (II) solid solutions, (5) 139*c*.

Fan, Ming. See Chen, Jia-ping.

Fang, P. H., and Fatuzzo, E. Switching properties in ferroelectrics of the family $Bi_4Ba_{m-2}Ti_{m+1}O_{3(m+2)}$, (11) 305*g*.

Fansteel Metallurgical Corp. Method of making solid capacitor, P (8) 221*b*.

Fantur, C. L. Electric incandescent lamp, P (8) 220*f*.

Faraday, B. J. See Ritter, J. C.

Farbenfabriken Bayer Akt.-Ges. Continuously operating machine for mixing and/or reacting materials, P (11) 308*g*. Gamma-ferric oxide crystals and processes for their production, P (8) 225*b*. Process and apparatus for determining the distribution of grain size in powders, P (1) 17*b*. Process for the continuous production of chromium trioxide, P (4) 109*e*. Process for the decomposition of titanium dioxide-containing minerals with hydrochloric acid, P (5) 133*j*. Process for the working up of hydrolysis acids obtained in the production of titanium dioxide, P (1) 19*b*.

Farbwerke Hoechst Akt.-Ges. vorm. Meister Lucius & Bruening. Process for preparing porous shaped structures of carbon or graphite, P (2) 38*c*.

Faria, L. J. de. See Lima de Faria, J.

Farkas, E. See Dodson, V. H.

Farley, E. P. See Marynowski, C. W.

Farmer, V. C. See Russell, J. D.

Farnsworth, P. L., and Coble, R. L. Deformation behavior of dense polycrystalline SiC, (6) 166*a*.

Farr, A. E. See Cox, J. E.

Farr, J. D., and Bowman, M. G. Thermodynamic properties and phase relations in the U–C system and selected U–M–C systems, B (6) 172*a*.

Farrell, M. R. See Willmott, K. N.

Farrington, T. See Avizonis, P. V.

Farrow, T. J. Method of cleaning mold equipment, P (10) 268*f*.

Faruqi, F. A. See Qazi, M. A.

Fasnacht, J. J. See McWilliams, D. E.; Triplett, B. L.

Fassel, V. A., Dallmann, W. E., and Hill, C. C. Critical study of carbon-reduction techniques for the determination of oxygen in thorium and yttrium metals, (5) 131*e*.

Fasselle, R. J. de. See Mellen, E. J., Jr.

Fastabend, H. See Schellmann, W.

Fatuzzo, E. See Fang, P. H.

Fatuzzo E., Harbeke, G., and Ruppel, W. Ferroelectric device, ferroelectric body, and method of fabrication thereof, P (1) 14*b*.

Faugeras, P. F. See Bourgeois, M.

Faulkner, E. A., Whippey, P. W., Newman, R. C., and Thomson, J. J. Electron spin resonance in diamond coat, (3) 81*f*.

Faulstich, M. Multicomponent systems for the production of optical glass (II) system B_2O_3–La_2O_3–ThO_2–Ta_2O_5–Nb_2O_5, (2) 32*d*. Optical glass, P (7) 184*c*.

Fay, A. C. Bathtub fitted with removable panel, center drain, and wall sealing means, P (9) 230*d*.

Fay, C. F. See Harshberger, S. D.

Fayard, M. Observation of dislocations in ordered alloys by transmission electron microscopy, B (6) 175*c*.

Feagin, R. C. See Bebbington, P. J.

Febbo, P. P., Levey, R. P., Jr., and Pohto, H. A. Pressure intensifier, P (6) 161*e*.

Feder, H., Fredrickson, D., Greenberg, E., Hubbard, W., Nuttall, R., Rudzitis, E., Settle, J., and Wise, S. Application of oxygen- and fluorine-bomb calorimetry to nuclear materials, B (6) 175*g*.

Fedock, M. P. See Limes, R. W.

Fedorov, N. F. See Toropov, N. A.

Fedorov, P. I. See Bol'shakov, K. A.

Fedorov, P. I., Dudareva, A. G., and Drobot, N. F. System InI_3–CuI, (10) 291*e*.

Fedorov, P. I., and Yakunina, V. M. Interactions of chlorides of gallium, sodium, copper(I), and silver, (11) 317*g*.

Fedorovskii, Ya. A. See Ivanov, Yu. A.

Fedorovskii, Ya. A., and Tykachinskii, I. D. Role of catalyst in the volume crystallization of glass, (1) 5*i*.

Fedoseev, A. D. See Skorik, Yu. I.

Fedoseev, A. D., and Kucharskaya, E. V. Organic derivatives of kaolin, B (2) 56*j*.

Fedoseev, I. V., and Nemkova, O. G. Oxidation of titanium nitride in dry and moist air, (4) 112*e*.

Fehner, R. H. See Lodge, J. R.

Fehr, G. A. See Greener, E. H.

Fekete, J. M. See Coleman, J. J.

Feld, I. L. See Stanczyk, M. H.

Feldhoff, H. See Schmid, H.

Feldman, C. Cathode ray tube with transparent color screen, P (3) 72*f*.

Feldman, R. F. See Ramachandran, V. S.

Feldman, R. F., and Ramachandran, V. S. Character of hydration of $3CaO \cdot Al_2O_3$, (6) 165*f*.

Feldman, R. F., and Sereda, P. J. Sorption of water compacts of bottle-hydrated cement (I) sorption and length-change isotherms, (10) 262*d*; (II) thermodynamic considerations and theory of volume change, (10) 262*d*.

Feldspar Corp. Froth flotation of micaceous minerals, P (2) 47*f*.

Felten, E. J. Binary oxide systems of niobium pentoxide with oxides of common niobium alloying elements, (10) 283*h*. See Pettit, F. S.

Felten, E. J., Sprang, P. G., and Rosen, S. Phase relations in the system $CoNb_2O_6$–$CoTa_2O_6$, (6) 169*e*.

Felton, D. A. Dielectric properties of ceramics, (3) 72*d*.

Fenn, R. W., Jr. See Bragg, R. H.

Fenner, E. Thermogravimetry of condenser ceramics, (6) 170*i*.

Fenner, G. E. Strain sensitive apparatus and elements therefor, P (8) 222*c*.

Fenstermacher, J. E., Lesser, R. C., and Ryder, R. J. Study of water content of container glasses, (2) 32*c*.

Feofilov, P. P. See Kaplyanskii, A. A.

Feofilov, P. P., and Kaplyanskii, A. A. Spectra of divalent rare earth ions in crystals of alkaline earth fluorides (I) samarium, (9) 256*d*.

Ferault, G. See Bre, M.

Ferguson, I. F. Crystallite size, strain, and shape determinations on thoria from X-ray line broadening studies, (4) 110*d*.

Ferguson, L. C., and Hardinge, H. Beneficiation means and methods for autogenous grinding systems, P (4) 109*c*.

Ferguson, R. E. Apparatus for severing glass articles by thermal shock, P (2) 32*j*.

Fernandez Navarro, J. M. See Aleixandre Ferrandis, V.

Ferrandis, V. A. See Aleixandre Ferrandis, V.

Ferrante, J. F. Dielectric-coated foil capacitors, P (2) 41*c*.

Ferranti, Ltd. Semiconductive electroluminescent devices, P (2) 42*g*.

Ferrari, A., and Kling, N. G. Apparatus for treatment of solids for analysis, P (3) 77*a*.

Ferreira, W. See Barzaghi, L.

Ferreira, W., and Greco, J. A. Obtaining semiquantitative results with DTA, (2) 44*f*.

Ferreira Alves, V. See Santini, P.

Ferrer Olmos, L. Contribution to the Study of the Kaolins of the Valencia Region, B (4) 115*b*.
Ferretti, A. See Rogers, D. B.
Ferretti, A., Rogers, D. B., and Goodenough, J. B. Relation of the electrical conductivity in single crystals of rhenium trioxide to the conductivities of Sr_2MgReO_6 and Na_xWO_3, (9) 254*f*.
Ferris, L. M. See Bradley, M. J.; Haas, P. A.
Ferris, L. M., Bradley, M. J., and Gray, R. J. Phase relations in the U–C systems as determined by chemical, metallographic, and X-ray diffraction methods, B (6) 171*i*.
Ferro Corp. Gray ceramics containing a calcined mixture of aluminum and vanadium compounds, P (11) 304*b*. Method and apparatus for producing unwoven fabric, P (11) 298*h*. Method of porcelain enameling, P (9) 232*c*.
Ferron, O. J. See Souza Santos, P. de.
Ferry, R. See Cox, S. M.
Fette, W. Material feeding device for tableting machines, etc., P (4) 107*a*.
Feuer, I. Electroluminescent zinc sulfide of optimum luminosity per gram, P (9) 243*c*.
Feuersanger, A. E. Method of making titanium dioxide capacitors, P (3) 73*c*.
Fiberglas Canada, Ltd. Method of conditioning glass fiber strands, P (11) 298*k*.
Fiedler, W. S. Process for making article of vitreous material and metal, P (9) 237*b*.
Fielding, R. G. Color comparator, P (5) 132*c*.
Figurovskii, I. A. See Savonichev, G. V.
Fillatre, A. See Rappeneau, J.
Findlay, T. J. V. See Aylward, G. H.
Fine, M. E. See Groves, G. W.
Finicle, R. L. Process for coating radioactive spheroids with pyrolytic graphite, P (7) 189*f*.
Fink, E. L. UV laser emission by crystal excitons, (1) 25*i*.
Finney, P. F., and Hoepner, R. E. Thermocouple connector, P (4) 108*b*.
Finnie, I. Method for predicting creep in tension and compression from bending tests, (5) 138*c*.
Finnie, L. N. See Searcy, A. W.
Firnhaber, M. S. Apparatus for manufacturing fibers of thermoplastic material, P (4) 96*h*.
Firsching, F. H. Process for separating rare earth metal values, P (11) 312*i*.
Firsova, T. P. See Mel'nikov, A. Kh.
Firth, B. G. Cold cathode with nickel base, calcium oxide interface, and magnesium oxide layer, P (6) 159*a*.
Fischer, A. G. Crystal pulling apparatus, P (10) 278*b*. Device for producing recombination radiation, P (10) 278*c*.
Fischer, C. H. Tooling sheet metal parts for porcelain enamel, (2) 30*c*, (4) 91*c*.
Fischer, E. Equipment for the economic manufacture of special shapes by pressing and sintering, (2) 43*c*. Glass level measurement with stationary electrodes, (2) 31*c*.
Fischer, G. O. See Boehm, H. P.
Fischer, G. W. Coating composition, P (4) 91*f*.
Fischer, J., and Heckel, E. Hot water attack on silicate glasses, (8) 209*e*.
Fischer, J. J., and Bendes, R. E. Materials mixing and blending machine, P (10) 280*c*.
Fischer, P. See Stoll, E.
Fischer, R. J. See Brandmayr, R. J.
Fischer, W. A. Process for the production of linings for metallurgical furnaces, P (3) 70*f*.
Fischmeister, H. F. See Exner, H. E.
Fisher, D. G. See Adams, R. V.
Fisher, J. C., Jr. See Roche, M. A., Jr.
Fisher, W. L. Rocks and mineral resources of east Texas, (8) 225*i*.
Fisher, W. L., and Garner, L. E. Bloating characteristics of eastern Texas clays, (8) 225*a*.
Fisher Scientific Co. Optical test device for particle counting, P (8) 224*a*.
Fishlove, H., & Co. Ornamented drinking glass, P (9) 236*h*.
Fishwick, J. H. Effect of manganese and chromite ores on the fired properties of fireclays, (8) 225*a*.
Fitch, F. T., and Braun, A. B. Method for coating actinide oxide particles using zirconia sols, P (5) 126*d*.
Fitch, F. T., and Smith, J. G. Process for preparing stabilized zirconia sols, P (9) 247*f*. Rare earth actinide metal sols, P (10) 274*h*. Sols of zirconia and hafnia with actinide oxides, P (10) 283*e*.
Fitch, H. M. Palladium decorating compositions, P (2) 48*a*.
Fitzer, E. See Bonnke, M.
Fitzer, E., and Rubisch, O. Sintered resistance body, preferably for use as heating element, P (11) 303*h*.
Fitzer, E., and Schlesinger, H. Spiral and whisker growth in pyrolytic carbon, (9) 256*e*.
Fitzer, E., and Vohler, O. Nuclear fuel element with carbon jacket, P (1) 12*a*.
Fitzgerald, J. F. See Comer, J. J.
Fitzgerald, J. V. Ceramic products, P (6) 157*c*. See Kakos, M. J.
Flaherty, L. H. See Dean, H. N.
Flanary, J. R. See Bradley, M. J.
Flatley, D. W., Becke, H. W., and Stolnitz, D. Method of forming semiconductor junction, P (8) 221*h*.
Fleet, M. E. L. Preliminary investigations into the sorption of boron by clay minerals, (3) 85*b*.
Fleet, S. G. Crystal structure of dalyite, (7) 198*b*.
Flegman, A. W. Adsorption of sodium dodecyl sulfate by kaolinite, B (2) 56*i*.
Fleischer, J. See Schwiete, H. E.
Fleischer, R. L. See Brill, R. H.
Fleischhauer, G., Hackstein, K., Huschka, H., and Venet, P. Manufacture of nuclear reactor fuel elements and their coating with pyrolytic carbon, (9) 238*a*.
Fleischmann, H. Method for producing single-phase mixed crystals, P (5) 129*j*. Mixed-crystal thermoelectric compositions, P (1) 15*a*.
Fleming, M. G. See Jones, M. P.
Flengas, S. N. See Ranford, R. E.
Fletcher, H. E., Co. Method of flame working materials, P (1) 18*i*.
Fletcher, J. M., Hyde, K. R., and Landsman, D. A. Use of fluidized beds for producing carbides, B (6) 172*c*.
Fletcher, J. R., Marshall, F. G., Rampton, V. W., Rowell, P. M., and Stevens, K. W. H. Microwave ultrasonic paramagnetic resonance of the Cr^{3+} ion in magnesium oxide, (7) 201*d*.
Fletcher, K. E. Effect of Fe^{3+} and Al^{3+} on the polymorphism of tricalcium silicate, (2) 49*c*.
Fletcher, N. H. See Freezing of water, (8) 226*d*.
Fletcher, W. W., and Sales, R. M. Methods of batch analysis (I) analysis of soda-lime-silica glass batches; (II) analysis of a lead crystal glass batch, (9) 234*b*.
Fleurence, A., and Nicolas, J. Order and disorder of certain kaolinite group minerals, (7) 201*d*.
Flex-O-Lite Mfg. Corp. Method and apparatus for production of glass beads by dispersion of molten glass, P (6) 150*h*, P (8) 211*i*.
Flexon, J. D., and Troy, H. N. Glass furnace treatment, P (7) 183*d*.
Floerke, O. W. See Dietzel, A.
Flora, L. H. Assembly methods and devices for porcelain enamel units, (9) 231*g*.
Flora, T. See Toth, K.
Florea, V., et al. Computation and experimental determination of the coefficient of cubic expansion of enamel granules, (2) 30*c*.
Flores, J. G., and Schumacher, R. B. Insulation assembly and package, P (4) 97*a*.
Flotow, H. E., and Osborne, D. W. Thermodynamic properties of ZrH_2, ZrD_2, YH_3, and YD_3, B (6) 175*f*.
Floyd, R. J. Tennessee rock and mineral resources, (7) 196*f*.
Fluks, R. See Esveldt, C. J.
FMC Corp. Carbon-containing refractories, P (10) 273*b*. Glazed ceramic articles, P (1) 13*a*. Method of inhibiting corrosion with slowly soluble phosphate glasses, P (11) 296*a*. Method of producing magnesium hydroxide having variable particle sizes, P (5) 133*i*. Method of treating glass roving, P (6) 150*c*. Microscope furnace stage, P (2) 45*i*. Recovery of phosphorus values and [$CaO.SiO_2$] cement clinker from a phosphatic ore, P (5) 119*e*.
Focht, R. M. Apparatus for plating bricks, P (9) 239*i*.
Foerster, R. Most modern stoneware pipe factory in Europe, (1) 7*e*; (6) 151*d*.
Foex, M. Methods of using plasma torches for treating powdery refractory materials, P (9) 246*i*.
Fogelberg, T. Fuels and raw materials in the Swedish Glass industry up to 1913 (I), (1) 17*g*; (II) peat and coal, (4) 93*j*; (III), (8) 209*i*.
Fogel'son, R. L. See Ugai, Ya. A.
Folberth, O. G. Mix-crystal semiconductor devices, P (9) 243*h*.
Foley, J. R. Ontario Glass Mfg. Co., (4) 90*b*.
Follett, E. A. C., McHardy, W. J., Mitchell, B. D., and Smith, B. F. L. Chemical dissolution techniques in the study of soil clays (I, II), (2) 48*f*.
Folweiler, R. C. Method for sealing ceramics, P (6) 160*f*.
Fomenko, L. A. Magnetic spectra of nickel-zinc ferrites at different temperatures, (11) 318*a*.
Fomenko, V. S. See Samsonov, G. V.
Fonderie Officine Meccaniche Bongioanni. System and device for controlling the movements of an elastic covering membrane on dies for stamping clay tile by rotating drums, P (7) 191*b*.
Foos, R. A. See Maddox, R. L.
Foote Mineral Co. Composition and method for making deoxidized steel, P (11) 295*g*. Refractory products and method of making, P (4) 102*a*.
Forber, A., and Reid, A. M. Glass containing germanium sulfide, P (2) 33*a*.
Forbes, D. H. See Manasevit, H. M.
Ford, A. R. See Campbell, J. G.
Ford, J. O. See Mulford, R. N. R.
Ford, S. D. See Dugdale, R. A.
Ford, W. F. See Jackson, B.
Ford Motor Co. Ferroelectric memory element, P (10) 278*h*.
Forland, T. See Aukrust, E.
Forland, T., Grjotheim, K., Motzfeldt, K., and Urnes, S. (editors). Selected Topics in High Temperature Chemistry, B (10) 292*f*.
Forman, I. See Aster, H.
Formigoni, N. Integrated semiconductor tunnel diode and resistance, P (2) 41*g*.
Forrat, F. See Bertaut, E. F.
Forsyth, P. F. Process for producing ultrafine silicon nitride, P (1) 12*e*.
Forth, E. W. See McMurtrie, G.
Fortin, E. G. See Lessoff, H.
Fortucci, P. See Koury, F.
Fortuna, M. T. Blown glasses of the Acre cemetery, (5) 117*i*.
Forwood, C. T., and Lawn, B. R. Plastic deformation patterns on cleavage surfaces of lithium fluoride, (9) 253*c*.
Foseco International, Ltd. Mold dressings for use in foundry practice, P (11) 302*j*.
Foster, B. E. See Blaine, R. L.
Foster, G. M. Sociology of pottery—questions and hypotheses arising from contemporary Mexican work, B (6) 172*d*.
Foster, H. R. See Demarest, P. C.
Foster, L. M., and Long, G. Refractory composition, P (11) 303*a*.
Foster, L. M., and Pilkuhn, M. Electroluminescence near band gap in gallium phosphide containing shallow donor and acceptor levels, (1) 13*h*.
Foster, P. J. Radiation from luminous flames, (1) 17*f*.
Foster, P. K. Discussion of "Tridymite-cristobalite relations and stable solid solutions," (6) 166*j*.
Foster, P. K., and Hughes, I. R. Internal stress in ceramics containing cristobalite, (10) 287*c*.
Foster, P. K., Hughes, I. R., and MacKenzie, K. J. D. X-ray diffraction and thermal expansion properties of cristobalite-containing ceramics, (10) 291*g*.
Foster, W. R. See Rockett, T. J.
Fothergill, E. W. See Emblem, H. G.
Foti, A. See Alexander, D. E.
Fournie, R., Le Clerc, P., and Saint-James, Mme. Glass electrode measurement of pH under pressure and at high temperatures, (5) 131*i*.
Fournier, R. F., and Tas, R. Color index, P (10) 262*a*.
Fousek, J. See Brezina, B.
Fox, D. C. See Haas, K. J.
Fox, J. S., and De Bord, J. H. Method for fluid mold casting using casting slag, P (2) 38*c*. Slag composition for fluid mold casting, P (3) 71*a*.
Fox, T. U. See Lyon, J. E.
Fox, W. T., and Brown, J. A. Use of time-trend analysis for environmental interpretation of limestones, (1) 25*g*.
Fraenzel, E. H. Dryer for heating and removing moisture for aggregate material, P (8) 224*g*.
Francel, J., and Jagodzinski, R. F. Coating for glass and method of applying, P (9) 235*g*.
Francel, J., and Spanoudis, L. Method for cleaning glassworking tools, P (2) 34*b*.
Franciscis, A. de. Ancient glass discovery at Herculaneum, (3) 57*i*.
Frank, J. N., and Stott, R. A. Semiconductor contact means, P (10) 279*c*.
Frank, W. Apparatus with ground glass surface for film-type distillation, P (7) 182*f*.
Franke, E. A. Improvements in sheet glass drawing equipment, (10) 265*f*.
Franke, L. Small glass furnace with low fuel consumption for melting special glasses, (8) 211*a*.
Frank-Kamenetskii, V. A., Logvinenko, N. V., and Drits, V. A. Tosudite—a new mineral, forming the mixed layer phase in alushtite, B (2) 56*f*.
Frankl, D. R. Conditions for quasi-equilibrium in a semiconductor surface space-charge layer, (10) 284*h*. Electroluminescent device, P (5) 128*c*.
Franklin, A. D. Correlation of successive atomic steps in crystals by relaxation mode analysis, (1) 19*j*.
Franklin, C. E. L. Maturing behavior of glazes (I) bubble development and clearance, (7) 190*d*; (II) effect of the ceramic body, (10) 275*e*.
Franklin, E. Thermometer devices, P (1) 17*d*.
Franklin Institute of the State of Pennsylvania for the Promotion of Mechanic Arts. Thermoelectric devices, P (1) 15*e*.
Frantz, F. D., Jr. See Martin, J. H.
Franz Clouth Rheinische Gummiwarenfabrik Akt.-Ges. Agitator for granular materials, P (11) 308*j*.
Franz, H. Solubility of water vapor in alkali borate melts, (10) 266*h*. See Mulfinger, H. O.; Scholze, H.
Franzini, M., and Schiaffino, L. X-ray determination of the iron-magnesium ratio in biotites, (7) 203*h*.
Fraser, D. B. See Dodd, D. M.
Fraser, D. B., and King, J. C. Radiation insensitive quartz crystal devices, P (10) 279*a*.
Fraser, M., and Tilly, G. P. Bonding of metal plates to semiconductor materials, P (2) 41*a*.
Frazer, B. C. See Almodovar, I.
Frear, L. See Christensen, F. L.
Freck, D. V., and Wakefield, J. Method of using protective coating over layer of lithium being diffused into substrate, P (1) 14*j*.
Freden, S. Some aspects of the physics of frost heaving of mineral soils, B (7) 204*e*.
Fredericks, W. J. See Keneshea, F. J.
Fredley, J. C., and Sleighter, G. E. Coating of glass sheet while deformable and supported on gas, P (3) 63*c*. Method and apparatus for treating glass on a pressurized fluid bed, P (3) 64*a*.
Fredrick, R. E. Thermoelectric alloy, P (3) 74*b*.
Fredrickson, D. See Feder, H.
Fredriksson, B. See Rydinger, M.
Freebury, L. S. See Consett Iron Co., Ltd.
Freeman, D. C., Jr., and Stamires, D. N. Process for compaction of zeolite powders, P (1) 11*d*.
Freeman, G. A. Iodine-containing electric incandescent lamp with heat conserving envelope, P (2) 41*k*.
Freeman, I. L. Mineralogy of ten British brick clays, (5) 124*f*.
Freeman, L. See Shelton, H. J., Jr.
Freeman, M. P., and Fussman, F. Plasma production of titanium dioxide, P (11) 312*g*.
Freeth, W. E., and Mitchell, E. J. M. Method and electrode for electric arc welding, P (3) 60*b*.
Freevol, R. H. See Svec, J. J.
Frehn, F. Production of hard metal powders, P (1) 12*a*.
Frei, E. H. See Frei, J. F.
Frei, E. H., and Schieber, M. Fluorine containing spinel-type ferrites, P (4) 104*h*.

Frei, J. F., Frei, E. H., Oppenheim, U. P., and Cowan, C. I. Optical measuring device for obtaining a first derivative of intensity with respect to wavelength, P (1) 17*e*.

Freiman, D. J. Spacer retaining clip [for packaging], P (4) 98*b*.

Freise, E. J. See Takahashi, T.

French, A. H. See Veo, L. E.

French, C. V. See Greiner, N. S.

French, P. M. See Paris, R.

Freund, F., and Gingerich, K. A. Phosphatization of compact zirconium, (9) 253*e*.

Freund, H. (editor). Handbook of Microscopy in Technology (Vol. IV, Part 3) Microscopy in Sintering Technology, Especially Ceramics and Powder Metallurgy, B (9) 258*c*.

Frey, M., and Monier, J. C. Structural interpretation of twinning in anatase, (6) 170*e*.

Freytag, J. P., and Shroff, A. M. Method of manufacturing cathodes, P (10) 279*a*.

Frick, O., and Dietrich, H. E. Novelty glass fabric, P (10) 269*e*.

Fridrich, E. G. Metal halide vapor discharge lamp with near molten tip electrodes, P (9) 243*h*. Method of glass bulb manufacture and glass bulb, P (10) 269*d*. Starting of high temperature electrode lamps, P (9) 244*e*.

Friedel, J. High-strength materials, B (2) 55*g*.

Friedman, G. M. Terminology of crystallization textures and fabrics in sedimentary rocks, (2) 47*h*. See Gevirtz, J. L.

Friedrich, W. Continuous treatment of subdivided material with gas, P (10) 262*j*.

Frieser, R. G. Fabrication of semiconductor bodies, P (2) 41*a*.

Frigerio, G. See Amato, I.

Frilette, V. J., and Maatman, R. W. Process for preparing a platinum metal-crystalline zeolite catalyst, P (4) 101*f*.

Fripiat, J. J. See Calvet, R.

Fripiat, J. J., Rouxhet, P., and Jacobs, H. Proton delocalization in micas, (11) 319*b*.

Frisch, B. Hydration of α-alumina, (9) 250*c*.

Fritts, R. W., and Richards, J. D. Semiconductor device, P (6) 160*d*

Fritzlen, G. A. See Chisholm, C. G.

Froberg, M. L. See Day, F.

Frolov, V. K. See Oshchipkov, F. P.

Frolov, Ya. A. See Gur'yanova, M. F.

Frolova, A. I. See Zegzhda, D. P.

Frolova, E. G. See Kulyamina, L. L.

Frommer, M. A., and Ish-Shalom, M. Dielectric constant of pyrogenic silica as a function of specific surface, (9) 249*f*.

Frost, B. R. T. See Bradbury, B. T.

Frost, J. A. See Connett, B. E.

Frowner, B. F., and Greenberg, I. N. Alloy junction formation temperature and electroluminescence in 4H silicon carbide, (11) 313*h*.

Fry, D. L. See Lee, R. W.

Frye, H. D., and Pinotti, F. D. Glass tube forming apparatus, P (5) 122*j*.

Fryer, C. C. Impregnation of loose and poorly consolidated materials, (7) 194*h*.

Fuchs, E. G. Determination of lattice distortion of brittle crystal powders by X-ray diffractometry, (5) 131*f*.

Fuchs, R. J. Method of inhibiting corrosion with slowly soluble phosphate glasses, P (11) 296*a*.

Fuentes Guerra, R. Spanish ceramics toponomy, (2) 28*b*.

Fuerstenau, D. W. See Healy, T. W.

Fuhr, W. See Schaefer, H.

Fuhrman, Z. A. See Vitali, R.

Fuji Iron & Steel Co., Ltd. Method and apparatus for treating steel, P (9) 232*a*.

Fuji Shashin Film Kabushiki Kaisha. Transparent crystalline glass, P (6) 151*a*.

Fujii, K. Reactions between sodium silicate solution and sodium fluosilicate, (5) 140*i*.

Fujikake, Y. See Tsuzuki, K.; Watanabe, H.

Fujimoto, M. See Otsubo, K.

Fujishige, H. Reaction kinetics of formation and sulfating of Cu ferrite, (9) 254*a*.

Fujishiro, S. Extraordinary X-ray diffraction intensities of quenched TiC powder, (10) 286*f*.

Fujita, F. E. See Iwata, T.

Fujita, F. E., and Izui, K. Observation of lattice defects in graphite by electron microscopy (I), (4) 112*e*.

Fujita, K. See Kubo, T.

Fujita, R. See Masuda, M.

Fujitsu, Ltd. Method of producing semiconductor dendrites having both planes uniform, P (6) 160*d*. Method of producing a variable-capacitance germanium diode, P (6) 160*e*.

Fujiyama, T. Magnetic properties of sintered iron compacts containing phosphorus, (6) 158*d*.

Fukker, K. See Millner, T.

Fukuda, M. See Oizumi, K.

Fukui, S. See Ota, T.

Fukunaga, J. See Yoshida, N.

Fulk, M. E. Method and apparatus for producing fibers, P (1) 7*a*.

Fulk, W. F. See Smock, G. E.

Fuller, L. E. Zirconia-boron ablation coating, P (4) 91*i*.

Fuller, R. A., Dorsey, F. E., and Kulig, C. W. Glassware annealing lehr, P (9) 236*d*.

Fuller Co. Apparatus and method for processing material, P (5) 119*c*. Conveyor discharge system, P (8) 222*g*.

Fullmer, L. D. See Wilcox, W. R.

Fulmer Research Institute, Ltd. Ceramic materials, P (3) 70*d*.

Fulrath, R. M. See Hasselman, D. P. H.; Rossi, R. C.

Funabashi, S. See Minowa, S.

Funabashi, T. See Kameyama, A.

Funasaka, W., Ando, T., and Tomida, Y. Determination of yttrium in xenotime and in monazite by the X-ray fluorescence method, (9) 245*e*.

Funatogawa, Z. See Gondo, Y.; Usami, S.

Funk, H., and Stade, H. Preparation of potassium hydrosilicates (K_2HSiO_3)$_x$, $KHSi_2O_5$(I), and $KHSi_2O_5$(II) from methanole, (3) 85*e*.

Funke, V. F. See Tumanov, V. I.

Funke, V. F., and Panov, V. S. Effect of production conditions on the composition and properties of TiC–WC–Co alloys, (8) 215*d*.

Funke, V. F., Shulepov, V. I., and Yudkovskii, S. I. Structural dependence of the electrical resistivity of WC-Co alloys, (10) 290*g*.

Furlong, L. R. See Hyde, G. R.

Furukawa, M. See Miyamoto, O.

Furumi, K. See Miyatake, K.

Furuseth, S., Selte, K., and Kjekshus, A. Arsenides and antimonides of tantalum, (3) 79*h*. Redetermined crystal structures of $PdAs_2$, $PdSb_2$, PtP_2, $PtAs_2$, $PtSb_2$, α-$PtBi_2$, and $AuSb_2$, (3) 85*h*.

Furuta, T. See Enomoto, S.

Fuschillo, N. See Gimpl, M. L.

Fuschillo, N., Gimpl, M. L., and McMaster, A. D. Nichrome-silicon monoxide cermet resistor for compatible thin-film monolithic circuits, (7) 191*i*.

Fuss, F. N. Preanodization of tantalum electrodes, P (3) 74*d*.

Fussman, F. See Freeman, M. P.

Futagami, K. Diffraction topography of the X-ray diffraction spikes of diamond, (4) 110*h*.

Futamura, M. See Inoue, T.

Futer, R. E. Changing the temperatures of objects by gas jets, P (10) 282*b*.

Fyler, N. F. Cathode ray tube using fiber optics faceplate, P (5) 128*j*. Electron gun supporting technique, P (1) 14*a*.

Gabaglio, M., and Liscia, A. Technological and economical improvements in the fabrication of UO_2 ceramic fuel, (6) 154*b*. ThO_2–UO_2 ceramic fuel fabrication, (7) 187*j*.

Gabor, C. D. See O'Donnell, J. M.

Gabor, J. D., and Baerns, M. G. Fluidization of sinterable fines, P (11) 302*e*.

Gabrysh, A. F. Reply to discussion of "Decay products of radium in ceramics and their interaction with matter," (1) 12*j*.

Gabrysh, A. F., Eyring, H., Bezirjian, O. H., and Merrill, J. H. Decay products of radium in ceramics and their interaction with matter, (1) 12*h*.

Gaca, W. Rapid strength test for cements—pressing method, (2) 29*c*.

Gadalla, A. M. M., and White, J. Equilibrium relations in the system Cu–Fe–O, (7) 199*i*. Equilibrium relations in the system CuO–Cu_2O–TiO_2, (8) 226*b*.

Gaenge, F. See Schill, H.

Gaeth, R., Schmitt, B., and Breu, R. Process for making heat insulating refractory slabs, P (8) 218*d*.

Gage, P. R. See Bartlett, R. W.

Gaigalas, A. Mineralogical and petrographic composition of southeast Lithuania Pleistocene moraines (I) variation of the amount of rock and mineral fractions in the granulometric spectrum, (9) 252*f*; (II) difference in the amount of rock and mineral fractions in morainic deposits of different age, (9) 252*g*.

Gaiger, J. Luster finishes on vitreous enamel, (3) 59*g*.

Gailey, H. J. See Lindsay, J. G.

Gainer, T. M. See Whittaker, H.

Gaines, A. M., Perrotta, A. J., and Stephenson, D. A. Phenacite-spinel transition in $LiAlGeO_4$, (10) 289*a*.

Galtanova, L. Ya. See Pchelyakov, K. A.

Gak, B. N., and Gavrilov, N. S. Rapid drying of sanitary ware, (2) 39*h*.

Galasso, F., Barrante, J. R., and Katz, L. Alkaline earth-tantalum-oxygen phases including the crystal structure of an ordered perovskite compound, $Ba_2SrTa_2O_9$, (6) 165*c*.

Galdina, N. M. Service of high alumina refractories in tank furnaces, (10) 266*g*.

Galer, R. E., Wallace, L. A., Niebuhr, V. G., and Reinecke, P. W. Method and apparatus for blending pulverulent material, P (5) 119*a*.

Galewicz, C. See Kostecki, T.

Galey, W. F., Gulotta, J. A., and Umbel, F. K. Length and area partitioning methods and apparatus, P (7) 183*c*.

Gallagher, C. A. Clay pipe, (2) 35*f*.

Gallagher, J. S. See Burns, G. W.

Gallagher, P. K. Thermal decomposition of barium and strontium trisoxalato-ferrates(III), (7) 203*d*.

Gallagher, P. K., Monforte, F. R., and Schrey, F. Making small adjustments in the composition of garnets, (1) 13*g*.

Gallagher, P. K., and Thomson, J., Jr. Thermal analysis of some barium and strontium titanyl oxalates, (1) 25*j*.

Gallet, G. L. Metallized ceramic members, P (10) 278*b*.

Gallus, F. R. See Ross, J. W.

Galos, M., and Kurti, I. Strength testing of rocks by indentation, (7) 195*e*.

Gal'perin, E. L. See Vydrevich, E. Z.

Galvin, M. F. See Smith, R. G.

Ganci, C. J. Electrical resistor, P (2) 41*g*. Metal alloy resistors, P (7) 193*h*. Resistor, P (7) 194*d*.

Gandy, H. W. See Etzel, H. W.

Gandy, H. W., Ginther, R. J., and Weller, J. F. Energy transfer and Ho^{3+} laser action in silicate glass coactivated with Yb^{3+} and Ho^{3+}, (7) 199*g*. Laser oscillations and self Q-switching in triply activated glass, (7) 180*g*.

Ganguli, D., and Saha, P. Phase transformations in a natural beryl, (8) 226*d*.

Gannon, R. E. See Vasilos, T.

Ganser, H. New definitions for characterizing optical glass, (1) 4*i*.

Garabedian, F. G. See Kestigian, M.

Garashina, L. S. See Litvin, B. N.

Garbe, S. Evaporation of water from sodium silicate glasses, (4) 93*e*. See Hunter, W. H.

Garbin, J. G. Glass sheet bending mold with horizontal support surfaces, P (10) 268*d*.

Garcia, F. G. See Gonzalez Garcia, F.

Garcia, S. G. See Gonzalez Garcia, S.

Garcia-Blanco, S. See Smith, P.

Garcia Ramos, G. See Gonzalez Garcia, F.

Garcia Verduch, A. See Garcia Vicente, J.

Garcia Vicente, J., and Garcia Verduch, A. Halloysite as ceramic raw material, (8) 225*d*.

Garcia Vicente, J., and Sanchez Conde, C. Dilatometry of ceramic raw materials, (7) 198*e*.

Gardner, A. R. New strength, new ideas with engineered whiskers, (6) 171*c*.

Gardner, R. F. G., Moss, R. L., and Tanner, D. W. Electrical properties of alpha ferric oxide containing magnesium, (4) 111*b*.

Gardon, R. Method of annealing glass ribbon, P (8) 212*i*.

Garfinkel, H. M., and Rauscher, H. E. Diffusion of radiotracer sodium by the residual surface counting technique in soda-alumina-silica glasses, (9) 233*e*.

Garif'yanov, N. S., Rubtsov, M. I., and Ryzhmanov, Yu. M. Electron paramagnetic resonance in silicate glasses containing trivalent titanium, (7) 180*i*.

Garn, P. D. Thermoanalytical Methods of Investigation, B (9) 259*i*.

Garner, L. E. See Fisher, W. L.

Garraway, W. F. Thickness measuring instrument, P (9) 237*c*.

Garrett, C. G. B. Optical maser using internal reflection, P (2) 42*a*.

Garrett, K. H., Adwick, A. G., and Batchelor, E. R. Agglomeration process for producing spheroids from nuclear fuel ceramic powder, P (4) 99*j*.

Garrison, J. W., Porter, W. F., and Schmitz, E. F. Fiber forming apparatus, P (10) 267*h*.

Gartner, A. Crusher [jaw] with reciprocating movement, P (1) 18*d*.

Garton, G. See Baker, J. M.

Gartz, C. A., Jr. See Carney, D. E.; O'Connell, T. B.

Garwood, W. E., and Kerr, G. T. Conversion catalyst comprising an aluminosilicate prepared from a hydrogen organoperoxymetalloaluminosilicate, P (4) 100*i*.

Gary, W. W. Catalyst containing activated bauxite, P (4) 100*i*.

Garzio, A. C. Lids should fit (II), (8) 206*d*.

Gasiorek, S., and Widaj, J. Microscopic examination of the surface of ceramic bodies, (11) 310*a*.

Gaska, I. Photosensitivity of high resistance semiconductors, (6) 169*e*.

Gaska, I., and Dugnas, J. Change of conductivity in some high resistance semiconductors in the powerful field of superhigh frequency, (11) 314*f*.

Gaska, I., and Laurinavicius, A. Photoconductivity in polycrystalline CdS and CdSe, (8) 226*h*.

Gaska, R. A., Goodenough, R. D., and Simpson, L. D. Recovery of lithium chloride from mixtures of other salts and metals, P (10) 283*c*.

Gaskill, A. T., Cole, D. I., and Clark, R. E. Immersible thermocouple assembly, P (7) 195*d*.

Gasparac, R. J. See Balmer, H.

Gasparac, R. J., Szaj, A. P., and Turnwald, W. Crusher clearing system, P (11) 312*e*.

Gasparac, R. J., and Zoerb, H. M. Centrifugal unit for crusher and method, P (1) 18*c*.

Gasper, W. L. Treatment of porcelain enamel pickling waste, (8) 208*e*.

Gasperin, M. $Ca_5Ta_8O_{23}$, a new double oxide of calcium and tantalum, (7) 197*f*. Crystallographic study of a double oxide of tantalum and strontium, (6) 166*h*.

Gasson, E. J., and Jenkins, R. H. Process for producing a catalyst composed of tin and antimony oxides, P (6) 155*i*.

Gastinger, E. Preparation of compounds of lower oxidation state, (3) 85*d*.

Gaston, J. E. Mineral wool quality test, P (3) 77*c*.

Gastuche, M. C. See Calvet, R.

Gates, E. Propagation and oblique reflection of slant-mode hypersonic waves in quartz, (10) 289*f*.

Gathmann, M. H. Two part hot top, P (1) 12*e*.

Gatineau, L. Distribution of isomorphous substitutions in muscovite, (7) 198*g*.

Gatos, H. C. See Hanneman, R. E.; Sadagopan, V.

Gatti, A. Hydraulically moved control devices of the lower pressing plungers in molds for tile, etc., in ceramic, P (10) 280*b*.

Gatzke, H. Development of the KERA rapid firing technique for wall tile and other ceramic products, (9) 241*h*. Industrial planning for the construction of modern ceramic plants, (1) 9*f*; (6) 152*k*.

Gaudefroy, C., Jouravsky, G., and Permingeat, F. Marokite, $CaMn_2O_4$, a new mineral, (6) 168*d*.

Gault, J. M. Adjustable [monocrystalline] semiconductor punch-through device having three junctions, P (10) 277*g*. Field effect transistor, P (11) 306*e*.

Gavani, A. See Gergely, G.

Gavrilov, N. S. See Gak, B. N.
Gavrilova, I. V. See Sheftal, N. N.
Gavrilova, I. V., and Kuznetsova, L. I. Aspects of the growth of monocrystals of potassium dihydrogen phosphate, B (11) 319*j*.
Gavrish, A. M. See Sukharevskii, B. Ya.
Gayet, B., Holder, J., and Kurka, G. Melting of uranium dioxide by direct high frequency induction, (6) 153*b*.
Gazda, R. F. See Dennerlein, D. A.
Gebauer, J. See Odler, I.
Gebauer, J., and Odler, I. Cement hydration during heat treatment (II) effect of heat treatment on the phase composition and the evolution of the heat of hydration of the hydrated cement, (10) 262*c*.
Gebhardt, F., and Achilles, M. Determination of small amounts of magnesium in limestone, (10) 280*j*.
Gebhardt, F., and Kimmel, S. Analysis of glass raw materials by X-ray fluorescence spectroscopy, (6) 146*j*.
Gebrueder, Buehler. Mixing machine, P (10) 280*c*.
Gecsey, J. See Sapoff, M.
Geer, M. R. See Yancey, H. F.
Gefen, A. G. See Shelyubskii, V. I.
Geffcken, W. Multicomponent systems for the production of optical glass (I) fundamental relations, (2) 32*d*. Optical properties of glass systems (I) specific extinction of lead borates in glasses in admixture with barium borate, (5) 121*h*.
Gegznaite, L. See Pipinys, P.
Gehl, L. J. Method for molding cup-shaped bodies, P (9) 243*c*.
Gehrecke, S., Schaefer, H., and Schenkel, G. Statistical analysis of power consumption in the glass industry of the Federal Republic of Germany, (9) 234*i*.
Gehring, R. W. See Saunders, H. S.
Geiger, G. H., and Wagner, J. B. Electrical conductivity of hematite containing titanium or calcium and reduction of the doped hematite to magnetite in CO/CO_2 mixtures, (5) 135*e*.
Geilmann, W. Contributions to the knowledge of ancient glasses (IV) decomposition of glasses in the soil, (6) 144*b*; (VI) peculiar weathering phenomenon on Roman glass fragments, (6) 144*c*; (VII) cobalt as a coloring agent, (6) 144*a*.
Geilmann, W., Berthold, H. J., and Toelg, G. Contributions to the knowledge of ancient glasses (V) weathering products on window panes, (6) 144*c*.
Geilmann, W., Guenon, E., and Toelg, G. Silicate microanalysis (VI) determination of small contents of titanium and iron oxides in glasses according to the Tiron procedure, (4) 107*e*.
Geilmann, W., and Toelg, G. Silicate microanalysis (I) silica determination, (4) 107*d*; (II) determination of sulfate content, (4) 107*d*; (III) determination of phosphate content, (4) 107*e*; (IV) determination of calcium and magnesium oxide contents, (4) 107*e*; (V) determination of content of sodium and potassium oxides, (4) 107*e*; (VII) separation plan for the complete analysis of a small soda-lime glass sample, (4) 107*f*.
Gel'd, P. V. See Dubrovskaya, L. B.; Korshunov, V. A.; Krentsis, R. P.; Shveikin, G. P.
Geldermans, P. See Ahn, J.
Geller, H. I. See Prokopowicz, T. I.
Geller, S. Magnetic behavior of substituted ferromagnetic garnets, (9) 251*c*. Vanadium-containing garnets, P (10) 279*i*.
Gellner, L. Automatic presses for the ceramic industry, (2) 43*d*.
Gemesi, J. Limits and possibilities of the use of sonic energy in the silicate industry and in silicate research, (7) 195*c*.
Gendelev, S. Sh., and Yur'eva, E. K. Oxidation of crystals of ferrites with the spinel structure during growth by the verneuil method, B (11) 320*b*.
General Abrasive Co., Inc. Coated abrasive grain, P (11) 293*f*.
General Dynamics Corp. Burner assembly, P (11) 311*j*. Fuel element, P (8) 217*a*. Method of forming an insulating bond, P (5) 129*a*. Multiaperture ferrite core, P (1) 15*a*. Refractory material, P (10) 274*j*. Variable inductor [ferrite], P (10) 279*j*.
General Electric Co. Alloy, P (2) 37*j*. Apparatus for panel lamp manufacture, P (8) 211*g*. Base end structure for electric lamps, P (8) 220*j*. Bent end electric lamp having lead wires anchored at ends of bend and provided with expansion portion, P (5) 128*h*. Boron nitride having a new structure, P (1) 10*h*. Cathodic glow gaseous discharge device, P (5) 128*a*. Ceramic lamp construction, P (6) 158*j*. Coating composition, P (4) 91*f*. Crystal growing apparatus, P (10) 278*a*. Cubic boron nitride com act and method for its production, P (5) 11 Diamond-cubic boron nitride *pn* junction, P (10) 278*d*. Discharge lamp manufacture, P (7) 192*e*. Dispenser cathode, P (6) 159*b*, P (11) 305*f*. Electric discharge device, P (8) 220*e*; having improved dispenser cathode, P (11) 305*h*. Electric incandescent lamp, P (1) 6*g*, P (8) 220*fg*. Electric incandescent lamp with integral fuse, P (1) 6*g*. Electric lamp filament support, P (11) 298*b*. Electric lamp making apparatus, P (4) 96*f*. Electric lamp manufacture, P (1) 6*g*. Electric lamp with single ended pinch seal, P (11) 298*c*. Electrical capacitors and method of making, P (11) 305*j*. Electroluminescent cells with phosphor-conductor adhesion and manufacture thereof, P (8) 220*j*. Electroluminescent lamp manufacture, P (4) 104*e*, P (6) 159*e*. Electron emitter with activator of silicide, boride, or carbide of solid solution of barium and at least one other alkaline earth metal, P (9) 243*d*. Electron emitter utilizing nitride emissive material, P (11) 306*a*. Electrothermal fragmentation [of rock], P (1) 18*e*. Fluorescent panel lamp, P (4) 104*g*. Fluorescent panel lamp coating, P (7) 193*a*. Fluorescent panel lamp faceplate with opaque striping, P (6) 159*h*. Fluorescent panel lamp structure, P (8) 221*b*. Gearless rotary mill, P (11) 308*j*. Glass bodies and methods of treatment, P (11) 298*e*. Glass composition for hermetic seals, P (11) 296*a*. Glass-to-metal and glass-to-ceramic seals, P (11) 296*a*. Growth of single crystals, P (6) 159*h*. High pressure method and apparatus, P (11) 308*j*. High pressure [quartz] discharge lamp seal and base, P (2) 41*e*. High pressure metal vapor discharge lamp, P (4) 105*e*. High pressure sodium vapor lamp, P (7) 193*d*. High strength fibers, P (1) 6*f*. Hot cathode electron tube, P (2) 41*e*. Image tube having external semiconductive layer on target of wires in glass matrix, P (3) 73*f*. Immersible thermocouple assembly, P (7) 195*d*. Inhomogeneous magnesia-alumina optical lens, P (1) 6*h*. Inlet orifice for continuous casting apparatus, P (10) 274*b*. Inorganic bonded reconstituted micaceous products, P (1) 14*d*. Integral reflector tubular lamp, P (1) 6*h*. Iodine cycle incandescent electric lamp, P (6) 159*b*. Lead barium niobate ceramic composition, P (3) 73*g*. Luminescent niobates, P (6) 159*c*. Luminescent silicon carbide and preparation thereof, P (5) 128*i*. Magnetic bodies having magnetic anisotropy comprising conjoined thin films of molybdenum and nickel coated on a nonconductive substrate, P (6) 159*c*. Magnetic material, P (7) 193*g*. Manufacture of electroluminescent cells, P (8) 221*f*. Manufacture of helium separation apparatus, P (11) 298*d*. Metal to ceramic sealing structure, P (1) 14*h*. Metal halide vapor discharge lamp with near molten tip electrodes, P (9) 243*h*. Metallic halide electric discharge lamps, P (5) 128*j*. Metallizing filament, P (7) 193*i*. Method for converting hexagonal boron nitride to a new structure, P (1) 11*h*. Method of forming gallium arsenide semiconductor devices, P (9) 243*j*. Method for forming silica articles, P (9) 236*a*. Method of glass bulb manufacture and glass bulb, P (10) 269*d*. Method of joining thermoelectric elements and thermocouple, P (7) 193*b*. Method for making an electrolytic grinding wheel, P (2) 27*g*. Method for making thermistors and article, P (2) 42*b*. Method of manufacturing an electroluminescent panel, P (5) 129*g*. Method for producing lead telluride thermoelectric elements by vacuum hot-pressing, P (10) 279*c*. Method for sealing ceramics, P (6) 160*f*. Method for sputtering niobium or tantalum thin films, P (11) 307*d*. *N*-type semiconducting cubic boron nitride, P (2) 42*j*. Panel lamp inlead structure having a notched edge for lead-in conductors, P (5) 129*c*. Panel lamp seal, P (6) 150*f*. Panel lamp with terminal bases, P (8) 221*f*. Process for sealing vacuum-tight spinel bodies, P (6) 160*b*. Quartz to metal seal, P (1) 15*d*. Radiation sensitive electroluminescent devices, P (1) 15*e*. Radioactive apparatus for measuring temperature, P (5) 132*c*. Reflector fluorescent lamp, P (11) 307*b*. Remote reading temperature indicating system, P (9) 246*e*. Resistance furnace, P (1) 18*a*. Sealed electrical assembly, P (11) 307*c*. Semiconducting glass, P (9) 237*b*. Semiconductor contact means, P (10) 279*c*. Semiconductor switch, P (6) 160*j*. Small [<200 A] *pn*-junction tunnel-diode semiconductor, P (5) 130*c*. Solid-state electron source, P (2) 42*j*. Solion cell comprising a porous cathode on each side of the anode, P (1) 15*a*. Solion with graphite separators and electrodes, P (1) 15*a*. Spark tube having activated thermionic electrodes, P (11) 308*c*. Starting of high temperature electrode lamps, P (9) 244*e*. Storage electrode, P (5) 130*d*. Strain sensitive apparatus and elements therefor, P (8) 222*c*. Thermionic emitter and method of making, P (4) 106*e*. Thermocouple probe, P (5) 132*d*. Thin film storage electrode, P (1) 15*f*.
General Electric Co., Ltd. Articles of fused silica, P (2) 40*j*. Fluorescent lamp with a phosphor coating of platelike crystals, P (6) 159*g*.
General Instrument Corp. Contact for solid state diode, P (11) 305*d*. Controlled [silicon] rectifier comprising a resistive plating interconnecting adjacent *n* and *p* layers, P (11) 305*e*. Method of connecting contacts to thermoelectric elements, P (6) 159*f*. Method of making a transducer, P (7) 193*f*. Method of producing a semiconductor device, P (2) 42*f*.
General Kinematics Corp. Stepped [vibratory] screens, P (5) 131*b*.
General Micro-Electronics, Inc. Packaged electronic device, P (9) 243*j*.
General Motors Corp. Ceramics, P (5) 130*i*. Dry grinding of ceramics, P (5) 130*j*, P (8) 222*g*. Foundry mold coating, P (2) 37*f*. Method of making a thermionic device, P (6) 159*j*. Method of producing ohmic contacts on semiconductors, P (5) 129*i*. Mold and core coating composition from calcined hydrated aluminum silicate, mica, and bentonite, P (6) 155*c*. Muffler construction, P (10) 263*i*. Resistor composition and devices embodying it, P (5) 129*i*. Semiconductor device and method of fabricating, P (6) 160*e*. Silver oxide palladium electrode, P (1) 15*a*. Spark plug with multiple conductive seals, P (11) 308*e*. Spark plug and seal therefor, P (4) 106*c*. Spark plug with visual indicating discharge bulb, P (6) 161*c*. Transistor electrode connection, P (8) 222*b*. Uranium monocarbide thermionic emitters, P (5) 127*b*. Zirconium boride bearing, P (1) 12*f*.
General Precision, Inc. Microwave modulator using single crystal ferrite [sphere], P (5) 129*b*. Precision glass molding process and apparatus, P (2) 34*d*.
General Refractories Co. Basic carbon refractory, P (8) 217*b*. Basic refractory [metal clad] brick unit, P (4) 100*d*. Divided taper brick, P (3) 70*f*. Hinged refractory brick hanger, P (9) 240*d*. Lining of a converter, P (7) 188*c*. Magnesia refractory product and process, P (9) 240*i*. Method of forming plastic blocks, P (6) 154*j*. Plastic block forming machine, P (6) 155*d*. Process of making magnesia chrome refractory brick of increased strength at elevated temperatures, P (7) 189*h*. Refractory wall construction, P (11) 303*d*.
General Refractories, Ltd. Suspended refractory bricks, P (8) 218*g*.
General Telephone & Electronics Laboratories, Inc. Bonded synthetic mica laminate, P (4) 104*b*. Energy converter, P (11) 306*b*. Method of making titanium dioxide capacitors, P (3) 73*c*. Methods and apparatus for producing crystalline materials, P (3) 75*a*.
Genet, F. Preparation of disk samples from powders for examination by the Seeman-Bohlin method, (3) 76*h*.
Genshaft, Yu. S. See Livshits, L. D.
Geo. P. Reintjes Co., Inc. Dryer furnace wall tile, P (3) 77*f*.
George, D. See Williams, N. R.
George, H. J. C. Process of forming dielectric materials for condensers, P (3) 74*e*.
George, J. E., Zellers, J. T., Jr., King, R. P., and Miller, A. H. Sheet glass bending roll, P (11) 299*g*.
George, T. D. See Hilton, A. R.
Georgia Kaolin Co. Apparatus for whitening clay, P (5) 133*c*.
Georgia Tech Research Institute. Method and apparatus for obtaining data for determining surface area and pore volume, P (10) 281*h*.
Gerasimov, E., Lepkova, D., and Chervenkova, N. Production of foamed refractories, (6) 153*j*.
Gergely, G. Excitation spectra of ZnS phosphors (I) theoretical analysis, (11) 316*d*.
Gergely, G., Adam, J., and Bauer, G. T. Excitation spectra of ZnS phosphors (II) experimental results, (11) 316*d*.
Gergely, G., Gavani, A., and Burgos, M. E. Excitation spectra of ZnS phosphors (III) low temperature effects, (11) 316*d*.
German, W. L. Revolution in firing techniques, (3) 77*f*.
Gerritsen, H. J. See Sabisky, E. S.
Gerry, R. J. Protected refractory articles, P (7) 189*g*.
Gerson, R. See Jaffe, H.
Gerstenberg, D. Tantalum nitride film resistor, P (6) 161*b*.
Gertsik, E. M. See Nabiullin, F. H.
Geschwender, H. See Shoemaker, R. H.
Gessner & Co. G.m.b.H. Process for producing an insertion paper for the ceramic industry, P (10) 276*f*.
Gethard, P. E. See Zumwalt, L. R.
Getto, A. Ferrite process, P (11) 306*d*.
Getty, R. J. Agglomerating alumina, P (10) 282*i*.
Geulen, H. Sand quality requirements for the production of mirror glass, (3) 62*f*.
Geusic, J. E. See Johnson, L. F.
Geusic, J. E., and Van Uitert, L. G. Nd^{3+}-YAG laser amplifier and oscillator, P (8) 221*e*.
Gevirtz, J. L., and Friedman, G. M. Deep-sea carbonate sediments of the Red Sea and their implications on marine lithification, (11) 315*d*.
Ghose, S. Mg^{2+}–Fe^{2+} order in an orthopyroxene, $Mg_{0.88}Fe_{1.07}Si_2O_6$, (7) 201*c*.
Ghosh, S. K. See Heeger, A. J.
Ghosh, S. N., and Jain, S. K. Catalytic efficiency of Pyrex glass for the recombination of nitrogen ions, (8) 208*j*.
Giardini, A. A., and Tydings, J. E. Method of creating electrically semiconducting diamond, P (10) 278*f*.
Gibas, T., and Korbel, A. Examination of sintered alumina by the electron microscope using thin sections subjected to an acid and thermal treatment, (11) 310*f*.
Gibbons (Dudley), Ltd. Method of producing ceramic articles and articles produced, P (2) 38*h*.
Gibbs, D. F., and Hill, G. J. Variation of the dielectric constant of diamond with pressure, (7) 203*f*.
Gibbs, G. B. Diffusion creep of a thin foil, (9) 249*h*.
Gibbs, P. See Hills, R. G.; Vanfleet, H. B.
Gibbs, R. J. Error due to segregation in quantitative clay mineral X-ray diffraction mounting techniques, (3) 75*h*.
Gibson, J. O. Synthesis of uranium-zirconium carbide at 5000°K, B (6) 172*h*.
Gie, O. T., and Berghuis, P. J. Method of producing ceramic materials, P (4) 105*b*.
Gie, O. T., Tielrooy, H., and Biemans, L. J. M. Method of manufacturing ceramic articles by sintering preformed bodies and the ceramic articles, P (7) 196*b*.
Gier, J. de, Nienhuis, W. F., and Ruis, J. W. Cathode ray tube and method of making, P (9) 235*g*.

Giese, R. F., Jr. See Economy, J.; Matkovich, V. I.
Giese, R. F., Jr., Economy, J., and Matkovich, V. I. Interstitial derivatives of β-boron, (7) 200*c*.
Giese, R. F., Jr., Matkovich, V. I., and Economy, J. Crystal structure of YB_4, (7) 198*d*.
Giess, E. A. Vaporization of PbO–PbF_2 melt during solution growth of YIG crystals, (3) 87*a*. See Burns, G.
Giffen, J. W. Apparatus for forming glass articles, P (4) 96*g*.
Gigon, J., and Mayer, G. Device for measuring doses of thermal neutrons, P (3) 77*c*.
Gilard, P. See Bast, J. de.
Gilbert, A. Deformation and fracture of thoria, (1) 20*b*. See Reid, C. N.
Gilbert, L. M. See Scala, S. M.
Gilbert, W. W., and Swoboda, T. J. Magnetic materials and their preparation, P (6) 159*d*.
Gileva, K. G. See Skorik, Yu. I.
Gill, R. F., Jr. Manufacture of seals, P (3) 73*h*.
Gillam, E. See Norreys, J. J.
Gilles, P. W. Vaporization processes of refractory substances, B (6) 175*a*. See Wahlbeck, P. G.
Gillett, W. G. Method of fabricating abrasive leaves, P (1) 1*g*.
Gillhaus, H. UHF bushing-type capacitors, (8) 220*g*.
Gillies, G. M. See Blundell, A.
Gillott, J. E., and Ritchie, T. Note on the occurrence of crystals of calcium hydroxide and ettringite in voids in hardened portland cement paste, (1) 2*f*.
Gil'man, V. A., and Kolotyrkin, Ya. M. Mechanism of solution of zircon in acid fluorides, (9) 252*c*.
Gilmont, R., and Linton, W. R. Pressure stopcock, P (10) 269*h*.
Gilpin, W. C. See Lynam, T. R.
Gilvarry, J. J. Fracture of brittle solids (I) distribution function for fragment size in single fracture (theoretical), (3) 81*j*; (IV) two-dimensional distribution function for fragment size in single fracture (theoretical), (3) 82*a*; (V) (experimental), (3) 82*b*.
Gilvarry, J. J., and Bergstrom, B. H. Fracture of brittle solids (II) (experimental); (III) experimental results on the distribution of fragment size in single fracture, (3) 81*j*.
Gimpl, M. L. See Fuschillo, N.
Gimpl, M. L., Fuschillo, N., and McMaster, A. D. Oxidation of thin evaporated rhenium films, (7) 192*a*.
Gingerich, K. A. See Freund, F.; Knausenberger, M.
Gingerich, K. A., and Efimenko, J. Thermodynamic study of the thorium phosphides with a mass spectrometer, B (6) 175*c*.
Gingerich, K. A., and Wilson, D. W. Preparation and properties of thorium monophosphide, ThP_{1-x}, and phase studies of the partial system Th–ThP, (7) 202*f*.
Ginstling, A. M. See Budnikov, P. P.
Ginther, R. J. See Etzel, H. W.; Gandy, H. W.
Ginzburg, D. B. Glassmelting process, (9) 233*e*.
Ginzburg, D. B., and Khinkis, M. Ya. Better utilization of flue-gas heat in glass furnaces, (10) 264*g*.
Ginzburg, D. B., Matveev, M. A., and Kuksin, I. I. Rapid glass melting, (4) 95*b*.
Girard, R. T. Method for making thermistors and article, P (2) 42*b*.
Girciene, V. See Babonas, G.
Girshgorn, B. B. See Bobrova, T. N.
Gitlesen, G., and Motzfeldt, K. Melting point of alumina and some related observations, (2) 50*b*.
Giudici, M. See Asti, G.
Givargizov, E. I. See Sheftal, N. N.
Glaceries Reunies, Soc. Anon. Gravity bending furnace particularly for manufacturing bent glass sheet, P (7) 183*h*. Method and apparatus for the production of curved and hardened panes of glass, P (8) 213*e*.
Gladrow, E. M. See Thompson, C. E.
Gladyshevskii, E. I., Lakh, V. I., Skolozdra, R. V., and Stadnyk, B. I. Mutual solubility of disilicides of the transition metals from groups IV, V, and VI, (9) 252*j*.
Glaessel, C. See Metzel, H.
Glang, R. Materials and processes for passive thin-film components, (10) 277*e*.
Glas- und Spiegelmanufaktur Akt.-Ges. Method of fabricating hollow glass blocks with built-in exhaust ducts, P (10) 268*i*.
Glaser, H. I. Apparatus and method for producing flake glass, P (9) 235*d*. Continuous sodium silicate fibers, P (6) 149*h*. Method of coating continuous sodium silicate fibers, P (10) 268*g*.
Glaser, P. E., Black, I. A., Gustafson, G. L., and Soini, H. E. Apparatus for measuring thermal conductivity, P (6) 163*a*.
Glaser, P. W. See Watson, W. I.
Glaser, W. See Boggum, P.
Glaser, W., and Boggum, P. Thermal insulation in glass melting furnaces (I) thermal insulation of glass tank roofs, (9) 246*h*; (II) thermal insulation of fusion-cast tank blocks; (III), (9) 246*j*.
Glasser, F. P. See Williamson, J.
Glasson, D. R. Reactivity of lime and related oxides (XI) production of dolomitic lime, (10) 262*i*; (XII) hydration of dolomitic lime, (10) 262*j*.
Glatfelter, P. H., Co. Manufacture of calcium carbonate, P (10) 283*b*.
Glauser, A. Indirect method of detecting K_2SO_4 in portland cement clinkers, (8) 207*e*. Phase computation of portland cement clinker on an equivalent basis using Kuhl's lime standard, (2) 28*h*.
Glaverbel S. A. See Societe Anonyme Glaverbel.
Glazov, V. M. See Poretskaya, L. V.
Glazov, V. M., and Malyutina, G. L. Interactions of germanium with the arsenides of gallium and indium, (11) 317*h*.
Glenk, H., and Zott, H. Studies on magnetic amplifiers with ferrite cores, (8) 220*g*.
Glenny, E. Ceramics and the gas turbine, B (11) 320*h*.
Glenny, E., and Restall, J. E. Evaluation of the properties of protected molybdenum and 0.45% titanium-molybdenum alloy, (6) 152*a*.
Glidden Co. Manufacture of rutile TiO_2, P (2) 47*g*.
Globus, A. R. Process for the production of chrome concentrates, P (2) 48*c*.
Glotova, L. I. See Palkin, A. P.
Glukhikh, L. E., and Abrikosov, N. Kh. Investigation of the system Sn–Te in the region of the compound SnTe, (11) 318*c*.
Glushko, P. I., Dorokhov, V. I., and Nechiporenko, E. P. Oxidation kinetics of molybdenum disilicide, (10) 289*e*.
Glynn, A. T., Lisowski, H. J., and Saverse, R. R. Rotary pulverizer mill with aspirator [classifying] means, P (10) 283*d*.
Glynn, P. See Anderson, O. L.
Glynn, T. W. Window construction and glass block for use therein, P (3) 65*a*.
Gobrecht, H. Method of producing photosensitive layers of lead selenide, P (4) 105*e*.
Gobrecht, H., and Richter, A. Density measurement and disorder of lead selenide, (11) 315*j*.
Godbee, H. W., and Ziegler, W. T. Thermal conductivities of MgO, Al_2O_3, and ZrO_2 powders to 850°C (I) experimental, (6) 170*c*; (II) theoretical, (6) 170*g*.
Godden, G. A. Angerstein service and its attribution, (8) 205*i*.
Godron, Y. G. Vitreous compositions of matter, P (8) 214*a*.
Goebel, J. Decoration of ceramic ware, P (2) 40*d*.
Goeddel, W. V. Carbon coated metal carbide particles for nuclear reactor use, P (6) 154*j*. Development and utilization of pyrolytic-carbon-coated carbide fuel for the high temperature gas-cooled reactor, (3) 66*a*.
Goeser, P. A. Grinding method for interruptedly and continuously working mills and apparatus for practicing, P (2) 43*f*.
Goetzberger, A. See Nicollian, E. H.
Goggin, P. R., Henson, R. W., Perks, A. J., and Reynolds, W. N. Dimensional changes in the irradiated graphite lattice, (4) 110*i*.
Goins, R. R. Radiant heat drying method and apparatus, P (2) 46*f*.
Golay, M. J. E. Elution chromatography, P (4) 108*a*.
Golding, K. E. See Krieger, A. E.
Golding, R. D. See Dungan, R. H.
Goldman, A. See Lewis, H. D.
Goldmann, N. See Kroeger, C.
Goldmann, O., Himstedt, O., and Schwarze, E. Fuel oil gasification burner, P (6) 163*j*.
Gol'dshtein, L. Ya., and Okorokov, S. D. Possible large increase in the content of free CaO and MgO in portland cements during fusion, (2) 28*j*.
Goldsmith, G. J. See Yocom, P. N.
Goldsmith, J. R., and Northrop, D. A. Subsolidus phase relations in the systems $CaCO_3$–$MgCO_3$–$CoCO_3$ and $CaCO_3$–$MgCO_3$–$NiCO_3$, (4) 113*b*.
Goldstein, D. See Tidridge, W. A.
Goldstein, H. W. See White, D.
Goldstein, M. B., and McKinney, R. A. Application of flame-sprayed linings on the inside diameter of tubes, P (7) 179*b*.
Golightly, J. S. Bending glass sheets, P (7) 182*c*. Bending mold for glass sheets, P (3) 63*b*. Glass bending, P (2) 33*j*. Glass sheet bending mold with heat absorber, P (10) 268*d*. See Black, L. V.
Golightly, J. S., Doehlert, D. H., and Davidson, C. R., Jr. Method for bending glass sheets to compound curvatures, P (3) 64*c*.
Golightly, J. S., and McKelvey, H. E. Method and apparatus for bending glass sheets to compound curvatures, P (7) 183*f*.
Golik, E. M. See Cherepova, O. V.
Golovanov, A. V. See Golovanova, M. Ya.
Golovanova, M. Ya., and Golovanov, A. V. Effect of elastic and residual deformation on the ceramic forming process, (2) 43*d*.
Golovanova, T. G. See Belyaev, I. N.
Golubeva, M. S., and Medvedev, B. S. Ternary reciprocal system of the chlorides and sulfates of lithium and nickel, (2) 53*d*.
Goluecke, K., and Decker, H. Cone crusher, P (4) 109*d*.
Goncharov, E. G. See Ugai, Ya. A.
Goncz, J. H. Triggered spark gap, P (2) 43*b*.
Gondhalekar, R. T. See Bhide, V. G.
Gondo, Y., Usami, S., Itoh, K., Konno, H., and Funatogawa, Z. Ferromagnetic resonance in single-crystal thin films of iron, (2) 50*c*.
Gonser, B. W. (editor). Modern Materials—Advances in Development and Applications (Vol. 5), B (6) 174*g*.
Gontar, K. V. See Zakharchenko, M. A.
Gonzales, J. L. See Linares Gonzales, J.
Gonzalez Garcia, F., and Garcia Ramos, G. Ceramic clays of Andalucia (I) deposits of Guadalquivir and Corbones, Seville Province, Spain, (2) 46*h*; (II) deposits of La Campina, Seville Province, (2) 46*i*.
Gonzalez Garcia, S. Infrared spectrographic and X-ray diffraction study of a Spanish clay, (9) 250*j*.
Gonzalez Pena, J. M. See Aleixandre Ferrandis, V.
Goode, G. C., Herrington, J., and Jones, W. T. Analysis of lead titanate-zirconate ceramics—determination of lead, titanium, and niobium by differential cathode-ray polarography, (7) 194*j*.
Goode, J. H. See Bradley, M. J.
Goodenough, J. B. Properties imparted by *d* electrons, B (9) 259*d*. See Ferretti, A.; Rogers, D. B.
Goodenough, R. D. Lithium fluoride production, P (6) 164*f*. See Cooper, R. H.; Gaska, R. A.
Gooderham, W. J. Progress in laboratory apparatus, (5) 131*e*.
Goodland, N. Modernizing handmade brick production, (11) 300*g*.
Goodman, J. Method of preparing thin films on substrates by an electrical discharge, P (6) 160*b*.
Goodman, P. See Hilton, R. F.
Goodman, P., and King, C. B. Method of making high strength semicrystalline article, P (8) 213*i*.
Goodman, R. H., Bettens, A. H., and Josling, C. A. Excited X-rays identify minerals as ore moves down conveyor belt, (11) 312*c*.
Goodnight, H. See Reed, R. D.
Goodrich, B. F., Co. Catalyst comprising molybdenum oxide, tellurium oxide, and a manganese phosphate, P (4) 100*h*.
Goodrich, J. Inorganic fiber fabrics, (2) 54*h*.
Goodrich-High Voltage Astronautics, Inc. Method and apparatus for dispersing glomerate particles, P (6) 161*g*.
Goodyear, J. K., and Russell, R., Jr. New approach to vitrified technical ceramics, (9) 241*j*.
Gool, W. van. Relation between density and defect chemistry of crystalline solids, (9) 254*f*.
Gorbachev, A. A. Defective structure of fused quartz, (8) 209*b*.
Gorbai, Z. V. See Zaporozhtseva, O. K.
Gorbatenko, V. E. See Azarov, K. P.
Gorbunov, N. S. See Izvekov, V. I.
Gordon, E. See Crane, J.
Gordon, P. E., and Herczog, A. Method of manufacturing a capacitor, P (4) 105*a*.
Gordon, R. S. See Callister, W. D., Jr.
Gordon, Y. G. Glass compositions, P (7) 183*b*.
Gorina, I. N. See Makhnavetskii, A. S.
Gorle, F. G., and Huet, J. J. Powder metallurgy agglomeration method for fabrication of carbide spherical particles, B (6) 172*g*.
Gorman, L. V. Gold-germanium eutectic alloy for contact and alloy medium on semiconductor devices, P (6) 159*h*.
Gorman, R. J. See Redican, F. W.
Gorokhovskii, V. A. Stratification of glass, (1) 5*c*.
Gorokhovskii, V. A., Krogius, E. A., and Vlasov, V. A. Infrared spectroscopic investigation of the structure of films applied on glass surfaces by the aerosol method, (6) 148*a*.
Gorshtein, G. I. Ideality of systems with many isomorphic components, (10) 286*g*.
Gorski, W. Effect of X-radiation on quartz glass, (2) 31*i*.
Gort, W. J., and Tomassi, J. J., Jr. Impact-resistant glass-lined containers, P (3) 63*b*.
Gorton, A. T., Bitsianes, G., and Joseph, T. L. Thermal expansion coefficients for iron and its oxides from X-ray diffraction measurements at elevated temperatures, (2) 53*j*.
Gortsema, F. P. See Didchenko, R.
Goryacheva, V. P. See Bergman, A. G.
Goss, N. P., Watanabe, S., Kumai, K., Tsuda, S., and Matsuoka, H. Method and apparatus for treating steel, P (9) 232*a*.
Goswami, A. K. See Buessem, W. R.
Goto, F. See Hase, B.; Takita, S.
Goto, K., Russell, D. S., and Berman, S. S. Extraction and spectrophotometric determination of thorium with 8-quinolinol, (5) 131*h*.
Goto, T. See Ota, Z.
Goton, R. P. See Lowell, C. E.
Gotoo, K., and Naito, K. Study of U_4O_9 (I) anomaly of heat capacity near room temperature, (10) 290*j*.
Gotoo, K., Nomura, S., and Naito, K. Study of U_4O_9 (II) magnetic susceptibility, (10) 291*a*.
Gottardi, V., Bonetti, G., and Stanchi, L. Characteristics of container molds and their effect on the glass surface, (4) 92*e*.
Gottardi, V., and Locardi, B. Mechanism of the dissolution of metallic iron in molten glass, (4) 94*g*.
Gotthardt, H. See Konopicky, K.
Gottschalk, K. High pressure [quartz] discharge lamps seal and base, P (2) 41*e*.
Gould, T. R. Apparatus for producing glass filaments having a distributor cup within centrifugal rotor, P (5) 122*i*. See Simmers, C. D.
Gouz, C. Dislocations in ordered alloys, B (6) 175*d*.
Gow, J., III. See Barson, F.
Grabmaier, J. Method for producing highly pure rod-shaped semiconductor crystals and apparatus, P (3) 73*h*.

Grabmaier, J., and Rummel, T. Semiconductor device and method of producing it, P (6) 160*f*.
Grabmaier, J., and Sirtl, E. Method of producing mesa transistors and other semiconductor devices having portions of reduced cross section. P (6) 160*c*.
Grace, W. R., & Co. Fine sized powders of thoria, urania, and mixtures thereof and methods for their preparation, P (1) 11*d*. Method for coating actinide oxide particles using zirconia sols, P (5) 126*d*. Noncorrosive accelerator for setting of cements, (1) 3*b*. Preparation of ferric oxide sols and sol particles, P (10) 283*d*. Process for preparing microspheroidal silica, P (6) 164*j*. Process for preparing a silica-alumina-magnesia cracking catalyst, P (10) 274*f*. Process for preparing stabilized zirconia sols, P (9) 247*f*. Process for preparing synthetic faujasite, P (10) 283*e*. Rare earth actinide metal sols, P (10) 274*h*. Rare-earth oxides for polishing glass, P (10) 269*j*. Sols of zirconia and hafnia with actinide oxides, P (10) 283*e*. Temperature sensitive device, P (11) 308*b*.
Grach'yan, A. N. See Ponomarev, I. F.
Grady, R. F., Jr. Remote reading temperature indicating system, P (9) 246*e*.
Graebe, W. F. See Hart, L. D.
Graf, E. G. Ceramic capacitor, P (11) 305*b*.
Graf, R. B. See Hulse, C. O.
Graf, R. B., and Hulse, C. O. Effect of temperature on the mechanical properties of solid pressure-transmitting media (1) talc, (6) 167*b*.
Graff, W. A. Glass composition for hermetic seals, P (11) 296*a*.
Graff-Petersen, P. See Rosenqvist, I. T.
Grafton, W. F. Glass bending mold with sheet guide, P (3) 63*i*.
Graham, C. D., Jr. See Lommel, J. M.
Graham, L. J., and Chang, R. Some mechanical properties of vitreous selenium near its glass transition, (3) 85*g*.
Gramm, R. J. Optical test device for particle counting, P (8) 224*a*.
Grams, W. R., and Weininger, J. L. Solion cell comprising a porous cathode on each side of the anode, P (1) 15*a*. Solion with graphite separators and electrodes, P (1) 15*a*.
Granitsas, G. A. Electronic read-out device embodying glass coated metal wires, P (5) 128*d*.
Granquist, W. T. Synthetic silicate minerals, P (8) 225*i*. See Capell, R. G.
Grant, J. A. Method of making coated glass fiber combinations, P (10) 269*f*.
Grant, J. F. See Saunders, A. C.
Grant, W. A. See Carter, G.; Erents, K.
Grant, W. A., and Carter, G. Ion trapping and gas release phenomena, (4) 112*a*.
Grant, W. H., and Plusch, J. A. Brick treatment, P (8) 217*e*.
Graves, J. N. See Lonsdale, H. K.
Graves, K. W. Ablation in a high shear environment, (10) 263*c*.
Gravesteijn, J. C. See Vermeulen, G. A. W.
Gray, D. I. See Miller, C. F.
Gray, H. B. Molecular orbital theory for transition metal complexes, (3) 83*h*.
Gray, R. J. See Ferris, L. M.
Gray, W. E., Jr. See Bird, G. R.
Graynes, N. I. Gloss measurements—expect variations, (10) 281*c*.
Great Lakes Carbon Corp. Apparatus for making carbon electrodes or neutronic reactor core bars, P (10) 273*h*. Apparatus useful in the production of low-permeability high-density carbon and graphite bodies, P (6) 154*h*. Carbon electrodes or neutronic reactor core bars, P (10) 273*c*. Fabrication of carbon and graphite bodies, P (11) 302*c*. Production of low-permeability high-density carbon and graphite bodies, P (7) 189*e*.
Greaves, J. J. See Biglin, J. M.
Grebe, J. J., Miller, J. F., Rhinehart, W. L., and Wayt, T. R. Formable silicate composition, P (10) 273*h*.
Grebe, K. R. See Shevel, W. L., Jr.
Grebenshchikov, R. G. See Toropov, N. A.
Grebenshchikova, N. I., and Petrovskii, G. T. Kinetics of dissolution of some fluoberyllate glasses in water, (6) 148*d*.
Grebski, J. F., and Gromadowska, B. Rapid method of B_2O_3 determination in glasses containing 18% B_2O_3 by a weak source of slow neutrons, (3) 76*i*.
Grechanik, L. A. See Kitaigorodskii, I. I.
Greco, J. A. See Ferreira, W.
Green, A. C. High pressure metal vapor discharge lamp, P (4) 105*a*.
Green, A. K., Bien, F., and Bauer, E. Dislocated decoration in sodium chloride single crystals by electron bombardment, (9) 249*i*.
Green, A. P., Fire Brick Co. Suspended metal clad refractory, P (1) 12*d*.
Green, F. H., and Zurheide, G. B. Glass melting furnace with bridge wall, P (6) 150*a*.
Green, H. D. Mold coating and method of pouring ingots, P (1) 11*g*.
Green, R. J. Masking process for semiconductor elements, P (8) 221*g*.
Green, R. L. Technical developments in dinnerware—recent and current, (3) 71*g*.
Greenberg, E. See Feder, H.
Greenberg, I. N. See Frowner, B. F.
Greene, A. C., Hooper, H. O., and Bray, P. J. Thermal history of LiF single crystals during neutron irradiation, (9) 257*j*.
Greene, C. H. Surface flaws in glass and the statistics of flaw distribution, (6) 149*d*.
Greene, D. C. See Kendig, P. M.
Greene, L. E. Method of manufacturing an electroluminescent panel, P (5) 129*g*.
Greene, P. E. See Sobon, L. E.
Greener, E. H., Barone, F. J., and Hirthe, W. M. Electrical conductivity of single and polycrystalline near-stoichiometric rutile in the range 600° to 1400°C, (1) 20*j*.
Greener, E. H., Fehr, G. A., and Hirthe, W. M. Electrical conductivity of near-stoichiometric α-Nb_2O_5 in the range 900° to 1400°C, (4) 111*a*.
Greenham, A. C., Isherwood, B. J., and Wallace, C. A. Study of vibrations in quartz crystals using X-ray diffraction topography, (3) 86*i*.
Grego, P. See Dalton, R. H.
Greiner, W. Artistic development of Berlin porcelains—porcelain of the Berlin State Porcelain Factory, (8) 205*j*. Cuno Fischer, his animal ornamentation and contour reliefs, (1) 1*j*. Drinking glass for select beverage and festive occasions, (10) 261*i*. Hans Theo Baumann, (2) 27*j*.
Gremion, G., and Maire, J. Compression of agglomerated carbon at high temperature, (11) 314*d*.
Grenier, J. C., Martin, C., and Durif, A. Crystallographic study of lithium orthoniobates and orthotantalates, (9) 249*c*.
Grenier, N. S., and French, C. V. Asbestos-cement structural sheet, P (3) 70*b*.
Grenis, A. F., and Levitt, A. P. Infrared radiation of solids—refractory materials, (1) 9*f*.
Greskovich, C. See Stubican, V. S.
Gress, L., and Selka, F. Gas and liquid tight joint of graphite bodies, P (9) 240*b*.
Grgetic, E. F. See Russell, A. P.
Griest, E. M. Method of making an encapsulated impedance element, P (3) 73*b*.
Griest, E. M., and Tarcza, W. H. Electrical resistor, P (2) 41*f*.
Grieveson, P. See Alcock, C.
Griffin, J. B. Ceramic complexity and cultural development—the Eastern United States as a case study, B (6) 172*d*.
Griffith, J. S. See Bliton, J. L.
Griffith, M. V. Off-peak electricity and the lime-water reaction—novel method of storing heat, (6) 163*i*.
Griffiths, D. H. Sized glass fabric and method, P (4) 98*b*.
Griffiths, L. B. Defect structure and polytypism in silicon carbide, (11) 315*f*.
Griffiths, R., and Radford, C. Calculations in Ceramics, B (3) 88*a*.
Grigor'eva, L. F. See Totesh, A. S.
Grigor'eva, V. V., Dubinin, V. P., Sergeenkova, V. M., and Osayuk, V. V. Long-term strength of hard chromium carbide alloys, (3) 68*d*.
Grigor'eva, V. V., and Sergienkova, V. M. Growth of disperse aluminum oxide particles during the preparation of nickel specimens, (1) 21*j*.
Grigson, C. W. B., and Dove, D. B. Scanning electron diffraction of film growth, (10) 281*c*.
Grim, R. E. Some industrial applications of fundamental clay mineralogy, B (2) 56*j*.
Grimmeiss, H. G., and Scholz, H. Method of manufacturing a photoconducting device, P (9) 243*a*.
Gring, J. L., and Mooi, J. Boehmite base precursor, P (7) 188*i*.
Grinshtein, Yu. L. See Brekhovskikh, S. M.
Grishchenko, V. F. See Delimarskii, Yu. K.
Griswold, A. B. Glass image and its associations, (3) 57*j*.
Griswold, T. W. Method for controlling diffusion of an active impurity material into a semiconductor body, P (7) 193*i*.
Gritz, E. E. See Ropp, R. C.
Grjotheim, K. See Forland, T.
Grochowski, F., and Ziemba, B. Typical chemical composition of glass for tableware, (11) 297*a*.
Grodkiewicz, W. H., and Nitti, D. J. Oxide crystal growth by flux evaporation, (11) 318*d*.
Groisberg, M. S. See Yasinskaya, G. A.
Grollier-Baron, T., and Penez, A. Determination of some trace impurities in electrocast refractories, (7) 186*c*.
Gromadowska, B. See Grebski, J. F.
Gromek, M. T. See Myer, J. H.
Gronvald, F. See Westrum, E. F., Jr.
Gropyanov, V. M. See Avgustinik, A. I.
Grose, R. W. Process for recovery of titania values, P (2) 48*a*.
Grosh, R. J. See Love, T. J.
Gross, G. E., and Gutshall, P. L. Evidence of a dislocation feeding mechanism for crack reinitiation in F-colored NaCl, (6) 167*b*.
Gross, K. A. X-ray line broadening and stored energy in deformed and annealed calcite, (3) 87*e*.
Gross, P., Hayman, C., and Clayton, (Mrs.) H. Heats of formation of uranium silicides and nitrides, B (6) 175*f*.
Grosskopf, K. Constructional ceramics from the rotary table press, (11) 308*g*. See Arcuri, F.
Grossmann, G., and Ariya, S. M. Magnetic susceptibility of the solid solution of FeO in MgO, (4) 112*j*.
Grosvalet, J. Field-effect transistor devices, P (11) 306*e*.
Grosvalet, J., and Leclerc, P. Methods for manufacturing semiconductor devices, P (9) 243*g*.
Groteke, D. E. Coated mold and method of coating, P (10) 273*e*.
Groth, K. See Ekwall, P.
Grove, A. S. See Deal, B. E.
Grover, J. R. See Elliot, M. N.
Groves, G. W., and Fine, M. E. Solid solution and precipitation hardening in Mg–Fe–O alloys, (6) 169*j*.
Groves, J. D. Process for producing metal oxides, P (2) 48*e*.
Grubbens & Co. AB. Grinding apparatus, P (1) 18*e*.
Gruber, B. A. Boron phosphides, P (9) 247*e*. Method of preparing fibrous silicon carbide, P (7) 188*k*.
Grudemo, A. Conditions of cement research, (10) 262*e*.
Gruendler Crusher and Pulverizer Co. Grinders [hammer mill], P (4) 109*f*. Hammer mills, P (3) 78*g*.
Gruintjes, G. S., and Oudemans, G. J. Continuous hot-pressing, B (11) 320*b*.
Grulke, C. A. Composition of matter containing aluminum nitride and aluminum boride, P (9) 240*a*.
Grulke, C. A., and Ruggiero, J. D. Method of producing refractory body bonded by an aluminum nitride-aluminum boride composition, P (5) 126*a*.
Gruner, K. See Mueller, K. P.
Gruver, R. M. See Kirchner, H. P.
Grzelak, E. Methods of industrial enrichment of the feldspars from Strzeblow and the technological tests, (3) 78*f*.
Guarnieri, R. J. Black coating for fragile infrared radiation detectors, P (10) 277*i*.
Gubitose, N. F., and Monahan, J. J. Apparatus for assembling switches, P (11) 297*d*.
Gubkin, A. N. Ferroelectric properties of SrBa titanate, (4) 111*a*.
Gubser, R. See Bambauer, H. U.
Gubskaya, G. F., and Yevfimovskii, I. V. Electrical conductivity and viscosity of melts in the system Sb–Sb_2Se_3 in the solid and liquid states, (1) 21*a*.
Guecer, D. E., and Gurland, J. Comparison of the statistics of two fracture modes, (1) 19*h*.
Guenon, E. See Geilmann, W.
Guenther, K. G., and Haenlein, W. Mass filter and its use in glass research, (8) 210*a*.
Guenther, R. Burning process in flames in glass melting furnaces, (1) 17*e*. Conical stacks at old glassworks, (4) 92*j*. Development of the glass melting tank furnace, (4) 92*g*.
Guerra, R. F. See Fuentes Guerra, R.
Gugel, E. Refractory materials—a survey, (6) 153*d*. Silicon carbide as a constituent of industrial refractories, (10) 272*c*.
Gugel, H. Origin of the word "ceramic," (10) 292*b*.
Guggenheim, H. J., and Johnson, L. F. Laser utilizing rare earth activated yttrium and lanthanum trifluoride active media, P (5) 128*h*.
Guha, S. K., Gupta, K. S., and Sen, S. Casting property of clays and its control, (2) 39*b*.
Guidry, H. L. See Carr, B.
Guillet, G. R. Clay and shale in Ontario, (6) 164*d*.
Guinet, P. See Blum, P.
Gulde, C. J., and Holmes, A. B. Kiln for making [concrete] blocks, P (8) 207*e*.
Gul'din, I. T., Buzhinskaya, A. V., and Davydov, A. M. Simultaneous recording of the thermogram and polytherm of electrical conductivity of a melt by a Kurnakov pyrometer, (4) 107*f*.
Gul'ev, G. F. See Serdyuk, S. M.
Gulf Research & Development Co. Alumina product and its preparation, P (10) 282*j*. Aspirating [oil] spray nozzle, P (11) 311*j*. Catalyst composition comprising the oxides of alkali and chromium on eta alumina, P (6) 154*a*.
Gulf Research & Development Co. and National Lead Co. Cracking catalyst and process of cracking, P (8) 225*b*.
Gul'ko, N. V. See Berezhnoi, A. S.; Kordyuk, R. A.
Gulotta, J. A. See Galey, W. F.
Gulton Industries, Inc. Hydrophone, P (8) 221*d*. Thermoelectric generator, P (5) 130*c*.
Gumenyuk, E. L. See Cherepova, O. V.
Gumenyuk, V. S., and Lebedev, V. V. Investigation of the thermal and electrical conductivity of tungsten and graphite at high temperatures, (11) 318*c*.
Gumlich, H. E., and Schulz, H. J. Optical transitions in ZnS type crystals containing cobalt, (9) 252*g*.
Gunn, E. F., Jr. Treatment of pigmentary silica, P (11) 313*a*. See Heller, G. L.
Gunyaev, G. M. See Trostyanskaya, E. B.
Gupta, K. S. See Guha, S. K.
Gupta, S. D., Kumar, S., and Sinha, B. C. Method for the determination of trace amounts of iron in silicates, (2) 44*b*.
Gupta, S. K., and Prasad, S. N. Production of red glass bangles without selenium, (2) 32*e*.
Gupta, S. M. See Sen, P.
Gurevich, M. A. Calorimetry of vanadium carbides, (11) 314*e*.
Gurevich, Ts. N. See Kitaigorodskii, I. I.
Gurland, J. See Guecer, D. E.
Gur'yanova, M. F., and Frolov, Ya. A. Granulation of glass batch containing coarse sand, (4) 93*d*.
Guseva, A. D. See Nyankovskaya, R. N.
Gustafson, G. L. See Glaser, P. E.
Gustavson, G. E. See Erwin, L. R.
Gustin-Bacon Mfg. Co. Apparatus for detecting breaks during molten fiber formation, P (10) 267*g*. Apparatus for production of fine glass fibers, P (5) 122*j*. Expanding collet, P (7) 182*k*. Method and apparatus for forming fibers by spinning fluid blast and rotor, P (5) 123*i*.
Gutan, V. B. See Ehrenberg, W.

Guth, J. L. Properties of foreign anions in sodium aluminosilicates with three-dimensional framework, (2) 51*h*.
Gutsche, H. See Allegretti, J. E.
Gutshall, P. L. See Gross, G. E.
Gutwin, O. A. See Shevel, W. L., Jr.
Guzman, I. Ya. Porous ceramics made of highly refractory oxides and carbides, (7) 187*f*.

Haas, C. Phase transitions in crystals with the spinel structure, (5) 139*f*.
Haas, K. J., Fox, D. C., and Katz, M. J. Interactions of oxygen with surfaces of cadmium sulfide single crystals, (11) 317*i*.
Haas, P. A., and Clinton, S. D. Preparation of thoria and mixed-oxide microspheres, (10) 272*f*.
Haas, P. A., and Ferris, L. M. Dissolution of graphite-base reactor fuels by pressurized aqueous processes, (9) 238*c*.
Haba, A. See Blasiak, E.
Habashy, M. G. See El-Shamy, H. K.
Haber, J. See Bielanski, A.
Haber, N., and Lee, H. Grinder-blenders, P (5) 131*a*.
Haberecht, R. R. Semiconductor multistack for regulating charging of current producing cells, P (11) 308*a*.
Haberland, P. H. See Ropp, R. C.
Hack, P. See Mueller, H. R.
Hackett, J. W. Glass forming apparatus, P (5) 122*g*.
Hackstein, K. See Fleischhauer, G.
Hacskaylo, M., and Smith, R. C. Electrical properties of thin-film capacitors of the Dy_2O_3–B_2O_3–SiO_2 system, (8) 219*j*.
Haden, W. L., Jr., and Polon, J. A. Glycol coated attapulgite clay and compositions including it, P (4) 109*e*.
Hadert, H. Silicate cements for technical and dental use, (2) 29*g*.
Hadwiger, H. Bubbles and pinholes in cast-iron enamels, (3) 59*g*. One-coat enamels, (2) 30*i*.
Haendle, P. Wet preparation (of plastic bodies) and the machinery, (10) 280*c*.
Haenichen, J. C. High voltage semiconductor device, P (4) 105*c*. Semiconductor device and method, P (4) 106*g*.
Haenlein, W. See Guenther, K. G.
Haering, J. Large firing chamber, (11) 311*g*.
Haering, R. R. See Dumke, W. P.
Haertel, W. See Maeder, H. J.
Haertling, G. H. Grain growth and densification of hot-pressed lead zirconate-lead titanate ceramics containing bismuth, (4) 103*i*.
Haessly, W. F. Glass backup dies for multigun spot welders, (11) 295*g*.
Haessner, F. See Petzow, G.
Haeusser, A. Chemical stoneware—its development, manufacture, and use, (2) 39*c*. Salt glazing in tunnel kilns, (10) 276*c*. Sampling and winning of heavy clay raw materials, (3) 78*a*.
Haferkamp, H. See Matting, A.
Hafner, R. V. O. Maintenance of electric drives, (11) 300*f*.
Hafner, S. Order/disorder and infrared absorption (IV) infrared absorption of metal oxides with spinel structure, (3) 84*g*.
Hafner, S., and Laves, F. Order/disorder and infrared absorption (III) systems $MgAl_2O_4$–Al_2O_3 and $MgAl_2O_4$–$LiAl_5O_8$, (3) 84*f*.
Hagan, M. A. Glass bonded dry film lubricant, P (6) 149*i*.
Hagel, W. C., Jorgensen, P. J., and Tomalin, D. S. Initial sintering of α-Cr_2O_3, (2) 50*j*.
Hagemark, K. See Aukrust, E.
Haggett, R. O., and Amey, M. E. F. Transfer car system transforms brickworks, (3) 65*d*.
Haghihara, J. See Niwa, S.
Hagiwara, N. See Machida, J.
Haglington, J. B. See Lakin, J. R.
Hahn, E. L. See Riley, L. W.
Hahn, W. P. See Hannes, G. J.
Hailstone, R., and Seufert, L. E. High alumina refractory bodies, P (6) 154*c*.
Hainke, G. Method and apparatus for the manufacture of armored glass, P (2) 33*j*.
Haisty, R. W. Temperature dependence of the iron acceptor level in GaAs, (10) 291*i*. See Mehal, E. W.
Hajman, J. See Aster, H.
Hak, S. A. Contribution of a recent archeological discovery to the study of Syrian glass of the Roman period, (5) 117*i*.
Hakata, H. See Honjyo, T.
Halbig, J. B. See Wright, H. D.
Halden, F. A. See Marynowski, C. W.
Halderman, V. K. Tile, (2) 40*d*.
Hale, P. F. Composition and method for making deoxidized steel, P (11) 295*g*.
Haley, R. L., and Huffman, C. O. Apparatus and method for cutting glass sheets, P (8) 211*g*.
Halff, A. H., and Reid, A. F. Direct determination of density of solids, P (7) 195*b*.
Halg, W. See Stoll, E.
Hall, A. E. See Slayter, G.
Hall, C. R. Scattering of high energy electrons by the thermal vibrations of crystals, (3) 85*d*.
Hall, F. E. Flame-sprayed coatings, (2) 30*f*.
Hall, H. N. Refractory brick and furnace construction, P (8) 218*c*.
Hall, H. T. See Barnett, J. D.
Hall, H. T., and Compton, L. A. Group IV analogs and high pressure, high temperature synthesis of B_2O, (1) 21*h*.
Hall, J. A., Jr., and Sikina, T. V. Connection of semiconductor elements to thin film circuits using foil ribbon, P (5) 128*a*.
Hall, J. L. Bending device, P (10) 273*j*.
Hall, M. E., and Skoumbourdis, C. T. Indirect polarographic determination of aluminum, (3) 76*a*.
Hall, N. L. Ball mill with tensional and wear-resistant linings, P (11) 308*g*.
Hall, R. N. Crystal growing apparatus, P (10) 278*a*.
Hall, W. B. Deflocculants in the extrusion of clays, (3) 65*c*.
Hall, W. C. Radiation shielding composition comprising carbon and lead dispersed in cement, P (1) 3*c*.
Haller, G. L. See Burwell, R. L., Jr.
Hallowell, S. See Everglades, Ltd.
Halpern, V. See Anderson, J. C.
Halpin, W. J. Current from a shock-loaded short-circuited ferroelectric ceramic disk, (5) 128*a*.
Haltner, A. J., and Oliver, C. S. Effect of water vapor on the friction of molybdenum disulfide, (9) 238*d*.
Halverstadt, R. D., Stewart, D. A., and Hunt, C. J. Method for making an electrolytic grinding wheel, P (2) 27*g*.
Hamaguchi, Y. See Kunitomi, N.
Hamano, K. See Yamada, H.
Hamelink, W. B., and Swanson, C. E. Burner control apparatus, P (3) 77*f*.
Hamilton, C. H. Apparatus and method for making straight precision glass barrels or bodies for syringes, P (7) 182*j*.
Hamilton, D. L., Burnham, C. W., and Osborn, E. F. Solubility of water and effects of oxygen fugacity and water content on crystallization in mafic magmas, (7) 202*b*.
Hamilton, D. R. See Smith, W. J.
Hamilton, J. C. Method and mechanism for handling granular materials, P (9) 236*c*.
Hamilton, J. R. Parison mold with finish pin and plunger construction for glassware forming machines, P (11) 299*b*.
Hamlin, H. H. See Williams, A. L. W.
Hamlin, H. P. See O'Neill, B. J., Jr.
Hamman, D. J. Effects of radiation on electronic components, (4) 103*h*. See Wagner, W. A.
Hammar, M. See Dubois, A.
Hammarlund, B. G. Method of forming an [SiO_2] investment mold with potassium sulfate additive, P (5) 126*f*.
Hamme, J. V. See Stoops, R. F.
Hammer, N. A., Sr. Waterproofing preparation, P (3) 59*f*.
Hammerli, M. See Breck, W.
Hammond, D. L., and Benjaminson, A. Linear quartz thermometer, (2) 44*j*.
Hammond, J. P. Process for sintering uranium nitride with a sintering aid depressant, P (1) 12*g*.
Hammond, J. P., and Adamson, G. M., Jr. Fabrication of uranium monocarbide with a volatile sintering temperature depressant, B (6) 172*e*.
Hammond, J. P., and Sinha, K. K. Method for formulating master alloy compositions for use in dispersion hardened compacts, P (11) 302*j*.
Hammond, M. L. See Bragg, R. H.
Hampton, W. C. Radio frequency cell for gas chromatography, P (3) 77*d*.
Han, Wen-long, and Kuo, Chu-kun. Studies on the systems rare earth sesquioxides–beryllium oxide (III) stable and metastable equilibrium relation in the system Gd_2O_3–BeO, (5) 141*j*.
Handy, R. L. Quantitative X-ray diffraction measurements by fast scanning, (11) 293*i*.
Hangstefer, J. B. Method of making vertically and horizontally integrated microcircuitry, P (9) 243*j*.
Hankinson, K. D. See Stroud, D. E., Jr.
Hanna, R. Infrared absorption spectrum of silicon dioxide, (1) 22*a*.
Hanna Mining Co. Crusher jaw construction, P (6) 164*f*.
Hannam, H. J. Thin film storage electrode, P (1) 15*f*.
Hanneman, R. E., Banus, M. D., and Gatos, H. C. High pressure transition in InSb, (1) 22*d*.
Hanneman, R. E., and Strong, H. M. Pressure dependence of the emf of thermocouples, (6) 162*f*.
Hannes, G. J., and Hahn, W. P. Acoustical glass fiber panel with diaphragm action and controlled flow resistance, P (6) 149*j*.
Hanoka, J. I. See Henisch, H. K.
Hanse, A. B., and Kint, L. N. Crusher with variable opening screen grate, P (4) 109*e*.
Hansen, K. W. See Kolb, K. E.
Hansen, K. W., and Cutler, I. B. Electrical conductivity in $Fe_{1-x}O$–MgO solid solutions, (3) 81*a*.
Hansen, T. C. Effect of wind on creep and drying shrinkage of hardened cement mortar and concrete, (3) 58*e*. Influence of aggregate and voids on modulus of elasticity of concrete, cement mortar, and cement paste, (2) 28*i*.
Hansen, T. C., and Eriksson, L. Temperature change effect on behavior of cement paste, mortar, and concrete under load, (5) 118*i*.
Hansen, T. C., and Nielsen, K. E. C. Influence of aggregate properties on concrete shrinkage, (2) 28*g*.
Hansen, W. N. Preparation of binary compounds of uranium and thorium, P (11) 303*b*.
Hansford, R. C. High-silica molecular sieve zeolites, P (4) 103*c*.
Hanson, D. C. See Davies, B.; Whittemore, D. S.
Hanson, J. A. See Landgren, R.
Hanson, J. S. Glass bonded ferrite magnetic head, P (2) 41*c*.
Hanson, N. W., and Kurvits, O. A. Instrumentation for structural testing, (3) 59*c*.
Hanykyr, V. Kinetics of reaction of $SrTiO_3$ formation, (10) 287*a*.
Hanykyr, V., and Kutzendorfer, J. Determination of the extent of reaction in the formation of strontium titanate and zirconate by reactions in the solid state, (2) 49*g*.
Hara, A. See Miyoshi, A.
Hara, M. See Nakatogawa, T.
Hara, M., and Kerkhof, F. Scratch and hardness testing on broken glass surfaces in vacuum, (6) 148*i*.
Hara, N. See Takeya, Y.
Harada, M. Preparation of very fine metallic molybdenum powder, (11) 304*i*.
Haradome, M. See Hioki, R.
Harasowski, J., and Paczek, H. Method of activating bentonite clays, P (6) 164*g*.
Harbeke, G. See Fatuzzo, E.
Harbin, H. P. See Ulmer, G. C.
Harbin, H. P., Ulmer, G. C., and Padfield, R. C. Hydration resistance of periclase brick, (8) 215*i*.
Harbison-Carborundum Corp. Fused cast articles and method of making, P (5) 125*i*.
Harbison-Walker Refractories Co. Alumina refractories, P (4) 99*j*, P (6) 154*f*, P (11) 301*g*. Basic fused refractories, P (10) 273*i*. Brick treatment, P (8) 217*e*. Burned brick, P (3) 70*b*. Burned brick particularly suited for use in oxygen steelmaking, P (9) 239*j*. Burned impregnated brick, P (10) 273*a*. Calcium aluminate shapes, P (11) 301*j*. Casing brick, P (2) 37*b*. Fabrication of alumina refractories, P (3) 70*g*. Glass furnace lining, P (4) 100*c*. Immersion sampler, P (3) 70*j*. Investment molding method and compositions, P (10) 274*c*. Investment molding using refractory material and certain organic bases, P (4) 100*e*. Machine and method for making perforated brick, P (1) 11*g*. Metallurgical furnace lining, P (4) 100*i*, P (9) 240*j*. Method of forming refractory mold shapes, P (5) 126*e*. Method of lining a rotary kiln, P (11) 302*a*. Method of making monolithic refractory lining in metallurgical vessels, P (5) 126*i*. Method of recovery of magnesian values, P (11) 302*i*. Method of treating an investment mold, P (2) 38*j*. Mortar, P (1) 11*i*. New brick composition, P (1) 11*j*. Prevention of hydration, P (1) 12*b*. Prevention of hydration in magnesia refractories, P (5) 126*g*. Production of dead-burned magnesia in a shaft kiln, P (3) 70*g*. Production of refractory grain, P (4) 101*i*. Refractory, P (4) 101*j*, P (8) 218*a*, P (11) 303*j*. Refractory brick, P (4) 102*a*. Refractory with improved resistance to certain slag, P (5) 126*j*. Refractory liner brick with tongue and compound groove for forming circular tapered furnace stack constructions, P (11) 303*d*. Refractory practices, P (2) 38*f*, P (5) 127*a*. Refractory roof, P (2) 38*g*. Refractory shapes, P (5) 127*b*, P (6) 155*f*, P (9) 241*a*, P (10) 275*b*. Rotary kiln, P (8) 224*i*. Shaft kiln, P (7) 196*a*. Silica refractories, P (2) 38*f*, P (5) 127*c*. Vessel linings, P (7) 190*c*.
Harden, D. B. Glass fragments, mainly of the 12th to 13th century A.D., from northern Apulia, (9) 230*a*. Rothschild Lycurgus cup—addenda and corrigenda, (2) 27*i*.
Harden, E. H. See Craig, R. D.
Harding, A. G., and Adam, T. Thermal stress in ceramics applied as thermal barrier layers to turbine blades, (10) 263*c*.
Harding, W. E., Langdon, J. L., and Pecoraro, R. P. Method of forming contacts on semiconductors, P (10) 278*i*.
Hardinge, H. See Ferguson, L. C.; Russell, R. J.
Hardinge, H., Russell, R. J., and Zuercher, E. M. Grinding mill and process, P (4) 109*g*.
Hardy, A. E. Colorimetry of color television picture tube phosphor screens, (8) 219*i*.
Hare, W. A. Bonded alumina refractory, P (6) 154*h*.
Harel, S., Pessahovitz, Z., Klein, C. H., and Peskin, B. Process for the production of magnesium fluoride, P (9) 247*i*.
Harendza-Harinxma, A. J. Beta tantalum [oxide] thin-film capacitors, P (11) 305*j*.
Hargasser, H. See Ruechardt, H.
Harkort, D. See Fahrenberger, U.
Harkort, H. J. New deflocculants for earthenware bodies and their effects on the casting behavior and properties of the bodies, (6) 156*j*.
Harkulich, T. M., Magder, J., Vukasovich, M. S., and Lockhart, R. J. Ferroelectrics of ultrafine particle size (II) grain growth inhibition studies, (7) 191*e*.
Harmon, S. L. Pressure rollers, P (6) 150*i*.
Harms, W. O. See Carlsen, F. L., Jr.
Harper, E. A. See Brett, H. H.
Harper, H. F., Lee, B. W., and Davies, A. Method and apparatus for the production of bent toughened glass, P (3) 63*h*.
Harrell, B. R., Prindle, H. B., and Edwards, S. P. Addition of melamine-formaldehyde to magnesium oxycement to improve the resistance to the passage of water, P (5) 119*a*.
Harrell, W. C. See Kunkle, G. E.
Harrington, R. E. Anomalous surface heating rates, (9) 246*f*.
Harrington, T. L. See Vanstrum, R. C.
Harrington, W. L., Skogerboe, R. K., and Morrison, G. H. Quantitative spark source mass spectrometry using cryosorption pumping, (2) 45*g*.
Harris, D. M. Apparatus and method for producing single crystal structures, P (6) 158*d*.

Harris, H. C. See Conder, N. H.
Harris, H. M. See Paige, J. I.
Harris, H. M., Kelley, J. E., and Kelly, H. J. Devitrification of a lithium disilicate glass, (5) 120*g*.
Harris, J. E., and Masters, B. C. Effect of a surface oxide film on the lifetime of vacancies in quenched specimens, (9) 249*f*.
Harris, J. M., and Audet, H. J. Electroluminescent instrument lighting, P (2) 41*h*.
Harris, R. E. Diffusion method, P (2) 41*c*.
Harris, W. F. Pneumatic conveying—special problems of density, (3) 74*j*.
Harris, W. H., Jr. Abrading tool structure, P (7) 177*h*.
Harrison, D. E. See Subbarao, E. C.
Harrison, G. R. See Hodges, L. R., Jr.
Harrison, J. D. L. See Isaacs, J. W.
Harrison, J. D. L., and Isaacs, J. W. Preparation of UC and $(U_{0.85}Pu_{0.15})C$ by the reduction of oxides with carbon in flowing argon, B (6) 172*c*.
Harrison, J. D. L., Isaacs, J. W., Roberts, W. G., and Russell, L. E. Sintering of (UPu)C in argon, B (6) 172*e*.
Harrison, J. W. See Thorpe, T.
Harrison, W. N. Availability of the new technology, (7) 203*i*.
Harry W. Dietert Co. Base and trim water proportioning system and method, P (4) 100*d*. Cylindrical screening apparatus, P (1) 16*a*. Dryer and heater for granular material, P (4) 100*a*. Sampling mechanism, P (6) 163*d*.
Harryman, P. D., and Oakes, D. T. Method for improving the yield of an attapulgite clay, P (3) 78*j*.
Harshaw Chemical Co. Tetragonal zirconium oxide containing calcium oxide, P (3) 79*d*.
Harshberger, S. D., McKee, P. E., and Fay, C. F. Method of forming plastic blocks, P (6) 154*j*. Plastic block forming machine, P (6) 155*d*.
Hart, C. M. Worm drive for glass [drawing] machine, P (5) 124*d*.
Hart, L. D., and Graebe, W. F. Method of preparing alumina casting slips, P (9) 240*c*. Method of preparing casting slips from alumina hydrate, P (9) 240*d*.
Hart, M. Observations of Pendelloesung fringes in elastically deformed crystals, (1) 23*f*.
Hart, R. G. See Michaud, G. G. J.
Hart brothers Machine Co. Worm drive for glass [drawing] machine, P (5) 124*d*.
Hartford, W. H., Kelly, W. R., Oechsli, B. L., and Kurtz, B. E. Beneficiation of chromium ore, P (2) 47*c*.
Harth, R. See Klement, R.
Hartley, C. S., and Hirth, J. P. Resolution of stresses in single-crystal deformation, (8) 227*j*.
Hartley, K. Nuclear fuel processing, P (2) 38*j*.
Hartman, T. E., Blair, J. C., and Bauer, R. Electrical conduction through SiO films, (9) 242*h*.
Hartmann, H. J. Method of producing electrical semiconductor devices, P (11) 307*a*.
Hartmann, W. See Reich, H. F.
Hartwell, J. M. Diverse uses of montmorillonite, (7) 196*g*.
Hartwig, F. J. Tapping nozzle for molten refractories, P (2) 38*i*.
Hartwig, J. See Reidl, R. W.
Haruta, K. See Spencer, W. J.
Haruta, K., and Spencer, W. J. Strain in thin metal films on quartz, (9) 256*e*.
Harvey, M. H. New panel system makes unlimited designs possible, (8) 214*g*.
Harvey, R. D. Thermal expansion of certain Illinois limestones, (8) 225*i*.
Harwood, M. G. Electrical conductivity of rutile (III, IV), B (11) 320*g*. Variation with time of the electrical conductivity of rutile, (3) 87*a*.
Harwood Engineering Co. High pressure press, P (11) 309*a*.
Hasan, S. T., Aslam, M., and Imam, H. Utilization of Balcrete foaming agent (IV) production of lightweight cellular plaster boards, (11) 294*j*.
Hase, B., Goto, F., and Nimura, I. Comparative study on durability of three basic bricks made of magnesia clinker (96, 96, and 92% MgO) and chromite (33, 30, and 30% Cr_2O_3) used in an open-hearth furnace roof, (10) 270*h*.
Hase, B., Goto, F., and Sasaki, J. Effects of pressing velocity and period of maintenance of fixed pressure on the physical properties of firebrick during formation, (3) 67*c*.
Hasegawa, K. See Ota, E.
Hasegawa, M. See Kato, E.
Hasegawa, S. See Saito, S.
Hashin, Z. Elastic behavior of fiber reinforced materials of arbitrary transverse phase geometry, (1) 20*i*.
Hashmi, M. H., Rashid, A., Umar, M., and Azam, F. Spectrophotometric determination of gold, copper, and cobalt, (5) 131*i*.
Hasiguti, R. R. See Matsuura, E.
Hasiguti, R. R., Minami, K., and Yonemitsu, H. Electrical resistivity and defect energy levels in reduced titanium dioxide at low temperatures, (10) 285*f*.
Hass, E. See Kindel, E.
Hassell, H. L., and Bondi, A. Mixing of viscous non-Newtonian fluids in packed beds, (1) 23*j*.
Hasselman, D. P. H. Theory of thermal shock resistance of semitransparent ceramics under radiation heating, (3) 86*i*.
Hasselman, D. P. H., and Fulrath, R. M. Proposed fracture theory of a dispersion-strengthened glass matrix, (3) 62*b*.
Hastings, C. H. Measuring and controlling property variability, (2) 44*a*.
Hastings, J. A. See Schnable, G. L.
Hastings, W. F., and Lampson, M. L. Glass working conveying apparatus, P (2) 33*b*.
Hatch, S. E. See Carnall, E., Jr.
Hattori, T. See Kato, S.
Hauck, J. E. Guide to optical materials, (2) 31*f*. New inorganic filaments are stiffer and lighter than metals, (6) 171*e*. Plastics and nonmetallics, (4) 115*a*.
Hauck, J. E., and Vaccari, J. A. Aerospace materials—today and tomorrow, (2) 54*f*.
Hauck Mfg. Co. Spark monitor for fuel burner, P (9) 246*j*.
Hauschild, U. Preparation of nordstrandite, P (4) 109*c*. Process for the preparation of nordstrandite alumina, P (3) 79*c*.
Hauser, G. P. See Sayers, J. B.
Hausmann, P. See Baier, E.
Hausner, H. H. See Bonis, L. J.
Haussuehl, S. Elastic and thermoelastic properties of gypsum, $CaSO_4 \cdot 2H_2O$, (7) 199*a*.
Hauth, J. J. See Bloomster, C. H.; Mills, L. E.
Havel, V., and Kuna, L. Refractory concrete flue gas ducts, (8) 216*f*.
Haven, I. See Haven, Y.
Haven, Y., and Kats, A. Hydrogen in α-quartz, (5) 137*e*. Method of treating quartz for optical use, P (3) 64*c*.
Havens, A. B. See Stroud, D. E., Jr.
Havens, R. W. Porous metal mold for glass articles, P (8) 213*c*.
Havranek, P. H. See Davies, B.
Havranek, P. H., and Davies, B. Vessel linings, P (7) 190*c*.
Haw, S. G. Method of making a hot top, P (3) 70*c*.
Hawkes, W. H., and Moore, A. A. Evaluation of some high-alumina materials, (2) 36*f*. High temperature tunnel kiln, its operation and design, and the selection of refractories, (10) 282*d*.
Hawkins, E. G. See Napolitano, A.
Hawkins, N. J. See Affleck, J. H., III.
Hawley, G. G. Definitions and multiple meanings, B (6) 171*i*. Put punch in your writing, B (6) 171*i*.
Hawley, W. G. See Bennett, H.
Hay, J. O. Tetragonal zirconium oxide containing calcium oxide, P (3) 79*d*.
Hayakawa, K., Nunome, K., Kawase, K., and Ikuta, S. Dose estimation of electron beam by glass method, (10) 284*j*.
Hayakawa, S. See Nitta, T.; Ouchi, H.
Hayakawa, S., Nagase, K., and Nitta, T. Effects of TiO_2 on semiconduction of $BaTiO_3$ ceramics, (3) 72*f*.
Hayami, R. See Brindley, G. W.
Hayami, R., Tanaka, H., and Ogura, T. Process for manufacturing ceramic-like products from glass by microscopic crystallization, P (5) 124*c*.
Hayao, T. See Kameyama, A.
Hayashi, H. Silicosis, (10) 292*c*. See Oinuma, K.
Hayashi, N., and Iida, Y. NiO–Li_2O solid solution, (10) 288*i*.
Hayashi, N., and Miyashita, T. Display of critical switching curves of magnetic thin films on a TV picture tube, (6) 157*g*.
Hayashi, T. Experiments made to standardize erosion test methods—results of each committee, (9) 238*g*. Unfired sleeves of 90 to 93% SiO_2, (1) 10*d*. See Makiguchi, T.; Mori, S.
Hayashi, T., and Doihara, T. Study of prevention of the migration of iron oxide and silicate in basic refractories, (10) 272*g*.
Hayashi, T., and Ishizawa, K. Changes in mineral composition and physical properties of zircon ladle brick, (8) 214*j*.
Hayashi, T., and Komoda, H. Experiments made to standardize erosion test methods—analysis of results of each committee, (9) 238*h*.
Hayashi, T., and Nitta, S. Rectification phenomena in Si-SiO_2-metal diodes, (10) 277*i*.
Hayashi, T., and Shibuno, M. Effect on dolomite and magnesia clinker due to heated atmosphere, (3) 66*i*.
Hayashi, T., and Tabata, K. Tests on drain phenomenon of basic brick at high temperature, (6) 154*c*.
Hayashi, T., Tabata, K., and Okuda, S. Effect of chromic oxide addition on properties of high-fired basic brick, (10) 271*g*.
Hayashi, T., Tsuji, S., and Anazawa, S. Semiconductor devices, P (10) 279*e*.
Hayashi, Y. See Niwa, S.
Haydl, W. H., and Quate, C. F. Microwave emission from n-type CdS, (7) 201*c*.
Hayes, G. D. Method and apparatus for forming fibers, P (8) 213*a*.
Hayman, C. See Gross, P.
Hays, F. R. Method of making cathode ray tube faceplates, P (8) 213*g*.
Hazeltine Research, Inc. Gaseous discharge lamp, P (10) 278*i*.
Hazlett, R. N. See Leonard, J. T.
Head, B. L. See Bartow, W. T.
Heal, G. R. See Dollimore, D.
Healy, G. W., and Kothen, C. W. Electric furnace, P (2) 37*d*.
Healy, T. W., and Fuerstenau, D. W. Oxide–water interface—interrelation of the zero point of charge and the heat of immersion, (1) 24*a*.
Healy, T. W., Herring, A. P., and Fuerstenau, D. W. Effect of crystal structure on the surface properties of manganese dioxides, (9) 249*a*.
Heany Industrial Ceramic Corp. Wire guide for extruding machines, P (7) 190*b*.
Heap, H. R. See McMillan, P. W.
Heasley, J. H. See Cooper, A. R., Jr.
Heath, D. L. Electrical porcelain developments, (4) 102*f*.
Heaton, W. R. Glass-encased semiconductor, P (11) 306*g*.
Heckel, E. See Fischer, J.
Heckroodt, R. O., and Roering, C. High-aluminous chlorite—swelling chlorite regular mixed-layer clay mineral, (7) 200*e*.
Hedger, H. J. Arc-melting of uranium carbide, B (6) 172*f*. See McLaren, J. R.
Hedger, H. J., and Williams, J. Uranium nitride-iron nuclear fuel cermets, P (5) 127*b*.
Hedger, H. T. See Brett, H. H.
Hedges, A. J. Gunned refractories, (2) 36*j*.
Hedley, C. S. See Lynam, T. R.
Hedvall, J. A. Activity of solid surfaces, (3) 79*f*.
Heeger, A. J., Ghosh, S. K., and Blocker, T. G., III. ^{55}Mn nuclear magnetic resonance in manganese ferrite, (2) 50*d*.
Heeley, E. J. Tension strength of some vitreous enamels, (5) 119*g*.
Heestand, R. L., and Leitten, C. F., Jr. Single-step process for preparation of uranium dioxide from uranium hexafluoride, P (9) 241*b*.
Heflinger, L. O. See Brooks, R. E.
Hegyi, I. J. Monoclinic zinc phosphide preparation, P (4) 105*h*.
Heide, H. See Neuhaus, A.
Heigl, C. Present-day German ceramics—exhibition of the Bavarian State Industrial Institute, Nuernberg, Oct.-Nov. 1965, (6) 144*b*.
Heijmer, G. B. Surface coating compositions comprising plaster of Paris and method of producing, P (8) 207*g*.
Heim, E. See Borgstedt, H. U.
Heindorf, W. See Vogel, W.
Heinemann, H., Kraus, J. W., and Spector, M. L. Method of sealing refractory vessel containing radioactive wastes, P (1) 11*d*.
Heinrich, E. W. Microscopic Identification of Minerals, B (9) 258*g*.
Heinze, G., Knopf, H., and Schubert, K. Process for the continuous production of chromium trioxide, P (4) 109*e*.
Heissing, H. See Ruechardt, H.
Heiter, G. L. Ferrite frequency converter with dielectric low pass filter, P (9) 243*d*.
Helbing, C. H. Coating composition and method of preparation, P (8) 212*c*. Method for producing glass fibers, P (11) 299*f*. See Dennis-ton, D. W.
Helfferich, F. See Peterson, D. L.
Helgesson, C. Flame-sprayed ceramic coatings, (2) 30*e*.
Heller, G. L., White, J. W., and Gunn, E. F., Jr. Process for producing pigmentary silica, P (5) 134*a*.
Heller, L. Sorption of glycol and glycerol by preheated monoionic montmorillonite, B (2) 56*d*. See Bodenheimer, W.
Heller, L., and Ben-Yair, M. Effect of sulfate solutions on normal and sulfate resisting portland cement, (9) 230*j*.
Heller, P. V. N. See Andres, R. J.
Helme Products, Inc. Fluid [jet] grinding mill with interchangeable liners, P (4) 106*j*.
Helming, B. H. Method of and arrangement for dressing moist raw materials with solid undesired inclusions, P (8) 207*f*.
Helsen, J. See Calvet, R.
Hemming, N. R. Ceramics in the hypersonic air-breathing engine, B (11) 320*h*.
Hemstock, G. A. Color-reactable inorganic adsorbent pigment and coating composition containing it, P (3) 71*j*. Color-reactable inorganic adsorbent pigment and sensitized sheet material coated therewith, P (4) 109*d*. High surface area aluminum silicate and method of making, P (3) 78*g*. Method of treating chrysotile and product produced, P (2) 47*j*.
Henault, N. C. See Loscudo, F. A.
Hencken, H. G. Polishing pads, P (6) 150*i*, P (9) 236*i*.
Henderson, B. Exchange-coupled F-center pairs in magnesium oxide, (9) 250*b*.
Henderson, C. M. Thermoelectric unit and process of using to interconvert heat and electrical energy, P (9) 244*c*.
Henderson, J. See Ward, R. G.
Henderson, M. I. Particle studying device control circuit, P (11) 311*c*.
Hendrickson, E. A. Mosaics—Hobby and Art, B (6) 174*g*.
Hendrix, W. P. See Orr, C., Jr.
Hengge, E. Preparation of a new silicon subnitride, $(Si_6N_2)_n$, (3) 85*e*.
Henin, S. See Caillere, S.
Henisch, H. K., Dennis, J., and Hanoka, J. I. Crystal growth in gels, (6) 166*a*.
Henker, H. See Siebertz, K.
Hennequin, F. Surfacing of glass, P (2) 34*j*.
Henney, J., and Jones, J. W. S. Phases in the zirconium–carbon–oxygen system, B (11) 320*e*.
Henney, J., Jones, J. W. S., and Hill, N. A. Cell size variations in thorium monocarbide, B (6) 171*j*.
Hennicke, H. W., and Leers, K. J. Determination of elastic constants by the dynamic (resonance) method, (6) 144*i*.
Hennicke, H. W., and Lehmann, H. Softening under torsional stress, (10) 272*c*.
Hennicke, H. W., and Niesel, K. Dehydration of pyrophyllite, (6) 166*a*.
Hennicke, H. W., Schwiete, H. E., and Sieckmann, J. Determination of the wear resistance (hardness) of glazes, (8) 218*j*.

Hennig, G. Lamellar compounds of graphite with nitrogen pentoxide as possible reactor hazards, (3) 83*h*.
Henry, G. Device for cooling drawn glass, P (5) 122*c*.
Henry, G., Brichard, E., and Plumat, E. Apparatus for melting products such as glass and method of working, P (10) 267*a*.
Henry, G. R. Metallurgical furnace lining, P (4) 100*i*. See Davies, B.
Henry, G. R., King, D. F., and Davies, B. Prevention of hydration, P (1) 12*b*.
Henry, J. L. Method of preparing alumina refractory, P (9) 240*d*.
Hensley, J. L. Methods of making abrasive wheels, P (8) 205*f*.
Hensoldt, M., & Soehne, Optische Werke AG. Method of producing a glass scale, P (4) 97*d*.
Henson, R. W. See Goggin, P. R.
Hepburn, L. L. Gas mixing, P (5) 132*d*.
Herbert, J. L. Opal glass with a low coefficient of thermal expansion, P (11) 299*a*.
Herbert Simpson Corp. Mixer, P (7) 194*g*.
Herbst, J. Glass Technology Practice, B (4) 115*b*.
Herbstein, F. H., and Snyman, J. A. Identification of Eckstrom-Adcock iron carbide as Fe_7C_3, (7) 200*a*.
Herczog, A. See Borrelli, N. F.; Gordon, P. E.
Herenguel, J. See Boghen, J.
Hergenrother, K. M. Method of growing single crystal silicon carbide, P (4) 101*d*.
Herkimer, P. F., and Lottridge, N. M., Jr. Mold and core coating composition from calcined hydrated aluminum silicate, mica, and bentonite, P (6) 155*c*.
Herkimer, P. F., Lottridge, N. M., Jr., and McCullough, D. G. Foundry mold coating, P (2) 37*f*.
Hermann, F. Detection of excess kiln heat, (11) 311*f*.
Hermann, P. See Mueller-Neuglueck, H. H.
Hermanski, W. Use of microscopy in the field of electrotechnical and electronic ceramics, (11) 310*h*.
Hermsdorf, C. Use of dust protection apparatus in the ceramic industry, (10) 280*c*.
Heron, J. B., Jr., and Fabricius, J. H. Ceramic capacitor, P (6) 158*i*.
Herpin, A. G. See Boucher, B.
Herrera, J. E. See Vanik, M. C.
Herriman, J. D. See Arkless, K.
Herring, A. P. See Healy, T. W.
Herrington, J. See Goode, G. C.
Herrmann, E. R. Method of molding ceramic articles, P (5) 131*c*.
Herrmann, K. R. Measuring the thixotropy of plastic ceramic bodies, (10) 275*g*. Study of the buckling of flat-bottomed vessels, (2) 40*a*; reply to discussion, (2) 40*c*.
Hersch, P. A. Electrochemical gas analyzer, P (3) 77*d*. Method and means for oxygen analysis of gases, P (3) 77*b*.
Herzog, A. H. See Derby, W. R.
Heslop, R. B., and Pearson, E. F. Effect of arsenate and of transition-metal ions on the precipitation of phosphate as ammonium 12-molybdophosphate, (2) 44*c*.
Hess, F. B., and Erskine, G. B. Glass tubing severing machine, P (5) 123*a*.
Hess, F. O. Industrial burner with recuperative means, P (10) 282*c*. Manufacture of structural slabs, P (6) 154*g*.
Hess, R. J. Vibratory screw feeder, P (1) 16*c*.
Hesse, A. Yielding bowl locking ring for crushers, P (11) 313*a*.
Hesselbarth, H. See Lehmann, H. A.
Hesselbrock, H. Problems of electrostatic dust removal and requirements for further technical development, (11) 308*i*.
Hettes, K. Venetian trends in Bohemian glassmaking in the 16th and 17th centuries, (2) 28*b*.
Heuer, A. H. Deformation twinning in corundum, (9) 249*d*.
Heuer, R. P. Basic carbon refractory, P (8) 217*b*. Basic refractory [metal clad] brick unit, P (4) 100*d*. Lining of a converter, P (7) 188*e*. Magnesia refractory product and process, P (9) 240*i*. Process of making magnesia chrome refractory brick of increased strength at elevated temperatures, P (7) 189*h*.
Heyer, R. H., and Newby, J. R. Formability of porcelain enameling sheets, (9) 231*i*.
Heyman, A. A. Apparatus for forming surfaces of optical elements, P (8) 211*f*.
Heyne, C. A., and Johnson, J. R. Article decorating, P (7) 182*b*.
Heystek, H. Components of a diversified lab, (2) 54*h*.
Hibino, T. See Wakao, Y.
Hickman, B. S. See Walker, D. G.
Hickman, B. S., and Williams, L. S. Effect of neutron irradiation on molybdenum, niobium, and zirconium disilicides, (5) 135*b*.
Hicks, J. W., Jr. Doubly clad light-conducting fibers with the outer cladding being partially light absorbing, P (8) 212*e*. Fiber optical scanning device, P (6) 149*h*. Metal and glass fiber structures and electrical devices using same, P (6) 159*e*. Method of forming a fused energy-conducting device, P (3) 64*d*. Method of making metal and glass fiber structures, P (10) 269*f*.
Hidy, G. M., and Lilly, D. K. Solutions to the equations for the kinetics of coagulation, (4) 113*b*.
Higashi, A. See Muguruma, J.
Higashi, I. See Atoda, T.
Higgins, E. L. See Sparks, R. A.
Highberg, C. W. Grinding of materials with hard abrasives, P (5) 117*g*. Surfacing of materials, P (6) 151*b*.
Higuchi, S., and Yasunaga, K. Reduction in regenerator checker-brick consumption by raking hot slag out of open-hearth furnace slag chamber, (10) 272*b*.
Hilbiber, D. F. Voltage regulator, P (6) 161*c*.
Hildebrandt, M. See Vassiliev, A.
Hill, C. C. See Fassel, V. A.
Hill, G. J. See Gibbs, D. F.
Hill, J. S., and Albert, H. J. Loss of weight of platinum, rhodium, and palladium at high temperatures, (3) 83*a*.
Hill, N. A. See Henney, J.
Hill, P. R., and Trout, O. F., Jr. Heat protection apparatus, P (11) 296*b*.
Hill, R. F., Paprocki, S. J., and Keller, D. L. Method of making a thermionic device, P (6) 159*j*. Uranium monocarbide thermionic emitters, P (5) 127*b*.
Hill, R. M., and Dore, B. V. Energy converter, P (11) 306*b*.
Hillig, W. B., and Charles, R. J. Surfaces, stress-dependent surface reactions, and strength, B (2) 55*h*.
Hillman, G. E. See Blakemore, G.
Hills, R. G., and Gibbs, P. Positive impurity ion emission from α-quartz, (9) 253*d*.
Hilton, A. R., and Jones, C. E. Nonoxide IVA-VA-VIA chalcogenide glasses (II) infrared absorption by oxide impurities, (11) 296*j*.
Hilton, A. R., Jones, C. E., and Brau, M. Nonoxide IVA-VA-VIA chalcogenide glasses (I) glass forming regions and variations in physical properties, (11) 296*h*.
Hilton, A. R., Jones, C. E., Dobrott, R. D., Klein, H. M., Bryant, A. M., and George, T. D. Nonoxide IVA-VA-VIA chalcogenide glasses (III) structural studies, (11) 297*b*.
Hilton, D. A., and Buddery, J. H. Conversion of irradiated fuel swarf to a stable ceramic suitable for long-term storage, (1) 8*i*.
Hilton, R. F., and Goodman, P. Refractory materials, P (4) 102*c*.
Hilton, R. F., Steen, W. J., and Steele, B. C. H. Refractory products and their production, P (5) 127*b*.
Hilton, R. M. See O'Connor, J. R.
Hime, W. G., and LaBonde, E. G. Particle size distribution of portland cement from Wagner turbidimeter data, (3) 59*e*.
Himmelstein, P., Liebmann, B., and Schoefer, L. Fabrication of cast uranium carbide rods, B (6) 172*f*.
Himstedt, O. See Goldmann, O.
Hinder, J. W. Ceramic creations of Konrad Quillmann, (6) 144*b*. Dieter Crumbiegel, teacher and ceramist, (8) 205*i*. Dorothea and Volker Ellwanger, potters in the Black Forest, (8) 205*j*. Ruth Koppenhoefer, a Palatinate potter, (10) 261*j*. Small studio of high standing—Signe Lehmann, (1) 2*a*.
Hinkle, J. H., Jr., Weaver, E. J., and Smith, L. M. Tricalcium phosphate, P (6) 165*a*.
Hinz, I., and Dietzel, A. Phase boundaries of the cubic mixed crystal ZrO_2-MgO from 1800°C to the melting point, (7) 202*c*.
Hinz, W., and Kunth, P. O. Phase separation and nucleation in the preparation of glass-ceramics, (4) 94*d*.
Hioki, R., Haradome, M., and Kukimoto, H. Photoconductivity of sintered (Cd,Zn)S layers, (10) 289*b*.
Hippel, A. R. von. Building from atoms, B (9) 259*d*. Conduction and breakdown, B (9) 259*f*. (editor) Molecular Designing of Materials and Devices—Papers Presented at the Third Summer Session on Modern Materials Research Sponsored by the Laboratory for Insulation Research, Massachusetts Institute of Technology, Cambridge, 1963, B (9) 258*h*. Survey, B (9) 259*d*.
Hiragushi, K. See Ohba, H.
Hirai, M. See Sugiura, M.
Hirai, T., and Iwaki, T. Method of manufacturing electrodes for fuel cells, P (1) 11*c*.
Hiraiwa, O. See Suzuki, K.
Hiramatsu, A. Comparative study on a cupola lined with (1) roseki brick and unfired fireclay brick and (2) roseki brick and ZrO_2 patching material, (1) 8*c*.
Hirano, M. See Takeya, Y.
Hirayama, C. Nd^{3+} fluorescence in alkali borate glasses, (6) 148*h*. See Melamed, N. T.
Hirayama, H. See Kumai, H.
Hirota, E. See Kubota, B.; Nakayama, N.
Hirsch, R. Programmed valve system [for a glass molding machine], P (7) 184*g*.
Hirschowitz, B. I., and Peters, W. Method and apparatus for making fibrous light-conducting devices, P (5) 123*j*.
Hirshon, J. M. Semiconductor device and method of fabrication, P (10) 279*d*.
Hirst, D. M. See Oyawoye, M. O.
Hirt, T. J., and Palmer, H. B. Kinetics of deposition of pyrolytic carbon films from methane and carbon suboxide, (4) 112*c*.
Hirth, J. P. Kinetic and thermodynamic properties of surfaces—surface energy, surface diffusion, and growth and dissolution or evaporation processes, B (7) 204*e*. See Hartley, C. S.
Hirthe, W. M. See Greener, E. H.
Hirthe, W. M., Melville, A. T., and Wackman, P. H. Preparation by ion bombardment of near-stoichiometric rutile (TiO_2) for transmission electron microscopy, (9) 253*e*.
Hi-Speed Blending and Mixing Corp. Grinder-blenders, P (5) 131*a*.
Hitachi, Ltd. Method of manufacturing sintered materials, P (10) 274*h*. Single multielectrode electron tube having a disk shaped ceramic stem with a recessed portion in one face thereof, said recess portion having a metal layer thereon, P (11) 308*c*.
Hitachi Ranpu Kabushiki Kaisha. Method of producing phosphors, P (4) 105*d*.
Hivac, Ltd. Method of constructing cold cathode gas discharge tubes, P (4) 105*d*.
Hjelm, L. N. See Wurst, J. C.
Hlabse, T., and Walton, A. G. Nucleation of calcium phosphate from solution, (2) 44*e*.
Hlavac, J., and Strnad, P. Kinetics of SiO_2 solution in $Na_2O \cdot 2B_2O_3$ melt, (7) 200*g*.
Hlavac, J., and Strnad, Z. Dissolving of disperse SiO_2 in a melt of $Na_2O \cdot 2B_2O_3$, (10) 284*k*.
Hlavac, J., and Vaskova, L. Crystallization of reduced silica glass in an oxidizing atmosphere, (2) 31*c*.
Ho Bin Im. See Im, H. B.
Ho, L., and Levine, A. K. Bonded synthetic mica laminate, P (4) 104*b*.
Hoadley, G. B. See Mattauch, R. J.
Hoagland, L. C. See Reti, A. R.
Hoak, R. D. See Bramer, H. C.
Hobaugh, J., Otto, H., and Padilla, V. Shaped refractory heat exchange bodies and process for making, P (7) 189*j*.
Hobbs, H. A. See Campbell, W. B.
Hobson, J. P. Measurements with a modulated Bayard-Alpert gage in aluminosilicate glass at pressures below 10^{-12} torr, (10) 281*f*.
Hoch, W., Abeck, W., and Hund, F. Gamma-ferric oxide crystals and their production, P (8) 225*b*.
Hochberg, M. S. See Kummer, D. L.
Hochmann, K. See Sterk, E.
Hockin, J., and Charlton, R. J. Monolithic investment shell casting, P (1) 11*h*.
Hocquard, R. Elements of construction in glazed lightweight concrete, P (8) 208*c*.
Hodge, N. See Sowden, R. G.
Hodge, N., Moreton-Smith, M., White, D. B., and Sowden, R. G. Behavior of carbides in hydrogen and oxygen, B (6) 172*i*.
Hodges, C. M. See Crookston, J. A.
Hodges, H. W. M. Aspects of pottery in temperate Europe before the Roman Empire, B (6) 172*e*.
Hodges, L. R., Jr., Rodrigue, G. P., Harrison, G. R., and Sanders, A. D. Magnetic and microwave properties of calcium vanadium-substituted garnets, (9) 251*d*.
Hodgkins, C. E. See Carter, G.
Hodgson, A. A. Fibrous Silicates, B (11) 319*i*.
Hodgson, B. P. See McMillan, P. W.
Hoekstra, K. See Schoenlaub, R. A.
Hoenig, C. L., and Searcy, A. W. Knudsen and Langmuir evaporation studies of stannic oxide, (4) 112*d*.
Hoens, M. F. A., Murdoch, A. W., and Bubenicek, J. Mechanical strength of enameled ware, (11) 295*i*.
Hoepner, R. E. See Finney, P. F.
Hoeppner, W. L. Refractory development in the glass furnaces, (2) 36*h*.
Hoffman, J. G. See Mulford, R. N. R.
Hoffman, L. C. Resistor compositions, P (1) 15*e*, P (5) 130*a*.
Hoffman, M. S. Low cost method of sanding brick, (1) 7*i*. New moving-envelope kilns, management incentive programs keep Jackson China competitive, (1) 12*j*.
Hoffman, P. See Akerman, K.
Hoffman Electronics Corp. Semiconductor device, P (8) 221*j*.
Hoffmann, U. Ceramics reinforced with fibers, (10) 275*f*.
Hoffmann, W. See Bayer, G.
Hofmann, F., and Schafer, L. Apparatus for manufacturing shapes of uranium carbide, P (9) 239*i*.
Hofmann, U. See Boehm, H. P.
Hohmann, F. R. Method for drawing glass, P (7) 184*a*.
Hohmann, M. See Mehlo, W.
Hokkeling, P., Koch, A. J. J., Marks, C. P., Steeg, M. G. van der, Vos, K. J. de, and Zijlstra, H. Process for making MnAl permanent magnet having tetragonal phase, P (10) 279*h*.
Holcomb, R. H. Integral reflector tubular lamp, P (1) 6*h*.
Holcomb, R. H., and Thomasson, G. I. Quartz to metal seal, P (1) 15*d*.
Holdash, I. J. Mounting means for abrasive products, P (9) 229*g*.
Holden, A. F. High emissivity coatings for furnaces, (9) 232*a*.
Holden, A. N. Ceramics for the nuclear age at Vallecitos [Atomic Laboratory], (2) 36*d*.
Holden, R. L. See Seymour, J. A.
Holder, J. See Gayet, B.
Holdridge, D. A. See Keeling, P. S.
Holister, G. S. Determination of *in situ* stresses in rock and concrete, (4) 108*j*.
Holl, W. W., Jr., and Walton, R. W. Apparatus for treatment of solids for analysis, P (3) 77*b*.
Holland, C. J., and Buell, H. W. Flexible abrasive coated cloth, P (5) 117*f*.
Holland, H. See Lehmann, H.
Hollander, L. E., Jr. See Quinn, R. A.
Holle, R. F. Fluorescent panel lamp structure, P (8) 221*b*.
Holler, E. J. Method and apparatus for forming multiple-bore tubing, P (6) 150*f*.
Holley, C. E., Jr. See Hubbes, E. J., Jr.

Hollister, E. Broach for curved graphite passages, P (11) 301*i*.
Holloway, P. W. See Baker, C. L.
Hollox, G. E., and Smallman, R. E. Oxidation products of titanium carbide, (7) 201*h*.
Holm, J. L. Phase relations in the systems NaF–LiF, NaF–KF, and NaF–RbF, (3) 84*g*. Phase transitions and structure of the high-temperature phases of some compounds of the cryolite family, (3) 84*h*.
Holmes, A. B. See Gulde, C. J.
Holmes, L., and Schieber, M. Magnetic ordering in Eu_3O_4 and $EuGd_2O_4$, (9) 251*e*.
Holmes, S. D. See Arnold, V. E.
Holmquist, S. B. Hydrothermal silica transformations, (8) 226*g*. Ionic formulation of redox equilibria in glass melts, (5) 121*b*. Oxygen ion activity and the solubility of sulfur trioxide in sodium silicate melts, (10) 265*j*.
Holophane Co., Inc. Glare reducing refractor, P (7) 183*a*. Luminaire, P (7) 183*d*.
Holschlag, J. B. See Day, F.
Holstein & Kappert Maschinenfabrik Phonix G. m.b.H. Bottles, P (1) 6*e*.
Holzinger, R. J., Reid, L. E., and Blake, G. D. High temperature lubrication process, P (11) 311*g*.
Homarek, K. L., and Silver, M. Thermodynamic properties of zirconium-oxygen, titanium-oxygen, and hafnium-oxygen alloys, B (6) 175*g*.
Homeyer, R. H. Resilient-backed abrasive stone, P (4) 89*g*.
Honda, H. See Miyatake, K.
Honda, H., Sanada, Y., and Inoue, K. Diamond synthesis by electric discharge shock technique, (4) 110*f*.
Honda, T. See Namazu, R.
Honeycombe, R. W. K. Microstructure of steels, B (6) 173*h*.
Honeywell, Inc. Burner control apparatus, P (3) 77*f*. Controlling apparatus, P (11) 294*j*. High temperature sensors, P (3) 77*a*. Low friction material, P (3) 70*a*. Temperature measuring apparatus, P (6) 163*e*.
Honjyo, T., and Hakata, H. Apparatus for automatically inspecting ampoules, P (2) 32*h*.
Hooker Chemical Corp. Tricalcium phosphate, P (6) 165*a*.
Hooper, F. C., Millar, C. H., and Loth, J. L. Technique for the evaluation of surface absorptivity of materials exposed to plasma radiation, B (6) 173*e*.
Hooper, G. D. Magnetic material, P (7) 193*g*.
Hooper, H. O. See Greene, A. C.; Knutson, C. D.
Hootman, H. E. See Knudsen, I. E.
Hoover, J. I. See Ritter, J. C.
Hope, A. J. N. See Davy, J. R.
Hopkins, R. W. How to use caustic soda in glass, (2) 31*f*.
Hopwood, T. W. Attrition mill apparatus and method, P (1) 18*c*.
Horak, L. Determination of the content of blast-furnace slag in cements, (8) 206*j*.
Horan, J. J., Brown, J. R., Jr., and Pressler, M. F. Open hemispherical transducers, P (4) 105*j*.
Horder, B. R., and Sowden, R. G. Vacuum sintering of uranium/plutonium carbides, B (6) 172*e*.
Hori, J. Electroluminescence in SiC single crystals, (10) 276*j*.
Horibe, T., Kuwabara, S., and Yamada, H. Change of strength of brown electrocorundum abrasive grains by heat treatment, (5) 117*f*.
Horiguchi, Y. Formation of zinc orthosilicate by explosive shock, (10) 286*j*.
Horiuchi, S., and Yamaguchi, J. Diffusion of boron in silicon through oxide layer, (10) 284*c*.
Horizons, Inc. Method of preparing fiber reinforced metals, P (2) 38*f*. Preparation of alumina monofilaments, P (11) 303*a*. Preparation of carbide structures, P (11) 303*c*. Preparation of inorganic oxide monofilaments, P (11) 303*d*.
Horn, A. J. See Bell, K. R.
Hornstein, M. How to choose a glass grinder, (3) 61*i*.
Hornung, A. Tool life of grinding wheels, (8) 205*f*.
Horspool, J. M. See Mowat, J. A. S.
Horton, J. C., and King, H. M. Method of making impurity-type semiconductor electrical contacts, P (11) 306*e*.
Horton, R. A. See Watts, C. H.
Horton, R. C. See Marzocchi, A.
Horton, R. C., Alexander, M. R., and Miller, W. H. Method of coating flexible fibrous glass strands, P (4) 97*a*.
Horwedel, L. C. Industrial uses for solid lubricants, (8) 215*b*.
Hosbein, L. H. Refractory wall and nose construction, P (6) 155*f*.
Hosbein, L. H., and Kimmlinger, K. T. Means for mounting metallic members in brick molds, P (6) 154*i*.
Hosono, H. See Nakamura, H.
Hossain, M. A. See Das, M. B.
Hostetler, D. T. Oscillating limestone shaker, P (5) 133*j*.
Hotine, W., and Babcock, S. W. Variable inductor [ferrite], P (10) 279*i*.
Hou, Pao-hang. Microscopic identification of stones in window glass production, (3) 61*d*.
Houck, R. L. See Allen, A. C.
Hough, R. L. Pyrolytic titanium diboride filaments for composites, (4) 99*i*.
House, O. F. See Cassaday, H. L.
Housley, F. Zircon bricks in glost tunnel kilns, (2) 37*i*. See Clements, J. F.
Houston, J. M. Electric discharge device having improved dispenser cathode, P (11) 305*h*.
Hove, J. E., and Riley, W. C. (editors). Ceramics for Advanced Technologies, B (5) 142*e*. Modern Ceramics—Some Principles and Concepts, B (5) 142*i*.
Howard, W. E. See Chang, L. L.
Howatt, G. N. Hydrophone, P (8) 221*d*.
Howatt, G. N., and Schwartz, D. S. Thermoelectric generator, P (5) 130*c*.
Howe, E. E. Comparative properties of porcelain enamel and organic finishes, (9) 231*h*.
Howe Sound Co. Apparatus for the production of ceramic, cermet, and metal components, P (10) 280*e*. Ceramic multilayer graphite mold and method of fabrication, P (7) 188*i*. Graphite mold and fabrication method, P (10) 273*i*. Graphite shell molds and method of making, P (9) 240*c*. Mold and method of fabrication, P (9) 240*j*. Precision casting mold and methods and materials for production and use, P (6) 155*d*. Precision mold and method of fabrication, P (6) 155*e*.
Howeth, M. S., Thornton, H. R., and Burroughs, J. E. Materials vs. heat: how to protect materials from heat, (4) 114*j*; how to test and evaluate the effects of heat, (4) 114*i*; properties of materials in a heat environment, (4) 114*i*.
Howitt, T., Jr. See Cortright, S. A.
Howl, D. A., and Mann, C. A. Back-pressurizing technique of leak testing, (2) 43*j*.
Hoynant, G. Method of producing porous carbon elements, P (7) 188*i*.
Hren, J. See Ranganathan, S.
Hrishikesan, K. G. See Armbrust, B. F., Jr.; Brown, W. H.; Carithers, V. G.; Watson, D. R.
Hrma, P. Determination of the structural and mechanical properties of the kaolin-water system, (7) 198*a*.
Hrovat, M., and Speuer, G. Pressed spherical graphite fuel elements for high temperature reactors, (9) 238*g*.
Hsu, Hsiao-pai. See Chang, Hwei-min.
Hu, Ho-fang, and Kan, Fu-hsi. Infrared absorption spectra of Ce^{3+} ions in glass, (3) 61*i*.
Hu, Hui-chung. See Chien, Ju-chung.
Hu, Yung-pu. See Ting, Chao-rung.
Hu, Yung-pu, and Ting, Chao-rung. Investigation of the determination of SO_3 in gypsum and portland cement by the static-ion exchange method (I) determining SO_3 in gypsum, (4) 90*f*.
Huang, A. B. Analysis of physical adsorption isotherms in ultra-high-vacuum range, (9) 248*c*.
Huang, Ching-kuen. See Chen, Jia-ping.
Huang, C. Y. D. See Ebling, W. F., Jr.
Huang, Dah-neng, and Wang, Wen-yee. Aspects of the mechanical strength of cement and concrete, (6) 144*f*.
Huang, Hsi-huai. See Chen, Sho-hsian; Chou, Yu-hwa.
Huang, I-hsuan. See Wang, Chang-wen.
Huang, S. See Edwards, P. L.
Hubal, K. H. See Nitzsche, S.
Hubbard, E. K. See Blaine, R. L.
Hubbard, S. E. See Monk, C. B.
Hubbard, W. See Feder, H.
Hubbes, Z. J., Jr., and Holley, C. E., Jr. Thermodynamic properties of the actinide carbides including new measurements of the heats of formation of some Th, U, and Pu carbides, B (6) 175*d*.
Hubble, D. H., and Kappmeyer, K. K. Slag erosion resistance of various types of BOP brick, (8) 216*c*.
Hubble, D. H., Kappmeyer, K. K., and Debenham, W. S. Development, properties, and service of direct-bonded basic brick, (1) 8*c*.
Hubble, D. H., and Silverman, E. N. Method of producing stainless-clad steel plate, P (5) 123*h*.
Huber, J. M., Corp. Amorphous hydrogen aluminosilicate pigments, P (9) 247*d*. Kaolin clay beneficiation, P (3) 78*j*.
Huber, W. R., and Tisinai, G. F. Deeply hardenable [steel] liner member for grinding mill, P (7) 194*f*.
Hubert, A. See Roj, W.
Hucke, E. Automation in the production of lightweight aggregate, (2) 35*d*. Controlling apparatus, P (11) 294*j*.
Hudd, R. N. Factors in purchasing of porcelain enamel process equipment, (6) 145*f*.
Huddle, R. A. U. Nuclear fuel materials, P (4) 101*b*.
Huet, H. See Delange, M.; Vertes, P.
Huet, J. J. See Gorle, F. G.
Huff, D. R. Method of making containers of bonded fiber glass, P (2) 34*g*.
Huffaker, V. J. Adobe making machine, P (4) 98*f*.
Huffman, C. O. See Curtze, E. W.; Haley, R. L.
Hughes, C. S. Method of preparing tile surfaces, P (4) 98*h*.
Hughes, E. E. G. See Thomas, J. M.
Hughes, F. H. Method of weakening vitreous tubes to facilitate breaking thereof, P (5) 123*i*.
Hughes, G. See Bickerdike, R. L.
Hughes, I. R. Mineral changes of halloysite on drying, (10) 288*f*. See Foster, P. K.
Hughes, O. H., Tredgold, R. H., and Williams, R. H. Photoemission studies on barium titanate, (9) 253*g*.
Hughes, R. C. Method of making mercury-doped germanium semiconductor crystals, P (11) 306*i*.
Hughes, W., and Evans, A. W. Production of metal oxides, P (1) 19*b*.
Hughes Aircraft Co. Bonds for oxidized materials, P (6) 158*g*. Ceramic-metal seal, P (8) 220*c*. Compound semiconductor devices, P (10) 278*a*. Device for slicing crystalline material, P (11) 305*f*. Gold bonded boron containing semiconductor devices, P (2) 41*d*. Gold boron alloy and method of making the same, P (1) 11*e*. Method of making alloy connections to semiconductor bodies, P (4) 105*h*. Method of making a ceramic supported semiconductor device, P (8) 221*j*. Method for making a gallium arsenide transistor, P (7) 193*d*. Method of making semiconductor devices, P (4) 105*a*. Method of measuring nuclear radiation utilizing a semiconductor crystal having a lithium compensated intrinsic region, P (3) 77*b*. Method of producing stable gallium arsenide and semiconductor diodes, P (7) 193*h*. *P*-type alloy bonding of semiconductors using a boron-gold alloy, P (2) 42*c*. Semiconductor diode and method of making, P (7) 194*e*. Silicon bonding technology, P (6) 160*j*. Thermal radiant energy detecting device, P (9) 244*b*. Thermocompression bonding chisel, P (1) 15*d*.
Hughes Tool Co. Drop hammer impact tester, P (10) 281*g*.
Hugle, F. B., and Hugle, W. B. Semiconductive films and method of producing them, P (4) 106*f*.
Hugle, W. B. See Hugle, F. B.
Hukuda, S. See Sato, M.
Hulm, J. K. See Blaugher, R. D.; Pessall, N.
Hulse, C. O. See Graf, R. B.
Hulse, C. O., and Copley, S. M. High-temperature compressive deformation equipment, (6) 162*d*.
Hulse, C. O., and Graf, R. B. Effect of temperature on the mechanical properties of solid pressure-transmitting media (II) pyrophyllite, (6) 167*c*.
Hulse, C. O., and Paak, J. A. Analysis of deformation of a fireclay refractory, (7) 185*c*.
Hulse, C. O., and Tice, W. K. General fracture method for preparation of foils for transmission electron microscopy, (5) 136*d*.
Hume, I. N. Excavations at Clay Bank in Gloucester County, Virginia, 1962–1963, (10) 261*j*.
Hume, W. G., Mivelaz, W. F., and Connolly, J. D. Use of infrared spectrophotometry for the detection and identification of organic additions in cement and admixtures in hardened concrete, (11) 293*h*.
Humenik, M., Jr. See McHugh, C. O.
Hummel, F. A. See Argyle, J. F.; Brown, J. J.
Hummel, J. M. See Kleist, D.
Humphreys, G. D. Mechanical air classifier, P (5) 131*c*.
Hund, F. Heterotype mixed phases of fluorite or fluorite-like structures in predominantly oxide host lattices, (7) 200*a*. See Hoch, W.
Hung, Chang Lin. Double epitaxial layer functional block, P (5) 128*b*.
Hunsberger, J. F. See Lorenzo, M. P.
Hunt, C. J. See Halverstadt, R. D.
Hunt, J. W. See Bateson, S.
Hunt, P. H. Production of dislocation-free silicon single crystals, P (11) 307*i*.
Hunter, R. E. Feldspar in Illinois sands—a further study, (7) 196*h*.
Hunter, R. H. See Smith, H. W.
Hunter, R. S. Methods for the measurement of color and appearance, (7) 178*h*.
Hunter, W. H., and Garbe, S. Article handling machine, P (9) 242*b*.
Huntt, R. L. See Blankenship, A. C.
Huo, Gun-tsuan. See Cheng, Jie-jian.
Hupp Corp. Gas fired infrared heaters, P (4) 108*e*. Radiant gas burner, P (2) 46*f*, P (7) 190*c*.
Hurley, J. W. See Birks, L. S.
Huron Portland Cement Co. Method and apparatus for blending pulverulent material, P (5) 119*a*. Sampler, P (2) 45*j*.
Hurrell, J. P. See Baker, J. M.
Hursh, R. W. See Ketterer, R. J.
Hurst, E. Abrasive articles and methods of making, P (7) 177*i*.
Hurvitz, H. Electroluminescent frequency sensitive visual indicator, P (5) 128*c*.
Huschka, H. See Fleischhauer, G.
Hutchins, J. R., III. Dissolution kinetics in viscous systems where diffusion and free convection are rate controlling, (6) 147*f*. See Cowan, J. H.; Schlotzhauer, L. R.
Hutchins, M. C. Asbestos paper containing carbon and method of making it, P (11) 301*i*.
Huzimura, R. See Ato, Y.
Hwang, Chi-hsing, and Kung, Chia-shen. Effect of water/cement ratio on the structure and strength of hardened cement paste, (8) 206*h*.
Hwang, Hsi-hwai. See Huang, Hsi-huai.
Hwang, Shih-liang. Rotary kiln liner of refractory concrete prepared from low calcium aluminate cement, (2) 36*j*.
Hyatt, E. P., and Laird, H. R. Dielectric titanate body improvement, (6) 157*e*.
Hyde, C., and Sheets, H. D., Jr. Combustion chamber liner for well gas and air burner, P (3) 70*f*.
Hyde, G. R., Domingues, L. P., and Furlong, L. R. Improved dilatometer, (11) 310*g*.
Hyde, J. R. See Carr, B.
Hyde, K. R. See Fletcher, J. M.
Hyde, K. R., Landsman, D. A., Morris, J. B., Seddon, W. E., and Tulloch, H. J. C. Preparation of uranium nitride and carbonitrides from uranium oxide in a fluidized bed, B (11) 320*d*.

Hydrocarbon Research, Inc. Reduction of ilmenite and similar ores, P (3) 79*c*.
Hymowitz, J. B. Bubblers, P (2) 33*d*.
Hyodo, S., and Okuda, F. Glass cracking caused by underwater spark, (6) 147*h*.
Hyun, Kun Sup, and Chazal, L. E. M. de. Statistical definition of perfect mixtures of solids of different sizes, (5) 141*c*.

Iannicelli, J. Kaolin clay beneficiation, P (3) 78*j*.
Ibuki, S., Komiya, H., and Yamashita, H. Anomalous photovoltaic effect of CdS single crystals, (10) 276*j*.
Ichiba, S. Study of the solid reaction between zinc oxide and ferric oxide by the use of fission product rare gas, (4) 113*j*.
Ichikawa, Y. Positive temperature coefficient bead thermistor, P (1) 15*c*.
Ichinose, N., and Kurihara, K. Electrical properties of Y_2O_3 doped calcium diferrite, (11) 304*j*.
Iga, T. See Okuda, H.; Sano, S.
Igarashi, T. See Szabo, A.
Ignatova, V. A. See Artamonova, N. V.; Borisov, B. I.
Ihara, M., and Arimori, T. Electromotive force of silicate melt concentration cells with semipermeable bridges, (5) 135*h*.
Ihde, F. J., Jr. See Lally, R. E.
Iida, S. Mechanism of disaccommodation in ferrites, (10) 277*e*. See Inoue, T.; Kodera, H.; Shiratori, K.; Tasaki, A.
Iida, Y. See Hayashi, N.; Nitta, T.
Iizima, S., and Kikuchi, M. Electroluminescence in gallium phosphide single crystals, (10) 285*h*.
Ikeda, Jun-ichi. See Watanabe, H.
Ikeda, T. See Uchida, N.
Ikeda, T., and Okano, T. Piezoelectric ceramics of lead zirconate-titanate modified by bismuth ferrite, (10) 277*g*.
Ikeda, T., Okano, T., and Watanabe, M. Ternary system PbO–TiO–ZrO, (4) 113*g*.
Ikegami, S. Mechanism of microwave dielectric dispersion in polycrystalline $BaTiO_3$, (4) 104*a*.
Ikegami, S., Ueda, I., and Ise, Y. Optical absorption and electrical conductivity of reduced $BaTiO_3$ single crystal, (10) 289*b*.
Ikenoue, S. Recent improvement of basic refractories, (1) 9*g*. Refractories for LD converter, (8) 216*f*.
Ikornikova, N. Yu., Shorygin, V. A., and Vasil'chikova, I. A. Growth of calcite monocrystals under hydrothermal conditions, B (11) 319*j*.
Ikushima, A., and Suzuki, T. Internal friction of LiF at low temperatures, (10) 287*d*.
Ikuta, S. See Hayakawa, K.
Ikuta, Y. See Okagaki, H.; Sugawara, M.
Iler, R. K. See Alexander, G. B.
Il'ina, N. I. See Bol'shakov, K. A.
Ilkova, P. See Christova, R.
Illarionov, V. V. See Smirnova, Z. G.
Illigen, A. See Torkar, K.
Illing, A. M. Floor and wall tile research, (2) 39*b*.
Illing, A. M., and Balinkin, I. Precision in measurement of small color differences, (1) 12*j*.
Illyn, A. V., Palmer, G. G., and Popoff, V. L. Lead barium niobate ceramic composition, P (3) 73*g*.
Il'yasov, I. I. Fusibility diagram of the ternary system Na,Cs,Pb||Cl, (10) 286*b*. Ternary system of the chlorides of sodium, cesium, and cadmium, (1) 25*i*.
Il'yasov, I. I., and Bergman, A. G. Fusibility diagram of the reciprocal system of the chlorides and bromides of potassium and cadmium, (5) 136*c*.
Ilyushchenko, N. G. See Anfinogenov, A. I.
Im, H. B., and Wickham, D. G. Nickel-manganese-ferrous ferrite, P (5) 129*c*.
Im, S. S. Method of simultaneously fabricating a plurality of semiconductor *pn* junction devices, P (11) 307*d*. Tunnel diode devices with junctions formed on predetermined faces, P (9) 244*d*.
Imai, H. See Tsuzuki, K.; Watanabe, H.
Imai, M. See Brookes, C. A.
Imam, H. See Hasan, S. T.
Imamura, H. Continuous control of water content of cement raw slurry, (9) 230*h*.
Imamura, H., Uchida, K., and Tominaga, H. X-ray emission analysis of cement raw mix by radioisotopes, (9) 231*b*.
Immediata, T. M. See Ebling, W. F., Jr.
Imoto, S. See Stoecker, H. J.
Imoto, S., Sano, T., Takada, Y., Yamamoto, K., Watanabe, K., Isoda, T., and Uchikoshi, H. Studies of uranium dicarbide and sesquicarbide, B (6) 171*g*.
Imperial Chemical Industries, Ltd. Manufacture of finely divided silica, P (5) 133*d*.
Imris, P. See Landspersky, H.
Inczedy, J., Nemeshegyi, G., and Erdey, L. Separation and determination of rare earth metals by ion exchange chromatography (I) photometric determination of rare earth ions, (8) 223*h*; (II) chromatographic separation of rare earths combined with chemical detection, (8) 223*j*.
Independence Foundation and Koppers Co., Inc. Process for recovery of titania values, P (2) 48*a*.
Indiana General Corp. Apparatus for pressing slurries, P (5) 130*h*.
Inductotherm Linemelt Corp. Bushing insulator for core type induction furnace, P (3) 70*c*.
Ingamells, C. O. See Luth, W. C.
Ingham, A. J. Heat-insulating compositions and their use, P (10) 273*j*.
Inkley, F. A., and Coleman, J. W. Use of porous materials for obtaining ultrahigh vacuum, (3) 76*h*.
Inoue, A. Results of using zircon ladle brick (I) when used for slag line only and when used in lower side wall of ladle, (7) 187*f*; (II) condition of used electric furnace brick, (7) 187*f*. See Kochi, T.; Nameishi, N.
Inoue, K. Apparatus for electrically sintering discrete [conductive] bodies, P (7) 195*j*. Method of synthesizing diamond particles by utilizing electric discharge, P (1) 1*h*. See Honda, H.
Inoue, S. Studies of cell division with an improved polarizing microscope, B (9) 259*g*.
Inoue, Toru, and Iida, S. Method of manufacturing ferromagnetic oxides, P (11) 306*i*.
Inoue, Toru, Mizuta, H., and Iida, S. Effect of cation vacancies on the magnetic annealing of $Co_xFe_{3-x}O_4$, (10) 285*f*.
Inoue, Toshiro. Adjustment of basicity of slag in ladles for extending the life of lining brick, (9) 237*i*. Influence of various factors on the unit refractory consumption for open-hearth furnaces, (8) 215*d*. Lengthening the life of an open-hearth furnace by using gunned refractories, P (7) 186*i*. Use of zircon brick for ladle lining (II) condition of used brick, (7) 188*d*.
Inoue, Toshiro, and Futamura, M. Use of zircon brick for ladle lining (I), (7) 188*d*.
Inoue, Toshiro, and Morita, H. Causes and prevention of stopper head failure, (3) 65*g*.
Inoue, Toshiro, Shimogo, Y., and Matsufuji, H. Results of using basic brick for open-hearth floor, (3) 69*a*.
Inozemtsev, Yu. P. See Shal'nev, K. K.
Insley, R. H. See Schurecht, H. G.
Insolio, T. A. Apparatus for drawing glass sheet with control device, P (3) 62*f*.
Institut Metallurgii im. A. A. Baikov. Installation for production of glass insulated microwire directly from liquid metal, P (9) 232*f*.
Institute of Gas Technology. Method of making fuel cell elements, P (2) 38*d*.
Insulwool Products Proprietary, Ltd. Spinner for producing mineral fibers, P (5) 124*c*.
International Business Machines Corp. Apparatus for coating articles by cathode sputtering [in vacuum], P (7) 192*h*. Capacitors and process for making, P (11) 305*a*. Coated objects and methods of providing the protective coverings therefor, P (7) 192*c*. Decoupling capacitor, P (10) 278*b*. Electrical resistance compositions, elements, and methods of making, P (7) 192*h*. Electroluminescent phosphor containing moisture absorbents, P (4) 104*e*. Electrooptic light coupling of optical fibers, P (1) 6*i*. Ferrite process, P (11) 306*d*. High iron magnesium manganese ferrite, P (3) 73*e*. Lasers utilizing internal reflection techniques, P (7) 193*f*. Magnetic [ferrite] memory element, P (10) 278*b*. Method and apparatus for [vapor] depositing films of refractory metal oxides and refractory metals, P (1) 14*h*. Method of fabricating high gain cryotrons, P (6) 159*g*. Method of fabrication of crystalline shapes, P (7) 193*a*. Method of forming contacts on semiconductors, P (10) 278*i*. Method of forming a glass film on an object and the product produced, P (1) 3*e*. Method of forming an integral masking fixture by epitaxial growth, P (5) 129*b*. Method of producing ferrite core assembly for magnetic storage devices, P (5) 129*h*. Method for producing semiconductor articles, P (6) 160*c*. Method for producing square loop nickel ferrous ferrite, P (5) 129*j*. Method of simultaneously fabricating a plurality of semiconductor *pn* junction devices, P (11) 307*d*. Method of tailoring thin film impedance devices, P (9) 243*f*. *Pnpn* semiconductor translating device and method of construction, P (2) 42*b*. Quantum mechanical tunneling semiconductor device, P (4) 106*d*. Semiconductor heterojunction device, P (5) 130*b*. Semiconductor laser with optical cavity, P (7) 194*a*. Silicon oxide film formation, P (6) 161*a*. Surface protection for tunneling semiconductor devices, P (10) 279*f*. Switching transistors with controlled emitter-base breakdown, P (5) 130*b*. Tunnel diode devices with junctions formed on predetermined faces, P (9) 244*d*. Uranium and lanthanide activated alkaline earth molybdate and tungstate phosphors, P (10) 279*i*.
International Commission on Glass, Sub-Committee AII (editors). Chemical Durability of Glass—A Bibliographic Review of Literature, B (3) 88*h*.
International Minerals & Chemical Corp. Measuring apparatus for particulate material streams, P (1) 16*b*. Silica pigments from fluosilicic acid, P (11) 312*j*.
International Nickel Co., Inc. Method for fluid mold casting using casting slag, P (2) 38*c*. Slag composition for fluid mold casting, P (3) 71*a*.
International Pipe & Ceramics Corp. Tile construction, P (5) 127*i*.
International Rectifier Corp. Adjustable [monocrystalline] semiconductor punch-through device having three junctions, P (10) 277*g*. Field effect transistor, P (11) 306*e*. Method of forming a semiconductor rim by sandblasting, P (1) 278*j*. Method of making a transistor containing a multiplicity of depressions, P (4) 105*a*. Temperature compensated silicon controlled rectifier, P (11) 308*b*.
International Resistance Co. Method of cutting glass, P (7) 184*a*. Method of making electrical resistors, P (5) 129*b*.
International Standard Electric Corp. Continuously graded electrode of two metals for semiconductor devices, P (11) 305*e*. Method of producing electrical semiconductor devices, P (11) 307*a*. Method of producing photosensitive layers of lead selenide, P (4) 105*e*. Semiconductor device and method of producing it, P (6) 160*f*.
International Telephone & Telegraph Corp. Method of making masks for vapor deposition of electrodes, P (11) 306*h*. Planar semiconductor device, P (11) 307*f*.
Intrater, J. Method of connecting contacts to thermoelectric elements, P (6) 150*f*.
Ionics, Inc. Colloidal silicon carbide and method of making, P (5) 125*h*.
Iowa State University Research Foundation, Inc. Atomizer burner, P (10) 281*g*.
Irvin, J. C. Gallium arsenide semiconductor diode and method, P (11) 306*g*.
Irving, B. A. Grain boundaries in growing oxide films (1), (2) 50*d*.
Irwin, G. W. Glassware forming machine timing valve assembly, P (1) 6*e*.
Irwin, G. W., and Mumford, E. H. Air operated neck molds, P (7) 182*f*.
Isaac, J. Machine for severing blanks of refractory products, P (8) 217*d*.
Isaacs, J. W. See Harrison, J. D. L.
Isaacs, J. W., Maskell, C. W., and Harrison, J. D. L. Hollow-cathode electron beams and their application to the melting of refractory materials, P (11) 320*h*.
Isaacs, J. W., and Palreyman, M. Process for the preparation of UC-PuC fuel elements, P (5) 126*h*.
Isaacs, R. P. Albany slip clay—50 years later, (9) 247*b*.
Isacks, A. J., Jr., and Lugg, R. R. Process for preparation of sintered metallic oxide catalyst pellets, P (10) 274*e*.
Isaeva, E. A., Makasheva, I. E., and Obukhov, A. P. Neutron activation analysis of pure silicon carbide, (6) 153*f*.
Isago, M. See Machida, J.
Isakova, M. See Levcheva, K.
Isakova, R. A., Nesterov, V. N., and Shendyapin, A. S. Vapor pressure of the sulfides of lead and indium, (2) 53*f*.
Isard, J. O. See Savage, J. A.; Searstone, K.
Ise, Y. See Ikegami, S.
Iseki, T. See Tagai, H.
Isherwood, B. J. See Greenham, A. C.
Isherwood, T. H. Method of producing ceramic articles and the articles produced, P (2) 38*h*.
Ishibashi, T. See Nameishi, N.
Ishida, R. Decomposition of Al_2O_3–SiO_2 system compounds for the determination of alkali elements, (11) 309*j*.
Ishiguro, K. See Sasaki, T.
Ishii, D. See Takeuchi, T.
Ishii, E. See Okuda, H.; Sano, S.; Sugiura, M.
Ishikawa, K. See Ota, Z.
Ishikawa, Y. Magnetic properties of ilmenite–hematite system at low temperature, (4) 112*g*.
Ishiki, H. See Watanabe, H.
Ishizawa, K. See Hayashi, T.
Ishizuka, M. See Nakayama, J.
Ish-Shalom, M. See Frommer, M. A.
Isings, C. Fourth-century glass jar with applied masks, (4) 89*i*.
Iskander, Z. Pottery found in the tomb of Neferwptah and its significance, B (6) 172*f*.
Iskhakov, Kh. Sh., and Keler, E. K. Conditions of formation and electrical properties of solid solutions of $SrTiO_3$ with $SrZrO_3$, (5) 134*c*. Solid phase reactions in the system SrO–TiO_2–ZrO_2, (5) 140*j*.
Isoda, T. See Imoto, S.
Israel, State of, Government of Israel. Process for the formation of metalliferous coatings on inorganic bodies, P (8) 219*e*.
Israeli, Y. Sidonian mold-blown glass vessels in the Museum Haaretz, (4) 90*d*.
Isreeli, J. See Skeggs, L. T.
Isupov, V. A. See Smolenskii, G. A.
Itakura, M., and Toyoda, H. Electrical conductivity and Hall coefficient of CdS single crystal, (4) 103*j*.
I-T-E Circuit Breaker Co. Alumina porcelain insulators for electrical apparatus, P (4) 103*a*.
Ito, M. See Lin, T. H.
Ito, T. See Ao, T.; Asano, T.; Enomoto, S.; Tasaki, J.
Itoh, K. See Gondo, Y.
Ivanov, F. S. See Shushkin, V. F.
Ivanov, I. Problems in the production of chamotte refractories, (5) 125*g*.
Ivanov, V. E. See Verkhorobin, L. F.
Ivanov, V. E., Nechiporenko, E. P., Krivoruchko, V. M., and Mitrofanov, A. S. Features of vacuum siliciding of some refractory metals, (10) 271*b*.
Ivanov, V. E., Nechiporenko, E. P., Osipov, A. D., and Zmii, V. I. Effect of stress on the imperfection of silicide layers on molybdenum, (11) 295*d*.
Ivanov, Yu. A., and Fedorovskii, Ya. A. Electron microscope study of glass films obtained by evaporation, (10) 264*h*.
Ivanova, A. B. See Zhmud', E. S.
Ivanova, N. S. See Minenko, V. I.
Ivanova, V. M. See Syritskaya, Z. M.

Ivanova, V. V., Kapyshev, A. G., Venevtsev, Yu. N., and Zhdanov, G. S. Determination of the symmetry of unit cells of $(K_{0.8}Bi_{0.8})TiO_3$ and $(Na_{0.8}Bi_{0.8})TiO_3$ ferroelectrics and of high-temperature phase transformations in $(K_{0.8}Bi_{0.8})TiO_3$ by X rays, (5) 135*c*.
Ivensen, V. A., and Eiduk, O. N. Structure of two-phase cemented carbides, (9) 256*g*.
Ivensen, V. A., Eiduk, O. N., and Pivovarov, L. Kh. Deformation regularities of sintered WC-Co hard alloys, (8) 215*b*.
Ivensen, V. A., and Koval'skii, A. E. Dependence of the electrical resistivity of tungsten carbide-cobalt alloy on its structure, (10) 284*c*.
Iwai, S. See Arizumi, T.; Tagai, H.
Iwai, T. See Schwiete, H. E.
Iwaida, T. See Ohta, C.
Iwaki, T. See Hirai, T.
Iwamoto, K. See Ouchi, H.
Iwamoto, S., and Sudo, T. Chemical reactions among clay minerals, calcium carbonate, and ammonium chloride, (9) 248*c*.
Iwata, M., Iwata, T., and Yamamoto, M. Experiments on the memory effect in α-Fe_2O_3, (10) 286*e*.
Iwata, T. See Iwata, M.
Iwata, T., Fujita, F. E., and Suzuki, H. Energy of the interstitial atom in graphite, (4) 111*e*.
Iyengar, K. T. S. R., Chandrashekhara, K., and Krishnaswamy, K. T. Strength of concrete under biaxial compression, (2) 29*i*.
Izet, H. German potters in Istanbul, (3) 57*j*.
Izui, K. See Fujita, F. E.
Izumi, G., and Kita, M. Molding abilities [workability] of octadecylamine salts in silica powder, (10) 288*j*.
Izushi, T. See Tasaki, J.
Izvekov, V. I., Gorbunov, N. S., and Babad-Zakhryapin, A. A. Iron diffusion in hematite, (11) 318*i*.

Jaccodine, R. J., and Schlegel, W. A. Measurement of strains at Si-SiO_2 interface, (9) 252*b*.
Jack, K. H., and Winterburn, J. A. Method of fine annealing transparent vitreous silica, P (4) 97*a*. Method of tempering by heat treating vitreous silica, P (4) 97*i*.
Jackson, B., and Ford, W. F. Quantitative study of bonding in basic refractories, (7) 187*i*.
Jackson, C. B. See Burke, O. W., Jr.
Jackson, D. D., Barton, G. W., Jr., Krikorian, O. H., and Newbury, R. S. Vaporization of gadolinium and thorium dicarbides, B (6) 175*d*.
Jackson, N. H. Refractories for the nonferrous metals industries, (5) 125*a*.
Jackson, P. F. S., and Whitehead, J. Analysis of titanium dioxide pigments by spark-source mass spectrography, (10) 280*g*.
Jackson, T. A. Power-spectrum analysis of two "varved" argillites in the Huronian Cobalt Series (Precambrian) of Canada, (5) 140*a*.
Jackson, W. Status of wollastonite glazes for sanitary ware, (2) 40*a*.
Jacobs, C. D. Apparatus for producing dust, P (3) 78*e*.
Jacobs, C. W. F. Glazes for brick and structural clay products, (2) 35*g*.
Jacobs, H. See Fripiat, J. J.
Jacobsen, E. H. Microwave ultrasonics, (5) 128*c*.
Jacquin, C. See Basty, W. du.
Jaffe, H. See Cook, W. R., Jr.
Jaffe, H., and Gerson, R. Method of preparing lead titanate ferroelectric ceramics, P (2) 42*e*.
Jager, H. Apparatus for preheating raw cement material, P (1) 3*c*.
Jagodzinski, H. Cooperative phenomena and glass formation with special reference to SiO_2, (5) 120*f*.
Jagodzinski, R. F. See Francel, J.
Jahn, W. Multicomponent systems for the production of optical glass (III) new optical glasses based on fluorine, (2) 32*e*. Optical crown glass, P (2) 34*c*. Radiation resistant optical glasses, (9) 234*c*.
Jain, S. K. See Ghosh, S. N.
Jakubekova, D. See Bruthans, Z.
Jamakov (Yamakov), I. See Stefanov, G.
Jambor, J. Long term study of the system CaO–silica gel–H_2O at 20°C, (2) 28*e*.
James, B. W., and Yates, B. Thermal expansion of sodium fluoride at low temperatures—Grueneisen parameters of sodium fluoride and rubidium bromide, (3) 87*a*.
James, D. R. See Wurst, J. C.
James, R. E. Broseley clay pipe, (9) 229*j*.
James, W. G. See Edwards, G. J.
Jameson, H. L. Sampling mechanism, P (6) 163*d*.
Jamnik, F. Device for the fabrication of U-shaped profiles of glass in a continuous rolling procedure, P (4) 96*c*.
Jamnik, F., and Pelzl, A. Equipment for exact shaping especially by bending of continuously produced glass bands under simultaneous all over rolling friction, P (7) 182*g*. Process for distortionless shaping of glass bands to glass profiles, P (7) 184*f*. Process and equipment for the production of continuous building elements of glass, P (5) 124*a*.
Janes, S., and Nixdorf, J. Production of sintered bodies of boron carbide and nitride, (9) 238*i*.
Janetos, N. S. See Marzocchi, A.
Janota, R. B., and Keefe, D. G. Adhesive patching composition, P (8) 207*d*.
Janowski, K. R., Chase, A. B., and Stofel, E. J. Growth defects in flux-grown rubies, (10) 286*c*.
Jansen, K. Method of continuously forming carbon articles, P (10) 274*e*.
Jantsch, O. Long-term relaxation of the surface conductivity of silicon, (10) 287*h*.
Jarasse, L., and Joirst, J. Electrode structure, P (8) 220*i*.
Jarchow, O. Atomic arrangement and structure refinement of $(Ca,Na)CO_3$ cancrinites, (7) 197*i*.
Jaron, M. G. See O'Neill, B. J., Jr.
Jarosi, J. J. See Brown, W. F.
Jarvis, G. D. Installation of ceramic terminals in metal vacuum systems by electron beam welding, (10) 277*b*.
Jarzebski, Z. M. Hall coefficient and conductivity measurements of cadmium oxide in terms of sintering temperature, (6) 167*i*.
Jasinski, J., and Monks, J. R. Glass making batch and method, P (5) 122*h*.
Jasper, H. P., and Kreuz, R. J. Method and apparatus for subdividing particulate [catalyst] solids, P (2) 47*h*.
Jasutis, V. See Tolutis, V.
Javaux, G. Glass processing apparatus including a reciprocating roller, P (11) 298*h*. Process and apparatus for production of continuous fire-polished glass sheet, P (5) 123*j*, P (9) 236*j*.
Jeanneret, J. L. Mold dressings for use in foundry practice, P (11) 302*j*.
Jebsen-Marwedel, H. Network of problems between glass and refractories, (1) 4*g*.
Jeffery, P. G., and Kipping, P. J. Determination of constituents of rocks and minerals by gas chromatography (II) determination of some gaseous constituents, (2) 44*b*.
Jeffrey, G. A. See Dutta, S. N.
Jeffreys, D. C. Electroluminescent phosphor containing moisture absorbents, P (4) 104*e*.
Jelli, A. See Calvet, R.
Jenaer Glaswerk Schott & Gen. Apparatus with ground glass surface for film-type distillation, P (7) 182*f*. Method of measuring the outside diameter of glass tubing, especially during manufacture, P (10) 269*h*. Optical crown glass, P (2) 34*c*. Optical glass, P (7) 184*c*.
Jenckel, E. See Karsch, K. H.
Jendrisak, J. E. Apparatus for bending glass sheets or plates, P (3) 62*e*. Glass [gravity] bending apparatus for forming curved glass panes having conical surface portions, P (5) 122*g*. Hold down device for glass bending mold, P (3) 63*b*.
Jenemann, H., and Zimmermann, G. Determination of low sulfur contents in glasses and glass raw materials by electrodialysis and spectrophotometric determination as chloranilic acid, (3) 60*h*.
Jenkins, J. D., and Reynolds, C. B. Apparatus for applying metal cases to bricks, P (11) 301*h*.
Jenkins, L. R. D. Device comprising a III-V compound semiconductor body and at least one contact, P (9) 243*b*.
Jenkins, R. H. See Gasson, E. J.
Jenkins, W. H. Press forming apparatus for forming wafers from drips of glass, P (11) 299*d*.
Jensen, A. J. Pyrolytic deposition of protective coatings of semiconductor surfaces, P (6) 160*d*.
Jensen, J. R. See Cochran, M. C.
Jenssen, L. W. See Melichar, J. T.
Jerger, J., Jr. Optical infrared-transmitting glass compositions, P (6) 150*d*.
Jeschke, J. C. Precipitation process for preparing acicular magnetic metal oxide particles, P (6) 160*a*.
Jeschke, P. Texture analysis of basic refractory brick, (8) 216*d*.
Jewell, R. A. See Wakelyn, N. T.
Jobson, D. A. See Thorn, J. D.
Jochim, F. Self-gripping tongs, P (11) 299*g*.
Jochmann, F. Arsenic in glass, (10) 264*j*. Fluorine opaque and clear glasses as coatings for lampshades and new more suitable batches, (10) 264*i*. Ruby-red glass rod with metallic precipitates and goldlike surface crystals, (2) 32*h*.
Joeckel, S. V. Infrared heating unit, P (5) 132*f*.
Joenk, R. J. See McGuire, T. R.
Johannsen, K. Molten ceramic oxides as possible fuel matrixes for homogeneous thermal nuclear reactors, (6) 153*e*.
Johansen, H. A. See Pessall, N.
Johansen, I. T. Electrical conductivity in evaporated silicon oxide films, (7) 199*a*.
Johanson, L. N. See Bengtson, K. B.
John Zink Co. Burner assembly producing radiant heat, P (10) 282*f*.
Johns-Manville Corp. Acoustical glass fiber panel with diaphragm action and controlled flow resistance, P (6) 149*j*. Apparatus for forming fiber, P (5) 122*f*. Apparatus for making foamed ceramic products, P (5) 130*f*. Apparatus for the manufacture of asbestos-cement tubes, P (7) 188*h*. Apparatus for producing fibers, P (7) 182*a*. Apparatus for producing glass filaments having a distributor cup within centrifugal rotor, P (5) 122*i*. Apparatus for producing a propulsion stream adapted to attenuate fibers, P (7) 182*b*. Apparatus for producing strand packages of uniform length, P (8) 211*i*. Asbestos-cement structural sheet, P (3) 70*b*. Asbestos-glass fiber saturating paper containing thermoplastic resin and aluminum acid phosphate, P (1) 10*h*. Asbestos paper containing carbon and method of making it, P (11) 301*i*. Gas mixing device, P (6) 163*j*. Glass fiber filter tubes, P (10) 268*b*. High flow rate perlite filter aids, P (5) 124*f*. Manufacture of asbestos-cement products, P (2) 37*b*. Method of applying silicate to wet asbestos-slag cement sheets after formation but prior to consolidation, F (11) 302*g*. Methods for making asbestos fiber products, P (11) 302*j*. Method of preparing perlite products, P (5) 124*i*. Mineral wool board, P (8) 217*j*. Rotor for [centrifugally] forming glass filaments, P (7) 184*g*.
Johnson, A. D. Read-out device having bonding material between a face panel and a cover panel, P (11) 307*a*.
Johnson, C. A., and Volk, W. Reduction of ilmenite and similar ores, P (3) 79*c*.
Johnson, C. J. Some dielectric and electrooptic properties of $BaTiO_3$ single crystals, (10) 290*b*.
Johnson, D. E., and Lofftus, F. H. Method of making nuclear fuel compact, P (1) 11*j*.
Johnson, E. S. Gypsum composition and building construction, P (11) 295*a*.
Johnson, G. H. (compiler and editor). Ceramic Metal Systems and Enamel Bibliography and Abstracts—1965, B (7) 204*a*.
Johnson, H. B., Johnson, O. W., and Cutler, I. B. Effect of water vapor on dielectric loss in MgO, (8) 226*b*.
Johnson, H. B., Tolar, N. J., Miller, G. R., and Cutler, I. B. Dipole relaxation in CaF_2 doped with NaF, (9) 249*i*.
Johnson, H. T. (editor). Electronic Properties of Materials—A Guide to the Literature, B (1) 26*c*.
Johnson, J. R. Gauging apparatus, P (10) 267*j*. See Heyne, C. A.; Sowman, H. G.
Johnson, J. R., and Smith, R. M. Dip-coating machine, P (11) 298*b*.
Johnson, J. S. See Kraus, K. A.
Johnson, L. F. Optical maser comprising the active medium CaF_2:Nd, P (9) 243*h*. See Guggenheim, H. J.; Ross, R. E.
Johnson, L. F., Geusic, J. E., and Van Uitert, L. G. Coherent oscillations from Tm^{3+}, Ho^{3+}, Yb^{3+}, and Er^{3+} ions in yttrium aluminum garnet, (10) 284*b*.
Johnson, L. F., and Nassau, K. Optical maser comprising the active medium $CaWO_4$:Ho, P (7) 194*a*; $CaWO_4$:Tm^{3+}, P (7) 193*j*. Optical maser using trivalent neodymium ions in a calcium tungstate host lattice, P (3) 74*b*.
Johnson, L. F., and Soden, R. R. Optical masers comprising the active media $SrMoO_4$:Nd, $CaMoO_4$–Nd, and $PbMoO_4$:Nd, P (9) 243*i*.
Johnson, L. R. See Levinson, S.
Johnson, L. W. Rock crusher with braked head, P (1) 19*c*.
Johnson, M. M. Plasma arc sprayed catalysts, P (10) 274*j*.
Johnson, O. W. See Johnson, H. B.
Johnson, P. W. See Peters, F. A.
Johnson, R. C., and Alley, J. K. Growth and properties of zirconia and titania whiskers from fused salt baths, (1) 22*b*.
Johnson, R. C., Alley, J. K., Warwick, W. H., and Shell, H. R. Synthesis of fibrous silicon nitride, P (6) 155*g*.
Johnson, R. E., and Wurst, E. C., Jr. Gallium arsenide body containing copper, P (9) 243*f*.
Johnson, R. H. See Wilbanks, W. H.
Johnson, R. W. Use of induction heating for floating zone melting above 2000°C, (2) 53*e*.
Johnson, R. W., and Daane, A. H. Electron requirements of bonds in metal borides, (4) 111*d*.
Johnson, T. See Tarlton, J. W.
Johnson, W. E. Formability of extra-low-carbon steels, (4) 91*g*. Sliding frictional characteristics of deep drawing lubricants, (4) 91*d*.
Johnson, W. E., and Mathias, B. B. Inspecting containers with lug finishes, P (7) 183*j*.
Johnston, A. R. Strain-free electrooptic effect in single-crystal barium titanate, (10) 290*f*.
Johnston, G. B. See Curry, N. A.
Johnston, J. See Toth, L. E.
Johnston, W. D. Formulation of oxidation-reduction reactions in glass melts, (10) 264*j*. Optical spectra of the various valence states of vanadium in Na_2O·$2SiO_2$ glass, (1) 4*j*.
Johnston, W. D., and Chelko, A. Oxidation-reduction equilibria in molten Na_2O·$2SiO_2$ glass in contact with metallic copper and silver, (11) 297*d*.
Joiret, J. See Jarasse, L.
Joksch, C. Ceramic junction capacitors (DRALOWID MULTICAP), (8) 219*h*.
Jonas, A. J. Use of wet clays, (7) 185*d*.
Jones, C. E. See Hilton, A. R.
Jones, C. K. See Pessall, N.
Jones, F. L. Coating for refractory metal, P (11) 295*f*. High-temperature resistant self-healing coating and method of application, P (11) 296*c*.
Jones, H. S., Jr. See Reggia, R.
Jones, I. G. See Milner, G. W. C.
Jones, J. B. See Wilson, C. P., Jr.
Jones, J. T., and Cutler, I. B. Stoichiometry of MgO-Mn_2O solid solutions in air at high temperatures, (11) 319*b*.
Jones, J. W. S. See Henney, J.
Jones, M. D., and Mee, C. H. B. Photoluminescence of barium oxide, (3) 84*c*.
Jones, M. J. See Bange, G. R.
Jones, M. P., and Fleming, M. G. Identification of Mineral Grains—A Systematic Approach to the Determination of Minerals for Mineral Processing Engineers and Students, B (7) 204*f*.
Jones, R. A. Modified zeolitic molecular sieves and process for producing, P (3) 79*c*.
Jones, R. G., and Winscott, P. E. Apparatus for printing on bottles or the like, P (5) 122*g*.
Jones, R. L. See Osment, H. E.

Jones, W. Classification method and apparatus, P (3) 77*b*, P (11) 311*c*.
Jones, W. C. Ceramic fiber reinforced rocket nozzles, (2) 30*b*.
Jones, W. H. Thin film electron emissive electrode, P (10) 279*g*.
Jones, W. T. See Goode, G. C.
Jonge, J. de, Linden, P. C. van der, and Ruiter, J. W. de. Device for treating semiconductor materials by melting, P (9) 243*b*.
Jonsson, O. See Wilhelmi, K. A.
Jorba, M. P. y. See Perez y Jorba, M.
Jordan, C. C. See Cropp, D. I.
Jorgensen, A. Apparatus for making multiple glazed units, P (11) 297*e*.
Jorgensen, P. J. See Hagel, W. C.
Jos. Schlitz Brewing Co. Drinking glass, P (2) 33*g*.
Joseph, A. D., and Petrusha, J. A. Method of improving lithiated nickel oxide fuel cell electrodes, P (4) 105*h*.
Joseph, T. L. See Gorton, A. T.
Joseph Crosfield & Sons, Ltd. Method of making calcium silicate materials, P (5) 126*g*.
Joseph Dixon Crucible Co. Stopper rod assembly, P (10) 275*d*.
Joshi, A. W., and Sinha, K. P. Low temperature thermal conductivity of ferrimagnetic insulators, (9) 242*j*.
Joshi, M. S., and Vagh, A. S. Hillocks on prism faces of cultured quartz, (9) 250*b*. Role of spirals in the growth of prism faces of cultured quartz, (5) 140*b*.
Joshi, R. V., and Menon, A. K. Thermal glow peaks in KCl:Tl around room temperature, (3) 87*c*.
Josien, F. A., and Renaud, R. Solid state reactions in the system Fe–W–C—preparation of a $(Fe,W)_3C_3$ type double carbide, (2) 51*e*.
Josling, C. A. See Goodman, R. H.
Jost, K. H. See Wodtcke, F.
Jouannaud, C. See Burko, J.
Joubert, J. C. See Bertaut, E. F.; Martin, C.
Joubert, J. C., and Durif, A. Crystallographic study of a lithium-chromium vanadate, (6) 166*i*. Preparation of some spinels with cation vacancies, (7) 202*i*.
Joubert, J. C., and Durif-Varambon, A. Replacement of iron in $CuFeO_2$ and $NaFeO_2$, (6) 169*g*.
Jouravsky, G. See Gaudefroy, C.
Jovanovic, A. See Blinc, R.
Jowanowicz, A. Opticopolarization method of measuring stresses in glass by the principle of Senarmont, (8) 210*h*.
Jowett, A. Gangue mineral contamination of froth, (7) 194*g*.
Juel, L. H., and Bailey, B. L. Apparatus for making carbon electrodes or neutronic reactor core bars, P (10) 273*ch*.
Jugovic, Z. T. Application of spectrophotometric and EDTA methods for rapid analysis of cement and raw materials, (11) 293*j*. See Kalousek, G. L.
Juhasz, A., and Konkoly, J. Filter presses for separating solids from liquids, P (11) 308*i*.
Juhasz, Z. Shrinkage of the inner structure of kaolin between 600° and 1200°C, (9) 255*b*.
Julio, J. P. Glass treatment tempering nozzle arrangements and method of tempering, P (4) 97*a*.
Julsrud, E. See Bruun, H. H.
Juri, G. Continuous kiln for structural clay products with movable hearth and its charging and discharging, P (8) 224*f*.
Jurid-Werke G.m.b.H. Process for making cermets and articles made therefrom, P (10) 264*a*.

Kabanov, N. P. See Borisov, B. I.
Kabi, S. K. See Tepper, F.
Kabushiki Kaisha Hitachi Seisakusho. Fabrication of exothermic self-hardening mold, P (2) 37*e*. Hollow-cathode discharge lamp for emission of atomic resonance lines, P (6) 159*j*. Hollow-cathode discharge tube for generating atomic resonance lines, P (5) 128*h*. Method of fabricating semiconductor devices by alloying a gold disk containing active impurities to a germanium pellet, P (6) 159*h*. Method of producing semiconductor devices, P (6) 160*d*. Silicon rectifying junction structures for electric power and process of production thereof, P (11) 308*c*. Temperature compensated zener diode, P (6) 161*c*. Treatment of phosphors, P (11) 308*c*.
Kachalov, S. S., and Kovsh, G. I. Heating of glass furnaces with natural gas, (10) 265*f*.
Kachhava, C. M. See Dass, L.
Kachhava, C. M., and Saxena, S. C. Simple method for calculating thermal expansion of ionic crystals, (2) 51*c*.
Kachur, B. K. See Serdyuk, S. M.
Kadota, Y. See Yoshida, H.
Kaes, H. H. See Brueckner, R.
Kaestner, F. See Schulze, H. J.
Kagan, C. A. R. See Blade, J. W.
Kagel, W. Ancient island pottery at Frauenwoerth on the Chiemsee, (1) 1*i*.
Kahlenberg, J. F. Ampul sealing apparatus, P (10) 267*f*.
Kahn, H. L. Quantitative analysis by atomic absorption, (1) 17*a*.
Kahn, J. S. See Newkirk, H. W.
Kahn, J. S., and Wadleigh, W. Electron transmission microscopy of polycrystalline beryllium oxide, (7) 199*g*.
Kainarskii, I. S., Degtyareva, E. V., and Orlova, I G. Interrelation between the electrical and mechanical strengths of corundum ceramics, (1) 23*a*.
Kainuma, Y. Diffraction pattern caused by temperature diffuse scattering (I) general theory, (4) 110*g*.
Kaiser, H. D. See Delaney, R. A.
Kaiser, R. See Meissner, H. P.
Kaiser, W. K. Diffusion technique for making composite optical maser crystals, P (2) 41*d*.
Kaiser Aluminum & Chemical Corp. Apparatus for applying metal cases to bricks, P (11) 301*h*. Bending device, P (10) 273*j*. Hot pressing of powdered refractory material, P (9) 240*e*. Method of continuously hot pressing powdered refractory material, P (10) 274*f*. Method of enameling anodized aluminum, P (3) 60*a*. Method of preparing alumina refractory, P (9) 240*d*. Method of producing active alumina, P (3) 79*a*, P (4) 109*b*. Method for producing active alumina nodules, P (3) 79*b*. Production of potassium permanganate activated alumina composite, P (4) 101*k*. Refractory, P (9) 241*e*, P (10) 274*i*. Refractory and process of making, P (6) 155*e*. Refractory structure for a rotary kiln, P (4) 108*f*. Suspendable refractory unit, P (5) 127*a*.
Kaiser Industries Corp. Method of continuously forming carbon articles, P (10) 274*e*.
Kajima, K. See Tasaki, J.
Kakodkar, C. Glass and ceramic industries in India, (2) 54*f*.
Kakol, M., Nowak, W., and Sobanski, R. New approach to values of the heat balance of the Hoffmann kiln, (8) 224*g*.
Kakos, M. J., and Fitzgerald, J. V. Ceramic tile, P (1) 13*d*.
Kalhammer, F. R. Ultrasensitive phototransistor device comprising wafer having high resistivity center region with opposite conductivity, diffused, low-resistivity, and translucent outer layers, P (3) 74*f*.
Kali-Chemie Akt.-Ges. High temperature-resistant catalyst carrier and method of preparation thereof, P (5) 125*j*. Preparation of nordstrandite, P (4) 109*c*. Process for the preparation of nordstrandite alumina, P (3) 79*c*.
Kali-Forschungs-Anstalt G.m.b.H. Electrostatic separation of minerals, P (2) 47*e*.
Kalinina, A. M. High-temperature transformations of synthetic kaolinite, (11) 317*j*.
Kalinina, V. E. See Zolotarev, E. K.
Kalinkina, I. F. See Nyankovskaya, R. N.
Kalinowski, B. See Adamski, T. W.
Kallander, D. A. Method of making semiconductor device, P (5) 129*f*.
Kalle Akt.-Ges. Spray drying process and apparatus therefor, P (11) 309*c*.
Kalman, A. Application of X-ray intensity statistics in the case of inorganic substances—method for determination of crystal symmetries and space groups, (11) 313*e*. See Peter, E.
Kalmykov, V. I. See Savonichev, G. V.
Kal'nitskii, N. R. See Belyaev, I. N.
Kalousek, G. L. Method of curing calcium silicate insulating materials, P (4) 101*a*.
Kalousek, G. L., Bishop, D. L., and Shannon, R. F. Method of manufacturing calcium silicate insulating materials, P (9) 240*a*.
Kalousek, G. L., Camarda, F. V., Kopanda, J. E., and Jugovic, Z. T. Analysis of asbestos-cement binders, (6) 144*d*.
Kalvenas, S., and Pozela, J. Effect of surface finish on the electrical conductivity of germanium and silicon in high electric fields, (3) 72*e*.
Kambara, Y. See Takita, S.
Kamenetskii, S. P. See Zhukov, A. V.
Kamenskii, D. S. See Kreymer, G. S.
Kameyama, A., Funabashi, T., Kusakawa, I., Watanabe, J., Hayao, T., Takashima, Y., and Maruyama, N. Annular fluorescent lamps, P (11) 297*c*.
Kamimura, K., Sereda, P. J., and Swenson, E. G. Changes in weight and dimensions in the drying and carbonation of portland cement mortars, (1) 2*d*.
Kaminow, I. P. Barium titanate light phase modulator, (4) 103*h*.
Kaminskaya, V. S. See Matveev, M. A.
Kamiura, M. French refractories, (6) 152*f*.
Kamiya, Y. Effect of inelastic scattering on mean and anomalous absorption coefficients of electrons in magnesium oxide crystals studied by electron microscope, (4) 110*c*. See Lawn, B. R.
Kamiyama, M. See Karube, N.
Kampert, H. M. Block stacking machine, P (9) 237*f*.
Kampf, L. Durability of masonry, (11) 299*j*.
Kamptz, H. v. See Petzold, A.
Kamyshanskii, I. P. See Cherpak, A. G.
Kan, Fu-hsi. See Hu, Ho-fang.
Kan, Fu-hsi, Chiang, Chung-hung, Tsai, Ying-shih, and Lee, Hsi-shan. Fluorescence and stimulation in Nd-doped glass, (6) 147*e*.
Kanamori, J. See Date, M.
Kanaoka, S. See Kato, E.
Kane, P. F. Semiconductor materials research, (5) 131*h*.
Kanics, A. Apparatus for handling bulk material, P (8) 222*f*.
Kano, H. See Miyatake, K.
Kantor, Ya. M. See Budnikov, P. P.
Kapany, N. S., and Capellaro, D. F. Photosensitive reader using optical fibers, P (8) 213*d*.
Kapel, I. B. See Souza Santos, P. de.
Kapel, I. B., and Souza Santos, P. de. Ceramic properties of flint clays from Montes Claros, Minas Gerais, (3) 78*a*.
Kaplan, T. A. Magnetic ordering in Heisenberg magnets, B (9) 259*e*.
Kaplyanskii, A. A. See Feofilov, P. P.
Kaplyanskii, A. A., and Feofilov, P. P. Spectra of divalent rare earth ions in crystals of alkaline earth fluorides (II) europium and ytterbium, (9) 256*e*.
Kappey, H. J. See Zirngibl, H.
Kappmeyer, K. K. See Hubble, D. H.
Kapustkin, D. M. See Chernyak, M. G.
Kapyshev, A. G. See Ivanova, V. V.
Karagoz, B. Y. See Bailey, B. L.
Karaivanov, I. See Brashnarova, A.
Karaki, T. See Tanaka, H.
Karalis, S. N., Pies, J. R., and Slattum, C. L. Glass enclosed carbon-film resistor, P (7) 193*b*.
Karapetyan, G. O. Luminescence of glasses with lanthanide activators, (6) 148*f*.
Karasik, A. Kh. Device for investigating the properties of ferrite parts in the sonic and ultrasonic frequency ranges, (1) 13*g*.
Karch, Z. Colorimetric determination of selenium in ruby glasses, (10) 264*c*. Structure of the coloring pigment in selenium ruby glasses from the standpoint of analytical studies, (8) 211*d*. Theoretical principles of selenium losses in the melting of red (selenium ruby) glasses and the problem of reducing them (I) causes of selenium losses, (9) 235*d*.
Karchmar, Ts. A. See Shelyubskii, V. I.
Karesz, J. See Browarski, I.
Karet, J. M. Sprayed ceramics protect equipment, (9) 232*c*.
Karev, V. N. See Matyushenko, N. N.
Karlyuk, V. N. See Bondarev, K. T.
Karp, M. See Kuros, T.
Karpechenko, V. G. See Kitaigorodskii, I. I.
Karpus, A. See Audzijonis, A.
Karsch, K. H. Study of the transformation range of glasses, (7) 181*i*.
Karsch, K. H., and Jenckel, E. Thermal and mechanical investigations of alkali borate glass, (4) 95*d*.
Kartmazov, C. N. See Vasyutinskii, B. M.
Karube, N., Yamamoto, K., and Kamiyama, M. Thermal oxidation of silicon, (10) 291*c*.
Kasberg, A. H. Method of producing uranium carbide, P (7) 188*j*.
Kaser, J. D. Radioactive waste disposal using colemanite, P (11) 303*j*.
Kashintsev, V. P. Influence of geometric dimensions of the cooling section of the furnace on the readiness of the glass to be handled by the VVS machine, (1) 4*c*.
Kastanek, J. See Sirbal, H.
Kasuya, Y. See Okubo, S.
Kasymova, S. S. Physicochemical properties of sodium-strontium silicate glasses, (1) 4*j*.
Katagiri, M. See Saito, S.
Katano, Y. See Kubo, K.
Kataoka, M. See Takashi, T.
Katayama, H. See Shionoya, S.
Kato, C. Change of infrared absorption spectra in the range 3660 to 3740 cm^{-1} by the dehydration and rehydration of clay minerals, (5) 134*f*. Change of infrared spectra of clay minerals by dehydration, especially in the range 500 to 550 cm^{-1}, (5) 134*g*.
Kato, E., and Choshi, I. Preparation of hard fire iron red glaze, (4) 102*e*.
Kato, E., and Hasegawa, M. Electrical resistivity of carbon composite sintered materials (II) effects of firing temperature on resistivity, (4) 103*j*; (III) inner changes during sintering and their effects on resistivity, (10) 285*c*.
Kato, E., and Kanaoka, S. Chemical and mineral composition of antimony yellow (I) preparation of antimony yellow, (4) 102*d*.
Kato, E., and Morita, S. Underglaze blue by celsian type color, (4) 103*b*.
Kato, M. See Kubo, T.; Minowa, S.
Kato, M., Mizuta, M., and Minowa, S. Slaking reaction of CaO, (1) 10*j*.
Kato, M., Yamada, M., Kosaka, M., and Minowa, S. Applicability of silicon nitride brick and its erosion by molten nonferrous metals, (4) 99*a*.
Kato, M., Yamada, M., and Minowa, S. Relation between the diffusion of carbon in solid iron and the adherence of the ceramic coating, (4) 91*b*.
Kato, R. Optical properties of LiF in the extreme ultraviolet, (10) 289*d*.
Kato, S. See Okuda, H.; Sano, S.
Kato, S., Yamamoto, R., Hattori, T., and Nishimura, Y. Modulus of rupture and some properties of porcelain bodies, (4) 102*i*.
Kato, Y. See Morita, K.
Kats, A. See Haven, Y.
Katsumata, I. See Ohta, Z.
Katsura, K., Wakabayashi, A., Koga, M., and Koyama, Y. Deteriorated zones of magnesia refractories and dolomite brick used both in an open hearth and in a converter (I) effect of Al_2O_3 and SiO_2 as impurities, (6) 152*b*.
Katsura, T. See MacDonald, G. A.
Katz, G., and Roy, R. Flux growth and characterization of β-Ga_2O_3 single crystals, (4) 111*c*.
Katz, H. Ceramic tube with self-supporting frame grid electrode system, P (2) 41*b*.
Katz, L. See Dickson, J. G.; Donohue, P. C.; Galasso, F.
Katz, M. J. See Haas, K. J.
Katzschmann, R. Influence of La_2O_3 and ThO_2 on the crystallization behavior of optical glasses, (2) 31*g*.
Kaufman, M. M. Techniques associated with inductive sensing of tunnel diode memory cells, P (3) 74*b*.
Kaufman, R. G. See Kirk, R. M.

Kaufmann, W. See Seidel, W.
Kausen, R. C. Adhesives for high and low temperature (1), (2) 54*e*.
Kautz, W. G. Air atomizer for airless spray gun, P (1) 16*e*.
Kavaliauskas, J. See Babonas, G.
Kavaliauskiene, G. See Viscakas, J.
Kawai, N., and Otake, T. Method of producing magnesia clinker using anhydrous magnesium chloride as a mineralizer, P (2) 38*i*.
Kawaji, A. See Shiraishi, M.
Kawakami, I. See Kitamura, Y.
Kawakita, K., Otsuka, A., Tsutsumi, Y., Danjo, K., and Okada, Y. Compression process of spherical glass powders, (8) 208*h*.
Kawakubo, T. See Nomura, S.
Kawakubo, T., Yanagi, T., and Nomura, S. Properties of titanium sesquioxides containing vanadium ions, (10) 290*c*.
Kawalec, M. See Wieczorowski, K.
Kawamura, S. See Yamaguchi, G.
Kawase, K. See Hayakawa, K.
Kawecka, J. J., and Mumford, E. H. Glassware pressing apparatus with hydraulic control, P (10) 268*d*.
Kay, M. I. See Almodovar, I.
Kayatt, P. J. Method of making miniature gas discharge tubes, P (4) 105*j*.
Kaye, B. H., and Treasure, C. R. G. Thermal stability of sedimenting suspensions used to measure particle size distributions, (2) 45*c*.
Kazda, J. Electrogravimetric study of water in clays, (2) 49*j*.
Kazennov, B. A. Growth of lead sulfide monocrystals by Tammann's method, B (11) 320*a*.
Kaznacheeva, K. F. See Bergman, A. G.
Ke, Wen-min, Xan, Wen-ching, and Chang, Chi-yuan. Influence of BaO on the formation of portland cement clinker, (5) 118*g*.
Kean, J. S., Sr. Shipping crate for unitized packages [of glass sheets], P (4) 98*a*.
Kearns, W. J. Hot cathode electron tube, P (2) 41*e*.
Keattch, C. J. Estimation and determination of sulfate in soils and various other siliceous and calcareous metals, (9) 245*f*.
Kebler, R. W. See Rudness, R. G.
Keefe, D. G. See Janota, R. B.
Keeling, P. I. See Blodgett, W. E.
Keeling, P. S., and Holdridge, D. A. Mineralogical and chemical composition of Etruria marls from North Staffordshire, B (2) 56*a*.
Keer, L. M. Stress distribution at the edge of an equilibrium crack, (1) 25*f*.
Kehl, N. H. Refractory composition and method of producing same, P (5) 126*j*.
Kehl, W. L., and Stewart, M. M. Alumina product and its method of preparation, P (10) 282*j*.
Keil, K. Mineralogical modal analysis with the electron microprobe X-ray analyzer, (7) 195*d*.
Keiser, H. W. Back painting of glass, (9) 229*j*.
Keler, E. K. See Fan, Fu-Kan; Iskhakov, Kh. Sh.
Keler, E. K., and Chzhan, Tsin-Chun. Elastic properties of some clays and kaolins in relation to their heat treatment, (10) 282*g*.
Kell, R. D. Method of adhering [phosphor] particles to a support surface, P (11) 306*j*.
Keller, C., & Co. Transporting equipment, especially for loading molded ceramic pieces into dryers, P (8) 222*g*.
Keller, C. H. See Paquette, R. E.
Keller, D. L. See Bugl, J.; Chubb, W.; Hill, R. F.
Keller, J. D., and Meltzer, R. J. Reflecting diffraction grating for minimizing anomalies, P (5) 132*c*.
Keller, W. Apparatus for crucible-free zone melting of semiconductor material, P (11) 305*j*. Method and apparatus for floating-zone melting of semiconductor material, P (10) 278*d*. See Reuschel, K.
Keller, W., and Kramer, H. Method of crucible-free zone melting of semiconductor material, P (3) 73*i*.
Keller, W., and Spenke, E. Process for preparing semiconductor ingots within a depression, P (9) 244*a*.
Keller, W. D. See Reesman, A. L.
Kelley, J. E. See Harris, H. M.
Kelly, A., and Tyson, W. R. Fiber-strengthened materials, B (2) 55*g*.
Kelly, E. F. See Klerk, J. de.
Kelly, F. J., and McKee, K. H. Alloy, P (2) 37*j*.
Kelly, H. J. See Harris, H. M.; Paige, J. I.
Kelly, J. D. See Barch, H. W.; Malobicky, R. L.
Kelly, W. R. See Hartford, W. H.
Kelsall, D. F. Study of breakage in a small continuous open-circuit wet ball mill, (5) 130*j*.
Kelsey, R. H. Preparation of inorganic oxide monofilaments, P (11) 303*d*.
Kemp, H. T., Jr., Stalter, T. L., and Mueller, E. E. Inhibitors of microbial growth in porcelain enamel slips, (6) 145*h*.
Kempf, R. Colloidal and colloid-chemical processes in opal and pearl glasses, (10) 264*b*. Copper ruby glass, (7) 179*j*. Selenium ruby glass, (4) 95*e*.
Kendall, E. G. Special ceramics, (2) 55*a*.
Kendall, E. G., Slaughter, J. I., and Riley, W. C. New class of hypereutectic carbide compositions, (10) 272*d*.
Kendall, L. F., Jr., and Bredt, J. H. Method for producing lead telluride thermoelectric elements by vacuum hot-pressing, P (10) 279*c*.
Kendig, P. M., and Greene, D. C. Electroacoustic transducer for detection of low level acoustic signals over a broad frequency range, P (6) 159*c*.
Keneshea, F. J., and Fredericks, W. J. Diffusion of cadmium ions in solid potassium chloride, (7) 198*c*.
Ken-Mar Clay Products, Ltd. Method and apparatus for the production of hardened clay products, P (11) 300*d*.
Kennametal, Inc. Abrasive wheel, P (11) 293*f*. High temperature nozzle, P (4) 100*d*.
Kennecott Copper Corp. Dual-pivoting cradle type roll crusher, P (1) 18*d*. Method of crushing ores with explosive energy released in a liquid medium and apparatus therefor, P (1) 18*i*.
Kennedy, A. J. Creep model, (1) 19*d*.
Kennedy, G. C. See Sharp, W. E.
Kennedy, P. Process of producing spheroids of nuclear fuel materials by agglomeration, P (4) 101*k*.
Kennedy Van Saun Mfg. & Engineering Corp. Stationary circular contact cooler for calcined lime and other materials, P (11) 295*c*.
Kent, R. A., and Margrave, J. L. Mass spectrometric studies at high temperatures (VII) sublimation pressure of chromium(II) fluoride and the dissociation energy of chromium(I) fluoride; (VIII) sublimation pressure of iron(II) fluoride, (9) 251*k*.
Keramatik G.m.b.H. Burner for furnaces, P (1) 17*i*.
Kerkhof, F. Determination of the maximum fracture velocity of various glasses with the sonic method, (7) 179*f*. See Hara, M.
Kerper, M. J., and Scuderi, T. G. Modulus of rupture of glass below room temperature, (10) 265*j*. Relation of strength of thermally tempered glass to fracture mirror size, (1) 5*h*.
Kerr, G. T. See Garwood, W. E.
Kerr, G. T., and Kokotailo, G. T. Sodium zeolite ZK-4, a new synthetic crystalline aluminosilicate, (6) 164*j*.
Kerr-McGee Oil Industries, Inc. Method of acid leaching uranium ores, P (7) 188*g*.
Kerstan, H. See Kerstan, W.
Kerstan, W., and Kerstan, H. Celadon glazes, (8) 218*i*.
Keski, J. R., and Cutler, I. B. Effect of manganese oxide on sintering of alumina, (1) 20*d*.
Kessler, W. See Dippel, T.
Kesten, P. N. Spark plug with multiple conductive seals, P (11) 308*e*. Spark plug and seal therefor, P (4) 106*c*.
Kester, T. See Nechtschein, M.
Kestigian, M. See Yocom, P. N.
Kestigian, M., Leipziger, F. D., Carter, J. R., and Garabedian, F. G. Preparation of $K_4Nb_6O_{17}$ single crystals, (10) 289*f*.
Kestner, H. R. See Pate, A. F.
Ketterer, R. J., and Hursh, R. W. Inorganic bonded reconstituted micaceous products, P (1) 14*d*.
Keutel, M. See Meyer, K.
Kevorkov, A. M. See Sheftal, N. N.
Keyes, R. J. See Zeiger, H. J.
Keys, D. L. See Broderick, J. P.
Keys, D. L., Broderick, J. P., and Lohnes, F. G. Remote powder feed for flame spraying torch, P (11) 296*c*.
Keyser, W. L. de. Note concerning the exothermal reaction of kaolinite and the formation of a spinel phase preceding that of mullite, B (2) 56*d*.
Keyser, W. L. de, Wollast, R., and Laet, L. de. Study of OH groups in kaolin materials, B (2) 56*c*.
Kharitonov, F. Ya. Kinetics of corundum crystallization, (5) 137*j*.
Kharitonov, Yu. Ya. See Mal'tseva, N. N.
Khayutin, Yu. G. See Sovalov, I. G.
Khazanov, V. E. See Aslanova, M. S.
Khazemova, T. F. See Skiba, O. V.
Khershel'mann, V., and Berg, A. Determining the tendency of steel to develop fish-scaling in enamels, (6) 145*d*.
Khil'ko, V. V. See Nichiporenko, S. P.
Khinkis, M. Ya. See Ginzburg, D. B.
Khodakov, G. S. Principles of gas flow through finely porous bodies, (5) 140*c*.
Khodakovskaya, R. Ya. See Kitaigorodskii, I. I.
Khodolei, V. I. See Olival'nyi, F. A.
Khomyakov, K. G. See Tret'yakov, Yu. D.
Khorol'skii, Yu. M. See Vidro, L. I.
Khramkov, V. P. Electric furnace for softening apparatus glass, (7) 180*e*.
Khrycheva, D. D. See Vasil'ev, Ya. V.
Kibbey, H. S. Abrasive article containing zirconium tetrafluoride filler, P (11) 293*f*.
Kida, K., Abe, M., and Nishigaki, S. Method of producing beryllium oxide from beryllium containing ores, P (5) 133*f*.
Kidwell, C. H. Classifying and reducing method and apparatus, P (8) 225*b*.
Kieffer, E. Discussion of "Study of the buckling of flat-bottomed vessels," (2) 40*b*.
Kiehl, J. P., and Nicolle, J. Glass and slag resistant refractories and process of making same, P (7) 188*c*.
Kiehl, J. P., and Valentin, G. Thermal shock resistance of refractory products, (10) 273*b*.
Kielski, A. Solid phase reactions between magnesium and chromium oxides, (7) 187*g*.
Kienow, S., and Sauthoff, J. Chemically bonded magnesite-chrome brick under a changing torsional load, (7) 185*g*.
Kierkegaard, P., Longo, J. M., and Marinder, B. O. Crystal structure of $VOSO_4$, (2) 49*c*.
Kiffer, A. D., Nestor, O. H., Tensmeyer, L. G., and Corbitt, B. J. Use of two magnetic fields in a low pressure arc system for growing crystals, P (5) 131*b*.
Kihlstedt, P. G. Mineral surface and water phase, B (7) 204*c*.
Kikuchi, M. See Iizima, S.; Koda, S.
Kilby, J. S. Method of making miniaturized electronic circuits, P (9) 243*j*.
Kilby, J. S., and Lathrop, J. W. Semiconductor networks, P (2) 42*i*.
Kim, K. H. Resistor composition, P (5) 129*b*.
Kimberlin, C. N., Jr. See Eberly, P. E., Jr.
Kimble, F. E. Continuous kiln, P (7) 195*b*.
Kimmel, S. See Gebhardt, F.
Kimmlinger, K. T. See Hosbein, L. H.
Kimpe, C. de. See Calvet, R.
Kimura, H. See Takagi, T.
Kimura, M. Refractory raw materials of South African republics, (9) 239*c*.
Kimura, S. See Yamada, H.
Kimura, Y. Ultrasonic wave propagation velocity in ferrite and the elastic constant, (11) 305*i*.
Kinase, W. Theory of the dielectric constants of barium titanate, (11) 305*h*.
Kindel, E., Hass, E., and Schroeder, W. Beacon especially suited for airport runways (to be rolled over), P (10) 267*e*.
Kindl, B. Gettering processes, (9) 245*i*.
King, C. B. See Goodman, P.
King, D. F. Silica refractory, P (5) 127*c*. See Birch, R. E.; Henry, G. R.
King, H. M. See Horton, J. C.
King, J. C. See Fraser, D. B.; Laudise, R. A.
King, L. D. P. Radiation reactor, P (10) 274*h*.
King, P. See Schulman, J. H.
King, R. P. See George, J. E.
King, W. G., Leete, C. R. J., and McKeag, A. H. Fluorescent lamp with a phosphor coating of platelike crystals, P (6) 159*g*.
King, W. J., and Uppgren, J. J. Mold and core binder for foundry use, P (1) 11*g*.
Kingery, W. D. See Rhodes, W. H.
Kini, K. A., and Stacy, W. O. Adsorption of helium by carbonaceous solids, (4) 109*i*.
Kinkade, W. A. See McCleary, R. E.
Kinney, S. P. Checker block and checker construction made therefrom, P (3) 70*e*.
Kinney, S. P., Engineers, Inc. Checker block and checker construction made therefrom, P (3) 70*e*.
Kinsky, J. F. See Zaslavsky, D.
Kint, L. N. See Hanse, A. B.
Kipping, P. J. See Jeffery, P. G.
Kirby, C. K. Roundup of tests for porcelain enamel finishes, (11) 295*d*.
Kirby, R. C. See Peters, F. A.
Kirchner, H. P., and Gruver, R. M. Chemical strengthening of polycrystalline ceramics, (7) 197*i*.
Kirchoff, A. (translator). Set 15,000 brick per hour and still maintain flexibility, (2) 35*i*.
Kirchoff, P. M. Drain line coupling for plain end glass pipe, P (5) 122*e*.
Kirk, R. D. See Schulman, J. H.
Kirk, R. M., Overton, G. W., Specht, C. H., and Kaufman, R. G. Abrasive sponge, P (8) 205*g*.
Kirk, S. Ophthalmic lens hardening apparatus, P (9) 236*g*.
Kirk Optical Lens Co., Inc. Ophthalmic lens hardening apparatus, P (9) 236*g*.
Kirklin, P. W., Auzins, P., and Wertz, J. E. Hydrogen-containing trapped hole center in magnesium oxide, (5) 137*e*.
Kirson, B. See Bodenheimer, W.
Kiryushkin, A. M. See Tsaritsyn, M. A.
Kisch, H. J. Study of medium to calcic plagioclase feldspars from coal-ash slags, (6) 170*f*.
Kiselev, B. A. Production of glass-reinforced plastics and articles made from them, (6) 148*e*.
Kishi, T., and Sakurai, J. Thermal glow of some commercial glasses irradiated by ultraviolet, X, and γ rays, (7) 181*j*.
Kishida, M. Selection of materials for stopper head and sleeve for handling specific steel materials when the ladling temperature is raised to 1160° to 1690°C, (9) 239*e*. See Shimada, N.; Takahashi, O.
Kiss, K., Magder, J., Vukasovich, M. S., and Lockhart, R. J. Ferroelectrics of ultrafine particle size (I) synthesis of titanate powders of ultrafine particle size, (7) 191*e*.
Kistler, S. S., and Rue, C. V. Reinforced snagging wheel, P (9) 229*g*.
Kita, H. See Masuda, M.
Kita, M. See Izumi, G.
Kitahara, A. See Maeno, M.
Kitaigorodskii, I. I., Fainberg, E. A., and Grechanik, L. A. Influence of certain oxides on the reduction of lead silicate glasses in hydrogen, (4) 93*f*.
Kitaigorodskii, I. I., Gurevich, Ts. N., and Beus, M. D. Reasons for the deformation of glass during crystallization, (10) 266*b*.
Kitaigorodskii, I. I., Karpechenko, V. G., and Grechanik, L. A. Significance of the polarization properties of ions for developing fusible glasses, (4) 95*c*.
Kitaigorodskii, I. I., and Khodakovskaya, R. Ya. Possibilities of differential thermal analysis in studying the crystallization of glass, (9) 234*j*.
Kitaigorodskii, I. I., Khodakovskaya, R. Ya., and Artamonova, M. V. Phase transformations in the catalytic crystallization of glass in the system SiO_2–Al_2O_3–MgO, (9) 253*b*.
Kitaigorodskii, I. I., and Kopytov, L. N. Strengthening sheet glass by etching, (7) 181*i*.
Kitaigorodskii, I. I., and Rostokinskii, V. V. Forming glass films, (9) 233*d*.
Kitaigorodskii, I. I., Rostokinskii, V. V., and Elinek, V. I. Method of determining the breaking and elastic characteristics of films, (9) 233*j*.

Kitaigorodskii, I. I., and Shirkevich, T. L. Effect of the nature of glass crystallization on the structure of foam glass, (4) 93*a*.
Kitaigorodskii, I. I., and Usvitskii, M. B. Origin and development of the crystalline phase in glasses, (6) 148*a*. Study of certain physicochemical properties of glasses as a function of their composition, (10) 266*d*.
Kitajima, S. See Mihara, Y.
Kitamura, S. Effect of oxygen on sintered cadmium sulfide photoconducting films, (10) 276*i*.
Kitamura, S., Kubo, T., and Yamashita, T. Enhancement of photoconductivity in cadmium sulfide single crystals, (4) 111*h*.
Kitamura, Y. Comparative study of Japanese and American bottom sleeves used for a 150-ton ladle, (1) 8*c*. Hot maintenance repairs to ladle lining by means of a gun, (1) 9*e*. Quality and durability of ladle bottom brick and mortar, (3) 68*h*.
Kitamura, Y., and Kawakami, I. Changes in the method of water-cooling the front and rear walls of a 120-ton fixed type open hearth, (3) 65*g*.
Kittel, J. H. See Neimark, L. A.
Kitzinger, E. See Bergstein, A.
Kivlighn, H. D., Jr. Solid state reactivity and glass crystallization behavior of some alkali aluminogermanates, (4) 95*h*.
Kiwaki, S. See Okugawa, T.
Kjekshus, A. See Alcock, N. W.; Bjerkelund, E.; Furuseth, S.; Selte, K.
Klahr, C. N. Fabrication of semiconductor devices by transmutation doping, P (8) 221*a*.
Klamer, K. Technology of electroceramics, (7) 192*g*.
Klasens, H. A. Photoconducting phosphors, B (9) 259*f*.
Klass, D. L. See Martinek, T. W.
Klein, Adalbert. German contribution to modern European ceramic design, (10) 261*h*. New investigations of historic porcelains, (3) 58*b*. Postage stamps featuring ceramics, (10) 261*i*.
Klein, Alexander. Expansive and shrinkage-compensated cements, P (8) 207*d*. High-alumina cement, P (9) 231*d*.
Klein, B. Hollow spheres—versatile design tool, (4) 108*j*.
Klein, C. A. Laser-action threshold in electron-beam excited gallium arsenide, (10) 287*e*.
Klein, C. H. See Harel, S.
Klein, D. L. Semiconductor surface cleaning, P (3) 74*g*.
Klein, D. L., and MacDonald, R. W. Method of fabricating semiconductor contacts, P (2) 41*j*.
Klein, G. deV. Dispersal and petrology of sandstones of Stanley-Jackfork boundary, Ouachita fold belt, Arkansas and Oklahoma, (5) 133*c*.
Klein, H. M. See Hilton, A. R.
Klein, M. J. Structure of explosively shocked MgO crystals, (3) 86*b*.
Klein, P. D., and Erenrich, E. H. Tritiated alumina as a reagent for self-labeling chromatographic analyses, (5) 131*j*.
Klein, W. A. See Duwell, E. J.
Kleinert, P. See Bergstein, A.
Kleingers, A. B., Jr. See Bergstein, F. D.
Kleinschmidt, R. S. See Lees, S.
Kleinteich, R. Sealing glass-copper tubing, (10) 266*g*. Structure of the flame and thermoplastic working of glass, (10) 266*a*.
Kleist, D. See Slayter, G.
Kleist, D., and Hummel, J. M. Uniformity indicator, P (2) 35*a*.
Kleist, D., Snow, H. J., and Buchanan, C. S. Method of and apparatus for forming fibers, P (11) 298*f*.
Klemens, P. G. See Klerk, J. de.
Klement, R., and Harth, R. Lead apatites and tertiary lead phosphate, (3) 83*j*.
Klemm, W., and Volkmann, H. Electron microscopic study of the production of glass-ceramics, (2) 31*a*.
Klerk, J. de, and Kelly, E. F. Vapor-deposited thin-film piezoelectric transducers, (10) 277*e*.
Klerk, J. de, Klemens, P. G., and Kelly, E. F. Multilayer enhancement of microwave piezoelectric conversion in CdS–SiO layers, (10) 288*b*.
Kliesch, C. Fundamentals of the control of pot furnaces, (7) 180*a*.
Klimaszewski, I. C. Method of preparing zirconium oxide, P (7) 188*h*.
Klimaviciene, V. Comparative lithological characteristics of Lithuania's quaternary sands (main genetic types) (I) granulometric analysis, (11) 314*c*.
Klimenko, V. N. Strength of chromium carbide hard alloys, (10) 272*d*.
Kline, D., and Bray, P. J. Nuclear magnetic resonance investigations of the structure of glasses in the system $NaF–Na_2O–B_2O_3$, (6) 148*i*.
Kline, R. E., and Starnes, W. C. Catalyst composition comprising the oxides of alkali and chromium on eta alumina, P (6) 154*a*.
Kling, H. P., and Weissmann, T. S. Hafnium oxide-europium oxide compounds and compositions for reactor control elements, P (2) 37*g*.
Kling, N. G. See Ferrari, A.
Klingler, N., Strauss, E. L., and Komarek, K. L. Reactions between silica and graphite, (8) 227*h*.
Klingler, E. See Dawihl, W.
Kloeckner-Humboldt-Deutz Akt.-Ges. Cone crusher, P (4) 109*d*. Method and apparatus for heating and burning cement raw material containing alkali, P (1) 3*a*. Vibratory conveyor, particularly bin-discharge conveyor, P (1) 16*d*. Vibratory grinding mill, P (1) 19*b*. Vibratory grinding mill of the drum type, P (1) 19*c*.
Klossika, W. Method of marking semiconductor crystals, P (10) 279*b*.
Knapp, E. J., Reas, L. F., and Sayers, M. Containers [paperboard] for TV bulbs, tubes, and the like, P (4) 96*b*.
Knapp, O. Application of glass fiber products in the building industry, (3) 60*e*. Structure of soda-lime glasses, (10) 266*b*. Use of glassware in the chemical industry, (1) 5*j*.
Knapp, W. J. See Neely, J. R.; Shanley, F. R.; Weiss, D.
Knapp, W. R., and Smith, E. R. Method for forming balls from thermoplastic materials, P (8) 213*g*.
Knapsack-Griesheim Akt.-Ges. Mineral-bound material, P (8) 217*i*. Process for the manufacture of a catalyst containing vanadium and tin oxides, P (6) 155*h*.
Knausenberger, M. See Baernighausen, H.
Knausenberger, M., Brauer, G., and Gingerich, K. A. Preparation and phase studies of titanium phosphides, (8) 227*a*.
Kneipple, J. H. Composite glass fiber products and process of preparing the same, P (2) 33*d*.
Kniefel, R. M. See Bentle, G. G.
Kniepkamp, H. See Rummel, T.
Knight, H. R. Induction heating method for making molds, P (9) 240*e*.
Kniseley, R. N. Atomizer burner, P (10) 281*g*.
Knop, O., Brisse, F., and Castelliz and Sutarno, L. Determination of the crystal structure of erbium titanate, $Er_2Ti_2O_7$, by X-ray and neutron diffraction, (5) 134*j*.
Knopf, H. See Heinze, G.
Knopp, A. N., and Stickler, R. Effect of residual atmospheres on silicon surfaces, (11) 316*e*.
Knudsen, I. E., Hootman, H. E., and Levitz, N. M. Fluid-bed process for the direct conversion of uranium hexafluoride to uranium dioxide, (3) 67*b*.
Knutson, C. D., Hooper, H. O., and Bray, P. J. Nuclear magnetic resonance study of decomposition in neutron-irradiated LiF, (9) 252*c*.
Kobayashi, M. See Atoda, T.
Kobayashi, R. See Koonce, K. T.
Kobayashi, T. See Munekata, E.; Nakamura, H.
Kobe Steel Works, Ltd. Very high pressure apparatus, P (9) 245*a*.
Kobell, S. Work of the Bern (Switzerland) School of Ceramics, (8) 206*d*.
Kobrin, C. L. Composites—the grand strategy, (3) 59*h*.
Koch, A. J. J. See Hokkeling, P.
Koch, P. H. Graphite-plate heat exchange apparatus, P (4) 100*d*.
Koch, R. L. Semiconductor device, P (4) 106*g*.
Kocharov, E. P. Developments in the manufacture of glass fiber in East Germany, (9) 233*d*.
Kochi, T., Nameishi, N., and Inoue, A. Deteriorated zones of magnesia refractories and dolomite brick used both in an open hearth and in a converter (III) change in the lattice constant for magnesia clinker and seawater magnesia clinker during heating, (6) 152*d*.
Kocsis, G. See Locsei, B. P.
Koda, S., Morozumi, S., and Kikuchi, M. Electron microscope study of the interaction between dislocations and oxide particles in magnesium, (1) 21*e*.
Koda, Y., and Takagi, S. Separation of ^{140}La from a $^{140}Ba–^{140}La$ mixture by coprecipitation with ferric hydroxide, using several organic bases as precipitants, (4) 107*c*.
Kodera, H., Iida, S., and Sugita, Y. Method of fabricating semiconductor devices by alloying a gold disk containing active impurities to a germanium pellet, P (6) 159*h*.
Kodera, H., Iida, S., and Tauchi, S. Diffusion of impurities in the semiconductor melt (III) experimental determination of thickness of the solute diffusion layer in the melting process, (11) 304*i*.
Kodera, H., and Tauchi, S. Diffusion of impurities in the semiconductor melt (II) dynamical analysis of impurity redistribution in the melting process, (11) 304*i*.
Koehler, E. K., and Patzak, I. Effect of addition of aluminum sulfate on the ceramic properties of refractory clays and on the mineralogical structure of the fired products, (3) 66*f*.
Koehler, E. K., and Routschka, G. Firing behavior of clays in various atmospheres, (5) 136*g*.
Koenig, A. See Bauer, W.
Koenig, C. J. Some considerations regarding fast firing vitrified bodies, (6) 156*j*.
Koenig, W. K. Cement sack pallet and handling equipment, P (4) 91*a*.
Koepernik, K. H. High temperature-resistant catalyst carrier and method of preparation thereof, P (5) 125*j*.
Koerner, E. L. See Downing, J. H.
Koester, A., and Rogner, H. Stable, alkali-rich sodium silicates, P (9) 247*i*.
Koffinke, R. A. Solid bowl centrifuge with air circulation control, P (11) 309*c*.
Koga, M. See Katsura, K.
Kogan, V. S. See Vasyutinskii, B. M.
Kohane, T., and Silverman, B. D. Electrical conduction in nickel ferrous ferrites, (4) 103*i*
Kohl, L. Method of making a porous ceramic product, P (11) 300*c*.
Kohlhass, B. See Muller, F.
Kohlmuller, R., and Leitner, N. Cryoscopic study of some alkaline and alkaline-earth vanadates in molten vanadium hemipentoxide, (2) 48*j*.
Kohn, H. W. γ-radiation-induced exchange of deuterium with silica surfaces, (9) 250*e*.
Kohn, J. A. See Tauber, A.
Kohn, J. A., and Eckart, D. W. Mixed-layer polytypes related to magnetoplumbite, (9) 252*h*.
Kohn, J. D. See Nesbitt, H. M.
Kohra, K., and Watanabe, H. Measurement of anomalous absorption coefficients of electrons for MgO crystals, (10) 288*d*.
Koide, K. See Tachibana, S.
Koizumi, M. See Kume, S.
Kojima, A. See Otani, S.
Kokorish, E. Yu. See Ozolis, K. K.
Kokotailo, G. T. See Kerr, G. T.
Kolb, E. D. [Hydrothermal] crystal growth container, P (11) 306*h*. See Laudise, R. A.
Kolb, E. D., and Laudise, R. A. Hydrothermally grown ZnO crystals of low and intermediate resistivity, (7) 191*h*.
Kolb, K. E., and Hansen, K. W. Time and temperature effects on silica distribution in borate glasses, (3) 62*b*.
Kolek, R. L., and Eilerman, G. E. Method of sizing glass fibers and epoxy resin emulsion therefor, P (7) 184*a*.
Kolene Corp. Methods and compositions for cleaning metal, P (9) 232*d*.
Kolesnichenko, G. A. See Naidich, Yu. V.
Kolesova, V. A. Studies of synthetic and natural eucryptite, (5) 141*f*.
Kolle, G. F. Bushing insulator for core type induction furnace, P (3) 70*c*.
Kollmorgen Corp. Method of producing aspheric surfaces on mirrors or lenses, P (1) 7*c*.
Kolobova, K. M. See Nemnonov, S. A.
Kolostori, J. Rapid method for fractional-fill determination of ball mills, (2) 43*f*.
Kolotii, A., and Delimarskii, Yu. K. Electrochemical investigation of the system $SnCl_2–KCl$, (1) 21*b*.
Kolotyrkin, Ya. M. See Gil'man, V. A.
Koiski, T. L., and Ling, H. W. Solid electrolyte capacitors utilizing anodes derived from tantalum-titanium alloys, (8) 220*f*.
Koltermann, M. Thermal decomposition of the hydrated magnesium silicates, (3) 86*i*. See Lehmann, H.; Mueller, K. P.
Koltermann, M., and Kupzog, E. Physicochemical behavior of cold-bonded refractory brick, (9) 238*e*.
Koltermann, M., and Mueller, K. P. Crystal chemistry and thermal behavior of sepiolite, hectorite, saponite, palygorskite, and anthophyllite, (3) 80*h*.
Koltermann, M., and Wiegmann, D. Torsional testing of fireclay brick at high temperature, (9) 239*e*.
Kolthoff, B. (compiler). Glass Terminology—A German-English Glossary, B (6) 172*i*.
Kolthoff, I. M., and Elving, P. J. (editors) **with Sandell, E. B.** Treatise on Analytical Chemistry (Part I) Theory and Practice (Vol. 6), B (3) 88*f*.
Komarek, K. L. See Klinger, N.
Komarova, L. P. See Vladimirov, L. P.
Komisarek, J. A. Solid electrolytic capacitor with layer comprising silica on the electrolyte layer, P (6) 161*b*.
Komiya, H. See Ibuki, S.
Komoda, H. See Hayashi, T.
Konikova, R. S. See Vladimirov, L. P.
Koning, J. de, and Bosman, M. Method of and apparatus for separating particles of different specific gravity in a jig, P (8) 225*c*.
Konishi, Y. See Niwa, S.
Konkoly, J. See Juhasz, A.
Konno, H. See Gondo, Y.
Kononko, V. P. See Zakharikov, N. A.
Konopicky, K. Change in grain size during the pressing of granular mixtures, especially of refractory bodies, (10) 270*g*. Composition of aluminosilica refractories and the factors on which it depends, (5) 125*e*. International study of the method of testing for under-load refractoriness, (1) 9*g*. Problems of modern refractories research, (3) 68*g*. Testing the degree of firing of fireclay, (2) 37*e*.
Konopicky, K., Bruchhausen, C., and Bird, R. Investigations on silica brick for electric furnace roofs, (6) 152*h*.
Konopicky, K., Dietzel, A., Oel, H. J., and Saalfeld, H. Processes at the interface between refractory material and glass or slag, (5) 125*h*.
Konopicky, K., Mueller, E., Mueller, J., and Reich, H. F. Testing of the degree of firing of fireclay, (2) 37*e*.
Konopicky, K., and Patzak, I. Investigations of structure and transformation of minerals of the sillimanite group, (10) 287*h*.
Konopicky, K., Patzak, I., and Dohr, H. Investigations in the binary system $Al_2O_3–SiO_2$, (5) 137*f*.
Konopicky, K., and Routschka, G. Observations of the silica crown of a glass tank—brick showing different surface effects on their hot face, (10) 265*b*.
Konopicky, K., Routschka, G., and Baum, M. Morphology and crystal size distribution of mullite in fireclay, (2) 36*c*.
Konopicky, K., Routschka, G., and Lohre, W Comparison of the erosion of high alumina brick by alkali containing atmospheres and by soda-lime glass melts, (1) 8*f*.
Konopicky, K., Tkotz, G., and Kowalczyk, F. Determination of density with an air comparison pycnometer, (3) 75*f*.
Konopicky, K., Wohlleben, K., and Gotthardt, H. Softening of glass pot mixtures under torsion, (1) 5*b*.
Konopicky, K., Wohlleben, K., and Mill, G. Development of mechanical strength in refractory products during drying, (9) 238*a*.

Konstantinov, V. See Shturbanov, M.
Konstantinov, V. I. See Tsui, Bin-Sin'.
Konstantinov, V. I., and Tsui, Bin-Sin'. Melting temperature and thermal stability of potassium fluorotantalate, K_2TaF_7, (1) 23*h*.
Konta, J. Raw kaolin of Sedlec (Zettlitz) near Karlsbad, (1) 18*h*, (2) 47*d*.
Kontes Glass Co. Pressure stopcock, P (10) 269*k*. Stopcock and plug retainer therefor, P (11) 299*k*.
Kooi, E. Zener diode, P (8) 222*b*.
Kooi, E., and Schmitz, A. Method of providing alloy contacts on semiconductor bodies, P (4) 105*f*.
Koonce, K. T., Deans, H. A., and Kobayashi, R. Generalization of gas-liquid partition chromatography to study high pressure vapor-liquid equilibria of multicomponent systems, (1) 21*g*.
Koop, C. H. Mold patch support, P (1) 7*a*.
Koopman, P. Coated abrasive grain, P (11) 293*f*.
Koopmans, K., and Rieck, G. D. Thickness of the disturbed layer on ground quartz powder with particle size of 1.5*μ*, (3) 87*h*.
Kopanda, J. E. See Kalousek, G. L.
Kopchak, M. C. Comparison of properties of various grades of porcelain enameling steels, (4) 91*e*.
Kopera, J. Manufacturing process for reusable molds, P (4) 100*g*.
Kopito, L. High temperature furnace, P (5) 132*e*.
Koppers Co., Inc. Beneficiation means and methods for autogenous grinding systems, P (4) 109*c*. Grinding mill lining and control of the wear thereof, P (1) 16*a*. Grinding mill and process, P (4) 109*g*. Lightweight concrete, P (11) 295*a*. See Independence Foundation.
Kopytov, L. N. Strength reduction in glass following mechanical damage to its surface, (7) 181*g*. See Kitaigorodskii, I. I.
Korach, M., and Menyhart, M. Behavior of silicon carbide in the burning space, (5) 125*a*.
Korach, M., and Moldvai, R. Preparation of porous ceramic sampler for chromatographic measurements, (2) 45*c*.
Koranyi, G., and Nador, B. Silver ion sorption properties of glass surfaces, (5) 121*d*.
Korbel, A. See Gibas, T.
Kordek, M. See Winogradow, L.
Kordes, E. Light dispersion, ultraviolet vibrations, and light transmission in the ultraviolet of oxidic glasses (I), (1) 4*e*.
Kordesch, K. V. See Clark, M. B.
Kordonskaya, R. K. See Zavarzina, E. I.
Kordyuk, R. A., and Gul'ko, N. V. Tetrahedra in the system $MgO–Al_2O_3–ZrO_2–SiO_2$, (9) 257*g*.
Korelova, A. I., and Makarova, T. A. Polishing capacity of Russian and imported polishing powders, (5) 121*i*.
Korobko, M. I. See Serdyuk, S. M.
Korol'kov, D. V. See Shchukarev, S. A.
Korshunov, B. G. See Pashinkin, A. S.; Safonov, V. V.; Shevtsova, Z. N.
Korshunov, B. G., Lidina, E. D., and Shevtsova, Z. N. Fusibility diagram in the system $MoCl_5–AlCl_3–FeCl_3$, (10) 286*b*.
Korshunov, B. G., and Safonov, V. V. Thermal analysis of melts in the system $NbCl_4–NaCl–KCl$, (5) 141*i*.
Korshunov, B. G., and Vyrskaya, L. A. Physicochemical study of the system $WCl_5–AlCl_3–NaCl$ and $WCl_5–FeCl_3–NaCl$, (3) 84*g*.
Korshunov, V. A., and Gel'd, P. V. Electrical properties of the higher silicide of manganese, (11) 316*a*.
Korton, G. Thermocouple probe, P (5) 132*d*.
Korzina, E. N. See Shevtsova, Z. N.
Kosaka, M. See Kato, M.; Minowa, S.; Takayanagi, T.
Kosco, J. C. Silver-refractory metal electrical contact having refractory metal carbide in the marginal layer of its active contact face, P (3) 74*h*.
Kosloff, A. Ceramic Screen Printing, B (3) 88*g*.
Kosolanova, T. Ya. See Samsonov, G. V.
Kosolapov, T. Ya. See L'vov, S. N.
Koss, P. Coating of nuclear fuel particles with pyrolytic carbon in a fluidized bed, (9) 237*j*.
Kossovskaya, A. G., Drits, V. A., and Aleksandrova, V. A. Trioctahedral micas in sedimentary rocks, B (2) 56*e*.
Kost, M. E. See Mikheeva, V. I.
Kostanyan, K. A., and Saakyan, K. S. Electrical conductivity of some industrial glasses in the molten state, (9) 233*i*.
Kostecki, T., and Galewicz, C. Measuring and controlling the thickness of glass sheet, (2) 31*j*.
Kostenko, E. A. See Nichiporenko, S. P.
Kostetskii, B. I., Belitskii, M. E., and Natanson, M. E. Determination of carbon and silicon in sintered nickel-base materials by the method of spectral analysis, (3) 66*c*.
Kosti, T. M., and Moe, L. A. Semiconductor devices, P (3) 74*f*.
Kostiner, E. See Banks, E.
Kothen, C. W. See Healy, G. W.
Kotlyar, A. A. See Zhmud, E. S.
Kotlyar, A. E. Use of gas-electric heating in tank furnaces for glass container production, (9) 235*h*.
Kotosonov, N. V. See Ugai, Ya. A.
Kottas, H. Determination of Poisson's ratio [of portland cement mixtures] by measurement of the Young and torsional elastic moduli, (6) 144*j*.
Kouchich, A. V. See Schlicke, H. M.
Koupil, Z. Problems connected with the mass production of cements with high early strength (quick setting cements), (8) 207*f*.
Koury, F., and Fortucci, P. Process for increasing light emission, stabilization, and rejuvenation of electroluminescent lamps and phosphors, P (2) 42*d*.
Koutz, S. L. Fuel element, P (8) 217*a*.
Koutz, S. L., and Turner, R. F. Fuel element, P (11) 302*f*.
Koval'chenko, M. S., and Samsonov, G. V. Relaxation phenomena during the hot compacting of molybdenum carbide, (1) 290*i*.
Kovalev, I. T. See Voronov, N. M.
Koval'skii, A. E. See Ivensen, V. A.
Kovchur, S. G. Crystal glass with low PbO content, (7) 170*j*.
Kovsh, G. I. See Kachalov, S. S.
Kovzel, N. I. See Avdasev, V. I.
Kowalczyk, F. See Konopicky, K.
Kowalka, W. R. See Morgan, J. E.
Koyama, Y. See Katsura, K.
Kozin, G. N. See Serdyuk, S. M.
Kozlovskii, M. I. Production of crystallization nuclei at the surface of an aqueous solution by a spark discharge, B (11) 319*i*.
Kozlovskii, V. Developments in the Polish glass industry, (10) 264*e*.
Koz'min, M. I., and Minakov, A. G. Alternate melting of colored and colorless glass without stopping the tank furnace, (9) 232*h*. Zone type glass furnace, (9) 235*j*.
Koz'min, M. I., and Skripko, S. A. Chemically desalted water for silvering glass, (9) 233*a*.
Kozuka, T. See Ota, E.
Kraft, P., and Schlomer, J. Method for the production of an improved metal/ceramic material and articles, P (5) 120*a*.
Krag, W. E. See Zeiger, H. J.
Krainik, N. N. See Smolenskii, G. A.
Kraitzer, I. C. Process for extraction of thoria and ceria from rare earth ores, P (8) 225*f*.
Kramer, B. E. Method of forming a refractory metal rocket nozzle, P (4) 91*i*.
Kramer, H. See Keller, W.
Kramer, H., and Pinto, L. J. Flame-photometric determination of sodium in uranium ores, (2) 44*g*.
Kramer, W. Method and apparatus for cooling burned materials discharged by a furnace for burning cement, magnesite, lime, or the like, P (11) 311*i*.
Kramer, W. E., and Mazelsky, R. Crystal growth of *β*-spodumene, (6) 166*a*.
Kranitz, M. See Seal, M.
Krasil'nikova, L. M., and Presnov, V. A. Thermographic analysis of crystallized glasses of the system $Na_2O–SiO_2$, (4) 95*e*.
Krasnov, A. N., and Sleptsov, V. M. Arc plasma in powder metallurgy, (7) 178*f*.
Krasnov, Yu. N. See Smirnov, M. V.
Krasotkina, N. I. See Voronin, N. I.
Kratochvil, I. Effect of draft conditions on the uniform working of rotary kilns with an exchanger system, (11) 311*f*.
Kraus, J. W. See Heinemann, H.
Kraus, K. A., Marcinkowsky, A. E., Johnson, J. S., and Shor, A. J. Salt rejection by a porous glass, (5) 121*j*.
Krause, J. T. See Kurkjian, C. R.
Krauss, G. See Kumagai, H. Y.
Krauss, H. See Thuy, J.
Krauth, A., and Oel, H. J. Characterization of the properties of oxide powders, (9) 248*h*.
Kreglo, J. R., Jr. Dilatometer for heated specimens under external stress, P (5) 132*d*.
Kreimer, G. S., and Alekseyeva, H. A. Mechanism of fracture in sintered tungsten-cobalt carbides, (10) 288*e*.
Krentsis, R. P., and Gel'd, P. V. Thermal capacity of iron silicides at 55° to 300°K, (10) 291*b*.
Krestnikova, E. N. See Slavyanskii, V. T.
Kretz, R. Analyses of equilibrium in garnet-biotite-sillimanite gneisses from Quebec, (7) 197*d*.
Kreuter, J. C. See Vuyk, J.
Kreuz, R. J. See Jasper, H. P.
Krey, R. A. Methods and materials for metallizing ceramic or glass bodies, P (2) 42*g*.
Kreymer, G. S., Tumanov, V. I., Kamenskii, D. S., and Pavlova, Z. I. Tensile strength and rupture mechanism of sintered tungsten carbide cobalt alloys in compression, (10) 272*i*.
Kriegel, W. W., Palmour, H., III, and Choi, D. M. Preparation and mechanical properties of spinel, B (11) 320*f*.
Krieger, A. E., and Golding, K. E. Inspection apparatus for transparent glass sheets, P (11) 298*b*.
Kriegsman, B. Method of producing a semiconductor device, P (2) 42*f*.
Kriek, H. J. S., Segal, B. B., Steyn, J. G. D., and Waal, P. de. Mechanism of wear of magnesite rotor linings, (8) 215*g*.
Krikorian, O. H. See Jackson, D. D.; Lofgren, N. L.
Krings, A. See Schnabel, O.
Kringstad, K. See Langmyhr, F. J.
Krischner, H. See Torkar, K.
Krisciunas, V., and Mikalkevicius, M. Effect of temperature on the optical absorption edge in trigonal selenium single crystals, (3) 81*j*.
Krishnan, R. See Makram, H.
Krishnaswamy, K. T. See Iyengar, K. T. S. R.
Krisleit, R. F. See Caprio, M. J.
Krivolapov, M. M. Machine for beveling glass, (9) 233*i*.
Krivoruchko, V. M. See Ivanov, V. E.
Krivtsov, N. V., and Zinov'ev, A. A. Fusibility diagrams in the systems $LiClO_4–Ca(ClO_4)_2$ and $NaClO_4–Ca(ClO_4)_2$, (1) 21*f*.
Krochmann, J. Transmission of window glass, (1) 5*h*.
Kroeger, C., and Campana-Ros, J. Velocity of the reactions in glass melting (VIII) reactions of alumina, (4) 96*a*.
Kroeger, C., and Goldmann, N. Carbon dioxide solubility in glasses, (9) 232*j*.
Kroeger, C., and Lummerzheim, D. Radiological determination of carbon dioxide in soda-lime-silica glasses in different stages of melting, (1) 5*f*.
Kroeger, C., and Marwan, F. Velocity of the reactions in glass melting (VI) effect of additions on reaction rate in soda-limestone-quartz basic batch; (VII) dependence of batch melting time on the nature and amount of products formed by batch reactions, (4) 96*a*.
Kroeger, C., and Soerstroem, L. Vapor pressure of silicate glasses and their components, (4) 95*i*.
Kroeger, C., and Stratmann, J. Vapor pressure and decomposition pressure of several alkali compounds in the glass melt, (3) 62*b*.
Kroeger, F. A. Effect of doubly ionizable vacancy acceptors on the conductivity of donor doped semiconducting compounds with special reference to CdTe and ZnTe, (11) 316*a*. Electronic conductivity of calcia-stabilized zirconia, (5) 128*c*.
Kroenert, W. See Schwiete, H. E.
Kroenert, W., and Schwiete, H. E. Investigations of the systems $MgO–SiO_2$ and $MgO–Al_2O_3–SiO_2$, (11) 318*c*.
Kroenke, W. J. Mechanical test for anisotropy—failure of aluminoborosilicate glass fibers under combined loadings of tension and torsion, (10) 265*g*.
Krogius, E. A. See Botvinkin, O. K.; Gorokhovskii, V. A.
Krohn, H. W. See Watts, C. H.
Kroichuk, L. A. See Budnikov, P. P.
Krokhin, V. A. See Morozov, I. S.
Kroko, L. J. See Chang, H. C.
Kronsbein, J., Buteau, L. J., Jr., and DeHoff, R. T. Measurement of topological parameters for description of two-phase structures with special reference to sintering, (5) 138*i*.
Kroone, B. Effect of repeated wetting and drying on carbonation and shrinkage of cement mortars, (8) 206*g*.
Kropp, D. E., and Agron, A. M. Apparatus for attaching parts to glass coated apparatus, P (9) 232*e*.
Kroyer, K. K. K. Process of making a crystallizable glass material, P (10) 263*a*.
Krueger, R. See Langauer, T.
Krueppel, A. See Bischoff, F.
Kruglitskii, N. N. See Ovcharenko, F. D.
Kruglitskii, N. N., Martsin, I. I., Ovcharenko, F. D., and Nichiporenko, S. P. Formation of coagulation structures in dispersions of clay minerals after autoclaving, (3) 81*i*.
Kruglitskii, N. N., Ovcharenko, F. D., Nichiporenko, S. P., and Vagner, G. R. Study of the salt resistance of dispersions of clay minerals, (10) 290*i*.
Kruishoop, J. C. W. Method of manufacturing compact bodies of manganic oxide and/or iron oxide and bodies thus obtained, P (8) 221*c*.
Kruithof, A. M. See Cornelissen, J.
Krupnick, A. C. See Zerlant, G. A.
Kruse, O. Material feeding device for tableting machines and the like, P (4) 107*a*.
Krylov, E. I., and Sanatina, V. N. Orthoniobates of samarium and europium, (11) 318*c*.
Kryuchenkov, D. A. Use of aluminous alkaline materials for bottle production, (9) 235*f*.
Kryukova, O. H. See Mikheeva, V. I.
Ku, Cho-ju. Measurement of the thermal conductivity of glass in the temperature range −150° to 50°C, (8) 210*c*.
Ku, Gen-sheng. See Chang, Sheng-yuan.
Kubicz, A. Effect of the firing atmosphere on the physical properties of chromite-magnesite refractories, (7) 186*f*.
Kubli, S. A. See Sleptsov, V. M.
Kubo, I. Crystal growth of zinc oxide by chemical reaction of zinc fluoride with air, (10) 284*a*.
Kubo, K. Radiation effects in LiF crystals, (10) 290*d*. Radiation induced optical absorption in crystalline quartz and fused silica, (4) 112*i*.
Kubo, K., and Katano, Y. Dislocation network in neutron-irradiated LiF crystal, (4) 110*j*.
Kubo, T. See Kitamura, S.
Kubo, T., Kato, M., Nakazato, K., and Fujita, K. Solid state reaction in the system $TiO_2–CoO$, (9) 255*j*.
Kubodera, H. Apparatus for mixing, agitating, abrading, or crushing various materials, P (2) 47*b*.
Kubota, B., and Hirota, E. Electrical resistivity of ferromagnetic chromium dioxide, (4) 111*c*.
Kubota, B., Nishikawa, T., Chiba, H., and Sugimura, M. Method for preparing CrO_2 of rutile type crystalline structure, P (6) 164*h*.
Kubota, B., Nishikawa, T., and Yanase, A. Magnetic properties of chromium oxide modified by vanadium oxide, (10) 288*a*.
Kucharskaya, E. V. See Fedoseev, A. D.
Kuczynski, G. C. See Readey, D. W.
Kudelka, D. Wall covering material made from common brick clays, (2) 36*a*.
Kudzmauskas, S. See Audzijonis, A.
Kuebler, R. A. See Pate, A. F.
Kuehl, B. Multi-work-function cathode, P (6) 160*h*.
Kuehne, K. Chemistry, physics, and technology of the silicates—present and future, (2) 54*g*. Function of mobile ions in glass, (7) 180*j*. Systematology of silicate glasses, (4) 95*c*.
Kuehnel, R. Determinations of the sedimentary environment of clays by measuring the electrical conductivity of water extracts, B (2) 56*h*.

Kuehner, J. A. See Ollerhead, R. W.
Kuendig, W. See Constabaris, G.
Kuenning, W. H. Improved method of testing tensile bond strength of masonry mortars, (11) 300*b*.
Kuether, F. W. High temperature sensors, P (3) 77*a*. Temperature measuring apparatus, P (6) 163*e*.
Kuhn, W. E. Method of making submicron size nitrides and carbides, P (5) 126*j*.
Kukal, Z. Geochemical evolution of clayey and carbonate sediments of early Paleozoic of central Bohemia, (11) 317*d*.
Kukarkin, A. I. Improving burner design for glass tank furnaces, (9) 233*f*.
Kukharskaya, E. V. See Skorik, Yu. I.
Kukimoto, H. See Hioki, R.
Kukolev, G. V., and Lisovaya, E. D. Intensifying the vitrification of earthenware bodies with combined additives, (6) 156*g*.
Kukovsky, E. G. See Ovcharenko, F. D.
Kuksin, I. I. See Ginzburg, D. B.
Kukusheva, M. See Bachvarov, S.
Kukusheva, M., and Simeonov, K. New compositions for white earthenware tile, (6) 156*i*.
Kulas, H. F. Blasting abrasives, (4) 91*b*.
Kul'chitskii, L. I. Studies on the crystal chemistry of the surface of clay minerals and the clay–water–ions system by spectrophotometric analysis, B (2) 56*i*.
Kulcsar, F. Ferroelectric ceramic compositions, P (10) 278*g*.
Kulig, C. W. See Fuller, R. A.
Kulik, A. I. See Levintovich, E. V.
Kulikova, E. N., Ryabov, V. A., and Rogozhin, Yu. V. Application of an organosilicon coating by the aerosol method on sheet glass during drawing, (6) 146*i*.
Kulikovskii, B. N., Mikhailov, Yu. N., and Kuznetsov, V. G. Roentgenographic investigation of products of oxidation of tellurium, (10) 290*j*.
Kulkarni, A. K., and Moorthy, V. K. Sintering of thoria powders (III) studies on hot pressing of thoria powders, (5) 125*d*.
Kulling, A. See Tillmann, P.
Kulyamina, L. L., and Frolova, E. G. Glass coatings on the inside of steel pipes, (1) 3*e*.
Kulygin, I. P. See Budnikov, P. P.
Kumagai, H. Y., Thompson, J. M., and Krauss, G. Properties and structure of thin silicon films sputtered on fused quartz substrates, (7) 192*c*.
Kumai, H., Manabe, T., Hirayama, H., and Takahashi, Y. Fused cast basic brick used in the electric furnace walls, (7) 186*g*.
Kumai, K. See Goss, N. P.
Kumar, S. See Gupta, S. D.
Kumar, S., and Nag, B. B. Electrical properties of crystallized glasses in the system MgO–Al_2O_3–SiO_2–TiO_2, (2) 31*j*.
Kume, S., and Koizumi, M. Synthetic pollucites in the system $Cs_2O \cdot Al_2O_3 \cdot 4SiO_2$–$Cs_2O \cdot Fe_2O_3 \cdot 4SiO_2$–$H_2O$—their phase relationship and physical properties, (3) 86*b*.
Kumins, C. A. See Arnheim, W. M.
Kummer, D. L., and Hochberg, M. S. Heat insulating and ablative structure and method of making same, P (1) 11*f*.
Kun, Sup Hyun. See Hyun, Kun Sup.
Kuna, L. See Havel, V.
Kundra, M. C. See Murthy, H. P. S.
Kung, Chia-shen. See Hwang, Chi-hsing.
Kunin, N. F., and Yurchenko, B. D. Regularities in the compacting of powders of different materials, (1) 9*h*.
Kunitomi, N., Hamaguchi, Y., and Anzai, S. Neutron diffraction study on manganese telluride, B (2) 55*c*.
Kunkle, G. E., and Harrell, W. C. Glass planing process, P (7) 183*e*.
Kunth, P. O. See Hinz, W.
Kuntz, R. S. Crusher jaw construction, P (6) 164*f*.
Kuntz, U. E. Process for producing silicon nitride and a product thereof, P (4) 101*f*.
Kunz, W. Production of a new dehydrated and highly basic lead carbonate, P (4) 109*h*.
Kuo, Chu-kun. See Han, Wen-long.
Kuo, Chu-kun, and Yen, Tung-sheng. Studies on the systems rare earth sesquioxides-beryllium oxide (II) activity of beryllium oxide and the structural model of BeO-rich melts (0 to 40% (mole) $LaO_{1.5}$) in the system La_2O_3–BeO, (5) 141*h*.
Kupetz, G. New pressed glass developments—a work report, (4) 94*b*.
Kupfer, V. V. Sonic-chemical method in processing raw materials, (9) 234*e*.
Kupka, F. X-ray diffraction investigation of structural changes of quartz during treatment, (10) 291*f*.
Kuprzog, E. See Koltermann, M.
Kure, F. Fineness of grinding, (3) 71*e*.
Kurick, J. F. See Davis, C. W., Jr.
Kurihara, K. See Ichinose, N.
Kurka, G. See Gayet, B.
Kurkjian, C. R., and Krause, J. T. Acoustic spectra of Na_2O–GeO_2 glasses, (4) 92*a*. Effect of OH content on the acoustic spectra of B_2O_3 glass, (4) 93*b*.
Kuroda, Y. See Yamada, H.
Kuros, T., and Karp, M. White and colored engobes for facing tile, (3) 71*g*.
Kurti, I. See Galos, M.
Kurtz, B. E. See Hartford, W. H.
Kurtz, P. See Weiss, D.
Kurvits, O. A. See Hanson, N. W.
Kurz, E., and Reinecke, H. Process for separating solids from suspensions, P (6) 161*f*.
Kusakawa, I. See Kameyama, A.
Kushakovskii, V. I. See Budnikov, P. P.
Kushida, T. See Milberg, M. E.
Kutateladze, K. S., and Zedginidze, E. N. Nitriding of kaolin, (6) 153*g*.
Kutsev, V. S., Smagina, E. I., and Morzheedova, R. N. B-form of the oxide Sm_2O_3, (10) 283*j*.
Kutzendorfer, J. Calculation of the activation energy of solid state reactions of polydisperse mixtures, (10) 283*i*. See Hanykyr, V.
Kutzer, L. G. Joining ceramics and glass to metals, (2) 40*i*.
Kuwabara, S. See Horibe, T.
Kuwahara, H. Method of testing the quality of materials for stopper heads, (9) 238*d*.
Kuwayama, S. Transparent crystalline glass, P (6) 151*a*.
Kuzmick, J. N., and Littlefield, J. B. Molded composition brake shoe comprising organic bond, hard mineral filler, and cryolite, P (4) 101*a*.
Kuz'min, E. A., and Belov, N. V. Crystalline structure of the simplest silicates of La and Sm, (7) 198*e*.
Kuz'mina, I. P., and Antonova, V. F. Crystallization of zincite under hydrothermal conditions, B (11) 320*c*.
Kuz'mina, I. P., and Litvin, B. N. Possibility of production of crystals of montroydite (HgO) under hydrothermal conditions, B (11) 320*c*.
Kuznetsov, A. K. See Fan, Fu-Kan.
Kuznetsov, S. I., Derevyankin, V. A., and Shklyar, R. Sh. Problem of "trisodium hydroaluminate," (5) 140*d*.
Kuznetsov, V. A. Zinc sulfide crystals grown from a melt, B (11) 320*c*.
Kuznetsov, V. G. See Kulikovskii, B. N.
Kuznetsov, V. G., and Palkina, K. K. Phase diagrams and structure of melts in the systems Bi_2Se_3–Sb_2Te_3 and Bi_2Te_3–Sb_2Se_3, (11) 318*c*.
Kuznetsov, V. G., Palkina, K. K., and Dmitriev, A. V. Electrical conductivity and thermal emf of solid solutions of the systems Bi_2Se_3–Sb_2Te_3 and Bi_2Te_3–Sb_2Se_3, (11) 316*j*.
Kuznetsova, K. F. See Tumanov, V. I.
Kuznetsova, L. I. See Gavrilova, I. V.
Kvetinskas, B. Crystalline zeolite U, P (7) 196*g*.
Kwei, T. K. See Arnheim, W. M.
Kyoden, H. See Mori, S.
Kyser, D. F. See Mann, J. E.

Laar, J. van, and Scheer, J. J. Fermi level stabilization at semiconductor surfaces, (10) 286*f*.
Laat, C. D. J. C. de. See Bril, A.
La Bate, M. D. Consumable hot top with inserts of exothermic material, P (1) 11*a*. Consumable hot top with tie-down members, P (1) 11*b*.
La Baume, P. Shapes of Roman glasses and ceramics—a comparative study, (10) 261*j*.
Labino, D. Egyptian sand-core technique—a new interpretation, (9) 229*j*. Gas mixing device, P (6) 163*j*.
LaBonde, E. G. See Hime, W. G.
Laboratory for Electronics, Inc. Frequency selective coupling device having ferrite elements biased to different resonant frequencies, P (11) 306*f*.
Labosky, R. See Murata, Y.
Lacasse, A. R. Method for forming and winding glass strands, P (11) 298*j*.
Lach, V. Ceramics as protection against ionizing radiation, (11) 300*i*.
La Chapelle, T. J. See Crishal, J. M.
Lachenmayr, H. See Oel, H. J.
Lachnik, E. See Pawlowska, H.
Lack-Albrecht G.m.b.H., and Leipold, F. X. Process for decorating articles of porcelain, earthenware, majolica, etc., P (9) 242*a*.
Lacmann, R. Crystallization on substrates—work of formation of crystal nuclei, (3) 80*i*.
Lacombe, P. Polishing and etching methods and their application to optical metallography, B (6) 173*g*.
Lacroix, R., and Blavat, H. Metallic appliances and components subjected to contact with molten materials at high temperature, P (5) 132*a*.
Lacy, E. D. Statistical model of polymerization/depolymerization relations in silicate melts and glasses, (2) 32*i*;—correction, (5) 121*f*.
Ladd, R. Brick-lined tanks, (6) 151*k*.
Lade, R. W. See Mattauch, R. J.
Laet, L. de. See Keyser, W. L. de.
Lafferty, J. M. Electron emitter utilizing nitride emissive material, P (11) 306*a*.
Lafontaine, I. See Bairiat, H.
Lagally, P., and Argyle, P. Steam cure of siloxane-coated glass containers, (10) 266*h*.
Lagos, C. C., and Strock, L. W. Method of preparing electroluminescent devices, P (3) 73*g*.
La Grouw, C. M. See Baas, G.
Lahiri, D. See Paul, A.
Laine, L. H. See Binkert, C. F.
Lainer, B. D. See Chistyakov, Yu. D.
Laird, H. R. See Hyatt, E. P.
Laird, J. S., and Stephens, A. Brick stacking device, P (6) 151*d*.
Lajarte, S. D. de. Glass compositions, P (2) 33*j*, P (8) 212*h*. Process for the manufacture of flat glass, P (2) 34*f*. See Peyches, I.
Lajzerowicz, J. Study on the infrared absorption of lead potassium pyrosilicate, lead potassium pyrogermanate, and their solid solutions, (8) 227*e*.
Lakatos, T., and Simmingskold, B. Effect of glass composition on corrosion of pot clays, (8) 209*e*.
Lake, D. E. Transistor electrode connection, P (8) 222*b*.
Lakh, V. I. See Gladyshevskii, E. I.
Lakin, J. R. Progress in refractories for steelmaking, (5) 125*j*.
Lakin, J. R., and Haglington, J. B. Research on aluminosilicate refractories, (7) 187*e*.
Lal, K. See Chopra, S. K.
Lally, R. E., and Ihde, F. J., Jr. Process of preparing finely divided silicas of varied properties, P (10) 283*f*.
Lamb, A. Glass beads from the Malay Peninsula, (9) 229*j*. Note on glass fragments from Pengkalan Bujang, Malaya, (5) 118*e*.
Lamb, H. W. Tile press mechanism, P (3) 72*a*.
Lambert, J. D. B. See Bradbury, B. T.
Lambert, R. E. Method of and apparatus for making thermoplastic sheet material, P (2) 33*i*. See Touvay, R.
Lampert, M. A. See Steele, M. C.
Lamprey, H. See Culbertson, J. B.
Lamprey, H., Culbertson, J. B., and Ripley, R. L. Process for producing ultrafine powders of refractory materials, P (8) 218*g*.
Lampson, M. L. See Hastings, W. F.
Landa, L. M. See Brekhovskikh, S. M.
Lander, J. J., and Morrison, J. Low-energy electron diffraction study of graphite, (6) 168*j*.
Lander, J. J., and Rhyne, J. W., Jr. Silver oxide palladium electrode, P (1) 15*a*.
Landgraf, R. C. Multiaperture ferrite core, P (1) 15*a*.
Landgren, R., Hanson, J. A., and Pfeifer, D. W. Improved procedure for proportioning mixes of structural lightweight concrete, (3) 58*j*.
Landis, G. W. Why radiant tube furnaces for water tanks, (6) 146*d*.
Landrigen, A. B. See Blocher, J. M., Jr.
Landsman, D. A. See Fletcher, J. M.; Hyde, K. R.
Landsperasky, H., and Imris, P. Determination of mass of sediment by radioactive radiation, (11) 309*g*.
Lang, A. R. Mapping Dauphine and Brazil twins in quartz by X-ray topography, (10) 288*b*. See Lawn, B. R.; Schlossin, H. H.; Takagi, M.
Lang, F. M., Magnier, P., and May, S. Study of the oxidation of carbon, (4) 113*i*.
Lang, G. W. Tile machine [conveyor], P (9) 242*d*.
Lang, W. B., Warren, W. C., Thompson, R. M., and Overstreet, E. F. Bauxite and kaolin deposits of the Irwinton district, Georgia, (3) 77*j*.
Langauer, T. See Schwiete, H. E.
Langauer, T., Krueger, R., and Schwiete, H. E. Effect and behavior of silicones on glass surfaces (II), (7) 179*g*.
Langdon, J. L. See Harding, W. E.
Lange, J. Complexometric glass analysis, (10) 264*c*.
Lange, K. Automation in the heavy clay industry, (6) 151*c*.
Lange, W. H. See Mayer, W. J.
Lange, W. J. See Singleton, J. H.
Langen, P. Agitator for granular materials and the like, P (11) 308*j*.
Langer, G. Acoustic particle counter—preliminary results, (8) 222*h*.
Langereis, C. See Eckerlin, P.
Langley, L. W. Solid-state phenomena in control, (7) 192*g*.
Langlois, R. E., and Stream, R. M. Strand delivery apparatus, P (10) 270*b*.
Langmuir, D. Stability of carbonates in the system MgO–CO_2–H_2O, (3) 85*j*.
Langmyhr, F. J., and Kringstad, K. Investigation of the composition of the precipitates formed by the decomposition of silicate rocks in 38 to 40% hydrofluoric acid, (7) 200*d*.
Langseth, A. O., and Lodge, J. R. Method of making stain-resistant roofing granules and product thereof, P (1) 13*b*.
Lanzdorf, J. H. See Reed, R. J.
Lapham, D. M. See O'Neill, B. J., Jr.
Lapin, V. V. See Tsvetkov, A. I.
Lapitskii, A. V. See Berdonosov, S. S.
Lapitskii, Yu. A. See Arabei, B. G.
Laporte Titanium, Ltd. Manufacture of oxides, P (5) 133*e*. Manufacture of titanium dioxide, P (1) 18*g*. Process of classifying calcined conditioned titanium dioxide pigment slurries, P (4) 109*d*. Titanium dioxide pigments, P (8) 225*j*.
Lappie, W. C. Recovery of phosphorus values and $[CaO \cdot SiO_2]$ cement clinker from a phosphatic ore, P (5) 119*e*.
Larach, S., and Yocom, P. N. Method for preparing rare earth activated zinc sulfide phosphors and products thereof, P (11) 306*j*.
Larin, G. N. Electrodes for electric arc welding and hard-surfacing of gray and high-strength cast irons, P (8) 208*b*.
Larsen, L. L. Orbital-spin crystal pulling, P (4) 106*a*.
Larsson, K. Device for filtering air in spray-painting booths, P (2) 43*e*.
Lasher, G. J. See Dill, F. H.
Lassman, B. Pressure molding of dry material, P (1) 16*b*.
Lassman, Benjamin, & Son. See Benjamin Lassman & Son.
Lathrop, J. W. See Kilby, J. S.
Latsh, V. V., Minaev, N. G., Somin, B. Kh., and Stepina, N. E. Dissolving the excess of ferric oxide in NiZn ferrite, (4) 110*a*.
Latvys, V. See Mikailiene, E.
Lauder, W. B., and Copson, R. L. Production of ultrafine alpha alumina and such alpha alumina, P (10) 283*b*.
Laudise, R. A. See Kolb, E. D.
Laudise, R. A., Ballman, A. A., and King, J. C. Impurity content of synthetic quartz and its effect upon mechanical *Q*, (6) 168*a*.
Laudise, R. A., Kolb, E. D., and DeNeufville, J. P. Hydrothermal solubility and growth of sphalerite, (3) 82*c*.

Lauer, G. G., and Bonstedt, K. P. Factors influencing the performance of pitch binders in the baking of small carbon electrodes, (4) 111*i*.
Laurent, B. See Peyches, I.
Laurila, E. A. High-intensity magnetic separator, P (7) 190*j*.
Laurinavicius, A. See Gaska, I.
Laves, F. See Bambauer, H. U.; Hafner, S.
Lavin, E. See Mont, G. E.
Lavin, E., and Mont, G. E. Laminated safety glass, P (11) 298*c*.
Lavin, E., Mont, G. E., and Price, A. F. Laminated safety glass, P (11) 298*c*.
La Vine, P. F. Impregnation and coating with split-offs of vermiculite and products thereof, P (11) 296*d*.
Lavino, E. J., & Co. Apparatus for manufacturing a refractory brick, P (9) 239*h*. Apparatus for plating bricks, P (9) 239*i*. Refractory brick and furnace construction, P (8) 218*c*. Refractory bricks, P (6) 155*d*.
Lavrenko, V. A. Protective action of an aluminum oxide coating on nickel, (1) 24*j*.
Lavrinenko, I. A. See Naidich, Yu. V.
Law, H. B. Art of making electron-optical reticles, P (4) 104*j*. Color cathode ray tube with index stripes on ultraviolet-emitting phosphor layer, P (11) 305*d*.
Lawn, B. R. See Forwood, C. T.
Lawn, B. R., Kamiya, Y., and Lang, A. R. X-ray topographic study of planar growth defects in a natural diamond, (2) 54*d*.
Lawson, D. C. See Chelini, J. M.
Lawther, W. D. Method for preparing shell molding compositions, P (9) 240*f*.
Lax, B. See Zeiger, H. J.
Lax, L. See Baumann, J.
Lazar, J. Practical applications of granulometric distribution curves, (6) 169*g*. Two new methods for determining rock strength, (2) 45*f*.
Lazarev, A. N., Tenisheva, T. F., Bondar, I. A., and Toropov, N. A. Infrared spectra of lanthanide oxyorthosilicates, (5) 137*c*.
Lazzari, S. See Lotto, B.
Leach, E. M. See Chisholm, C. C.
Leach, G. B. Computer data processing system calculation of glaze formulas, (1) 12*h*.
Leake, J. A. See Cooper, M.
Leaman, H. E. See Smock, G. E.; Stalego, C. J.
Lear Siegler, Inc. Thin film electron emissive electrode, P (10) 279*g*.
Leary, D. E. See Brown, A. W.
Leary, J. A., Thomas, R. L., Ogard, A. E., and Wonn, G. C. Thermal conductivity and electrical resistivity of UC, (U,Pu)C, and PuC, B (6) 172*j*.
Leask, M. J. M. See Ball, M.
Leatham, E. Production of refractory grain, P (4) 101*i*.
Leatham, E., and Pack, A. H. Production of dead-burned magnesia in a shaft kiln, P (3) 70*g*.
Leatham, E., Pack, A. H., and Weaver, E. P. Method of recovery of magnesian values, P (11) 302*i*.
Leaycraft, E. C. See Di Marco, H. A.
Lebedev, A. A. Durability of silicon carbide in a complex stressed state, (10) 285*b*. Estimate of the strength of cermets in a complex stressed state, (1) 8*g*.
Lebedev, A. G. See Zhukovskii, V. M.
Lebedev, V. V. See Gumenyuk, V. S.
Le Clerc, P. Electroprotection of refractories, P (6) 146*c*. See Fournie, R.; Grosvalet, J.
Le Comte, P. Creep in rock salt, (1) 19*d*.
LeCraw, R. C. See Matthews, H.
LeCraw, R. C., Wood, D. L., Dillon, J. F., Jr., and Remeika, J. P. Optical transparency of yttrium iron garnet in the near infrared, (1) 23*g*.
Lecrivain, L. Study of the mechanical and thermal properties of refractories at elevated temperatures, (8) 223*j*, (11) 301*d*.
Lee, B. W. See Harper, H. F.
Lee, H. See Haber, N.
Lee, Hsi-shan. See Kan, Fu-hsi.
Lee, K., Muir, H., and Catalano, E. Magnetic and chemical properties of europium fluoride, (7) 200*i*.
Lee, R. W. Diffusion of hydrogen in natural and synthetic fused quartz, (4) 110*h*.
Lee, R. W., and Fry, D. L. Comparative study of the diffusion of hydrogen in glass, (5) 120*e*.
Lee, W. L. Determination of proportional limit by direct readout, (3) 75*i*.
Leers, K. J. See Hennicke, H. W.
Leers, K. J., and Memmert, S. Automatic apparatus for the determination of the thermal conductivity of a plate of building and insulating materials, (1) 7*e*.
Lees, S., Batteau, D. W., and Kleinschmidt, R. S. Method of determining the volume of particles in a mixture, P (5) 132*b*.
Leesona Corp. Method of improving lithiated nickel oxide fuel cell electrodes, P (4) 105*h*.
Leete, C. R. J. See King, W. G.
Leeuw, G. de. Gas burner, P (11) 311*f*.
Lefever, R. A. Methods and apparatus for producing crystalline materials, P (3) 75*a*.
Lefever, R. A., Wickersheim, K. A., and Chase, A. B. Further investigation of factors influencing domain configurations in yttrium iron garnet, (5) 136*j*.
Lefevre, M. Apparatus for tracing and breaking glass sheets, P (2) 33*b*.
Leflet, H. A., Jr. Apparatus for bending and annealing glass sheets, P (8) 211*d*. Method and apparatus for bending glass sheets, P (4) 97*d*. See Carson, F. J.
Leflet, H. A., Jr., and Carson, F. J. Method of bending glass sheets, P (6) 150*j*.
Le Gargasson, G. See Perilhou, J. R.
Leger, L., and Bray, J. Experimental study of the controlled crystallization of alkaline-earth silicoaluminate glasses, (11) 296*i*.
Le Gras, J. Y. J. Process and apparatus for dividing glass, P (9) 236*i*.
Lehfeld, K. Method of fabricating hollow glass blocks with built-in exhaust ducts, P (10) 268*i*.
Lehman, H. S., Pliskin, W. A., and Ruggles, R. L., Jr. Silicon oxide film formation, P (6) 161*a*.
Lehman, K. A. *L*-band properties of single-crystal 600-G calcium vanadium bismuth iron garnet, (9) 251*a*.
Lehmann, H. See Hennicke, H. W.
Lehmann, H., and Holland, H. Transformations of gypsum and its dehydration products, (9) 257*h*.
Lehmann, H., and Koltermann, M. Investigations with the Enslin apparatus, (9) 245*c*.
Lehmann, H., and Lohrmann, H. Crystallization of highly acidic Thomas pig-iron slags, (8) 206*g*.
Lehmann, H., and Maelzig, G. Behavior of mortars containing cements of various compositions at high temperature, (3) 65*g*.
Lehmann, H., and Roesky, W. Development of the strength and hydration of portland and slag cements at 20°, 5°, and 1°C, (1) 2*f*.
Lehmann, H. A., and Hesselbarth, H. Lithium aluminates (II) the compound Li_5AlO_4, (3) 83*a*.
Lehmann, H. A., Schadow, H., and Papenfuss, H. J. Chemistry and constitution of borates (VI) magnesium lithium borates $MgLiBO_3$, $MgLi_2B_2O_5$, (3) 80*c*.
Lehmann, H. A., and Woeckel, H. Chemistry and constitution of borates (V) isomorphism between carbonates and borates—the systems Li_2CO_3–Li_3BO_3 and Na_2CO_3–$CaNaBO_3$, (3) 80*b*.
Lehmann, L. B. Method of strengthening glass articles, P (2) 34*a*.
Lehmann, W. Method for processing electroluminescent phosphor, P (7) 193*h*.
Lehnhaeuser, W. Boron phosphate in glazes, (10) 275*e*. Dilatometer tests with ceramics, (6) 162*b*.
Lehr, G. J. See Badger, A. E.
Leipold, F. X. See Lack-Albrecht G.m.b.H.
Leipold, M. H. Impurity distribution in MgO, (10) 286*h*.
Leipold, M. H., and Nielsen, T. H. Hot-pressed high-purity polycrystalline MgO, (4) 99*d*.
Leipziger, F. D. See Kestigian, M.
Leisenberg, M. Control board for tunnel kilns, P (8) 224*f*. Oil firing in the ceramic industry, (6) 163*j*.
Leister, K. Continuously operating machine for mixing and/or reacting materials, P (11) 308*g*.
Leitner, N. See Kohlmuller, R.
Leitten, C. F., Jr. See Heestand, R. L.
Leitz, Ernst, G.m.b.H. See Ernst Leitz G.m.b.H.
Leja, J. Froth flotation, (7) 194*f*.
Lemeshonok, V. D. See Avdasev, V. I.
Lempa, R. F. Industrial burner, P (2) 46*e*.
Lenczner, D. Strength and elastic properties of the 9-in. brickwork cube, (10) 270*c*.
Lenel, F. V. Mechanism of material transport in sintering, (11) 318*a*.
Lengyel, B., and Csakvari, B. Alkali error of the glass electrode (II) effect of glass composition on the alkali error, (8) 208*g*.
Lengyel, B., Csakvari, B., and Boksay, Z. Alkali error of the glass electrode (I) interpretation of the alkali error, (8) 208*g*.
Lengyel, B., Csakvari, B., and Toperczer, J. Alkali error of the glass electrode (III) new contributions to the interpretation, (8) 208*g*.
Lenihan, W. S., Jr., and Reidl, R. W. Method for preparing boron nitride, P (6) 155*a*.
Lenihan, W. S., Jr., and Roche, M. A., Jr. Aluminum vaporizer, P (2) 37*a*.
Lennon, J. W. Nomograph for converting average intercept size to average grain size, (8) 226*j*.
Lenoir, L. Glass furnace construction with an eduction tunnel which is provided with a vault, P (8) 212*a*.
Lentz, E. C. Ceramic coated exhaust systems, (9) 231*g*.
Lenzo, P. V. See Spencer, E. G.
Leo, D. C., Lepore, D. A., and Nielsen, J. W. Dependence of the magnetic properties of $Y_3Fe_{5-x}Ga_xO_{12}$ and $Y_3Fe_{5-x}Al_xO_{12}$ on thermal history, (11) 315*a*.
Leonard, A. See Calvet, R.
Leonard, J. E., and Arthur, E. P. Encapsulated transducer, P (1) 6*i*.
Leonard, J. T., and Hazlett, R. N. Rheology of thixotropic suspensions of magnesium montmorillonite, (7) 190*f*.
Leonard, L. A. See Carr, K.
Leonard, L. B. Method of making glass electrode, P (1) 7*b*.
Leonov, A. I. Valency of cerium in synthetic and natural cerium aluminates and silicates (I) compounds of the perovskite group, (5) 142*d*.
Leont'ev, L. I., Bogoslovskii, V. N., and Chufarov, G. I. Question as to the existence of solid solution between mono- and dicalcium ferrites, (1) 13*h*.
Leont'eva, I. A. See Plyshevskii, Yu. S.
Lepkova, D. See Gerasimov, E.
Lepore, D. A. See Leo, D. C.
Leppelmeier, E. T. See Chernin, M. A.
Lepselter, M. P. Selective removal of material using cathodic sputtering, P (11) 307*d*. Semiconductor contact, P (11) 307*e*. See Marinaccio, L. P.
Lerner, M. W. See Eberle, A. R.
LeRoux, H. Strength of fused quartz in water vapor, (2) 51*f*.
Leroux, J., and Mahmud, M. X-ray quantitative analysis by an emission-transmission method, (3) 76*i*.
Leroy, P., and Simon, R. Method of casting and firing a layered ceramic article, P (11) 302*h*.
Leshchinskaya, Z. L. See Selivanova, N. M.
Leshchinskaya, Z. L., Selivanova, N. M., and Strel'tsov, I. S. Heat of formation of barium selenite, (9) 250*f*.
Lesin, A. D., and Lokshina, R. V. Characteristics of vibratory mills, (4) 106*i*.
Lesser, R. C. See Fenstermacher, J. E.
Lessoff, H., and Fortin, E. G. Square loop molybdenum modified ferrites, P (3) 74*a*.
Lester, G. R. Process for producing anhydrous alumina, P (3) 79*d*.
Letort, M. Y. Stress resistance of refractory materials at high temperatures, (2) 37*b*.
Leupolz, V. Advantages of hot processing, (2) 35*b*.
Levand, V. A., Jr. Electric lamp manufacture, P (1) 6*g*.
Levcheva, K., Isakova, M., and Bachvarov, S. Production of talc-based heat-resistant ceramic ware, (6) 156*g*.
Levecque, M., and Charpentier, M. Burner for producing gaseous mixtures in centrifugal fiber attenuating apparatus, P (8) 212*b*. Method of and apparatus for producing fibers from thermoplastic material, P (2) 34*b*. Process and apparatus for production of fibers from thermoplastic material, particularly glass fibers, P (8) 213*f*.
Levecque, M., and Mabru, M. Apparatus for the manufacture of fibers, particularly glass fibers, P (8) 211*g*.
Leventhal, M., and Bray, P. J. Nuclear magnetic resonance investigations of compounds and glasses in the systems PbO–B_2O_3 and PbO–SiO_2, (7) 201*f*.
Levetan, R. V. Electroluminescent cells with phosphor-conductor adhesion and manufacture thereof, P (8) 220*j*. Electroluminescent lamp and manufacture thereof, P (6) 159*e*.
Levey, R. P., Jr. Alumina-cobalt-gold composition, P (4) 109*b*. Metal shapes having increased compressive strengths, P (9) 244*h*. See Febbo, P. P.
Levialdi, A. See Asti, G.
Levi-Lamond, P. R. Method of making semiconductor devices with plated area, P (8) 221*a*.
Levin, E. M. Liquid immiscibility in the rare earth oxide-boric oxide systems, (10) 287*f*. Phase equilibria in the system niobium pentoxide–boric acid, (8) 226*b*. Phase equilibria in the system niobium pentoxide–germanium dioxide, (8) 226*c*.
Levin, M. Plastering composition, P (4) 91*a*.
Levin, P. A. Determination of gold in ceramic colors, (6) 161*j*.
Levine, A. K. See Ho, L.
Levine, A. K., and Natansohn, S. Growth of sheet crystals of fluorphlogopite, (4) 103*j*.
Levine, A. K., and Palilla, F. C. YVO_4:Eu, a new highly efficient phosphor for color television, (8) 220*i*.
Levine, B. H., and Mair, L. Effects of firing temperature on the properties of steels used for porcelain enameling, (9) 231*h*.
Levine, G. A. Pneumatic sensing device with digital readout, P (6) 150*g*.
Levine, S. What you should know about refractories, (11) 301*f*.
Levinskii, Yu. V. See Arabei, B. G.
Levinson, L. S. High temperature heat content of uranium carbides, B (6) 172*j*.
Levinson, S., Douglas, G., and Johnson, L. R. Hydrothermal solubility of Al_2O_3 in $Na_2B_4O_7$ solution, (3) 82*b*.
Levinstein, H. J. See Nassau, K.
Levintovich, E. V., Shakhtin, D. M., Kulik, A. I., Logachev, M. S., Miroshnichenko, V. Ya., and Slavgorodskaya, E. Ya. Determining bulk density and density variations in glass tank blocks by gamma-radiation absorption, (6) 152*d*.
Levitas, E. G. See Zegzhda, D. P.
Levitin, R. Z. See Yevtushchenko, L. A.
Levitt, A. P. Recent advances in alumina whisker technology, (4) 99*c*. See Grenis, A. F.
Levitz, N. M. See Knudsen, I. E.
Levstik, A. See Blinc, R.
Lewchuk, R. R. See Moser, F.
Lewis, A. D. See Deeren, T. J.
Lewis, D., and Lindley, M. W. Enhanced activity and the characterization of ball-milled alumina, (2) 50*a*.
Lewis, D. C. See Sadler, A. G.; Westwood, W. D.
Lewis, D. C., Westwood, W. D., and Sadler, A. G. Thin films of magnetic oxides, (6) 158*b*.
Lewis, E. D., and Braun, J. H. TiO_2 manufacture, P (1) 19*c*.
Lewis, H. D., and Goldman, A. Theorems for calculation of weight ratios to produce maximum packing density of powder mixtures, (7) 203*b*.
Lewis, H. R., and Surmeian, S. N. Prestressed ceramic transducer, P (4) 106*c*.
Lewis, J. A. See Lewis, J. H.
Lewis, J. G. Method of making shielding for high temperature furnace, P (5) 132*h*.
Lewis, J. H., and Lewis, J. A. Sandpaper cot, P (3) 57*g*.
Lewis, M. H. Electron microscope study of precipitation in MgO single crystals, (9) 249*i*.

Leybold-Anlagen Holding A. G. Method and apparatus to dry powdery substances under a vacuum using electrical gas discharges, P (6) 161*d*.

Leyman Corp. Method of making machinable high energy permanent magnets, P (7) 193*d*.

Li, Chi-fa. See Morozov, I. S.

Li, Chi-fa, and Morozov, I. S. Interaction of tin chloride with the chlorides of the rare-earth metals, iron, and sodium, (1) 22*e*. Thermal and tensimetric study of the systems formed by tin chloride with the chlorides of the alkali metals and ammonium, (9) 257*j*.

Li, Ching-heng. Rotating-needle method for determining some light indices of transparent minerals, (5) 131*h*.

Libbey-Owens-Ford Glass Co. Apparatus for bending and annealing glass sheets, P (8) 211*d*. Apparatus for bending glass sheets with an outrigger support, P (3) 62*e*. Apparatus for bending glass sheets or plates, P (3) 62*e*, P (4) 96*f*. Apparatus for bending and tempering glass sheets, P (5) 122*c*. Apparatus for cutting sheets of glass, P (6) 149*j*. Apparatus for delivering fusible material to a glass melting furnace, P (2) 32*i*. Apparatus for forming sheet glass, P (9) 235*c*. Apparatus for heating glass sheets, P (9) 235*d*. Apparatus for producing all-glass multiple sheet glazing units, P (11) 297*f*. Apparatus for producing sheet glass, P (6) 149*a*. Automobile windshield of laminated glass having embedded antenna wires, P (1) 6*e*. Bending mold for bending glass sheets with heat distributor, P (11) 297*f*. Bending mold with peripheral heat absorber, P (10) 267*f*. Compositions for sealing holes in glass, P (2) 33*e*. Glass furnace with muffle lip-tile, P (6) 150*a*. Glass polishing compositions of rare earth nitrates, P (6) 150*b*. Glass sheet bending apparatus with guide means, P (4) 96*j*. Glass sheet support roll, P (1) 6*d*. Glass stream heating in a continuous ribbon furnace, P (8) 212*b*. Inspection apparatus for transparent glass sheets, P (11) 298*b*. Laminated glazing unit, P (4) 97*a*. Marking apparatus, P (4) 97*c*. Method and apparatus for bending glass sheets, P (4) 97*d*. Method and apparatus for drawing sheet glass, P (4) 97*e*. Method and apparatus for melting glass, P (10) 268*j*. Method and apparatus for mixing glass batch materials, P (2) 34*a*, P (9) 236*f*. Method and apparatus for press bending and tempering glass sheets, P (10) 268*a*. Method and apparatus for producing all-glass multiple sheet glazing units, P (1) 6*j*. Method of bending glass sheets, P (6) 150*j*, P (9) 236*i*. Method of bending glass sheets with a compressional zone, P (4) 97*j*. Method for bending and tempering glass sheets, P (10) 268*e*. Method of controlling temperatures in sheet glass with heat absorptive material, P (9) 236*j*. Method of cutting sheets of glass, P (5) 123*d*. Method of laminating glass, P (4) 97*c*. Method of producing multiple sheet glazing units, P (3) 64*a*. Method of producing transparent electrically conducting glass sheets and article resulting therefrom, P (8) 213*b*. Method for surfacing glass, P (10) 269*c*. Polishing composition feed system, P (6) 150*h*. Pressing glass-plastic sandwiches, P (7) 184*e*. Process and apparatus for [spray] filming irregular shaped objects, P (7) 184*f*. Process for preventing scale in glass furnace, P (5) 124*d*. Process for treating glass furnace, P (6) 151*a*. Production of multiple glass sheet glazing units, P (9) 237*a*. Recovery of waste grinding materials, P (9) 237*b*. Sheet glass bending roll, P (11) 299*g*. Sheet handling apparatus, P (2) 34*h*. Sheet material handling device, P (8) 214*b*. Shipping crate for unitized packages [of glass sheets], P (4) 98*a*. Treatment of glass batch materials, P (3) 65*b*.

Liberty Glass Co. Apparatus for printing on articles such as bottles or the like, P (5) 122*g*.

Licentia-Patent-Verwaltungs-G.m.b.H. and Sendlinger Optische Glaswerke G.m.b.H. Beacon especially suited for airport runways (to be rolled over), P (10) 267*e*.

Lidina, E. D. See Korshunov, B. G.

Lidstrom, L. Bonding of amines to silicates, B (7) 204*e*.

Lieber, W. New rapid method of determining the hydraulic properties of granulated blast-furnace slags, (8) 207*e*. See Spohn, E.

Liebmann, B. See Himmelstein, P.

Liedberg, D. J., Smid, R. J., and Bergeron, C. G. Microseparation in lead borate glasses, (3) 61*e*

Liedberg, K. H., and Peterson, S. F. A. Electrostatic spray coating apparatus, P (1) 3*h*.

Liehn, W. Experience with a unique recuperative tank furnace, (4) 93*f*.

Lieneweg, F. Errors and effects in optical temperature measurement with total radiation, partial radiation, and color pyrometers, (6) 163*h*.

Lightner, L. F., and Nobles, E. L. Processing and testing variables affecting alkali resistance determinations, (6) 146*c*.

Lignes Telegraphiques et Telephoniques. Ferromagnetic materials and production methods, P (9) 243*e*. Magnetic material of high permittivity, P (8) 221*f*. Temperature compensated reciprocal ferrite phase shifter, P (11) 308*a*.

Ligon, E. R. Clay pipe take out device, P (4) 98*g*.

Lilly, D. K. See Hidy, G. M.

Lima de Faria, J. Condensed way of representing inorganic close-packed structures, (7) 197*j*. Systematic derivation of inorganic close-packed structures—AX and AX_2 compounds, sequence of equal layers, (7) 203*a*.

Limansky, I. Glass-metallizing technique, P (8) 212*a*.

Limes, R. W. Refractories for basic oxygen furnaces, (11) 301*b*.

Limes, R. W., and Fedock, M. P. Refractory composition, P (3) 70*i*.

Lin, Jih-tong. See Niu, Yen-nan.

Lin, T. H., and Ito, M. Theoretical plastic distortion of a polycrystalline aggregate under combined and reversed stresses, (1) 25*i*.

Lin, W., Steinfink, H., and Weiss, E. J. Phase equilibria and crystal chemistry of the rare earth group VI systems (III) neodymium–tellurium, (5) 139*i*.

Linares, R. C. Properties and growth of flux ruby, (9) 254*c*. See Ballman, A. A.

Linares, R. C., and McGraw, R. B. Vapor growth of yttrium iron garnet, (6) 171*a*.

Linares, R. C., McGraw, R. B., and Schroeder, J. B. Growth and properties of yttrium iron garnet single-crystal films, (3) 82*e*.

Linares, R. C., and Schroeder, J. B. Plural directional growing of crystals, P (6) 160*j*.

Linares Gonzales, J. See Martin-Vivaldi, J. L.

Linares Gonzales, J., and Martin-Vivaldi, J. L. Rheology of bentonite suspensions as drilling muds, B (2) 56*h*.

Lincius, A. Heavy mineral concentrates and their granulometic composition in Kursiu Nerija [Lithuania] beaches, (9) 250*g*.

Lincoln, B. Method of and apparatus for classifying fibers by length, P (10) 283*c*.

Lincoln, E. T., and Ervin, J. M. Method and apparatus for producing fibers from mineral materials, P (2) 34*a*.

Lincoln, R. C., and Osment, H. E. Production of potassium permanganate activated alumina composite, P (4) 101*k*.

Lindblad, F. W. Circular saw, P (3) 57*g*.

Lindblom, Y., and Stahl, N. Wear measurements on the lining of a Kaldo converter, (10) 273*f*.

Linden, P. C. van der. See Jonge, J. de.

Lindenthal, J. W. Production of refractory silica articles, P (3) 70*h*.

Lindeskog, B. Solubility of nitrogen in electric furnace steel slags—discussion of the effect of slag as a barrier against nitrogen pickup in the melt, (10) 290*b*.

Lindgens & Sohne. Production of a new dehydrated and highly basic lead carbonate, P (4) 109*k*.

Lindholm, U. S. Some experiments with the split Hopkinson pressure bar, (1) 25*a*.

Lindholm, U. S., and Yeakley, L. M. Dynamic deformation of single and polycrystalline aluminum, (10) 285*d*.

Lindley, M. W. See Lewis, D.

Lindop, T. W. Silicon nitride—a new engineering ceramic, (8) 216*j*.

Lindquist, R. H. Method of preparing improved magnetic material of controlled particle size, P (2) 42*d*. See Constabaris, G.

Lindsay, J. G., and Gailey, H. J. Method of making low soda alumina of small crystal size, P (10) 283*c*.

Lindstrom, R. E., and Winget, J. O. Process for separating rare-earth elements by ion exchange, P (4) 109*g*.

Ling, H. W. See Kolski, T. L.

Lingane, J. J. Analytical Chemistry of Selected Metallic Elements, B (3) 88*a*.

Lingl, H. Apparatus for stacking bricks, P (11) 308*f*. Burner for furnaces, P (1) 17*i*. Ceiling constructions for furnaces, P (9) 246*h*.

Lingl, H., Jr., and Morrison, N. T. Automatic setting with the Lingl machine, (4) 98*c*.

Lingo, R. W. See Cropp, D. I.

Ling-Temco-Vought, Inc. Heat-resistant article, P (6) 146*f*.

Linkison, W. S. See Eyre, P. B.

Linne, S. The ethnologist and the American Indian potter, B (6) 172*d*.

Linotype & Machinery, Ltd. Color comparator, P (5) 132*c*.

Linson, D. H. Capacitor including aluminum silicate scavenger, P (2) 41*b*.

Linton, R. W. See Vessey, E. W.

Linton, W. R. See Gilmont, R.

Linzey, R. See Busen, K. M.

Lionel Corp. Pitch lens blocker ball and blanks, P (11) 299*d*.

Lipatova, N. P. See Morozov, I. S.

Lipovskii, I. E., and Dorofeev, V. A. Volnovakha basalt as a raw material for casting brick, (6) 154*e*.

Lipp, A. Elementary unit cell of boron carbide, (6) 167*j*. Process for the continuous production of boron nitride, P (1) 12*d*.

Lipp, G. D. Glass stream feeder, P (11) 298*i*. See Eck, R. D.

Lippman, A., Jr. See Carithers, V. G.

Lippmann, R. J. Glass feeding, P (4) 96*i*.

Lirones, N. G. Apparatus for the production of ceramic, cermet, and metal components, P (10) 280*e*. Ceramic multilayer graphite mold and method of fabrication, P (7) 188*i*. Graphite mold and fabrication method, P (10) 273*i*. Mold and method of fabrication, P (9) 240*j*. Precision casting mold and methods and materials for production and use, P (6) 155*d*. Precision mold and method of fabrication, P (6) 155*e*.

Liscia, A. See Gabaglio, M.

Lisnyak, S. S. See Belikov, A. M.

Lisovaya, E. D. See Kukolev, G. V.

Lisowski, H. J. See Glynn, A. T.

Listhuber, F. E. Manufacture and properties of sheet steel, (10) 263*i*. Unalloyed and low-alloy mass-produced high-quality sheet steels, (2) 30*e*.

Litherland, T. E. Oil fired kilns for ceramics, (1) 17*j*.

Litovchenko, M. I. See Dorf, Z. P.

Litterst, R. S. Radiant energy measuring device and method, P (10) 281*i*.

Little, Arthur D., Inc. See Arthur D. Little, Inc.

Little, I. F. C. Small tunnel kiln cuts costs and boosts production, (9) 237*g*.

Littlechild, J. E. Manufacture of sintered uranium dioxide bodies, P (4) 100*f*.

Littlefield, J. B. See Kuzmick, J. N.

Littler, E. S. See Oxley, G. H.

Litton Precision Products, Inc. Cathode ray tube using fiber optics faceplate, P (5) 128*j*. Electron gun supporting technique, P (1) 14*a*.

Litton Systems, Inc. Electrostatic separation means, P (7) 196*i*.

Litvin, B. N. See Kuz'mina, I. P.

Litvin, B. N., Dem'yanets, L. N., and Garashina, L. S. Crystallization of alkaline-earth molybdates under hydrothermal conditions, B (11) 320*d*.

Litvin, B. N., and Mel'nikov, O. K. Hydrothermal synthesis of trigonal silicates and germanates of zinc, B (11) 320*d*.

Litvinov, P. I., and Zhuravleva, R. A. Region of glass formation in the system SiO_2–Al_2O_3–CeO_2, (9) 234*c*.

Litwin, J., Tomaszewski, L., and Auleytner, J. Investigation of the real structure of CdSe single crystals deformed by uniaxial pressure, (6) 168*j*.

Litz, L. M. See Mercuri, R. A.

Liu, Chang-ling. Mineral type and chemical composition of fireclay in China, (5) 138*c*.

Liu, Chu-lin. See Chang, Kung-jui.

Liu, C. J., and Sieckmann, E. F. Refractive index of calcium oxide, (9) 254*c*.

Liu, Fu-yu. See Chang, Hwei-min.

Liu, Yu-shu. See Shen, Chi-yu.

Livovich, A. F. Properties of pneumatically placed refractory concretes, (2) 36*f*.

Livshits, L. D., Genshaft, Yu. S., and Ryabinin, Yu. N. Phase diagram of the crystal hydrates of $MgSO_4$ at high pressures, (10) 289*g*.

Lloyd, D. E. Hot-pressing of ceramics, (5) 130*g*.

Lloyd, H. L. See Wood, G. W.

Lloyd, J. E. See Taylor, H. A.

Lloyd, M. H. Method of preparing compactible thorium oxide-plutonium oxide particles, P (9) 240*e*.

Lobanov, N. I. See Veankov, V. T.

Locardi, B. See Bonnetti, G.; Gottardi, V.

Loch, L. D. Metal oxide semiconductors, (6) 158*g*.

Locher, F. W. See Richartz, W.

Lockett, J. A. See Moore, F.

Lockhart, R. J. See Harkulich, T. M.; Kiss, K.

Lockhart, R. J., and Magder, J. Ferroelectrics of ultrafine particle size (III) thin barium titanate layers for capacitors, (7) 191*e*.

Lockhart, R. J., and Wainer, E. Preparation of alumina monofilaments, P (11) 303*a*.

Lockhart, W. K. Cover glass for light signals, P (5) 122*b*.

Lockheed Aircraft Corp. Coating for refractory metal, P (11) 295*f*. Electroluminescent phosphors and method for making same, P (10) 278*f*. High-temperature resistant self-healing coating and method of application, P (11) 296*c*. Inorganic surface coatings, P (3) 59*j*. Semiconductive diode of single-crystal rutile and method of making same, P (1) 15*k*.

Locsei, B. P. Recent contributions to the confirmation of the existence of the metakaolinite state, (6) 169*d*. Technical developments in the manufacture of aluminosilicate refractories, (3) 69*h*. Thermogravimetric investigation of mullite formation in the system kaolinite–aluminum fluoride, (2) 53*d*.

Locsei, B. P., Kocsis, G., and Somogyi, A. Technological parameters of tempered safety glass manufacture, (9) 235*b*.

Lodge, J. R. See Langseth, A. O.

Lodge, J. R., and Fehner, R. H. Method of making roofing granules and product thereof, P (8) 214*f*.

Lodige, F. See Lodige, W.

Lodige, W., Lodige, F., and Lucke, J. Mixing apparatus, P (11) 309*a*.

Loeber, H. See Schnabel, O.

Loebner, E. E. Multilayer semiconductor electroluminescent output device, P (11) 307*d*.

Loeffler, J. Absorption of alumina on the surface of sheet glass, (8) 208*g*. Bubble formation in the reaction of glass melts with refractory materials, (6) 146*j*. Comment on "Assessment of heterogeneity in glass," (9) 233*a*. Determination of small quantities of silicic acid, (3) 75*j*. Diffusion processes between quartz and molten glass (III) supplement, (4) 92*i*. Liquid phase in fused-cast refractories, (2) 36*i*. Measurement of the homogeneity of glass, especially for the purpose of characterizing the output of tanks, (3) 61*b*. Physical and chemical reactions which lead to flux-line attack and upward drilling in glass tanks, (4) 94*e*.

Loeffler, K. O. See Chopoorian, J. A.

Loehrke, H. F. Composite articles and method of making the same, P (3) 63*c*.

Lofftus, F. H. See Johnson, D. E.

Lofgren, N. L., and Krikorian, O. H. Vapor pressure of Th(*g*) above ThC_2 as determined by emission spectroscopy, B (6) 172*j*.

Loftin, R. L. Nuclear level gaging, (5) 131*f*.
Logachev, M. S. See Levintovich, E. V.
Logan, R. A. Temperature sensitive element, P (9) 244*a*.
Logel, P. C. See Riebling, E. F.
Loginova, T. Z. See Tykachinskii, I. D.
Logvinenko, N. V. See Frank-Kamenetskii, V. A.
Loh, E., and Doell, W. Loading mechanism for machines for working on optical lenses, P (9) 236*e*.
Lohman, W. E. Automatic burner control system for rotary kilns, P (5) 132*f*.
Lohnes, F. G. See Keys, D. L.; Schilling, D. C.
Lohre, W. See Konopicky, K.
Lohrmann, H. See Lehmann, H.
Loiacono, G. M. See Nassau, K.
Lokay, J. D. Tracer studies in container glass furnaces, (2) 32*f*.
Lokshina, R. V. See Lesin, A. D.
Lomas, H. Analysis of gas evolved from shales for brickmaking, (10) 270*c*.
Lommel, J. M., and Graham, C. D., Jr. Magnetic bodies having magnetic anisotropy comprising conjoined thin films of molybdenum and nickel coated on a nonconductive substrate, P (6) 159*c*.
Long, E. L., Jr. See Osborne, M. F.
Long, G. See Foster, L. M.
Long, J., and Teichner, S. J. Production of homodispersed spherical particles of titania in the oxyhydrogen flame, (8) 225*f*.
Long, M. J., Dawson, J. W., and Soderquist, C. E. Liquid scintillation spectrometer detection chamber and removable tray for supporting a plurality of sample containers, P (11) 311*e*.
Long, R. A. Composite ceramic body and method of forming the same, P (1) 14*g*. Method and composition for exothermic brazing of metal joints, P (11) 296*a*.
Longbottom, P. See Miller, R.
Longfellow, H. W. Electroluminescent lamp manufacture, P (4) 104*e*.
Longo, J. M. See Donohue, P. C.; Kierkegaard, P.
Longo, J. M., and Ward, R. Magnetic compounds of hexavalent rhenium with the perovskite-type structure, (7) 201*a*.
Lonsdale, H. K., and Graves, J. N. Vaporization of the dicarbides of uranium, thorium, and protactinium, B (6) 175*c*.
Lonza-Werke Elektrochemische Fabriken G.m.b.H. Process for preparation of refractory substances in the form of hollow spheres starting from silicates containing magnesium, P (7) 189*a*.
Loofbourow, J. S., Jr. See Campbell, I.
Loon, W. van. See Schepers, J. H.
Loopstra, B. O. Neutron diffraction investigation of U_3O_8, B (2) 55*i*.
Lopato, L. M. See Tresvyatskii, S. G.
Lopato, L. M., and Tresvyatskii, S. G. Phase diagram of the system Y_2O_3–MgO, (1) 24*c*.
Lorang, B. See Deportes, C.
Lorenzo, M. P. Method of producing abrasive surface layers, P (1) 1*g*.
Lorenzo, M. P., and Hunsberger, J. F. Process of making metal bonded diamond abrasive articles, P (7) 177*i*.
Loriers, J. See Briat, B.
Loscudo, F. A., and Henault, N. C. Method and apparatus for packaging filamentary materials, P (4) 97*h*.
Loshkarev, B. A., and Yudin, I. A. Properties of ceramics in the system ZnO–TiO_2, (10) 290*a*.
Lotgering, F. K. Influence of Fe^{3+} ions at tetrahedral sites on the magnetic properties of $ZnFe_2O_4$, (9) 250*e*.
Loth, J. L. See Hooper, F. C.
Lotto, B., and Lazzari, S. Measurement of electrical resistance of glass in the liquid state, (8) 210*a*.
Lottridge, N. M., Jr. See Herkimer, P. F.
Lotz, K. E. See Baier, E.
Louden, W. C., and Pinter, R. S. Ceramic lamp construction, P (6) 158*f*.
Loudon, R. Excitations in crystals, (10) 286*b*.
Lourenco, O. B., and Souza Santos, P. de. Ceramic properties of Brazilian zirconium minerals, (1) 18*d*.
Love, T. J., and Grosh, R. J. Radiative heat transfer in absorbing, emitting, and scattering media, (1) 24*e*.
Lovell, B. W., and Epstein, D. J. Dynamic squareness in polycrystalline garnets, (2) 49*b*.
Lovell, H. L. See Utley, R. W.
Lovenselli, R. See Anselin, F.
Lovins, G. H. See Bentley, G. P.
Lowell, C. E., and Goton, R. P. Method of preparing an oxidation resistant article, P (11) 302*e*.
Loy Meng Yeo. See Yeo, Loy Meng.
Lozier, W. W., Null, M. R., and Eschenbach, R. C. Solar simulation apparatus, P (11) 308*c*.
Lu, S., and Rabson, T. A. Polarization of light from Nd^{3+}-glass lasers, (10) 289*e*.
Lu Li Ho Cement Works and Nanking Chemical Engineering Institute. Effects of alkalis on the production and properties of cement, (5) 118*f*.
Luberoff, B. J., Rickles, R. N., and Stuchell, R. W. Method of producing nitrides of aluminum and boron, P (9) 240*g*.
Lucas, A. C. See Durkee, R. K.
Lucas, R. T. See Young, J. A.
Lucas, T. E. Properties of high vacuum pumps, (1) 16*j*.
Lucena Conde, F. See Martin Vivaldi, J. L.
Lucke, J. See Lodige, W.
Luckey, H. H. See Van Couvering, A.
Ludlow, I. K. Symmetry of a color center in magnesium oxide, (9) 257*b*.
Ludlow, I. K., and Runciman, W. A. Uniaxial stress spectra in magnesium oxide, (3) 87*j*.
Ludowici, L. F. Tile mold, P (8) 222*f*.
Ludwig, H. C. See Cotter, G. H.
Ludwig, N. C., and Tresouthick, S. W. Apparatus for analyzing cement kiln exit gases, P (2) 45*h*.
Ludwig, U. See Schwiete, H. E.
Luescher, J., and Zega, B. Semiconductor device having self-protection against overvoltage, P (9) 244*c*.
Luft, L. See Tepper, F.
Lugg, R. R. See Isacks, A. J., Jr.
Luikov, A. V. Application of irreversible thermodynamic methods to heat and mass transfer, (7) 197*g*.
Lukacs, I., and Strusievici, C. Polymorphism of sodium metavanadate, (3) 84*j*.
Lukacs, J. See Abrecht, H.
Lukashenko, G. M. See Eremenko, V. N.
Lukaszewski, G. M. Differential thermal analysis (I) general introduction; (II) present status; (III) theoretical background; (IV) physical meaning of the heat conduction equation; (V) physical and mathematical models; (VI) initial and boundary conditions of heat conduction; (VII) nature of the heat transfer problem, (6) 162*a*; (VIII) solution of heat transfer problems, (8) 223*e*. Extended program control in thermogravimetry, (9) 245*g*.
Lukes, F., and Schmidt, E. Oxidation of silicon in dry oxygen, (5) 139*f*.
Lukonin, G. A. See Abel'chuk, N. A.
Luk'yanova, O. I., Uvarova, I. Yu., and Rebinder, P. A. Physicochemical properties of sodium silicates high in silica, (2) 28*i*.
Luley, A. H. See Costain, T. S.
Lummerzheim, D. See Kroeger, C.
Lunt, B. G., and Meulen, G. J. R. van der. Bulk storage of cement for a concrete laboratory, (1) 2*c*.
Luoma, E. J. Method of determining the dielectric constant of a material using calibrated standards, P (5) 132*b*.
Lupfer, D. A. Electrical component and method of manufacture, P (10) 278*e*.
Lusher, K. G. Glass sealing compositions and method for modifying same, P (7) 183*f*. Magnetic solder glass coatings and method, P (7) 183*d*. Method of printing, P (8) 213*a*.
Lusher, K. G., and Wells, L. J. Method and apparatus for decorating containers, P (11) 298*e*.
Luth, W. C., and Ingamells, C. O. Gel preparation of starting materials for hydrothermal experimentation, (1) 21*g*.
Luthi, B. Ferroacoustic resonance and acoustical birefringence in gadolinium iron garnet, (7) 199*d*.
Luthra, J. See Primak, W.
Lux, G. A. Improved methods of cleaning, (4) 91*h*.
Luzhnaya, N. P. See Slavnova, G. K.; Tsui, Bin-Sin'.
L'vov, S. N., Nemchenko, V. F., Kosolapov, T. Ya., and Samsonov, G. V. Electrical properties of chromium carbides, (11) 316*a*.
Lyasin, V. F. See Botvinkin, O. K.
Lye, R. G. Thermoelectric power of titanium carbide, (8) 228*c*.
Lykken, W. H. Extraction method, P (11) 312*f*. Pulverizer and classifier, P (3) 79*b*.
Lynam, T. R., Booth, C., Hedley, C. S., Singleton, E., and Gilpin, W. C. Method of making metal covered refractory bricks, P (2) 38*c*.
Lynam, T. R., Nicholson, A., and Gilpin, W. C. Silica refractories, P (7) 190*a*.
Lynch, C. T. See Mazdiyasni, K. S.; Mersol, S. A.; Robinson, L. B.
Lynch, R. S., and Smith, B. K. Electroluminescent device, P (10) 278*f*.
Lynch Corp. Parison mold with finish pin and plunger construction for glassware forming machines, P (11) 299*b*. Plunger mechanism for glass gob feeder, P (7) 184*c*. Tube mechanism for glass gob feeder, P (6) 151*b*.
Lyon, J. E., Fox, T. U., and Lyons, J. W. Inhibited phosphoric acid for use in high-alumina refractories, (8) 215*c*.
Lyons, J. W. See Lyon, J. E.
Lyons, S. C. See Moore, J. C.
Lysak, J. Method of and apparatus for sealing glass-type envelopes, P (10) 278*d*.
Lysak, S. V. See Sukharevskii, B. Ya.
Lytle, W. O. See Orr, L. E.
Lyubimova, T. Yu., and Rebinder, P. A. Crystallization hardening of cements in the zone of contact with different solid phases (fillers), (3) 58*g*.
Lyutaya, M. D., and Bukhanevich, V. F. Chemical and thermal stability of nitrides of group III elements, (1) 19*h*.

Maak, I. See Eckerlin, P.
Maatman, R. W. See Frilette, V. J.
Mabru, M. See Levecque, M.
McAdam, R. L. See Shaler, R. G., Jr.
McAleer, W. J. See Allegretti, J. E.; Barkemeyer, H. R.
McAleer, W. J., and Pollak, P. I. Method of determining the concentration of active impurities present in a gaseous decomposable semiconductor compound, P (5) 132*b*.
McAllister, W. A. Calcium and magnesium silicate phosphors with activator comprising terbium, P (9) 242*f*. Phosphor, P (1) 15*b*.
McAnespie, P. See Burak, N.
McAtee, J. L., Jr., and Shaw, D. W. Mutual adsorption of clay minerals and colloidal hydrous chromium oxide—an electron-microscopic investigation, (10) 288*d*.
McBride, J. R. See Stephens, F. N.
McBurney, W. C. Multiple-compartment china [shipping] carton, P (4) 103*d*.
McCaldin, J. O. Compound semiconductor devices, P (10) 278*a*.
McCallum, D. W. See Erwin, L. R.
MacCallum, R. B. Preparation of ferric oxide sols and sol particles, P (10) 283*d*.
McCamont, J. W. See Bartlett, R. W.
McCartney, E. R. See Moorehead, D. R.
McCartney, E. R., and Yeo, Loy Meng. Viscosities of kaolin-water suspensions with additions of a basic aluminum chloride complex, (5) 127*i*.
McClarney, H. W. Methods to construct masonries, P (1) 7*g*.
McCleary, L. C. See Peiser, H. S.
McCleary, R. E., and Kinkade, W. A. Method for making ultrafine calcium sulfate dihydrate crystals, P (10) 263*b*.
McClure, W. L. Apparatus for transporting solids, P (9) 244*f*.
McCollister, H., and Van Vlack, L. H. MgO–$MgFe_2O_4$ microstructures, (1) 13*g*.
McConnell, D. G. See Ostrach, S.
McConnell, L. W. See Bebbington, P. J.
McCoppin, G. T. Apparatus for forming and collecting mineral fibers, P (10) 267*h*.
McCord, J. Porcelain enamel, (2) 30*c*.
McCord, W. M., Jr. Abrasive article backed with stretchable-compressible material, P (2) 27*f*.
McCorkle, K. H. See Morse, L. E.
McCormack, W. R. Substrates having solderable gold films formed thereon and methods of making the same, P (4) 106*d*.
McCown, W. E. See Dunipace, D. W.
McCoy, E. E., Jr. Resonant vibration technique for laboratory determination of shear wave velocity, (8) 223*g*.
McCoy, W. See Egan, J. J.
McCracken, G. M. Performance of a high speed getter pump using a cooled titanium film, (3) 76*e*.
McCreight, D. O. See Davies, B.
McCreight, L. R., Rauch, H. W., Sr., and Sutton, W. H. Ceramic and Graphite Fibers and Whiskers, B (5) 142*d*.
McCullough, D. G. See Herkimer, P. F.
McDaniel, C. L., and Schneider, S. J. Phase relations between Cr_2O_3 and IrO_2 in air, (6) 169*e*.
McDaniel, C. V., and Maher, P. K. Process for the preparation of synthetic faujasite, P (10) 283*e*.
MacDonald, G. A., and Katsura, T. Chemical composition of Hawaiian lavas, (7) 197*g*.
MacDonald, N. C., and Everhart, T. E. Direct measurement of the depletion layer width variation vs. applied bias for a *pn* junction, (10) 284*f*.
MacDonald, R. W. See Klein, D. L.
MacDonald, W. J. Method of supplying heat of fusion to glass-to-glass seal, P (1) 7*a*.
McDonnell Aircraft Corp. Heat insulating and ablative structure and method of making same, P (1) 11*f*.
MacDowell, J. F. Glass body having surface crystalline layer thereon and method of making it, P (11) 298*f*. Semicrystalline body and method of making it, P (5) 124*a*. See Eppler, R. A.
Macedo, P. B. See Napolitano, A.
MacEwan, D. M. C., and Sutherland, H. H. Use of periodograms for studying two- and three-dimensional irregularities in crystals, B (2) 56*a*.
Macey, J. G. Recovery of lithium from brines, P (10) 283*c*.
McFadden, C., and Remmey, G. B. Burner means for furnaces, P (7) 195*g*.
MacFarlane, R. D. See Corsini, A.
McGarry, P. E., and Siddle, J. D. Flotation of sphalerite, P (5) 133*d*.
McGee, J. D. Electron image intensifying devices, P (5) 128*c*.
McGee, T. D. Constitution of fireclays at high temperatures (I) methods of analysis; (II) mineralogical composition; (III) deformation characteristics, (3) 65*j*.
McGibbon, R. C. Quantum mechanical tunneling semiconductor device, P (4) 106*d*.
McGrain, P. Fuller's earth resources of the Jackson Purchase Region, Kentucky, (7) 196*i*. Review of Kentucky's clay resources, (8) 225*h*.
McGraw, R. B. See Linares, R. C.
McGraw-Edison Co. Apparatus for slip casting ceramic electrical ware, P (4) 103*a*. Fuse with hydrated arc extinguishing material, P (4) 104*i*. Lightning arrester valve element and method for making the same, P (1) 14*f*.
McGuire, J. C. Carbide deposition on tantalum, P (10) 263*g*.
McGuire, J. C., and Bowdish, D. D. High temperature furnace, P (5) 132*e*.
McGuire, R. L. See Barnett, R. L.
McGuire, T. R., Shafer, M. W., Joenk, R. J., Alperin, H. A., and Pickart, S. J. Magnetic structure of $EuTiO_3$, (9) 251*f*.
McHardy, W. J. See Follett, E. A. C.
Machida, J., Hagiwara, N., Yamada, T., Isago, M., and Sugishita, N. Method of producing phosphors, P (4) 105*d*.
Machlin, E. S. Classical model of solid solutions based on nearest-neighbor interactions which involve both central and linked-central forces, (11) 314*a*. See Class, W. H.

McHugh, C. O., Whalen, T. J., and Humenik, M., Jr. Dispersion-strengthened aluminum oxide, (10) 284*h*.
MacHutchin, J. G., Cowan, D. B., Allam, I. W., and Byler, W. H. Tritium activated self-luminous compositions, P (3) 74*d*.
McIlvaine, R. L. Base and trim water proportioning system and method, P (4) 100*d*. Mixer, P (7) 194*g*.
McIlvried, K. E. See White, W. B.
McKeag, A. H. See King, W. G.
McKee, Arthur, G., & Co. See Arthur G. McKee & Co.
McKee, K. H. See Kelly, F. J.
McKee, P. E. See Harshberger, S. D.
McKelvey, A. F. See Schnable, G. L.
McKelvey, H. E. Glass sheet bending mold, P (5) 122*i*. Method and apparatus for bending glass, P (7) 183*e*. Method of inspecting tempered glass sheets, P (10) 269*e*. See Black, L. V.; Cox, S. F.; Golightly, J. S.
McKenica, W. L. Method of preparing fine metal wires, P (2) 34*i*.
McKenna, P. M. Abrasive wheel, P (11) 293*f*. High temperature nozzle, P (4) 100*d*.
Mackenzie, J. D. Progress in glass, (11) 297*e*. Semiconducting glass-bonded mica—a new electronic ceramic composite, (6) 158*i*. See Secrist, D. R.
Mackenzie, J. D., and Mitoff, S. P. Semiconducting glass, P (9) 237*b*.
MacKenzie, K. J. D. See Foster, P. K.
McKenzie, L. G. See Chaklader, A. C. D.
McKibben, R. K. Roller-actuated vibro-energy mill, P (10) 280*e*. Vibro-energy mill, P (10) 283*e*.
McKibbin, K. See Smith, M. C.
McKillop, J. H. Industrial minerals in Newfoundland, (1) 18*e*.
McKinney, R. A. See Goldstein, M. B.
McKinnis, C. L. Borosilicate glass melting method, P (11) 297*g*.
McKinstry, H. A. Thermal expansion of clay minerals, (2) 53*i*.
Mackus, T. J. See McNeill, W.
MacLachlan, O. C. Manufacture of sheet steel bathtubs, (6) 145*j*.
McLaren, A. C., and Phakey, P. P. Dislocations in quartz observed by transmission electron microscopy, (3) 81*d*.
McLaren, J. R., Regan, M. C., and Hedger, H. J. Sintering behavior of uranium carbide, B (6) 172*d*.
McLean, D. Optical metallography, B (6) 173*h*.
McLean, D. A., and Nicodemus, D. S. Oxide underlay for printed circuit components, P (3) 74*c*.
McLean-Elrick, A. See Paris, R.
McLellan, R. B. Thermodynamics of dilute Fe–C solid solutions, (5) 141*i*.
McManus, D. A. Study of maximum load for small-diameter sieves, (4) 107*i*.
McMaster, A. D. See Fuschillo, N.; Gimpl, M. L.
McMaster, H. A. Glass actuated control for the conveyor mechanism of a glass bending furnace, P (3) 63*g*. Means for releasing stresses produced in glass during cooling in a glass shaping mold, P (8) 212*h*.
McMaster, H. A., and Nitschke, N. C. Apparatus for heat treating glass sheets, P (7) 182*h*.
McMillan, P. W., and Hodgson, B. P. Bonded metal-ceramic elements, P (5) 128*h*. Crystalline material and method of making the same, P (4) 96*b*.
McMillan, P. W., Hodgson, B. P., and Partridge, G. Process of bonding glass or ceramic to metal, P (3) 64*e*. Sealing glass-ceramics to metals (I) selection of materials and direct sealing methods, (11) 297*f*.
McMillan, P. W., Partridge, G., Hodgson, B. P., and Heap, H. R. Sealing glass-ceramics to metals (II) sealing by intermediate bonds, (11) 297*h*.
McMurtrie, G., Nagel, R. W., and Forth, E. W. Bathroom structure and fixture, P (11) 304*f*.
McMurtry, C. H. See Taylor, K. M.
McNally, R. N. See Alper, A. M.
McNeil, G. Integrated semiconductor resistance element, P (10) 278*b*.
McNeill, W., and Mackus, T. J. Apparatus for electrophoretic deposition of lamellar fluorphlogopite mica sheets, P (1) 14*e*.
McPherson, A. L. Expanding collet, P (7) 182*h*.
McRae, W. A. See O'Connor, T. L.
McRoberts, W. C. Glass bending molds, P (1) 6*a*.
McSkimin, H. J. See Thurston, R. N.
McStrack, D. D. See Burrage, L. M.
McTaggart, G. D. Ceramic refractory and method, P (2) 37*d*.
McWhorter, A. L. See Zeiger, H. J.
McWilliams, D. E. See Triplett, B. L.
McWilliams, D. E., Fasnacht, J. J., and Eilerman, G. E. Method of forming a glass fiber reinforced resinous body, P (7) 184*b*.
Maddocks, F. S. See Thun, R. E.
Maddox, C. There is more in brickmaking than meets the eye, (9) 237*h*.
Maddox, R. L., and Foos, R. A. Process for producing basic beryllium material of high purity, P (9) 247*g*.
Mae, S. See Muguruma, J.
Maeda, H. Multiple ceramic variable disk capacitor, P (2) 42*i*.
Maeda, S. See Maeno, M.
Maeder, H. J., and Bunger, W. Vibratory grinding mill, P (1) 19*b*.
Maeder, H. J., and Haertel, W. Vibratory grinding mill of the drum type, P (1) 19*c*.
Maeder, H. J., and Wehren, P. Vibratory conveyor, particularly bin-discharge conveyor, P (1) 16*d*.
Maekawa, S. Extending the lining life of a large electric arc furnace, (3) 67*g*. Improvement in the shape of brick for open-hearth furnace roofs, (8) 215*b*. Relation between the mineral structure of runner brick and that of sand which has entered the ingot, (1) 10*a*. Relation between the temperature of molten steel in the ladle and the life of ladle brick, (1) 10*a*. Study on results of using zircon brick for basic open-hearth ladles, (9) 239*f*.
Maekawa, S., Nakagawa, Y., and Matsumi, S. Study on the origin of oxide inclusions in steel, (1) 10*b*.
Maekawa, S., and Soga, M. Proceedings of the Pouring Pit Refractory Subcommittee Meeting (II) results of erosion tests with the submitted slag and with synthetic slag, (4) 99*g*.
Maelzig, G. See Lehmann, H.
Maeno, M. Study on the manufacture of fine silicate powder from acid clay (I) properties of acid clays and silica hydrogels; (II) process of formation of silica gel, (9) 247*f*.
Maeno, M., Takahashi, A., Maeda, S., and Oto, T. Study on the manufacture of fine silicate powder from acid clay (VI) preparation of fine silicate powder for rubber reinforcing filler, (9) 247*c*.
Maeno, M., Takahashi, A., Maeda, S., Oto, T., and Kitahara, A. Study on the manufacture of fine silicate powder from acid clay (III) manufacture of fine silica powder containing small amounts of calcium silicate, (9) 247*i*; (V) preparation of fine powder of calcium silicate, (9) 247*b*.
Maeno, M., and Yoshihara, T. Study on the manufacture of fine silicate powder from acid clay (IV) manufacture of ultrafine silica powder containing small amounts of calcium silicate, (9) 247*b*.
Maerker, R. Electrophoretic application of enamel, (9) 231*i*.
Magder, J. See Harkulich, T. M.; Kiss, K.; Lockhart, R. J.
Magnetfabrik Bonn Gewerkschaft Windhorst. Method and apparatus for making magnetically anisotropic permanent magnets, P (11) 306*a*.
Magnier, P. See Accary, A.; Lang, F. M.
Magnier, P., and Accary, A. Solubility of uranium in uranium monocarbide, B (6) 171*i*.
Magnier, P., Callard, C., Tournarie, M., and Accary, A. Orientation relations between monocarbide and dicarbide phases in uranium–carbon alloys, B (6) 171*i*.
Magnier, P., Traure, J., and Accary, A. Solubility of oxygen and nitrogen in uranium carbide, B (6) 171*g*.
Mah, A. D. Heat of formation of tantalum carbide, (1) 22*b*.
Mahan, G. D. Temperature dependence of the band gap in CdTe, (5) 141*e*.
Maher, P. K. See McDaniel, C. V.
Mahmoodi, P. Apparatus for determining thermal conductivity, P (10) 281*e*.
Mahmoud, N. S. See Sherif, I. I.
Mahmud, M. See Leroux, J.
Maho, C. Method of preparing magnetic acicular gamma iron oxide, P (11) 306*j*.
Mahoney, W. P. Treatment of newly formed glass articles, P (7) 184*h*.
Maienthal, E. J., and Taylor, J. K. Determination of tellurium by cathode-ray polarography, (2) 44*c*.
Maier, G. See Stoll, E.
Maier, P. Regulation of a group of oil burners for light, medium, and heavy oil, (6) 163*g*.
Maiklem, W. R., and Campbell, F. A. Study of the clays from Upper Cretaceous bentonites and shales in Alberta, (3) 86*d*.
Maio, A. D. See Townsend, R. L.
Mair, L. See Levine, B. H.
Maire, J. See Gremion, G.
Maissel, L. I. See Davidse, P. D.
Maissel, L. I., and Riseman, J. Apparatus for coating articles by cathode sputtering [in vacuum], P (7) 192*h*.
Maissel, L. I., and Young, D. R. Method of tailoring thin film impedance devices, P (9) 243*f*.
Maiya, P. S., and Blakely, J. M. Technique for study of mass transport mechanisms at crystal surfaces, (2) 53*c*.
Majdic, A. See Schwiete, H. E.
Majumdar, A. J. See Nurse, R. W.
Majumdar, A. J., and Roy, R. P–T dependence of the sphalerite $\rightleftarrows$ wurtzite inversion in ZnS, (6) 169*i*.
Makarenko, G. N. See Samsonov, G. V.
Makarova, T. A. See Korelova, A. I.
Makasheva, I. E. See Isaeva, E. A.
Makhnavetskii, A. S., and Gorina, I. N. Measurement of the heterogeneity of glasses with standard spectrophotometers (1) 4*f*.
Makhnavetskii, A. S., and Shtol'man, E. M. Results and conclusions of complex physicotechnological investigations of the production of continuously rolled glass, (8) 210*i*.
Makhnavetskii, A. S., Zadumin, O. S., and Gorina, I. N. Results of complex studies of the physicomechanical properties of continuously rolled raw glass, (8) 210*h*, (11) 297*f*.
Makhnavetskii, A. S., Zadumin, O. S., and Zakhar'ina, T. N. Complex studies of continuously rolled glass, (11) 296*f*.
Makiguchi, T. Structural change and corrosion of MBC cupola refractory, (10) 272*f*.
Makiguchi, T., and Hayashi, T. Consideration of the erosive action on acidic firebrick for cupolas, (1) 8*h*.
Makihara, M. Silvered mica capacitor and method of making the same, P (10) 279*f*.
Makino, M., Ohba, A., and Shinobu, M. Comparison of used MgO 93% and MgO 96% magnesia clinker basic brick, (6) 151*j*.
Makino, M., and Shinohara, Y. Comparison of basic brick made of 95% MgO magnesia clinker and 35% Cr_2O_3 chromite with brick made of 91% MgO clinker and 31% Cr_2O_3 chromite after use, (10) 271*b*.
Makram, H., and Krishnan, R. Growth of nickel ferrite single crystals, (10) 286*e*.
Malachowski, F. Jar mill mounting, P (4) 107*a*.
Malhotra, V. M., and Wallace, G. G. New method for determining fineness of cement, (6) 144*g*.
Malhotra, V. M., Zoldners, N. G., and Woodrooffe, H. M. Ring test for tensile strength of concrete, (3) 59*f*.
Malicheff, A. Method and apparatus for the skimming of molten glass, P (5) 123*b*.
Malinaric, P. J. See Berg, D.
Mallinder, F. P., and Proctor, B. A. Strengths of flame-polished sapphire crystals, (7) 202*g*.
Mallory, J. D., and Ryan, L. D. Method for joining glass parts, P (10) 269*e*.
Mallory, P. R., & Co., Inc. Semiconductor multistack for regulating charging of current producing cells, P (11) 308*a*.
Malmstadt, H. V. See Walters, J. P.
Malobicky, R. L. See Barch, H. W.
Malobicky, R. L., Barch, H. W., Kelly, J. D., and Valchar, C. E. Method and apparatus for supporting glass sheets, P (3) 63*j*.
Mal'tseva, N. N., and Kharitonov, Yu. Ya. Infrared absorption spectrum of magnesium hydride, (3) 82*f*.
Malyshev, S. I. See Abel'chuk, N. A.
Malyuchkov, O. T., and Povitskii, V. A. Investigating the borides of transition metals by the nuclear magnetic resonance method, (10) 287*f*. Nuclear magnetic resonance method of studying CrB, LaB_6, and crystalline boron, (10) 289*b*.
Malyutina, G. I. See Glazov, V. M.
Mamalui, Yu. A. See Borovik, E. S.
Mambourg, J. E. See O'Connell, T. B.
Mamedov, Kh. S., and Belov, N. V. Structural analogy (isostructurism) between diorthosilicates and orthoborates, (4) 113*d*.
Manabe, T. See Kumai, H.; Watanabe, H.
Manarz, A. See Camagni, P.
Manasevit, H. M., Forbes, D. H., and Cadoff, I. B. Growth of single-crystal silicon on beryllium oxide, (11) 317*g*.
Mandal, S. S., and Roy, S. B. Thermal properties of mica (1), (6) 164*d*.
Mandl, G. Change in skeletal volume of a fluid-filled porous body under stress, (1) 19*g*.
Mandorf, V., Jr. Refractory compositions, P (8) 218*c*.
Mandt, P. Mining and preparation of the arkoses from the Triassic basin at Weiherhammer, (3) 78*h*. Ternary system feldspar–petalite–wollastonite and its uses in bodies and glazes, (3) 86*e*.
Mann, A. J. Circular furnace roof and component refractory bricks, P (4) 100*i*.
Mann, C. A. See Howl, D. A.
Mann, C. W. See Brandt, F. R.
Mann, J. Composite commode and overflow trough, P (10) 262*b*.
Mann, J. E., and Kyser, D. F. Semiconductor and method of forming by diffusion, P (6) 160*j*.
Manning, W. R., Marlowe, M. O., and Wilder, D. R. Temperature and porosity dependence of Young's modulus of polycrystalline dysprosium oxide and erbium oxide, (5) 141*g*.
Manring, W. H. See Conroy, A. R.; Van Denberg, J. F.
Mansfield Sanitary, Inc. Mold and core construction, P (1) 13*d*.
Manusov, E. B. See Rozenblyum, I. S.
Manusovich, M. I. See Smirnov, E. I.
Manvelyan, M. G., and Ter-Zakharyan, S. M. Study of the change in alkali content during electric melting of lamp glass, (4) 95*b*.
Manzo, J. See Angeleri, F. B.
Mapes, W. H. Comparative economics of glass melting—gas vs. electric, (8) 224*c*.
Marafioti, J. J. Flux free bonded article, P (7) 182*j*. Method of making a flux free bonded article, P (5) 129*c*.
Marceau, W. E. See Dolf, H. R.
Marchal, M. See Accary, A.
Marchand, A. Magnetic anisotropy theory of pyrocarbons, (4) 112*f*.
Marchand, G., and Sarrat, P. Filtration-desiccation method and apparatus, P (10) 280*a*.
Marcinkowsky, A. E. See Kraus, K. A.
Marek, J. See Satava, V.
Marel, H. W. van der. See Beutelspacher, H.
Mareschal, M. See Quezel-Ambrunaz, S.
Maretheu, M. See Boirat, M.
Marezio, M., and Remeika, J. P. High pressure phase of $LiGaO_2$, (5) 136*j*.
Margason, L. L. See Burgman, J. A.
Margiloff, I. B. Flame working minerals, P (7) 196*i*.
Margola, G. B. Once-firing only, (1) 12*h*.
Margrave, J. L. See Kent, R. A.; Mezaki, R.
Mariacher, G. Discovery of two Venetian bottles of the 15th century, (4) 89*j*. Glass in the Museo Civico at Brescia, (8) 206*b*.
Mariano, A. N. Single crystal mounting device for the Philips diffractometer, (3) 76*c*.

Maricq, E. P. Electrothermic machine for welding glass containers, chiefly pharmaceutic phials, P (8) 212*f*.
Marinaccio, L. P., and Lepselter, M. P. Method of making low resistance contact to silicon semiconductor device, P (8) 221*a*.
Marinace, J. C. Method of forming an integral masking fixture by epitaxial growth, P (5) 129*b*.
Marinder, B. O. See Kierkegaard, P.
Marinina, V. T. Study of the reaction (friction, wetting, spreading, and adhesion) of molten glass with refractories, (10) 266*g*. Surface tension of commercial glasses in air and nitrogen, (8) 211*j*.
Marinina, V. T., and Utolina, L. S. Wetting of refractory concrete by molten glass, (9) 235*i*.
Maris, H. J. Absorption of sound waves in perfect dielectric crystals, (2) 48*e*.
Maritz, J. F. See Murray, K. A.
Markarian, M., and Peck, D. B. Method of making a ceramic capacitor, P (6) 159*i*.
Markels, M., Jr., and Eichbauer, R. N. Process for producing finely divided rounded particles, P (3) 75*b*.
Markeviciene, R., Mikailiene, E., and Slizys, V. Beneficiation of Anyksciai [Lithuania] quartz sands, (7) 196*c*.
Markin, T. L., Roberts, L. E. J., and Walter, A. Thermodynamic data for uranium oxides between UO_2 and U_3O_8, B (6) 175*f*.
Markov, A. I., Mikhailov, N. V., and Rebinder, P. A. Approximate calculation of the strength of concretes as a function of degree of hydration, water/cement ratio, and volume of trapped air, (9) 230*g*.
Markova, M. See Babachev, G.
Marks, C. P. See Hokkeling, P.
Marland, J. A. Rotary kiln drive mechanism, P (9) 246*i*.
Marlowe, M. O. See Manning, W. R.
Marples, J. A. C. See Nichols, J. L.
Marschalko, B. See Barna, J.
Marsh, H., O'Hair, T. E., and Reed, R. Oxidation of carbons and graphites by atomic oxygen—electron microscope study of surface changes, (2) 51*f*.
Marsh, H., O'Hair, T. E., and Wynne-Jones, W. F. K. Oxidation of carbons and graphites by atomic oxygen—kinetic studies, (2) 51*c*.
Marshakova, T. A. See Ugai, Ya. A.
Marshall, F. G. See Fletcher, J. R.
Martin, A. E. Batch preparation as a technical problem in the glass industry, (6) 146*j*.
Martin, C. See Grenier, J. C.
Martin, C., and Durif, A. Crystallographic data of anhydrous lithium chromate, (7) 198*f*.
Martin, C., Durif, A., and Joubert, J. C. Crystallographic data on lithium zinc fluoride, Li_2ZnF_4, (7) 198*f*.
Martin, D. C. See Barron, L. H.
Martin, D. G. Radiation damage effects in crystals, (8) 227*e*.
Martin, F. W., and Zimar, F. Fusion seals and their production, P (9) 235*j*.
Martin, G., and Music, E. G. Method of making a ceramic platen for a brazing fixture, P (10) 274*h*.
Martin, G. F. See Parr, N. L.
Martin, J. H., and Frantz, F. D., Jr. Capacitor with electrodes of metal coated particles, P (5) 128*j*.
Martin, J. J., and Edwards, J. B. Correlation of latent heats of vaporization, (1) 19*i*.
Martin, J. K. Automated soft-mud brick production, (2) 35*d*.
Martin, J. M. Blank mold means with pneumatic operated plunger for fabricating seamless high optical quality glass articles, P (2) 33*c*.
Martin, K. See Millner, T.
Martin, R. C. Cement composition, P (5) 119*d*.
Martin, R. E. See Burzynski, A. J.
Martin, R. G. Moisture sensing control, P (11) 311*b*.
Martin, W. H., and Brocklehurst, J. E. Thermal expansion behavior of pyrolytic graphite-bromine residue compounds, (4) 113*j*.
Martin, W. R., and Weir, J. R. Metal-clad fuel element with copper foil interlayer, P (4) 100*h*.
Martin Marietta Corp. Application of flame-sprayed linings on the inside diameter of tubes, P (7) 179*b*. Hafnium oxide-europium compounds and compositions for reactor control elements, P (2) 37*g*. Refractory composition and method of producing same, P (5) 126*j*.
Martin-Vivaldi, J. L. See Linares Gonzales, J.
Martin-Vivaldi, J. L., Linares Gonzales, J., and Alias Perez, L. J. Genesis of the montmorillonite in the Cabo de Gata bentonites, B (2) 56*g*.
Martin Vivaldi, J. L., Sanchez Camazano, M., and Lucena Conde, F. Clay minerals in soils of Salamanca Province, Spain (I) clay fraction of the surface layer, (9) 247*b*.
Martinek, T. W., and Klass, D. L. Preparation of silica for use in electric-field-responsive compositions, P (7) 194*b*.
Martinelli, J. Laser-induced damage thresholds for various glasses, (8) 209*i*.
Martinelli, R. Microtome knife, P (4) 97*j*.
Martinet, J. R. Refractory, P (6) 155*a*. See Neely, J. E.
Martsin, I. I. See Kruglitskii, N. N.
Martusevicius, M., and Martynaitis, M. Increase of phosphoanhydrite resistance to water, (1) 2*b*.
Martynaitis, M. See Daumantas, E.; Martusevicius, M.
Martyny, W. C. Fluorescent panel lamp coating, P (7) 193*a*. Fluorescent panel lamp faceplate with opaque striping, P (6) 159*h*.
Martyny, W. C., and Parillo, E. V. Panel lamp inlead structure having a notched edge for lead-in conductors, P (5) 129*c*.
Maruyama, N. See Kameyama, A.
Marwan, F. See Kroeger, C.
Marynowski, C. W., Halden, F. A., and Farley, E. P. Variables in plasma spraying, (8) 208*e*.
Marzocchi, A. See Shulver, W.
Marzocchi, A., and Horton, R. C. Method for improving the adhesion of vinyl polymers to glass fibers by the use of nitrogen compounds, P (5) 123*g*.
Marzocchi, A., and Janetos, N. S. Elastomeric glass fiber products and process, P (8) 212*e*. Process of coating glass fibers with hydrolyzed condensation product of amino silane and copolymerizable monomer, P (8) 213*g*. Sized glass fiber, P (1) 7*b*.
Marzocchi, A., and Otto, W. H. Coating fibrous glass yarns, P (11) 297*i*.
Marzocchi, A., and Waugh, J. A. Surface treatment of attenuated glass, P (5) 124*c*.
Mash, D. H. Electroluminescent lamp with a dielectric reflective material, P (2) 41*i*.
Mashkin, L. See Dimov, D.; Petkov, P.
Maskell, C. W. See Isaacs, J. W.
Maslennikova, G. N. See Bukhalova, G. A.
Maslennikova, G. N., and Buchenkova, A. F. Ceramic materials with improved mechanical properties for high-voltage applications, (6) 157*b*.
Maslov, V. N., Davydov, A. A., Demenkov, N. M., and Nabatova, L. V. Twin structure of germanium dendritic strips, B (11) 320*a*.
Maslov, V. N., Pelevin, O. V., Epifanova, K. I., and Davydov, A. A. Crystallization of a film between parallel growing germanium dendrites, B (11) 320*a*.
Mason, D. E. Semiconductive electroluminescent devices, P (2) 42*g*.
Mason, R. A. L., Nelson, E. H., and Rigden, S. A. R. Articles of fused silica, P (2) 40*j*.
Mason, R. K. Dinnerware, (2) 39*g*.
Massachusetts Institute of Technology. Semiconductor infrared maser, P (9) 244*c*.
Massalski, T. B. (editor). Alloying Behavior and Effects in Concentrated Solid Solutions—Based on a Symposium, Cleveland, 1963, B (6) 171*f*.
Masse, D. P., and Muan, A. Phase relations in the system CoO–SiO_2, (7) 202*e*.
Masse, D. P., Rosen, E., and Muan, A. Activity-composition relations in Co_2SiO_4–Fe_2SiO_4 solid solutions at 1180°C, (7) 197*b*.
Masson, C. R. Approach to the problem of ionic distribution in liquid silicates, (3) 79*f*.
Masters, B. C. See Harris, J. E.
Masuda, I. Wavelength dependence of quantum efficiency and absorption coefficient of Zn-SiO_2/Mn powder phosphor, (4) 114*h*.
Masuda, M., Kita, H., and Fujita, R. Device for polishing glass, P (5) 122*d*. Machine for chemically polishing glass, P (4) 97*b*.
Masuda, S. See Asano, T.
Masuda, S., Onishi, T., and Saito, H. Inlet-gas humidification system for an electrostatic precipitator, (5) 118*j*.
Matchabely, G. A. See Dzotsenidze, G. S.
Matchen, B. Electrode holder for high temperature heating apparatus furnace, P (7) 195*j*.
Mateiko, Z. A. See Bukhalova, G. A.
Mateiko, Z. A., and Bukhalova, G. A. Cross sections of the quaternary reciprocal system Na^+, Ca^{2+}, Ba^{2+}||F^-, Cl^-, (6) 166*a*.
Materiel Ceramique Moderne S.A.R.L. Automatic handling equipment particularly for drying molded products, P (7) 195*g*. Improvement in the manufacture of ceramic products, P (6) 161*f*.
Mathias, B. B. Inspecting rims of open mouth containers, P (10) 268*b*. See Johnson, W. E.
Mathias, B. B., and Murley, E. M., Jr. Inspecting articles, P (7) 183*i*.
Mathieu, M. Topochemical reactions, B (6) 175*c*.
Mathur, S. C. Magnetic properties of copper acetate at low temperatures, (3) 83*d*.
Matkin, D. I., and Bowen, D. H. Whisker growth within single crystals of magnesium oxide, (4) 114*a*.
Matkovich, V. I. See Economy, J.; Giese, R. F., Jr.
Matkovich, V. I., Colton, E., and Peret, J. L. Refractory materials and method of making same, P (9) 241*f*.
Matkovich, V. I., Giese, R. F., Jr., and Economy, J. Packing of B_{12} groups in boron and boride structures, (7) 202*b*. Phases and twinning in $C_2Al_2B_{22}$ (beta AlB_{12}), (8) 226*g*.
Matkovich, V. I., and Peret, J. L. Method of preparing cubic boron phosphide, P (8) 217*e*.
Matoba, T., Nakase, E., and Sakaba, A. Carburization of tantalum oxide, (7) 197*c*.
Matousek, J. See Satava, V.
Matson, F. R. Ceramic ecology—an approach to the study of the early culture of the Near East, B (6) 172*f*. Ceramic queries, B (6) 172*f*. (editor) Ceramics and Man, B (6) 172*c*.
Matson, L. K., Reid, F. J., and Miller, J. F. Resistance devices, P (11) 307*b*.
Matsubayashi, Y., and Sato, R. Grinding mill, P (4) 109*f*.
Matsuda, J., and Suito, E. Studies of the crystallization of lithium silicate glasses, (7) 181*c*.
Matsufuji, H. See Inoue, T.
Matsui, K. See Matsuura, E.
Matsukura, Y., and Oda, J. Multiple heterolayer composite semiconductor device, P (11) 307*e*.
Matsumi, S. See Maekawa, S.
Matsumoto, H., Yamauchi, S., and Nishiyama, G. Alumina base cermet (III) sintering mechanism of Al_2O_3–Fe and effects of the addition of Fe_2O_3; (IV) effect of addition of CaO, MgO, SiO_2, or TiO_2 on sintering of Al_2O_3–Fe–Fe_2O_3; (V) effect of addition of CaO–SiO_2 mixture; (VI) effect of addition of MgO–SiO_2 mixture, (6) 151*g*.
Matsumoto, Y., Nemoto, Y., and Suzuki, K. Method of manufacturing a substantially stress free cathode ray tube, P (7) 184*g*.
Matsumura, I. See Niwa, S.
Matsumura, T. See Nameishi, N.
Matsuno, S. See Ando, J.
Matsuno, Y. Graphic presentation of composition of grinding wheels—relation of grain-bond-pore volume fraction, bulk density, and bond content, (4) 89*f*.
Matsuo, Y., and Sasaki, H. Effect of grain size on microcracking in lead titanate ceramics, (5) 135*b*.
Matsuoka, H. See Goss, N. P.
Matsushima, T., and Thoburn, W. J. Application of differential thermal analysis to the dissociation of MnO_2 and Mn_2O_3, (1) 19*e*.
Matsushiro, A. Graphite brick set in the molding board for top casting, (1) 9*d*.
Matsushita Electric Industrial Co., Ltd. Method of manufacturing electrodes for fuel cells, P (1) 11*c*. Method for preparing CrO_2 of rutile type crystalline structure, P (6) 164*h*. Piezoelectric ceramic compositions, P (10) 279*g*. Process for fabricating magnetic ferrite cores, P (8) 221*g*. Radiating burner apparatus, P (5) 132*h*.
Matsuura, E., Matsui, K., and Hasiguti, R. R. Method of ohmically connecting filament to semiconducting material, P (3) 73*g*.
Matsuzaki, R. See Saeki, Y.
Mattare, L. A., Dent, J. W., Rich, D. J., and Smith, J. F. Dry material [pneumatic] transfer apparatus, P (1) 16*a*.
Mattauch, R. J., Lade, R. W., and Hoadley, G. B. Tables of F(U_S, U_B) and G(U_S, U_B) functions for semiconductor surface calculations, (10) 277*j*.
Mattern, J. S., and Plunkett, R. G. Method of making multifocal lenses, P (7) 184*g*.
Mattern, J. S., and Robert, R. R. Apparatus for forming optical elements, P (3) 62*i*.
Matthews, A. G. Machine blending of plaster, (5) 127*e*.
Matthews, H., Singh, S., and LeCraw, R. C. Sublattice contributions to the infrared rotary dispersion in YIG, (10) 291*c*.
Matthews, J. W. Role of contaminants in the epitaxial growth of gold on sodium chloride, (4) 112*j*. Technique for preparing single-crystal films of iron on clean sodium chloride substrates, (4) 104*e*.
Matthias, B. T. Ferromagnetic compound and devices including elements thereof, P (5) 128*e*.
Mattimoe, P. T. Laminated glazing unit, P (4) 97*a*.
Mattimoe, P. T., and Elton, W. L. Method of laminating glass, P (4) 97*c*.
Matting, A., and Haferkamp, H. Stress development in plastics with embedded glass fibers, (6) 148*j*. Tension development in synthetic resins with glass fiber reinforcement, (4) 95*d*.
Mattoon, D. R. Ceramic muffler with resilient sealing gaskets, P (4) 96*a*. Ceramic mufflers, P (4) 96*b*.
Mattox, W. J. Crystalline zeolite composition and method of preparation thereof, P (11) 312*f*.
Matveev, M. A. See Ginzburg, D. B.
Matveev, M. A., Mazo, E. E., and Kaminskaya, V. S. Strontium glasses—their properties and applications, (7) 181*b*.
Matveev, M. A., and Rabukhin, A. I. Relation between density of aqueous solutions of alkali silicates and their composition, (10) 266*d*.
Matyushenko, N. N. Thermal expansion of tungsten and molybdenum disilicides, (9) 257*i*. See Verkhorobin, L. F.
Matyushenko, N. N., Karev, V. N., and Verkhorobin, L. F. Beryllides of samarium, europium, and ytterbium of composition ABe_{13}, (11) 313*j*.
Mauer, P. B. See De Paolis, P. F.
Maul Brothers, Inc. Apparatus for forming glassware, P (9) 235*b*. Long stroke single gob glassware forming machine, P (4) 97*b*.
Maurer, R. D. Neodymium glass laser having an output at about 9180 A, P (11) 299*i*. Traveling wave laser amplifier with glass filter, P (2) 34*j*. See Borrelli, N. F.
Mausteller, J. W. See Tepper, F.
Max-Planck-Institut fur Eisenforschung. Process for the production of linings for metallurgical furnaces, P (3) 70*f*.
Maxson, G. J., and Motyl, E. J. Process for producing cadmium-bearing ferrites, P (5) 129*e*.
May, I., and Rowe, J. J. Solutions of rocks and refractory minerals by acids at high temperatures and pressures—determination of silica after decomposition with hydrofluoric acid, (3) 76*d*.
May, M. Andesite, a new building material, (3) 71*b*. Karl Heinz Modigell, (1) 1*i*. Turkish ceramics in the Munich City Museum, (8) 206*d*.
May, S. See Lang, F. M.
Mayer, C. H. Method of constructing cold cathode gas discharge tubes, P (4) 105*d*.
Mayer, G. See Gigon, J.
Mayer, J. W. Method of measuring nuclear radiation utilizing a semiconductor crystal having a lithium compensated intrinsic region, P (3) 77*b*.

Mayer, R. P., and Stowe, R. A. Mercury porosimetry—breakthrough pressure for penetration between packed spheres, (4) 112*b*.
Mayer, W. J., Lange, W. H., and Turner, T., Jr. Zirconium boride bearing, P (1) 12*f*.
Mayer, W. P., and Richardson, S. H. Bottle coating machine, P (8) 212*a*.
Mayer China Co. Support for ceramic ware, P (10) 275*a*.
Mayers, K. F. Glass-to-metal seal, P (10) 278*i*.
Mayhew, G. C. See Paul, W. B., Jr.
Mayhew, R. W., and Vogelpohl, R. L. Method for forming rectangular faceplate, P (10) 269*c*.
Mays, R. K., and Williams, L. E. Amorphous hydrogen aluminosilicate pigments, P (9) 247*d*.
Mazdiyasni, K. S., and Lynch, C. T. Preparation of alkoxides of some transition and rare-earth metals and the formation of powders and coatings of ultrahigh purity zirconia, B (11) 320*f*.
Mazdiyasni, K. S., Lynch, C. T., and Smith, J. S. Metastable transitions of zirconium oxide obtained from decomposition of alkoxides, (6) 168*f*.
Mazelsky, R. See Kramer, W. E.
Mazil, S. New trends in diamond wheels, (9) 229*f*.
Mazilova, N. V. See Nyankovskaya, R. N.
Mazo, E. E. See Matveev, M. A.
Mazur, A. K. See Pollyak, V. V.
Mchedlov-Petrosyan, O. P. See Babushkin, V. I.
Meacham, D. D., Smith, W. D., and Talcott, R. C. Tube having a heat conducting mount, P (3) 74*e*.
Meadowcroft, T. R., and Richardson, F. D. Structural and thermodynamic aspects of phosphate glasses, (1) 5*d*.
Meadows, F. W., and Pearce, N. Machines for operating on blanks of ceramic ware, P (3) 72*b*.
Meadows, G. W. See Alexander, G. B.
Medawar, O. Brazilian Ceramic Bibliography, (2) 54*f*.
Mednikova, E. I., and Sharnopol'skaya, E. T. Glass electrets, (7) 180*b*.
Medvedev, B. S. See Golubeva, M. S.
Medvedeva, Z. S. See Slavnova, G. K.
Mee, C. H. B. See Jones, M. D.
Meer, W. Semiconductor *pn* junction device and method of its manufacture, P (11) 308*a*. See Ruechardt, H.
Meerson, G. A., and Roi, S. Investigating the conditions for obtaining zirconium nitride and hydride direct from the dioxide, (1) 9*h*.
Megaw, H. D. Competitive structures and phase transitions, B (9) 259*d*.
Mehal, E. W., Haisty, R. W., and Shaw, D. W. GaAs epitaxial technology for integrated circuits, (7) 191*f*.
Mehan, R. L., and Berry, J. M. Nonlinear behavior in three-point bending of high-strength, high-modulus fibers, (4) 112*d*.
Mehlo, W., and Hohmann, M. Spray drying process and apparatus therefor, P (11) 309*c*.
Mehrotra, B. See Saalfeld, H.
Meier, A. P. Method for making incandescent lamps, P (11) 299*d*.
Meier, W. M. Crystal structure of mordenite (ptilolite), (3) 80*c*.
Meinert, N. See Broemer, H.
Meiring, G. L. See Alberts, L.
Meissner, H. P., Michaels, A. S., and Kaiser, R. Rate of pellitization of zinc oxide powders, (3) 74*i*.
Meissner, M. Hydrostatic pressure device, P (3) 75*a*.
Meissnerova, H. See Stanek, J.
Meister, G. See Wainio, A. W.
Meister, R., and Daemmer, H. Heat exchange process in the bottom of a pot furnace, (4) 93*d*.
Meitina, V. A. See Berzon, S. A.
Mekhanoshina, L. N. See Nazafchuk, T. N.
Melamed, N. T., Hirayama, C., and Davis, E. K. Laser action in neodymium-doped glass produced through energy transfer, (10) 287*c*.
Melcher, G. J. Fibrous glass brush bristle, P (5) 122*f*.
Melford, D. A. Topography, composition, and structure—a survey of some modern metallographic techniques, B (6) 173*h*.
Melichar, J. T., Jenssen, L. W., and Ostapovich, J. Apparatus for forming asbestos-cement tubes, P (7) 188*f*.
Mellaart, J. Anatolian pottery as a basis for cultural syntheses, B (6) 172*f*.
Mellen, E. J., Jr., Webb, J. M., Fasselle, R. J. de, and Dudek, J. A. Injection molding of ceramic cores, P (3) 70*a*.
Mel'nikov, A. Kh., Firsova, T. P., and Molodkina, A. N. Synthesis of pure samples of potassium peroxydicarbonate and a study of some of its properties, (4) 113*e*.
Mel'nikov, O. K. See Litvin, B. N.
Mel'nikova, M. A. See Syritskaya, Z. M.
Melrose, J. C. Thermodynamic relations between immersional and adhesional wetting, (4) 114*b*.
Meltzer, R. J. See Keller, J. D.
Melville, A. T. See Hirthe, W. M.
Memmert, S. See Leers, K. J.
Mendelsohn, L. I., Orth, E. D., Curran, R. E., and Robie, E. D. Preparation and properties of positive temperature coefficient thin-film thermistors, (10) 277*i*.
Mendelson, K. S. See Southgate, P. D.
Menelly, R. A. See Bernier, C. J.
Menezes, I. de. See Stubican, V. S.
Mennerich, F. A. Method of controlling production of continuous filaments, P (2) 34*c*. Method of forming fibrous glass yarn, P (1) 7*b*.
Menon, A. K. See Joshi, R. V.
Mentzel-Marx, A. Exhibition at the Helmhaus in Zurich, (3) 57*i*.
Menyhart, M. See Korach, M.
Menyuk, N., Dwight, K., and Wold, A. Ferrimagnetic spiral configurations in cobalt chromite, B (2) 55*c*.
Merck & Co., Inc. Apparatus for the preparation of semiconductor material, P (4) 104*h*. Continuous growth of crystalline materials, P (7) 192*d*. Deposition chamber including heater element enveloped by a quartz workholder, P (3) 72*j*. Method of determining the concentration of active impurities present in a gaseous decomposable semiconductor compound, P (5) 132*b*. Monocrystalline elongate polyhedral semiconductor material, P (4) 105*i*. Preparation of magnesium trisilicate, P (11) 312*h*. Temperature compensating barrier layer semiconductor, P (9) 244*a*.
Mercuri, R. A., and Litz, L. M. Purification of refractory materials, P (6) 155*a*.
Mering, J. Swelling, dispersion, and hydration of clays, (7) 203*h*.
Mering, J., and Oberlin, A. Study by microscopy and electronic microdiffraction of hectorite, montmorillonite, and nontronite, (8) 227*f*.
Merit Products, Inc. Abrasive article, P (10) 261*f*. Abrasive device and method of fabrication, P (6) 143*g*. Flap-type wheel, P (3) 57*h*. Method of fabricating abrasive leaves, P (1) 1*g*.
Merkel, H. See Wenzel, F. E.
Merker, L. See Wondratschek, H.
Merker, L., and Scholze, H. Effect of the water content of silicate glasses on their transformation and softening behavior, (5) 120*j*.
Merker, W. T., and Shatzel, N. W. Lens aligning and blocking apparatus, P (9) 236*e*.
Merrill, H. B., Jr. Electron probe X-ray microanalyzer, (10) 280*i*.
Merrill, J. H. See Gabrysh, A. F.
Merritt, R. B., and Trewhella, R. M. Sealed electrical assembly, P (11) 307*c*.
Merry, J. D., and Vondracek, C. H. Insulated electrical members and process for producing the same, P (8) 221*d*.
Mersol, S. A., Vahldiek, F. W., and Lynch, C. T. Microhardness anisotropy and slip in single crystal tungsten disilicide, (5) 138*d*.
Merwe, J. H. van der. See Vermaak, J. S.
Meschi, D. J. See Searcy, A. W.
Mesecke, C. M. Method for forming *pn* junctions in indium antimonide with special application to infrared detection, P (2) 42*a*.
Messerschmidt, S. Device for lapping and grinding balls, P (7) 194*g*.
Meszaros, F. W. See Smith, A. W.
Metcalfe, A. G. See Schmitz, G. K.
Metco, Inc. Flame spray clad powder composed of a refractory material and nickel or cobalt, P (8) 208*i*.
Metrimpex Magyar Muszeripari Kulkereskedelmi Vallalat. Method for the examination of the separation of suspensions and emulsions, P (6) 163*b*.
Metters, N. T. Glass cleaning compositions, P (7) 183*b*.
Metz, P. Manufacture of refractory materials, P (5) 154*f*. Process for making refractory articles, P (7) 189*j*. Refractory composition and process for making same, P (3) 70*j*.
Metzel, H. Standardization of saggers for porcelain flatware, (2) 39*j*.
Metzel, H., and Glaessel, C. Heat balance calculations for a tunnel kiln using liquefied gas fired at various speeds and suggestions for design modifications of porcelain kilns, (10) 282*c*.
Meulen, G. J. R. van der. See Lunt, B. G.
Meyer, A. Testing method for predetermining the 28-day standard strength of cement in 5 hours, (4) 90*h*.
Meyer, Andreas. Adhesion mechanism of molybdenum-manganese metallizing layers on corundum ceramics (I) reaction mechanism and adhesion; (II) metallization of corundum ceramics of low silica content, (6) 157*e*.
Meyer, August. Method and apparatus for scoring semiconductor plates to be broken into smaller bodies, P (4) 105*c*.
Meyer, A. E. Method of acid leaching uranium ores, P (7) 188*g*.
Meyer, D. R. See Meyer, O. E., Sr.
Meyer, F., and Spalthoff, W. Determination of the water content in glasses by nuclear magnetic resonance and comparison of the data with measurements of the infrared OH bands, (3) 60*i*.
Meyer, H. Comments on "Phase boundaries of the cubic' mixed crystal" ZrO_2–MgO from 1800°C to the melting point, (7) 202*c*.
Meyer, H., and Poehnitzsch, H. Glass evolution and bubble formation in fused cast refractories at high temperatures, (4) 93*b*.
Meyer, H. W. J. W. See Cornelissen, J.
Meyer, K., and Keutel, M. Submicroscopic morphology of the mechanical deformation of rock salt crystals, (3) 86*j*.
Meyer, O. E., Sr., and Meyer, D. R. Methods and apparatus for electrically piercing microscopic holes in dielectric materials, P (4) 105*g*.
Meyer, P. First international conveyor fair in Basle, (9) 244*f*.
Meyer Laboratories, Inc. Methods and apparatus for electrically piercing microscopic holes in dielectric materials, P (4) 105*g*.
Meyers, W. F., and Wells, L. J. Article decorating, P (10) 267*c*.
Mezaki, R., Tilleux, E. W., Barnes, D. W., and Margrave, J. L. High-temperature thermodynamic properties of some refractory borides, B (6) 175*g*.
Mezentseva, N. V. Maximum permissible air content of the dust of tungsten and titanium carbide, silicide, and nitride powders, (3) 68*g*.
Mezey, E. J., and Schwantje, H. H. W. Pigmentary silicon carbide, P (11) 303*a*.
Mezhekova, L. I. See Botvinkin, O. K.
Miag Muhlenbau und Industrie G.b.m.H. Continuous treatment of subdivided material with gas, P (10) 262*j*.
Micaud, G. See Rappeneau, J.
Miccioli, B. R. Thermal expansion behavior of niobium carbide-graphite composites, (8) 216*e*.
Michael, V. F. Method and apparatus for forming glass-reinforced resin pipe, P (4) 97*f*.
Michaels, A. S. See Meissner, H. P.
Michalik, E. R. Manufacture of glass sheets, P (6) 150*e*. Method of manufacture of flat glass, P (6) 150*b*.
Michalik, E. R., and Misson, G. W. Enclosed chamber for floating glass on a molten bath, P (7) 182*f*. Method and apparatus for manufacture of float glass, P (6) 150*g*. Method of removing surface defects from glass sheets, P (9) 236*e*.
Michaud, G. G. J., and Hart, R. G. Plutonium enriched uranium fuel for nuclear reactors, P (8) 218*b*.
Michaud, H. See Deiss, W. J.
Michel, A. Bonding and general properties of semimetallic compounds, B (6) 175*c*.
Michelitsch, M. Semiconductor device and method of producing it, P (6) 160*f*.
Microcyclomat Co. Extraction method, P (11) 312*f*. Pulverizer and classifier, P (3) 79*b*.
Micro State Electronics Corp. Method of making a tunnel diode assembly, P (6) 160*a*.
Midland-Ross Corp. Self-stabilizing combustion apparatus, P (11) 311*j*.
Miederer, W., Ziegler, G., and Doetzer, R. Method of crucible-free production of gallium arsenide rods from alkyl galliums and arsenic compounds at low temperatures, P (4) 105*e*.
Mierzejewska, S., and Niemyski, T. Preparation of crystalline boron carbide by vapor phase reaction, (3) 68*e*.
Migitaka, M. Temperature compensated zener diode, P (6) 161*c*.
Mihara, Y., Kitajima, S., and Abe, S. Method of making semiconductor devices by forming a damage layer on a surface of a semiconductor body and then alloying through said damage layer, P (5) 129*f*.
Mikailiene, E. See Markeviciene, R.
Mikailiene, E., Latvys, V., Dundzys, P., and Slizys, V. Physical and chemical properties of Lithuania clay fine fractions (I) quaternary clays, (9) 253*a*.
Mikailiene, E., Parfenov, V. A., Latvys, V., Slizys, V., and Dundzys, P. Physical and chemical properties of Lithuania clay fine fractions (II) prequaternary clays, (9) 253*b*.
Mikalkevicius, M. See Krisciunas, V.
Mikhailov, N. V. See Markov, A. I.; Sil'chenko, L. A.; Sovalov, I. G.; Ur'ev, N. B.
Mikhailov, Yu. N. See Kulikovskii, B. N.
Mikhailova-Bogdanskaya, Z. A. See Pollyak, V. V.
Mikhaleva, Z. A. See Styunkel', T. B.
Mikheeva, V. I., and Kost, M. E. Some properties of hydrides of lanthanum and neodymium, (4) 113*d*.
Mikheeva, V. I., Selivokhina, M. S., and Kryukova, O. H. Fusibility diagram in the system of the hydrates of potassium oxide and potassium borohydride, (4) 111*e*.
Mikhova, M. See Dyakovska, Ts.
Miklashevskii, A. I. Fireclay wall ceramics with reduced fire glaze, (6) 156*b*.
Miklosek, M. See Walters, E. L.
Mikus, C. A. Treatment of glass, P (3) 65*b*. See Curtze, E. W.
Milad, N. E. See Tobia, S. K.
Milanese, G. See Dellepiane, E.
Milberg, M. E., Otto, K., and Kushida, T. Electrical conductivity and nuclear magnetic resonance chemical shift in cesium silicate glasses, (5) 120*c*.
Mill, G. See Konopicky, K.
Millar, C. H. See Hooper, F. C.
Miller, A. H. See George, J. E.
Miller, B. C. Furnace section for kiln, P (2) 46*d*. Impact hammer for hammer mills, P (1) 18*f*.
Miller, C. F., and Gray, D. I. Sealed articles and methods of forming the same, P (1) 15*f*.
Miller, D. G., Singleton, R. H., and Wallace, A. V. Metal fiber reinforced ceramic composites, (6) 146*a*.
Miller, D. N., Jr. Petrology of Pierce Canyon redbeds, Delaware Basin, Texas and New Mexico, (5) 133*f*.
Miller, E. D., Jr. Alumina refractories, P (4) 99*j*, P (11) 301*g*. Calcium aluminate shapes, P (11) 301*j*. Fabrication of alumina refractories, P (3) 70*g*. Refractory, P (4) 101*j*. See Davies, B.
Miller, E. D., Jr., and Davies, B. Modulus of rupture of alumina-silica refractories at elevated temperatures, (9) 238*e*.
Miller, E. D., Jr., and Scott, R. K. Immersion sampler, P (3) 70*j*.
Miller, G. D. Heat emittance properties of materials, (2) 54*g*.
Miller, G. E. See Rion, R. G.
Miller, G. L., and Wagner, S. E. Semiconductor detector method, P (11) 307*g*.

Miller, G. R. See Johnson, H. B.
Miller, J. F. See Grebe, J. J.; Matson, L. K.
Miller, J. M. See Crawley, D. J.
Miller, J. W. Crystal puller, P (5) 128*a*.
Miller, N. E. See Townley, C. W.
Miller, R., and Longbottom, P. Process of classifying calcined conditioned titanium dioxide pigment slurries, P (4) 109*d*.
Miller, R. C. See Burdick, G. A.
Miller, S. L. Transistor, P (3) 74*d*.
Miller, W. H. See Eberly, P. E., Jr.; Horton, R. C.; Shulver, W.
Millet, J. F. Graphitized carbon articles containing rare earths, P (9) 240*c*.
Millet, R. Method and apparatus for the manufacture of fibers from glass or other thermoplastic materials, P (7) 183*i*.
Millhiser, R. G. Method for handling grit, P (5) 131*c*.
Milliken, W. U. Palletized structure of cylindrical products, P (5) 124*i*.
Millner, T. Behavior of dopes in tungsten sorts produced by powder metallurgy, (11) 313*i*.
Millner, T., Fukker, K., Martin, K., and Dvorszky, M. Method of manufacturing electrical heating elements with improved aluminum oxide coating, P (3) 73*d*.
Mills, B. D., and Payne, R. F. Continuously graded electrode of two metals for semiconductor devices, P (11) 305*e*.
Mills, D. See Ross, J. W.
Mills, L. E., Hauth, J. J., Bloomster, C. H., and Carroll, D. F. Fuel element for a nuclear reactor, P (4) 100*a*.
Milner, G. W. C. See Taylor, B. L.
Milner, G. W. C., Phillips, G., Jones, I. G., Crossley, D., and Rowe, D. H. Chemical analysis of actinide carbide ceramics and cermets for main constituents, B (6) 172*i*.
Milos, F. Refractories market in Canada, (6) 153*d*.
Miltschitzky, G., and Schindelin, W. Basic welding powders, P (1) 3*f*.
Min, Syu-kwei. See Cheng, Sun.
Minaev, N. G. See Latsh, V. V.
Minakov, A. G. See Koz'min, M. I.
Minakov, V. A. See Bondarev, K. T.
Minami, K. See Hasiguti, R. R.
Minami, T. See Tanaka, M.
Minami, Z., and Tsukagoshi, Y. Relation between method of cupola operation and erosion of refractories in the melting zone, (1) 9*j*.
Minardi, J. Effect of variations in the coefficient of thermal expansion on thermal stress, (5) 119*h*.
Mincher, A. L. Dispersion-strengthened cobalt alloys, (11) 301*b*.
Mindick, M., and Thompson, A. C. Method of producing alumina-coated silica in sol form, P (8) 225*c*. Method of producing a stable titania coated silica sol, P (6) 164*h*.
Minenko, V. I., Petrov, S. M., and Ivanova, N. S. Nature of molten glasses in the system lead oxide–silica, (9) 234*e*.
Mineral Industries Corp. of America. Apparatus for delaminating laminar minerals, P (5) 133*b*. Method of treating kaolin, P (8) 225*c*.
Minerals & Chemicals Philipp Corp. Agglomeration of bauxite fines, P (3) 78*e*. Catalyst containing activated bauxite, P (4) 100*i*. Clay products and aqueous systems containing same, P (11) 312*d*. Color-reactable inorganic adsorbent pigment and coating composition containing the same, P (3) 71*j*. Color-reactable inorganic adsorbent pigment and sensitized sheet material coated therewith, P (4) 109*d*. Glycol coated attapulgite clay and compositions including the same, P (4) 109*e*. High surface area aluminum silicate and method of making same, P (3) 78*g*. Method for producing spherical bauxite adsorbent granules, P (4) 101*j*. Method of treating chrysotile and product produced thereby, P (2) 47*j*. Sorbent products and method for making same from attapulgite clay, P (6) 155*g*. Treated clay slurries, P (5) 134*a*. Viscosity stabilized clay slurry, P (10) 283*g*.
Minkoff, I. Hole formation in crystal growth by surface adsorption of an impurity, (3) 82*j*.
Minnesota Mining & Mfg. Co. Abrasive sponge, P (8) 205*h*. Apparatus for determining thermal conductivity, P (10) 281*e*. Inorganic reflex-reflective aggregate, P (11) 298*j*. Method of making roofing granules and product thereof, P (8) 214*f*. Method of making stain-resistant roofing granules and product thereof, P (1) 13*b*. Mica sheet composite and method of making same, P (2) 42*i*. Precipitation process for preparing acicular magnetic metal oxide particles, P (6) 160*a*. Semiconductor device, P (6) 160*d*. Supersize film forming resins on coated abrasives, P (8) 205*g*. Thermoelectric alloy, P (3) 74*b*. Urea-formaldehyde resin bonded abrasive sheet, P (8) 205*h*.
Minnick, L. J. Nonplastic composition containing pozzolan, lime, and blast furnace slag, P (4) 101*b*.
Minowa, S. See Kato, M.; Takayanagi, T.
Minowa, S., Kato, M., and Funabashi, S. Use of silicon nitride brick and its corrosion by molten nonferrous metals, (7) 188*b*.
Minowa, S., and Kosaka, M. Erosion of silicon nitride refractories by electrolytic iron, (9) 238*f*.
Minowa, S., Ozaka, M., Yamada, M., Nishida, H., and Miura, H. Rate of erosion of clay-bonded SiC brick by molten iron and the qualities of the raw materials, (4) 99*a*.
Mione, A. J. See Stoops, R. F.
Mirchev, B. Apparel for workers in the glass, ceramic, and cement industries, (2) 54*f*.
Mirgalovskaya, M. S. See Skudnova, E. V.
Mirgalovskaya, M. S., and Strel'nikova, I. A. Interaction of aluminum antimonide with sulfur, (9) 251*c*.
Mironenko, L. A. See Vidro, L. I.
Mironova, M. L. See Botvinkin, O. K.
Miroshnichenko, V. Ya. See Levintovich, E. V.
Miroshnikov, V. N., and Denisenko, E. T. Assessment of the feasibility of operation of nickel-graphite compositions in steam atmospheres at industrial parameters, (11) 313*h*.
Mirza, B. V. See Oza, T. M.
Miscicka, M. Rapid methods of analysis in silicate chemistry—determination of alkali content by ion exchange and volumetric methods, (3) 76*a*.
Misler, Zh. V. See Bergman, A. G.
Misson, G. W. Gas module systems for heat transfer and/or fluid support of glass or other sheet materials, P (3) 63*g*. Handling of sheet material, P (3) 63*j*. See Michalik, E. R.
Mita, M. Magnesite deposits in Japan, (6) 153*b*.
Mitchell, A. Vibrational spectra of glassy oxides containing nitrogen in solution, (1) 6*a*. Vibrational spectrum of metaborate trimer and polymer ions and of metaborate fluoride mixtures, (2) 53*h*.
Mitchell, B. D. See Follett, E. A. C.
Mitchell, E. J. M. See Freeth, W. E.
Mitchell, M. M., and Ditrick, N. H. Stability effects in MOS enhancement transistors, (3) 72*c*.
Mitchell, R. F., Bruce, J. A., and Armington, A. F. New compound, boron triiodide-phosphorus triiodide, (7) 201*f*.
Mitchell, W. J., and Raab, V. C. Manufacture of shaped crystalline zeolitic molecular sieve bodies, P (10) 276*b*.
Mitman, E. T. See Veo, L. E.
Mitoff, S. P. See Mackenzie, J. D.
Mitrofanov, A. S. See Ivanov, V. E.
Mitsubishi Denki Kabushiki Kaisha. Process of producing solid composition resistors of monolithic structure, P (2) 42*e*.
Miura, H. See Minowa, S.
Mivelaz, W. F. See Hume, W. G.
Miwa, T., Yoshimori, T., and Takeuchi, T. Determination of boron in ceramic materials by the pyrohydrolytic separation and coulometric titration, (9) 245*c*.
Miyahara, S. See Okada, T.
Miyaji, K. See Miyazaki, E.
Miyamoto, O., Tanaka, Y., and Furukawa, M. Rapid determination of carbon in ceramic products by use of a high frequency combustion furnace, (4) 107*h*.
Miyashita, T. See Hayashi, N.
Miyata, N. See Usami, S.
Miyatake, K. Physical properties of the soft nozzle observed at high temperature, (1) 9*e*.
Miyatake, K., and Furumi, K. Destructive mechanism of basic brick (III) effects of both the SiO_2 content of brick and basicity of slag on element transition, (3) 66*a*. Erosion mechanism of basic brick used in a copper reverberatory furnace, (6) 152*g*. Erosion mechanism of tar-dolomite brick used for open-hearth rear wall, (3) 67*d*.
Miyatake, K., Furumi, K., and Kano, H. Change in texture of high purity magnesia brick used in a 30-ton electric arc furnace wall, (10) 270*j*. Comparative test on three types of unburned magnesia-chrome brick made from magnesia clinker (97% MgO) and silica bonded clinker combined with two chrome ores used in the roof of an open-hearth furnace, (10) 270*j*. Destructive mechanism of basic brick (IV) effect of MgO content of magnesia clinker on slag penetration, (7) 186*g*. Movement of fused matter in basic refractories at high temperature, (8) 216*c*.
Miyatake, K., Furumi, K., and Shikano, H. Comparison of physical properties of SiO_2-bonded and Fe oxide-bonded magnesia clinker, (7) 185*j*.
Miyatake, K., and Senba, K. Shape of the screw bolt for a graphite stopper head, (1) 10*f*.
Miyatake, K., Senba, K., and Honda, H. Erosion of LD converter zircon ladle brick, (9) 238*f*. Method of making zircon ladle brick, (7) 187*c*.
Miyatake, K., and Ueda, M. Thermal stress of a nozzle, (6) 154*d*.
Miyatake, K., Ueda, M., and Tazaki, S. Hydrodynamic experiment on ladle pouring nozzles, (8) 215*i*.
Miyazaki, E., and Miyaji, K. Enhancement of reverse current in semiconductor diodes by electron bombardment, (10) 276*j*.
Miyazaki, T. See Takeuchi, H.
Miyazawa, K., and Tomita, K. Effect of MgO on the properties of portland cement, (8) 206*j*.
Miyoshi, A., and Hara, A. High temperature hardness of WC, TiC, TaC, NbC, and their mixtures, (6) 152*f*.
Mizuno, M., Noguchi, T., and Naka, S. Formation of $ZrTiO_4$ from ZrO_2 and rutile or anatase, (11) 304*j*.
Mizuta, H. See Inoue, T.
Mizuta, M. See Kato, M.
Mkrtchyan, S. M. See Zakharchenko, M. A.
Mo och Domsjo Aktiebolag. Binding composition and method of making same, P (2) 29*f*.
Mobil Oil Corp. Aluminous cement slag composition and method of increasing compressive strength of same, P (10) 262*g*. High temperature lubrication process, P (11) 311*g*.
Mock, J. A. Coatings and finishes, (4) 91*d*. Flame sprayed coatings, (6) 145*g*. See Clauser, H. R.
Mocker, H. W., and Collins, R. J. Mode competition and self-locking effects in a *Q*-switched ruby laser, (10) 288*g*.
Mockli, R. Grinding disk, P (9) 229*f*.
Modry, S., and Pelzbauer, Z. Electron microscopic study of hardened cement pastes by the replica method, (11) 310*e*.
Moe, L. A. See Kosti, T. M.
Moeller, C. E. New thermal insulations, (4) 114*j*.
Moening, R. J. Leakage inhibiting supporting structure, P (3) 73*h*.
Moenke, H., and Moenke, L. Optical Determination Methods and Apparatus for Mineralogists and Chemists, B (6) 174*h*.
Moenke, L. See Moenke, H.
Moertl, G., Palaontas, A., Skalla, N., and Zednicek, W. Behavior of different qualities of cladding in steel-clad and reinforced basic refractories in regard to temperature requirements in oxidizing atmospheres, (8) 214*i*.
Moertl, G., Skalla, N., Weidner, A., and Zednicek, W. Chrome ore-containing brick of high mechanical strength, (11) 300*i*.
Moffat, A. R. L. See Clements, J. F.
Mogensen, F. New method of solving screening problems, (6) 164*h*.
Mogilevskaya, O. Ya., and Roshchina, P. A. Toxicity of the oxides of rare-earth elements gadolinium and dysprosium, (2) 55*a*.
Mohr, A. J., Jr. See Buyers, A. G.
Mohyuddin, I. See Popper, P.
Mokievskii, V. A. See Dement'eva, G. I.; Voitsekhovskii, V. N.
Mokievskii, V. A., and Afanas'ev, I. I. Formation of skeletal cavities in lithium fluoride crystals, B (11) 319*j*.
Molchanov, V. S. See Zitkeviciute, I.
Moldvai, R. See Korach, M.
Moles, L. See Belardi, R. J.
Moleva, V. A. See Chukhrov, F. V.
Moll, W. F., Jr. See Brindley, G. W.
Mollard, P. Process of agglomerating fine crystals and cryolite product, P (2) 48*b*. Process for the manufacture of trihydrate of alumina, P (10) 283*c*.
Molodkina, A. N. See Mel'nikov, A. Kh.
Molstedt, B. V. See Delaune, L. J.
Monahan, J. J. See Gubitose, N. F.
Mones, A. H. See Delaney, R. A.
Mones, A. H., and Neisser, K. E., Jr. Electrical resistance compositions, elements, and methods of making same, P (7) 192*h*.
Monforte, F. R. See Gallagher, P. K.; O'Bryan, H. M., Jr.
Monforte, F. R., and Schnettler, F. J. Ferrite compositions and method of manufacture, P (4) 104*f*.
Monier, J. C. See Frey, M.
Moniz, A. C. See Souza Santos, P. de.
Monk, C. B., and Hubbard, S. E. External wall panel and wall formed therefrom, P (7) 185*b*.
Monk, G. W. Apparatus and method for elutriating and measuring fine solid particles, P (11) 311*a*.
Monks, J. R. Method and apparatus for agitating molten glass, P (6) 150*f*. See Jasinski, J.
Monna, I. See Tanaka, H.
Monolith Portland Cement Co. Kiln brick, P (9) 240*f*. Kiln brick of portland cement clinker with a fused shell, P (9) 240*g*. Material ring removal from a rotary kiln, P (3) 77*g*.
Monsanto Co. Apparatus and method for producing single crystal structures, P (6) 158*d*. Article having a silicon carbide substrate with an epitaxial layer of boron phosphide, P (1) 14*f*. Boron phosphides, P (9) 247*e*. Clay beneficiation, P (2) 47*d*. Laminated safety glass, P (7) 183*c*, P (11) 298*c*. Method for improving the yield of an attapulgite clay, P (3) 78*j*. Method of preparing fibrous silicon carbide, P (7) 188*k*. Process and apparatus for the production of single crystal compounds, P (6) 160*b*. Process for preparation of sintered metallic oxide catalyst pellets, P (10) 274*e*. Process for producing oxides in the form of hollow shells, P (11) 303*f*. Production of epitaxial films, P (9) 244*a*. Safety laminates, P (7) 184*g*. Slim crystalline rod pullers with centering means, P (9) 244*e*. Thermoelectric unit and process of using to interconvert heat and electrical energy, P (9) 244*c*.
Monsanto Chemicals, Ltd. Production of refractory molds, P (1) 12*b*.
Mont, G. E. See Lavin, E.
Mont, G. E., and Lavin, E. Laminated safety glass, P (7) 183*c*.
Montecatini Societa Generale per l'Industria Mineraria e Chimica and Varda, G. de. Process and apparatus for improving the resistance of porous refractory materials to corrosive action, P (8) 218*c*.
Montgomery, E. C., Dean, H. N., and Cowley, C. H. Production of multiple glass sheet glazing units, P (9) 237*a*.
Mooi, J. See Gring, J. L.
Mook, G. C. See Brown, W. F.
Mooney, C. F. See Apple, J. M.
Moore, A. A. See Hawkes, W. H.
Moore, B. C. Vacuum sealing of rough surfaces, (10) 277*d*.
Moore, F. See Astbury, N. F.
Moore, F., and Lockett, J. A. Plasticity and packing, (10) 275*j*.
Moore, G. E. Fabricating semiconductor devices, P (2) 41*j*.
Moore, H. Henry Clifton Sorby, B (6) 173*g*.
Moore, J. C., and Lyons, S. C. Apparatus for whitening clay, P (5) 133*c*.
Moore, R. L. See Allemann, R. T.
Moore, T. J. See Reilley, J. M.

Moorehead, D. R., and McCartney, E. R. Hydrothermal formation of calcium silicate hydrates, (1) 22*f*.
Moorthy, V. K. See Kulkarni, A. K.
Moosbrunner Glasfabriks Akt.-Ges. Device for the fabrication of U-shaped profiles of glass in a continuous rolling procedure, P (4) 96*c*. Equipment for exact shaping especially by bending of continuously produced glass bands under simultaneous all over rolling friction, P (7) 182*g*. Glass reinforcing apparatus, P (1) 6*c*. Process for distortionless shaping of glass bands to glass profiles, P (7) 184*f*. Process and equipment for the production of continuous building elements of glass, P (5) 124*a*.
Mooser, E., and Boelsterli, H. U. Process of preparing gallium sulfide flakes and photoconductive device using same, P (10) 279*j*.
Morales, R., and West, P. W. Precipitation of calcium fluoride from homogeneous solution, (11) 310*d*.
Moran, J. J. Filter flask assembly, P (10) 267*j*.
Moran, R. Pretreatment of sheet metal for enameling, (10) 263*j*.
Moreau, C. See Blum, P.
Moreau, N. Blow mold with movable support, P (8) 211*i*. Continuous strip forming apparatus with heater unit, P (5) 122*a*.
Moreau, N., and Seifert, J. A. Glass tube forming, P (7) 183*g*.
Morelock, C. R. High strength fibers, P (1) 6*f*. Method for forming silica articles, P (9) 236*a*.
Moreton, R. Silicon carbide coatings on molybdenum and tungsten, B (11) 320*e*.
Moreton-Smith, M. See Hodge, N.
Morey, D. R., and Sheldon, S. Optically immersed photoconductive cells, P (6) 150*e*.
Morey, G. W. Electrical insulating glass composition and apparatus encapsulated therewith, P (3) 73*b*.
Morgan, J. C., Jr. See Dean, H. N.
Morgan, J. E. Electrostatic decoration of hot glass, P (5) 122*e*.
Morgan, J. E., Kowalka, W. R., and Swift, H. R. Apparatus for heating glass sheets, P (9) 235*d*.
Morgan, J. G. See Osborne, E. L., Jr.; Reagan, P. E.
Morgan, L. J. Gas burner, P (4) 108*d*.
Morgan, W. L. See Russell, R. G.; Slayter, G.
Morgan, W. L., and Scheffler, L. F. Separation of crystals from a boric anhydride matrix, P (3) 71*a*.
Morgan Refractories, Ltd. Electrical connection, P (7) 192*f*. Refractory products and the production thereof, P (5) 127*b*.
Morganite Research & Development, Ltd. Making articles of aluminum nitride, P (5) 126*a*. Refractory materials, P (4) 102*c*.
Mori, C. See Enomoto, S.
Mori, C., and Enomoto, S. Industrial applications of beta ray excited X rays (XII) plating thickness measurement by X-ray emission-spectroscopic method using ^{147}Pm beta ray source, (11) 310*h*.
Mori, S., and Hayashi, T. Deteriorated zones of magnesia refractories and dolomite brick used both in an open hearth and in a converter (II) changes in the physical properties of three types of magnesia clinker fired in different atmospheres, (6) 152*c*.
Mori, S., Hayashi, T., and Kyoden, H. Comparative study on corrosion of ladle brick used under various heat conditions (time of exposure to heat and exposure to heat under pressure of molten steel), (3) 65*k*.
Mori, T. See Tagai, H.
Morie, G. P., and Sweet, T. R. Analysis of mixtures of aluminum, gallium, and indium by solvent extraction and gas chromatography, (2) 43*i*. Determination of aluminum and iron by solvent extraction and gas chromatography, (6) 161*i*.
Morimoto, S. See Dryden, J. S.
Morio, A. See Sakurai, S.
Morita, H. See Inoue, T.; Nameishi, N.
Morita, K. Spectrographic determination of rare earth in steel (I) determination of yttrium by grating spectrograph and Littrow type spectrograph, (4) 107*g*.
Morita, K., Naka, K., and Kato, Y. Spectrographic determination of rare earth in steel (II) determination of yttrium by compact atom counter, (4) 107*g*.
Morita, S. See Kato, E.
Morita, S., Nishiwaki, M., and Yanagihara, Y. Various methods of using ladle refractories at Tobata No. 1 converter mill from September 1959 to November 1963, (3) 70*a*.
Moritz, G. E. Continuous casting system, P (1) 11*b*.
Moriya, T., Akao, Y., and Tamaru, S. Studies on the dissolving phenomena of powdered mixtures (I) dissolving process of mixtures of powdered substances with different solubilities in water (SiO_2–NaCl system), (5) 141*d*.
Moriya, T., and Yatabe, Shun-ichi. Studies on the dissolving phenomena of powdered mixtures (II) SiO_2–Na_2CO_3 system, (5) 141*f*.
Moriyama, T., and Abe, T. Crystallization of $CaSO_4 \cdot 2H_2O$ in the manufacture of phosphoric acid by the wet process (I) crystal growth of $CaSO_4 \cdot 2H_2O$ in the mixed acid H_3PO_4 and H_2SO_4; (II) transition rate of $CaSO_4 \cdot {}^1/_2H_2O$ to $CaSO_4 \cdot 2H_2O$ in the mixed acid; (III) effects of the impurities on the transition rate of $CaSO_4 \cdot {}^1/_2H_2O$ to $CaSO_4 \cdot 2H_2O$ in the mixed acid; (IV) transition rate of $CaSO_4 \cdot {}^1/_2H_2O$ to $CaSO_4 \cdot 2H_2O$ in phosphoric acid by the wet process, (11) 315*a*.
Morley, J. R. High temperature apparatus, P (1) 17*i*. Systems and processes for coating by evaporation, P (10) 279*g*.
Morozov, A. N. See Belikov, A. M.
Morozov, I. S. See Li, Chi-fa.
Morozov, I. S., and Krokhin, V. A. Interaction of niobium oxychloride with the chlorides of the alkali metals and thermal stability of the pentachloroxyniobates, (11) 317*g*.
Morozov, I. S., and Li, Chi-fa. Interaction of the chlorides of tantalum, niobium, iron, and aluminum with the chlorides of tin, (11) 317*d*.
Morozov, I. S., Lipatova, N. P., and Simonich, A. T. Thermal and tensimetric study of the system $NbCl_5$–$ZrCl_4$–KCl, (1) 25*d*.
Morozumi, S. See Koda, S.
Morrell, J. C. Dental impression materials, P (5) 127*f*, P (10) 263*a*.
Morris Bean & Co. Molding composition and method, P (8) 218*a*.
Morris, J. B. See Hyde, K. R.
Morris, J. W. Laminating techniques, P (5) 123*f*.
Morris, R. A., and Salat, R. F. Nude ion gage assembly, P (11) 307*e*.
Morrison, G. H. See Harrington, W. L.; Ruch, R. R.
Morrison, H. M. Dislocation enhanced impurity diffusion, (3) 80*j*.
Morrison, J. See Lander, J. J.
Morrison, N. T. See Lingl, H., Jr.
Morse, L. E., McCorkle, K. H., and Schilling, C. E. Method of preparing high-density compactible uranium dioxide particles, P (10) 274*i*.
Morton, W. A. Furnace roof, P (7) 188*a*.
Morzheedova, R. N. See Kutsev, V. S.
Mosaic Fabrications, Inc. Fiber optical scanning device, P (6) 149*h*. Metal and glass fiber structures and electrical devices using same, P (6) 159*e*. Method of aligning fibers of a multiple fiber bundle, P (8) 212*h*. Method of making metal and glass fiber structures, P (10) 269*f*.
Mosby, F. A. Electric lamp filament support, P (11) 298*b*.
Moschetti, A. See Passmore, E. M.
Moscker, E. See Osterholtz, C. E.
Moser, F., and Lewchuk, R. R. Method of supporting glass for polishing, P (4) 97*h*.
Moser, H. See Torkar, K.
Moser, J. B. See Blumenthal, R. N.
Moser, L. Foreign influence on Baden glass, (8) 206*a*.
Moser, R. Single crystal growth and polymorphism of Nb_2O_5 and Ta_2O_5, (6) 169*j*.
Moshier, R. W. See Scribner, W. G.
Moss, H. I., and Stollar, W. P. Die design for pressure sintering, (10) 280*a*.
Moss, R. L. See Gardner, R. F. G.
Moteki, K. See Nishino, T.
Motorola, Inc. High voltage semiconductor device, P (4) 105*c*. Method of making semiconductor device, P (5) 129*f*. Planar transistor with a relatively higher resistivity base region, P (11) 307*f*. Semiconductor current limiter, P (11) 307*g*. Semiconductor device and method, P (4) 106*g*.
Motyl, E. J. See Maxson, G. J.
Motzfeldt, K. See Forland, T.; Gitlesen, G.
Moulin, N. See Schmitz-Du Mont, O.
Moulson, A. J., Phillips, W. R., and Popper, P. Interaction between metals and ceramics at high temperature and its effect on electrical insulation, B (11) 320*g*.
Mounteer, J. E. See Domicone, J. J.
Mountvala, A. J., and Abowitz, G. Textural characteristics and electrical properties of vacuum evaporated silicon films, (2) 40*h*. Thermoelectric properties of vacuum evaporated PbTe films, (i) 14*d*.
Mountvala, A. J., and Murray, G. T. Role of the grain boundary in the elevated temperature fracture behavior of magnesia, (9) 255*d*.
Mowat, J. A. S., Pickles, S., and Horspool, J. M. Development of mixed carbide fuel preparation and fabrication routes at D.E.R.E., B (6) 172*d*.
Moyson, J., and Petruzella, J. Semiconductor switch, P (6) 160*j*.
Mozelewski, E. J. See Schindler, P. H., Jr.
Mrackova-Metlicka, A. Process for making semiconducting ceramic glazes, P (10) 276*e*.
M. S. A. Research Corp. Preparation of metal borides, P (9) 241*c*.
Muan, A. See Masse, D. P.; Rosen, E.; Schwerdtfeger, K.
Mueller, C. International summer seminar for ceramics in Gmunden, (9) 230*b*. Isostatic pressing, (9) 241*h*.
Mueller, C. W. See Robinson, P. H.
Mueller, E. Determinations of vibrated volume and Enslin value to determine the degree of firing of fireclay, (3) 66*e*. See Konopicky, K.
Mueller, E. E. See Kemp, H. T., Jr.
Mueller, E. W. Defects in metal crystals, B (9) 259*e*. Field ion microscopy, (1) 16*j*.
Mueller, H. R. Modern conveyors for internal transport, (10) 280*b*. Transport aids in brickworks, (7) 185*c*.
Mueller, H. R., and Hack, P. Producing crystalline calcium oxide in an electric arc furnace, P (8) 218*a*.
Mueller, J. See Konopicky, K.
Mueller, K. P. See Koltermann, M.
Mueller, K. P., Koltermann, M., and Gruner, K. Crystallization of lithium silicate melts under different cooling conditions, (9) 249*b*.
Mueller, P. See Schwiete, H. E.
Mueller, P. F. See Wondratschek, H.
Mueller, R. F. See Sharma, T.
Mueller, W. Modern pickling facilities for enameling plants, (10) 263*j*.
Mueller, W. M. (editor). Energetics in Metallurgical Phenomena (Vol. II) Proceedings of Seminar, University of Denver, 1963, B (7) 204*d*.
Mueller-Neuglueck, H. H., and Hermann, P. Determination of the silicon carbide content of refractory materials, (7) 186*i*.
Mueller-Warmuth, W. Magnetic resonance in glasses (II) results, (4) 94*e*.
Muguruma, J., Mae, S., and Higashi, A. Void formation by nonbasal glide in ice single crystals, (9) 258*a*.
Muir, D. Method of making finely divided silicon dioxide, P (2) 47*i*.
Muir, H. See Lee, K.
Muirhead, J. Electrophoretic deposition, (5) 119*i*.
Mukaibo, T., Naito, K., Sato, K., and Uchijima, T. Heat of formation of U_3O_7, B (6) 175*f*. Measurement of the specific heat of uranium carbides above room temperatures, B (6) 175*c*.
Mukerji, J. Structure of silicates in the liquid state, (7) 202*j*.
Mukherjee, B. Clay minerals in ancient sediments of extra-Peninsular region, India, B (2) 56*e*.
Mulfinger, H. O. Physical and chemical solubility of nitrogen in glass melts, (10) 265*j*. See Scholze, H.
Mulfinger, H. O., and Franz, H. Bonding of chemically dissolved nitrogen in oxide glass melts, (1) 3*i*.
Mulfinger, H. O., and Scholze, H. Solubility and diffusion of helium in glass melts (I) solubility; (II) diffusion, (9) 234*e*.
Mulford, R. N. R., Ford, J. O., and Hoffman, J. G. Volatility of plutonium carbide, B (6) 175*c*.
Mulisch, E. Granulators in the heavy clay industry, (8) 214*c*.
Mullen, W. G., and Dolch, W. L. Periscope-type strain gage measures creep in immersed specimens, (6) 162*a*.
Muller, F., Kohlhass, B., and Winners, L. Method and apparatus for heating and burning cement raw material containing alkali, P (1) 3*a*.
Muller, M. W. Pulsed ferromagnetic microwave generator, P (8) 221*j*.
Muller, W. Method and apparatus for making magnetically anisotropic permanent magnets, P (11) 306*a*.
Mullington, P. See Oliver, J.
Mullins, W. W. See Nichols, F. A.
Mulroy, B. Technical control of bone china, (10) 276*d*.
Multer, R. K. Impact testing of ceramics, (6) 162*d*.
Mumford, E. H. Double parison transfer means, P (2) 33*g*. Invert mechanism on glass forming machine, P (5) 123*d*. See Irwin, G. W.; Kawecka, J. J.
Mundell, J. M. See Corbin, D.
Munekata, E., Suehiro, K., Ueda, T., and Kobayashi, T. Process for producing iron oxide with a low silica content, P (5) 133*j*.
Munley, F. A. See Peiser, H. S.
Munsterberg, H. Ceramic Art of Japan—A Handbook for Collectors, B (1) 26*a*.
Munters, C. G. Method of heat treating an inorganic fibrous body for moisture transfer and/or heat, P (4) 101*e*.
Mura, T. See Dundurs, J.
Murakami, K. See Tanaka, H.
Murasik, A. See Bertaut, E. F.
Murasik, A., and Roult, G. Magnetic structure of Mn_2FeO_4 by neutron diffraction, B (2) 55*j*.
Murata, Y. Single multielectrode electron tube having a disk shaped ceramic stem with a recessed portion in one face thereof, said recess portion having a metal layer thereon, P (11) 308*c*.
Murata, Y., and Labosky, R. Bonded boron nitride, P (6) 158*f*.
Murata Mfg. Co., Ltd. Capacitor comprising an *n*-type semiconductor metallic oxide and a layer of compensated material, P (10) 277*j*. Hybrid ceramic filters having two-terminal piezoelectric resonator in shunt with three-terminal piezoelectric resonator to improve harmonic rejection, P (6) 159*j*.
Murav'ev, V. I., Drits, V. A., and Zarubitskaya, A. N. Decomposition of phlogopite by electrodialysis, B (2) 56*f*.
Murawsky, F. See Schubert, M.
Murdoch, A. W. Ceramic coatings on metal, (I, II), (4) 91*b*. Effect of washing materials on enameled surfaces, (3) 59*i*. See Hoens, M. F. A.
Murley, E. M., Jr. Apparatus for inspecting hollow syringe cartridges and the like, P (10) 267*j*. See Mathias, B. B.
Murphy, E. Radio-frequency dielectric ovens, P (8) 213*i*.
Murphy, P. J. Method and composition for decorating glass-ceramics, P (10) 268*g*.
Murray, F. L. See Sikina, T. V.
Murray, G. T. Electron beam heating gains impetus as a research tool, (5) 135*i*. See Mountvala, A. J.
Murray, K. A., and Maritz, J. F. Spectrographic determination of tin in low-grade tin ores, (11) 310*e*.
Murray, M. J. See Atkins, A. G.
Murray Corp. of America. Automatic production of pressed ware from plastic material, P (2) 40*a*. Bathtub construction, P (7) 179*c*. Removal of scrap material incident to pressed ware production, P (5) 127*g*.

Murthy, H. P. S., Kundra, M. C., and Rao, H. V. B. Comparative study of hydraulic press and pneumatic hammer as brick forming machines, (2) 35*h*. Comparative study of some methods of compaction of mixes of dry-press consistency, (2) 35*i*. Effects of pressure and the influence of bonds on the compaction of granular ceramic powders, (2) 39*i*.
Murthy, M. K. Thermal expansion of some alkali phosphate glasses, (6) 149*i*.
Murthy, M. K., and Scroggie, B. Properties of glasses in the system B_2O_3–GeO_2, (6) 148*e*. Properties and structure of glasses in the system M_2O–Al_2O_3–GeO_2 (M = Li, Na, K), (2) 32*f*.
Murthy, M. K., and Westman, A. E. R. Constitution of mixed-alkali phosphate glasses (IV) constitution of lithium-cesium phosphate glasses, (7) 179*i*.
Murthy, P. R., and Patel, C. C. Thermal studies on hydrates of zirconyl, thorium, and uranyl perchlorates, (8) 228*b*.
Muschelknautz, E. Process and apparatus for determining the distribution of grain size in powders, P (1) 17*b*.
Mushenko, E. S. See Palkin, A. P.
Music, E. G. See Martin, G.
Musschoot, A., and Thomson, M. G. Stepped [vibratory] screens, P (5) 131*b*.
Myasnikov, K. A. Selection of a flowsheet for high-output machine-tank and cutting departments, (5) 121*a*.
Myer, J. H., and Gromek, M. T. Device for slicing crystalline material, P (11) 305*f*.
Myers, R. E. Two-stable high-resolution electron-actuated resists, P (11) 308*d*.
Myers, R. L. Enamel fish scale control on decarburized enameling sheets, (6) 145*c*.
Myerson, R. L. Methods of making dental restorations, P (7) 191*a*.
Myerson Tooth Corp. Methods of making dental restorations, P (7) 191*a*.
Myhre, O. A. C. von. Ceramic receptacle having rubber impact layer, P (8) 219*c*.
Myl, J. See Adametz, O.
Myles, J. W. See Carley-Macauly, K. W.
Myl'nikova, I. E. See Bokov, V. A.
Mylroie, C. A. See Duffek, E. F.

Naake, H. J. Method of joining thermoelectric elements and thermocouple, P (7) 193*b*.
Nabatova, L. V. See Maslov, V. N.
Nabiullin, F. H., Adamjan, R. G., Gertsik, E. M., Ushko, U. Y., Dolgov, V. M., Tselov, J. N., and Sharanov, V. P. Device for scoring of crystalline semiconductor materials, P (3) 73*a*.
Nador, B. See Koranyi, G.
Nag, B. B. See Kumar, S.
Nagami, K. Hot repair of open-hearth furnace roof by dry gunning, (10) 271*e*. Lifespan of open-hearth roof and its relation to pig-iron mixing ratio, proportions of cold pig iron, oxygen, and heavy oil, (3) 68*c*. Results of service tests on SiC nozzle, (3) 69*a*. Results of using graphite and SiC brick placed beneath ingot molds in top casting, (1) 10*d*.
Nagano, K. See Ouchi, H.
Nagao, H. See Bortz, S. A.
Nagasaki, S., and Nishikawa, Y. Properties of dolomite clinker and its manufacture, (10) 272*h*.
Nagase, K. See Hayakawa, S.; Nitta, T.
Nagel, R. W. See McMurtrie, G.
Nagy, K. See Balla, B.
Naidich, Yu. V., and Kolesnichenko, G. A. Investigation of the wetting of diamond and graphite by molten metals and alloys (III) wetting of diamond crystals, (1) 1*e*.
Naidich, Yu. V., Lavrinenko, I. A., and Eremenko, V. N. Role of capillary phenomena in densification during sintering in the presence of a liquid phase, (9) 255*a*.
Naito, K. See Gotoo, K.; Mukaibo, T.
Naka, K. See Morita, K.
Naka, S. See Mizuno, M.
Nakagawa, Y. See Maekawa, S.
Nakahara, K. Rotary kiln and method of freeing it of a fire ring therein, P (3) 77*k*.
Nakajima, H. Report on the merits of unfired ladle brick, (1) 10*b*.
Nakajima, K. See Weissmann, S.
Nakajima, N. Operation of 1300-ton hot metal mixer, (7) 187*e*.
Nakamichi, T., and Yamamoto, M. Antiferromagnetic magnetostriction in CoO and NiO single crystals, (4) 109*j*.
Nakamura, H., Kobayashi, T., Tanimoto, S., and Hosono, H. Radiating burner apparatus, P (5) 132*b*.
Nakamura, M. See Tachibana, S.
Nakano, K. See Okuda, H.
Nakano, M. Buffer effects in the spectrochemical analysis of niobium-tantalum mixtures, (6) 161*j*.
Nakase, E. See Matoba, T.
Nakatogawa, T., Ogawa, T., Hara, M., and Okano, S. Silicon rectifying junction structures for electric power and process of production, P (11) 308*c*.
Nakayama, J. Direct measurement of fracture energies of brittle heterogeneous materials, (1) 20*a*.
Nakayama, J., and Ishizuka, M. Experimental evidence for thermal shock damage resistance, (8) 215*k*.
Nakayama, N., Hirota, E., and Nishikawa, T. Hot-pressing of CrO_2, (2) 50*h*.
Nakazato, K. See Kubo, T.
Nakazumi, Y., Suzuki, K., and Yazima, T. Etch patterns in TiO_2 single crystals, (10) 286*a*.
Nalco Chemical Co. Method of preparing ceramic molds, P (3) 70*d*, P (9) 240*e*. Method of producing alumina-coated silica in sol form, P (8) 225*c*. Method of producing a stable titania coated silica sol, P (6) 164*h*. Process for producing extruded xerogels containing magnesia particles, P (10) 274*g*.
Namazu, R., and Honda, T. Method of producing semiconductor dendrites having both planes uniform, P (6) 160*d*.
Nameishi, N. Bonding materials between grains in basic high-fired brick, (10) 270*e*. Experiments made to standardize erosion test methods, (9) 238*g*. Siliceous sleeves produced by the dry process, (1) 10*g*. See Kochi, T.
Nameishi, N., and Inoue, A. Characteristics (chemical composition, mineral structure, and physical properties) of roseki suitable for pouring pit refractories, (3) 65*g*.
Nameishi, N., and Ishibashi, T. ZrO_2-SiO_2-Al_2O_3 refractories for ladles, (9) 239*f*.
Nameishi, N., Ishibashi, T., and Inoue, A. Effect of SiO_2 content of magnesia clinker in magnesia-chrome brick used in an open-hearth roof, (3) 67*a*. Study on erosion of the tar-dolomite brick lining of an LD converter, especially where a perforated lance is used, (8) 216*c*.
Nameishi, N., Ishibashi, T., and Matsumura, T. Performance of open-hearth roof built of basic brick of low silica, iron oxide bonded periclase, (6) 153*i*.
Nameishi, N., Ishibashi, T., and Yoshino, H. Use of gunning refractories for ladle brick maintenance and its results, (8) 216*c*.
Nameishi, N., and Matsumura, T. Structural change of tar-dolomite brick used for a 60-ton oxygen converter, (3) 69*c*.
Nameishi, N., Morita, H., Ishibashi, T., and Matsumura, T. Repair of a hot metal mixer with a dry type gunning mix, (7) 187*c*.
Nandi, D. N. See Banerjee, J. C.
Nangoh, T. See Nishiyama, T.
Nanigian, J. Ribbon thermocouples in the 3000° to 5000°F range, (7) 195*i*.
Nanking Chemical Engineering Institute. See Lu Li Ho Cement Works.
Naoumidis, A. See Stoecker, H. J.
Napara-Volgina, S. G. See Dorf, Z. P.
Napolitano, A. See Spinner, S.
Napolitano, A., Macedo, P. B., and Hawkins, E. G. Viscosity and density of boron trioxide, (1) 6*b*. Wide-range (up to 10^{10} poises) rotating cylinder viscometer, (4) 96*d*.
Naray-Szabo, I. See Albert, J.
Naray-Szabo, I., and Argay, G. Crystal structure of crocoite, $PbCrO_4$, (6) 166*e*. Crystal structure of sodium selenate, Na_2SeO_4, (6) 166*g*.
Nascimento, A. C. See Angeleri, F. B.
Nashiwa, H. See Sugasawa, K.
Nassau, K. Calcium tungstate (IV) theory of coupled substitution, (9) 248*e*. Process for growing neodymium doped single crystal divalent metal ion tungstates, P (9) 244*a*. See Johnson, L. F.; Smith, R. G.; Spencer, E. G.
Nassau, K., and Levinstein, H. J. Ferroelectric behavior of lithium niobate, (10) 286*g*.
Nassau, K., Levinstein, H. J., and Loiacono, G. M. Comprehensive study of trivalent tungstates and molybdates of the type $L_2(MO_4)_3$, (10) 284*e*. Domain structure and etching of ferroelectric lithium niobate—correction, (1) 20*b*.
Nassau, K., and Loiacono, G. M. Calcium tungstate (III) trivalent rare earth substitution, (9) 248*e*.
Nassau, K., Porto, S. P., and Yariv, A. Optical maser comprising the active medium $CaWO_4$: Pr, P (9) 243*i*.
Natansohn, S. See Levine, A. K.
Natanson, M. E. See Kostetskii, B. I.
Natco Corp. Apparatus for filling structural clay tile, P (4) 98*g*.
Natelson, S. Apparatus for the automatic chemical sequential treatment and analysis of small quantities of material, P (2) 45*h*.
Nath, P. See Douglas, R. W.
Nath, P., and Douglas, R. W. Cr^{3+}-Cr^{6+} equilibrium in binary alkali silicate glasses, (3) 60*f*.
Nath, P., Paul, A., and Douglas, R. W. Physical and chemical estimation of trivalent and hexavalent chromium in glasses, (3) 61*i*.
Nathan, M. I. See Dill, F. H.
Nathanson, L. Frequency selective coupling device having ferrite elements biased to different resonant frequencies, P (11) 306*f*.
National Beryllia Corp. Burner throat, P (2) 46*c*. Insulating heat-sink holder for transistors, P (7) 193*e*. Method of producing high density ceramic articles, P (4) 101*g*.
National Lead Co. Alkali metal titanium phosphate glass, P (4) 96*e*. Ceramic capacitor, P (11) 305*b*. Frit compositions for vitreous enamels, P (2) 30*f*. Method for producing titanium dioxide of pigment quality, P (8) 225*d*. Process for the production of zirconia, P (8) 225*g*. Synthetic silicate minerals, P (8) 225*i*. See Gulf Research & Development Co.
National Research Corp. Crucible coated with reaction product of aluminum and boron nitride coating, P (7) 188*j*. Crucible externally lined with filamentary carbon, P (4) 100*j*. Process of making niobium stannide superconductors, P (2) 42*d*. Superconductor, P (6) 161*a*.
National Research Council. Process for producing readily dispersible SiO_2 and Al_2O_3 solids, P (3) 79*a*.
National Research Development Corp. Electron image intensifying devices, P (5) 128*c*. Heat resisting material and method for making it, P (2) 37*h*, P (3) 73*d*.
National Semiconductor Corp. Semiconductor device, P (4) 106*g*.
Naujokas, A. A. Method of making lenses, P (7) 184*g*.
Nauroth, P., and Becker, A. Method of producing finely divided siliceous pigments, P (5) 133*h*.
Nauta, C. J. Mixing devices, P (11) 309*b*.
Nautamix, N. V. Mixing devices, P (11) 309*b*.
Navarro, J. M. F. See Fernandez Navarro, J. M.
Navarro Alvargonzalez, J. M. Mechanical properties of bentonites, (2) 50*a*.
Navias, L. Inhomogeneous magnesia-alumina optical lens, P (1) 6*h*.
Navratiel, H. Flow properties of granular dry-press powders, (8) 219*c*.
Nawapong, P. See Rundqvist, S.
Nayak, U. N. High temperature oil-fired ceramic kiln, (2) 46*e*.
Naymik, D. A. Method of making integrated semiconductor devices, P (5) 129*d*.
Nazarchuk, T. N., and Mekhanoshina, L. N. Oxidation of boron carbide, (3) 68*a*.
Nazarova, N. A. See Borisov, B. I.
Neal, J. P. Froth flotation of micaceous minerals, P (2) 47*f*.
Neant, D. See Duc, X. Nguyen.
Neary, F. X. See Broderick, J. P.
Nechiporenko, E. P. See Glushko, P. I.; Ivanov, V. E.; Verkhorobin, L. F.
Nechtschein, M., and Kester, T. Variation with temperature of the electronic paramagnetic resonance signal of neutron irradiated polycrystalline graphite, (4) 114*h*.
Neckenbuerger, E. Ferrite devices for the modulation and switching of microwaves, P (11) 306*c*.
Nedbal, I. Refractoriness of concrete (I), (2) 29*e*; (II), (9) 231*a*.
Nedoma, J. Graphical method for indexing X-ray powder diffraction patterns of hexagonal and tetragonal substances, (7) 195*a*.
Neely, James E., and Ernsberger, F. M. Absence of devitrification at bubble surfaces in soda-lime glasses, (8) 208*f*.
Neely, Joseph E., Martinet, J. R., and Bowman, J. Refractory, P (10) 274*i*.
Neely, J. R., and Knapp, W. J. California wollastonites, (2) 46*h*.
Neil, D. L. Method and product for the disposal of radioactive wastes, P (7) 190*j*.
Neimark, L. A., Kittel, J. H., and Crothers, C. C. Irradiations of PuC and UC-PuC, B (6) 172*b*.
Neisser, K. E., Jr. See Mones, A. H.
Nekhoroshev, A. V. Hydrothermal and pneumatic processing of building materials, (4) 98*g*. New principles of the thermal treatment of clays, (11) 312*f*. Processes of cementation (hardening) in the systems silica–water and clay–water, (2) 29*a*.
Nekrasov, M. M., and Poplavko, Yu. M. Ferroelectric properties of solid solutions in the ternary system $Ba(Ti,Zr,Sn)O_3$, (4) 111*j*.
Nelson, C. E. Burner throat, P (2) 46*c*.
Nelson, E. H. See Mason, R. A. L.
Nelson, G. C. Ceramics—A Potter's Handbook, B (10) 292*d*.
Nelson, J. S. See Buckley, F. T.
Nelson, J. T. See Arnold, S. R.
Nelson, O. L., and Anderson, D. E. Hot-electron transfer through thin-film Al-Al_2O_3 triodes, (5) 137*d*. Potential barrier parameters in thin-film Al-Al_2O_3-metal diodes, (5) 128*e*.
Nelson, R. F. See Rindner, W.
Nelson, R. M. See Block, A.
Nelson, R. S. Grinding wheel, P (11) 293*f*.
Nelson, S. H. See Wanlass, C. L.
Nemchenko, V. F. See L'vov, S. N.
Nemec, F. See Bouvier, G.
Nemecz, E., Varju, G., and Barna, J. Allevardite from Kiralyhegy, Tokaj Mountains, Hungary, B (2) 56*c*.
Nemeshegyi, G. See Inczedy, J.
Nemkova, O. G. See Fedoseev, I. V.
Nemnonov, S. A., and Kolobova, K. M. Atomic interaction and inner electron state of iron atoms in silicides, (11) 313*i*.
Nemoto, H. Actual results given by zircon brick in open-hearth furnace ladles, (9) 237*i*.
Nemoto, Y. See Matsumoto, Y.
Neretina, A. Ya. See Titkov, N. I.
Nesbitt, J. D. Self-stabilizing combustion apparatus, P (11) 311*j*.
Nesbitt, J. D., and Kohn, H. M. Heating apparatus, P (1) 6*e*.
Nesbitt, R. W. Determination of magnesium in silicates by atomic absorption spectroscopy, (11) 309*f*.
Neshpor, V. S., and Barantseva, I. G. Heat conduction of molybdenum silicides, (7) 199*j*.
Neshpor, V. S., and Ordanyan, S. S. Shear moduli of some transition metal silicides, (9) 255*i*.
Neshpor, V. S., and Samsonov, G. V. Rhenium disilicide as a new high-melting point semiconductor, (11) 319*b*.
Ness, H. H. Method and means for producing chromatographic capillary columns, P (6) 150*b*.
Nessim, A. A., and Wajda, R. L. Rheology of cement pastes and fresh mortars, (1) 3*b*.
Nesterov, V. N. See Isakova, R. A.
Nestor, O. H. See Kiffer, A. D.
Nethercot, A. H., Jr. Electrooptic light coupling of optical fibers, P (1) 6*i*.
Netto, J. E. P. See Paiva Netto, J. E.

Neuhaus, A., and Heide, H. Hydrothermal investigations in the system Al_2O_3–H_2O (I) phase boundaries and fields of stability of boehmite, diaspore, and corundum at pressures above 50 atm, (7) 200*i*.
Neuimin, A. D. See Pal'guev, S. F.
Neuimin, A. D., Pal'guev, S. F., and Chebotin, V. N. Reduction of cerium dioxide in oxide mixtures of system CeO_2–La_2O_3 and electrical conductivity of mixtures, B (1) 26*c*.
Neuimin, A. D., Pal'guev, S. F., Strekalovskii, V. N., and Burov, G. V. Investigation of structural components and electrical conductivity and its character in systems ZrO_2–CaO–NiO and ZrO_2–CaO–Fe_2O_3, B (1) 26*b*.
Neuimin, A. D., Yushina, L. D., Ovchinnikov, Yu. M., and Pal'guev, S. F. Nature of electrical conductivity of solid solutions of Bi_2O_3–SrO, B (1) 26*c*.
Neuroth, N. Method of measuring the outside diameter of glass tubing during manufacture, P (10) 269*h*. Quick indicating radiation pyrometer for temperature measurement between 300° and 900°C, (2) 45*i*.
Neuzil, J., and Neuzil, L. Calculation of course of sedimentation in centrifugal field, (7) 197*i*.
Neuzil, L. See Neuzil, J.
Neville, A. H., Jr. Metering and discharging apparatus, P (11) 309*b*.
New Jersey Zinc Co. Flotation of sphalerite, P (5) 133*d*.
Newbury, R. S. See Jackson, D. D.
Newby, J. R. See Heyer, R. H.
Newhall, D. H. High pressure press, P (11) 309*a*.
Newkirk, H. W., and Smith, D. K. Studies on the formation of crystalline synthetic bromellite (I) microcrystals, (2) 51*j*; (II) macrocrystals, (2) 52*e*.
Newkirk, H. W., Smith, D. K., and Kahn, J. S. Synthetic bromellite (III) some optical properties, (11) 319*b*.
Newkirk, J. B. See Austerman, S. B.
Newman, R. C. See Faulkner, E. A.
Newnham R. E. See Caron, L. G.
Newnham, R. E., Caron, L. G., and Santoro, R. P. Magnetic properties of $CaCoSiO_4$ and $CaFeSiO_4$, (6) 168*a*.
Newnham, R. E., Redman, M. J., and Santoro, R. P. Neutron-diffraction study of $Co_2B_2O_6$, (9) 252*b*.
Newton, H. S. Inflatable former for the manufacture of hot tops, P (5) 126*a*.
Newton, R. C. Kyanite-sillimanite equilibrium at 750°C, (5) 138*c*. Thermal stability of zoisite, (1) 25*b*.
Newton, R. G. Some problems in the dating of ancient glass by counting the layers in the weathering crust, (5) 118*d*.
Nichiporenko, S. P. See Kruglitskii, N. N.
Nichiporenko, S. P., Khil'ko, V. V., and Kostenko, E. A. Theoretical principles for compounding ceramic batches, (2) 55*a*.
Nicholls, M. J. See Shennan, J. B.
Nichols, B. D. See Aamodt, R. L.
Nichols, E. F. See Shell, H. R.
Nichols, F. A., and Mullins, W. W. Surface-(interface-) and volume-diffusion contributions to morphological changes driven by capillarity, (5) 141*c*.
Nichols, J. L., and Marples, J. A. C. Investigation of the U-Fe-C and Pu-Fe-C ternary phase diagrams with some observations on the U-Pu-Fe-C quaternary, B (6) 172*a*.
Nicholson, A. See Lynam, T. R.
Nicholson, B. J. Case for replacing the torr by the millibar as a unit of pressure, (9) 248*h*.
Nicholson, D. Variation of surface area during the thermal decomposition of solids, (2) 53*f*.
Nicholson, G. C. Grain growth in magnesium oxide containing iron oxide or titanium dioxide, (2) 50*f*.
Nickel, H. See Stoecker, H. J.
Nickerson, J. D., and Burkert, G. M. Silica pigments from fluosilicic acid, P (11) 312*j*.
Nickle, A. G. See Braunwarth, V. A.
Nicodemus, D. S. See McLean, D. A.
Nicolas, J. See Fleurence, A.; Vassiliev, A.
Nicolle, J. See Kiehl, J. P.
Nicollian, E. H., and Goetzberger, A. MOS conductance technique for measuring surface state parameters, (10) 288*a*.
Niebuhr, V. G. See Galer, R. E.
Nieder-Vahrenholz, H. G. See Schaefer, H.
Niehues, K. J. See Schaefer, H.
Niekerk, J. N. van. See Plug, C.
Nielsen, A., Bergh, S. S., and Troberg, B. Catalyst for the synthesis of ammonia and method of producing, P (6) 154*a*.
Nielsen, J. W. Method of making a microwave element, P (3) 73*b*. See Adams, I.; Leo, D. C.
Nielsen, J. W., and Zneimer, J. E. High power microwave components, P (4) 104*j*.
Nielsen, K. E. C. See Hansen, T. C.
Nielsen, S. See Savage, J. A.
Nielsen, T. H. See Leipold, M. H.
Niemitz, G. Stationary circular contact cooler for calcined lime, P (11) 295*c*.
Niemyski, T. See Mierzejewska, S.
Nienhuis, W. F. See Gier, J. de.
Niepenberg, H. P. Use of natural gas in the ceramic industry, (8) 224*c*.
Niesel, K. See Hennicke, H. W.
Niesen, R., and Prible, G. High alumina plastic refractory installed by high frequency vibration, (8) 215*i*.
Nightingale, H. C. Piezoelectric crystal, P (4) 106*a*.
Nijman, J. Tumbling mill, (6) 161*d*.
Nikitin, B. N. See Alakin, A. I.
Nikolaev, N. A. See Andryukhina, T. D.
Nikoll, R. Shaping method and apparatus for forming panel which exhibits optical effects, P (5) 124*b*.
Nikonov, N. P. See Yudin, N. A.
Nilsson, U. I. Pulsed oil feeding system for industrial furnaces, P (2) 46*c*.
Nimura, I. See Hase, B.
Ninomiya, H. See Yoshida, H.
Nippon Electric Co., Ltd. Ceramic sealed window, P (1) 6*f*. Method of heat treating semiconductor devices to stabilize current amplification factor characteristic, P (4) 105*f*. Method of making semiconductor devices by forming a damage layer on a surface of a semiconductor body and then alloying through the damage layer, P (5) 129*f*. Method of manufacturing heterojunction elements, P (10) 279*a*. Multiple heterolayer composite semiconductor device, P (11) 307*e*. Semiconductor devices, P (10) 279*e*.
Nippon Gaishi Kaisha, Ltd. Method of producing beryllium oxide from beryllium containing ores, P (5) 133*f*.
Nippon Sheet Glass Co., Ltd. Device for polishing glass, P (5) 122*d*. Machine for chemically polishing glass, P (4) 97*b*.
Nippon Telegraph & Telephone Public Corp. Method for producing thin titanoceramic film, P (3) 73*j*.
Nishida, H. See Minowa, S.
Nishigaki, S. See Kida, K.
Nishikawa, T. See Kubota, B.; Nakayama, N.
Nishikawa, Y. See Nagasaki, S.
Nishimura, Y. See Kato, S.
Nishino, T., and Moteki, K. Studies on the sintering of MgO (III) reactions between lime and chromium oxide, (4) 113*g*.
Nishiwaki, M. See Morita, S.
Nishiyama, G. See Matsumoto, H.
Nishiyama, T., Nangoh, T., and Sono, K. Fabrication of exothermic self-hardening mold, P (2) 37*e*.
Nishizawa, Jun-Ichi. See Sukegawa, T.
Nissen, H. U. See Bambauer, H. U.
Nisso Seiko Kabushiki Kaisha. Grinding mill, P (4) 109*f*.
Nitsche, J. E. Ceramic burner plate, P (8) 224*e*.
Nitsche, R. Crystal growth and electro-optic effect of bismuth germanate, $Bi_4(GeO_4)_3$, (3) 80*j*.
Nitschke, N. C. See McMaster, H. A.
Nitta, S. See Hayashi, T.
Nitta, T. See Hayakawa, S.
Nitta, T., Nagase, K., and Hayakawa, S. Electroless nickel-phosphorus alloy electrode for semiconductive barium titanate ceramics, (9) 242*i*.
Nitta, T., Nagase, K., Hayakawa, S., and Iida, Y. Formation and properties of barium metalplumbate, (1) 21*c*.
Nitti, D. J. See Grodkiewicz, W. H.
Nitzsche, S., Wick, M., and Hubal, K. H. Method of applying protective silicone rubber tape covering layer to hollow glass articles, P (4) 97*j*.
Niu, Yen-nan, and Lin, Jih-tong. Precise mercury volumenometer, (6) 162*d*.
Niwa, S. Study of high purity magnesia brick used in a 2-ton electric arc furnace wall, (10) 272*f*.
Niwa, S., and Haghihara, J. Relations between the thermal conductivity of SiC stopper head and corrosion of the stopper rod, (3) 68*j*.
Niwa, S., Konishi, Y., and Matsumura, I. Results of using high alumina brick for the roof of a two-ton electric arc furnace, (8) 216*j*.
Niwa, S., Matsumura, I., and Hayashi, Y. Durability of ladle brick with special reference to bottom brick, (7) 186*e*. High Al_2O_3 brick used as ladle lining for high Mn steel (I, II), (4) 99*c*.
Niwa, S., and Suga, O. Results of service tests on tarred sleeves, (1) 10*c*.
Nixdorf, J. See Eberle, L.; Janes, S.
Noack, R. L. Method of making magnetic ferrite sheet with embedded conductors, P (7) 193*e*.
Noakes, M. L. Preliminary investigations on the electron-beam melting of UC, B (6) 172*g*.
Noble, J. V. Techniques of Painted Attic Pottery, B (9) 259*e*.
Noble, M., and Ruelle, L. A. Preparation of purified aluminum nitride, P (7) 189*e*.
Nobles, E. L. See Lightner, L. F.
Nobles, E. L., and Cook, D. C. Properties and performance of enameling clays, (4) 91*j*.
Noda, T. See Otsubo, K.
Noel, J. A. Coatings, P (1) 13*f*.
Nogard, G., and Urban, R. Method and apparatus for removing impurities in manufacture of glass, P (3) 63*h*.
Noguchi, T. See Mizuno, M.
Noguchi Institute. Process for producing iron oxide with a low silica content, P (5) 133*j*.
Nolan, R. W. See Arthur, E. P.
Nollet, P. See Burko, J.
Nomura, S. See Gotoo, K.; Kawakubo, T.
Nomura, S., and Kawakubo, T. Phase transition in the $Sr(Ni_{1/2}W_{1/2})O_3$–$Ba(Ni_{1/2}W_{1/2})O_3$ system, (10) 289*a*.
Nomura, Y., and Tobisawa, S. Anomalous paramagnetic susceptibility of shocked ZnS phosphor, (10) 283*h*.
Nonamaker, F. C. Rare-earth oxides for polishing glass, P (10) 269*j*.
Nopco Chemical Co. Process of preparing finely divided silicas of varied properties, P (10) 283*f*.
Nordberg, M. E. Method of shaping a glass article, P (1) 7*c*. See Elmer, T. H.
Nordberg Mfg. Co. Bowl liner for gyratory crusher, P (5) 133*c*. Centrifugal unit for crusher and method, P (1) 18*c*. Crusher clearing system, P (11) 312*e*. Seal for gyratory crushers, P (11) 312*j*. Yielding bowl locking ring for crushers, P (11) 313*a*.
Nordquist, C. E., and Ross, M. O. Muffler construction, P (10) 263*i*.
Nordquist, C. E. Snow tire and insert therefor, P (11) 303*i*.
Noreika, A. J. See Evans, T.
Norestam, R. Scandium manganese(III) oxide, a compound isotypic with $LuMnO_3$, (2) 51*b*.
Norgard, F. C. See Enslen, R. H.
Norman, V. See Whaley, T. P.
Norreys, J. J. Compressive creep of uranium monocarbide, B (6) 172*a*.
Norreys, J. J., Wheeler, M. J., and Gillam, E. Preparation and properties of uranium sesquicarbide, B (6) 171*i*.
North, J. M. Skull melting of plutonium-bearing carbides, B (6) 172*f*.
North American Aviation, Inc. Glass bonded dry film lubricant, P (6) 149*i*.
North American Mfg. Co. Fuel [gas] burner with adjustable nozzle, P (5) 132*g*.
North American Philips Co., Inc. Apparatus for evacuating an electric filament lamp or discharge tube through a protruding exhaust tube and for sealing off the exhaust tube, P (5) 128*f*. Apparatus for melting glass with charging means, P (7) 182*i*. Apparatus for working glass tubing, P (4) 96*j*. Cathode ray tube and method of making, P (9) 235*g*. Device for bending a straight tube into a circular shape, P (2) 33*f*. Device comprising a III–V compound semiconductor body and at least one contact to the body, P (9) 243*b*. Device for floating zone melting, P (5) 128*b*. Device for treating semiconductor materials by melting, P (9) 243*b*. Devitrified glass-to-metal compression seal, P (3) 63*d*. Electric incandescent lamp, P (7) 192*f*. Electric lamp, P (9) 243*c*, (10) 278*d*. Ferrite devices for the modulation and switching of microwaves, P (11) 306*c*. Fuel element for use in nuclear reactors, P (8) 217*b*. Gas-filled electric incandescent lamp, P (5) 128*f*. Method of applying an alkaline earth metal getter, P (10) 278*e*. Method and device for the mass production of glass rod and glass tube, P (2) 34*d*. Method and device for sealing together glass parts, P (11) 298*i*. Method of improving the electrical properties of a gallium arsenide semiconductor device, P (8) 221*i*. Method of joining metal component parts with glass leading-in members, P (1) 14*i*. Method for making lithium nickel ferrite having a substantially rectangular hysteresis loop, P (4) 105*i*. Method of making mercury-doped germanium semiconductor crystals, P (11) 306*i*. Method of manufacturing a bulb [from glass tubing], P (1) 7*b*. Method of manufacturing ceramic articles by sintering preformed bodies and the articles, P (7) 196*b*. Method of manufacturing compact bodies of manganic oxide and/or iron oxide and bodies obtained, P (8) 221*c*. Method of manufacturing display screens for cathode-ray tubes, P (3) 73*d*, P (4) 105*b*. Method of manufacturing magnetic heads with bonding gap-filling materials, P (7) 193*f*. Method of manufacturing a photoconducting device, P (9) 243*a*. Method of manufacturing photoelectric semiconductor devices, P (9) 243*c*. Method of manufacturing reinforced cathode-ray tube for television display, P (3) 64*i*. Method of manufacturing semiconductor devices, P (5) 129*g*, P (11) 306*i*. Method of preparing a cadmium oxide photoconductor, P (8) 221*d*. Method for preparing manganese-zinc-ferrous ferrite, P (8) 221*d*. Method of producing ceramic materials, P (4) 105*b*. Method of producing monocrystals of a semiconductor via the vapor phase, P (2) 42*f*. Method of providing alloy contacts on semiconductor bodies, P (4) 105*f*. Method of providing light diffusing coatings on quartz and the coated objects, P (4) 97*f*. Method of splitting nonmetallic brittle materials and devices for carrying out such methods, P (2) 47*j*. Method of treating quartz for optical use, P (3) 64*c*. Process for making MnAl permanent magnet having tetragonal phase, P (10) 279*h*. Semiconductive material, semiconductive and thermoelectric devices, P (7) 194*d*. Semiconductor devices and methods for their manufacture, P (3) 74*g*. Sodium vapor lamp having a tin oxide coating, P (3) 64*j*. Temperature-independent transducer, P (1) 15*b*. Tungsten filament lamp comprising hexafluoride gas at partial pressure not exceeding 10 torrs, P (10) 279*h*. Vanadium-containing ferrimagnetic material, P (1) 15*g*. Zener diode, P (8) 222*b*.
Northover, W. R. See Dewald, J. F.; Pearson, A. D.
Northrop, D. A. See Goldsmith, J. R.
Norton, R. W. Stopcock and plug retainer therefor, P (11) 299*h*.
Norton Co. Apparatus for making magnesium oxide crystals, P (7) 188*g*. Coated abrasives, P (10) 261*f*. Electrode holder for high temperature heating apparatus furnace, P (7) 195*j*. Equipment for burning refractory products, P (4) 108*g*. Grinding wheel, P (11) 293*f*. Internal reinforcement of molded rotatable articles, P (10) 261*g*. Light porous refractory brick and method, P (9) 240*h*. Metering and discharging apparatus, P (11)

309*b*. Method for use in the manufacture of grinding wheel assemblies, P (10) 261*f*. Mounting means for abrasive products, P (9) 229*g*. Oxide coated articles with metal undercoat, P (9) 232*d*. Process for producing crystalline alumina, P (2) 27*f*. Protected refractory articles, P (7) 189*g*. Reinforcement of molded abrasive articles, P (10) 261*f*. Silicate minerals having increased surface area and absorption properties and method of preparation, P (11) 303*f*.

Norwitz, G. Determination of zirconium in zirconium metal and zirconium powder by use of mandelic acid, (11) 309*j*.

Nosova, Z. A., and Vitokhina, V. M. Zircon colors for glazes, (10) 276*g*.

Novack, T. Method of forming glass ribbons, P (4) 97*b*.

Novack, T., and Schlotzhauer, L. R. Glass delivery method, P (10) 268*a*.

Novikov, G. I. See Sun, Yui-Lin'.

Novikov, G. I., and Polyachenok, O. G. Investigation of the systems $NdCl_3$–Nd and $PrCl_3$–Pr, (10) 287*g*.

Novikova, T. A. See Tumanov, V. I.

Novosad, J., and Standart, G. Studies on granular materials (IV) calculation of the shaft torque for mixing granular materials, (3) 75*a*.

Novoselova, A. V. See Aslanov, L. A.; Popovkin, B. A.; Tsyun'khua, L.; Zlomanov, V. P.

Novotny, J. See Spurny, Z.

Novozhilova, L. D. See Demkina, L. I.

Nowak, W. See Kakol, M.

Nowotny, H. See Wittman, A.

Nozdracheva, T. F. See Vorob'eva, O. V.

Nozdracheva, T. F., and Vorob'eva, O. V. New types of metal oxide films, (1) 4*i*.

NRA, Inc. Method of preparing thin films on substrates by an electrical discharge, P (6) 160*b*.

Nuclear Corp. of America. Resonance electroluminescent display panel, P (6) 160*d*.

Nuclear-Chicago Corp. Industrial-process-type measurements employing gamma-ray backscattering, P (11) 311*e*.

Nuclear Materials and Equipment Corp. Classification method and apparatus, P (3) 77*b*, P (11) 311*c*. Method of dissolving ceramics containing beryllia, P (1) 11*i*. Method of producing uranium carbide, P (7) 188*j*.

Null, M. R. See Lozier, W. W.

Nunn, J. C. Desiccation of electronic enclosures using boron nitride hot sealing method, P (6) 159*b*.

Nunome, K. See Hayakawa, K.

Nurse, R. W., Welch, J. H., and Majumdar, A. J. CaO–Al_2O_3 system in a moisture-free atmosphere, (2) 48*j*.

Nuttall, R. See Feder, H.

Nutting, J. Electron microscope and its application to the study of metals, B (6) 173*h*.

Nuttle, R. G. See Berstein, G.

N. V. Koninklijke Nederlandsche Glasfabriek Leerdam. Glass furnace construction with an eduction tunnel which is provided with a vault, P (8) 212*a*.

N. V. Philips' Gloeilampenfabrieken. Ceramic bodies for piezoelectric applications, P (7) 192*a*. Ceramic products, their production, and apparatus therefor, P (10) 282*g*. Photoconductor, P (10) 279*e*. Photoconductor based on chalcogenides, P (10) 279*f*. Process for making ceramic bodies for piezoelectric use, P (7) 194*b*. Process for making a monocrystalline body, P (10) 276*d*.

N. V. Vereenigde Glasfabrieken (United Glassworks). Gas burner, P (11) 311*f*. Method of making hollow glassware with a stem and a foot, P (11) 299*b*. Package for glasses or such fragile objects, P (1) 7*b*.

Nyankovskaya, R. N., Guseva, A. D., Yaroslavtseva, I. A., Kalinkina, I. F., and Mazilova, N. V. Quaternary reciprocal system of the fluorides, bromides, and carbonates of sodium and potassium, (1) 24*b*.

Nystrom, E. H. B. Production of mineral fibers, P (9) 237*d*.

Nytronics, Inc. Electrical component and method of manufacture, P (10) 278*e*.

Oakes, D. T. See Harryman, P. D.

Oakes, E. W. Abrasive tester, P (4) 108*b*.

Oakley, O. H. Design considerations for manned deep-sea vehicles, (2) 54*i*.

Obenauer, K. Observations on Sieburg stoneware, (1) 1*j*.

Obenshain, G. R. Method of decorating glass bottles, P (10) 268*h*.

Oberholtzer, A. V. Impregnation and coating with split-offs of vermiculite and products thereof, P (11) 296*d*.

Oberlies, F. See Pohlmann, G.

Oberlin, A. See Mering, J.; Tchoubar, C.

Oberschmidt, L. E. Brickor—model of progress and diversification, (4) 98*f*. Findlay refractories—a study in craftsmanship, (8) 215*h*. Lavino adds tar impregnating facility to MgO product line, (8) 215*f*. Research at General Refractories pays off, (4) 99*e*. Shale fines reclaimed at lightweight aggregate plant, (4) 98*f*. Washington Brick—a study on oil firing, (8) 224*d*. World's first mechanical face setting at Midland Brick, (8) 214*d*.

Oblival'nyi, F. A., Khodolei, V. I., and Valagura, I. A. Conveyor for transporting and cutting plate glass, (10) 264*e*.

O'Brien, N. R. See Smith, W. H.

O'Bryan, H. M., Jr., Monforte, F. R., and Blair, R. Oxygen content of nickel ferrites at 1300°C, (1) 13*g*.

O'Bryan, H. M., Jr., and O'Connor, P. B. Growth of rare earth aluminum garnets by floating zone technique, (7) 191*h*.

Obukhov, A. P. See Isaeva, E. A.

Obukhovskii, Ya. A. See Bidnaya, D. S.; Sysoev, L. A.

Oceanic Process Corp. Process for producing titanium dioxide concentrate and other useful products from ilmenite and similar ores, P (8) 225*g*.

Ochiai, T. See Tsuzuki, K.; Watanabe, H.

O'Connell, T. B., Badger, A. E., and Shamp, D. E. Compositions for sealing holes in glass, P (2) 33*e*.

O'Connell, T. B., Carney, D. E., Shamp, D. E., and Gartz, C. A., Jr. Process for treating glass furnace, P (6) 151*a*.

O'Connell, T. B., Swift, H. R., and Mambourg, J. E. Process for preventing scale in glass furnace, P (5) 124*d*.

O'Connor, J. R. Quenching of Dy^{2+} fluorescence by Y^{3+} in CaF_2:Dy^{2+} lasers, (1) 24*e*.

O'Connor, J. R., and Hilton, R. M. Effect of Y^{3+} on the reduction of Sm^{3+} in CaF_2, (1) 20*g*.

O'Connor, P. B. See O'Bryan, H. M., Jr.

O'Connor, T. E. Process for the production of metal borides and nitrides, P (9) 241*e*. Process for the production of [turbostratic] boron nitride, P (6) 155*i*. See Thomas, J., Jr.

O'Connor, T. L., and McRae, W. A. Colloidal silicon carbide and method of making, P (5) 125*h*.

Oczos, K. Grinding of low voltage insulators, (8) 219*d*.

Oda, J. Method of manufacturing heterojunction elements, P (10) 279*a*. See Matsukura, Y.

O'Dell, L. J. Fabric tube type dust collector and method of operating it, P (2) 43*f*.

Odin, I. N. See Popovkin, B. A.

Odle, H. A. Glare reducing refractor, P (7) 183*a*.

Odler, I. See Gebauer, J.

Odler, I., and Gebauer, J. Cement hydration during heat treatment (I) effect of heat treatment on the degree of hydration of cement and the physical properties of the hardened cement paste, (10) 262*c*.

Odnodvortsev, P. E. See Tsaritsyn, M. A.

O'Donnell, J. M., and Gabor, C. D. Casing brick, P (2) 37*b*.

Oechsli, B. L. See Hartford, W. H.

Oehlrich, K. H., and Schmidt, K. R. Method and apparatus for handling pulverulent material, P (4) 107*a*.

Oel, H. J. Behavior of viscosity of technical glasses between 10^9 and 10^{14} poises, (5) 120*d*. See Konopicky, K.; Krauth, A.; Torkar, K.

Oel, H. J., Lachenmayr, H., and Dietzel, A. Opacification of glazes and enamels with zircon, (6) 156*c*.

Oesterheld, K. A. Method of and apparatus for corrugating sheets of fibrous cement [by vacuum], P (4) 101*a*.

Oesterreichisch-Amerikanische Magnesit A.G. Process for making bricks or fused bodies, refractory and resistant to hydration, based on magnesia, particularly magnesite brick, P (8) 218*d*. Process of making regenerators for industrial furnaces, P (6) 155*g*.

Ogard, A. E. See Leary, J. A.

Ogawa, T. See Nakatogawa, T.; Ohba, H.

Ogden, J. S. See Alexander, C. A.

Oglebay Norton Co. Hot top refractory and/or exothermic unit, P (2) 38*a*. Hot top and seal signal device therefor, P (5) 126*a*.

Ogura, T. Unburned SiC brick used for electric furnace ladle, (3) 69*d*. See Hayami, R.

O'Hair, T. E. See Marsh, H.

O'Hanlon, A. See Winter, L.

O'Hara, S. See Bennett, A. I., Jr.

Ohashi, K. See Okuda, H.

Ohashi, T., and Watanabe, A. Sintering of vanadium dioxide, (2) 51*c*. Temperature dependence of electrical resistivity of VO_2 powder, (10) 291*h*.

Ohba, A. See Makino, M.

Ohba, H. Effects of atmosphere on the results of a slag corrosion test (II) variations in slag corrosion caused by furnace atmosphere, (8) 215*f*. Problems of basic brick from the user's viewpoint and development in the quality of direct bonded brick, (10) 272*g*. Proceedings of the Pouring Pit Refractory Subcommittee Meeting (V) atmosphere created inside a furnace under an erosion test with the submitted slag and the effect of the atmosphere on refractories, (4) 99*h*. Rate of temperature increase in heating furnaces (I) temperature rise after repair and cracks in brick, (7) 187*b*. See Wada, K.

Ohba, H., Hiragushi, K., and Ogawa, T. Changes in slag composition in the ladle during pouring, (7) 185*f*. Comparison of results of X-ray examination of stopper head and its service test, (9) 237*j*. Merits of unburned ladle brick (I), (1) 9*d*; (II) anticorrosive properties, (3) 68*h*. Results of using Japanese nozzles made of American materials (II), (1) 10*e*.

Ohba, H., Hiragushi, K., and Tanaka, M. Velocity of temperature rise in a reheating furnace and expansion rate of the roof brick, (3) 70*a*.

Ohba, H., Hiragushi, K., and Yamamoto, H. Mechanism of change in properties of siliceous refractory mortar in molten iron, (10) 271*i*.

Ohba, H., and Sugita, K. Tests on creep of magnesia brick caused by compressive load at high temperature, (9) 239*a*.

Ohba, H., Sugita, K., and Shimada, K. Effect of high temperature firing at 2000°C on the properties of Cr–Mg brick, (3) 66*j*. Influence of basicity and temperature on the slag penetration of magnesia bricks—study of the reaction of slag on magnesia brick (I), (8) 215*c*. Mechanism of wear of tar-bonded dolomite brick in an electric arc furnace wall, (7) 187*a*.

Ohio Brass Co. Capacitor including aluminum silicate scavenger, P (2) 41*b*.

Ohlson, G. See Elgenstierna, R. M.

Ohlsson, O. W. Apparatus for the measurement of physical quantities, P (3) 77*a*.

Ohmega Laboratories. Capsulated bulb and method of making, P (11) 305*b*. Method of making an electrical device comprising a glass capsule and a wire lead fused therein, P (3) 64*f*.

Ohnishi, H., and Teranishi, T. Crystal distortion in copper ferrite-chromite series, (4) 110*c*.

Ohorodnik, A. See Sennewald, K.

Ohta, C., and Iwaida, T. Reaction of slags with magnesia clinker (92 to 98% MgO), (10) 272*a*. See also Ota, C.

Ohta, Z., Tanemura, F., Tsukino, M., and Katsumata, I. Comparative test on cased bricks with 96 and 92% MgO used in a 30-ton electric arc furnace wall, (10) 270*i*. See also Ota, Z.

Ohtsuka, A. Pigments of titanium-tin and aluminum-chromium spinels, (5) 139*i*.

Oil Shale Corp. Shaped refractory heat exchange bodies and process for making, P (7) 189*j*.

Oinuma, K., and Hayashi, H. Infrared study of mixed-layer clay minerals, (9) 250*j*.

Oishi, J. High temperature determination by a new gas thermometer with constant bulb temperature (I) measuring methods, (4) 107*d*.

Oishi, M. See Ato, Y.

Oizumi, K., Fukuda, M., and Otani, G. Apparatus for blowing glass bulbs, P (3) 62*f*.

Okada, T., Yamadaya, T., and Miyahara, S. Role of cation vacancies in disaccommodation of manganese ferrite, (10) 290*a*.

Okada, Y. See Kawakita, K.

Okada, Y., and Shimamura, G. Comparative study on two types of magnesia-chrome brick made from magnesia clinker (96 and 92% MgO) used in roof of an open-hearth furnace, (10) 270*h*.

Okagaki, H. See Sugawara, M.

Okagaki, H., and Ikuta, Y. Hollow-cathode discharge tube for generating atomic resonance lines, P (5) 128*h*.

Okal'nik, G. N. See Borisov, B. I.

Okamoto, E. Comparative study on the use of fired and unfired SiC ladle brick, (1) 8*e*.

Okano, S. See Nakatogawa, T.

Okano, T. See Ikeda, T.

Okhotin, M. V., and Rybchinskaya, A. V. Crystal optical method for determining defects in glass, (4) 92*b*.

Okhotin, M. V., and Yakovleva, K. P. Temperature of upper limit of crystallization of sodium-calcium-magnesium-aluminosilicate commercial glasses containing 15% Na_2O, (1) 5*f*.

Okorokov, S. D. See Gol'dshtein, L. Ya.

Okubo, S., Tsuzuki, K., Kasuya, Y., and Shimizu, H. Trial use of high-fired magnesia brick in wall of electric arc furnace, (10) 273*e*.

Okuda, F. See Hyodo, S.

Okuda, H., Kato, S., and Iga, T. Formation of mullite from kaolin minerals below 900°C, (4) 111*d*. High-temperature phase changes in kaolinitic clays, (5) 137*b*.

Okuda, H., Ohashi, K., Ishii, E., and Nakano, K. Synthesis of mullite by flame fusion technique, (4) 99*f*.

Okuda, H., Ohashi, K., Nakano, K., and Ishii, E. Photoelastic observation on stress distribution in single crystals of alumina, (10) 289*b*.

Okuda, S. Heat of wetting of clay—effects of drying and heating pretreatments, (4) 111*g*. See Hayashi, T.

Okugawa, T., and Kiwaki, S. Construction of electric AYC furnace roof with high alumina stamping refractory and results of use, (10) 271*c*. Method of gunning for hot repair of hot metal mixer and its effects, (10) 271*j*.

Olah, I. See Abramovici, R.

Olander, D. R. See Rufeh, F.

Olby, J. K. Method of preparing zirconium silicate ceramic stains, P (9) 242*c*.

Olcott, J. S., and Stookey, S. D. Glass body having a semicrystalline surface layer and method of making, P (8) 212*f*.

Oles, A. See Boucher, B.

Oliver, C. S. See Haltner, A. J.

Oliver, D. W., and Slack, G. A. Ultrasonic attenuation in insulators at room temperature, (8) 220*h*.

Oliver, E. M. Factors affecting oxidation and porcelain enamel adherence, (6) 145*e*.

Oliver, J. Mechanical plaster preparation by an automatic vacuum-mixer, (10) 275*i*.

Oliver, J., and Mullington, P. Metal spraying of moldmaker's cases, (4) 102*g*. Preparation of molds for the plastic making of flatware, (5) 127*h*.

Oliver, R. "Hoverkiln"—the rapid firing kiln, (8) 224*f*.

Oliver, T. A., and Cooper, N. W. Depositional environments of Ireton formation, central Alberta, (2) 46*j*.

Ollerhead, R. W., Almqvist, E., and Kuehner, J. A. Method of utilizing nuclear reactions in the study of oxide layers, (9) 252*d*.

Olmos, L. F. See Ferrer Olmos, L.
Olphen, H. van. Thermodynamics of interlayer adsorption of water in clays (I) sodium vermiculite, (4) 114*c*.
Olsen, A. H., and Trutner, D. G. Apparatus for controlled movement of flame heating means to form spiral lamp tubes, P (6) 149*j*.
Olson, D. Rejuvenator for grinding disk, P (6) 143*i*.
Olson, R. H. See Abbott, R. B.
Olson, W. G. See Shobert, W. R.
O'Malley, R. F. See Schumb, W. C.
O'Neill, B. J., Jr., Lapham, D. M., Jaron, M. G., Socolow, A. A., Thomson, R. D., and Hamlin, H. P. Properties and uses of Pennsylvania shales and clays, (11) 312*h*.
Onishi, M. See Asada, C.
Onishi, T. See Masuda, Sen-ichi.
Ono, S. See Yamaguchi, G.
Ono, Y. See Yamaguchi, G.
Onoda Cement Co., Ltd. Apparatus for aging quicklime, P (5) 119*b*. Vertical kiln and a method for preparation of calcined products, P (9) 231*e*.
Onodera, G. C. Semiconductor current limiter, P (11) 307*g*.
Openshaw, P. R., and Shrier, L. L. Gas flow through a porous oxide in relation to oxidation kinetics, (2) 50*c*.
Operhall, T. Graphite shell molds and method of making, P (9) 240*c*.
Oppenheim, U. P. See Frei, J. F.
Optics Technology, Inc. Fiber optics code apparatus, P (9) 235*j*. Photosensitive reader using optical fibers, P (8) 213*d*.
Ordanyan, S. S. See Neshpor, V. S.
Orlandini, K. A., Wahlgren, M. A., and Barclay, J. Solvent extraction studies with a hydrochloric acid-2-ethylhexanol system, (3) 76*g*.
Orlofsky, S. Industrial loads demand 5000°F temperatures, (8) 224*g*.
Orlova, I. G. Mechanism of deformation during heating of unfired corundum ceramics, (10) 288*c*. See Kainarskii, I. S.
Ormsby, W. C., and Bolz, L. H. Microtexture and composition of reaction products in the system kaolin–lime–water, (8) 226*j*.
Orr, C., Jr., and Hendrix, W. P. Method and apparatus for obtaining data for determining surface area and pore volume, P (10) 281*h*.
Orr, J. S. See Davy, J. R.
Orr, L. E., Lytle, W. O., and Saunders, A. E. Coated vehicle glazing closures, P (6) 149*f*.
Orrville Tile Co. Machine for producing and handling elongated tubular items, P (6) 151*f*.
Orth, E. D. See Mendelsohn, L. I.
Osasyuk, V. V. See Grigor'eva, V. V.
Osborn, E. F. See Hamilton, D. L.
Osborn, R. H., and Yost, M. C. Ablation cooled rocket nozzle, P (5) 125*g*.
Osborne, D. W. See Flotow, H. E.
Osborne, M. F., Long, E. L., Jr., and Morgan, J. G. Performance of prototype experimental gas-cooled reactor (EGCR) fuel under extreme conditions, (3) 68*d*.
Osborne, P. S. Shielding concrete and aggregates, P (5) 119*e*.
Osborne Associates. Shielding concrete and aggregates, P (5) 119*e*.
Oshchipkov, F. P. See Botvinkin, O. K.
Oshchipkov, F. P., and Frolov, V. K. Melting of glass ZS-4 in tank furnaces, (5) 121*c*.
Osipov, A. D. See Ivanov, V. E.
Osment, H. E. Method of producing active alumina, P (3) 79*a*. See Lincoln, R. C.
Osment, H. E., and Emerson, R. B. Method for producing active alumina nodules, P (3) 79*b*.
Osment, H. E., and Jones, R. L. Method of producing active alumina and the product, P (4) 109*b*.
Ostapchenko, E. P. See Zhmud', E. S.
Ostapovich, J. See Melichar, J. T.
Osterhoitz, C. E., Moscker, E., and Baab, K. A. Sonic testing of steel ladle nozzles, (2) 37*b*.
Ostis, S. Method of forming an electrical capacitor, P (11) 306*c*.
Ostrach, S., and McConnell, D. G. Melting ablation about decelerating spherical bodies, (4) 99*e*.
Ostrikova, N. V. See Palkin, A. P.
Ostrow, S. Temperature measuring device, P (4) 108*b*.
Ota, C. Seawater magnesia industry—production method and characteristics of product, (9) 239*d*. See also Ohta, C.
Ota, E., Kozuka, T., Sakai, S., Hasegawa, K., Sawamoto, H., and Yamamoto, T. Pressure analysis on compressed tetrahedron (II) dimension of gasket and accuracy of generated pressure, (10) 289*g*.
Ota, T., Wakabayashi, A., and Fukui, S. Test for patching material made in the U.S.A., (1) 10*d*.
Ota, T., and Yamamoto, T. Physical and chemical properties of the American made patching material, Cupoline, (1) 9*d*. Physical and chemical properties of French made patching material, KP-1, (1) 9*d*.
Ota, Z., Ishikawa, K., and Goto, T. Results of tests on special siliceous ladle brick made of natural raw materials, (9) 239*d*. See also Ohta, Z.
Otake, T. See Kawai, N.
Otani, G. See Oizumi, K.
Otani, S., and Kojima, A. Thermal transformation of SiO_2-Al_2O_3 gels prepared from methylsiloxy-aluminum compounds, (9) 257*a*.
Oto, T. See Maeno, M.
Otremba, R. R. Process for producing extruded xerogels containing magnesia particles, P (10) 274*g*.
Otsubo, K. Spinel type checker brickwork built in an open hearth furnace, (7) 187*h*.
Otsubo, K., Noda, T., Ukumori, M., and Fujimoto, M. Results of using bloating type clay brick instead of zircon brick for the slag line and sleeve end of ladles for killed steel, (8) 216*i*.
Otsuka, A. See Kawakita, K.
Otsuki, T., and Taniguchi, T. Phosphate bond castable refractories, (8) 216*e*.
Ott, R. E. Measurement and control of ground coat slip, (6) 145*j*.
Otte, H. M., and Esquivel, A. L. Evaluation of two least-squares methods for precision determination of hexagonal lattice parameters from Debye-Scherer patterns, (1) 21*i*.
Otters, E. See Reiners, E.
Otto, Dr. C., & Comp. G.m.b.H. Manufacture of products containing silicon carbide, P (6) 154*e*. Manufacture of thermal shock resistant refractory materials and shapes, P (6) 154*i*.
Otto, H. See Hobaugh, J.
Otto, K. Electrical conductivity of SiO_2–B_2O_3 glasses containing lithium or sodium, (5) 120*d*. See Milberg, M. E.
Otto, P. See Schwiete, H. E.
Otto, W. H. See Marzocchi, A.
Ouchi, H., Nagano, K., and Hayakawa, S. Piezoelectric properties of $Pb(Mg_{1/3}Nb_{2/3})O_3$–$PbTiO_3$–$PbZrO_3$ solid solution ceramics, (1) 13*h*.
Ouchi, H., Nagano, K., and Iwamoto, K. Piezoelectric ceramic compositions, P (10) 279*g*.
Oudar, J. Phenomena of nucleation in gas-metal reactions, B (6) 175*c*.
Oudemans, G. J. See Gruintjes, G. S.
Oughtibridge Silica Firebrick Co., Ltd. Production of a refractory siliceous body primarily for the roofs of arc furnaces and bricks or blocks, P (7) 189*f*. Silica refractories, P (7) 190*a*.
Outlook Engineering Corp. Apparatus for indicating presence of predetermined color in sample, P (1) 17*d*.
Ovcharenko, F. D. See Kruglitskii, N. N.
Ovcharenko, F. D., et al. Colloid Chemistry of Palygorskites, B (8) 228*f*.
Ovcharenko, F. D., and Kukovsky, E. G. Relation between the colloid chemistry and crystal chemistry of clay minerals, B (2) 56*i*.
Ovcharenko, F. D., Tretinnik, V. Yu., and Kruglitskii, N. N. Structural-mechanical criteria in evaluating the coagulation action of electrolytes on water dispersions of montmorillonite, (9) 256*f*.
Ovchinnikov, Yu. M. See Neuimin, A. D.
Overstreet, E. F. See Dunlap, J. C.; Lang, W. B.
Overton, G. W. See Kirk, R. M.
Owen, A. E. Discussion of "Electrical conduction and oxygen diffusion in calcium aluminoborate and aluminosilicate glasses," (3) 60*i*.
Owen, W. H. Investment molding method and composition, P (10) 274*c*.
Owen, W. H., and Scott, R. K. Investment molding using refractory material and certain organic bases, P (4) 100*e*.
Owens, J. J. See Skalko, F. C.
Owens, W. H. Separation of Hf and Zr values by solvent extraction, P (11) 312*j*.
Owens-Corning Fiberglas Corp. Apparatus for delivering multifilament strands, P (10) 267*g*. Apparatus for forming an airborne curtain of liquid material, P (2) 32*i*. Apparatus for forming and collecting fibers, P (3) 62*g*; mineral fibers, P (10) 267*h*. Apparatus for forming fibers, P (3) 62*h*. Apparatus for forming heat-softenable materials, P (11) 297*e*. Apparatus for forming and processing fibers, P (8) 211*e*. Apparatus for forming and processing textile fibers and filamentary materials, P (9) 235*b*. Apparatus for heat control of forehearths, P (7) 182*g*. Apparatus for indicating material stream characteristics by calorimetry, P (5) 122*f*. Apparatus and method for melting heat-softenable material, P (5) 122*f*. Apparatus and method for producing flake glass, P (9) 235*d*. Apparatus for processing heat-softenable materials, P (9) 235*e*. Apparatus for producing fibers from heat-softenable material, P (5) 122*i*. Apparatus for producing uniform continuous fibers, P (10) 267*c*. Apparatus for severing a liquid stream, P (6) 149*b*. Attenuated mineral filaments, P (4) 96*j*. Borosilicate glass melting method, P (11) 297*g*. Calcium silicate insulating material and method of producing, P (4) 100*e*. Coating fibrous glass yarns, P (11) 297*i*. Combined fiber and cellular article, P (11) 297*j*. Continuous sodium silicate fibers, P (6) 149*h*. Crystalline fibers, P (8) 212*c*. Devitrifying a glass about glass fibers on a conductor, P (11) 298*a*. Dielectric panels, P (9) 235*i*. Elastomeric-glass fiber products and process, P (8) 212*e*. Electrical control system, P (4) 108*g*. Electrically conductive elements and their manufacture, P (7) 192*i*. Feeder for melting glass spheres for fiber drawing, P (7) 182*h*. Feeder for producing fibers, P (11) 298*c*. Fibrous glass air filters, P (6) 149*i*. Fibrous glass brush bristle, P (5) 122*f*. Flake glass breakout detector and method of controlling glass breakout, P (3) 63*e*. Glass fiber binder composition containing tall oil pitch, P (6) 149*j*. Glass fiber product, P (8) 212*j*. Glass foam, P (1) 6*a*. High temperature resistant borated alkyd resins and their preparation, P (2) 33*d*. High temperature resistant vitreous material and method of producing, P (5) 123*b*. Insulation assembly and package, P (4) 97*a*. Lamellar structure, P (7) 183*b*. Method and apparatus for forming fibers, P (5) 123*h*, P (11) 298*f*; fine fibers, P (7) 183*h*; glass fibers, P (2) 33*h*. Method and apparatus for packaging filamentary materials, P (4) 97*h*. Method and apparatus for processing heat-softenable materials, P (9) 236*g*. Method and apparatus for processing high temperature batch materials, P (10) 268*a*. Method and apparatus for producing bonded fibrous products, P (11) 298*g*. Method and apparatus for producing fibers, P (1) 7*a*, P (2) 34*a*. Method and apparatus for reducing fuzzing and breaking of strands, P (9) 236*k*. Method of applying binder to porous fibrous glass mats, P (5) 123*c*. Method of coating continuous sodium silicate fibers, P (10) 268*g*. Method of coating flexible fibrous glass strands, P (4) 97*a*. Method for continuously wrapping formed filaments of a rotor about an internal core, P (7) 183*j*. Method of controlling production of continuous filaments, P (2) 34*c*. Method of curing calcium silicate insulating materials, P (4) 101*a*. Method for forming crystal-free glass fibers, P (10) 268*j*. Method of forming fibrous glass yarn, P (1) 7*b*. Method of forming fibrous structures from a combination of glass fibers and cellulosic fibers, P (4) 97*b*. Method for improving the adhesion of vinyl polymers to glass fibers by the use of nitrogen compounds, P (5) 123*g*. Method of making coated glass fiber combinations, P (10) 269*f*. Method of making curly composite fibers, P (9) 236*b*. Method of manufacturing calcium silicate insulating materials, P (9) 240*a*. Method of preparing fibrous glass reinforcements, P (3) 64*j*. Method for producing curled fibers, P (5) 123*h*. Method for producing electrically conductive elements, P (11) 299*c*. Method of producing a lamellar metal structure, P (2) 34*j*. Method, system, and apparatus for processing filament-forming mineral materials, P (11) 299*h*. Muffler internally coated with highly refractory fibers, P (5) 123*i*. Pipe insulation, P (9) 236*h*. Process of coating glass fibers with hydrolyzed condensation product of amino silane and copolymerizable monomer, P (8) 213*g*. Production of [intermeshed] vitreous fiber products, P (4) 98*c*. Programing apparatus, P (4) 108*f*. Reinforcement of lower density inorganic structures, P (2) 34*h*. Separation of crystals from a boric anhydride matrix, P (3) 71*a*. Size composition for glass, treated glass structures, and method for manufacturing same, P (10) 270*a*. Sized glass fiber, P (1) 7*b*. Slitter for mat materials, P (2) 34*h*. Strand delivery apparatus, P (10) 270*b*. Structural panel and method for producing, P (4) 98*c*. Structures comprising vitrified and devitrified mineral fibers, P (3) 64*j*. Surface treatment of attenuated glass, P (5) 124*c*. Uniformity indicator, P (2) 35*a*. Viscometer for glass furnace, P (6) 151*b*. Voltage magnitude and temperature control in a heated device, P (7) 184*h*.
Owens-Illinois, Inc. Air operated neck molds, P (7) 182*f*. Apparatus for forming solid glassware in a carbon die, P (10) 267*i*. Apparatus for inspecting hollow syringe cartridges, P (10) 267*j*. Bottle gaging, P (11) 297*h*. Coating for glass and method of applying, P (9) 235*g*. Composite articles and method of making, P (3) 63*c*. Conveying and feeding glass articles into a lehr, P (9) 235*h*. Dip-coating machine, P (11) 298*b*. Filter flask assembly, P (10) 267*j*. Gaging apparatus, P (10) 267*j*. Glass forming apparatus, P (10) 268*c*. Glass furnace treatment, P (7) 183*d*. Glass sealing compositions and method for modifying same, P (7) 183*f*. Inspecting and assorting glass containers, P (10) 268*g*. Magnetic solder glass coatings and method, P (7) 183*d*. Method and apparatus for decorating containers, P (11) 298*e*. Method of cleaning mold equipment, P (10) 268*f*. Method of decorating glass bottles, P (10) 268*h*. Method for forming rectangular faceplate, P (10) 269*c*. Method of increasing the chemical resistance of glass surfaces, P (2) 34*f*. Method of strengthening delivery points and stems of laboratory glassware, P (9) 236*g*. Parison forming apparatus, P (11) 299*b*. Porous metal mold for molding glass articles, P (8) 213*e*. Pressing plunger for glass parisons, P (11) 299*d*.
Owens-Illinois Glass Co. Alumina refractories and preparation, P (6) 154*g*. Apparatus for blowing and cooling glassware, P (5) 122*c*. Apparatus for forming glass articles, P (8) 211*e*. Apparatus for homogenizing molten glass in a forehearth, P (3) 62*j*. Apparatus for melting glass, P (1) 6*d*. Apparatus and method for drawing glass tubes, rods, etc., P (2) 32*i*. Apparatus for skimming and stirring molten glass, P (2) 32*j*. Article banding apparatus, P (6) 149*c*. Article decorating, P (7) 182*b*, (10) 267*c*. Cathode-ray and other vacuumized tubes resistant to fracture and capable of controlled devacuation, P (3) 72*e*; tubes resistant to violent devacuation, P (3) 72*f*. Container and/or vial shaping apparatus and method therefor, P (6) 149*g*. Detecting crizzles in hollow glass containers [by light], P (7) 182*f*. Discharge apparatus for refining molten glass, P (4) 96*e*. Double parison transfer means, P (2) 33*g*. Forming short-length glass tubes, rods, etc., P (2) 33*i*. Glass feeding, P (4) 96*i*. Glass forming apparatus, P (5) 122*g*. Glass making batch and method, P (5) 122*h*. Glass pipe coupling, P (5) 122*i*. Glass pressing apparatus, P (9) 236*b*. Glass stirring apparatus, P (5) 122*i*. Glass tube forming apparatus, P (5) 122*j*. Glassware forming machine timing valve assembly, P (1) 6*e*. Glassware pressing

apparatus with hydraulic control, P (10) 268*d*. High expansion glass and seals, P (6) 150*c*. Inorganic metal oxides containing cobalt, antimony, and tantalum and method of preparing them, P (7) 193*e*. Inspecting articles, P (7) 183*d*. Inspecting containers with lug finishes, P (7) 183*j*. Inspecting glass container for horizontal checks, P (7) 183*j*. Inspecting rims of open mouth containers, P (10) 268*h*. Invert mechanism on glass forming machine, P (5) 123*d*. Joining glass members and encapsulation of small electrical components, P (2) 33*d*. Luminescent ceramic material of cadmium, boron, and manganous oxides, P (5) 123*f*. Method and apparatus for agitating molten glass, P (6) 150*f*. Method and apparatus for decorating glassware, P (8) 212*j*. Method and apparatus for forming hollow glass articles, P (4) 97*g*. Method and apparatus for forming multiple-bore tubing, P (6) 150*f*. Method and apparatus for inspecting cylindrical objects by photosensitive means, P (5) 123*i*. Method of and apparatus for reshaping glass tubes, P (9) 236*i*. Method and apparatus for severing mold charges of molten glass, P (10) 268*c*. Method for cleaning glassworking tools, P (2) 34*b*. Method of electrostatic screen printing, P (6) 150*j*. Method for forming apertures in hollow glass articles, P (1) 7*a*. Method for forming and delivering glass, P (6) 150*a*. Method of forming small glass envelopes, beads, etc., P (2) 34*f*. Method for joining glass parts, P (10) 269*e*. Method and mechanism for handling granular materials, P (9) 236*c*. Method for mold release during glass forming, P (8) 213*j*. Method of printing, P (8) 213*a*. Neck mold [inverting] apparatus for glass forming machine, P (6) 150*d*. Neutron-absorptive glass, P (2) 34*b*. Photoelectric inspection of containers for dirty finishes, P (5) 123*j*. Pressure rollers, P (6) 150*i*. Process for forming spherical silica beads, P (9) 241*d*.

Oxley, C. E. Method of producing a gel, P (8) 217*g*.

Oxley, G. H., and Littler, E. S. Method and apparatus for annealing sheet glass, P (4) 97*c*. Method and apparatus for the manufacture of sheet glass, P (4) 97*h*.

Oxley, J. H. See Blocher, J. M., Jr.

Oyama, T. See Ao, T.

Oyawoye, M. O., and Hirst, D. M. Occurrence of a montmorillonite mineral in the Nigerian younger granites at Ropp, Plateau Province, Northern Nigeria, (5) 133*e*.

Oza, T. M., and Mirza, B. V. Thermal decomposition of magnesium nitrate, (2) 53*d*.

Ozaka, M. See Minowa, S.

Ozark Reconditioning Co. Method of making containers of bonded fiber glass, P (2) 34*g*.

Ozarow, V. Luminescent silicon carbide and preparation thereof, P (5) 128*i*.

Ozawa, U., and Yamada, T. Erosion resistance of fireclay brick to high calcareous slag (II) relation between mullite formation and erosion resistance, (6) 152*h*; (III) effects of metallic oxides or salts on the erosion resistance of Korean kaolin, (6) 152*j*.

Ozolis, K. K., and Kokorish, E. Yu. Production of monocrystals of gallium arsenide, B (11) 320*d*.

Pacault, A. See Poquet, E.

Pace, N. A. See Shell, H. R.

Pacific Clay Products. Method of making clay pipe, P (6) 151*g*.

Pack, A. H. See Leatham, E.

Pack, A. H., and Campbell, W. W. Shaft kiln, P (7) 196*a*.

Packard-Bell Electronics Corp. Ceramic capacitor, P (7) 192*a*.

Paczek, H. See Harasowski, J.

Paderno, Yu. B. See Samsonov, G. V.

Padfield, R. C. Expansion problems in the use of high strength basic brick, (1) 9*a*. See Harbin, H. P.

Padilla, V. See Hobaugh, J.

Page, H. A. Method of enameling anodized aluminum, P (3) 60*a*.

Paige, J. I., Harris, H. M., and Kelly, H. J. Devitrification of vacuum-melted glasses of the lithium metasilicate-silica series, (1) 3*j*.

Paiva Netto, J. E. See Angeleri, F. B.

Pakulska, M. Trends in the development of charging systems for glass melting furnaces, (8) 211*b*.

Paladino, A. E. Discussion of "Oxygen content of nickel ferrites at 1300°C," (6) 166*j*.

Paladino, A. E., and Roiter, B. D. Czochralski growth of yttrium-gallium garnet, (2) 49*e*.

Palaontas, A. See Moerti, G.

Palermo, J. J. See Bonazoli, R. P.

Paley, J. J. See Affleck, J. H., III.

Pal'guev, S. F. See Neuimin, A. D.; Smirnov, M. V.; Volchenkova, Z. S.; Yushina, L. D.

Pal'guev, S. F., and Neuimin, A. D. Study of the type of conductivity of solid oxides by emf measurements, B (1) 26*i*.

Palilla, F. C. See Levine, A. K.

Palinchak, S. See Wagner, W. A.

Palkin, A. P., and Afinogenov, Yu. P. Interactions in the quaternary reciprocal system of substitution $AgCl + CuCl + Zn \rightarrow ZnCl_2 + Ag + Cu$, (1) 22*i*. Interactions in the system $AgCl + Cu \rightleftharpoons CuCl + Ag$, (1) 22*j*.

Palkin, A. P., Afinogenov, Yu. P., and Mushenko, E. S. Interactions in the system $AgCl + CuCl + Pb \rightarrow PbCl_2 + Ag + Cu$, (11) 317*i*.

Palkin, A. P., and Ostrikova, N. V. Fusibility diagram in the system $GaCl_3$–$AlCl$, (1) 21*d*.

Palkin, A. P., Ostrikova, N. V., and Vigutova, T. N. Interactions in the system $InCl_3$–In, (11) 317*j*.

Palkin, A. P., and Polivanova, T. A. Quaternary reciprocal system of the chlorides, bromides, and sulfates of sodium and thallium, (5) 140*g*. Quaternary system Tl_2Cl_2–Tl_2Br_2–Na_2SO_4–K_2SO_4, (9) 254*i*.

Palkin, A. P., Vigutova, T. N., and Glotova, L. I. Fusibility diagram of the $InCl_3$–$TlCl$ system, (1) 21*d*.

Palkina, K. K. See Kuznetsov, V. G.

Pall, A. See Svehla, G.

Palmer, G. G. See Illyn, A. V.

Palmer, H. B. Analysis of carbon deposition kinetics in isothermal flow systems, (4) 109*j*. See Hirt, T. J.

Palmer, J. W. Marit Aschan, enamelist of our time, (8) 206*d*.

Palmer, W. F. High conduction semiconductor diode, P (4) 104*j*.

Palmisano, R. R., and Drager, J. Low-density aluminum-ceramic composite, (9) 232*a*.

Palmour, H., III. See Kriegel, W. W.

Palomares, J. See Travesi, A.

Palowkar, D. R. See Ranby, P. W.

Palreyman, M. See Isaacs, J. W.

Pamnani, K. Direct rapid determination of combined water in gypsum, (3) 75*e*.

Pamnani, K., and Agnihotri, S. K. Modified method for the determination of ferrous iron in rocks and minerals, (10) 281*g*.

Pamplin, B. R. Semiconducting compounds, (3) 72*j*.

Pankova, N. A. Change in the composition of bubbles in sheet glass subject to temperature conditions of the tank furnace, (1) 3*i*. Composition of bubbles in different zones in a sheet-glass tank furnace, (4) 92*h*. Paths of movement of bubbles in tank furnaces for melting sheet glass, (6) 148*b*. See Solinov, F. G.

Pankratova, G. F. See Zaionts, R. M.

Panov, V. S. See Funke, V. F.

Papenfuss, H. J. See Lehmann, H. A.

Paprocki, S. J. See Hill, R. F.

Paquette, R. E., and Keller, C. H. Self-starting arc lamp, P (11) 307*d*.

Paquin, P. Analysis of some clay minerals by quantitative dilatometric tests, (7) 197*j*. Trends in the evolution of ceramic products, (7) 203*i*.

Parady, V. How to reinforce holes in filament wound structures, (2) 40*g*.

Paramount Pictures Corp. Color screen with electron- and light-absorptive material separating adjacent color strips, P (3) 72*i*.

Paraskov, B. Titania-zirconia frits, (5) 119*i*.

Pardue, E. Drinking glass, P (2) 33*g*.

Pare, X., and Ducros, P. Nuclear magnetic resonance study on the water in beryl, (7) 201*j*.

Parfenov, V. A. See Aleinikov, F. K.; Mikailiene, E.

Parfenov, V. A., Aleinikov, F. K., and Slizys, V. Thermographic method for determining glass transformation temperature, (7) 182*a*.

Parillo, E. V. See Martyny, W. C.

Paris, R., McLean-Elrick, A., Davies, J. M., and French, P. M. Bonding of UC and UC-iron cermets to canning materials, B (6) 172*g*.

Parisot, J. Graphites and carbons—high temperature materials, (11) 301*f*.

Park, R. C., and Wilder, A. H. Glass article inspecting, P (4) 96*h*.

Parke, R. M. Inlet orifice for continuous casting apparatus, P (10) 274*b*.

Parke, S. See Bingham, K.; Watson, A. I.

Parker, C. M., and Pierce, W. E. Selecting porcelain enameled steels, (2) 30*d*.

Parker, D. E., and Parssinen, E. J. Reinforced ceramic cylindrical transducers, P (4) 106*e*.

Parker, E. R. See Toth, L. E.

Parker, M. J. See Schreter, R. E.

Parker, S. G. See Sihvonen, Y. T.

Parker, T. J. See Burfoot, J. C.

Parker, T. J., and Burfoot, J. C. Structure of transition fronts in barium titanate, (5) 141*c*.

Parker, W. E., and Rakszawski, J. F. Oxidation resistant carbonaceous bodies and method for making, P (9) 241*a*.

Parker, W. H. Low-cost regeneration of ferric sulfate etch baths, (4) 91*i*.

Parkhachev, V. N. Installation for production of glass insulated microwire directly from liquid metal, P (9) 232*f*.

Parks, V. J. See Durelli, A. J.

Parnovskii, L. K. See Cherepova, O. V.

Parr, N. L. Heat resisting material and method for making it, P (2) 37*h*.

Parr, N. L., and Martin, G. F. Heat resisting material and method for producing it, P (3) 73*d*.

Parrish, W. (editor). X-Ray Analysis Papers, B (7) 204*h*.

Parry, R. J., and Reid, A. M. Manufacture of heat absorbing glasses, P (3) 63*e*.

Parsons, J. R. Power press process for forming lightweight refractory articles and articles so made, P (10) 274*a*.

Parssinen, E. J. See Parker, D. E.

Partridge, G. See McMillan, P. W.

Pascard, R. See Anselin, F.; Bauschmann, W.

Paschali, C. E. See Volpe, M. L.

Paschedag, H. J. Tubular incandescent lamp, P (10) 279*h*.

Pashchenko, B. V. Calculating the strength of glass pipes laid in the ground, (4) 92*e*.

Pashinkin, A. S. See Dembovskii, S. A.; Tsyun'khua, L.

Pashinkin, A. S., Drobot, D. V., Shevtsova, Z. N., and Korshunov, B. G. Determination of the vapor pressure of the anhydrous chlorides of yttrium and samarium, (1) 20*i*.

Pashkovskii, M. V. See Volzhenskii, D. S.

Pasierb, E., Jr. See Rappaport, P.

Pask, J. A. See Borom, M. P.; Copley, S. M.; Hulse, C. O.

Paskauskaite, L. See Sasnauskas, K.

Passmore, E. M., Moschetti, A., and Vasilos, T. Brittle-ductile transition in polycrystalline aluminum oxide, (9) 248*d*.

Passmore, E. M., and Vasilos, T. Creep of dense, pure, fine-grained aluminum oxide, (4) 110*c*.

Pasternak, R. A. See Bergsnov-Hansen, B.

Pastorek, R. L. See Dancy, E. A.

Patchen, F. D. See Dunlap, I. R.

Pate, A. F., Kuebler, R. A., and Kestner, H. R. Panel lamp with terminal bases, P (8) 221*f*.

Patel, A. R., and Bahl, O. P. Etch spirals in graphite, (7) 199*b*.

Patel, A. R., Vagh, A. S., and Bahl, O. P. Growth of NaCl whiskers on NaCl single crystals, (7) 199*j*.

Patel, C. C. See Murthy, P. R.

Patent-Treuhand-Gesellschaft fuer elektrische Gluehlampen m.b.H. Electric high pressure discharge lamp of high luminous intensity, P (2) 41*e*. Electrical miniature incandescent lamp and method of making, P (10) 267*g*. Electrically heated tank furnace for melting quartz, P (1) 6*h*. Furnace for the continuous drawing of quartz tubing, P (11) 298*d*. High-pressure discharge lamp inlead construction, P (2) 33*b*. Incandescent lamp for projectors, P (10) 268*f*. Multi-work-function cathode, P (6) 160*h*. Photoflash lamp and method, P (2) 34*d*, P (10) 279*g*. Tubular incandescent lamp, P (10) 279*h*.

Patrick, M. W., and Bauer, K. E. Radiant gas burner, P (7) 196*c*.

Patrick, T. See Pflaumer, P. E.

Pattengill, M. D. See Bradley, M. J.

Patterson-Kelley Co., Inc. Gas burner, P (4) 108*d*. Materials mixing and blending machine, P (10) 280*c*.

Patzak, I. Problems in the determination of cristobalite by X-ray diffraction—estimation of the degree of crystalline disorder, (6) 162*h*. See Koehler, E. K.; Konopicky, K.; Steinhoff, E.

Paukste, J. See Deksnys, A.

Paul, A. See Douglas, R. W.; Nath, P.

Paul, A., and Douglas, R. W. Cerous-ceric equilibrium in binary alkali borate and alkali silicate glasses, (3) 60*h*. Ferrous-ferric equilibrium in binary alkali silicate glasses, (3) 61*e*. Mutual interaction of different redox pairs in glass, (5) 121*f*.

Paul, A., and Lahiri, D. Manganous-manganic equilibrium in alkali borate glasses, (11) 296*h*.

Paul, H. L., Jr. Method for making ball valves, P (10) 276*c*.

Paul, J. Simultaneous determination of phosphorus, arsenic, and germanium and the separation of silicon and arsenic by solvent extraction, (9) 246*a*.

Paul, W. See Besson, J. M.

Paul, W. B., Jr., and Mayhew, G. C. Refractory wall construction, P (11) 303*d*.

Paulavicius, R. See Aleinikov, F. K.

Paulik, F. See Erdey, L.

Paulik, F., Paulik, J., and Erdey, L. Apparatus for thermal analysis, P (11) 311*c*.

Paulik, I., and Somodi, A. Economy of service campaigns of glass tank furnaces, (3) 60*j*.

Paulik, J. See Erdey, L.; Paulik, F.

Pauthenet, R. See Bertaut, E. F.

Pavilica, S. R. Method of lining a rotary kiln P (11) 302*a*. Rotary kiln, P (8) 224*i*.

Pavlov, V. S. Heat exchange in a zonal glass furnace, (9) 233*f*.

Pavlova, Z. I. See Kreymer, G. S.

Pavlushkin, N. M., Zhuravlev, A. K., and Eitingon, S. I. Enameling jewelry made of aluminum, (5) 118*a*.

Pavol, M., Jr. See Sawyer, E. W., Jr.

Pawlowa, I. See Symowa, W.

Pawlowska, H., and Lachnik, E. Spectrographic analysis of technical and ancient glasses, (2) 28*c*.

Paymal, J. Method for producing in a glass article stresses heterogeneously distributed, P (9) 236*d*. Process for treating glass to produce reverse stresses and product, P (9) 237*d*.

Paymal, J., and Bonnaud, M. Modifications of glasses under the influence of radiation, (5) 121*e*.

Payne, D. A. Fabrication, properties, and uses of electronic and magnetic ceramics, (6) 157*h*.

Payne, R. F. See Mills, B. D.

Pchelyakov, K. A. Approximate calculation of the flow rate pattern along the depth of the molten glass, (8) 208*i*.

Pchelyakov, K. A., and Gaitanova, L. Ya. Investigation of hydraulics and convection flows of molten green glass, (8) 209*i*.

Pchelyakov, K. A., and Sokolov, A. A. Modeling of the hydraulics and flow of molten glass in relation to output, (10) 265*j*.

Peacock, J. See Evans, A. W.

Peakall, K. A. See Antill, J. E.

Peakall, K. A., and Antill, J. E. Oxidation of UC-10%Fe, B (6) 172*h*.

Pearce, J. W. Molds and methods of preparing them, P (5) 126*b*.

Pearce, M. L. Calculation of oxygen ion activities in sodium silicate and sodium borate melts, (1) 19*g*.
Pearce, M. L., and Beisler, J. F. Diffusion studies of Na_2O–SiO_2–Fe_2O_3 melts at 1200°C, (11) 315*f*.
Pearce, N. Fully automatic equipment for the tableware industry (I, II), (7) 190*f*. See Meadows, F. W.
Pearch, L. E., and Surckla, P. P. Gas burner, P (11) 311*f*.
Pearse, G. E. Mining anhydrite at Billingham, (3) 78*h*.
Pearson, A. D. See Dewald, J. F.
Pearson, A. D., Peterson, G. E., and Northover, W. R. Tb^{3+} fluorescence and nonradiative energy transfer from Gd^{3+} to Tb^{3+} in borate glass, (6) 149*f*.
Pearson, E. F. See Heslop, R. B.
Pearson, G. L. See Allen, J. W.
Pearson, R. G. See Burwell, R. L., Jr.
Pease, D. C. Preparation of fibrous titanium dioxide, P (6) 155*f*.
Pease, R. F. W., and Ploc, R. A. Scanning electron microscopy as applied to the oxidation of iron, (5) 140*e*.
Peavey, F. H., & Co. Semiconductor devices, P (3) 74*f*.
Pechiney, Compagnie de Produits Chimiques et Electrometallurgiques. Process for treatment of minerals low in alumina, P (7) 189*b*. Thorium oxides and mixed thorium oxides and method, P (2) 48*b*.
Pechini, M. P. Barium titanium citrate, barium titanate, and processes for producing, P (4) 104*a*.
Peck, D. B. See Markarian, M.
Peck, T. W. Article orienting apparatus, P (2) 33*b*.
Pecoraro, R. P. See Harding, W. E.
Pedigo, C. L., and Alexander, B. T. Method of preparing an extended catalyst consisting of cobalt oxide, molybdenum oxide, and alumina, P (1) 18*j*.
Pedro, G. Clay Mineral (Phyllosilicate) Classification, B (7) 204*a*.
Peek, S. C., Jr. See Spencer, D. E.
Peeps, D. J. Spray gun using high pressure coating material, P (2) 43*h*.
Peeters, J. M. Glass drawing apparatus with pivotal cooler, P (11) 298*h*.
Peiser, H. S., and Wachtman, J. B., Jr. Reduction of crystallographic point groups to subgroups by homogeneous stress, (1) 24*f*.
Peiser, H. S., Wachtman, J. B., Jr., Munley, F. A., and McCleary, L. C. Splitting of equivalent points in noncentrosymmetric space groups into subsets under homogeneous stress, (3) 85*i*.
Pek Labs, Inc. Self-starting arc lamp, P (11) 307*d*.
Pekarev, A. I. Method for constructing a composition-property diagram of a ternary system, (3) 83*f*.
Pelavin, M. H. See Skeggs, L. T.
Pelevin, O. V. See Maslov, V. N.
Pell, E. M. Method of forming gallium arsenide semiconductor devices, P (9) 243*j*.
Peller, P. See Bailey, B. L.
Peloschek, H. P. See Esveldt, C. J.
Peloschek, H. P., and Vrolijks, M. H. M. Method of manufacturing magnetic heads with bonding gap-filling materials, P (7) 193*f*.
Peltier, M. See Rombau, P.
Pelton, E. R. See Stein, G. A.
Pelzbauer, Z. See Modry, S.
Pelzl, A. See Jamnik, F.
Pena, J. M. G. See Gonzalez Pena, J. M.
Penberthy, H. L. Glass furnace with means to agitate the molten glass, P (10) 268*c*. Method of forming refractory casting, P (5) 123*e*.
Pendas, S. de A. See Aza Pendas, S. de.
Pendergast, W. J. Method for the fabrication of tantalum film resistors, P (9) 243*i*.
Pendleton, W. W. See Saums, H. L.
Penez, A. See Grollier-Baron, T.
Peng, Fu-nan. Nucleation agents in diabase melts, (8) 216*c*.
Pennsalt Chemicals Corp. Apparatus for analyzing for particle size distribution, P (11) 311*a*.
Penoza, F. J. Extrusion of ferrous metals through dies of metal silicides, P (1) 11*c*.
Pentecost, J. L., and Eliason, L. K. Characterizing materials above 1500°C, B (6) 173*e*.
Pentek, I., and Uhlmann, E. Experimental results in the development of the top fired tunnel kiln, (2) 46*c*.
Perss, L. Refractory and cohesive materials having metallic phase and ceramic phase, method of producing same, and method of coating using same, P (2) 38*f*.
Perdue, R. D. See Cohn, M. I.
Pereira da Costa, J. E. Control of the manufacture of pigments and their use in sanitary-ware glazes, (2) 39*d*.
Perel, J., and Schieber, M. Magnetic moments of some mixed rare earth iron garnets, (10) 277*d*.
Peret, J. L. See Matkovich, V. I.
Perez, L. J. A. See Alias Perez, L. J.
Perez y Jorba, M., Tilloca, G., and Collongues, R. Structure and properties of strontium zirconate—study of the ZrO_2-SrO equilibrium diagram—extension to the study of other MO_2–M'O systems, B (6) 173*d*.
Perfilova, I. L. See Shchukarev, S. A.
Perilhou, J. R., and Le Gargasson, G. Fuel element for use in nuclear reactors, P (8) 217*b*.
Perkin-Elmer Corp. Elution chromatography, P (4) 108*a*. Plural directional growing of crystals, P (6) 160*j*.
Perks, A. J. See Goggin, P. R.
Perlman, R. Process for the formation of metalliferous coatings on inorganic bodies, P (8) 219*e*.
Permaglass, Inc. Apparatus for heat treating glass sheets, P (7) 182*h*. Means for releasing stresses produced in glass during cooling in a glass shaping mold, P (8) 212*h*.
Permingeat, F. See Gaudefroy, C.
Pernichele, A. D. See Rich, M.
Perona, G. See Bassi, A.
Perri, J. A., and Riseman, J. Coated objects and methods of providing the protective coverings therefor, P (7) 192*c*.
Perrier, G. See Perrier, R.
Perrier, R., and Perrier, G. Machine adapted to turn bottles, flasks, etc., upside down, P (1) 6*i*.
Perrotta, A. J. See Gaines, A. M.
Perry, E. S., and Burns, N. H. Simple setup for applying impact loads, (2) 45*b*.
Persianov, I. C. See Vaitkus, J.
Pesatova, S. Dominik Biemann, (5) 117*j*.
Peschke, J. von. Calculation of convection flows in glass tanks, (3) 60*f*.
Peskin, B. See Harel, S.
Pessahovitz, Z. See Harel, S.
Pessall, N., Jones, C. K., Johansen, H. A., and Hulm, J. K. Critical supercurrents in niobium carbonitrides, (6) 165*j*.
Pessok, S. Contact for solid state diode, P (11) 305*d*. Controlled [silicon] rectifier comprising a resistive plating interconnecting adjacent *n* and *p* layers, P (11) 305*e*.
Petch, N. J. See Congleton, J.
Peter, E., and Kalman, A. Quantitative X-ray analysis of crystalline multicomponent systems, (5) 131*f*.
Peters, D. W. Barrier effect insulator, P (10) 277*h*. Electrical properties of an alumina polyphase heterojunction, (1) 21*a*.
Peters, E. R. Diamond drill bit, P (6) 143*h*.
Peters, E. T., and Ryan, J. J. Comment on "Pressure dependence of the emf of thermocouples," (6) 162*g*.
Peters, F. A., Johnson, P. W., and Kirby, R. C. Methods for producing alumina from clay—an evaluation of the sulfurous acid-caustic purification process, (9) 247*e*.
Peters, W. See Hirschowitz, B. I.
Petersen, L. Method and apparatus for making cement, P (5) 119*a*.
Petersen, S. A. Apparatus for producing strand packages of uniform length, P (8) 211*i*.
Peterson, C. L. Electric discharge device having heat conserving shields and [glass] sleeve, P (7) 192*e*.
Peterson, C. R. Method and apparatus for dispersing glomerate particles, P (6) 161*g*.
Peterson, D. L., Helfferich, F., and Blytas, G. C. Sorption and ion exchange in sedimentary zeolites, (5) 141*a*.
Peterson, G. E. See Pearson, A. D.
Peterson, S. F. A. See Liedberg, K. H.
Petery, A. von. Mixing equipment for glass factories, (3) 74*i*.
Petkov, P. See Dimov, D.
Petkov, P., P'nevski, I., Mashkin, L., Dimov, D., Smoleva, D., and Stoyanova, L. Effectiveness of different fuels used in the glass industry, (2) 31*i*.
Petkus, E. J., and Tevebaugh, A. D. Preparation of actinide monocarbide, P (7) 189*c*.
Petrenko, I. Yu. Complex thermal analysis of dispersion materials and melts, (8) 222*j*.
Petrosov, I. Ch. See Sarkisyan, S. G.
Petrov, S. M. See Minenko, V. I.
Petrov, T. G. Growth of crystals during reciprocating motion in a solution, B (11) 320*b*.
Petrov, V. P. See Titkov, N. I.
Petrov, V. P., and Tomakov, P. P. Nature of sungulite, B (2) 56*g*.
Petrovskii, G. T. See Grebenshchikova, N. I.
Petruk, W. Relationship between the specific magnetic susceptibility and the iron plus manganese content of chlorite, (3) 85*b*.
Petrusha, J. A. See Joseph, A. D.
Petruzella, J. See Moyson, J.
Pettibone Mulliken Corp. Crusher with variable opening screen grate, P (4) 109*e*.
Pettit, F. S., Randkiev, E. H., and Felten, E. J. Formation of $NiAl_2O_4$ by solid state reaction, (5) 136*j*.
Petzold, A., and Roehrs, M. Refractory Concretes, B (6) 174*c*.
Petzold, A., Wihsmann, F. G., and Kamptz, H. v. Microindentation hardness of some silicate glasses and their atomic significance, (2) 32*d*.
Petzow, G., Preisler, E., and Haessner, F. Nuclear reactor absorbers, P (7) 189*b*.
Peyches, I., Lajarte, S. D. de, and Laurent, B. Manufacture of flat glass, P (8) 212*f*.
Peyches, P. I. Method and apparatus for polychrome striped screens for color television receiver, P (8) 213*b*.
Pfann, W. G. Piezoresistive material, P (8) 221*f*.
Pfaudler Permutit, Inc. Apparatus for attaching parts to glass coated apparatus, P (9) 232*e*. Apparatus and method for healing glass lined pipe, P (7) 179*a*. Glass lined fitting and process for glass lining of pipe fitting, P (5) 120*a*.
Pfeifer, D. W. See Landgren, R.
Pfeifer, O. W., and Shannon, R. F. Reinforcement of lower density inorganic structures, P (2) 34*h*.
Pfister, M. C. Radiation pyrometer for measuring the color temperature, P (9) 246*e*.
Pflaumer, P. E., Patrick, T., and Philbrick, J. W. Method and apparatus for semiconductor wafer handling, P (11) 306*b*.
Pfluger, R. Glass reinforcing apparatus, P (1) 6*e*.
Pfuhl, H. Plans for the construction of a sanitary ware plant, (1) 12*i*, (6) 156*f*.
Phakey, P. P. See McLaren, A. C.
Phelps, G. W., and Wunnik, J. van. Casting slip control, (6) 155*j*.
Phelps Dodge Copper Products Corp. Ceramic-coated electrically conductive wire and method of making, P (3) 59*j*.
Philadelphia Quartz Co. Compositions of matter containing organic silicates, P (7) 190*h*. Organic phosphates—stabilization of silica sols and dispersions or suspensions of silica and siliceous materials, P (9) 247*f*. Shell mold process, P (11) 303*e*. Spherical particles of anhydrous sodium metasilicate and method of manufacture, P (1) 13*d*. Stable, alkali-rich sodium silicates, P (9) 247*i*.
Philbrick, J. W. See Pflaumer, P. E.
Philco Corp. Apparatus [horizontal furnace] for growing fluoride crystals, P (11) 305*j*. Connection of semiconductor elements to thin film circuits using foil ribbon, P (5) 128*a*. Desiccation of electronic enclosures using boron nitride hot sealing method, P (6) 159*b*. Method for fabricating a rectifying connection to a body of *n*-type germanium, solder, and semiconductor device, P (6) 159*h*. Method of fabricating thin film R-C circuits on single [glass] substrate, P (9) 243*i*. Method for improving the electrical characteristics of germanium semiconductor devices, P (4) 105*g*. Process for rapidly etching a flat-bottomed pit in a germanium wafer, P (10) 279*a*. Semiconductor device and method of fabrication, P (10) 279*d*. Semiconductor integrated structures and methods for fabrication, P (11) 307*j*. Thin film signal translating device utilizing emitter comprising CdS film, insulating layer, and means for applying potential thereacross, P (2) 43*a*. Ultrasensitive phototransistor device comprising wafer having high resistivity center region with opposite conductivity, diffused, low-resistivity, and translucent outer layers, P (3) 74*f*.
Philipps, T. E. See Doob, H., Jr.
Philips Electronics & Pharmaceutical Industries Corp. Glass-to-metal seal, P (10) 278*i*.
Phillips, A. B. Planar transistor with a relatively higher resistivity base region, P (11) 307*f*.
Phillips, B. See Chang, L. L. Y.
Phillips, B., and Chang, L. L. Y. Condensed-phase relations in the system Mo–O, (6) 165*j*.
Phillips, B., Chang, L. L. Y., and Scroger, M. G. Condensed-phase relations in the system Co–W–O at high temperature (1000° to 1700°C), (6) 165*h*.
Phillips, C. J. Strength and weakness of brittle materials, (5) 121*g*.
Phillips, G. See Milner, G. W. C.
Phillips, N. W. F. See Braunwarth, V. A.
Phillips, W. B. See Skofronick, J. G.
Phillips, W. R. See Moulson, A. J.
Phillips Petroleum Co. Apparatus for determining rheological properties, P (6) 163*a*. Cement compositions and methods of utilizing same, P (2) 29*g*. Plasma arc sprayed catalysts, P (10) 274*j*. Radiant drying of particulate material, P (8) 224*g*. Radiant heat drying method and apparatus, P (2) 46*f*.
Philp, S. F. See Shannon, J. P.
Phoenix Gems, Inc. Synthetic stone bodies with controlled properties, P (6) 145*a*.
Physical Sciences Corp. Insulating coating compositions for electrical conductors, P (10) 263*h*. Wire coating apparatus, P (9) 232*f*.
Pick, H. H., and Stanley, N. Dual-pivoting cradle type roll crusher, P (1) 18*d*.
Pickart, S. J. See McGuire, T. R.
Pickles, S. See Mowat, J. A. S.
Pierce, J. A. See Stock, D. F.
Pierce, W. E. New applications for porcelain enamel—now and tomorrow, (8) 207*j*. See Parker, C. M.
Piermarini, G. See Weir, C.
Pierrot, A. Magnetic material of high permittivity, P (8) 221*f*.
Pies, J. R. See Karalis, S. N.
Pietrzak, J. Proton magnetic resonance study of the structure of alum single crystal, (6) 169*b*.
Pietsch, T. Process for increasing the thermal insulating properties of vitreous materials and their adhesion to coherent substances, P (3) 64*h*.
Pigeot, A. See Burko, J.
Pigford, T. H. See Rufeh, F.
Pilas, F. J. Electron mounting structure of a high frequency electron tube, P (6) 159*f*.
Pilkington, L. A. B. Manufacture of flat glass, P (2) 33*f*, P (3) 63*c*, P (10) 268*h*. Protective atmosphere for sheet glass casting rolls, P (4) 98*d*.
Pilkington Brothers, Ltd. Apparatus for the manufacture of flat glass, P (3) 63*a*. Glass containing germanium sulfide, P (2) 33*a*. Manufacture of flat glass, P (2) 33*f*, P (3) 63*c*, P (10) 268*h*. Manufacture of heat absorbing glasses, P (3) 63*e*. Method of and apparatus for annealing sheet glass, P (4) 97*c*. Method and apparatus for the manufacture of sheet glass, P (4) 97*h*. Method and apparatus for the production of bent toughened glass, P (3) 63*h*. Methods of and apparatus for toughening curved sheets of glass, P (2) 34*b*. Method

of producing toughened glass, P (4) 97*e*. Protective atmosphere for sheet glass casting rolls, P (4) 98*d*. Radiant type cooler in apparatus for producing glass in ribbon form, P (11) 299*f*. Snapping of sheets of glass, P (10) 270*a*.

Pilkuhn, M. See Foster, L. M.

Pilny, F. Ceramic wall covering, (3) 71*c*.

Piloyan, G. O. See Tsvetkov, A. I.

Piltz, G. Fire resistance of brick raw materials, (2) 35*f*.

Pinaev, G. F. Construction of phase diagrams of reciprocal systems by use of weight percentages, (6) 165*g*.

Pines, A. N. Wear- and strain-resistant coated articles, P (3) 60*b*.

Pinot, M. See Bacchella, G. L.

Pinotti, A. D. See Bishop, F. L.

Pinotti, F. D. See Frye, H. D.

Pinter, R. S. See Louden, W. C.

Pinto, L. J. See Kramer, H.

Piper, W. W. Growth of single crystals, P (6) 159*h*.

Pipinys, P., Gegznaite, L., and Raulickyte, A. Effect of electric field on the photoluminescence of ZnS-Pb, (9) 242*f*.

Pirogov, Yu. A. Properties of protective coatings applied to metals by flame spraying (atomization), (4) 91*j*.

Pirogovskaya, G. P. See Bogdanova, N. I.

Pishch, I. V. Cliche method in production, (4) 92*g*.

Pither, L. F. Discharge apparatus for refining molten glass, P (4) 96*c*. See Allman, O. H.

Pitirimov, B. Z. See Efimov, A. I.

Pittsburgh Corning Corp. Sound absorbing systems, P (1) 7*c*.

Pittsburgh Plate Glass Co. Apparatus for bending glass, P (7) 182*f*. Apparatus for drawing sheet glass, P (3) 62*g*, P (5) 122*de*. Apparatus for making multiple glazed units, P (11) 297*e*. Apparatus and method for cutting glass sheets, P (8) 211*g*. Apparatus and method for scoring continuously moving glass sheets, P (6) 149*a*. Automatic glass area measuring device, P (10) 267*d*. Bending glass sheets, P (5) 122*a*, P (7) 182*c*. Bending mold for glass sheets, P (3) 63*b*. Bending mold with leading apertured plate, P (2) 33*c*. Blowing frame for tempering glass sheets, P (4) 96*a*. Coated vehicle glazing closures, P (6) 149*f*. Coating composition and method of preparation, P (8) 212*c*. Coating of glass sheet while deformable and supported on gas, P (3) 63*c*. Composite glass fiber products and process of preparing, P (2) 33*d*. Enclosed chamber for floating glass on a molten bath, P (7) 182*f*. Gas module systems for heat transfer and/or fluid support of glass or other sheet materials, P (3) 63*g*. Glass bending, P (2) 33*j*. Glass bending apparatus with pivot support points, P (3) 63*h*. Glass bending mold with pivoted end sections, P (7) 183*a*. Glass bending mold positioning and orienting apparatus, P (7) 183*a*. Glass bending mold with sheet guide, P (3) 63*i*. Glass bending molds, P (1) 6*a*. Glass cutting [computer] control apparatus, P (11) 298*g*. Glass drawing apparatus, P (1) 6*a*; with pivotal cooler, P (11) 298*h*. Glass fiber sizing composition, P (10) 268*b*. Glass fiber treatment, P (9) 236*a*. Glass melting furnace with bridge wall, P (6) 150*a*. Glass planing process, P (7) 183*e*. Glass sheet bending mold, P (5) 122*i*. Glass sheet bending mold with heat absorber, P (10) 268*d*. Glass sheet bending mold with horizontal support surfaces, P (10) 268*d*. Glass sheet drawing apparatus with an energy transmitter, P (1) 6*d*. Handling of sheet material, P (3) 63*j*. Heat exchanger for sheet glass drawing apparatus, P (8) 212*d*. Heat treatment of conveyed glass and apparatus therefor, P (3) 63*a*. Laminating techniques, P (5) 123*f*. Length and area partitioning methods and apparatus, P (7) 183*c*. Manufacture of glass sheets, P (6) 150*e*. Method of annealing glass ribbon, P (8) 212*i*. Method and apparatus for bending glass sheets, P (5) 123*g*, P (7) 183*e*; to compound curvatures, P (7) 183*f*. Method and apparatus for drawing glass sheet, P (3) 63*f*. Method and apparatus for forming fibers, P (8) 213*a*; hollow glass fibers, P (10) 268*j*. Method and apparatus for manufacture of float glass, P (6) 150*g*. Method and apparatus for producing fibers, P (5) 123*a*. Method and apparatus for supporting glass sheets, P (3) 63*j*. Method and apparatus for treating glass on a pressurized fluid bed, P (3) 64*a*. Method and apparatus for vertically supporting and heat treating a glass sheet, P (3) 64*b*. Method for bending glass sheets, P (3) 64*c*. Method for bending glass sheets to compound curvatures, P (3) 64*c*. Method for drawing glass, P (7) 184*a*. Method for forming glass fibers, P (11) 298*j*. Method for forming a glass fiber reinforced resinous body, P (7) 184*b*. Method for forming and winding glass strands, P (11) 298*j*. Method of heat treating glass sheets, P (3) 64*e*; while being conveyed, P (7) 184*d*. Method of inspecting tempered glass sheets, P (10) 269*e*. Method of manufacture of flat glass, P (6) 150*b*. Method of preparing zirconium oxide, P (7) 188*h*. Method for producing glass fibers, P (11) 299*f*. Method of producing welded double glazing units, P (10) 269*a*. Method for the production of glass fibers, P (8) 213*c*. Method of removing surface defects from glass sheets, P (9) 236*e*. Method of sizing glass fibers and epoxy resin emulsion therefor, P (7) 184*a*. Method of supporting glass for polishing, P (4) 97*h*. Method of tempering glass sheets supported on a bending mold, P (10) 269*e*. Method of treating and conveying glass sheets, P (3) 64*b*. Phototropic glass and methods, P (11) 299*c*. Pigmentary silicon carbide, P (11) 303*a*. Pivoted glass sheet bending mold, P (7) 184*d*. Process for producing titanium oxide pigments, P (3) 79*a*. Production of fiber glass strand, P (11) 299*d*. Production of pigmentary titanium oxide, P (2) 48*a*. Separation of Hf and Zr values by solvent extraction, P (11) 312*j*. Sized glass fabric and method, P (4) 98*b*. Transmission baffle in glass drawing zone, P (4) 98*d*. Treatment of glass, P (3) 65*b*. Turnover device, P (6) 151*b*. Vibrating sieve, P (10) 280*e*.

Pivovarov, L. Kh. See Ivensen, V. A.

Pivovarov, L. Kh., Yanshin, S. I., Semerchan, A. A., and Baskin, M. L. Effect of high pressures and temperatures on tungsten monocarbide, (10) 271*j*.

Pixley, G. W. Lightweight aggregate production—use of soft alluvial clay as raw material, (6) 151*g*.

Pizzarello, F. A. Method of producing stable gallium arsenide and semiconductor diodes made therefrom, P (7) 193*h*.

Pizziolo, A. See Bairiat, H.

Place, T. M., Sr. Method of making electrical resistance element, P (11) 306*d*.

Plankenhorn, W. J. Spontaneous spalling, (5) 119*j*.

Planning Institute of Cement and Glass Industries, Laboratory of Raw Materials. Use of carbide sludge for manufacturing portland cement, (3) 59*d*. See also Scientific Research Institute of Building Materials.

Plas, L., van der. Identification of Detrital Feldspars, B (6) 172*i*.

Plath, I. Decorative Arts of Sweden, B (7) 204*c*.

Plesch, P. H. English and continental glass in the collection of Dr. and Mrs. Peter H. Plesch, (5) 118*a*.

Plewczynski, J. See Winogradow, L.

Pliskin, W. A. Effect of phosphorus in SiO_2 as shown by infrared spectroscopy, (10) 285*g*. See Lehman, H. S.

Pliskin, W. A., and Conrad, E. E. Method of forming a glass film on an object and the product produced, P (1) 3*e*.

Ploc, R. A. See Pease, R. F. W.

Plotnikova, V. V. See Bobrova, T. N.

Plug, C., and Niekerk, J. N. van. Universal X-ray fluorescent method for the quantitative analysis of nonmetallics, (11) 310*g*.

Plum, G. Cost of wages in the production of heavy clay products in the Common Market, (1) 7*h*.

Plumat, E. Device for the protection of barriers in glass furnaces, P (4) 96*d*. Glass furnace having a refining chamber for the molten glass, P (9) 236*a*. Process and furnace for melting and working products such as glass, P (3) 64*f*. See Henry, G.

Plumat, E., Toussaint, F., and Boffe, M. Formation of bubbles by electrochemical processes in glass, (11) 296*e*.

Plunkett, R. G. See Mattern, J. S.

Plusch, J. A. See Grant, W. H.

Plyshevskii, Yu. S., Leont'eva, I. A., and Smirnova, G. M. Physical-chemical properties of barium hexaborate, (11) 319*a*.

Plyushchev, V. E. See Samuseva, R. G.

P'nevski, I. See Dimov, D.; Petkov, P.

Podolsky, L. Furnace for producing oriented graphite, P (4) 108*d*.

Poegel, H. J. Effect of alkaline earth oxides on the viscosity and structure of glass melts, (10) 264*e*. Viscosity and structure of molten glass, (1) 6*b*.

Poehnitzsch, H. See Meyer, H.

Poelstra, W. G. See Brous, J.

Poeschel, E. See Eberle, L.

Pohlmann, G., and Oberlies, F. Fungus growth on glasses, (5) 120*f*.

Pohto, H. A. See Febbo, P. P.

Pointon, A. J., and Robertson, J. M. Ceramic properties of nickel ferrite and the porosity broadening of the ferromagnetic resonance line width, (3) 72*c*.

Poirier, G., and Duchene, J. Device for crystallographic study at high temperature and in controlled atmosphere, (8) 223*d*.

Polak, A. Galle glass—luxurious, cheap, and imitated, (3) 57*j*. Regence casket with engravings after Ovid, (5) 118*b*. Signatures on Galle glass, (9) 230*b*. Sulfides and medals, (9) 230*c*.

Polakowski, N. H., and Ripling, E. J. Strength and Structure of Engineering Materials, B (6) 174*i*.

Poland, M. E. Spark plug with conical seat sealing washer, P (4) 106*a*.

Polaroid Corp. Method of forming [Ta] carbide coated coiled filaments for lamps, P (5) 129*b*. Method of making electric lamps, P (2) 42*b*.

Polch, F. J. Internal reinforcement of molded rotatable articles, P (10) 261*g*.

Poletaev, I. F. See Samuseva, R. G.

Polhemus, J. H., and Ammon, R. Whirlpool apparatus, P (2) 48*c*.

Polivets, Yu. G. Mechanized conveyer SM461A for making sanitary ware, (6) 156*h*.

Polito, W. J. See Rozgonyi, G. A.

Polivanova, T. A. See Palkin, A. P.

Pollak, P. I. See Barkemeyer, H. R.; McAleer, W. J.

Pollard, J. H., Bowler, D. L., and Pomerantz, M. A. Electrical conductivity induced in MgO by relativistic electron bombardment, (7) 199*b*.

Pollyak, V. V., and Mikhailova-Bogdanskaya, Z. A. Controlling glass composition by density measurements, (8) 209*a*.

Pollyak, V. V., Soskova, V. D., and Mazur, A. K. Melting sheet glass at high temperatures, (10) 265*i*.

Polon, J. A. See Haden, W. L., Jr.

Polyachenok, O. G. See Novikov, G. I.

Polyakov, Yu. A. See Dembovskii, S. A.

Polymer Corp. Coating method and apparatus, P (4) 91*g*.

Polysius G.m.b.H. Apparatus for firing and sintering a powdered product and its operation, P (6) 163*j*. Method of and arrangement for dressing moist raw materials with solid undesired inclusions, P (8) 207*f*. Method of and arrangement for making cement clinker, P (6) 144*j*.

Pomerantz, D. I. Planar semiconductor devices, P (11) 307*f*.

Pomerantz, M. A. See Pollard, J. H.

Poncelet, E. F. Mechanism of fracture propagation, (1) 23*g*.

Poncelet, G. See Calvet, R.

Ponomarev, I. F., Grach'yan, A. N., and Zubekhin, A. P. Effect of mineralizing additives on the formation of cement clinker as a function of the electronegative cation and anion of the mineralizer, (8) 206*f*.

Poonia, N. S., Boparai, K. S., and Bhagwat, W. V. Determination of copper with *m*-(mercaptoacetamido)phenol as a gravimetric reagent, (3) 75*e*.

Poplavko, Yu. M. See Nekrasov, M. M.

Popoff, V. L. See Illyn, A. V.

Popov, M. I. See Borisov, B. I.

Popov, N. T. See Zezin, M. A.

Popov, S. N. See Smolenskii, G. A.

Popova, A. A. Growth of Cr_2O_3 monocrystals by the verneuil method, B (11) 320*c*.

Popovkin, B. A. See Zlomanov, V. P.

Popovkin, B. A., Odin, I. N., and Novoselova, A. V. System lead oxide–lead selenide, (10) 291*f*.

Poppa, H. Progress in the continuous observation of thin-film nucleation and growth processes by electron microscopy, (10) 281*i*.

Popper, P. Production of dense bodies of silicon carbide, P (11) 303*g*. (Editor) Special Ceramics 1964—Proceedings of a Symposium Held by the British Ceramic Research Association, Stoke-on-Trent, July 1964, B (11) 320*e*. See Chantrell, P. G.; Moulson, A. J.

Popper, P., and Mohyuddin, I. Preparation and properties of pyrolytic silicon carbide, B (11) 320*e*.

Poquet, E., and Pacault, A. Re-evaluation of the magnetism of carbons, (4) 112*j*.

Porcelain Enamel Institute, Standards Committee. Test for alkali resistance of porcelain enamel, (9) 232*d*.

Porembka, S. W. See Carlson, R. J.

Poretskaya, L. V., Abrikosov, N. Kh., and Glazov, V. M. Investigation of the system Sb–Te in the region of the compound Sb_2Te_3 in the solid and liquid states, (10) 287*f*.

Porneuf, A. Industrial casting of uranium carbide, B (6) 172*f*.

Port, E. B. See Sopchak, P.

Porta, P. See Cimino, A.

Porter, E. H. Monocrystal transistors with region for isolating unit, P (9) 243*h*.

Porter, W. F. See Garrison, J. W.

Porter, W. L. Laminated glass, P (9) 236*e*.

Portnov, V. N. See Belyustin, A. V.

Portnova, V. A. See Botvinkin, O. K.

Porto, S. P. See Nassau, K.

Possis Machine Corp. Apparatus for preparing specimens for chromatographic analysis, P (10) 281*f*.

Posypaiko, V. I. Method of determining the degree of stable diagonals in multicomponent reciprocal systems, (1) 23*h*.

Posypaiko, V. I., and Dombrovskaya, N. S. Exchange reactions in the five-component reciprocal system of the chlorides, bromides, and nitrates of sodium, rubidium, and thallium, (1) 21*j*.

Poteat, L. E., and Yust, C. S. Creep of polycrystalline thorium dioxide, (9) 249*a*.

Potter, P. E. Effect of oxygen on the sintering of UC and $(U_{0.8}Pu_{0.2})C$, B (6) 172*d*. Volatility of plutonium carbide, B (6) 172*j*.

Pottinger, J. S. See Brett, H. H.

Pouget, R. See Bariand, P.

Pouilly, M. L. Factors and equipment in the spraying of porcelain enamel, (7) 178*h*.

Poulsen, E. See Bredsdorff, P.

Pound, G. M. Statistical mechanics of nucleation and crystal growth, B (7) 204*d*.

Povitskii, V. A. See Malyuchkov, O. T.

Powder Melting Corp. Powder melting torch, P (3) 60*b*.

Powell, D. E., and Spear, B. W. Cathode-ray and other vacuumized tubes resistant to fracture and capable of controlled devacuation, P (3) 72*e*; tubes resistant to violent devacuation, P (3) 72*f*.

Powell, E. R. Apparatus for making foamed ceramic products, P (5) 130*f*.

Powell, R. W., and Tye, R. P. Thermal conductivities of some electrically conducting compounds, B (11) 320*g*.

Power, R. B. Cold cathode display device with fluorescent indicia anodes, P (9) 243*a*.

Power Jets (Research & Development), Ltd. Production of dense bodies of silicon carbide, P (11) 303*g*.
Powers, J. T. See Schroeder, A.
Powers, W. H. Ceramic coated muffler with liquid flow gaps between partitions and shell, P (5) 120*a*. Method of manufacturing a muffler including coating with ceramic, P (7) 179*e*.
Powers, W. H., and Russell, C. K. Dolomite brick and method of making it, P (11) 302*c*.
Pozela, J. See Dienys, V.; Kalvenas, S.; Silalnikas, V.
Pramaggiore, A. See Alfille, L.
Prandl, W. Refinement of garnet structure by neutron diffraction, B (2) 55*f*.
Prasad, J. Effect of some physical factors on the differential thermal analysis of kaolinite, (1) 20*e*. Infrared absorption spectra of some clay minerals and mica type structures, (6) 168*e*. See Bishui, B. M.
Prasad, J., and Bishui, B. M. Dehydroxylation reaction kinetics of some Indian kaolinitic clays, (2) 49*g*.
Prasad, S. N. See Gupta, S. K.
Prasad, T. V. Studies on Indian refractory clays—examination of clays by DTA and X-ray and electron microscopic techniques, (7) 203*b*. See Yedavalli, B. V. S.
Pratt, C. R., Jr., and Tarcza, W. H. Electrical capacitor, P (10) 278*d*.
Pray, R. E., and Schieltz, N. C. Gypsum crystals form in portland cement in a desiccator over a water-sulfuric acid solution, (8) 207*c*.
Precision Metalsmiths, Inc. Apparatus for forming ceramic shell molds, P (5) 125*g*. Ceramic shell molds and methods of production, P (7) 188*j*.
Preisler, E. See Petzow, G.
Preiss, K. Measuring the thickness of a concrete slab by gamma ray transmission, (9) 231*f*.
Prelesnik, A. See Blinc, R.
Preliwitz, S. B. Elongated relatively thin metal capacitor probe in combination with a conveying means for determining the dielectric properties of bulk material, P (11) 311*d*.
Presnov, V. A. See Krasil'nikova, L. M.
Pressler, M. F. See Horan, J. J.
Presto, V. Influence of zirconium opacifiers on ceramic colors, (1) 12*j*.
Preston, E. Platinum in the glass industry—design of protective sheathing, (11) 301*i*.
Preston, P. J. Method for cooling a gaseous suspension of titanium dioxide, P (2) 47*h*.
Preudhomme, J. Method of and apparatus for cutting glass, P (11) 298*e*.
Preuss, H. J. See Broemer, H.
Prewitt, C. T. See Wuensch, B. J.
Prezioni, L. M., and Zecca, J. J. Baseless double-ended electric incandescent lamp, P (10) 277*i*.
Pribble, G. See Niesen, R.
Price, A. F. See Lavin, E.
Price, C. E., and Walworth, C. B. Refractory composition, P (4) 102*b*.
Price, P. B. See Brill, R. H.
Price, R. J. Young's modulus of pyrolytic carbon in relation to preferred orientation, (2) 54*a*.
Price, W. R., and Stringer, J. Oxidation of vanadium at high temperatures, (3) 68*c*.
Priest, J., Caswell, H. L., and Budo, Y. Stress anisotropy in silicon oxide films, (2) 51*h*.
Prikhodchenko, N. A. See Budnikov, P. P.
Primak, G. J. Method for the production of casting slip, P (9) 242*c*.
Primak, W., and Luthra, J. Radiation blistering—interferometric and microscopic observations of oxides, silicon, and metals, (9) 254*i*.
Prince, E. Sublattice magnetizations in lithium ferrite as a function of temperature, B (2) 55*j*.
Prince, F. J., and Szell, C. Radiant gas burner, P (2) 46*f*.
Prindle, H. B. See Harrell, B. R.
Prior, H. A. See Taylor, B. L.
Prismo Safety Corp. Process of peening metals with coated glass beads, P (4) 98*c*. Reflective spheroids, P (8) 213*i*. Reflex reflective granule and marking material made thereof, P (8) 213*i*. Retro-reflective particles and reflective markers and compositions containing such particles, P (8) 213*j*.
Pritchard, C. Formation of *pn* junctions in silicon, P (11) 306*c*.
Pritchard, C., and Zeitman, S. A. Processing semiconductive material, P (11) 307*h*.
Pritchard, D. H. Cascaded phosphor layers for color display including one of discrete coherent particles, P (4) 104*c*.
Probst, H. B. See Sanders, W. A.
Prochazka, R. Continuous measurement of dust concentration at working points by means of electrical contacts, (2) 44*a*.
Proctor, B. A. Fracture of glass, (2) 31*c*. See Mallinder, F. P.
Products Development Co. Method of upgrading sand, P (4) 101*j*.
Produits Chimiques Pechiney-Saint-Gobain. Porous products based on alumina, P (10) 274*j*.
Proffitt, P. M. C. See Chirnside, R. C.
Prohaszka, P. J. H., and Enos, W. K., Jr. Glass tube cooling device and method, P (9) 236*c*.
Prokof'eva, Z. I. See Tsaritsyn, M. A.
Prokopets, V. F. See Bil'tyukova, E. P.
Prokopowicz, T. I., and Geller, H. I. Modified barium titanate ceramic materials and capacitor, P (4) 105*g*.
Protti, A. M. See Amato, I.
Pshenitsyn, P. A. See Shal'nev, K. K.
Pucher, S. Direct determination of alumina in cement analysis by electrochemical indication, (3) 58*h*.
Puddington, I. E., and Sirianni, A. F. Process for producing readily dispersible SiO_2 and Al_2O_3 solids, P (3) 79*a*.
Pugachev, N. S. See Verkhorobin, L. F.
Pugh, J. D. See Shaw, R.; Steadman, R.
Pugh, N., and Bell, T. Standardization in color control, (6) 146*g*.
Pukh, V. P. See Vitman, F. F.
Pulfrich, H., and Stopora, H. Metallizing sintered alumina ceramic bodies, P (6) 154*j*.
Pullman, Inc. Method of sealing refractory vessel containing radioactive wastes, P (1) 11*d*. Pneumatic apparatus for handling pulverulent materials, P (4) 107*a*. Tunnel kiln system, P (7) 196*b*.
Purvis, R. J. Mica sheet composite and method of making, P (2) 42*i*.
Pustovalov, V. V. Thermal conductivity of refractory powders and sintered ceramics, (2) 37*h*.
Putnam, J. T. Refractories, (2) 36*g*.
Putner, T. See Ball, R.
Pyrotemp Corp. Pyrometric lance apparatus, P (11) 311*d*.

Qazi, M. A., and Faruqi, F. A. Low-lead borosilicate glazes for artware, (11) 304*b*.
Quaas, J. F. Carbide welding rod, P (8) 208*a*. Flux-coated welding electrode and composition, P (5) 120*b*. See Barr, L. C.; Wasserman, R. D.
Quaas, J. F., and Broderick, J. P. Flame-spraying torch, P (4) 91*h*. Method, filler alloy, and flux for brazing, P (9) 232*b*.
Quaiser, N. Exploratory drilling of refractory clays, (8) 225*b*.
Quaker Oats Co. Method for manufacturing foundry cores and molds, P (2) 38*f*.
Quality Components, Inc. Ceramic capacitor, P (8) 220*a*.
Quarrell, A. G. Metallography—a hundred years after Sorby, B (6) 173*g*.
Quartz & Silice S. A. Process of forming dielectric materials for condensers, P (3) 74*e*.
Quast, H. F., and Rummel, T. Device for pulling monocrystalline semiconductor rods, P (5) 128*b*.
Quate, C. F. See Haydl, W. H.
Quetsch, J. G., Jr. See De Mille, C. L.
Quezel-Ambrunaz, S., and Mareschal, M. Crystal parameters of rare earth chromites, (6) 166*d*.
Quigley Co., Inc. High density, high refractory ceramic composition for open hearth furnace bottoms and method, P (6) 154*d*. Method of producing lightweight high temperature [acid] refractory products, P (1) 11*d*. Refractory slurry mixer and applicator, P (7) 189*j*.
Quinn, R. A., and Hollander, L. E., Jr. Semiconductive diode of single-crystal rutile and method of making, P (1) 15*h*.
Quinn, R. G. Asbestos-glass fiber saturating paper containing thermoplastic resin and aluminum acid phosphate, P (1) 10*h*.
Quinn, R. M. Method and apparatus for detecting surface unevenness, P (7) 183*g*.
Quinn, T. O. Apparatus for pressing slurries, P (5) 130*h*.
Quiroz, R., and Ronco, J. J. Power consumption in granular solid systems in discontinuous rotary cylinders (III) cylinders with blades, (1) 15*j*.
Quist, T. M. See Zeiger, H. J.
Quist, W. E. See Davis, R. A.
Quittkat, W. Phase formation reactions during the burning of cement raw mixes containing lime, hydrated lime, and limestone and their importance in the burning process, (1) 2*g*.
Qureshi, M. H. See Ashraf, M.
Qureshi, S. A., and Reza, S. Study on "static" fluidization, (11) 312*b*.

Raab, V. C. See Mitchell, W. J.
Raalte, J. A. van. Conduction phenomena in rutile single crystals, (4) 110*b*.
Rabenau, A. See Eckerlin, P.
Rabenau, A., Roeder, E., and Scholz, S. Method for the study of sintering of refractories up to 3000°C and 1000 kg/cm², (11) 301*h*.
Rabinovich, A. E., and But, A. I. Automatic electrical dewatering of ceramic slips, (2) 39*a*.
Rabinovich, S. M. Apparatus for measuring the thickness of silver layers on mirrors, (10) 280*h*.
Rabkin, D. M. See Bukhalova, G. A.
Rabson, T. A. See Lu, S.
Rabukhin, A. I. See Matveev, M. A.
Raczek, T. A. Method of preparing paper from mica flakes and a silicone, P (6) 160*b*.
Radford, C. Raw materials (V) flint and quartz, (3) 78*j*; (VII) effect of flux in a body, (4) 102*i*. See Griffiths, R.; Robinson, P. C.
Radiant Color Co. Bright pastel compositions containing daylight fluorescent pigments, P (4) 104*c*.
Radio Corp. of America. Apparatus for manufacturing reed switches, P (10) 267*a*. Art of making electron-optical reticles, P (4) 104*j*. Cascaded phosphor layers for color display including one of discrete coherent particles, P (4) 104*c*. Color cathode ray tube with index stripes on ultraviolet-emitting phosphor layer, P (11) 305*d*. Device for producing recombination radiation, P (10) 278*c*. Doubly doped titanium dioxide maser element, P (11) 305*g*. Electron mounting structure of a high frequency electron tube, P (6) 150*f*. Ferroelectric device, ferroelectric body, and method of fabrication, P (1) 14*b*. Method of adhering [phosphor] particles to a support surface, P (11) 306*j*. Method of and apparatus for sealing glass-type envelopes, P (10) 278*d*. Method of fabricating semiconductor devices, P (3) 73*j*, P (10) 278*h*. Method of forming semiconductor junction, P (8) 221*h*. Method of making luminescent screens for cathode ray tubes, P (11) 306*f*. Method of making magnetic ferrite sheet with embedded conductors, P (7) 193*e*. Method for preparing rare earth activated zinc sulfide phosphors and products thereof, P (11) 306*j*. Methods and materials for metallizing ceramic or glass bodies, P (2) 42*h*. Monoclinic zinc phosphide preparation, P (4) 105*h*. Multilayer semiconductor electroluminescent output device, P (11) 307*d*. Nonlinear tunnel resistor and method of manufacture, P (6) 160*i*. Ohmic contact to III-V semiconductive compound bodies, P (2) 42*a*. Process for preparing luminescent [silicate] materials, P (1) 15*c*. Radiation powered semiconductor devices, P (10) 279*b*. Semiconductive devices, P (11) 307*e*. Semiconductor devices, P (2) 42*k*, P (6) 160*g*. Semiconductor devices with silver-gold lead wires attached to aluminum contacts, P (11) 307*h*. Solid state devices utilizing a metal between two semiconductor materials, P (7) 194*b*. Solid state triode, P (7) 194*c*. Square loop molybdenum modified ferrites, P (3) 74*a*.
Radkova, A. See Brashnarova, A.
Rado, P. Evolution of porcelain, (5) 127*d*.
Radomysel'skii, I. D. See Apininskaya, L. M.
Radwan, M. K. Suggested template to be used in the characterization of some silicate minerals in the OH region of the infrared spectrogram, (7) 203*c*.
Raentsch, K., and Vogel, A. Method of producing a glass scale, P (4) 97*d*.
Raether, H. Avalanches and gas breakdown, B (9) 259*f*.
Raff, H., and Schwesinger, G. Effect of internal stress on the rigidity of large glass lenses and telescope mirrors, (2) 31*g*.
Ragan, R. C. Electrical resistor and method of producing, P (8) 220*h*. Precision electrical fuse, P (11) 307*f*.
Ragone, D. V. Studies of properties of uranium-containing carbides for thermionic conversion, B (6) 172*a*.
Raibourn, P. Color screen with electron- and light-absorptive material separating adjacent color strips, P (3) 72*i*.
Raine, F. F. Refractory and process of making, P (6) 155*e*.
Rairden, J. R., and Smith, W. H. Chemically formed oxide coating on aluminum, P (8) 207*h*.
Raitburd, Ts. M., and Slonimskaya, M. V. Nature of the hydration of exchange cations in clay minerals, (3) 83*j*.
Rakov, I. D. See Zezin, M. A.
Rakowsky, V. Whirlpool apparatus, P (2) 48*c*.
Rakszawski, J. F. See Parker, W. E.
Raleigh, C. B. Crystallization and recrystallization of quartz in a simple piston-cylinder device, (1) 19*i*.
Ralkova, J. Diffusion of radioisotopes in basalt, (7) 198*e*.
Ralph, B. See Ranganathan, S.
Ralph, B., and Bowkett, K. M. Streak contrast in field-ion micrographs, (9) 246*c*.
Ramachandran, S. Chemical durability of some industrial glasses, (7) 179*g*.
Ramachandran, V. S. See Chopra, S. K.; Feldman, R. F.
Ramachandran, V. S., Feldman, R. F., and Sereda, P. J. Unsoundness test for limes without cement, (2) 29*c*.
Ramakrishna, J. Electric field gradients in ionic crystals (III) nuclear quadrupole resonance in thorium tetrachloride, (10) 285*a*.
Ramos, G. G. See Garcia Ramos, G.
Rampton, V. W. See Fletcher, J. R.
Ramsay, R. C. See Dettling, C. J.
Ramsey, T. H., Steinfink, H., and Weiss, E. J. Phase equilibria and crystal chemistry of the rare earth group VI systems (IV) lanthanum–tellurium, (5) 139*a*.
Ranachowski, J. Mechanical strength of electrotechnical porcelain and its determination by nondestructive methods, (11) 304*c*.
Ranby, P. W., and Palowkar, D. R. Titanium and tin activated magnesium borate lumines cent material, P (4) 106*f*.
Rand, M. H. Some inconsistencies in the thermodynamic data for uranium compounds, B (6) 175*f*.
Rand, M. H., and Street, R. S. Anomalous thermal expansion in the plutonium monocarbide phase region, B (6) 171*j*.
Randklev, E. H. See Pettit, F. S.
Randoux, M. See Coekelbergs, R.
Ranford, R. E., and Flengas, S. N. Platinum-rhodium-oxygen electrode in silicate melts, (5) 139*j*.
Ranganathan, S., Bowkett, K. M., Hren, J., and Ralph, B. Interpretation of field-ion micrographs—streak contrast, (3) 82*j*.
Rank, E. G. See Cater, E. D.; Eick, H.
Rank Precision Industries, Ltd. Testing of surface straightness, P (1) 17*c*.
Rao, B. V. J. Reply to discussion of "Properties and structure of glasses in the binary systems alkali–TiO_2," (1) 5*i*.
Rao, H. V. B. See Murthy, H. P. S.; Yedavalli, B. V. S.

Rao, S. V. L. N. See Berry, L. G.
Rao, V. V. S. Calcination and sintering study of ceria, (2) 48*h*.
Rappaport, P., and Pasierb, E., Jr. Radiation powered semiconductor devices, P (10) 279*b*.
Rappeneau, J., Bocquet, M., Micaud, G., and Fillatre, A. Effects of radiation on the physical properties of graphites, (4) 110*f*.
Rapson, J. E. Petrography and derivation of Jurassic-Cretaceous clastic rocks, southern Rocky Mountains, Canada, (3) 78*i*.
Rasch, R. Catalytic separation of carbon in fireclay brick, (7) 185*f*. Investigation of refractoriness under load, (3) 68*a*. Secondary reactions in the silica transformation, (8) 227*a*.
Rashid, A. See Hashmi, M. H.
Rasmussen, E. Apparatus for conveying finely divided material, P (5) 130*f*.
Rasmussen, F. Air separator with fluidized discharge, P (11) 308*j*.
Rasmussen, S. E. See Christensen, A. N.
Rassel, P., and D'Harcour, J. C. Direct-on and conventional enameling of decarburized steel sheets, (10) 263*d*.
Rasul, C. G., and Cable, M. Spontaneous bubble formation in silicate melts at high temperatures, (11) 297*i*.
Ratcliff, G. J. See Belasco, M.
Ratcliff, G. J., and Belasco, M. Alloy-diffusion process for fabricating germanium transistors, P (10) 277*g*.
Rateyev, M. A. Modification degree of clay minerals during the stage of sedimentation and diagenesis of marine deposits, B (2) 56*e*.
Rath, J. Modulus of elasticity of a two-component material, (10) 288*h*.
Rathenau, G. W. Electrons in metallic systems, B (9) 259*f*.
Rau, F. J. See Ward, C. R.
Rauch, G. C., Rose, R. M., and Wulff, J. Observations on microstructure and superconductivity in the niobium–hydrogen system, (7) 201*c*.
Rauch, H. W., Sr. See McCreight, L. R.
Rauland Corp. Electron discharge devices, P (6) 159*e*.
Raulickyte, A. See Pipinys, P.
Raup, O. B. Clay mineralogy of Pennsylvanian redbeds and associated rocks flanking Ancestral Front Range of central Colorado, (5) 132*j*.
Rauschenfels, E. See Abraham, D.
Rauscher, H. E. See Garfinkel, H. M.
Rausell-Colom, J. A. Swelling of butyl-ammonium-vermiculite, B (2) 56*i*.
Rawling, J. R., and Elliott, J. F. Reduction of silica in blast furnace slag–metal systems, (1) 9*g*.
Rawson, H. Graphical methods for the conversion of binary and ternary glass compositions from weight to mole percentages, (3) 61*g*. Report on the symposium on glass in electronics, (11) 297*e*. See Adams, R. V.
Rawstron, G. O. Testing of surface straightness, P (1) 17*c*.
Ray, N. H. Manufacture of finely divided silica, P (5) 133*d*.
Raybestos-Manhattan, Inc. Molded composition brake shoe comprising organic bond, hard mineral filler, and cryolite, P (4) 101*a*.
Rayne, J. A. Some electronic properties of extensive solid solutions and intermetallic compounds, B (6) 171*g*.
Rayner, J. H. Multivariate analysis of montmorillonite, (6) 169*b*.
Raynor, E. J. See Wyllie, P. J.
Raytheon Co. Fabrication of barrier material devices, P (3) 73*c*. Ferroelectric signal-translating device having voltage-controlled signal delay, P (6) 159*g*. Stress sensitive tunnel diode transducer, P (11) 308*a*. Transistor, P (3) 74*d*.
Read, J. E. See Riviere, J. C.
Readey, D. W. Mass transport and sintering in impure ionic solids, (8) 226*i*.
Readey, D. W., and Kuczynski, G. C. Sublimation of aluminum oxide in hydrogen, (2) 52*c*.
Reagan, P. E., Morgan, J. G., and Sisman, O. Fission-gas release from pyrolytic-carbon-coated fuel particles during irradiation at 2000° to 2500°F, (6) 152*d*.
Reaney, D. W. See Reaney, W. A.
Reaney, W. A., and Reaney, D. W. Rotary calcining kiln, P (11) 295*b*.
Reardon, P. H. Pitch lens blocker ball and blanks, P (11) 299*d*.
Reas, L. F. See Knapp, E. J.
Rebel, J. W. Method of manufacturing display screens for cathode-ray tubes, P (3) 73*d*.
Rebinder, P. A. See Luk'yanova, O. I.; Lyubimova, T. Yu.; Markov, A. I.; Sil'chenko, L. A.; Ur'ev, N. B.
Rech, W. J. Method of making ceramic dishware, P (11) 304*c*.
Rechter, H. L. See Bliton, J. L.
Rectenwald, C. E. See Clark, J. W.
Redican, F. W., Blair, L. R., Yang, J. C., and Gorman, R. J. Manufacture of asbestos-cement products, P (2) 38*b*.
Rediker, R. H. See Besson, J. M.; Zeiger, H. J.
Redman, M. J. See Newnham, R. E.
Reduction Engineering Corp. Classifying and reducing method and apparatus, P (8) 225*b*.
Reed, R. See Marsh, H.
Reed, R. D., Goodnight, H., and Zink, J. S. Burner assembly producing radiant heat, P (10) 282*f*.
Reed, R. J., and Lanzdorf, J. H. Firing and controlling kilns above 3000°F, (7) 195*f*.
Reed, T. B., and Fahey, R. E. Electric furnace for operation in oxidizing, neutral, and reducing atmospheres to 2400°C, (10) 282*a*.
Reeg, C. P. See Ch'in, N. C.-H.
Rees, V. C. Electrical control system, P (4) 108*g*. Programming apparatus, P (4) 108*f*.
Reese, T. J. See Cox, S. F.
Reesman, A. L., and Keller, W. D. Calculation of apparent standard free energies of formation of six rock-forming silicate minerals from solubility data, (9) 248*f*.
Reeve, K. D., and Clare, T. E. Comments on "Sintering in very pure magnesium oxide and magnesium oxide containing vanadium" and "Sintering in calcium oxide and calcium oxide containing strontium," (8) 226*a*.
Reeves, C. C., Jr. See Dixon, J. R.
Refractory & Insulation Corp. Electrostatic precipitator power connection, P (2) 43*e*.
Regan, M. C. See McLaren, J. R.
Regelson, E. Infrared calibration lamp, P (3) 73*f*.
Reggia, F., and Jones, H. S., Jr. Reciprocal ferrite waveguide phase shifter having means to rotate the magnetic field about an axis transverse to the longitudinal axis of the ferrite rod, P (10) 279*c*.
Regie Nationale des Usines Renault. Refractory and cohesive materials having metallic phase and ceramic phase, method of producing, and method of coating using them, P (2) 38*f*.
Regourd, M. Determination of the lattice of microscopic crystals—application to the different forms of calcium trisilicate, (7) 198*i*.
Reh, H. H. Methods of developing a dense cordierite body, (10) 272*b*.
Reiber, H. Photoflash lamp, P (10) 279*g*.
Reich, H. F. Causes of the different degrees of expansion and contraction of corundum-containing fireclay brick, (7) 185*h*. Relations between densification, mullite formation, slag resistance, and firing of [refractory] clays, (2) 36*i*. See Konopicky, K.
Reich, H. F., and Hartmann, W. Method for the simultaneous determination of the workability and water retention of refractory mortars, (7) 187*c*.
Reichard, H. F. See Dresher, W. H.
Reid, A. F. See Halff, A. H.
Reid, A. M. See Forber, A.; Parry, R. J.
Reid, C. N., Gilbert, A., and Rosenfield, A. R. Dislocation multiplication, (3) 81*a*.
Reid, F. J. See Matson, L. K.
Reid, L. E. See Holzinger, R. J.
Reid, R. B. Thermal boundary construction, P (9) 241*d*.
Reidl, R. W. See Lenihan, W. S., Jr.
Reidl, R. W., and Hartwig, J. Titanium diboride articles and method for making, P (2) 38*i*.
Reijnders, A. Device for bending a straight tube into a circular shape, P (2) 33*f*.
Reijnen, P. Equilibrium between ferrites with a spinel structure and oxygen, (7) 191*j*.
Reiling, G. H. Metallic halide electric discharge lamps, P (5) 128*j*.
Reilley, J. M., Wooding, W. H., and Moore, T. J. Electric arc welding flux and method, P (1) 3*g*.
Reimschussel, G. P. See Sadler, T. H.
Reinecke, H. See Kurz, E.
Reinecke, P. W. See Galer, R. E.
Reinen, D., and Schmitz-Du Mont, O. Color and constitution of inorganic solids (IV) use of light absorption for determining structural features in crystal lattices, (3) 80*e*.
Reiners, E., and Otters, E. Vibratory mill, P (11) 309*c*.
Reinhard, R. H. Clay beneficiation, P (2) 47*d*.
Reinhardt, K. Young German ceramists—exhibition in Muthesius-Werkkunstschule, Kiel, West Germany, (10) 262*a*.
Reintjes, Geo. P., Co., Inc. See Geo. P. Reintjes Co., Inc.
Reintjes, G. P., and Byfield, D. R. Dryer furnace wall tile, P (3) 77*f*.
Reis, W. von. See Eichhorn, R.
Reitmayer, F. Dispersion of some optical glasses in the spectral region 0.33 to 2.0*μ* and its dependence on the characteristic frequency of the glass, (2) 31*g*. See Schuster, E.
Reller, V. S. Cold water quicklime slaker, P (3) 59*e*.
Remeika, J. P. See LeCraw, R. C.; Marezio, M.; Wood, D. L.
Remington, R. C. Precision glass molding process and apparatus, P (2) 34*d*.
Remmey, G. B. See McFadden, C.
Renaud, R. See Josien, F. A.
Renkey, A. L. Refractory shapes, P (6) 155*f*.
Rennen, H. See Schwiete, H. E.
Renner, H. Separation of zirconium, hafnium, niobium, and tantalum by introducing as a dry solid into the central step of a liquid-liquid partition system, P (10) 283*d*.
Renshaw, G. D. See Thomas, J. M.
Repkin, Yu. D. See Samsonov, G. V.
Repsher, R. W. See Van Broekhoven, J.
Republic Steel Corp. Refractory composition, P (3) 70*i*.
Research Corp. Process for separating rare earth metal values, P (11) 312*i*.
Resnick, R., Steinitz, R., and Seigle, L. Determination of diffusivity of carbon in tantalum and columbium carbides by layer-growth measurements, (5) 135*b*.
Restall, J. E. See Glenny, E.
Reti, A. R., Brian, P. L. T., and Foagland, L. C. Short-time high temperature oxidation of cobaltous oxide, (5) 140*g*.
Rettig, G. Granulation—its place in chemical engineering, (1) 15*a*.
Reumann, O. Ceramic colors for underglaze decoration and for staining bodies and glazes, (3) 71*c*.
Reuschel, K. Method of doping semiconductor material, particularly silicon, with boron, P (6) 159*g*. Method of producing electronic semiconductor devices by precipitation of monocrystalline semiconductor substances from a gaseous compound, P (4) 105*c*.
Reuschel, K., and Keller, W. Method for producing a semiconductor device with a monocrystalline semiconductor body, P (4) 105*e*.
Reuter, R. Method of preparing ceramic molds, P (3) 70*d*, P (9) 240*e*.
Reuter, R. A. Duplex carbon-coated fuel particles, (3) 66*d*.
Revnivtsev, V. I., Dmitriev, Yu. G., et al. Use of ultrasonics for enriching quartz sands, (2) 47*a*.
Revolinsky, E., Brown, B. E., Beerntsen, D. J., and Armitage, C. H. Selenide and telluride systems of niobium and tantalum, (8) 227*a*.
Rez-Radiant, Inc. Gas burner, P (11) 311*f*.
Rexall Drug & Chemical Co. Abrasive articles and methods of making, P (7) 177*i*.
Rexford, H. E. Method of fire-polishing edges of hollow articles, P (8) 213*f*.
Reynolds, C. B. See Jenkins, J. D.
Reynolds, D. H. See Roman, R. J.
Reynolds, F. H., and Elliot, A. B. M. Etching corundum with silicon, (9) 250*a*.
Reynolds, R. C., Jr. X-ray study of an ethylene glycol-montmorillonite complex, (6) 171*a*.
Reynolds, W. N. See Goggin, P. R.
Reynolds, W. N., and Thrower, P. A. Enhanced nucleation of radiation damage in graphite, (4) 111*f*. Nucleation of radiation damage in graphite, (2) 50*j*.
Reynolds Metals Co. Alumina hydrate and method of preparation, P (10) 273*b*. Continuous casting system, P (1) 11*b*. Method of molding alumina, P (11) 302*c*. Process for producing substantially kappa-phase alumina, P (4) 109*f*. Process for the production of alumina, P (6) 164*j*.
Reys, J. Coated graphite products, P (10) 273*d*.
Reza, S. See Qureshi, S. A.
Reznikov, L. G. Machines for glazing household porcelain, (2) 39*g*.
Rhead, G. E. Surface diffusion and the growth of oxide particles on metal surfaces, (2) 52*g*.
Rheem Mfg. Co. Glass-coated steel article, P (11) 295*j*.
Rheinische Kalksteinwerk G.m.b.H. Method and system for the automatic controlling of grid coolers or traveling grids, P (1) 3*a*.
Rhinehart, W. L. See Grebe, J. J.
Rhodes, J. R. Method and apparatus for measuring the concentration of an element in a mixture by an X-ray absorption analysis technique, P (11) 311*a*.
Rhodes, W. H. Etching and chemical polishing of single-crystal $SrTiO_3$, (3) 81*g*.
Rhodes, W. H., and Carter, R. E. Cationic self-diffusion in calcia-stabilized zirconia, (6) 165*e*.
Rhodes, W. H., and Kingery, W. D. Dislocation dependence of cationic diffusion in $SrTiO_3$, (11) 315*g*.
Rhyne, J. W., Jr. See Lander, J. J.
Ribaud, G. L. Bonded molecular sieves, P (2) 47*d*.
Rice, A. C. Fraction separation of aqueous rare earths using amines, P (9) 247*e*.
Rich, D. J. See Mattare, L. A.
Rich, E. A. E., and Brockman, J. J. Gearless rotary mill, P (11) 308*j*.
Rich, M., and Pernichele, A. D. Petrography of portions of the Duperow formation (Upper Devonian) in western North Dakota, (2) 46*j*.
Richard, E. J. Mold for steel casting, P (8) 218*a*.
Richard, J. D. Particle size analyzer, P (1) 17*a*.
Richards, James D. See Fritts, R. W.
Richards, John D. Effect of various sulfate solutions on the strength and other properties of cement mortars up to 80°C, (1) 2*j*.
Richards, Joseph D. See Cheever, G. D.
Richards, K. J. Oriented growth of dehydration products of calcium sulfate dihydrate, (7) 178*d*. See Wagstaff, F. E.
Richardson, F. D. See Meadowcroft, T. R.; Sharma, R. A.
Richardson, H. M. See Carr, K.
Richardson, R. E. Blowing frame for tempering glass sheets, P (4) 96*a*. Glass bending apparatus with pivot support points, P (3) 63*h*. Method and apparatus for bending glass sheets, P (5) 123*g*.
Richardson, S. H. See Mayer, W. P.
Richartz, W., and Locher, F. W. Morphology and combination with water of calcium silicate hydrates and the structure of hardened cement paste, (2) 28*f*.
Richter, A. See Gobrecht, H.
Ricke, W., and Schaudinn, K. High tension capacitors made of high dielectric constant ceramics, (9) 241*j*.
Ricker, W. C., and Simpson, G. H. Encapsulated thermostatic switch having a heater in the stem, P (11) 306*a*.
Rickles, R. N. See Luberoff, B. J.
Ricklin, S. See Rulon-Miller, R.
Ridge, M. J., and Boell, G. R. Water requirement of calcined gypsum (IV) effects of gum arabic, (8) 207*b*.

Ridgley, D. H. See Rogers, D. B.; Whipple, E. R.
Ridout, D. E. U. See Ropp, R. C.
Riebling, E. F. Structure of B_2O_3 and binary aluminoborate melts at 1600°C, (2) 32*a*.
Riebling, E. F., and Logel, P. C. Dipping electrode electrical conductance instrument for use to 1700°C, (11) 310*b*.
Rieck, G. D. See Koopmans, K.
Riede, R. G. Method of preparing perlite products, P (5) 124*i*. See Vander Linden, C. R.
Riedel, L. Wetting of limestone and quartz by melting soda—a phenomenological study, (5) 122*b*.
Rieger, W. Planning and construction of tunnel kilns, (6) 163*j*.
Riek, M. R. High intensity carbon electrode, P (9) 243*f*.
Ries, H. B. Possibilities of rationalizing batch preparation of heavy clay bodies, (1) 7*f*.
Rieter-Werke K. G. Dipl. Ing. Walter Handle. Cylinder press for the manufacture of mitered tile, P (8) 214*e*.
Rieth, H. F. Ceramic capacitor, P (7) 192*a*.
Rietz, C. du. Chemisorption of collectors, B (7) 204*e*.
Rigby, G. R. Grooved refractory brick construction, P (8) 217*e*.
Rigden, S. A. R. See Mason, R. A. L.
Rigg, C. Report on the symposium on fuel and power in the glass industry, (11) 297*e*.
Rijckeart, J. F. Electric lamp, P (9) 243*c*.
Riley, B. Carbide formation by reaction hot-pressing of oxides and carbon, B (6) 172*d*.
Riley, H. L., and Romanski, A. Vanadium pentoxide potassium pyrosulfate catalyst and method of preparation, P (4) 102*b*.
Riley, J. D. See Roberson, C. L.
Riley, J. P. See Abdullah, M. I.; Brewer, P. G.; Chan, K. M.
Riley, L. W., Bass, M., and Hahn, E. L. Stimulated emission from 4.3% abundant ^{50}Cr ions in ruby, (1) 25*e*.
Riley, W. C. See Hove, J. E.; Kendall, E. G.
Rimsky, A. See Bariand, P.
Rindner, W., and Nelson, R. F. Stress sensitive tunnel diode transducer, P (11) 308*a*.
Ringot, C. Fuel element for nuclear reactors, P (1) 11*e*.
Rion, R. G., and Miller, G. E. New spall test for porcelain enameled aluminum, (6) 146*c*.
Ripley, R. L. See Culbertson, J. B.; Lamprey, H.
Ripling, E. J. See Polakowski, N. H.
Riseman, J. See Maissel, L. I.; Perri, J. A.
Riseman, J. H. Glass electrode and method of making, P (4) 96*i*.
Ristic, M. M. Theoretical studies of the sintering process (I) characteristic magnitudes of the sintering process and mechanism; (II) sintering of a body with closed pores, (2) 37*g*; (III) kinetics of the initial phase of sintering from the standpoint of the theory of absolute reaction rates, (4) 113*i*; (IV) mathematical-phenomenological study of the kinetics of sintering, (5) 141*g*.
Ritchie, I. M. Thermoelectric bonding material, P (5) 130*b*.
Ritchie, T. Effect of restraint on the shrinkage of masonry mortars, (3) 58*i*. See Gillott, J. E.
Rittenhouse, J. B., and Singletary, J. B. Materials for space stations, (5) 133*d*.
Ritter, C. J., and Dennen, W. H. Blackening of natural quartz by γ-irradiation, (11) 314*c*.
Ritter, G. F., Jr. Method and apparatus for press bending and tempering glass sheets, P (10) 268*a*.
Ritter, G. F., Jr., and Carson, F. J. Marking apparatus, P (4) 97*c*.
Ritter, G. F., Jr., and Welker, R. H. Apparatus for cutting sheets of glass, P (6) 149*j*; method, P (5) 123*d*.
Ritter, J. A. Plastering composition, P (4) 91*a*.
Ritter, J. C., Robinson, M. N., Faraday, B. J., and Hoover, J. I. Room temperature oxidation of silicon during and after etching, (5) 140*c*.
Ritze, R. G. Apparatus for the classification of finely divided materials, P (2) 47*b*.
Ritzman, R. L. See Townley, C. W.
Ritzmann, H. Method of and arrangement for making cement clinker, P (6) 144*j*.
Rivas, J. L. A. See Alvarez Rivas, J. L.
Rivers, W. F. Dry material [pneumatic] transfer apparatus, P (1) 16*a*.
Riviere, J. C. See Thorpe, T.
Riviere, J. C., Thompson, J. B., Read, J. E., and Wilson, I. Performance of a simple cryogetter pump, (2) 44*g*.
Rivoir, L. See Smith, P.
Roach, G. H. Hot pressing of powdered refractory material, P (9) 240*e*. Method of continuously hot pressing powdered refractory material, P (10) 274*f*.
Roach, T. J. Method of forming a semiconductor rim by sandblasting, P (10) 278*j*.
Roark, R. J. Formulas for Stress and Strain, B (9) 258*c*.
Robbins, M. Site preference of Ge^{4+} in magnetic spinels, (5) 140*h*.
Robbins, M., and Banks, E. Effect of fluoride-compensated Co^{2+} on the anisotropy of $BaFe_{12}O_{19}$, (2) 49*e*.
Roberson, C. L. Apparatus for producing uniform continuous fibers, P (10) 267*c*.
Roberson, C. L., Canfield, S. A., and Riley, J. D. Viscometer for glass furnace, P (6) 151*b*.
Robert, R. R. See Mattern, J. S.
Roberts, E. S., and Christmann, L. J. Process for producing selenium dioxide, P (10) 283*g*.
Roberts, G. C. See Cox, G. A.
Roberts, G. J., and Roberts, J. P. Oxygen tracer investigation of the diffusion of "water" in silicate glass, (9) 234*h*.
Roberts, H. See Dowley, A.
Roberts, J. P. Introduction to "point defects," (5) 137*e*. See Roberts, G. J.
Roberts, L. E. J. See Markin, T. L.
Roberts, M. J. Ceramic aluminas and present trends in their development and use, (6) 164*b*.
Roberts, W. G. See Harrison, J. D. L.
Robertson, J. A. Microscope furnace stage, P (2) 45*i*.
Robertson, J. M. See Blodgett, W. E.; Pointon, A. J.
Robertson, J. S. Flex Lox jointed sewer pipe as developed by Clayburn-Harbison, Ltd., (6) 151*e*.
Robertson, R. F. See Salmon, T.
Robie, E. D. See Mendelsohn, L. I.
Robie, N. P. Silicon aluminum boride complex, P (3) 57*g*.
Robiette, A. G. E., and Brandes, E. A. Ceramic materials, P (3) 70*d*.
Robinson, L. B., Vahldiek, F. W., and Lynch, C. T. Hot pressing zirconia, P (2) 37*i*.
Robinson, M. N. See Ritter, J. C.
Robinson, P. Small tunnel kiln for firing miniature ceramic parts, (5) 132*e*.
Robinson, P. B. Research and development in the ceramic industry, (6) 171*d*.
Robinson, P. C. Raw materials (VI) origin and nature of ceramic fluxes, (4) 102*i*.
Robinson, P. C., and Radford, C. Raw materials (II) processing English ball clays, (1) 18*i*; (III) china clay, (I) 18*j*; (IV) quartz sand, chert, and flint, (2) 47*e*.
Robinson, P. H., and Mueller, C. W. Deposition of silicon upon sapphire substrates, (7) 191*e*.
Roche, M. A., Jr. See Lenihan, W. S., Jr.
Roche, M. A., Jr., and Fisher, J. C., Jr. Refractory article, P (8) 218*b*.
Rochow, H. See Eberle, L.
Rock Island Oil & Refining Co., Inc. Method and apparatus for forming glass-reinforced resin pipe, P (4) 97*f*.
Rockett, T. J., and Foster, W. R. System silica–sodium tetraborate, (2) 53*b*.
Rockwool Aktiebolaget. Apparatus for making pipe insulating shells from mineral wool, P (8) 211*f*.
Roden, J. S. See Strobach, C. G.
Rodionova, S. I. Change in the composition of glass during continuous flow, (1) 3*j*.
Rodis, F. See Cremer, J.
Rodrigue, G. P. See Hodges, L. R., Jr.
Rodriguez, A. R., and Cronin, J. Process for manufacturing multilayer ceramic capacitors, P (5) 129*d*.
Rodriguez, A. R., and Stapleton, R. E. Electric capacitor and method for producing, P (11) 305*h*.
Rodwell, W. See Thorn, J. D.
Roedder, E. Laboratory reconnaissance of the liquidus surface in the pyroxene system enstatite–diopside–hedenbergite–ferrosilite ($MgSiO_3$–$CaMgSi_2O_6$–$CaFeSi_2O_6$–$FeSiO_3$), (3) 83*e*.
Roeder, E. See Rabenau, A.
Roeder, E., and Scholz, S. Simple hot-press for laboratory investigations, B (11) 320*h*.
Roehrs, M. See Petzold, A.
Roering, C. See Heckroodt, R. O.
Roes, J. B. Method of forming an insulating bond, P (5) 129*a*.
Roesky, W. See Lehmann, H.
Rogacheva, E. D. See Belyustin, A. V.
Rogers, B. A. Nature of Metals, B (4) 115*d*.
Rogers, D. B. See Ferretti, A.
Rogers, D. E., Ferretti, A., Ridgley, D. H., Arnott, R. J., and Goodenough, J. B. Single-crystal growth and properties of the perovskites $LaVO_3$ and YVO_3, (9) 255*e*.
Rogers, D. G. Capacitor electrode and method, P (7) 192*j*.
Rogers, M. F., Jr. Glass recipe book of the New England Glass Company, (5) 118*c*.
Rogers, M. G. See Daniel, V.
Rogner, H. See Koester, A.
Rogovoi, M. I. Controlling the hardening of fused cast refractories, (6) 151*j*.
Rogovoi, M. I., Verlotskii, A. A., and Rublevskii, I. P. Fusion casting with hot tops—control of shrinkage cavities in the production of fused bakor refractories, (5) 125*f*.
Rogozhin, Yu. V. See Kulikova, E. N.; Zaionts, L. A.
Roi, S. See Meerson, G. A.
Roisli, A. Plasma—a new technology, (11) 311*h*.
Roiter, B. D. See Paladino, A. E.
Roj, W., and Hubert, A. Method of correcting the refractive index of optical glasses during melting, (8) 210*e*.
Rokhlin, P. N. See Shestak, N. A.
Rokhvarger, A. E. Automation of ceramic batching and mechanized mill loading, (6) 155*j*.
Rollet, A. P., and Cohen-Adad, R. Systems water–alkali hydroxide, (2) 53*b*.
Rollof, G. See Weiss, A.
Roman, R. J., Bhappu, R. B., and Reynolds, D. H. Manganese dioxide-sulfuric acid oxidation of molybdenite, (5) 138*g*.
Romanov, B. E., and Surovitskaya, G. I. Effect of chemical decolorizers on the degree of oxidation of iron in glass, (4) 92*j*.
Romanski, A. See Riley, H. L.
Rombau, P., and Peltier, M. Thorium oxides and mixed thorium oxides and method, P (2) 48*b*.
Romeo, P. L. Production of metal-carbon compounds, P (10) 274*g*.
Romstadt, J. L. Process and apparatus for [spray] filming irregular shaped objects, P (7) 184*f*.
Romstadt, J. L., and Vascik, R. A. Method of producing transparent electrically conducting glass sheets and article resulting therefrom, P (8) 213*b*.
Ronca, F. P. Sizing of abrasive grain, (7) 177*f*.
Ronco, J. J. See Quiroz, R.
Ropp, R. C. Luminescence of pyrosilicate structures activated by lead, (7) 200*h*.
Ropp, R. C., Gritz, E. E., Haberland, P. H., and Ridout, D. E. U. Cathodoluminescent properties of europium-activated yttrium and gadolinium oxides, (8) 219*g*.
Rosa, J. Magnesium hydrosilicates as stabilizers for magnesia cements, (2) 28*f*. Sound cements with high MgO content, (2) 29*h*. Three-stage clinker burning, (7) 178*e*. World standards and trends in cement and lime calcining, (2) 29*d*.
Roschuk, S. J. Process for producing crystalline alumina, P (2) 27*f*.
Rose, A. Solid state devices utilizing a metal between two semiconductor materials, P (7) 194*b*. Solid state triode, P (7) 194*c*. Space-charge-limited currents, B (9) 259*f*.
Rose, C. G., and Andersen, J. C. Refractory carbide bodies and method of making them, P (8) 224*k*.
Rose, K. S. B. See Sayers, J. B.
Rose, R. M. See Rauch, G. C.
Rosecrans, H. F. Method of applying binder to porous fibrous glass mats, P (5) 123*c*.
Rosen, E. See Masse, D. P.
Rosen, E., and Muan, A. Stability of $MgAl_2O_4$ at 1400°C as derived from equilibrium measurements in $CoAl_2O_4$-$MgAl_2O_4$ solid solutions, (3) 86*b*. Stability of zircon in the range 1180° to 1366°C, (1) 25*d*.
Rosen, G. See Anderson, W. L.
Rosen, S. See Felten, E. J.
Rosenberg, A. M. See Dodson, V. H.
Rosenberg, D. J. Oven for curling resin impregnated fibrous mat, P (6) 150*f*.
Rosenberg, M. D. Living cell, B (9) 259*f*.
Rosenblith, W. A. Sensory coding in the nervous system, B (9) 259*g*.
Rosenfield, A. R. See Reid, C. N.
Rosenqvist, I. T., and Graff-Petersen, P. (editors). International Clay Conference 1963–Proceedings of the Conference Held in Stockholm, Sweden, August 1963 (Vol. 2), B (2) 55*i*.
Rosenstein, R. D. See Donohue, P. C.
Rosenthal, G. Efflorescence, frost resistance, and silicone treatment of brick, (10) 270*d*.
Roshchina, P. A. See Mogilevskaya, O. Ya.
Rosmus, K. Austrian brick industry 1945–1965, (2) 35*c*.
Rosner, D. E., and Allendorf, H. D. High temperature kinetics of graphite oxidation by dissociated oxygen, (1) 22*d*.
Ross, A. J. See De Vries, E. R.
Ross, B. Semiconductor device, P (8) 221*j*.
Ross, James W., Jr. Method and apparatus for electrolytically determining a species in a fluid, P (9) 246*d*.
Ross, John W., Boynton, D. R., Mills, D., and Gallus, F. R. Apparatus for thermally working minerals, P (5) 133*b*.
Ross, M. O. See Nordquest, C. E.
Ross, O. P. Counterweight adjustments a vital factor in woven wire belt life, (8) 222*d*.
Ross, R. E., and Johnson, L. F. Bending mold with peripheral heat absorber, P (10) 267*f*.
Ross, R. P. Steelmaking furnace, P (11) 303*i*.
Ross, W. A. Ceramic firing forum, (1) 17*f*.
Rossi, A. T. Machine for printing on bottles, P (11) 298*d*.
Rossi, R. C., and Fulrath, R. M. Final stage densification in vacuum hot-pressing of alumina, (1) 21*c*.
Rossiter, M. J. Moessbauer spectra of some spinel oxides containing iron, (5) 138*g*.
Rostokinskii, V. V. See Kitaigorodskii, I. I.
Rosztoczy, F. E. Growth of crocoite single crystals, (3) 82*d*.
Rota Patent A. G. Method for flame cutting and sealing planar ends of a glass container, P (2) 34*e*.
Roth, M. How to measure moisture in solids, (10) 281*c*.
Roth, R. J. Electrostatic application of porcelain enamels, (6) 145*j*.
Roth, R. S., and Wadsley, A. D. Multiple phase formation in the binary system Nb_2O_5–WO_3 (I) preparation and identification of phases, (6) 168*f*; (II) structure of the monoclinic phases $WNb_{18}O_{50}$ and $W_3Nb_{18}O_{55}$, (6) 168*h*; (III) structures of the tetragonal phases $WNb_{14}O_{44}$ and $W_3Nb_{14}O_{44}$, (6) 168*i*; (IV) the block principle, (6) 169*a*.
Roth, W. L. Magnetic properties of normal spinels with only A–A interactions, B (2) 55*j*.
Rothenberg, P. Enameled silver, (8) 206*a*.
Rothenstein, W. See Weiss, A.
Rothwell, E. Remotely operated high temperature furnace, (8) 224*i*.
Rotschild, S. Method of preparing a cadmium oxide photoconductor, P (8) 221*c*.
Rotsey, W. B., and Wright, W. J. Mechanical behavior of ceramics, (6) 171*c*.
Rottmann, H. R. Inspecting glass container for horizontal checks, P (7) 183*j*. Method and apparatus for inspecting cylindrical objects by photosensitive means, P (5) 123*i*. Photoelectric inspection of containers for dirty finishes, P (5) 123*j*.

Roult, G. See Broquetas Colominas, C.; Murasik, A.
Rouse, I. Caribbean ceramics—a study in method and in theory, B (6) 172*d*. The New York Planning Conference, B (6) 172*d*.
Rousseau, A. See Dupuis, F.
Rousset, P. See Accary, A.
Rousset, P., and Accary, A. Atmospheric corrosion of uranium-carbon alloys, B (6) 172*h*.
Routschka, G. See Koehler, E. K.; Konopicky, K.
Rouzhet, P. See Fripiat, J. J.
Rowden, E. Firing in the heavy clay and refractories industries, 1950–1964, (5) 125*f*.
Rowe, D. H. See Milner, G. W. C.
Rowe, G. E. Apparatus for moving newly formed glassware onto a conveyor, P (7) 182*a*. Conveyor drive mechanism for glassware forming machines, P (7) 182*e*. Glassware forming machine, P (3) 63*j*. Takeout mechanism for double gob glassware forming machine, P (3) 65*b*.
Rowe, J. D. See Spell, D. M., Jr.
Rowe, J. J. See May, I.
Rowell, P. M. See Fletcher, J. R.
Rowlands, R. R. Review of the slip casting process, (2) 39*h*.
Roy, D. M. See Schlaudt, C. M.
Roy, H. Determination of surface area of ceramic clay by differential thermal analysis, (7) 198*a*.
Roy, N. N. Modified spindle stage permitting the direct measurement of 2*V*, (6) 162*f*.
Roy, R. See Berkes, J. S.; Cohen, H. M.; Datta, R. K.; Katz, G.; Majumdar, A. J.; Stubican, V. S.; Taylor, A. M.; Vedam, K.; Weber, J. N.
Roy, S. B. See Mandal, S. S.
Roy, S. K. D. See Choudhuri, A. K.
Royak, S. M. See Budnikov, P. P.
Royal China, Inc. Article handling machine, P (9) 242*b*.
Royce, D. V., Jr. See Carithers, V. G.
Rozanov, N. P. See Shal'nev, K. K.
Rozenblyum, I. S., and Manusov, E. B. Automatic control of the firing cycle in tunnel kilns, (2) 46*b*.
Rozgonyi, G. A., Polito, W. J., and Schwartz, B. Ultra-high-vacuum station for thin film and residual gas analysis studies, (9) 246*e*.
Rozhanskii, A. I. See Zakharikov, N. A.
Rozhdestvenskaya, V. V. See Shashkov, Yu. M.
Rubel, W., and Deventer, G. Casting mold and method of making, P (4) 100*f*.
Ruben, S. Electrical resistor, P (2) 41*f*. Refractory composition and electrical resistance made therefrom, P (11) 303*a*.
Rubin, J. J., and Van Uitert, L. G. Growth of large yttrium vanadate single crystals for optical maser studies, (10) 277*a*.
Rubinchik, S. M. See Sokolov, V. A.
Rubisch, O. See Fitzer, E.
Rubisch, O., and Schmitt, R. Properties of silicon carbide bodies of various densities, (9) 239*a*.
Rublevskii, I. P. See Rogovoi, M. I.
Rubtsov, M. I. See Garif'yanov, N. S.
Ruch, R. R., Tera, F., and Morrison, G. H. Preconcentration of trace elements by precipitation ion exchange using organic-hydrochloric acid systems, (2) 45*a*.
Ruchman, J. C. See Childs, B. G.
Rudd, M. O., Tripp, W. C., and Beasley, G. A. Method and apparatus for processing of ophthalmic lens, P (4) 97*i*.
Rudenko, V. K. See Tokareva, M. V.
Ruding, G. H. Apparatus for producing fibers, P (7) 182*a*.
Rudloff, W. See Brandt, W. W.
Rudness, R. G., and Kebler, R. W. Production of single crystals from incongruently melting material, P (11) 307*j*.
Rudnitskaya, E. S. See Chukhrov, F. V.
Rudnyi, N. M. See Venediktova, R. I.
Rudolph, R. R., and Strutz, C. J., Jr. Method and apparatus for decorating bottles, P (3) 63*f*.
Rudolph, R. R., Strutz, C., Jr., and Strutz, F. C. Bottle decorating apparatus, P (8) 212*b*.
Rudy, E. Thermodynamics of high-melting uranium and thorium compounds, B (6) 175*a*. See Benesovsky, F.; Toth, L. E.
Rudzitis, E. See Feder, H.
Rue, C. V. See Kistler, S. S.
Rueb, F. Systems of dust extraction with recovery of the material, (1) 16*d*.
Ruechardt, H., Hargasser, H., Meer, W., and Heissing, H. Diffused-base transistors, preferably for high-frequency operation, P (3) 73*b*.
Rueckert, U. Exhibition by Michelle Mandray in Kempten, (1) 1*j*.
Ruegge, F. (editor). Structural Clay Products Yearbook 1965, B (3) 88*d*.
Ruehrwein, R. A. Production of epitaxial films, P (9) 244*a*.
Ruelle, L. A. See Noble, M.
Rufeh, F., Olander, D. R., and Pigford, T. H. Solubility of helium in uranium dioxide, (6) 153*i*.
Ruggiero, J. D. See Grulke, C. A.
Ruggles, R. L., Jr. See Lehman, H. S.
Ruh, E. See Ryan, J. R.; Wallace, R. W.
Ruh, E., Wallace, R. W., and Willenbrock, H. C. Thermal conductivity and thermal expansion of basic oxygen furnace refractories, (8) 216*d*.
Ruis, J. W. See Gier, J. de.
Ruiter, J. W. de. See Jonge, J. de.
Rulon-Miller, R., and Ricklin, S. Bearing composition, P (11) 301*i*.
Rummel, T. Apparatus for preparing semiconductor rods, P (4) 104*h*. Apparatus for pulling rod-shaped crystals of semiconductor material from a melt in a crucible, P (9) 242*j*. See Grabmaier, J.; Quast, H. F.
Rummel, T., and Dorner, J. Method of pulling a semiconductor crystal from a melt, P (10) 279*d*.
Rummel, T., Kniepkamp, H., and Emeis, R. Producing rod-shaped semiconductor crystals, P (5) 129*f*.
Rummel, W. W. Materials for MHD ducts, B (6) 173*c*.
Rummery, F. O. See Cheever, G. D.
Rumpf, H. See Schoenert, K.
Rumpf, K. Shales from Osterwald (Germany), (3) 78*b*.
Runciman, W. A. See Ludlow, I. K.
Rundell, H. J. See Wildt, H. A.
Rundqvist, S. Crystal structure of Mo_4P_2, (1) 19*h*. See Sellberg, B.
Rundqvist, S., and Nawapong, P. Crystal structure refinements of some MnP-type phosphides, (2) 49*b*.
Runnstrom-Reio, V. See Ekwall, P.
Runyan, W. R. See Alexander, E. G.
Rupli, R. G. Apparatus for blowing and cooling glassware, P (5) 122*c*.
Ruppel, W. See Fatuzzo, E.
Rupprecht, G. Ferroelectric signal-translating device having voltage-controlled signal delay, P (6) 159*g*.
Rush, R. W. Support for ceramic ware, P (10) 275*a*.
Rushmer, M. A. Progress report on the development of a standardized test for continuity of porcelain enamel coatings, (7) 178*j*.
Rushmer, M. A., and Burdick, M. D. Weather resistance of porcelain enamels exposed for seven years at various sites, (6) 146*b*, (11) 295*e*.
Russell, A. P., and Grgetic, E. F. Electric lamp making apparatus, P (4) 96*f*.
Russell, C. K. See Powers, W. H.
Russell, D. S. See Goto, K.
Russell, J. D. Material transporting device, P (11) 309*a*.
Russell, J. D., and Farmer, V. C. Infrared spectroscopic study of the dehydration of montmorillonite and saponite, (1) 22*b*.
Russell, L. E. See Harrison, J. D. L.
Russell, L. E., et al. (editors). Carbides in Nuclear Energy—Proceedings of a Symposium Held at the Atomic Energy Research Establishment, Harwell, Bucks, England, November 1963, B (6) 171*j*.
Russell, R., Jr. See Goodyear, J. K.
Russell, R. G. See Christen, D. L.; Slayter, G.
Russell, R. G., Morgan, W. L., and Scheffler, L. F. Crystalline fibers, P (8) 212*c*.
Russell, R. J. See Hardinge, H.
Russell, R. J., and Hardinge, H. Grinding mill lining and control of wear, P (1) 16*a*.
Russow, J. See Weiss, A.
Rutz, R. F. See Dill, F. H., Jr.
Ryabinin, Yu. N. See Livshits, L. D.
Ryabov, V. A. See Kulikova, E. N.
Ryan, J. D. See Alexander, H. M.
Ryan, J. J. See Peters, E. T.
Ryan, J. R. See Smoot, T. W.; Walther, F. H.
Ryan, J. R., Ruh, E., and Clark, C. B. Laser microprobe analysis of glass defects, (4) 94*e*.
Ryan, L. D. See Etzel, G. L.; Mallory, J. D.
Rybchinskaya, A. V. See Okhotin, M. V.
Rybicki, N. Apparatus for compressing material, P (4) 106*j*.
Ryckman, G. E. Multicolor stamping machine P (7) 191*c*.
Ryder, R. J. See Fenstermacher, J. E.
Rydinger, M., Fredriksson, B., and Blaus, J. Heating means, P (7) 188*d*.
Rydlewicz, A. H. Apparatus for moving newly formed glassware articles of unstable configuration onto a conveyor, P (7) 182*j*.
Ryley, J. F. See Cassaday, H. L.
Ryndina, A. M. See Efimov, A. I.
Ryshkewitch, E. I., Strott, A. J., and Utz, D. L. Method of producing high density ceramic articles, P (4) 101*g*.
Ryzhmanov, Yu. M. See Garif'yanov, N. S.
Saakyan, K. S. See Kostanyan, K. A.
Saale-Glas G.m.b.H. Optical glass and its manufacture, P (10) 269*f*.
Saalfeld, H. Thermal transformation and crystallography of petalite and spodumene, (3) 87*e*. See Konopicky, K.
Saalfeld, H., and Mehrotra, B. Electron diffraction study of aluminum oxides, (7) 199*e*.
Sabatier, G. Composition of sedimentary clays, (7) 197*j*.
Sabelli, C. See Cocco, G.
Sabelli, L. Rapid drying equipment and its effect on the mechanization of Italian brickworks, (11) 300*a*.
Sabisky, E. S., and Gerritsen, H. J. Doubly doped titanium dioxide maser element, P (11) 305*g*.
Saburi, O. Capacitor comprising an *n*-type semiconductor metallic oxide and a layer of compensated material, P (10) 277*j*.
Sacco, R. M. See Smith, L. I.
Saccomonano, J. M. Ladles, P (2) 38*b*.
Sachdev, P. L. See Ward, R. G.
Sack, W. Mechanism of the selenium-ruby reaction, (9) 233*i*.
Sackett, W. J., Sr. Compound and blending apparatus, P (9) 244*g*.
Sadagapan, V., and Gatos, H. C. Superconductivity in the transition metal carbides $Mo_{4.8}Si_3C_{0.6}$, $Mo_{0.88}Hf_{0.12}C_{0.73}$, and Mo_2C, (9) 257*a*.
Sadler, A. G. Ferrimagnetic oxides and polycrystalline ferrites, (6) 157*i*. See Lewis, D. C.; Westwood, W. D.
Sadler, A. G., Westwood, W. D., and Lewis, D. C. Differential thermal analysis of ferrite raw materials and compounds, (6) 157*f*.
Sadler, A. J. Manufacture of silicon controlled rectifiers, P (6) 159*e*.
Sadler, T. H., and Reimschussel, G. P. Methods for making asbestos fiber products, P (11) 302*j*.
Sadofsky, J. See Auskern, A. B.
Sadownick, E. M. High temperature [graphite] nozzle for rocket motor, P (3) 70*j*.
Saeki, Y., and Matsuzaki, R. Hydrolysis of niobium pentachloride and tantalum pentachloride, (11) 317*b*.
Saelzle, E. Process for polishing articles of crystal or lead-crystal glass, P (10) 269*i*.
Safonov, V. V. See Korshunov, B. G.
Safonov, V. V., Korshunov, B. G., and Shevtsova, Z. N. Study of the interaction of the chlorides of niobium(IV) with the chlorides of rubidium and cesium in melts, (5) 141*b*.
Sah, Chih-Tang. Surface-potential controlled semiconductor device, P (2) 43*a*.
Saha, P. See Bandyopadhyay, T.; Ganguli, D.
Saho, M. See Tagai, H.
Sahu, B. K. Sieving characteristics of symmetrical tabular grains with any roundness value, (2) 43*h*. Theory of sieving, (2) 43*h*. Transformation of arithmetic and phi size-distribution moments, (5) 142*a*. Transformation of weight- and number-frequencies for phi-normal size distribution, (5) 142*b*.
Saia, F. J. See De Mille, C. L.
Saint-Jacques, E. C. Classification selectors for solids in gaseous suspension, P (5) 130*j*.
Saint-James, Mme. See Fournie, R.
Saito, F. Transient phenomena in ruby maser, (4) 104*g*.
Saito, H. See Masuda, Sen-ichi.
Saito, S., Katagiri, M., Yuza, H., and Hasegawa, S. Etching of ceramic surfaces by electric discharge in electrolyte solutions, (5) 136*d*.
Saji, T. Composition and densities of dehydrated phosphoric acids, (7) 197*i*. Solidification of dehydrated phosphoric acids, (7) 202*j*.
Sakaba, A. See Matoba, T.
Sakai, S. See Ota, E.
Sakamoto, N. Magnetic properties of cobalt titanate, (11) 304*i*.
Sakamoto, Y. See Doi, M.
Sakharov, V. I. See Shal'nev, K. K.
Sakharova, N. A. See Cherepova, O. V.
Saksena, B. D. Interpretation of the infrared spectrum of α-quartz in the 3μ region on the basis of localized modes due to substitutional impurities, (9) 251*d*. Optical transmission of some quartz samples in the ultraviolet and 3μ region, (9) 252*g*.
Sakurai, J. See Kishi, T.
Sakurai, S., Watabe, S., and Morio, A. Method for producing thin titanoceramic film, P (3) 73*j*.
Sala Maskinfabriks Aktiebolag. High-intensity magnetic separator, P (7) 196*j*.
Salat, R. F. See Morris, R. A.
Saldern, A. von. Ancient glass in Split, (4) 89*h*. Mosaic glass from Hasanlu, Marlik, and Tell al-Rimah, (9) 230*d*.
Sales, R. M. See Fletcher, W. W.
Salesse, M. See Boghen, J.
Salibekov, S. E. See Arabei, B. G.
Salmang, H. Status of research on glass structure, (5) 121*f*.
Salmi, J. V. Slag pocket wall, P (9) 241*c*.
Salmon, T., and Robertson, R. F. Gas phase adsorption and surface area determination of minerals, (5) 136*d*.
Salovskii, A. P. See Bergman, A. G.
Salton, Inc. Banded glass container constructions, P (6) 149*d*.
Salzano, F. J. See Auskern, A. B.
Samsonov, G. V. High-Temperature Compounds of Rare Earth Metals with Nonmetals, B (3) 88*i*. See Bondarev, V. N.; Koval'chenko, M. S.; L'vov, S. N.; Neshpor, V. S.
Samsonov, G. V., and Dubovik, T. V. Technology for making refractory components from aluminum nitride, (3) 69*j*.
Samsonov, G. V., Kosolanova, T. Ya., and Makarenko, G. N. Synthesis and some physicochemical properties of yttrium carbide, (4) 113*f*.
Samsonov, G. V., Paderno, Yu. B., and Fomenko, V. S. Hexaborides of the rare-earth metals, (9) 240*h*.
Samsonov, G. V., and Repkin, Yu. D. Nitriding of aluminum powder under pressure, (7) 178*h*.
Samsonov, G. V., and Slepstov, V. M. Preparation of boron-silicon alloys, (11) 301*i*.
Samsonov, G. V., Vainshtein, E. E., and Paderno, Yu. B. Results of the electrophysical and X-ray spectral analysis of hexaborides of rare earth elements, (10) 290*j*.
Samsonov, G. V., and Yasinskaya, G. S. Interaction between high-melting compounds and molten metals, (10) 271*e*.
Samuseva, R. G., Plyushchev, V. E., and Poletaev, I. F. Phase diagrams of the systems Na_2CrO_4–Rb_2CrO_4 and Na_2CrO_4–Cs_2CrO_4, (1) 24*d*.
San Antonio Chemicals, Inc. Process for preparing cesium compounds from cesium alum, P (1) 19*a*.
Sanada, Y. See Honda, H.
Sanatina, V. N. See Krylov, E. I.

Sanchez, M. G. See Acker, E. G.; Vanik, M. C.
Sanchez Camazano, M. See Martin Vivaldi, J. L.
Sanchez Conde, C. See Garcia Vicente, J.
Sandell, E. B. See Kolthoff, I. M.
Sandenaw, T. A., and Storms, E. K. Heat capacities of $NbC_{0.70}$, $NbC_{0.82}$, $NbC_{0.98}$, and Nb_2C below 320°K, (9) 250*f*.
Sanders, A. D. See Hodges, L. R., Jr.
Sanders, D. P. Process for rapidly etching a flat-bottomed pit in a germanium wafer, P (10) 279*a*.
Sanders, R. W. See Dickson, D. J.
Sanders, W. A., and Probst, H. B. Hardness of five borides at 1625°C, (5) 136*i*.
Sandmann, H., and Doetzer, R. Apparatus for [electrolytically] doping and contacting semiconductor bodies, P (9) 242*i*.
Sandstrom, J. P. See Crishal, J. M.
Sandulov, D. B. See Budnikov, P. P.
Sandulova, A. V., Andrievskii, A. I., and Dronyuk, M. I. Growth forms of crystals of germanium and silicon grown from gaseous solution, B (11) 320*a*. Morphology of needle, whisker, and strip crystals of silicon, B (11) 320*b*.
Sandvikens Jernverks Aktiebolag. Composition for metal casting molds, particularly ingot molds and hot tops, P (10) 273*f*. Heat-insulating compositions and their use, P (10) 273*j*. Hot top, P (10) 274*a*. Hot top casing for casting molds, P (2) 38*a*. Method of making hot tops for ingot molds, P (2) 38*e*.
Sanford, R. A., and Erickson, H. Synthetic alumina, silica-alumina hydrocarbon cracking catalyst, and method for hydrocarbon cracking, P (9) 241*c*.
Sanno, A. P. de, & Son, Inc. Method of producing abrasive surface layers, P (1) 1*g*. Process of making metal bonded diamond abrasive articles, P (7) 177*i*.
Sano, S. See Sugiura, M.
Sano, S., Kato, S., Ishii, E., and Iga, T. Reduced pressure sintering of MgO as high frequency insulator (I), (10) 290*f*. Sintered mixture of magnesia and vanadium pentoxide as high frequency insulator, (4) 102*j*.
Sano, T. See Imoto, S.
Santini, P., Souza Santos, P. de, and Ferreira Alves, V. Determination of carbon and organic matter in clays, (2) 46*h*.
Santoro, R. P. See Caron, L. G.; Newnham, R. E.
Santos, H. L. de S. See Souza Santos, H. L. de.
Santos, P. de S. See Souza Santos, P. de.
Santy, M. J. See Blumenthal, J. L.
Sapoff, M. Method of covering resistor bead, P (7) 193*j*.
Sapoff, M., and Gecsey, J. Method of making bead type thermistors, P (3) 73*a*.
Sara, R. V. Hafnium–carbon system, (5) 136*g*.
Saraf, S. K. See Satterfield, C. N.
Sargent, J. W., and Schroder, O. W. Glass replaces steel for coil banding, (2) 31*e*.
Sarian, S., and Weart, H. W. Factors affecting the morphology of an array of solid particles in a liquid matrix, (5) 136*e*.
Sarkisyan, S. G., and Petrosov, I. Ch. Main factors for clay mineral formation of Tertiary volcanic and sedimentary deposits on the territory of the Yerevan district (Armenian S.S.R.), B (2) 56*g*.
Sarrat, P. See Marchand, G.
Sasa, Y. See Atoda, T.
Sasaki, H. Apparatus for aging quicklime, P (5) 119*b*. See Matsuo, Y.
Sasaki, J. See Hase, B.
Sasaki, T., and Ishiguro, K. Spectrophotometer for determining optical constants in the vacuum ultraviolet region, (4) 107*h*.
Sasek, L. See Stanek, J.
Sasnauskas, K., Paskauskaite, I., and Elzbutas, H. Electrical conductivity of $Ca(OH)_2$ and amorphous SiO_2 aqueous solutions, (6) 167*h*.
Satava, V. New type of inorganic binder [plaster], (11) 294*a*. Simple device for determining the apparent density of small samples of porous materials, (2) 45*j*. Thermographic study of the formation of ultramarine, (2) 53*d*.
Satava, V., Marek, J., and Matousek, J. Hydration kinetics of α- and β-calcium sulfate hemihydrates, (7) 200*f*.
Sato, G. Process of producing solid composition resistors of monolithic structure, P (2) 42*e*.
Sato, K. See Mukaibo, T.
Sato, M., and Hukuda, S. Phase diagram of the system YF_3–PbF_2, (5) 139*h*.
Sato, R. See Matsubayashi, Y.
Sato, T., and Shimoiizaka, J. Flocculation and dispersion of fine particles in nonpolar organic solvent, (6) 156*c*.
Satomi, K. Oxygen positional parameters of tetragonal Mn_3O_4, (4) 112*f*.
Satterfield, C. N., and Saraf, S. K. Anisotropic diffusivities in pressed catalyst pellets, (2) 36*c*.
Satterfield, E. L. See Woodward, R. M.
Sauber, C. A., and Branstetter, M. W. Cement compositions and methods of utilizing same, P (2) 29*g*.
Sauber, M. Ceramic honeycomb, (9) 237*j*.
Sauer, J. M. Rotary kiln lining, P (7) 196*d*.
Saulnier, T. A. Color-television screening by the slurry process, (8) 208*g*. Method of making luminescent screens for cathode ray tubes, P (11) 306*f*.
Saum, C. J. See Blundell, A.
Sauman, Z. Study of the system CaO–SiO_2–H_2O under hydrothermal conditions, (2) 29*a*.
Saums, H. L., and Pendleton, W. W. Method of making electromagnetic structures for high-temperature service, P (11) 296*b*.
Saunders, A. C., and Grant, J. F. Radiant gas burner tile, P (2) 38*d*.
Saunders, A. E. See Orr, L. E.
Saunders, H. S., and Gehring, R. W. Ceramic-coated electrically conductive wire and method of making, P (3) 59*j*.
Saur, E. J. Process of making niobium stannide bodies, P (11) 307*g*. Superconductor, P (6) 161*a*.
Sauthoff, J. See Kienow, S.
Sautier, F. Artificial magnetic oxides, P (5) 128*g*.
Savage, J. A., and Isard, J. O. Additional studies of cation sensitive glass electrodes, (6) 146*h*.
Savage, J. A., and Nielsen, S. Infrared transmission of telluride glasses, (6) 148*b*.
Saverse, R. R. See Glynn, A. T.
Savioli, F., and Aliprandi, G. Determination of the slagging resistance of refractory materials, (7) 186*a*.
Savonichev, G. V., Figurovskii, I. A., Kalmykov, V. I., and Bykov, V. V. Conveyor-line system for producing and processing glassware, (4) 92*b*.
Savonichev, G. V., Figurovskii, I. A., Sobolevskii, S. I., and Bykov, V. V. Melting lead crystal in a tank furnace, (10) 265*h*.
Sawamoto, H. See Ota, E.
Sawyer, E. W., Jr. Treated clay slurries, P (5) 134*a*.
Sawyer, E. W., Jr., and Pavol, M., Jr. Viscosity stabilized clay slurry, P (10) 283*g*.
Sawyer, J. P. Jackson's incentive programs for production foremen and quality control personnel, (1) 12*j*.
Saxena, S. C. See Dass, L.; Kachhava, C. M.
Sayers, J. B. Fuel elements for nuclear reactors, P (6) 154*c*.
Sayers, J. B., Rose, K. S. B., Coobs, J. H., Hauser, G. P., and Vivante, C. Irradiation behavior of coated particle fuels, B (6) 172*c*.
Sayers, M. See Knapp, E. J.
Sayre, H. S. Conveyor discharge system, P (8) 222*g*.
Sazhnov, V. K. See Baraboshkin, A. N.
Scala, E. See Schuster, D. M.
Scala, S. M., and Gilbert, L. M. Sublimation of graphite at hypersonic speeds, (4) 99*e*.
Schaarschmidt, E. C. Deposition chamber including heater element enveloped by a quartz workholder, P (3) 72*j*.
Schaden, K. See Eipeltauer, E.
Schadow, H. See Lehmann, H. A.
Schaefer, A. Resistance of concrete to frost and salt, (1) 2*j*.
Schaefer, D. L. Storage electrode, P (5) 130*d*.
Schaefer, H. See Bauer, D.; Gehrecke, S.
Schaefer, H., and Dohmann, K. D. Chemistry of the elements niobium and tantalum (XX) the reaction $11Nb + 3SiO_2 = 6NbO + Nb_5Si_3$, (3) 80*d*.
Schaefer, H., and Fuhr, W. Chemistry of the elements niobium and tantalum (XLIII) compounds of niobium with P, As, Sb, S, Se, and Te—synthesis and chemical transport, (11) 314*h*.
Schaefer, H., Schnering, H. G., Niehues, K. J., and Nieder-Vahrenholz, H. G. Chemistry of the elements niobium and tantalum (XLVII) niobium fluoride, (11) 314*i*.
Schaeffler, L. See Aronson, H.
Schaetzer, L. Dental ceramics, (3) 71*e*.
Schafer, L. See Hofmann, F.
Schairer, J. F. See Schreyer, W.
Schaudinn, K. Long rod insulators, (9) 241*i*. See Ricke, W.
Schauer, A. Thermal expansion, Grueneisen parameter, and temperature dependence of lattice vibration frequencies of aluminum oxide, (1) 25*a*.
Scheer, J. J. See Laar, J. van.
Scheffler, L. F. See Morgan, W. L.; Russell, R. G.
Schellmann, W., and Fastabend, H. Bloating ability of clays and its causes, B (2) 56*j*.
Schenkel, G. See Gehrecke, S.
Schepers, J. H., and Loon, W. van. Method of controlling the pyrochemical bonding of a clay–carbon system, P (6) 164*a*.
Scheuer, E. W. Dehydrated mica products and method of making, P (4) 104*d*.
Schiaffino, L. See Franzini, M.
Schieber, M. See Frei, E. H.; Holmes, L.; Perel, J.
Schiefferle, J. A. Experience with cover coat direct-on, (4) 91*g*. Measurement of rheology of cover coat slips, (7) 178*f*.
Schieltz, N. C. See Pray, R. E.
Schievenedel, P. See Selig, H.
Schill, H., and Gaenge, F. Regenerative capacitor, P (5) 129*g*.
Schiller, K. Effect of impurities and additions on the hydration of calcium sulfate plaster slurries, (11) 293*j*.
Schilling, C. E. See Morse, L. E.
Schilling, D. C., Lohnes, F. G., and Broderick, J. P. Flame spraying torch, P (10) 263*g*.
Schilling, G., and Weiss, W. Experiments to determine the homogeneity of glasses by the Shelyubskii method, (8) 209*g*.
Schilling, W., and Wiedenmann, H. Electrical miniature incandescent lamp and method of making, P (10) 267*g*.
Schillmoeller, A. Raw material selection, batch mixing, and transport in a pot furnace factory, (3) 62*c*.
Schindelin, W. See Miltschitzky, G.
Schindler, D. R., and Stuart, K. D. Manufacture of electroluminescent cells, P (8) 221*f*.
Schindler, P. H., Jr., and Mozelewski, E. J. Casting toilet bowls and like ceramic ware, P (2) 40*c*.
Schink, N. Method of producing an oxide coating on crystalline semiconductor bodies, P (9) 243*d*.
Schink, N., and Stoiber, R. Method of producing a silicon semiconductor device, P (10) 279*d*.
Schlaefer, H. L. See Wille, H. W.
Schlapp, D. M. Creep properties of glass under high strain, (2) 31*b*.
Schlaudt, C. M., and Roy, D. M. Join Ca_3SiO_4–$CaMgSiO_4$, (9) 251*h*.
Schlegel, H. Is dust extraction with bag filters efficient? (10) 280*a*.
Schlegel, W. A. See Jaccodine, R. J.
Schleifer, P. Catalytic crystallization of the vitreous phase of magmatic rocks, glasses, and metallurgical slags, (11) 296*e*. Influence of fluorine ions on the physicochemical properties of the vitreous state in the systems AlF_3–PbO–B_2O_3 and B–F–O, (10) 286*h*. Stabilization of the micro- and macrostructure of optical glasses, (11) 297*j*. Vitreous range in three-component systems based on Sb_2O_3 and the physicochemical properties of antimony glasses, (7) 182*c*.
Schlesinger, H. See Fitzer E.
Schlesinger, J. H. Siliceous dental filling, P (7) 191*a*.
Schlesinger, M. Optical studies of electron and hole trapping levels in quartz, (9) 252*f*.
Schlicke, H. M. Mutual substitution of networks and materials, B (9) 259*g*.
Schlicke, H. M., Kouchich, A. V., and Blomdahl, F. A. Capacitive component, P (7) 192*i*.
Schlitz, Jos., Brewing Co. See Jos. Schlitz Brewing Co.
Schloesser, J. Correlation among pore-size distribution, permeability, and diffusion in graphite, (10) 284*i*.
Schlomer, J. See Kraft, P.
Schlosser & Co. G.m.b.H. Mixing device for admixing additives to a melt, P (3) 64*d*.
Schlossin, H. H. Plastic relaxation of crack tip stresses in α-quartz, (3) 84*i*.
Schlossin, H. H., and Lang, A. R. Study of repeated twinning, lattice imperfections, and impurity distribution in amethyst, (3) 86*g*.
Schlotzhauer, L. R. See Novack, T.
Schlotzhauer, L. R., and Hutchins, J. R., III. Corrosion resistance of alumina-zirconia-silica refractories, (6) 152*b*.
Schmalz, H. H. See Bailey, J. S.
Schmid, H., and Feldhoff, H. Apparatus for continuous drying of powdery or granular materials in a high-frequency field, P (3) 77*i*.
Schmid, O. Glass phase in fused-cast aluminum oxide-zirconium oxide block, (1) 9*b*. Quartz transformation in silica brick, (2) 36*g*.
Schmidt, E. See Lukes, F.
Schmidt, E. D. D. See Vedam, K.
Schmidt, E. E. Ultrasonic testing of porcelain for cracks, (2) 40*e*.
Schmidt, E. W. Manufacture of clinker brick by the dry-press method—experiment or future, (2) 35*g*. Preparation of dry-press bodies by the liquid, wet, semiwet, and dry processes for the manufacture of wall tile, floor tile, and face brick, (9) 241*j*.
Schmidt, G. Measurement of dust and smoke density in industrial practice, (1) 16*h*.
Schmidt, K. High pressure sodium vapor lamp, P (7) 193*d*.
Schmidt, K. R. See Oehlrich, K. H.
Schmidt, M. Electrostatic screen printing applied to glass and ceramics, (2) 43*e*.
Schmidt, R. Electrodes to semiconductor wafers, P (6) 159*d*. Semiconductor contact, P (4) 106*f*.
Schmitt, B. See Gaeth, R.
Schmitt, F. O. Structure in living systems, B (9) 259*e*.
Schmitt, J., and Wittner, H. Electrolytic furnace with lined cathode pots for the production of aluminum, P (8) 217*j*.
Schmitt, R. See Rubisch, O.
Schmitz, A. Method of improving the electrical properties of a gallium arsenide semiconductor device, P (8) 221*i*. See Kooi, E.
Schmitz, E. F. See Garrison, J. W.
Schmitz, G. K., and Metcalfe, A. G. Stress corrosion of E glass fibers, (5) 121*g*.
Schmitz-Du Mont, O. See Reinen, D.
Schmitz-Du Mont, O., and Moulin, N. Color and constitution of inorganic solids (V) light absorption of trivalent chromium incorporated into the garnet structure, (3) 80*e*.
Schnabel, O., and Krings, A. Heat exchange in vacuum flasks, (8) 209*b*.
Schnabel, O., and Loeber, H. Physical processes in the constriction of fever thermometers, (6) 148*d*.
Schnable, G. L., McKelvey, A. F., and Hastings, J. A. Chemical technique for preparing oxide-isolated silicon wafers for microcircuits, (11) 304*g*.
Schneble, F. W., Jr., and Zeblisky, R. J. Method of making printed circuits, P (4) 105*j*.
Schneider, H. See Albrecht, W.
Schneider, P. See Schwamborn, P.
Schneider, P. J. Photosensitive bottle width selector, P (7) 184*d*.
Schneider, S. J. See McDaniel, C. L.
Schnering, H. G. Crystal structure of $BaCdO_2$, (3) 80*b*. See Bauer, D.; Schaefer, H.
Schnettler, F. J. See Monforte, F. R.
Schnurpfeil, J. 292 Selected and Well-Proved Glass Recipes with All Details and Technical Hints, All Specialities, B (3) 88*j*.
Schoefer, L. See Himmelstein, P.
Schoenbrunn, G. Internal pressure resistance of glass bottles subject to stress for long and short times, (4) 94*b*. See Wiegand, H.

Schoenert, K., Umhauer, H., and Rumpf, H. Strength of small glass spheres, (7) 181*i*.
Schoenlaub, R. A., Troyer, W., and Hoekstra, K. Burnout rates on a shale body, (4) 98*f*.
Scholes, S. R. Chemistry of selenium in glass, (3) 60*d*.
Scholz, H. See Grimmeiss, H. G.
Scholz, S. See Rabenau, A.; Roeder, E.
Scholze, H. Ion exchange in the extraction of soda-lime glasses with dilute salt solutions, (6) 148*c*. See Merker, L.; Mulfinger, H. O.
Scholze, H., and Franz, H. Infrared band at 4.25μ in glasses, (7) 180*f*.
Scholze, H., and Mulfinger, H. O. Discussion—glassy phase in Corhart ZAC blocks, (2) 36*i*.
Schonhuber, M. J. High-frequency mass spectrometer used as a gas-analytical flowmeter for improving, monitoring, and controlling processes carried out in vacuum, (9) 245*j*.
Schott, C. W. Glass spheres and underground proppants [*sic*] and methods of making, P (6) 150*c*. Method of treating a preformed glassy object, P (7) 184*b*.
Schreffler, R. Z. Flake glass breakout detector and method of controlling glass breakout, P (3) 63*e*.
Schreiber, E., and Anderson, O. L. Pressure derivatives of the sound velocities of polycrystalline alumina, (5) 140*c*.
Schreiber, E., and Soga, N. Elastic constants of silicon carbide, (7) 198*j*.
Schreieck, W. Method for producing building elements and especially building stones of sintered material or the like, P (11) 300*f*.
Schreter, R. E., Turpin, A. J., and Parker, M. J. Spark monitor for fuel burner, P (9) 246*j*.
Schrewelius, N. G. Electric resistance elements of silicon carbide and metal silicide, P (7) 195*i*.
Schrey, F. See Gallagher, P. K.
Schreyer, W. See Seifert, F.
Schreyer, W., and Schairer, J. F. Metastable solid solutions with quartz-type structures on the join SiO_2-$MgAl_2O_4$, (3) 85*e*.
Schrier, I. See Faas, K. D.
Schroder, O. W. See Sargent, J. W.
Schroeder, A., and Powers, J. T. Therapeutic dental cement and a method for treating carious teeth, P (8) 219*f*.
Schroeder, H. Glasses with selective reflection properties, (10) 265*c*.
Schroeder, J. Gas-filled electric incandescent lamp, P (5) 128*f*. Tungsten filament lamp comprising hexafluoride gas at partial pressure not exceeding 10 torrs, P (10) 279*h*.
Schroeder, J. B. See Linares, R. C.
Schroeder, W. See Kindel, E.
Schubert, K. See Heinze, G.
Schubert, M., and Murawsky, F. Process for the production of magnesium oxide from magnesium chloride hydrate, P (11) 303*g*.
Schueler, I. Jewish gold glasses, (9) 230*b*.
Schueller, K. H. Development of structure in porcelain (VI) chemical aspects and reactivity of the liquid phase, (2) 39*e*. Use of Seger cones for assessing the degree of firing, (3) 77*g*.
Schuermann, W. Fully automatic preparation of tar-dolomite brick, (2) 36*h*.
Schuermeyer, F. L. Photovoltage measurements on an Al-Al_2O_3-Al thin film sandwich, (9) 253*j*.
Schuetz, H. Removal of dust from hot gases by fabric filters, (1) 17*h*.
Schuitemaker, J. J. See Bleukens, P. C. M.
Schuld, L. A. Bottom discharge container with agitator, P (3) 78*f*.
Schulle, W. Effect of moisture on the thermal conductivity of refractories at room temperature, (11) 301*e*.
Schuller, W. H. W. Apparatus for drawing fibers of glass or other inorganic glasslike media from rods, P (10) 267*h*. Method and apparatus for the manufacture of a web or mat made from glass fiber, P (3) 63*g*. Method for continuously producing glass fiber mats, P (5) 123*d*.
Schulman, J. H. Luminescence in solids, B (9) 259*f*. Oppositely charged mixed collectors in flotation, B (7) 204*f*.
Schulman, J. H., Kirk, R. D., and King, P. Method of preparing transparent luminescent screens, P (10) 269*j*.
Schulte, K. Corrosion of magnesite regenerator brick by alkali sulfates and by SO_3, (10) 271*c*.
Schultz, D. A. See Davis, C. W., Jr.
Schultz, W. W., and Briggs, H. D. Radioactive apparatus for measuring temperature, P (5) 132*c*.
Schulz, E. See Wecht, P.
Schulz, E. O. Glass melting with freshwater limestones, (10) 264*j*.
Schulz, H. Grinding and polishing of glass, (10) 265*c*.
Schulz, H. J. See Gumlich, H. E.
Schulz, P. Electric high pressure discharge lamp of high luminous intensity, P (2) 41*e*.
Schulze, H. J., and Kaestner, F. How are the conceptions of viscosity, workability, plasticity, and binding power to be distinguished? (3) 71*g*.
Schulze, K. See Sommer, A.
Schulze, K. H. Technical weighing problems in glass batch plants, (3) 62*b*.
Schumacher, H. Ceramic filters—a new dipole filter, (9) 242*e*.
Schumacher, R. B. See Flores, J. G.
Schumb, W. C., and O'Malley, R. F. Fluorination of nitrides, (7) 199*f*.
Schurecht, H. G., and Insley, R. H. Spark plug seal, P (7) 194*c*.
Schuster, A. Hints and experiences in ceramic extrusion, (6) 161*d*.
Schuster, D. M., Teich, M. C., and Scala, E. Ruby whisker growth and characteristics, (9) 255*f*.
Schuster, E., and Reitmayer, F. Change in the refraction of glasses by one-dimensional force, tensile stress, (2) 31*a*.
Schutte, C. E. G. Determination of zirconium in South African granites, (11) 309*i*.
Schutte, H. D. Hammer mill [feed] control, P (9) 247*e*.
Schutte Pulverizer Co. Hammer mill [feed] control, P (9) 247*c*.
Schuvart, J. A. Side-entry fluid fuel injection system for furnaces, P (1) 18*a*.
Schwabe, K. Electrodes for the reduction of oxygen in the fuel cell, (8) 215*f*.
Schwabe, W. E., and Ciotti, J. A. Pyrometer, P (7) 195*d*.
Schwaerzler, G. International Ceramic (design) Competition, Faenza, 1965, (2) 27*j*.
Schwamborn, P., Cremer, G., Behrens, H., and Schneider, P. Process for controlling cooling in a tunnel furnace, P (10) 282*d*.
Schwantje, H. H. W. See Mezey, E. J.
Schwarcz, H. P. Origin of diamonds in drift of the north-central United States, (1) 23*h*. Oxygen and carbon isotopic fractionation between coexisting metamorphic calcite and dolomite, (10) 289*e*.
Schwartz, A. B. See Dwyer, F. G.
Schwartz, B. See Rozgonyi, G. A.
Schwartz, C. M. See Sclar, C. B.
Schwartz, D. S. See Howatt, G. N.
Schwartzwalder, K. See Counts, W. E.
Schwarz, K. E. See Evans, J. W.
Schwarze, E. See Goldmann, O.
Schweiker, M. A. Apparatus for stacking tiles in magazines, P (3) 71*j*.
Schweiker, M. A., and Watson, W. C. Blending apparatus comprising weighing-scale hoppers discharging tiles upon a conveyor, P (7) 190*h*. Blending apparatus and method, especially for tiles, P (4) 103*b*.
Schweinsberg, E. S. zu. Glass needs of a royal household in the late Middle Ages, (6) 144*b*. Specimen of Jena glass, (2) 28*b*. Style and shape of hollow glassware illustrating different historical periods, (4) 90*d*. Swabian drinking glass in Spain, (10) 262*b*.
Schwerdtfeger, K., and Muan, A., with Darken, L. S. Activities in olivine and pyroxenoid solid solutions of the system Fe–Mn–Si–O at 1150°C, (11) 313*d*.
Schwesinger, G. See Raff, H.
Schwiete, H. E. Black silica brick, (5) 125*c*. Glass phase in fused-cast tank blocks, (2) 36*i*. See Boneff, S.; Hennicke, H. W.; Kroenert, W.; Langauer, T.
Schwiete, H. E., Ehrcke, U., and Majdic, A. Behavior of magnesite brick in industrial furnaces, especially in regenerative checkerwork of glass melting tank furnaces, (7) 185*f*.
Schwiete, H. E., and Ellies, F. Investigations on the abrasion resistance of ceramic-bonded and fused cast refractory brick at high temperatures, (1) 9*a*.
Schwiete, H. E., and Fleischer, J. Solubility of zirconia in hydrofluoric acid—determination of the glassy phase in fused cast glass tank blocks, (6) 153*j*.
Schwiete, H. E., and Iwai, T. Ferrite phase in cement and its behavior during hydration, (3) 58*g*.
Schwiete, H. E., Kroenert, W., and Rennen, H. Reaction of calcium oxide with kaolinite between 450° and 850°C, (6) 169*j*.
Schwiete, H. E., Langauer, T., and Auchter, G. Effect and behavior of silicones on glass surfaces (1), (5) 120*h*.
Schwiete, H. E., Ludwig, U., and Mueller, P. Calcium aluminate hydrates, (7) 177*j*.
Schwiete, H. E., Ludwig, U., and Otto, P. Influence of diatomaceous earth on the technological properties of blast-furnace cement of low clinker content, (3) 59*b*.
Scientific Industries, Inc. Apparatus for the automatic chemical sequential treatment and analysis of small quantities of material, P (2) 45*h*.
Scientific Research Institute of Building Materials, Planning Institute of Cement Industry, Alumina Works. Experience in manufacturing low-silica high-iron cement from red mud, (6) 144*f*. See also Planning Institute of Cement and Glass Industries.
Sclar, C. B., and Carrison, L. C. High-pressure reactions and shear strength of serpentinized dunite, (11) 317*f*.
Sclar, C. B., and Schwartz, C. M. Relation of molar refraction to coordination in polymorphs of boron nitride and carbon, (8) 227*i*.
Sclar, N. Resonance electroluminescent display panel, P (6) 160*d*.
Scoledge, R. F. See Bonazoli, R. P.
Scoledge, R. F., and Bonazoli, R. P. Electric lamp with fuse, P (11) 305*i*.
Scott, D. W. See Crowder, G. A.
Scott, G. F. Light porous refractory brick and method, P (9) 240*h*.
Scott, J. J., and Turnbull, N. C. Apparatus for making magnesium oxide crystals, P (7) 188*g*.
Scott, R. E. Method of treating an investment mold, P (2) 38*j*. See Miller, E. D., Jr.; Owen, W. H.
Screm, G. See Bassi, A.
Scribner, W. G., Treat, W. J., Weis, J. D., and Moshier, R. W. Solvent extraction of metal ions with trifluoroacetylacetone, (3) 76*f*.
Scroger, M. G. See Chang, L. L. Y.; Phillips, B.
Scroggie, B. See Murthy, M. K.
Scuderi, T. G. See Kerper, M. J.
Scully-Anthony Corp. Manufacture of seals, P (3) 73*h*.
Seacrest, W. G. Blast furnace hot stove checkers, P (5) 125*h*.
Seage, T. T. Serial, for collectors, on Royal Rockingham porcelain (I) earlier years; (II) Brameld brothers; (III) ware and the men, (8) 206*b*.
Seakins, L. W., and Smith, S. Practical Brickwork, B (3) 88*a*.
Seal, M. Electron microscope aids diamond research, (9) 229*f*. Nature of diamond coat, (10) 288*f*. Structure in diamonds as revealed by etching, (1) 25*g*.
Seal, M., and Kranitz, M. Thermal decomposition of potassium chloroplatinate, (8) 228*a*.
Searcy, A. W. See Hoenig, C. L.
Searcy, A. W., and Finnie, L. N. Thermodynamics and high-strength materials, B (2) 55*g*.
Searcy, A. W., and Meschi, D. J. Calculation of integral and partial thermodynamic functions for solids from dissociation-pressure data, B (6) 175*g*.
Sears, G. W., Jr. See Brown, R. L.
Searstone, K., and Isard, J. O. Chemical durability of CaO-B_2O_3-Al_2O_3 and CaO-B_2O_3-Al_2O_3-SiO_2 glasses, (3) 60*j*.
Sebok, F. Efficiency of brick walls as a γ-radiation shield, (2) 35*d*.
Secrest, A. C. See Blocher, J. M., Jr.
Secrest, V. M. See Blocher, J. M., Jr.
Secrist, D. R., and Mackenzie, J. D. Microwave discharge deposition of oxide films at low temperatures, (10) 277*f*.
Seddon, W. E. See Hyde, K. R.
Seeley, S. B. Stopper rod assembly, P (10) 275*d*.
Seeman, J. M. Ion-sputtered coatings provide multifunctional finishes, (3) 72*f*.
Sefton, R. C. Lightweight concrete, P (11) 295*a*.
Segal, B. B. See Kriek, H. J. S.
Segnit, E. R. Microstructure of ceramic materials, (8) 223*b*. Mineralogy of some soda-lime-silica glazes, (5) 127*g*.
Seidel, W., and Kaufmann, W. Dust extraction of kiln gases in the stoneware industry with a MABA-TRON electrofilter, (10) 275*g*.
Seidl, A. Method of manufacturing foamed silicate structures, P (9) 240*b*.
Seidler, K. Photoflash lamp and method, P (2) 34*d*.
Seifer, G. B. Question of the zeolitic nature of the ferrocyanides of the transition metals, (4) 112*g*.
Seifer, G. B., and Tananaev, I. V. Normal orthophosphates of niobium and tantalum, (1) 23*c*.
Seifert, F., and Schreyer, W. Synthesis of a new mica, $KMg_{3.4}[Si_4O_{10}]D(OH)_2$, (6) 170*j*.
Seifert, J. A. See Moreau, N.
Seifert, J. R. See Allerton, G. L.
Seigle, L. See Brett, J.; Resnick, R.
Seiter, H. Method of reducing semiconductor junction areas, P (9) 243*f*.
Selas Corp. of America. Gas mixing, P (5) 132*d*. Glass melting furnace with submerged gas burners, P (7) 183*c*. Industrial burner, P (1) 17*j*, P (2) 46*e*, P (3) 77*g*. Industrial burner with recuperative means, P (10) 282*c*. Manufacture of structural slabs, P (6) 154*g*. Method and apparatus for particle forming and spray drying, P (9) 244*j*. Method of furnace operation, P (1) 17*j*. Method of melting glass with submerged combustion heaters and apparatus therefor, P (9) 236*d*.
Selden, G. Hydraulic cement mortar compositions, P (6) 144*i*.
Seldenrath, T. R., Verstraten, J., and Timmermans, F. J. H. Method of splitting nonmetallic brittle materials and devices for carrying out such methods, P (2) 47*j*.
Selgin, P. J. Magnetic and optical differential thickness measuring instrument, P (9) 246*d*.
Selig, H., and Schievenedel, F. Pneumatic conveying, storing, and/or mixing apparatus, P (5) 126*d*.
Selivanova, N. M. See Leshchinskaya, Z. L.
Selivanova, N. M., and Leshchinskaya, Z. L. Thermodynamic properties of strontium selenide, (9) 257*e*.
Selivokhina, M. S. See Mikheeva, V. I.
Selka, F. See Gress, L.
Sellberg, B., and Rundqvist, S. Crystal structure of Mo_3P, (2) 48*j*.
Selman, G. L., Spender, M. R., and Darling, A. S. Wetting of platinum and its alloys by glass (II) rhodium-platinum alloys and the influence of gold, (4) 96*c*; (III) microstructure and mechanical properties of gold-rhodium-platinum alloys, (5) 122*b*.
Selte, K. See Furuseth, S.
Selte, K., and Kjekshus, A. Magnetic properties of niobium selenides and tellurides, (1) 23*f*. Niobium selenides with approximate composition $NbSe_1$, (2) 50*i*.
Semenov, Ya. A. See Barsauskas, K.
Semerchan, A. A. See Pivovarov, L. Kh.
Semiconductor Research Foundation. Silicon semiconductor device for high frequency and method of its manufacture, P (9) 244*d*.
Semishin, V. I. Interactions of certain materials and metals with solid crystallohydrates, (1) 22*h*.
Sen, B. K., and Sen, S. Problems connected with the manufacture of steatites, (4) 102*g*. Production of high density grinding medium, (4) 102*h*.
Sen, P., and Gupta, S. M. Some physical and chemical properties of strontia and baria substituted soda-lime-silica glass, (4) 95*i*.

Sen, R. K. See Talapatra, S. K.
Sen, S. See Bhattacharyya, B. N.; Bhushan, B.; Guha, S. K.; Sen, B. K.
Senba, K. See Miyatake, K.
Sendeckyj, G. P. See Dundurs, J.
Senderovich, V. Ya. See Vargin, V. V.
Sendlinger Optische Glaswerke G.m.b.H. See Licentia-Patent-Verwaltungs-G.m.b.H.
Sendt, A. Influence of atmospheric oxygen on bubble formation in the galvanic cell platinum/glass-refractory material/platinum (II), (1) 4*c*.
Seney, J. S. Process for making a capacitor element for high temperature operation, P (8) 221*h*.
Sennewald, K., Vogt, W., and Ohorodnik, A. Process for the manufacture of a catalyst containing vanadium and tin oxides, P (6) 155*h*.
Sens, F. T. Apparatus and method for melting heat-softenable material, P (5) 122*f*.
Sens, F. T., and Stalego, C. J. Method and apparatus for forming fine fibers, P (7) 183*h*.
Sensonics, Inc. Temperature measuring device, P (4) 108*h*.
Serdyuk, S. M., Gul'ev, G. F., Kozin, G. N., and Svet, A. L. Measurement of metal temperature in converters by thermocouples with zirconium boride cermet tips, (3) 76*b*.
Serdyuk, S. M., Korobko, M. I., Sobolev, S. K., Sizenko, A. S., Kachur, B. K., and Vlasov, K. R. Measurement of the metal temperature in 50-ton converters by means of thermocouples protected by cermet zirconium boride end caps, (1) 16*h*.
Sereda, P. J. See Feldman, R. F.; Kamimura, K.; Ramachandran, V. S.
Sergeenkova, V. M. See Grigor'eva, V. V.
Sergeeva, G. N. See Syritskaya, Z. M.
Sergienkova, V. M. See Grigor'eva, V. V.
Sermon, G. T. Method of making high strength nuclear reactor elements, P (5) 126*h*.
Service (Engineers), Ltd. Machines for finishing articles of ceramic ware, P (6) 157*a*. Machines for operating on blanks of ceramic ware, P (3) 72*b*. Manufacture of pottery, P (7) 190*j*.
Servo Corp. of America. Optical infrared-transmitting glass compositions, P (6) 150*d*.
Sesini, R. See Bassi, A.
Sestak, J. See Bergstein, A.
Settle, J. See Feder, H.
Seufert, L. E. See Hailstone, R.
Seymour, J. A., and Holden, R. L. Reinforcement of molded abrasive articles, P (10) 261*f*.
Shafer, H. J., Jr. See Blank, J. M.
Shafer, M. W. See McGuire, T. R.
Shafer, M. W., and Suits, J. C. Preparation and Faraday rotation of divalent europium glasses, (6) 148*d*.
Shaffer, A. C. Bending mold with leading apertured plate, P (2) 33*c*.
Shaffer, P. T. B. Effect of crystal orientation on hardness of beta silicon carbide, (1) 20*c*.
Shaffer, W. R., and Dunn, J. B. Reflective spheroids, P (8) 213*i*.
Shafranovskii, I. I. See Dement'eva, G. I.
Shakhtin, D. M. See Levintovich, E. V.
Shalek, P. D. See Baskin, Y.
Shalek, P. D., and White, G. D. Studies in the system uranium carbide–uranium sulfide, B (6) 172*b*.
Shaler, A. J. Producing dense articles from powdered carbon and other materials, P (7) 189*d*.
Shaler, R. G. See Shaler, R. G., Jr.
Shaler, R. G., Jr., McAdam, R. L., and Shaler, R. G. Vinyl amine modified clay process, P (10) 283*e*.
Shallcross, F. V. Effects of fabrication parameters on structural and electronic properties of thin CdS and CdSe films, (7) 191*g*.
Shal'nev, K. K., Rozanov, N. P., Pshenitsyn, P. A., Inozemtsev, Yu. P., and Sakharov, V. I. Mechanism of cavitation erosion of cement and polymer concretes, (4) 90*j*.
Shamp, D. E. See O'Connell, T. B.
Shanley, F. R., and Knapp, W. J. Laminated metal-ceramic composite material (I, II), (1) 3*e*.
Shannon, J. P., Philp, S. F., and Trump, J. G. Insulation of high voltage across solid insulators in vacuum, (10) 277*b*
Shannon, R. F. High temperature resistant vitreous material and method of producing, P (5) 123*b*. Structural panel and method for producing, P (4) 98*c*. Structures comprising vitrified and devitrified mineral fibers, P (3) 64*j*. See Kalousek, G. L.; Pfeifer, O. W.
Shannon, R. F., and Sullivan, P. W. Combined fiber and cellular article, P (11) 297*j*.
Shapiro, E. See Backlin-Landman, H.
Shapkin, P. S. See Vasil'kova, I. V.
Sharanov, V. P. See Nabiullin, F. H.
Sharma, R. A., and Richardson, F. D. Activities of manganese oxide, sulfide capacities, and activity coefficients in aluminate and silicate melts, (1) 7*j*.
Sharma, T., Mueller, R. F., and Clayton, R. N. $^{18}O/^{16}O$ ratios of minerals from the iron formations of Quebec, (1) 23*d*.
Sharnopol'skaya, E. T. See Mednikova, E. I.
Sharp, J. H., Brindley, G. W., and Achar, B. N. N. Numerical data for some commonly used solid state reaction equations, (8) 226*a*.
Sharp, W. E., and Kennedy, G. C. System $CaCO_3$–CO_2–H_2O in the two-phase region calcite + aqueous solution, (2) 52*h*.
Sharpe, R. E. Divergent beam X-ray diffraction and its application to irradiated magnesia, (2) 49*a*.
Sharples, T. D. Apparatus for analyzing for particle size distribution, P (11) 311*a*.
Shashkov, Yu. M., and Rozhdestvenskaya, V. V. Growth of crystals of silicon carbide from the vapor state, B (11) 320*a*.
Shaskol'skaya, M. P. See Dobrzhanskii, G. F.
Shatova, N. P. Service of new types of refractories in the high-temperature melting of glass, (1) 10*f*.
Shatterproof Glass Corp. Glass [gravity] bending apparatus for forming curved glass panes having conical surface portions, P (5) 122*g*. Hold down device for glass bending mold, P (3) 63*b*.
Shatzel, N. W. See Merker, W. T.
Shaw, B. A. Magnetic cores for electrical devices and method of manufacture, P (11) 306*j*.
Shaw, D. W. See McAtee, J. L., Jr.; Mehal, E. W.
Shaw, E. W. Method of producing heat insulating panels, P (7) 184*j*.
Shaw, K. Color chemists get down to fundamentals (I), (8) 218*j*; (II), (10) 275*f*. Mechanization must replace a dying skill, (5) 127*f*. New interest in glass technology for the ceramist, (7) 181*a*.
Shaw, R., Steadman, R., and Pugh, J. D. Stacking faults in cronstedtite and other kaolin-type silicates, (7) 202*e*.
Shay, G. C. See Cortright, S. A.
Shchelkonogov, V. Ya. See Aleksandrov, L. N.
Shchukarev, S. A., and Perfilova, I. L. Interactions of the trichloride of vanadium with the chlorides of sodium, potassium, and rubidium, (11) 317*j*.
Shchukarev, S. A., Tolmacheva, T. A., and Tsintsius, V. M. Disproportionation of the tribromide of vanadium at high temperatures, (4) 110*a*.
Shchukarev, S. A., Vasil'kova, I. V., and Korol'kov, D. V. Interaction of di-, tri-, and tetrabromides of titanium with the bromides of rubidium and cesium, (11) 317*e*.
Shea, F. L., Jr., and Stecker, G. Apparatus useful in the production of low-permeability high-density carbon and graphite bodies, P (6) 154*h*. Production of low-permeability high-density carbon and graphite bodies, P (7) 189*e*.
Sheets, A. R., and Utz, D. L. Insulating heat-sink holder for transistors, P (7) 193*e*.
Sheets, H. D., Jr. See Hyde, C.
Sheets, M. Designer in industry, (4) 89*j*.
Sheftal, N. N. See Shubnikov, A. V.
Sheftal, N. N., and Gavrilova, I. V. Equilibrium shape of a crystal in relation to the bulk free energy, B (11) 319*i*.
Sheftal, N. N., Givargizov, E. I., Spitsyn, B. V., and Kevorkov, A. M. Growth of epitaxial germanium films from supercooled droplets, B (11) 319*h*.
Sheldon, B. E. See Whapham, A. D.
Sheldon, G. J. Method of forming apertured optical disks, P (6) 150*a*.
Sheldon, S. See Morey, D. R.
Shelkovnikov, B. A. Russian glass from the 11th to the 17th century, (9) 230*a*; in the first half of the 19th century, (4) 90*c*.
Shell, H. R. See Johnson, R. C.
Shell, H. R., Pace, N. A., and Nichols, E. F. Synthesis of large crystals of fluorphlogopite mica, P (3) 79*c*.
Shelton, H. J., Jr. Hammer mills, P (3) 78*g*.
Shelton, H. J., Jr., and Freeman, L. Grinders [hammer mill], P (4) 109*f*.
Shelton, J. W. Trend and genesis of lowermost sandstone unit of Eagle sandstone at Billings, Montana, (2) 47*j*.
Shelyubskii, V. I. New method for determining and controlling the homogeneity of glass, (7) 181*b*. See Brekhovskikh, S. M.
Shelyubskii, V. I., and Gefen, A. G. Automatic apparatus for determining the heterogeneity of glass, (4) 92*b*.
Shelyubskii, V. I., and Karchmar, Ts. A. Improved method for controlling the homogeneity of glass batches, (4) 93*c*.
Shen, Chi-yu, Chiao, Hung-ke, Liu, Yu-shu, and Chang, Ru-chao. Zonal studies of used magnesite-alumina brick in open-hearth furnace roofs, (8) 216*g*.
Shenango Ceramics, Inc. Method of making ceramic dishware, P (11) 304*c*.
Shenango China, Inc. Method of firing a tunnel kiln, P (11) 311*i*. Multiple-compartment china [shipping] carton, P (4) 103*d*.
Shendyapin, A. S. See Isakova, R. A.
Shennan, J. B., and Nicholls, M. J. Fabrication of small uranium carbide spheres, B (6) 172*b*.
Shepard, A. O. Rio Grande glaze-paint pottery—a test of petrographic analysis, B (6) 172*d*.
Shepard, A. P. See Dittrich, F. J.
Shepard, R. N. Method of making glass-to-metal seals, P (3) 64*g*.
Shephard, G. G. Static response characteristics for a carbon bolometer, (3) 76*g*.
Shepherd, E. J. Production of refractory molds, P (1) 12*b*.
Shepherd, J. F., and Bachler, C. L. Composition and method of forming an extended lead dioxide activator, P (1) 18*d*.
Shepherd Chemical Co. Composition and method of forming an extended lead dioxide activator, P (1) 18*d*.
Sherif, I. I., and Mahmoud, N. S. Measurements of thermal conduction and surface finish by the thermal comparator, (9) 245*d*.
Sherwood, A. E. Sealed glass thermocouple and adjustable thermostat assembly, (9) 245*j*.
Shestak, N. A. Melting glass in furnaces with divided zones, (10) 265*h*.
Shestak, N. A., and Rokhlin, P. N. Regenerative glass furnace with counterflow flame, (10) 266*c*.
Shevel, W. L., Jr., Gutwin, O. A., and Grebe, K. R. Method of producing ferrite core assembly for magnetic storage devices, P (5) 129*h*.
Shevelevich, R. S. Controlling the chemical composition of glass by its optical properties, (10) 264*d*.
Shevtsova, Z. N. See Korshunov, B. G.; Pashinkin, A. S.; Safonov, V. V.
Shevtsova, Z. N., Korzina, E. N., and Korshunov, B. G. Study of the interaction of praseodymium chloride with the chlorides of sodium and potassium in melts, (2) 52*a*.
Shevyakov, A. M. See Toropov, N. A.
Shiah, C. D. Process for producing titanium dioxide concentrate and other useful products from ilmenite and similar ores, P (8) 225*g*.
Shibuno, M. See Hayashi, T.
Shields, A. A. See Watts, C. H.
Shikano, H. See Miyatake, K.
Shimada, H. Results of using RP-1 patching material for a 2-ton cupola, (1) 10*e*.
Shimada, K. See Ohba, H.; Wada, K.
Shimada, N., and Kishida, M. Prolonging the life of open hearth furnace and regenerator roofs and increasing thermal efficiency by repairing the regenerator roof with gunning mix, (10) 272*g*.
Shimamura, G. See Okada, Y.
Shimazaki, T. See Tsuzuki, K.
Shimazu, M. Dust collector and its use in the refractory industry, (8) 215*c*.
Shimizu, F. See Takuma, H.
Shimizu, H. See Okubo, S.
Shimogo, Y. See Inoue, T.
Shimoiizaka, J. See Sato, T.
Shinobu, M. See Makino, M.
Shinoda, M. Method of producing a variable-capacitance germanium diode and product produced thereby, P (6) 160*e*.
Shinohara, Y. See Makino, M.
Shionogi & Co., Ltd. Apparatus for automatically inspecting ampoules, P (2) 32*h*.
Shionoya, S., Era, K., and Katayama, H. Decay characteristics of luminescence in ZnS phosphors by pulse light excitation, (5) 134*f*.
Shiraishi, M., Takashima, M., and Kawaji, A. Method of heat treating semiconductor devices to stabilize current amplification factor characteristic, P (4) 105*f*.
Shiraki, Y. Grinding of refractory materials, (7) 186*h*
Shiratori, K., and Iida, S. Anomalous temperature dependence of lattice constant of CrO_3, (10) 283*i*.
Shiratori, K., Tasaki, A., and Iida, S. Mechanism of reversible appearance of residual magnetization at low temperature transition in α-Fe_2O_3, (10) 277*f*.
Shiren, N. S. Ultrasonic maser amplification by stimulated phonon-photon double quantum emission in MgO, (10) 291*e*.
Shirkevich, T. L. See Kitaigorodskii, I. I.
Shisko, W. S. Incombustible board containing mineral and cellulosic fibers and metal oxide and method therefor, P (3) 70*a*.
Shkarlinskii, O. F. See Dubrovskii, V. A.
Shklyar, R. Sh. See Kuznetsov, S. I.
Shlyuko, V. Ya. Laboratory apparatus for electron-beam vacuum melting and machining of refractory cermets, (1) 17*h*.
Shober, F. R. See Wagner, W. A.
Shobert, W. R., and Olson, W. G. Friction and wear for carbon bearings, (2) 44*h*.
Shockley, W. Semiconductive device and method of making the same, P (5) 130*b*.
Shoemaker, R. H., and Geschwender, H. Methods and compositions for cleaning metal, P (9) 232*d*.
Shombert, D. J. Temperature compensating barrier layer semiconductor, P (9) 244*a*.
Shonebarger, F. J. Glass-to-metal and glass-to-ceramic seals, P (11) 296*a*.
Shonebarger, F. J., and Blau, H. H. Study of glass surfaces by generation of electrostatic charges, (10) 266*f*.
Shor, A. J. See Kraus, K. A.
Shorr, N. Transmission baffle in glass drawing zone, P (4) 98*d*.
Shorr, N., and Barsich, J. M. Glass sheet drawing apparatus with an energy transmitter, P (1) 6*d*.
Short, M. A., and Walker, P. L., Jr. Measurement of interlayer spacings and crystal sizes in turbostratic carbons, (4) 112*a*.
Short, T. N. Mechanical system sets drain tile, (8) 214*f*.
Shorygin, V. A. See Ikornikova, N. Yu.
Shoshan, S. Z. Versatran—for maximum flexibility in product handling, (8) 222*e*.
Shrier, L. L. See Openshaw, P. R.
Shringi, S. N. See Bhide, V. G.
Shriver, E. L. See Collins, J. D.
Shrode, W. A. See Cilker, W. H.
Shroff, A. M. Electron-emissive structure, P (9) 243*c*. See Freytag, J. P.
Shtasel, A. Method of making solid capacitor, P (8) 221*b*.
Shtaveman, A. V. See Berzon, S. A.
Shtol'man, Z. M. See Makhnavetskii, A. S.
Shtrom, E. N. See Arabei, B. G.
Shturbanov, M., and Konstantinov, V. Elimination of the harmful effect of limestone inclusions in the clay used for structural ceramics, (6) 151*d*.
Shubnikov, A. V. Scheme of subordination of crystallographic point groups and system, (9) 255*f*.
Shubnikov, A. V., and Sheftal, N. N. (editors). Growth of Crystals (Vol. 4), B (11) 319*j*.

Shulepov, V. I. See Funke, V. F.
Shulver, W., Miller, W. H., Atteridge, T. L., and Marzocchi, A. Electrically conductive elements and their manufacture, P (7) 192*i*. Method for producing electrically conductive elements, P (11) 299*e*.
Shumilina, V. I. See Borisov, B. I.
Shur, Ya. S. See Sokolov, A. D.; Startsev, N. E.
Shurtz, R. F. Refractory block molding machine, P (6) 155*b*. Refractory bonded with pitch, P (1) 12*b*.
Shushkin, V. F., and Ivanov, F. S. Ultrasonic defectoscope for ceramics, (10) 281*d*.
Shusterman, M. I. See Vladimirov, L. P.
Shvagirev, Yu. Ya. Washing-drying equipment for flat instrument glasses, (10) 267*f*.
Shvaiko, V. P. Black glaze for porcelain, (2) 39*a*.
Shvartsman, L. A. See Alekseev, V. I.
Shveikin, G. P., Gel'd, P. V., and Alyamovskii, S. I. Conditions of formation of the oxycarbides of niobium, (6) 165*d*.
Shyam, M. See Allen, J. W.
Sibert, M. E., and Tsukamoto, J. Inorganic surface coatings, P (3) 59*j*.
Siddiqi, F. A. See Akhtar, S. M.
Siddle, J. D. See McGarry, P. E.
Sidorenko, F. A. See Strekalovskii, V. N.
Sidorko, V. R. See Eremenko, V. N.
Siebertz, K., and Henker, H. Method for remelting a rod of crystallizable material by crucible-free zone melting, P (5) 129*a*.
Sieckmann, E. F. See Liu, C. J.
Sieckmann, J. See Hennicke, H. W.
Siegle, J. C., and Teti, J., Sr. Submerged arc welding process and flux composition utilizing fluorocarbon, P (11) 296*d*.
Siegmund, W. P. Composite image display device formed of fiber ribbons, P (7) 182*d*. Fiber optical faceplates having different numerical aperture values in two different directions, P (11) 298*d*. Fiber-optical image transfer device having a multiplicity of light absorbing elements, P (7) 182*i*. Method of making a fiber-optical image transmitting device, P (7) 184*f*. Method of making honeycomb structure, P (11) 299*c*.
Siemens & Halske Akt.-Ges. Apparatus for preparing semiconductor rods, P (4) 104*h*. Apparatus for pulling rod-shaped crystals of semiconductor material from a melt in a crucible, P (9) 242*j*. Ceramic tube with self-supporting frame grid electrode system, P (2) 41*b*. Device for pulling monocrystalline semiconductor rods, P (5) 128*b*. Diffused-base transistors, preferably for high-frequency operation, P (3) 73*b*. Method and apparatus for producing elongated strip-shaped crystalline semiconductor bodies, P (11) 306*b*. Method for producing highly pure rod-shaped semiconductor crystals and apparatus, P (3) 73*h*. Method of producing mesa transistors and other semiconductor devices having portions of reduced cross section, P (6) 160*c*. Method of producing a *pn* junction in a monocrystalline semiconductor device, P (9) 243*e*. Method of pulling a semiconductor crystal from a melt, P (10) 279*d*. Method of reducing semiconductor junction areas, P (9) 243*f*. Method for remelting a rod of crystallizable material by crucible-free zone melting, P (5) 129*a*. Producing rod-shaped semiconductor crystals, P (5) 129*f*. Regenerative capacitor, P (5) 129*g*. Semiconductor device and method of producing it, P (6) 160*f*. Semiconductor *pn* junction device and method of its manufacture, P (11) 308*a*.
Siemens-Planiawerke Akt.-Ges. fuer Kohlefabrikate. Gas and liquid tight joint of graphite bodies, P (9) 240*b*. Nuclear fuel element with carbon jacket, P (1) 12*a*. Sintered resistance body, preferably for use as heating element, P (11) 303*h*.
Siemens-Schuckertwerke Akt.-Ges. Apparatus for crucible-free zone melting of semiconductor material, P (11) 305*j*. Apparatus for [electrolytically] doping and contacting semiconductor bodies, P (9) 242*i*. Conveying apparatus (pneumatic) for fine-granular material, P (3) 75*b*. Electronic semiconductor members and method of their manufacture, P (4) 104*f*. Ferromagnetic bodies with high thermal shock resistance and process for obtaining them, P (8) 221*a*. Galvanomagnetic semiconductor devices, P (10) 278*i*. Method and apparatus for floating-zone melting of semiconductor material, P (10) 278*d*. Method and apparatus for handling pulverulent material, P (4) 107*a*. Method and apparatus for scoring semiconductor plates to be broken into smaller bodies, P (4) 105*c*. Method of attaching an electric connection to a semiconductor device, P (4) 105*c*. Method of crucible-free production of gallium arsenide rods from alkyl galliums and arsenic compounds at low temperatures, P (4) 105*e*. Method of crucible-free zone melting of semiconductor material, P (3) 73*i*. Method of doping semiconductor material, particularly silicon, with boron, P (6) 159*g*. Method of etching Si and Ge semiconductor bodies, P (10) 278*g*. Method of producing electrically asymmetrical semiconductor device of symmetrical mechanical design, P (5) 129*h*. Method of producing electronic semiconductor devices by precipitation of monocrystalline semiconductor substances from a gaseous compound, P (4) 105*c*. Method of producing an oxide coating on crystalline semiconductor bodies, P (9) 243*d*. Method for producing a semiconductor device with a monocrystalline semiconductor body, P (4) 105*e*. Method of producing a semiconductor member, P (11) 307*b*. Method of producing a silicon semiconductor device, P (10) 279*d*. Method for producing single-phase mixed crystals, P (5) 129*j*. Method of producing III-V semiconductor compounds in crystalline form, P (11) 307*a*. Method for surface treatment of semiconductor devices of the junction type, P (4) 105*f*. Mix-crystal semiconductor devices, P (9) 243*h*. Mixed-crystal thermoelectric compositions, P (1) 15*a*. Process for preparing semiconductor ingots within a depression, P (9) 244*a*. Zone melting gallium in a recycling arsenic atmosphere, P (9) 244*e*.
Siemssen, E. A. Method and apparatus for particle forming and spray drying, P (9) 244*j*.
Sienko, M. J., and Banerjee, B. Studies in nonstoichiometry—magnetic susceptibilities in the tungsten–oxygen system, (7) 203*c*.
Sienko, M. J., and Truong, T. B. N. Studies in nonstoichiometry—electrical conductivity and carrier mobility in lithium tungsten bronzes, (7) 203*c*.
Sigma Instruments, Inc. Electrical coupling device, P (7) 192*g*.
Signal Oil & Gas Co. Recovery of lithium from brines, P (10) 283*c*.
Sihvonen, Y. T. See Boyd, D. R.
Sihvonen, Y. T., and Parker, S. G. High performance photoresistor, P (1) 14*c*.
Sika Chemical Corp. Additives for concrete, mortar, and grout, P (2) 29*f*.
Sikina, T. V. Semiconductor integrated structures and methods for the fabrication thereof, P (11) 307*j*. See Hall, J. A., Jr.
Sikina, T. V., and Murray, F. L. Method of fabricating thin film R-C circuits on single [glass] substrate, P (9) 243*i*.
Silalnikas, V., and Pozela, J. Emission of hot electrons by silicon, (6) 167*a*.
Sil'chenko, L. A., Mikhailov, N. V., and Rebinder, P. A. Kinetics of the hydration of cement in concrete at elevated temperatures, (9) 231*d*. Selection of optimum holding time of concrete prior to hydrothermal treatment, (2) 29*f*.
Sileika, A. See Babonas, G.; Barsauskas, K.
Silika-und Schamotte-Fabriken Martin & Pagenstecher Akt.-Ges. Process for producing brick and refractory bodies, P (7) 189*b*.
Silver, M. See Homarek, K. L.
Silver, T. J. Method of compacting ferrite particles, P (10) 278*c*.
Silverman, B. D. See Kohane, T.
Silverman, E. N. See Hubble, D. H.
Silverman, W. B. Apparatus for skimming and stirring molten glass, P (2) 32*f*.
Silverwood, F. W. See Barradell-Smith, R.
Simandoux, P. See Basty, W. du.
Simanov, Yu. P. See Aslanov, L. A.
Simeonov, K. See Kukusheva, M.; Stefanov, G.
Simkovich, G. Some effects of point imperfections in ionic type crystals, (6) 170*b*.
Simmen, F. G. Hotel china developments, (2) 39*c*.
Simmers, C. D. Apparatus for forming fiber, P (5) 122*f*. Rotor for [centrifugally] forming glass filaments, P (7) 184*g*.
Simmers, C. D., Gould, T. R., and Anderson, R. C. Apparatus for producing a propulsion stream adapted to attenuate fibers, P (7) 182*b*.
Simmingskold, B. See Lakatos, T.
Simmons, E. L., and Wendlandt, W. W. Automatic apparatus for simultaneous thermogravimetric and magnetic susceptibility measurements, (11) 309*f*.
Simmons, J. A. New muscle for platen grinding, (6) 143*g*.
Simmons, R. G. See Ames, I.
Simon, E. Three ancient cameo glass vessels at Corning, Florence, and Besancon, (4) 90*a*.
Simon, R. See Leroy, P.
Simon-Carves, Ltd. Analysis of particle size distribution, P (5) 132*c*.
Simonich, A. T. See Morozov, I. S.
Simons, C. C. Method of explosively compacting powders to form a dense body, P (3) 75*a*. See Carlson, R. J.
Simova, M. See Dzhambazova, T.
Simpson, G. H. See Ricker, W. C.
Simpson, H. E. Mechanism of corrosion of glass (I, II), (2) 32*a*.
Simpson, L. A., and Carter, R. E. Oxygen exchange and diffusion in calcia-stabilized zirconia, (4) 112*e*.
Simpson, L. D. See Gaska, R. A.
Simulyte, E. See Deksnys, A.; Tolutis, V.
Sinclair, J. H. See Bell, K. R.
Sinclair Refining Co. Boehmite base precursor, P (7) 188*i*.
Sinclair Research, Inc. Synthetic alumina, silica-alumina hydrocarbon cracking catalyst, and method for hydrocarbon cracking, P (9) 241*c*.
Singer, E. See Bauer, W.
Singer, J., Jr. Composite supported fiber optic strip, P (11) 298*a*.
Singh, D. S. Measurement of spectral reflectivity with the Reichert microphotometer, (8) 223*a*.
Singh, S. See Matthews, H.
Singletary, J. B. See Rittenhouse, J. B.
Singleton, A. Kiln gun projectile, P (5) 132*g*.
Singleton, E. See Lynam, T. R.
Singleton, J. H., and Lange, W. J. Outgassing procedures for glass ultrahigh-vacuum systems, (10) 281*i*.
Singleton, R. H. See Miller, D. G.
Sinha, B. C. See Gupta, S. D.
Sinha, K. K. See Hammond, J. P.
Sinha, K. P. See Joshi, A. W.
Sinha, N. K. See Bateson, S.
Sinikas, R. I. See Demkina, L. I.
Sirera, S. B. Proceeding with its corresponding apparatus for the manufacturing of fibro [asbestos] cement articles, P (5) 126*h*.
Sirgo, V. H. Apparatus [horizontal furnace] for growing fluoride crystals, P (11) 305*j*.
Sirhal, H., and Kastanek, J. Determination of the permissible stresses in ceramic bodies as a basis for rapid firing, (11) 299*j*.
Sirianni, A. F. See Puddington, I. E.
Sirtl, E. See Grabmaier, J.
Sirvaitis, A., and Aleksejunas, B. X-ray sensitivity of single Sb_2S_3 crystals, (3) 87*g*.
Sisman, O. See Carroll, R. M.; Reagan, P. E.
Sivacek, M. Methods of activated sintering based on the use of chlorine, (10) 272*a*.
Sizelove, J. R. Contour design for "cascading by shaping" thermomagnetic devices, P (3) 72*i*.
Sizenko, A. S. See Serdyuk, S. M.
Skalko, F. C., and Owens, J. J. Apparatus for forming and processing textile fibers and filamentary materials, P (9) 235*b*.
Skalla, N. See Moertl, G.
Skantze, H., and English, C. J. Prebake anodes for electrolytic production of aluminum and coating therefor, P (5) 126*d*.
Skavdahl, R. E. See Burnham, J. B.
Skeggs, L. T., Whitehead, E. C., Smythe, W. J., Isreeli, J., and Pelavin, M. H. Method and apparatus for sequentially performing analyses on a plurality of fluid samples, P (6) 163*b*.
Skelleftea Gummifabriks AB. See Bolidens Gruvaktiebolag.
Skhirtladze, N. I. See Drotsenidze, G. S.
Skiba, O. V. See Smirnov, M. V.
Skiba, O. V., Smirnov, M. V., and Khazemova, T. F. Diffusion coefficients of U^{3+}, U^{4+}, and UO_2^{2+} ions in NaCl-KCl melt, B (1) 26*a*.
Skinner, H. Modern thermochemical methods for determining heats of formation, B (6) 175*g*.
Skinner, K. G. Apparatus for comparative determination of thermal conductivity, P (9) 246*c*.
Skoda, R. E. Method for sputtering niobium or tantalum thin films, P (11) 307*d*.
Skodzus, E. D. Container and/or vial shaping apparatus and method therefor, P (6) 149*g*.
Skofronick, J. G., and Phillips, W. B. Energy for surface mobility of thin discontinuous gold films on mica substrates, (7) 191*i*.
Skogerboe, R. K. See Harrington, W. L.
Skolozdra, R. V. See Gladyshevskii, E. I.
Skorik, Yu. I., Gileva, K. G., Kukharskaya, E. V., and Fedoseev, A. D. Increasing the number of ≡Si—OH surface groups in silicates with a laminated structure, (5) 137*g*.
Skoumbourdis, C. T. See Hall, M. E.
Skripko, S. A. See Koz'min, M. I.
Skrivan, J. F. Production of oxides by plasma process, P (11) 303*h*.
Skudera, W. J. See Wade, W. L.
Skudnova, E. V., and Mirgalovskaya, M. S. Effective coefficient of distribution of tellurium in aluminum antimonide, (1) 20*i*.
Skudnova, E. V., Mirgalovskaya, M. S., and Annamamedov, R. Distribution coefficient of zinc in indium antimonide, (9) 249*j*.
Slabodsky, F. Method of analyzing glass sheets for cutting, P (2) 33*g*.
Slack, G. A. Thermal conductivity of pure and impure silicon, silicon carbide, and diamond, (6) 170*h*. See Oliver, D. W.
Slater, C. Analysis of particle size distribution, P (5) 132*c*.
Slater, J. C. Predictions by a priori theory, B (9) 259*d*.
Slater, S. I. Semiconductor diode and manufacture thereof, P (6) 160*h*.
Slater Electric, Inc. Semiconductor diode and manufacture thereof, P (6) 160*h*.
Slattum, C. L. See Karalis, S. N.
Slaughter, J. I. See Kendall, E. G.
Slavgorodskaya, E. Ya. See Levintovich, E. V.
Slavnova, G. K., Luzhnaya, N. P., and Medvedeva, Z. S. Diagram of state of the system indium–selenium, (1) 20*j*. New data on the phase diagram of the system indium–selenium, (10) 288*i*.
Slavyanskii, V. T., Krestnikova, E. N., and Boreiko, B. M. New method of measuring glass viscosity in the range 10^5 to 10^{14} poises, (4) 94*j*.
Slayter, G. Method for forming crystal-free glass fibers, P (10) 268*j*. Pipe insulation, P (9) 236*h*.
Slayter, G., Russell, R. G., and Morgan, W. L. Muffler internally coated with highly refractory fibers, P (5) 123*i*.
Slayter, G., Snow, H. J., Russell, R. G., and Kleist, D. Apparatus for processing heat-softenable materials, P (9) 235*e*.
Slayter, G., Soltis, R. W., and Hall, A. E. Glass foam, P (1) 6*a*.
Slayter, G., and Woodward, R. M. Method of producing a lamellar metal structure, P (2) 34*j*.
Sleighter, G. E. See Fredley, J. C.
Sleptsov, V. M. See Krasnov, A. N.; Samsonov, G. V.
Sleptsov, V. M., and Kubli, S. A. Sintered filters from refractory compounds, (1) 10*g*.
Slizys, V. See Aleinikov, F. K.; Markeviciene, R.; Mikailiene, E.; Parfenov, V. A.; Vaitkus, J.; Zitkeviciute, I.
Sloczynski, J. See Bielanski, A.
Slonimskaya, M. V. See Raitburg, Ts. M.
Slooten, H. S. G. Preparation of granular thorium dioxide, P (5) 126*f*.
Smagina, E. I. See Kutsev, V. S.

Smakula, A. Defects in ionic crystals, B (9) 259*e*.
Small, A. B., and Babcock, H. N. Cementitious systems, P (5) 119*f*.
Small, R. L., and Drummond, W. W. Production of fiber glass strand, P (11) 299*d*.
Smalley, H. F. Effect of bubble structure on chemical and physical properties of ground coat porcelain enamels, (6) 145*g*. Rapid trouble shooting of porcelain enamel problems, (9) 232*b*.
Smallman, R. E. See Hollox, G. E.
Smallman, R. E., and Ashbee, K. H. G. Modern Metallography, B (9) 258*f*.
Smid, R. J. See Liedberg, D. J.
Smidth, F. L., & Co. Air separator with fluidized discharge, P (11) 308*j*. Apparatus for conveying finely divided material, P (5) 130*f*. Method and apparatus for making cement, P (5) 119*a*.
Smilga, A. See Vaitkus, J.
Smilga, A., and Viscakas, J. High-voltage photovoltaic effect in polycrystalline films of CdSe, (6) 167*j*.
Smirnov, E. I. Use of methods of mathematical statistics to study processes related to glass production, (10) 267*e*.
Smirnov, E. I., and Manusovich, M. I. Statistical study of technological operation of a glass melting tank furnace, (8) 211*c*.
Smirnov, M. V. (editor). Electrochemistry of Molten and Solid Electrolytes (Vol. II), B (1) 26*j*. See Anfinogenov, A. I.; Skiba, O. V.
Smirnov, M. V., and Krasnov, Yu. N. Behavior of TiO + C and Ti_2O_3 + C anodes during electrolysis of molten chlorides, B (1) 26*h*. Thermodynamics of formation of TiF_6^{3-} complex anion in molten salts, B (1) 26*h*.
Smirnov, M. V., and Pal'guev, S. F. Behavior of anodes of an intimate mixture of titanium dioxide and carbon during electrolysis of molten salts, B (1) 26*h*.
Smirnov, M. V., and Skiba, O. V. Equilibrium potentials of uranium dioxide electrodes in NaCl-KCl melt containing uranyl chloride, B (1) 26*j*.
Smirnov, V. P. Tank furnace for melting colored and coating glass, (9) 235*a*.
Smirnova, G. M. See Plyshevskii, Yu. S.
Smirnova, K. A. See Veankov, V. T.
Smirnova, Z. G., Illarionov, V. V., and Vol'fkovich, S. I. Heat of formation of fluorapatite, hydroxylapatite, and tricalcium phosphates (alpha and beta modifications), (5) 136*i*.
Smith, A. O., Corp. Glass coated member, P (2) 30*g*.
Smith, A. W., Meszaros, F. W., and Amata, C. D. Permeability of zirconia, hafnia, and thoria to oxygen, (6) 169*d*.
Smith, B. F. L. See Follett, E. A. C.
Smith, B. K. See Lynch, R. S.
Smith, D. C. See Combe, E. C.
Smith, D. F. Plaster of Paris products and their manufacture, P (3) 59*e*.
Smith, D. G. W. Chemistry and mineralogy of some emery-like rocks from Sithean Sluaigh, Strachur, Argyllshire, (11) 314*j*.
Smith, D. K. See Austerman, S. B.; Newkirk, H. W.
Smith, D. M. Hot-screen decorating of porcelain enameled products is easy with colored thermoplastics, (11) 295*k*.
Smith, E. R. See Knapp, W. R.
Smith, E. W. Vibrating ball mill method and apparatus, P (2) 43*h*.
Smith, F. H. Diamond grinding wheel dressers, P (10) 261*g*.
Smith, G. P. Ceramic heat exchanger structures, P (8) 217*g*. Method of making ceramic article, P (7) 184*e*.
Smith, G. P., and Stong, G. E. Structural ceramic bodies and method of making same, P (11) 304*d*.
Smith, G. V., Smith, R. G., and Thomas, A. G. Study of phase relations in U–Si–C system, B (6) 172*a*.
Smith, H. D., and Weiss, W. R. Bauxite brick, P (8) 217*d*.
Smith, H. R., Jr. Method of forming carbon vapor barrier, P (4) 101*c*.
Smith, H. W., and Hunter, R. H. Incandescent ceramic electrical igniter, P (2) 41*e*.
Smith, I. Tiled wall and floor surface covering and method and means for applying same, P (11) 304*e*.
Smith, J. F. See Mattare, L. A.
Smith, J. G. See Fitch, F. T.
Smith, J. S. See Mazdiyasni, K. S.
Smith, J. V. X-ray-emission microanalysis of rock-forming minerals (I) experimental techniques, (4) 114*c*.
Smith, J. V., and Stenstrom, R. C. Electron-excited luminescence as a petrological tool, (1) 21*b*.
Smith, L. I. Test procedure for dry grinding tungsten carbide with resinoid bonded diamond wheels, (8) 205*f*.
Smith, L. I., and Sacco, R. M. Armored diamond wheels for carbide grinding, (7) 177*e*.
Smith, L. M. See Hinkle, J. H., Jr.
Smith, L. N. Lustron revisited, (8) 207*j*.
Smith, M. C. Effects of temperature and strain rate on transverse tensile properties of H4LM graphite tested in helium and in vacuum, (4) 110*i*.
Smith, M. C., Eash, D. T., and McKibbin, K. Longitudinal tensile properties of H4LM graphite in the temperature range −253° to 500°C, (4) 112*e*.
Smith, M. J. Flashless encapsulated sphere manufacture, P (8) 217*a*. Fuel element manufacture, P (8) 217*b*. Method for extrusion of a graphite matrix containing coated particles, P (8) 217*e*.
Smith, P., Garcia-Blanco, S., and Rivoir, L. New structural type of metaborate anion, (3) 84*c*.
Smith, R. C. See Hacskaylo, M.
Smith, R. E. Method and apparatus for reducing fuzzing and breaking of strands, P (9) 236*h*.
Smith, R. G. See Smith, G. V.
Smith, R. G., Nassau, K., and Galvin, M. F. Efficient continuous optical second-harmonic generation, (10) 285*h*.
Smith, R. I. See Chelini, J. M.
Smith, R. M. See Johnson, J. R.
Smith, R. P. Wire guide for extruding machines, P (7) 190*b*.
Smith, R. W. See Counts, W. E.
Smith, S. See Seakins, L. W.
Smith, S. D. See Angress, J. F.
Smith, W. C. Method for forming enclosures for semiconductor devices, P (3) 73*j*.
Smith, W. D. See Meacham, D. D.
Smith, W. H. See Rairden, J. R.
Smith, W. H., and O'Brien, N. R. Middle and late Pennsylvanian flint clays, (2) 46*i*.
Smith, W. J. See Bennett, A. I., Jr.; Coleman, J. J.
Smith, W. J., Hamilton, D. R., and Coleman, J. J. Apparatus [furnace] for producing crystalline semiconductor material, P (1) 14*f*.
Smock, G. E., Fulk, W. F., Stream, R. M., and Leaman, H. E. Apparatus for delivering multifilament strands, P (10) 267*g*.
Smock, G. E., and Stream, R. M. Slitter for mat materials, P (2) 34*h*.
Smoke, E. J. See Ulrich, D. R.
Smolenskii, G. A., Isupov, V. A., Agranovskaya, A. I., and Krainik, N. N. New ferroelectrics of complex compositions (IV), (4) 112*c*.
Smolenskii, G. A., Isupov, V. A., Agranovskaya, A. I., and Popov, S. N. Ferroelectrics with diffuse phase transitions, (4) 111*b*.
Smoleva, D. See Dimov, D.; Petkov, P.
Smolyaninov, N. P. See Belyaev, I. N.
Smolyaninov, N. P., and Belyaev, I. N. Investigation of the system Bi_2O_3–WO_3–PbO, (1) 23*d*. Phase equilibria in the system Bi_2O_3–V_2O_5–PbO, (11) 318*h*.
Smoot, T. W. See Walther, F. H.; Whittemore, D. S.
Smoot, T. W., and Ryan, J. R. Method of forming refractory mold shapes, P (5) 126*e*.
Smothers, W. J. See Ulmer, G. C.
Smyth, B. Minerals can now be sorted by color, (11) 312*f*.
Smythe, L. E., and Whately, T. L. Determination of water in beryllium oxide, (7) 194*j*.
Smythe, W. J. See Skeggs, L. T.
Snaper, A. A. Pulverizer having ultrasonic drive means, P (3) 79*b*.
Snow, E. H., and Dumesnil, M. E. Space-charge polarization in glass films, (9) 234*g*.
Snow, H. J. See Kleist, D.; Slayter, G.
Snyder, E. C. Method of producing welded double glazing units, P (10) 269*a*.
Snyder, E. F., and Ziemke, M. C. Thermal radiation shields, (7) 195*j*.
Snyman, J. A. See Herbstein, F. H.
Sobanski, R. See Kakol, M.
Sobolev, S. K. See Serdyuk, S. M.
Sobolevskii, S. I. See Savonichev, G. V.
Sobon, L. E., and Greene, P. E. Crystal growth of some vanadium oxides, (3) 80*a*.
Sochackaya, G. A. See Budnikov, P. P.
Societa Italiana Refrattari Marghera Azionaria. Refractory elements for supporting tiles, etc., during glost firing, P (8) 218*c*.
Societe Amandinoise de Faiencerie et Produits Refractaires. Semiautomatic machine with two stations for shaping plates, P (6) 157*c*.
Societe Anonyme Glaverbel. Apparatus for melting products such as glass and method of working the same, P (10) 267*a*. Device for cooling drawn glass, P (5) 122*c*. Device for the protection of barriers in glass furnaces, P (4) 96*d*. Glass furnace having a refining chamber for the molten glass, P (9) 236*a*. Method and apparatus for the skimming of molten glass, P (5) 123*b*. Method of and apparatus for the thermal conditioning of molten glass before its shaping, P (4) 97*i*. Process and apparatus for manufacturing a fire-polished glass strip, P (9) 236*j*. Process and apparatus for production of continuous fire-polished glass sheet, P (5) 123*j*. Process and device for casting refractory parts, P (9) 241*c*. Process and device for improving the thermal uniformity of molten glass, P (6) 150*j*. Process and furnace for melting and working products such as glass, P (3) 64*j*.
Societe Anonyme Oxydes Francais. Artificial magnetic oxides, P (5) 128*g*.
Societe le Carbone-Lorraine. Graphitized carbon articles containing rare earths, P (9) 240*c*. Process for joining pieces of carbon or graphite to similar materials or to refractory metals, P (10) 263*j*.
Societe d'Electro-Chimie, d'Electro-Metallurgie et des Acieries Electriques d'Ugine. Process of agglomerating fine crystals and cryolite product, P (2) 48*b*. Process for the manufacture of trihydrate of alumina, P (10) 283*e*. Production of anhydrous alumina, P (10) 283*a*.
Societe d'Electro-Chimie, d'Electro-Metallurgie et des Acieries Electriques d'Ugine and Societe Generale de Produits Refractaires. Refractory products for the aluminum industry and other reducing metals, P (8) 218*e*.
Societe des Electrodes et Refractaires "Savoie." Method of producing porous carbon elements, P (7) 188*i*.
Societe d'Electronique et d'Automatisme. Reusable transfer plate for making printed circuitry, P (4) 106*e*.
Societe Generale de Produits Refractaires. Glass and slag resistant refractories and process of making same, P (7) 188*c*. Refractory products based on alumina, zirconia, and silica and process of obtaining them, P (10) 275*a*. See Societe d'Electro-Chimie, d'Electro-Metallurgie et des Acieries Electriques d'Ugine.
Societe des Verreries Industrielles Reunies du Loing. Opal glass with a low coefficient of thermal expansion, P (11) 299*a*.
Society of Glass Technology, Chemical Durability Committee. Effect of temperature on the water-extraction of alkali from glass, (6) 147*c*.
Society of Glass Technology, Furnace Committee. Assessment of furnace performance, (2) 46*a*.
Socolow, A. A. See O'Neill, B. J., Jr.
Socony Mobil Oil Co., Inc. Aluminosilicate processing, P (8) 217*a*. Castable fibrous refractory compositions and articles obtained therefrom, P (8) 217*f*. Cementing of high temperature wells, P (7) 178*d*. Conversion catalyst comprising an aluminosilicate prepared from a hydrogen organoperoxymetalloaluminosilicate, P (4) 100*i*. Process for preparing a platinum metal-crystalline zeolite catalyst, P (4) 101*f*.
Soda, Y. See Yamaguchi, G.
Soden, R. R. See Johnson, L. F.
Soderquist, C. E. See Long, M. J.
Sodhi, J. S. Export of glass and glassware—its performance, prospects, and problems, (2) 31*c*.
Soejima, S. See Yamaguchi, G.
Soerstroem, L. See Kroeger, C.
Soga, M. See Maekawa, S.
Soga, N. See Schreiber, E.
Soga, N., and Anderson, O. L. High-temperature elastic properties of polycrystalline MgO and Al_2O_3, (8) 226*f*. Simplified method for calculating elastic moduli of ceramic powder from compressibility and Debye temperature data, (7) 202*j*.
Soini, H. E. See Glaser, P. E.
Sokolov, A. A. See Pchelyakov, K. A.
Sokolov, A. D., and Shur, Ya. S. Effect of small additions of cobalt on the hysteresis loop of nickel-zinc ferrites, (11) 316*g*.
Sokolov, V. A., Banashek, E. I., and Rubinchik, S. M. Enthalpy of corundum in the range 678° to 1330°K, (11) 316*c*.
Sokol'skii, V. I. See Umanskii, A. M.
Sole, M. J. See Eyre, B. L.
Solheim, W. G., II. Functions of pottery in Southeast Asia—from present to past, B (6) 172*g*.
Solid State Products, Inc. Method of making vertically and horizontally integrated microcircuitry, P (9) 243*j*.
Solinov, E. F. See Botvinkin, O. K.
Solinov, F. G., and Pankova, N. A. Experimental determination of the rate of bubble movement in a melt, (4) 93*g*. Interfacial angles of wetting and their influence on the size of bubbles during the clarification process, (1) 4*d*. Processes of froth formation on the surface of molten glass, (1) 5*d*. Rate of bubble rise in molten glass with an unstable temperature schedule, (10) 266*a*. Study of the conditions of growth of bubbles in the fining of glass, (7) 181*f*.
Solinov, F. G., and Terman, V. B. Relation between waviness of sheet glass and thickness variation, (1) 5*h*.
Solinov, V. F. See Brekhovskikh, S. M.
Solov'ev, O. A. See Bondarev, D. E.
Soltis, R. W. See Slayter, G.
Solymosi, F. Defect structure and electrical properties of semiconducting oxides, (11) 315*f*. Effect of defect structure on reactivity of solids, (11) 315*j*.
Somers, A. V. Ceramics, P (5) 130*i*. Dry grinding of ceramics, P (5) 130*j*, P (8) 222*g*.
Somers, E. V. Energy-conversion devices, B (9) 259*g*.
Somin, B. Kh. See Latsh, V. V.
Sommer, A., and Schulze, K. Method of producing hardened bodies from bituminous mixes, P (9) 240*f*.
Sommer, A. H. Method for making U-V responsive photoemissive tubes, P (10) 278*j*.
Somodi, A. See Paulik, I.
Somogyi, A. See Locsei, B. P.
Somov, A. I. See Verkhorobin, L. F.
Sonin, A. S., and Zheludev, I. S. Isomorphism and ferroelectric properties, B (11) 320*e*. Search for new ferroelectrics and antiferroelectrics not belonging to the oxide group, B (11) 320*d*.
Sonnenschein, H. Conveying apparatus [pneumatic] for fine-granular material, P (3) 75*b*.
Sono, K. See Nishiyama, T.
Sony Corp. Method of manufacturing a substantially stress free cathode ray tube, P (7) 184*g*.
Soonpaa, H. H., and Dunning, J. W. New manipulable variable in crystal growing, (5) 139*e*.
Sopchak, P., and Port, E. B. Anhydrous dense soda ash, P (5) 133*a*.
Soppet, F. E. See Ayer, J. E.
Sorbie, T. B. Inspecting and assorting glass containers, P (10) 268*g*. See Early, R. L.
Sordinas, A. Report on the manufacture and marketing of the adjagba beads in Ghana, (5) 118*c*.
Sorokin, P. P. See Dill, F. H.
Soskova, V. D. See Pollyak, V. V.
Sosman, R. B. Phases of Silica, B (6) 174*h*.
Southgate, P. D. Mechanical relaxation of a point defect in MgO, (3) 83*d*.

Southgate, P. D., Mendelson, K. S., and DePerro, P. L. Kilocycle-range dislocation damping in magnesium oxide, (5) 138*b*.
Southwestern Engineering Co. Roller-actuated vibro-energy mill, P (10) 280*e*. Vibro-energy mill, P (10) 283*e*.
Southwestern Portland Cement Co. Bag house facility, P (10) 262*h*.
Souza Santos, H. L. de. See Angeleri, F. B.; See Souza Santos, P. de.
Souza Santos, P. de. See Angeleri, F. B.; Kapel, I. B.; Lourenco, O. B.
Souza Santos, P. de, and Ferron, O. J. Dictionary of refractories terminology, (2) 54*e*.
Souza Santos, P. de, Kapel, I. B., and Souza Santos, H. L. de. Physicochemical and ceramic properties of clays and kaolins from northeastern Brazil, (2) 47*b*
Souza Santos, P. de, Souza Santos, H. L. de, and Moniz, A. C. Brazilian clays and kaolins, (2) 46*g*.
Sovalov, I. G., Khayutin, Yu. G., and Mikhailov, N. V. Effect of turbulent and vibroturbulent agitation on the rheological properties of cement and cement-sand mortars, (3) 58*j*.
Sowden, R. G. See Ainsley, R.; Hodge, N.; Horder, B. R.
Sowden, R. G., and Hodge, N. Method of producing nuclear fuel monocarbides from higher carbides, P (11) 302*g*.
Sowman, H. G., Surver, R. L., and Johnson, J. R. Development of spherical pyrolytic-carbon-coated UC_2 and $ThUC_2$ fuel particles, (3) 66*i*.
Soyck, W. Development and present state of magnetic ceramics, (6) 157*j*.
Spaapen, J. B. M., and Verhoeven, A. C. J. Method of manufacturing semiconductor devices, P (11) 306*i*.
Spaeth, N. Experience with the regulation of pot furnaces, (7) 180*j*.
Spalthoff, W. See Meyer, F.
Spanoudis, L. See Francel, J.
Sparks, R. A., and Higgins, E. L. CW-pumped and nondegenerate parametric amplification of elastic waves in YIG, (6) 166*c*.
Spatz, P. M. Flue gas analysis applied to glass melting and conditioning, (6) 147*e*.
Spear, B. W. See Powell, D. E.
Spear, C. D. Method of making gamma-alumina fibers, P (6) 154*j*.
Specht, C. H. See Kirk, R. M.
Spector, M. L. See Heinemann, H.
Spell, D. M., Jr., and Rowe, J. D. Stress-relieved seal structure for arcuate fluorescent lamp or the like, P (11) 299*h*.
Spence, G. M. Material ring removal from a rotary kiln, P (3) 77*g*.
Spence, G. M., and Bryan, A. R. Kiln brick, P (9) 240*f*. Kiln brick of portland cement clinker with a fused shell, P (9) 240*g*.
Spencer, D. E., and Peek, S. C., Jr. Aperture fluorescent lamp, P (3) 72*e*.
Spencer, E. G., Lenzo, P. V., and Nassau, K. Elastic wave propagation in lithium niobate, (10) 285*j*.
Spencer, W. J. See Haruta, K.
Spencer, W. J., and Haruta, K. Defects in synthetic quartz, (7) 198*g*.
Spender, M. R. See Selman, G. L.
Spenke, E. See Keller, W.
Sperk, E. See Vohler, O.
Sperry Rand Corp. Gettering means in a vacuum deposition device, P (5) 128*f*.
Speuer, G. See Hrovat, M.
Spicer, T. S. See Utley, R. W.
Spielman, L. S. Tube-firing gas burner assembly, P (4) 108*g*.
Spielmann, W. K. Method and apparatus for producing elongated strip-shaped crystalline semiconductor bodies, P (11) 306*b*.
Spinner, S., and Napolitano, A. Further studies in the annealing of a borosilicate glass, (8) 209*j*.
Spitsyn, B. V. See Sheftal, N. N.
Spitz, J. See Besson, J.
Spohn, E., and Lieber, W. Reactions between calcium carbonate and portland cement—the systems C_3A–$CaCO_3$–H_2O and C_4AF–$CaCO_3$–H_2O, (2) 29*d*.
Spohr, H. See Bredsdorff, P.
Sprague Electric Co. Barium titanium citrate, barium titanate, and processes for producing same, P (4) 104*a*. Capacitor electrode and method, P (7) 192*j*. Capacitor with electrodes of metal coated particles, P (5) 128*j*. Ceramic capacitor, P (6) 158*i*, P (8) 220*a*. Hermetically sealed capacitor, P (10) 278*j*. Method of making a ceramic capacitor, P (6) 159*i*. Mixed metal-ceramic capacitor, P (3) 73*j*. Modified barium titanate ceramic materials and capacitor, P (4) 105*g*. Solid electrolytic capacitor with layer comprising silica on the electrolyte layer, P (6) 161*b*. Tantalum capacitor with glass-to-metal seal and resilient support for terminal, P (6) 161*b*.
Sprang, P. G. See Felten, E. J.
Spraying Systems Co. Apparatus for spray analysis, P (11) 311*b*.
Spreuwenberg, P. B. T. H. See Van Bakel, H. A.
Spriggs, R. M. See Brissette, L. A.
Spring, S. Problems in metal cleaning for porcelain enameling, (8) 208*b*.
Sproul, J. S. See Tidridge, W. A.
Spurny, Z., and Novotny, J. Effect of ionizing radiation on glasses—relation between optical absorption and thermoluminescence of borate glasses, (5) 120*i*.
Squires, A. M. Apparatus and method for conveying dry pulverulent solid in liquid-like state, P (10) 280*e*.
Srivastava, R. C. Fuel oil and oil burning, (2) 46*d*.
Srivastava, S. N. Interaction of colloidal particles with special reference to the role of macromolecules in van der Waals' interaction, (6) 168*f*.
Staatsmann, H. See Trier, W.
Stackpole Carbon Co. Producing dense articles from powdered carbon and other materials, P (7) 189*d*. Silver-refractory metal electrical contact having refractory metal carbide in the marginal layer of its active contact face, P (3) 74*h*.
Stacy, W. O. See Kini, K. A.
Stade, H. See Funk, H.
Stadler, H. L. Etched hillocks in $BaTiO_3$, (2) 50*a*. Forward velocity of 180° ferroelectric domain walls in $BaTiO_3$, (9) 250*c*. Thickness dependence of $BaTiO_3$ switching time, (9) 242*f*.
Stadnyk, B. I. See Gladyshevskii, E. I.
Staffordshire Potteries (Holdings), Ltd. Improved process of pottery production, P (10) 276*a*.
Stahl, D., and Strasser, A. Properties of solid solution uranium-plutonium carbides, B (6) 172*a*.
Stahl, N. See Lindblom, Y.
Stalego, C. J. Apparatus for forming fibers, P (3) 62*h*. Apparatus for forming heat-softenable materials, P (11) 297*e*. Apparatus for forming and processing fibers, P (8) 211*e*. Apparatus for producing fibers from heat-softenable material, P (5) 122*i*. Method and apparatus for forming fibers, P (5) 123*h*. Method and apparatus for forming glass fibers, P (2) 33*h*. Method and apparatus for processing heat-softenable materials, P (9) 236*g*. Method for continuously wrapping formed filaments of a rotor about an internal core, P (7) 183*j*. See Sens, F. T.
Stalego, C. J., and Leaman, H. E. Method for producing curled fibers, P (5) 123*h*.
Stalego, J. P. Glass fiber binder composition containing tall oil pitch, P (6) 140*j*. High temperature resistant borated alkyd resins and their preparation, P (2) 33*d*. Production of [intermeshed] vitreous fiber products, P (4) 98*c*.
Stalnecker, S. G., Jr., and Theobald, P. R. Electroconductive coating patterning, P (6) 159*c*.
Stalter, T. L. See Kemp, H. T., Jr.
Stamicarbon N. V. Method of and apparatus for separating particles of different specific gravity in a jig, P (8) 225*c*.
Stamires, D. N. See Freeman, D. C., Jr.
Stamp, T. B. Lead oxide mills, P (1) 18*g*.
Stamy, R. L. Drop hammer impact tester, P (10) 281*g*.
Stanchi, L. See Gottardi, V.
Stanczyk, M. H., and Feld, I. L. Continuous attrition grinding of coarse kaolin (II) closed-circuit tests, (5) 133*a*.
Standage, A. E., and Turneri, N. Three component system—epoxy resin reinforced with aluminum coated silica fibers, (4) 95*f*.
Standard Oil Co. Apparatus for spherulization of fusible particles, P (4) 96*i*. Calcium aluminate cement composition, P (4) 90*j*. Ceramic molding composition, articles made from same and process for making such articles, P (8) 217*h*. Glass microsphere and fiber filled polyester resin composition, P (4) 96*j*. Method and apparatus for subdividing particulate [catalyst] solids, P (2) 47*h*.
Standart, G. See Novosad, J.
Stanek, J., Sasek, L., and Meissnerova, H. Electrical glass melting, (7) 180*f*. Methods of measuring physicochemical quantities for the modeling of glass melting in electric furnaces, (2) 32*b*.
Stanford Research Institute. Barrier effect insulator, P (10) 277*h*. Method of making diamond, P (5) 117*h*. Two-stable high-resolution electron-actuated resists, P (11) 308*d*.
Stang, J. H. See Wagner, W. A.
Stanish, W. Color index, P (10) 262*a*.
Stanley, N. See Pick, H. H.
Stanton, C. C. Coupling for joining pipe sections of differing diameter, P (5) 122*b*.
Stapel, C. See Bekkering, H. M.
Staph, H. E. Protection of electrical components from damage by arcing or plasma discharges in vacuum systems, (4) 107*h*.
Stapleton, R. E. See Rodriguez, A. R.
Star Porcelain Co. Composite adsorbent filter body, P (5) 127*e*.
Stark, L. T. See Allerton, G. L.
Stark Ceramics, Inc. Metal channels and frames for walls formed of interlocking building blocks, P (5) 124*h*.
Starkey, D. A. Protective clothing, (3) 77*e*.
Starkey, J. Preliminary orienting procedure for single crystals with the Weissenberg camera, (9) 253*e*.
Starnes, W. C. See Kline, R. E.
Startsev, N. E., and Shur, Ya. S. Features in the domain structure of magnesium-manganese ferrites with a rectangular hysteresis loop, (11) 316*j*.
Starzacher, A. Results of hot torsion tests on basic brick, (11) 301*c*. Testing of thermal shock resistance of basic brick by air-quenching at various temperatures, (9) 239*j*.
Stauffer, R. A. See Allen, L. R.
Stauffer Chemical Co. Method of producing nitrides of aluminum and boron, P (9) 240*g*.
Staunton, J. J. J. See Bell, K. R.
Steadman, R. See Shaw, R.
Steadman, R., and Pugh, J. D. Etch pits and dislocations in cronstedtite, (3) 81*g*.
Steadman, R., and Toy, M. Formation of a spinel and a hexagonal ferrite by the thermal transformation of cronstedtite, (7) 199*h*.
Stearns, L. B. Method and means for etching glass and glass reinforced plastics, P (10) 269*g*.
Steatite & Porcelain Products, Ltd. Insulator having semiconductive layers to increase the capacitance thereof, P (6) 159*b*.
Stechemesser, R. Stress-optical investigations of plastic layers, (3) 62*h*.
Stecker, G. See Shea, F. L., Jr.
Steeg, M. G. van der. See Hokkeling, P.
Steele, B. C. H. See Hilton, R. F.
Steele, B. C. H., and Alcock, C. B. Factors influencing the performance of solid oxide electrolytes in high-temperature thermodynamic measurements, (7) 199*c*.
Steele, F. N., and Douglas, R. W. Observations on the absorption of iron in silicate and borate glasses, (3) 61*e*.
Steele, M. C., Ando, K., and Lampert, M. A. Avalanche breakdown double-injection induced negative resistance in semiconductors, (4) 103*f*.
Steele, R. E. See Emmel, D. R.
Steelman, D. M. Systems concept for efficient plant operation, (8) 208*d*.
Steen, W. J. See Hilton, R. F.
Steer, G. C. Apparatus and method for drawing glass tubes, rods, or the like, P (2) 32*i*.
Steetley Refractory Brick Co., Ltd. Method of making metal covered refractory bricks, P (2) 38*e*.
Steeves, R. W. Crucible externally lined with filamentary carbon, P (4) 100*j*. See Baer, C. A.
Stefanov, G., Simeonov, K., and Jamakov (Yamakov), I. Sintering of rutile ceramic in the presence of additives, (9) 255*f*.
Stefanov, S. Blue pigments for ceramic ware, (2) 39*a*. Steam moistening of ceramic bodies, (2) 35*i*.
Stegherr, A. Semiconductive material, semiconductive and thermoelectric devices, P (7) 194*d*.
Steierman, B. L. Joining glass members and encapsulation of small electrical components, P (2) 33*d*.
Stein, A. See Trier, W.
Stein, G. A., and Pelton, E. R. Clay pipe junctures and method, P (7) 185*a*.
Stein, J. L. Divided taper brick, P (3) 70*f*. Hinged refractory brick hanger, P (9) 240*d*.
Stein, L. B., Jr. Electrical coupling device, P (7) 192*g*.
Steinberger, I. T. See Brafman, O.
Steinbock, E. A., Jr. Investment mixer with enlarged mold supporting platform, P (7) 188*e*.
Steiner, C. See Diller, R. E.
Steinfink, H. See Lin, W.; Ramsey, T. H.
Steinhoff, E. Contact behavior of dolomite brick at 1600°C, (7) 186*a*. Experience with fused quartz brick in glass-melting furnaces, (4) 99*c*.
Steinhoff, E., and Patzak, I. Behavior of a siliceous plastic refractory in the hot repair of glass melting furnaces, (2) 36*d*.
Steinitz, R. See Resnick, R.
Steinke, G. Currents in glass tanks—a problem of equilibrium, (9) 233*b*.
Steinmetz, A., Botton, R., and Delgrange, J. P. Iron oxide pigments, P (10) 283*a*.
Stellwag-Carion, H. Rationalization in the refractories industry, (2) 36*g*.
Stengel, R. F. Why Rosenthal is undergoing a complete modernization, (3) 71*i*.
Stenstrom, R. C. See Smith, J. V.
Stepanenko, M. G., and Vilnis, K. K. Intensifying the working of glass tank furnaces with the aid of electric booster heating, (4) 94*a*.
Stephens, A. See Laird, J. S.
Stephens, F. N. See Stephens, J. F.
Stephens, F. N., and McBride, J. R. Apparatus for detecting breaks during molten fiber formation, P (10) 267*g*.
Stephens, J. F., and Stephens, F. N. Apparatus for production of fine glass fibers, P (5) 122*j*. Method and apparatus for forming fibers by spinning fluid blast and rotor, P (5) 123*i*.
Stephenson, D. A. See Gaines, A. M.
Stepina, N. E. See Latsh, V. V.
Sterk, E., and Hochmann, K. New method for distinguishing the different phases of polycrystalline ferrites, (2) 50*f*.
Stern, R. A. See Wade, W. L.
Sterzer, F. Low impedance coupled transmission line and solid state tunnel diode structure, P (11) 306*i*.
Stevens, D. E., Jr. See Veo, L. E.
Stevens, D. S. Apparatus [optical] for analyzing the size and number of particles in suspension, P (11) 311*b*.
Stevens, H. M., and Tucker, W. F. Slim crystalline rod pullers with centering means, P (9) 244*e*.
Stevens, J. P., & Co., Inc. Heat cleaning of fibrous glass fabrics, P (8) 212*c*. Novelty glass fabric, P (10) 269*c*.
Stevens, K. W. H. See Fletcher, J. R.
Stewardson, E. A., and Underwood, J. H. Reflection of soft X rays by polished surfaces of glass and steel, (3) 85*i*.
Stewart, D. A. See Halverstadt, R. D.
Stewart, I. M. Electron microscopy of fractured glass-ceramics, (2) 31*a*.
Stewart, M. M. See Kehl, W. L.
Stewart, R. C. See Bennett, A. I., Jr.; Coleman, J. J.
Stewartson, K. See Catherall, D.
Steyn, J. G. D. See Kriek, H. J. S.
Stichting Reactor Centrum Nederland. Preparation of granular thorium dioxide, P (5) 126*f*.
Stickel, A. See Carson, F. J.
Stickler, R. See Knopp, A. N.
Stickley, C. M. See Townsend, R. L.
Stiebritz, G. BK-pipes—concrete coated pipes, (1) 7*e*.

Stijntjes, T. G. W. See Van Gils, C. L. M.

Stiles, A. B. Mangano-chromia-manganite catalyst composition containing alkali metal and alkaline earth metal manganates, P (4) 100*f*. Method of preparing a catalyst composition consisting of manganese oxide-coated alumina with nickel or cobalt chromites and the product thereof, P (4) 101*g*.

Stiller, H. Interpretation of DTA investigations of titanomagnetites using magnetic and nonmagnetic reference materials, (11) 318*a*.

Stilley, G. W., and Cypher, J. H. Method of tempering glass sheets supported on a bending mold, P (10) 269*e*.

Stinnes, H. Glass forming mold, P (3) 63*i*.

Stirling, H. T. Process for making lightweight aggregate, P (1) 7*h*.

Stirling Sintering Corp. Process for making lightweight aggregate, P (1) 7*h*.

Stock, D. F. See Wishon, B. E.

Stock, D. F., Wishon, B. E., and Pierce, J. A. Refractory brick, P (4) 102*a*.

Stockton, J. Modifying a glassworking lathe to graduate glass tubes, (5) 121*e*.

Stoecker, H. J., Nickel, H., Imoto, S., and Naoumidis, A. System uranium-nitrogen, (9) 239*g*.

Stoeckmann, G. See Eichhorn, R.

Stofel, E. J. See Janowski, K. R.

Stoiber, R. See Schink, N.

Stoicheva, V. Synthesis of dielectric glasses in the system SiO_2–Al_2O_3–CaO–MgO with the addition of modifying oxides (BaO, TiO_2, ZnO), (5) 121*i*.

Stojadinovic, S. Hydration of β-$CaSO_4 \cdot {}^1/_2H_2O$ during the first 7 days, (8) 207*d*.

Stokes, R. J. Thermal-mechanical history and the strength of magnesium oxide single crystals (II) etch pit and electron transmission studies, (2) 53*c*. See Day, R. B.

Stoll, E., Fischer, P., Halg, W., and Maier, G. Redetermination of cation distribution of spinel ($MgAl_2O_4$) by means of neutron diffraction, B (2) 55*i*.

Stoliar, W. P. See Moss, H. I.

Stolnitz, D. See Flatley, D. W.

Stone, G. Gaseous discharge lamp, P (10) 278*i*.

Stone, S. A. Common sense approach to screening and grinding costs (IV), (2) 35*h*.

Stong, G. E. See Smith, G. P.

Stonkus, S., and Viscakas, J. Effect of Se atmosphere partial pressure on the electrical conductivity of CdSe single crystals, (3) 81*h*.

Stookey, S. D. Bone china and method of making it, P (6) 149*d*. Means for controlling the light transmission of a phototropic glass structure, P (8) 212*g*. Method of forming a devitrified glass seal with tungsten or molybdenum, P (10) 269*b*. Method of forming metallic films on glass, P (7) 184*c*. Phase transitions in condensed systems, B (9) 259*e*. Semicrystalline ceramic bodies and method, P (4) 98*d*. Strengthening glass and glass-ceramics by built-in surface compression, B (2) 55*h*. See Olcott, J. S.

Stoops, R. F. Cermet technology, (10) 270*f*.

Stoops, R. F., and Hamme, J. V. Method for stabilizing uranium monocarbide, P (1) 11*f*.

Stoops, R. F., and Mione, A. J. Novel uranium/uranium carbide cermet, B (6) 172*g*.

Stopek, S. See De Vaux, L. H.

Stopora, H. See Pulfrich, H.

Stork, J. Plastometer—a new apparatus for measuring the rheological properties of moldable materials, (3) 76*f*.

Stormont, R. W. See Wald, F.

Storms, E. K. See Bowman, A. L.; Sandenaw, T. A.

Story, M. S. See Adams, I.

Stott, C. K. Flushing cistern and watercloset suite of the double trap type, P (5) 127*g*.

Stott, R. A. See Frank, J. N.

Stowe, R. A. See Mayer, R. P.

Stoy, T. J. Refractory liner brick with tongue and compound groove for forming circular tapered furnace stack constructions, P (11) 303*d*.

Stoyanova, L. See Petkov, P.

Straba Handels-Akt.-Ges. Method of producing hardened bodies from bituminous mixes, P (9) 240*f*.

Strain, R. J., and Tooke, C. C. Intrinsic and extrinsic photomixing in semi-insulating GaAs, (7) 200*c*.

Strasser, A. See Stahl, D.

Strasser, R. G. Goblet with the monogram of the Landgraf Carl von Hessen by Georg Friedrich Killinger, (5) 118*d*.

Stratmann, J. See Kroeger, C.

Strauss, E. L. See Klinger, N.

Strauss, H. L., Jr. Dressing tool for abrasive grinding wheels, P (10) 261*g*.

Strauss, J. Transparent enameling—a critique, (4) 90*a*.

Strauss, K. Changes in tiled heating stoves through the ages, (6) 144*b*.

Stream, R. M. Apparatus for forming an airborne curtain of liquid material, P (2) 32*i*. See Langlois, R. E.; Smock, G. E.

Streatfield, G. R. Precious metals used in decoration of pottery, (8) 219*d*.

Street, R. S. See Rand, M. H.

Strekalovskii, V. N. See Neuimin, A. D.

Strekalovskii, V. N., Bessonov, A. F., Blasov, V. G., and Sidorenko, F. A. Phase transformations in the reduction and oxidation processes of uranium oxides, (11) 318*j*.

Strel'nikova, I. A. See Mirgalovskaya, M. S.

Strelow, F. W. E. Separation of trivalent rare earths plus Sc(III) from Al, Ga, In, Tl, Fe, Ti, U, and other elements by cation-exchange chromatography, (6) 163*c*.

Strel'tsina, M. V. See Totesh, A. S.

Strel'tsov, I. S. See Leshchinskaya, Z. L.

Strickland, E. T., and Amos, H. C. Method and apparatus for producing filaments, P (8) 213*c*.

Stringer, J. Vanadium–oxygen system—a review, (8) 228*b*. See Price, W. R.

Strnad, P. See Hlavac, J.

Strnad, Z. See Hlavac, J.

Strobach, C. G., and Roden, J. S. Glass-coated steel article, P (11) 295*j*.

Strobel, F. Vacuum-tight ceramic-to-metal seals, (9) 242*f*.

Strock, L. W. See Lagos, C. C.

Strong, H. M. See Hanneman, R. E.

Strott, A. J. See Ryshkewitch, E. I.

Stroud, D. E., Jr., Havens, A. B., and Hankinson, K. D. Apparatus for severing a liquid stream, P (6) 149*b*.

Stroud, J. S. Phototropic glass composition, P (8) 213*d*.

Structural Clay Products Institute. External wall panel and wall formed therefrom, P (7) 185*b*.

Strull, G. Plural emitter semiconductor device, P (1) 15*b*.

Strusievici, C. See Lukacs, I.

Strutz, Carl, & Co., Inc. See Carl Strutz & Co., Inc.

Strutz, C. J., Jr. See Rudolph, R. R.

Strutz, F. C. See Rudolph, R. R.

Stuart, K. D. See Schindler, D. R.

Stuart, W. A. Automatic determination of thoria in thoria-urania mixtures, (5) 131*d*.

Stubican, V. S., and Greskovich, C. Jahn-Teller distortion induced by tetrahedral-site Cr^{2+} ions in spinels, (10) 287*a*.

Stubican, V. S., and Menezes, I. de. Grain-boundary reactions in magnesia-chrome refractories—application of the electron probe (I), (11) 301*e*.

Stubican, V. S., and Roy, R. Mechanism of the precipitation of the spinel from MgO–Al_2O_3 solid solutions, (5) 138*a*. New approach to assignment of infrared absorption bands in layer-structure silicates, (3) 84*b*.

Stuchell, R. W. See Luberoff, B. J.

Stuckey, N. Mass production and accuracy in sheet glass cutting, (3) 61*b*.

Stucki, F. F. New wax binder, (9) 247*f*.

Stuetzer, O. M., and Sutton, A. M. Electrostatic separation means, P (7) 196*i*.

Stukan, T. I. Pneumatic-vacuum transport of glass batch and its components, (7) 181*c*. Working cycles for pneumatic-vacuum installations for batch transporting, (6) 161*e*.

Sturges, D. G., and Bartholomew, G. L. Neutron shielding using a composition comprising graphite, boron carbide, and carbonized residue, P (4) 101*a*.

Sturtevant Mill Co. Method and apparatus for separating low micron size particles, P (2) 47*h*. Pin grinding mechanism, P (2) 48*b*. Rotary pulverizer mill with aspirator [classifying] means, P (10) 283*d*.

Stute, J. See Wollank, G.

Stutske, W. A. Method for forming and delivering glass, P (6) 150*a*.

Styunkel', T. B., Mikhaleva, Z. A., and Vershinina, I. A. Conditions for obtaining silver tellurates, (1) 19*i*.

Su, Gouq-Jen. See De Clerck, D. H.

Su, Yao-sin. Titrimetric determination of titanium(III) in magnesia-titania refractories, (3) 69*b*.

Subbarao, E. C., and Harrison, D. E. Arsenate and phosphate phosphors, P (1) 14*f*.

Sudo, T. See Iwamoto, S.

Suehiro, K. See Munekata, E.

Suehiro, Y., Takashima, A., Suzuki, T., and Doi, H. Method of producing uranium dioxide powder, P (11) 302*h*.

Suga, O. See Niwa, S.

Sugasawa, K. Effect of steelmaking factors on the life of ladle brick, (9) 238*d*. Lengthening of the roof life of an open-hearth furnace by gunned refractories and balancing the productivity of the furnace by repairs to its lower part, (7) 186*i*. Plans for prolonging the service life of ladle brick, (7) 187*e*. Results of investigating the effects of mortar impregnated with ^{60}Co as tracer applied around graphite bricks, which are placed beneath ingot molds in top casting, (1) 10*b*. Trial use of plastic refractory in open-hearth furnace regenerator roof, (10) 273*f*.

Sugasawa, K., and Nashiwa, H. Results of using high alumina checker brick at the top of a hot-blast stove, (3) 69*b*.

Sugawara, M., Okagaki, H., and Ikuta, Y. Hollow-cathode discharge lamp for emission of atomic resonance lines, P (6) 159*j*.

Sugimoto, M. See Tanaka, T.

Sugimura, M. See Kubota, B.

Sugishita, N. See Machida, J.

Sugita, K. See Ohba, H.; Wada, K.

Sugita, Y. See Kodera, H.

Sugiura, M., Sano, S., Ishii, E., and Hirai, M. Forsterite porcelain as high frequency insulator (IV) relation between the microstructure and thermal expansion of forsterite porcelain; (V) relation between the microstructure and the electrical and mechanical properties of forsterite porcelain, (8) 219*g*. Sintered mixture of magnesia and beryllia as a high frequency insulator, (11) 305*a*.

Sugiura, T. See Takita, S.

Sugiura, Y. Note on Fe^{3+} ions in spinel structure, (10) 289*a*.

Suito, E. See Matsuda, J.

Suits, J. C. See Shafer, M. W.

Sukatschew, W. Practical method of testing kaolin to determine its suitability for ceramic bodies, (6) 162*d*.

Sukegawa, T., and Nishizawa, Jun-Ichi. Silicon semiconductor device for high frequency and method of its manufacture, P (9) 244*d*.

Sukharevskii, B. Ya., and Gavrish, A. M. Specific features of the polymorphous transformation of cristobalite, (5) 256*c*.

Sukharevskii, B. Ya., and Lysak, S. V. Effect of dislocations on the temperature characteristics of the polymorphous transformation of cristobalite, (9) 249*b*.

Sukhov, A. A. Rational type of checker for regenerators of glass furnaces, (2) 46*f*.

Sukhovei, V. A. See Zakharikov, N. A.

Sulger, O. Use of hollow brick made from fired clay, (2) 36*a*.

Sullivan, P. W. See Shannon, R. F.

Sullivan, R. R. See Walton, J. D., Jr.

Sullivan, W. A., Jr. Suspendable refractory unit, P (5) 127*a*.

Summerson, C. H. Crystal molds in dolomite—their origin and environmental interpretation, (11) 314*f*.

Summitt, R., and Borrelli, N. F. Infrared absorption in single crystal stannic oxide, (5) 137*b*.

Sump, K. R. See Brite, D. W.

Sun, Fan-min. See Cheng, Jie-jian.

Sun, Yui-Lin, and Novikov, G. I. Thermographic and calorimetric study of the system samarium trichloride–potassium chloride, (9) 257*f*.

Sun Oil Co. Apparatus for transporting solids, P (9) 244*f*. Attrition resistant siliceous catalysts and method of preparation thereof, P (4) 100*d*.

Sunbeam Engineering Corp. Furnace roof, P (7) 188*a*.

Sundquist, L. A. See Barr, H. N.

Surckla, P. P. See Pearch, L. E.

Surmeian, S. N. See Lewis, H. R.

Surovitskaya, G. I. See Romanov, B. E.

Surplice, N. A. Electrical conductivity of calcium and strontium oxides, (5) 135*d*.

Surver, R. L. See Sowman, H. G.

Sutarno, L. C. See Castelliz and Sutarno, L.

Sutcliffe, Speakman & Co., Ltd. Process and apparatus for removing brick, etc., from a pressing table, P (7) 194*h*.

Sutherland, H. H. See MacEwan, D. M. C.

Sutton, A. M. See Stuetzer, O. M.

Sutton, W. H. Whisker composite materials—a prospectus for the aerospace designer, (11) 295*e*. See McCreight, L. R.

Suzuki, H. Relation between sintering and creep of refractories, (8) 216*g*. See Iwata, T.; Tagai, H.

Suzuki, K. See Matsumoto, Y.; Nakazumi, Y.; Takeuchi, S.

Suzuki, K., and Hiraiwa, O. Proceedings of the Pouring Pit Refractory Subcommittee Meeting (IV) comparative study of the results of erosion tests with the submitted slag by means of a crucible and a cone, (4) 99*h*. Relations between the physical and chemical properties of runner brick and the damage done to them, (9) 239*e*. Results of thermal shock test and thermal conductivity measurements to determine the quality of stopper heads, (8) 216*i*.

Suzuki, T. Electron distribution in Cu_2O crystal, (4) 111*d*. X-ray study on the binding properties of Cu_2O and Ag_2O crystals, (10) 292*a*. See Ikushima, A.; Suehiro, Y.

Suzuki, Y., and Asada, E. Crystal distortion of FeO on cooling past its Neel temperature, (10) 284*a*.

Svec, J. J. Complete line produced at Cia. A. P. Green, (4) 99*b*. El Anfora produces 40 tons of whiteware daily, (4) 102*f*. Fabrica Nacional de Vidrio melts 300 tons of glass per day, (4) 93*h*. Ladrillera Monterrey S. A. produces 5.5 million tile per month, (4) 98*h*. Major renovation heavy at Cia Mexicana de Tubos de Albanal S. A., (4) 98*i*. Millions of spark plugs for Mexico, (4) 102*h*. New clay pipe plant for Midwest, (8) 214*f*. Newest Florida brick plant now in operation, (4) 98*i*. Owens-Illinois, Inc., builds first computer operated container plant, (8) 210*i*. Preheating clay products increases kiln output 20%, (4) 98*c*. Refresher for enamelers, (8) 208*c*. 1200 employed at Monterrey porcelain enamel plant, (4) 91*f*. Vidriera Mexico S. A. enlarges facilities, (4) 96*b*. Vidrio Plano de Mexico to expand by 60%, (4) 96*b*.

Svec, J. J., and Freevol, R. H. Design of high temperature fans, (8) 224*c*.

Svehla, G., and Pall, A. New chemical analysis methods for ceramic materials determination, (2) 44*d*.

Svejda, H. Silicate engineering education at the TGM (Technologisches Gewerbemuseum, Vienna), (2) 54*j*. Staatliche Versuchsanstalt fuer Silikattechnik, (6) 171*e*.

Svekolkina, L. G. See Volzhenskii, D. S.

Svenska Tendsticks Aktiebolaget. Apparatus for the measurement of physical quantities, P (3) 77*a*.

Svensson, A. N. See Fahlstrom, P. A. H. H.

Svet, A. L. See Serdyuk, S. M.

Sviridova, A. I. Optical properties and structure of zirconium dioxide films, (2) 51*b*.

Swalin, R. A. See Chen, W. K.

Swanson, C. E. See Hamelink, W. B.

Sweeney, W. E. See Birks, L. S.

Sweet, T. R. See Morie, G. P.

Swenson, E. G. See Kamimura, K.

Swicker, V. C. Glass, (2) 31*d*. Glass—problems of surface cords, (2) 31*e*.

Swift, H. R. See Morgan, J. E.; O'Connell, T. B.

Swift & Co. Adhesive patching composition, P (8) 207*d*.

Swiggard, E. M., and Clabaugh, W. S. Preparation of barium titanate semiconductors containing controlled amounts of neodymium, (10) 277*h*.
Swiss Aluminium, Ltd. Electrolytic furnace with lined cathode pots for the production of aluminum, P (8) 217*j*.
Swoboda, T. J. See Gilbert, W. W.
Sybeldon, J. A. Image tube having external semiconductive layer on target of wires in glass matrix, P (3) 73*f*.
Sykes, R. F. R. Preparation of glass grain samples for durability tests, (3) 61*j*.
Sylvania Electric Products, Inc. Aperture fluorescent lamp, P (3) 72*e*. Cathode base structure, P (6) 158*g*. Electric discharge device having heat conserving shields and [glass] sleeve, P (7) 192*e*. Electric discharge lamp with integral pressure regulator, P (4) 104*e*. Electric lamp with fuse, P (11) 305*i*. Electroluminescent device, P (5) 128*c*, P (10) 278*f*. Electroluminescent instrument lighting, P (2) 41*h*. Encapsulated thermostatic switch having a heater disposed in the stem, P (11) 306*a*. High conduction semiconductor diode, P (4) 104*j*. Incandescent lamp containing iodine, oxygen, and inert gas, P (6) 159*a*. Leakage inhibiting supporting structure, P (3) 73*h*. Method of preparing electroluminescent devices, P (3) 73*g*. Method of supplying heat of fusion to glass-to-glass seal, P (1) 7*a*. Process of aging tubes, P (8) 221*g*. Process for increasing light emission, stabilization, and rejuvenation of electroluminescent lamps and phosphors, P (2) 42*d*. Read-out device having bonding material between a face panel and a cover panel, P (11) 307*a*. Thermal boundary construction, P (9) 241*d*.
Symons, L. G. Bowl liner for gyratory crusher, P (5) 133*c*.
Symowa, W., Brajkowa, P., and Pawlowa, I. Glass fibers of improved chemical composition for the production of reinforced roofing paper, (11) 296*g*.
Syritskaya, Z. M. See Yudin, N. A.
Syritskaya, Z. M., Bil'tyukova, E. P., and Deulina, Z. N. Procedure for the chemical analysis of phosphate glasses, (1) 5*c*.
Syritskaya, Z. M., and Ivanova, V. M. Development of glass composition stable to glucose and ascorbic acid, (6) 147*e*.
Syritskaya, Z. M., and Mel'nikova, M. A. Study of the fields of glass formation in the system CeO_2–Al_2O_3–P_2O_5 (I), (6) 149*b*. Study of the physicochemical properties of glasses in the system CeO–Al_2O_3–P_2O_5—density and refractive index, (10) 266*f*.
Syritskaya, Z. M., and Sergeeva, G. N. Study of the influence of certain metaphosphates on the properties of glass in the system La_2O_3–SiO_2–P_2O_5 (II), (8) 211*f*.
Syritskaya, Z. M., and Zorina, G. V. Regions of glass formation in the systems R_2O–PbO (Bi_2O_3)–P_2O_5, (8) 210*a*.
Sysoev, L. A. See Bidnaya, D. S.
Sysoev, L. A., Obukhovskii, Ya. A., and Bidnaya, D. S. Crystallization of cadmium sulfide from solutions in cadmium halides, B (11) 320*c*.
Systems Research Laboratories, Inc. Ceramic diode pressure transducer and system, P (6) 158*j*.
Szabo, A., and Igarashi, T. Effect of ground state ESR saturation on ruby laser output at 90°K, (11) 316*b*.
Szabo, Z. Factors affecting the reactivity of semiconductive oxides during spinel formation processes, (11) 316*e*.
Szaj, A. P. See Gasparac, R. J.
Szanto, I. S. Recent developments of line profile analysis used in X-ray metallography, (8) 223*e*.
Szekely, J. Effect of variable temperature on unsteady-state diffusion in metals and slags, (3) 67*b*.
Szell, C. See Prince, F. J.
Szkudlapski, A. H. Etching of silicon and germanium, P (11) 306*c*.
Szuk, G. Setting and hardening of hydraulic materials (VI) long-time conductimetric study of the hardening process of building materials on cement base, (5) 118*g*.

Tabata, K. See Hayashi, T.
Tabikh, A. A. Quantitative analysis by X-ray emission spectrography, (2) 45*f*.
Tachibana, S., Nakamura, M., and Koide, K. Mold for titanium casting (V) molding with carbon powder, (6) 153*d*.
Tachiki, M. See Date, M.
Taesler, W. See Bruegger, W.
Taesler, W., and Bruegger, W. Modern electric tunnel kiln for high temperatures, (2) 46*e*.
Tagai, H., Iwai, S., and Iseki, T. Fundamental study of the reactions between magnesia and iron oxide, (9) 238*i*.
Tagai, H., Iwai, S., Iseki, T., Saho, M., and Mori, T. Fundamental study of the reaction between magnesia and manganese and chromium oxides, (10) 271*c*.
Tagai, H., and Suzuki, H. Test method for magnesia clinker, (10) 273*a*.
Tagano, H. Ceramic sealed window, P (1) 6*f*.
Tailor, J. P. Apparatus and method for gas contact spray drying, P (11) 308*j*.
Takabayashi, H. Relation between the size of magnesia clinker in basic brick used in an open-hearth furnace roof and the life of the roof, (7) 187*b*.
Takada, Y. See Imoto, S.
Takagi, M., and Lang, A. R. X-ray Bragg reflection, spike reflection, and ultraviolet absorption topography of diamonds, (7) 203*g*.
Takagi, S. See Koda, Y.
Takagi, T., Ueda, H., Tomono, M., and Kimura, H. Method of producing semiconductor devices, P (6) 160*d*.
Takahashi, A. See Maeno, M.
Takahashi, H. Note on the theory of barium titanate, (10) 289*a*.
Takahashi, O., and Kishida, M. Changes in type of converter masonry and life of converter, (10) 270*f*.
Takahashi, T. See Bassett, W. A.
Takahashi, T., and Freise, E. J. Determination of the slip systems in single crystals of tungsten monocarbide, (1) 20*g*.
Takahashi, Y. See Atoda, T.; Kumai, H.; Watanabe, H.
Takama, E. Mn–Zn–Fe ferrite having rectangular hysteresis loop, (6) 158*h*.
Takano, S. See Doi, M.
Takashi, T., and Kataoka, M. Method of measuring the afterexpansion or aftercontraction by volume, (8) 216*a*.
Takashima, A. See Suehiro, Y.
Takashima, M. See Shiraishi, M.
Takashima, Y. See Kameyama, A.
Takayanagi, T., Kosaka, M., and Minowa, S. Silicon nitride as accelerator for gelation of silicic acid sol in lost wax process, (6) 153*f*.
Takebayashi, H. Comparative study on the use of sleeves produced by various brickmakers, (1) 8*f*. Comparison of the results of using basic bricks of 97% MgO and 97% MgO clinker, (8) 215*a*. Method of laying ladle bottom brick and life of the bottom, (3) 68*i*.
Takemoto, S. Temperature dependence of the line width of ferrimagnetic resonance in polycrystalline nickel cadmium ferrite, (4) 113*f*.
Takeuchi, H., and Abe, K. Tungsten base alloys with low thermal expansion coefficient (II) mechanical properties of sintered W–Ni–Fe alloys, (11) 305*i*.
Takeuchi, H., Miyazaki, T., and Abe, K. Tungsten base alloys with low thermal expansion coefficient (I) sintering of W–Ni alloys and their properties, (11) 305*h*.
Takeuchi, S., and Suzuki, K. Statistico-thermodynamical study of the equilibrium between hydrogen gas and plutonium dihydride phase, B (6) 175*f*.
Takeuchi, T. See Miwa, T.
Takeuchi, T., and Ishii, D. Neutron-activation analysis of impurities in gelatin and alumina, (9) 245*f*.
Takeya, Y., Hirano, M., and Hara, N. Method of manufacturing sintered materials, P (10) 274*h*.
Takita, S., Goto, F., Sugiura, T., and Kambara, Y. High aluminous nozzle for high manganese steel, (1) 9*d*.
Takuma, H., and Shimizu, F. Semicontinuous wave generation in ruby optical masers, (10) 277*j*.
Talapatra, S. K., and Sen, R. K. Determination of elastic constants of monoclinic crystals from study of diffuse X-ray reflections, (7) 198*i*.
Talash, A. W., and Crawford, P. B. Rock properties computed from random pore size distribution, (4) 107*j*.
Talcott, R. C. Electron tube comprising beryllium oxide ceramic, P (4) 104*f*. See Meacham, D. D.
Tallan, N. M., and Vest, R. W. Electrical properties and defect structure of Y_2O_3, (9) 249*h*.
Talley, C. P. Method of producing refractory monocrystalline boron structures, P (4) 101*i*.
Talsma, H. Refractory product and process, P (8) 218*d*.
Talv, H. Method and apparatus for producing unwoven fabric, P (11) 298*h*.
Tamaru, S. See Moriya, T.
Tamas, F. (editor). Proceedings of the Seventh Conference on the Silicate Industry, Budapest, June 1963, B (2) 56*b*.
Tamosiunas, L. Chemical composition and practical importance of upper-Permian sulfate deposits in Lithuania, (11) 314*g*.
Tamura, H. Results of the experimental use of a siliceous material for cupola lining repairs, (1) 10*b*.
Tanaka, H. See Hayami, R.; Tanigawa, H.
Tanaka, H., Murakami, K., Monna, I., and Karaki, T. Influence of chemicals on the setting of cement (I) calorimetric studies on the hydration of $3CaO·Al_2O_3$, (2) 28*j*.
Tanaka, M. See Ohba, H.
Tanaka, M., and Minami, T. Infrared absorption band near 12.51μ of arsenic-sulfur glasses, (7) 180*d*. Relation of composition and density of arsenic-sulfur glasses, (7) 181*e*.
Tanaka, T. Cement kiln and refractories (I), (9) 237*j*; (II), (10) 270*f*. See Aoki, Y.
Tanaka, T., and Sugimoto, M. Thermal decomposition of gypsum, (4) 90*i*.
Tanaka, Y. See Miyamoto, O.
Tananaev, I. V. See Seifer, G. B.
Tananaeva, O. I. See Zlomanov, V. P.
Tanemura, F. See Ohta, Z.
Tanenbaum, M. New combinations of physical phenomena in device design, B (9) 259*g*.
Tanguy, M. See Boirat, M.
Tanigawa, H., and Tanaka, H. Process for manufacturing stabilized ceramiclike products from glass by microscopic crystallization, P (4) 98*a*.
Taniguchi, T. See Otsuki, T.
Tanimoto, S. See Nakamura, H.
Tanke, E. Yellow [inorganic] pigment and method of preparation, P (11) 313*b*.
Tanner, D. W. See Gardner, R. F. G.
Tarcza, W. H. See Griest, E. M.; Pratt, C. R., Jr.
Tariton, J. W., and Johnson, T. Method for curing concrete products, P (5) 119*c*.
Tarte, P. Infrared study of the dicalcium ferrite $2CaO·Fe_2O_3$ and of the solid solutions $2CaO·(Al,Fe)_2O_3$, (2) 50*b*.
Tarunin, A. A. See Bezpalov, K. M.
Tas, R. See Fournier, R. F.
Tasaki, A. See Shiratori, K.
Tasaki, A., and Iida, S. Experimental studies on the parasitic ferromagnetism of α-Fe_2O_3, (10) 286*c*. Magnetic properties of synthetic single crystals of α-Fe_2O_3, (4) 103*j*.
Tasaki, J. Preparation of magnetic ferrite by simultaneous precipitation (II) simultaneous precipitation from mixed solution of ferrous and ferric ions, (9) 253*f*.
Tasaki, J., and Ito, T. Preparation of magnetic ferrite by simultaneous precipitation (V) washing of precipitates; (VI) precipitation from mixed solution containing Zn^{2+}, Fe^{2+}, and Fe^{3+}, (9) 253*g*.
Tasaki, J., and Izushi, T. Preparation of magnetic ferrite by simultaneous precipitation (III) simultaneous precipitation from mixed solution of the divalent metallic ion instead of ferrous ion and ferric ion; (IV) formation of ferrite solid solution by simultaneous precipitation, (9) 253*g*.
Tasaki, J., Izushi, T., and Kajima, K. Preparation of magnetic ferrite by simultaneous precipitation (I) ferrite formation of precipitate from mixed solution of divalent metallic and ferric ions, (9) 253*f*.
Tasi, I. New ground enamels for sheet iron, (2) 30*g*.
Tatnall, R. F. Discussion of "Decay products of radium in ceramics and their interaction with matter," (1) 12*i*.
Tatro, G. H. Mechanism for handling glass containers, P (8) 212*h*.
Tatsak, J. E. Turnover device, P (6) 151*b*.
Tauber, A., and Kohn, J. A. Orthopyroxene and clinopyroxene polymorphs of $CoGeO_3$, (1) 23*i*.
Tauber, E. Basalt makes inexpensive stoneware and architectural shapes, (8) 214*d*.
Tauchi, S. Diffusion of impurities in the semiconductor melt (I), (11) 304*i*. See Kodera, H.
Taurone, D. T. "Pencil edging" plate and sheet glass, (2) 32*e*.
Tawara, Y. Relaxation loss in ferrites as a function of ferrous ion content, (4) 104*d*.
Taylor, A. M., and Roy, R. Zeolite studies (IV) Na–P zeolites and the ion-exchanged derivatives of tetragonal Na–P, (4) 114*e*.
Taylor, B. L., Milner, G. W. C., Birks, F. T., and Prior, H. A. Determination of minor constituents and contaminants in actinide carbide ceramics and cermets, B (6) 172*i*.
Taylor, H. A., and Lloyd, J. E. Processing of fissile and fertile material for nuclear reactors, P (7) 189*c*.
Taylor, H. D. Injection molding of intricate ceramic shapes, (10) 277*a*.
Taylor, J. K. See Maienthal, E. J.
Taylor, K. M. Refractory bodies and method of making same, P (7) 189*h*.
Taylor, K. M., McMurtry, C. H., and Andersen, J. C. Sintering characteristics of UC and (U,Pu)C with and without small additions of nickel, B (6) 172*d*.
Taylor, R. Thermal conductivity of pyrolytic graphite, (7) 203*c*.
Taylor, Smith & Taylor Co. Multicolor stamping machine, P (7) 191*c*.
Tazaki, S. See Miyatake, K.
Tchoubar, C., and Oberlin, A. Study of the alteration of albite by water containing dissolved CO_2, (8) 227*e*.
Teago, A. C. Mechanical handling apparatus, P (3) 65*d*.
Teague, E. D. Flame spraying as a method of forming bodies, (5) 130*e*.
Technicon Instruments Corp. Apparatus for treatment of solids for analysis, P (3) 77*a*. Method and apparatus for sequentially performing analyses on a plurality of fluid samples, P (6) 163*b*.
Teeter, R. M., and Doty, W. R. Glass vacuum seal to operate at high temperatures, (10) 281*b*.
Teferra, A. See Wiseman, G.
Teich, M. C. See Schuster, D. M.
Teichner, S. J. See Long, J.
Teilps, B. Successful production of tile by hot preparation, (11) 304*e*.
Tektronix, Inc. Electron beam display device, P (1) 14*j*. Lead-in seal for evacuated envelope of an electron discharge device [CRT] for connecting electrodes located within said envelope to a voltage source positioned outside said envelope, P (11) 306*i*.
Telefunken Akt.-Ges. Metallizing sintered alumina ceramic bodies, P (6) 154*j*. Method of measuring the electrical properties of a semiconductor crystal, viz., the specific resistance and the life span of the charge carriers of a high-ohmic crystal, P (2) 42*c*.
Telefunken Patentverwertungs-G.m.b.H. Heat sink for a ferrite material employing metal oxides as the dielectric material, P (7) 193*c*. Method of marking semiconductor crystals, P (10) 279*b*.
Temescal Metallurgical Corp. Method of forming carbon vapor barrier, P (4) 101*c*.

Temesi, S. Effect of undercooling and of the MgO and Al_2O_3 contents on the rate of crystal growth in blast-furnace slags, (6) 167*f*.
Tenisheva, T. F. See Lazarev, A. N.
Tenner, A. J. See Conley, K. H.
Tennery, V. J. Dielectric properties and phase transitions of ferroelectric sodium-strontium niobates, (8) 219*i*. High-temperature phase transitions in $PbZrO_3$, (10) 286*f*.
Tensmeyer, L. G. See Kiffer, A. D.
Tepper, F., Mausteller, J. W., Luft, L., and Kabi, S. K. Preparation of metal borides, P (9) 241*c*.
Tera, F. See Ruch, R. R.
Teranishi, S. See Wade, W. H.
Teranishi, T. See Ohnishi, H.
Terao, N. Structures of niobium oxides, (10) 290*h*.
Terman, V. B. See Borisov, B. I.; Solinov, F. G.
Ter-Zakharyan, S. M. See Manvelyan, M. G.
Teti, J., Sr. See Siegle, J. C.
Tevebaugh, A. D. See Petkus, E. J.
Tews, H. A. Metal fabrication problems and solutions, (4) 91*i*.
Texaco Experimental, Inc. Method of producing refractory monocrystalline boron structures, P (4) 101*i*.
Texas Instruments, Inc. Aluminum-germanium contact, P (3) 72*d*. Container closure device, P (1) 14*h*. Diffusion method, P (2) 41*c*. Gallium arsenide body containing copper, P (9) 243*f*. Glass-encased semiconductor, P (11) 306*g*. Glass enclosed carbon-film resistor, P (7) 193*b*. Gold-germanium eutectic alloy for contact and alloy medium on semiconductor devices, P (6) 159*h*. High performance photoresistor, P (1) 14*c*. Method of forming a ρn junction, P (9) 243*j*. Method for forming ρn junctions in indium antimonide with special application to infrared detection, P (2) 42*a*. Method of making miniaturized electronic circuits, P (9) 243*j*. Method of manufacturing a capacitor by reactive sputtering of tantalum oxide onto a silicon substrate, P (9) 243*a*. Orbital-spin crystal pulling, P (4) 106*a*. Production of dislocation-free silicon single crystals, P (11) 307*i*. Pyrolytic deposition of protective coatings of semiconductor surfaces, P (6) 160*d*. Resistivity-measuring device including solid inductive sensor, P (5) 129*h*. Semiconductor junction passivation, P (6) 160*i*. Semiconductor networks, P (2) 42*i*. Transistors and the fabrication thereof, P (9) 244*d*.
Textron, Inc., and American Optical Co. Lens blocks [metallic alloy], P (11) 298*c*.
Thatcher Glass Mfg. Co., Inc. Article orienting apparatus, P (2) 33*b*.
Theobald, P. R. See Stalnecker, S. G., Jr.
Thermal Syndicate, Ltd. Method of fine annealing transparent vitreous silica, P (4) 97*a*. Method of tempering by heat treating vitreous silica, P (4) 97*i*. Methods for the production of vitreous silica, P (11) 299*g*.
Thermo-Couple Products Co., Inc. Thermocouple connector, P (4) 108*b*.
Thevenot, G. Process for treating vermiculite and its use as thermal insulation compactant, P (10) 283*a*.
Thiele, W. Dust measurements with the konimeter, (10) 280*i*.
Thielepape, W. See Weiss, A.
Thiemann, H. Liebfriede Bernstiel—studio with tradition, (1) 1*j*.
Thies, G. Fundamentals of temperature control in small container glass tanks, (7) 180*b*.
Thoburn, W. J. See Matsushima, T.
Thom, C. Method of concentrating fluorspar ores [by froth flotation], P (1) 18*h*.
Thom, R. See Eick, H.
Thomas, A. G. See Smith, G. V.
Thomas, D. B. Furnace for thermocouple calibrations to 2200°C, (9) 245*h*.
Thomas, D. L. Method of heat treating glass sheets, P (3) 64*c*.
Thomas, E. A. Bathtub construction, P (7) 179*c*.
Thomas, G. Kikuchi electron-diffraction and dark-field techniques in electron-microscopy studies of phase transformations, (1) 16*f*.
Thomas, G., and Wang, S. Spin-wave excitation of magnetoacoustic modes and the beating of these modes in yttrium iron garnet, (10) 290*e*.
Thomas, J., Jr., Weston, N. E., and O'Connor, T. E. Turbostratic boron nitride—thermal transformation to ordered-layer-lattice boron nitride, (8) 228*d*.
Thomas, J. M., and Hughes, E. E. G. Localized oxidation rates on graphite surfaces by optical microscopy, (4) 112*d*.
Thomas, J. M., and Renshaw, G. D. Dislocations in calcite and some of their chemical consequences, (3) 81*b*.
Thomas, P. B. See Wood, W. G. E.
Thomas, R. L. See Leary, J. A.
Thomas, W. J., Sr. Apparatus for manufacturing a refractory brick, P (9) 239*h*. Refractory bricks, P (6) 155*d*.
Thomasson, G. I. See Holcomb, R. H.
Thompson, A. C. See Mindick, M.
Thompson, B. A. See Borchardt, H. J.
Thompson, C. E., and Gladrow, E. M. Porous carbon electrode preparation, P (1) 12*a*.
Thompson, C. E., Jr. Method of upgrading sand, P (4) 101*j*.
Thompson, C. W. See Bebbington, P. J.
Thompson, H. I., Fiber Glass Co. Method for preparing vitreous silica fibers, P (10) 269*j*.
Thompson, J. B. See Riviere, J. C.
Thompson, J. M. See Kumagai, H. Y.
Thompson, R. Borides—Their Chemistry and Applications, B (11) 319*e*.
Thompson, R. M. See Lang, W. B.
Thomsen, J. S. See Wilson, A. J. C.
Thomsen, S. M. See Yocom, P. N.
Thomson, J., Jr. See Gallagher, P. K.
Thomson, J. J. See Faulkner, E. A.
Thomson, M. G. See Musschoot, A.
Thomson, R. D. See O'Neill, B. J., Jr.
Thorington, L. Reinforced envelope for light source and method of making, P (3) 64*i*.
Thorley, T. Practical aspects of vacuum leak detection and location, (3) 76*g*.
Thorn, J. D., Rodwell, W., and Jobson, D. A. Moderator structures for nuclear reactors, P (9) 240*i*.
Thorn, R. J. See Ackermann, R. J.; Cater, E. D.
Thorn Electrical Industries, Ltd. Electroluminescent lamp with a dielectric reflective material, P (2) 41*i*. Titanium and tin activated magnesium borate luminescent material, P (4) 106*f*.
Thorne, D. Method of fabricating semiconductor devices, P (3) 73*j*.
Thornton, C. G. Method for improving the electrical characteristics of germanium semiconductor devices, P (4) 105*g*.
Thornton, H. R. See Burroughs, J. E.; Howeth, M. S.
Thorpe, T., Harrison, J. W., Riviere, J. C., and Adam, J. (UZr)C for thermionic converters, B (6) 172*g*.
Thrower, P. A. See Reynolds, W. N.
Thu, Tien-min. See Chang, Sheng-yuan.
Thun, R. E., and Maddocks, F. S. Capacitors and process for making same, P (11) 305*a*.
Thurston, R. N., McSkimin, H. J., and Andreatch, P., Jr. Third-order elastic coefficients of quartz, (5) 141*j*.
Thuy, J., and Krauss, H. Method of measuring the electrical properties of a semiconductor crystal, viz., the specific resistance and the life span of the charge carriers of a high-ohmic crystal, P (2) 42*c*.
T.I. (Group Services), Ltd. Method for the analysis of X-rays from an electron probe device, P (9) 246*d*.
Tice, W. K. See Hulse, C. O.
Tichane, R. M. Initial stages of the weathering process on a soda-lime glass surface, (5) 120*i*.
Tidridge, W. A., Goldstein, D., and Sproul, J. S. Carbon-containing refractories, P (10) 273*b*.
Tiede, R. L. Devitrifying a glass about glass fibers on a conductor, P (11) 298*a*. Glass fiber product, P (8) 212*j*. Method of making curly composite fibers, P (9) 236*b*.
Tielrooy, H. See Gie, O. T.
Tiemann, J. J. Small [<200 A] ρn-junction tunnel-diode semiconductor, P (5) 130*c*.
Tien, H. Ti. Ion exchange between alkali metal cations and sodium aluminosilicate gel at 276°, 298°, and 319°K, (10) 287*j*.
Tien, Tseng-ying, and Carlson, W. G. Piezoelectric ceramic composition of lead titanate and 0.1 to 5% (mole) calcium fluoride, P (7) 194*a*.
Tietjen, J. J., and Weisberg, L. R. Electron mobility in $GaAs_{1-x}P_x$ alloys, (10) 285*h*.
Tijoux, P. Device for heating continuous furnaces with vertical gas tubes, P (9) 246*h*.
Tile Council of America, Inc. Ceramic products, P (6) 157*c*. Ceramic tile, P (1) 13*d*. Construction material, P (1) 13*a*. Hydraulic cement mortar compositions, P (6) 144*i*.
Tilleux, E. W. See Mezaki, R.
Tillmann, P., Kulling, A., and Brombach, H. Apparatus for the agglomeration and separation of finely divided titanium dioxide from its gaseous vehicle, P (8) 225*j*.
Tilloca, G. See Perez y Jorba, M.
Tilly, G. P. See Fraser, H.
Timashev, V. V. See Butt, Yu. M.
Timmer, W. F., and Curry, N. A. Coated abrasives, P (10) 261*f*.
Timmerman, L. See Coekelbergs, R.
Timmermans, F. J. H. See Seldenrath, T. R.
Timms, P. L. See Bull, G. H.; Wood, A. A. R.
Timofeeva, V. A., and Bychkov, V. Z. Growth of potassium niobate crystals on seeds from a potash melt, B (11) 320*b*.
Ting, Chao-rung. See Hu, Yung-pu.
Ting, Chao-rung, and Hu, Yung-pu. Investigation of the determination of SO_3 in gypsum and portland cement by the static-ion exchange method (II) determining SO_3 in portland cement, (4) 90*h*.
Tinker, C. D. Lightweight aggregate and process of making it, P (2) 36*a*.
Tinker, D. Preheater, (2) 46*f*.
Tisdale, N. F., Jr. Exothermic side board suspension, P (9) 240*a*.
Tisinai, G. F. See Huber, W. R.
Titangesellschaft m.b.H. Apparatus for the agglomeration and separation of finely divided titanium dioxide from its gaseous vehicle, P (8) 225*j*.
Titkov, N. I., Petrov, V. P., and Neretina, A. Ya. Mineral Formation and Structure in Electrochemical Induration of Weak Rocks, B (9) 258*d*.
Tjok, P. B. See Burwell, R. L., Jr.
Tkscheva, G. S. See Ugai, Ya. A.
Tkotz, G. See Konopicky, K.
Tober, H. Red coloring of glass with silver compounds, (4) 95*c*.
Tobia, S. K., and Milad, N. E. Adsorption of phosphate ions by some Egyptian clays, (6) 165*a*.
Tobin, J. M. See Adelsberg, L. M.
Tobisawa, S. See Nomura, Y.
Tocci-Guilbert, B. Foamed polyurethane abrasive wheels, P (8) 205*h*.
Todorova, R. See Babachev, G.
Toelg, G. See Geilmann, W.
Tokarev, P. G. Production of heat-resistant glass pipe, (10) 266*a*.
Tokareva, M. V., and Rudenko, V. K. Reciprocal system of the nitrates and chlorides of lithium and barium, (9) 254*c*.
Tokyo Shibaura Electric Co., Ltd. Annular fluorescent lamps, P (11) 297*c*. Apparatus for blowing glass bulbs, P (3) 62*f*.
Tolar, N. J. See Johnson, H. B.
Toledano, P. Study of the borates of potassium and rubidium, (2) 52*i*.
Tolmacheva, T. A. See Shchukarev, S. A.
Tolmacheva, Z. I., and Eremenko, V. N. Relation between some properties of carbides and nitrides of the transition metals and their electronic structure, (9) 254*g*.
Tolutis, V. See Bertulis, K.; Deksnys, A.
Tolutis, V., and Jasutis, V. Effect of substrate temperature on the macro- and microstructure of thin CdTe films, (11) 316*g*.
Tolutis, V., and Simulyte, E. Electrical properties of thin cadmium telluride film contacts with metals of groups I, III, V, and VIII and thin film ρn junctions, (3) 81*d*. Investigation of thin cadmium telluride films with groups I and III impurities (II) cadmium telluride films with copper impurities, (6) 158*c*.
Tolutis, V., Simulyte, E., and Jasutis, V. Investigation of thin cadmium telluride films with groups I and III impurities (I) dependence of the structure of thin cadmium telluride films on copper concentration and base temperature, (3) 83*a*.
Tomakov, P. P. See Petrov, V. P.
Tomalin, D. S. See Hagel, W. C.
Tomassi, J. J., Jr. See Gort, W. J.
Tomaszewski, L. See Litwin, J.
Tomb, W. H., and Zine, A. R., Jr. Pipe coupling, P (4) 98*a*.
Tombrel, F. Effect of boron on the structure and mechanical properties of pyrocarbon at high temperatures, (11) 301*c*.
Tombs, N. C. See Comer, J. J.
Tomida, Y. See Funasaka, W.
Tominaga, H. See Imamura, H.
Tomita, K. See Miyazawa, K.
Tomita, Y., and Ariga, K. Process for the production of ladle bricks, P (8) 218*h*.
Tomkeieff, S. I. See Battey, M. H.
Tomkins, D. E. Method of firing a tunnel kiln, P (11) 311*i*.
Tomono, M. See Takagi, T.
Tomova, E. Production and properties of ceramics with high specific inductive capacitance, (2) 40*g*.
Tooke, C. C. See Strain, R. J.
Toperczer, J. See Lengyel, B.
Topsoe, H. F. A. See Wargons Aktiebolag.
Toptygin, D. Ya. Interaction of pentachlorides of niobium and tantalum with the chlorides of lithium and copper, (10) 287*c*.
Torkar, K., Krischner, H., and Moser, H. Phase diagram of PbO–Al_2O_3, (9) 252*i*.
Torkar, K., Oel, H. J., and Illigen, A. Self-diffusion and sintering kinetics of vanadium carbide, (9) 255*g*.
Torlin, F. I. Continuous line for breaking, severing, and packaging [sheet] glass, (4) 92*a*.
Tornati, M. See Bonnetti, G.
Torok, J. J. Glass pressing apparatus, P (9) 236*b*.
Toropov, N. A. See Boikova, A. I.; Lazarev, A. N.
Toropov, N. A., Fedorov, N. F., and Shevyakov, A. M. Infrared absorption spectra of the orthosilicates of some divalent elements, (10) 286*j*. Infrared absorption spectra of polymorphic modifications of dicalcium silicate, (1) 22*j*.
Toropov, N. A., and Grebenshchikov, R. G. Devitrification of bottle glass, (9) 233*d*.
Toropov, N. A., and Vasil'eva, V. A. Phase diagram of the binary system of the oxides of scandium and silicon, (5) 139*g*.
Torrey, F. J. Feeding and conveying ceramic materials by vibratory forces, (2) 43*f*.
Tory, H. N. See Flexon, J. D.
Toshev, V. Refractory insulation for high temperatures, (6) 153*c*.
Totesh, A. S., Grigor'eva, L. F., and Strel'tsina, M. V. Some features in the structure of the surface of vertically drawn sheet glass, (4) 95*h*. Study of the strength of ground and polished glass, (10) 266*j*.
Toth, K. Effect of fiber formation on the quality of slag wool (I), (9) 233*g*.
Toth, K., and Flora, T. Derivatographic examination of synthetic zeolites (I), (6) 166*g*.
Toth, L. E., Rudy, E., Johnston, J., and Parker, E. R. Superconducting critical temperatures of carbides and nitrides with the NaCl structure—superconductivity of MoC, (7) 203*f*.
Tournarie, M. See Magnier, P.
Toussaint, F. See Plumat, E.
Toussaint, H. Study on the solid state reactions between MnO_2 or Mn_3O_4 and the oxides CaO, ZnO, MgO, or CdO, (2) 52*a*.
Touvay, R. Glass tank furnaces with submerged heating and cooling means, P (2) 33*a*. Shaping glass sheet on molten metal bath, P (8) 214*a*.
Touvay, R., and Lambert, R. E. Apparatus for press bending glass, P (8) 211*h*.
Townley, C. W., Miller, N. E., Ritzman, R. L., and Burian, R. J. Irradiation studies of ceramic-coated nuclear fuel particles, (3) 68*c*.
Townsend, R. L., Stickley, C. M., and Maio, A. D. Thermal effects in optically pumped laser rods, (2) 53*e*.
Toy, M. See Steadman, R.
Toyoda, H. See Itakura, M.

Toyoshima, I. Hybrid ceramic filters having two-terminal piezoelectric resonator in shunt with three-terminal piezoelectric resonator to improve harmonic rejection, P (6) 159*j*.
Toytot, R. de, and Brolmann, H. Method and apparatus for protection of glass sheet in contact with metal bath, P (7) 183*j*.
Trachsler, W. Influence of metalworking on prehistoric pottery—some observations on iron age pottery of the Alpine Region, B (6) 172*e*. Precursors of polychrome painted pottery—some examples from the prehistory of Switzerland, B (6) 172*e*.
Tran, T. L. Study of phase separation and devitrification products in glasses of the binary system Na_2O–SiO_2, (2) 32*a*.
Transitron Electronic Corp. Crystal diode, P (1) 14*k*. Method of attaching metallic leads to silicon layers of semiconductor devices, P (2) 41*k*. Method of growing single crystal silicon carbide, P (4) 101*d*. Method of making semiconductor devices with plated area, P (8) 221*a*. Thermoelectric bonding material, P (5) 130*b*.
Traure, J. See Magnier, P.
Travesi, A., Palomares, J., and Dominguez, G. Neutron activation analysis of microgram amounts of thorium in uranium ores and process liquors by means of ^{232}Th, (11) 310*b*.
Travis, C. J. See Eargle, F. L.
Treacy, C. S. See Argueso, L. M., Jr.
Treasure, C. R. G. See Kaye, B. H.
Treat, W. J. See Scribner, W. G.
Tredgold, R. H. See Cox, G. A.; Hughes, O. H.
Treesdale Laboratories, Inc. Exothermic side board suspension, P (9) 240*a*.
Trent, R. L., and Webster, R. R. Resistivity-measuring device including solid inductive sensor, P (5) 129*b*.
Tresouthick, S. W. See Ludwig, N. C.
Tresvyatskii, S. G. See Lopato, L. M.
Tresvyatskii, S. G., and Lopato, L. M. Some factors determining the type of phase diagram in binary systems formed by refractory oxides, (10) 290*c*.
Tresvyatskii, S. G., Lopato, L. M., and Yaremenko, Z. A. Phase diagram of the system Sc_2O_3–MgO, (9) 252*j*.
Trethewey, W. C. Voltage magnitude and temperature control in a heated device, P (7) 184*h*.
Tretinnik, V. Yu. See Ovcharenko, F. D.
Tret'yachenko, L. A. See Eremenko, V. N.
Tret'yakov, V. I. See Baskin, M. L.
Tret'yakov, Yu. D., and Khomyakov, K. G. Activity of oxygen over solid solutions of ferrite of cobalt with magnetite, (11) 313*f*.
Treuherz, W. See Everglades, Ltd.
Treuting, R. G., and Wernick, J. H. Nb–Zr superconductor and process of making the same, P (8) 221*f*.
Trewhella, R. M. See Merritt, R. B.
Trier, W. Relation between temperature field and flow field in free convection in glass melts, (3) 62*e*.
Trier, W., and Beine, H. Temperature measurements inside the top roller of a glass casting machine, (10) 267*a*.
Trier, W., and Staatsmann, H. Calculation of temperature distribution and heat transfer in the top roller of a glass casting machine, (10) 264*g*.
Trier, W., and Stein, A. Simplified model for the calculation of heat exchange by radiation between the flame and particular points on the glass surface in a tank furnace, (4) 95*f*.
Triggs, W. M., and Blumenfeld, M. A. Semiconductor devices, P (6) 160*g*.
Trigunayat, G. C. Origin of dislocations in solution-grown crystals, (7) 201*g*.
Triplett, B. L., Fasnacht, J. J., McWilliams, D. E., and Eilerman, G. E. Glass fiber sizing composition, P (10) 268*b*.
Triponis, A. Subterranean brine in Lithuania and its industrial importance, (6) 164*c*.
Tripp, W. C. See Rudd, M. O.
Troberg, B. See Nielsen, A.
Trojer, F. Present knowledge of the phase composition of portland cement clinker, (10) 262*h*.
Troshchenko, V. T. Effect of nonuniform distribution of the number of pores in the cross sections of specimens on the strength characteristics, (11) 316*d*.
Trost, C. M. Fluid [jet] grinding mill with interchangeable liners, P (4) 106*j*.
Trostel, L. J., Jr. Stability of alumina and zirconia in hydrogen, (1) 10*a*.
Trostyanskaya, E. B., Gunyaev, G. M., and Tsaritsyn, M. A. Effect of chemical treatment of the surface on properties of glass film and glass plastics made from it, (9) 233*f*.
Trout, O. F., Jr. See Hill, P. R.
Troyer, W. See Schoenlaub, R. A.
Trudeau, U. P. Method and apparatus for forming hollow glass articles, P (4) 97*g*.
Trueb, R. E., and Walkow, A. M. Container closure device, P (1) 14*h*.
Truesdell, A. H. Ion-exchange constants of natural glasses by the electrode method, (7) 180*f*.
Trukhanova, Z. S. See Tumanov, V. I.
Trump, J. G. See Shannon, J. P.
Truong, T. B. N. See Sienko, M. J.
Trutner, D. G. See Olsen, A. H.
TRW, Inc. Method for improving grain structure and soundness in castings, P (7) 188*g*. Method and pattern material [Se + S] for precision investment casting, P (9) 240*c*.
TRW Semiconductors, Inc. Impurity diffusion method, P (6) 159*a*. Semiconductor and method of forming by diffusion, P (6) 160*j*.
Tsai, S. W., and Azzi, V. D. Strength of laminated composite materials, (8) 224*a*.
Tsai, Ying-shih. See Kan, Fu-hsi.
Tsarevskaya, N. P. See Alakin, A. I.
Tsaritsyn, M. A. See Trostyanskaya, E. B.
Tsaritsyn, M. A., Zakharenko, N. L., Odnodvortsev, P. E., Kiryushkin, A. M., and Prokof'eva, Z. I. Mechanized production of selenium ruby sheet glass, (4) 94*h*.
Tselov, J. N. See Nabiullin, F. H.
Tsenter, S. M. Semiautomatic machinery for grinding and polishing porcelain articles, (2) 39*i*.
Tsepkov, L. P. See Vitman, F. F.
Tseung, A. C. C. See Dickson, D. J.
Tsigler, V. D., and Chursina, L. S. Rapid method for determining the content of combustible additions in the manufacture of lightweight refractories, (6) 153*b*.
Tsikolin, G. I. See Bluvshtein, M. N.
Tsintsius, V. M. See Shchukarev, S. A.
Tsuda, S. See Goss, N. P.
Tsui, Bin-Sin'. See Konstantinov, V. I.
Tsui, Bin-Sin', Luzhnaya, N. P., and Konstantinov, V. I. Investigation of the ternary reciprocal system of the fluorides and chlorides of potassium and tantalum, (1) 23*e*.
Tsui, Ping-Hsih. See Tsui, Bin-Sin'.
Tsuji, S. See Hayashi, T.
Tsukagoshi, Y. See Minami, Z.
Tsukamoto, J. See Sibert, M. E.
Tsukawaki, Y. Mechanism of the mineralization of pottery stone (1) mineralogical study of rock alteration to pottery stone of some pottery stone deposits in San-in District, (1) 18*f*.
Tsukino, M. See Ohta, Z.
Tsushima, K. Molten-salt vaporization methods for growing some single crystals of refractory oxides, (5) 138*i*.
Tsutsumi, N. Summarization of refractories used and their application for cupola melting in Japan, (1) 10*b*.
Tsutsumi, Y. See Kawakita, K.
Tsuzuki, K. See Okubo, S.
Tsuzuki, K., Shimazaki, T., Ochiai, T., Fujikake, Y., and Imai, H. Service tests on unburned brick containing SiC for electric furnace ladles, (9) 239*e*.
Tsuzuku, T. Cavity growth by vacancy condensation and transformation to dislocation loop in the graphite structure, (4) 109*i*. Mechanical energy losses due to motion of dislocations in graphite and carbons, (4) 112*a*.
Tsvetkov, A. I., Lapin, V. V., Val'yashikhina, E. P., and Piloyan, G. O. Solid-phase interaction between carbonates and clay minerals during thermal analysis, B (2) 56*b*.
Tsyun'khua, L., Pashinkin, A. S., and Novoselova, A. V. Determination of the saturation pressure of vapors of the solid selenides and tellurides of germanium, (4) 110*f*.
Tubbs, E. H. Siphonic flush commode, P (3) 58*c*.
Tucakovic, I. Extrusion machinery, P (3) 75*c*.
Tucker, W. F. See Stevens, H. M.
Tulloch, H. J. C. See Hyde, K. R.
Tumanov, V. I. See Kreymer, G. S.
Tumanov, V. I., Funke, V. F., Trukhanova, Z. S., Novikova, T. A., and Kuznetsova, K. F. Heat treatment of tungsten carbide-cobalt alloys, (3) 67*c*.
Tung, C. F. See Vanstrum, R. C.
Tung, Shue-li. See Wei, Fan-chun.
Tung, Shue-li, and Wang, Yan-mou. Carbonation resistance of lime-fly ash brick, (2) 35*e*.
Tung-Sol Electric, Inc. Cold cathode display device with fluorescent indicia anodes, P (9) 243*a*. Cold cathode with nickel base, calcium oxide interface, and magnesium oxide layer, P (6) 159*a*. Masking process for semiconductor elements, P (8) 221*g*.
Tung-Sol Industries, Inc. Colored sealed beam lamp and method of making the same, P (11) 297*i*.
Turk, H. L. See Agajanian, A. H.
Turnbull, N. C. See Scott, J. J.
Turnbull, W. T. See Burnett, R. W.
Turner, P. A. Four-region switching transistor comprising a controlled current path in the emitter, P (10) 278*h*.
Turner, R. F. See Koutz, S. L.
Turner, R. F., and Winkler, E. O. Ceramic-matrix-type fuel element with graphite fabric affixed to exterior surface, P (3) 70*e*.
Turner, T., Jr. See Mayer, W. J.
Turneri, N. See Standage, A. E.
Turners Asbestos Fibres, Ltd. Method of and apparatus for classifying fibers by length, P (10) 283*c*.
Turnock, A. C. Fe–Nb oxides—phase relations at 1180°C, (5) 136*g*. Mn–Ta oxides—phase relations at 1200°C, (8) 226*j*. See Bright, N. F. H.
Turnwald, W. See Gasparac, R. J.
Turpin, A. J. See Schreter, R. E.
Turpin, G. Production of anhydrous alumina, P (10) 283*a*.
Tury, P. Shock and vibration resistant heater for indirectly heated cathodes of radio receiving tubes, P (10) 279*e*.
Twin Sisters Magnesia & Chemical Corp. Method and apparatus for the preparation of magnesium oxide by a spouting bed technique, P (8) 217*d*.
Tyco Laboratories, Inc. Magnetic cores for electrical devices and method of manufacture, P (11) 306*j*.
Tydings, J. E. See Giardini, A. A.
Tye, R. P. See Powell, R. W.
Tykachinskii, I. D. See Fedorovskii, Ya. A.
Tykachinskii, I. D., and Loginova, T. Z. Effect of heat treatment on the crystallization of glasses in the system SiO_2–Al_2O_3–ZnO, (6) 147*h*.
Tyler, B. A. Method of reinforcing a fiber glass and resin rod, P (8) 213*c*.
Tyler, B. M. Unitary brick and concrete tilt-up wall sections and molds for producing, P (8) 214*g*.
Tymczak, R. W. See Brown, D. G.
Tyner, R. E. Plunger mechanism for glass gob feeder, P (7) 184*e*. Tube mechanism for glass gob feeder, P (6) 151*b*.
Tyrner, J. M. Apparatus for ultrahigh pressures, P (6) 161*f*.
Tysaman Machine Co., Inc. Methods of making abrasive wheels, P (8) 205*f*.
Tyson, W. R. See Kelly, A.

Uchida, K. See Imamura, H.
Uchida, N., and Ikeda, T. Temperature and bias characteristics of $Pb(Zr–Ti)O_3$ family ceramics, (6) 158*i*.
Uchijima, T. See Mukaibo, T.
Uchikawa, H. See Yamaguchi, G.
Uchikoshi, H. See Imoto, S.
Ueda, H. See Takagi, T.
Ueda, I. See Ikegami, S.
Ueda, M. Acoustic method of testing the physical properties of fireclay brick without destruction, (1) 7*j*. See Miyatake, K.
Ueda, T. Comparative study on results of using basic brick containing U. S. Kaiser periclase and basic brick containing Japanese-made seawater magnesite for open-hearth roofs, (3) 65*i*. Mg–Cr brick (MgO 95% magnesia clinker) used in the front wall of an open-hearth furnace, (7) 187*e*. See Munekata, E.
Ugai, Ya. A., Kotosonov, N. V., Fogel'son, R. L., and Tkacheva, G. S. Some properties of Ca_3Sb_2 obtained by the method of S. A. Vekshinskii, (3) 85*h*.
Ugai, Ya. A., Marshakova, T. A., and Goncharov, E. G. Influence of the character of the chemical bond on the solubility of inorganic materials in the solid state, (1) 22*g*.
Uhlig, A. F. Detecting crizzles in hollow glass containers [by light], P (7) 182*f*.
Uhlir, L. Lead-containing and lead-free majolica enamels, (10) 263*h*.
Uhlmann, E. See Pentek, I.
Ukrainskii, Yu. M. See Aslanov, L. A.
Ukumori, M. See Otsubo, K.
Ulbert, P. See Bouvier, G.
Ullmann, H. H. Glass technology, (10) 265*b*.
Ullmann, J. W. See Bradley, M. J.
Ulmer, G. C. See Harbin, H. P.
Ulmer, G. C., Campbell, F., Jr., Smothers, W. J., and Harbin, H. P. Thermogravimetric and differential thermal analyses of basic oxygen furnace refractories, (6) 154*e*.
Ulmer, G. C., and White, W. B. Existence of chromous ion in the spinel solid solution series $FeCr_2O_4$–$MgCr_2O_4$, (2) 50*b*.
Ulrich, D. R., and Smoke, E. J. Devitrified barium titanate dielectrics, (5) 128*b*.
Umanskii, A. M., and Sokol'skii, V. I. Use of hard-alloyed tools when pressing cermet parts on transfer presses, (3) 69*j*.
Umar, M. See Hashmi, M. H.
Umbel, F. K. Glass cutting [computer] control apparatus, P (11) 298*g*. See Galey, W. F.
Umblia, E. Technology of ceramic materials for microelectronics, (1) 14*c*. Trends in the American glass industry, (4) 95*h*.
Umeno, M. See Arizumi, T.
Umhauer, H. See Schoenert, K.
Underwood, J. H. See Stewardson, E. A.
Underwood, J. T. Apparatus for forming and collecting fibers, P (3) 62*g*.
Unilever, Ltd. Method of producing a gel, P (8) 217*g*. Process for preparing silicates and for making bodies from them, P (10) 274*f*.
Union Carbide Canada, Ltd. Apparatus for thermally working minerals, P (5) 133*b*.
Union Carbide Corp. Aluminum vaporizer, P (2) 37*a*. Bonded molecular sieves, P (2) 47*d*. Bonding of refractory materials by means of cerium oxide-cerium sulfide mixtures and product, P (5) 125*h*. Bottle coating machine, P (8) 212*a*. Casting process using borax-silica slag, P (4) 100*g*. Catalyst composition consisting essentially of the oxides of iron, rare earth, and zirconium, P (4) 100*h*. Composition of matter containing aluminum nitride and aluminum boride, P (9) 240*a*. Crystalline zeolite L, P (2) 47*e*. Electric furnace, P (2) 37*d*. Epoxy resin abrasive structures and method therefor, P (4) 89*f*. Gas turbine nozzle vane and like articles, P (2) 37*g*. Hardened molecular sieve agglomerates and manufacture thereof, P (5) 127*g*. High intensity carbon electrode, P (9) 243*f*. High-temperature kiln, P (4) 108*c*. Manufacture of shaped crystalline zeolitic molecular sieve bodies, P (10) 276*b*. Method for growing crystals, P (4) 107*b*. Method for preparing boron nitride, P (6) 155*a*. Method of preparing an oxidation resistant article, P (11) 302*e*. Method of producing refractory body bonded by an aluminum nitride-aluminum boride composition, P (5) 126*a*. Modified zeolitic molecular sieves and process for producing same, P (3) 79*c*. Phosphate bonded basic refractory articles, P (4) 101*c*. Process for casting metals into asbestos-containing mold coating, P (7) 189*f*. Process for coating radioactive spheroids with pyrolytic graphite, P (7) 189*f*. Process for compaction

of zeolite powders, P (1) 12*d*. Process for producing ultrafine powders of refractory materials, P (8) 218*g*. Process for producing ultrafine silicon nitride, P (1) 12*e*. Production of single crystals from incongruently melting material, P (11) 307*j*. Purification of refractory materials, P (6) 155*a*. Pyrometer, P (7) 195*d*. Refractory article, P (8) 218*b*. Refractory compositions, P (8) 218*c*. Solar simulation apparatus, P (11) 308*c*. Spall resistant refractory brick, P (5) 127*a*. Sulfur treated asbestos, P (8) 218*f*. Thermoelectric conversion apparatus, P (8) 222*a*. Thermoelectric materials, P (7) 194*d*. Titanium diboride articles and method for making same, P (2) 38*i*. Ultrafine titanium boride, P (6) 155*h*. Use of two magnetic fields in a low pressure arc system for growing crystals, P (5) 131*b*. Wear- and strain-resistant coated articles, P (3) 60*b*. Zirconboron ablation coating, P (4) 91*i*. Zirconia-boron ablation coating, P (4) 91*i*.

Union Oil Co. of California. High-silica molecular sieve zeolites, P (4) 103*c*. Preparation of silica for use in electric-field-responsive compositions, P (7) 194*b*. Pretreatment of pelleted zeolites to improve crushing strength, P (6) 155*g*.

United Aircraft Corp. Ablation cooled rocket nozzle, P (5) 125*g*. Hardcoated mold press die, P (2) 43*g*. Method of compacting ferrite particles, P (10) 278*e*. Process for producing silicon nitride and a product thereof, P (4) 101*f*.

United Coke and Chemicals Co., Ltd. Vanadium pentoxide potassium pyrosulfate catalyst and method of preparation thereof, P (4) 102*b*.

United Glassworks. See N. V. Vereenigde Glasfabrieken.

United International Research, Inc. Process for the production of chrome concentrates, P (2) 48*c*.

United Kingdom Atomic Energy Authority. Agglomeration process for producing spheroids from nuclear fuel ceramic powder, P (4) 99*j*. Apparatus [electrolytic] for oxygen analysis of gases, P (7) 195*a*. Fuel elements for nuclear reactors, P (6) 154*c*. High-temperature nuclear fuel structures and their production, P (11) 1*f*. Manufacture of ceramic material mixed with a metal, P (9) 232*g*. Manufacture of cermets with metal members bonded thereto, P (5) 126*b*. Manufacture of sintered uranium dioxide bodies, P (4) 100*f*. Manufacture of uranium dioxide, P (5) 126*c*. Method and apparatus for measuring the concentration of an element in a mixture by an X-ray absorption analysis technique, P (11) 311*a*. Method of forming fibrous carbon articles, P (5) 126*e*. Method for producing a composite carbon article and articles produced thereby, P (5) 126*a*. Method of producing nuclear fuel monocarbides from higher carbides, P (11) 302*g*. Moderator structures for nuclear reactors, P (9) 240*i*. Nuclear fuel materials, P (4) 101*b*. Nuclear fuel processing, P (2) 38*j*. Process for hot pressing powder, P (4) 107*a*. Process for the preparation of uranium monocarbide-plutonium monocarbide fuel elements, P (5) 126*h*. Process of producing spheroids of nuclear fuel materials by agglomeration, P (4) 101*h*. Processing of fissile and fertile material for nuclear reactors, P (7) 189*c*. Production of spheroids, P (4) 107*b*. Thermal treatment of refractory materials, P (10) 275*b*. Thermometer devices, P (1) 17*d*. Uranium nitride-iron nuclear fuel cermets, P (5) 127*b*.

United Research, Inc. Method of determining the volume of particles in a mixture, P (5) 132*b*.

United States of America, Administrator of the National Aeronautics and Space Administration. Apparatus for producing high purity silicon carbide crystals, P (4) 100*b*. Heat protection apparatus, P (11) 296*b*. High temperature spark plug, P (4) 105*b*. Method of coating carbonaceous base to prevent oxidation destruction and coated base, P (10) 274*d*. Method of making impurity-type semiconductor electrical contacts, P (11) 306*e*.

United States of America, Secretary of the Air Force. Alkaline earth halide divalent dysprosium laser materials, P (6) 158*c*. Contour design for "cascading by shaping" thermomagnetic devices, P (3) 72*i*. Crystal pulling apparatus, P (10) 278*b*. Hot pressing zirconia, P (2) 37*i*. Method of determining the dielectric constant of irregularly shaped crystals, P (11) 306*c*. Method of fabrication of a microwave delay line, P (10) 278*h*. Method for producing conductive glass fiber yarn, P (3) 64*a*.

United States of America, Secretary of the Army. Apparatus for electrophoretic deposition of lamellar fluorphlogopite mica sheets, P (1) 14*e*. Apparatus and method for elutriating and measuring fine solid particles, P (11) 311*a*. Ferrite frequency converter with dielectric low pass filter, P (9) 243*d*. Integrated semiconductor resistance element, P (10) 278*b*. Low impedance coupled transmission line and solid state tunnel diode structure, P (11) 306*i*. Method of creating electrically semiconducting diamond, P (10) 278*f*. Method of making manganese ferrite film from nitrate solution, P (11) 306*f*. Method of processing ceramic type ferroelectric materials, P (10) 279*b*. Method for securing structures in precise geometric relationship, P (11) 307*c*. Piezoelectric crystal, P (4) 106*a*. Reciprocal ferrite waveguide phase shifter having means to rotate the magnetic field about an axis transverse to the longitudinal axis of the ferrite rod, P (10) 279*c*.

United States of America, Secretary of the Interior. Fraction separation of aqueous rare earths using amines, P (9) 247*e*. Process for separating rare-earth elements by ion exchange, P (4) 109*g*. Synthesis of fibrous silicon nitride, P (6) 155*g*. Synthesis of large crystals of fluorphlogopite mica, P (3) 79*c*.

United States of America, Secretary of the Navy. Apparatus for comparative determination of thermal conductivity, P (9) 246*c*. Ceramic adhesive composition, P (11) 302*a*. Electroacoustic transducer for detection of low level acoustic signals over a broad frequency range, P (6) 159*c*. Infrared calibration lamp, P (3) 73*f*. Laser with ytterbium activated glass sensitive element, P (1) 14*e*. Method of lowering the surface recombination velocity of indium antimonide crystals, P (1) 14*i*. Method for making U–V responsive photoemissive tubes, P (10) 278*j*. Method of preparing transparent luminescent screens, P (10) 269*j*. Open hemispherical transducers, P (4) 105*j*. Process for molding a glass fiber aerosol filter, P (7) 184*g*. Reinforced ceramic cylindrical transducers, P (4) 106*e*. Techniques associated with inductive sensing of tunnel diode memory cells, P (3) 74*b*.

United States of America, U.S. Atomic Energy Commission. Alumina-cobalt-gold composition, P (4) 109*b*. Apparatus for manufacturing shapes of uranium carbide, P (9) 239*i*. Broach for curved graphite passages, P (11) 301*i*. Carbide coatings for graphite, P (1) 10*j*. Carbide deposition on tantalum, P (10) 263*g*. Carbon coated metal carbide particles for nuclear reactor use, P (6) 154*j*. Ceramic-matrix-type fuel element with graphite fabric affixed to exterior surface, P (3) 70*e*. Ceramic to metal bonding process, P (2) 37*c*. Electrostatic apparatus for removal of dust particles from a gas stream, P (2) 43*e*. Fabrication of shapes by pneumatic impaction, P (1) 11*d*. Fluidization of sinterable fines, P (11) 302*e*. Fuel element, P (11) 302*f*. Fuel element for a nuclear reactor, P (4) 100*a*. High temperature furnace, P (5) 132*e*. Low power nuclear reactors, P (3) 70*c*. Metal-clad fuel element with copper foil interlayer, P (4) 100*h*. Metal shapes having increased compressive strengths, P (9) 244*h*. Method for formulating master alloy compositions for use in dispersion hardened compacts, P (11) 302*j*. Method of making hollow spherical UO_2 particles, P (11) 302*b*. Method of making nuclear fuel compact, P (1) 11*j*. Method and means for improving the electron emission from refractory conducting material, P (7) 193*g*. Method of preparing compactible thorium oxide-plutonium oxide particles, P (9) 240*e*. Method of preparing high-density compactible uranium dioxide particles, P (10) 274*i*. Method of preventing carburization of fuel element cladding metals by uranium carbide fuels, P (2) 38*g*. Method for stabilizing uranium monocarbide, P (1) 11*f*. Nuclear [ceramic] fuel element incorporating helical fissionable wire, P (11) 302*j*. Nuclear fuel particles coated with mixture of pyrolytic carbon and silicon carbide, P (7) 189*b*. Oxidation-resistant coating on articles of yttrium metal, P (10) 263*i*. Preparation of actinide monocarbide, P (7) 189*c*. Preparation of binary compounds of uranium and thorium, P (11) 303*b*. Pressure intensifier, P (6) 161*e*. Process for forming a uranium mononitride-uranium dioxide nuclear fuel, P (1) 12*d*. Process of making a sintered homogeneous dispersion of nuclear fuel and burnable poison, P (10) 274*c*. Process for sintering uranium nitride with a sintering aid depressant, P (1) 12*g*. Radiation reactor, P (10) 274*h*. Radioactive waste disposal using colemanite, P (11) 303*j*. Semiconductor detector method, P (11) 307*g*. Single-step process for preparation of uranium dioxide from uranium hexafluoride, P (9) 241*b*. System for separating particulate substances by reorienting gradients, P (6) 161*g*. Unpurged fuel element, P (11) 303*j*. Uranium mononitride fuel and method of making, P (1) 12*e*. Uranium monosulfide-uranium monophosphide solid solutions, P (10) 275*c*.

United States Borax & Chemical Corp. Abrasion resistant material bonding process using boron alloys, P (8) 216*j*. Abrasion resistant materials, P (8) 216*j*. Production of titanium diboride, P (7) 189*f*.

United States Ceramic Tile Co. Apparatus for securing a plurality of units in abutting relationship with one another, P (1) 13*c*.

United States Gypsum Co. Fiber forming apparatus, P (10) 267*h*. Gypsum composition and building construction, P (11) 295*a*. Method for making ultrafine calcium sulfate dihydrate crystals, P (10) 263*b*.

United States Radium Corp. Tritium activated self-luminous compositions, P (3) 74*d*.

United States Steel Corp. Apparatus for analyzing cement kiln exit gases, P (2) 45*b*. Apparatus for measuring temperature differences, P (7) 195*a*. Deeply hardenable [steel] liner member for grinding mill, P (7) 194*f*. Dolomite brick and method of making it, P (11) 302*c*. Elongated relatively thin metal capacitor probe in combination with a conveying means for determining the dielectric properties of bulk material, P (11) 311*d*. Method and apparatus for lining a hot top, P (5) 126*d*. Method of producing stainless-clad steel plate, P (5) 123*h*. Mold coating and method of pouring ingots, P (1) 11*g*. Slag pocket wall, P (9) 241*c*. Two part hot top, P (1) 12*e*. Wearing elements for blast furnace stockline, P (7) 190*a*.

United States Stoneware Co. Jar mill mounting, P (4) 107*a*. Rotator, P (1) 16*c*. Saddle for treating tower, P (5) 127*h*.

Universal Moulded Fiber Glass Corp. Equipment for making articles composed of fiber reinforced resin materials, P (9) 235*i*.

Universal Oil Products Co. Crystalline zeolite U, P (7) 190*g*. Process for producing anhydrous alumina, P (3) 79*d*.

Universal-Rundle Corp. Casting toilet bowls and like ceramic ware, P (2) 40*c*.

University of Illinois Foundation. Gas-impervious electrical feedthrough for use between two zones of differing pressures, P (2) 41*c*.

Univis, Inc. Method and apparatus for processing of ophthalmic lens, P (4) 97*i*.

Uppal, H. L. Scientific explanation of the plastic limit of soils, (11) 300*a*.

Uppgren, J. J. See King, W. J.

Upson, U. L. See Allemann, R. T.

Upton, L. O. Energy conducting fibers formed of sapphire cladded with quartz, P (4) 96*g*. Infrared transmitting fibers formed of arsenic and sulfur, P (1) 6*g*. Solder sealing glass members, P (4) 64*j*.

Urban, C. Applications of the flame-spraying technique, (6) 145*b*.

Urban, R. See Nogard, G.

Ur'ev, N. B., Mikhailov, N. V., and Rebinder, P. A. Structure forming role of solid surfaces during bonding with cement-water suspensions, (3) 59*c*.

Urnes, S. Electrical conductivity of $Ca(NO_3)_2$–KNO_3 glass, (2) 31*j*. See Blair, G. E.; Forland, T.

Urusovskaya, L. N. See Demkina, L. I.

Usami, S. See Gondo, Y.

Usami, S., Miyata, N., and Funatogawa, Z. Frequency dependence of ferromagnetic crystalline anisotropy of $Ni_xFe_{3-x}O_4$, (10) 286*j*.

Ushakov, D. F. Influence of crystallization on the properties of glasses in the system Li_2O–MgO–Al_2O_3–SiO_2, (4) 93*h*.

Ushko, U. Y. See Nabiullin, F. H.

Usikova, N. E. See Borovik, E. S.

Usvitskii, M. B. Unit for high-temperature DTA of materials, (8) 224*a*. See Kitaigorodskii, I. I.

Utley, R. W., Lovell, H. L., and Spicer, T. S. Preparation of coal refuse for the manufacture of lightweight aggregate, (7) 185*c*.

Utolina, L. S. See Marinina, V. T.

Utz, D. L. See Ryshkewitch, E. I.; Sheets, A. R.

Uvarova, I. Yu. See Luk'yanova, O. I.

Uyeda, Y. Preparation of magnesium trisilicate, P (11) 312*h*.

Uytterhoeven, J. See Calvet, R.

Vaccari, J. A. See Hauck, J. E.

Vactronic Lab. Equipment, Inc. Nude ion gage assembly, P (11) 307*e*.

Vagh, A. S. See Joshi, M. S.; Patel, A. R.

Vagner, G. R. See Kruglitskii, N. N.

Vahldiek, F. W. See Mersol, S. A.; Robinson, L. B.

Vainshtein, E. E. See Samsonov, G. V.

Vaisvilaite, A., and Vektaris, B. Effect of carbonaceous and feldspar impurities on the quality of silicate concrete, (9) 230*h*.

Vaitkus, J. See Viscakas, J.

Vaitkus, J., Aleinikov, F. K., and Slizys, V. Effect of heat treatment on some physical-mechanical properties and structure of silicate glasses (II) electrical properties, (7) 179*i*.

Vaitkus, J., Viscakas, J., Persianov, I. C., and Smilga, A. Anisotropy of photoconductivity in single CdSe crystals, (11) 313*i*.

Vajda, L. See Domokos, G.

Vakhrameev, V. S. See Bezpalov, K. M.

Valagura, I. A. See Oblival'nyi, F. A.

Valchar, C. E. See Cypher, J. H.; Malobicky, R. L.

Valentin, G. See Alfille, L.; Kiehl, J. P.

Valeton, I. Geochemical stratification in bauxite deposits of southern France, B (2) 56*h*.

Valigi, M. See Cimino, A.

Val'yashikhina, E. P. See Tsvetkov, A. I.

Van Bakel, H. A., and Spreuwenberg, P. B. T. H. Method of providing light diffusing coatings on quartz and quartz objects provided with such coatings, P (4) 97*f*.

Van Broekhoven, J., and Repsher, R. W. Halophosphate phosphor material of improved luminosity and maintenance characteristics for fluorescent lamps, P (8) 221*c*.

Vance, J. A. Zoning in igneous plagioclase—patchy zoning, (2) 54*c*.

Van Couvering, A., and Luckey, H. H. Semiconductor diode and method of making same, P (7) 194*e*.

Van Denberg, J. F., and Manring, W. H. Glass defects due to batch segregation (II), (4) 93*a*.

Vanden Berghe, L. Ceramic contributions to a knowledge of culture in prehistoric Iran, B (6) 172*g*.

Van Der Beck, R. R., Jr. Refractory products and method of making, P (4) 102*a*.

Vander Linden, C. R., and Riede, R. G. High flow rate perlite filter aids, P (5) 124*f*.

Vandervoort, R. R., and Barmore, W. L. Compressive creep of beryllium oxide-uranium dioxide mixtures, (1) 19*h*.

Van der Waals, J. D. Early ceramics in the Netherlands—two problems, B (6) 172*e*.

Van der Wal, J. F. See Clarenburg, L. A.

Van Dreser, M. L., and Altmann, B. G. Refractory, P (9) 241*e*.
Vanfleet, H. B., Baker, G. S., and Gibbs, P. Ag ion transport and deposition in α-quartz, (2) 48*e*.
Vanguard Instrument Corp. Liquid scintillation spectrometer detection chamber and removable tray for supporting a plurality of sample containers, P (11) 311*e*.
Van Gils, C. L. M., Stijntjes, T. G. W., and Waterbeemd, J. G. W. van de. Method for preparing manganese-zinc-ferrous ferrite, P (8) 221*d*.
Van Gorman, L. Aluminum-germanium contact, P (3) 72*d*.
Vanik, M. C. See Acker, E. G.
Vanik, M. C., Sanchez, M. G., and Herrera, J. E. Temperature sensitive device, P (11) 308*b*.
Van Loan, M., Jr. Comparison of various types of filters for nickel-dip solutions, (8) 207*i*.
Van Loan, P. R., and Chakrabarty, M. R. Crystal chemistry and dielectric properties in the systems $BaTiO_3$–UO_3 and $BaTiO_3$–$BaUO_3$, (6) 157*i*.
Van Qui, V. See Bertaut, E. F.
Vanstrum, R. C., Harrington, T. L., and Tung, C. F. Inorganic reflex-reflective aggregate, P (11) 298*j*.
Van Tassel, R. Crystal particularities in dolomite synthesis, (3) 80*a*.
Vantournhoudt, M. See Croegaert, J.
Van Uitert, L. G. Correlation of spin ordering temperatures for compounds containing divalent 3*d* transition metal ions, (6) 165*g*. Optical maser using single crystal molybdate composition, P (6) 160*i*. See Ballman, A. A.; Geusic, J. E.; Johnson, L. F.; Rubin, J. J.
Van Vlack, L. H. See McCollister, H.
Van Vulpen, A. See Bakker, M. A. M.
Varadi, P. F., and Dominguez, R. Tungsten metallizing of ceramics, (10) 277*b*.
Varda, G. de. See Montecatini Societa Generale per l'Industria Mineraria e Chimica.
Varga, J. E. Method of manufacturing a capacitor by reactive sputtering of tantalum oxide onto a silicon substrate, P (9) 243*a*.
Vargin, V. V. (editor). Catalyzed Controlled Crystallization of Glasses in the Lithium Aluminosilicate System (I), B (3) 88*g*.
Vargin, V. V., and Senderovich, V. Ya. Discoloration of titanium enamels, (6) 145*e*.
Varian Associates. Demountable metal-to-ceramic seal, P (10) 278*c*. Pulsed ferromagnetic microwave generator, P (8) 221*j*.
Varju, G. See Nemecz, E.
Varshneya, A. K., Cooper, A. R., Jr., and Cable, M. Changes in composition during electron microprobe analysis of K_2O–SrO–SiO_2 glass, (9) 232*j*.
Varty, A., and White, D. Application of multivariate analysis to montmorillonite, (5) 134*b*.
Vascik, R. A. See Romstadt, J. L.
Vashman, A. A. Electron paramagnetic resonance in alumina-based ceramics, (5) 136*a*.
Vasil'chikova, I. A. See Ikornikova, N. Yu.
Vasil'ev, V. P. Influence of ionic forces on the constants of instability of complex compounds, (5) 137*i*.
Vasil'ev, Ya. V., Khrycheva, D. D., and Ariya, S. M. Magnetic susceptibility of the lower oxides of titanium, (9) 251*f*.
Vasil'eva, V. A. See Toropov, N. A.
Vasil'kova, I. V. See Shchukarev, S. A.
Vasil'kova, I. V., Zaitseva, N. D., and Shapkin, P. S. Interaction of the hexa- and pentachloride of tungsten with the chlorides of sodium and potassium, (11) 317*e*.
Vasilos, T. See Brissette, L. A.; Passmore, E. M.; Wuensch, B. J.
Vasilos, T., and Gannon, R. E. Ablation properties of ceramics, (1) 7*j*.
Vaskova, L. See Hlavac, J.
Vassiliev, A., Nicolas, J., and Hildebrandt, M. Nickel ferrite containing cobalt and manganese, P (5) 129*b*. Ni–Mn–Al–Co ferrite, P (7) 193*i*.
Vassiliou, B. E., and Warner, H. O. Suspended refractory bricks, P (8) 218*g*.
Vassos, N. Gas-impervious electrical feedthrough for use between two zones of differing pressures, P (2) 41*c*.
Vasyutinskii, B. M., Kogan, V. S., Kartmazov, C. N., and Yakimenko, L. F. Formation of textured nitride layers on chromium produced by vacuum condensation from vapor phase, (10) 286*i*.
Vatterodt, K. Electrically heated tank furnace for melting quartz, P (1) 6*h*. Furnace for the continuous drawing of quartz tubing, P (11) 298*d*.
Vaughan, S. H., Jr. Refractory structure for a rotary kiln, P (4) 108*f*.
Vazquez, F. T. Flame photometry for the determination of alkalis in cements, (3) 58*f*.
Veankov, V. T., Lobanov, N. I., and Smirnova, K. A. Sound absorbing porous ceramics, (2) 37*b*.
Veatch, F. See Alford, H. E.
Veatch, F., Alford, H. E., and Croft, R. D. Apparatus for spherulization of fusible particles, P (4) 96*i*.
Veazie, F. M., and Womeldorph, R. C. Method and apparatus for processing high temperature batch materials, P (10) 268*a*.
Vedam, K., Schmidt, E. D. D., and Roy, R. Nonlinear variation of refractive index of vitreous silica with pressure to 7 kbars, (11) 318*c*.
Veitscher Magnesitwerke Akt.-Ges. Structural element of basic or neutral refractory containing carbon and its manufacture, P (10) 282*e*.
Vektaris, B. See Vaisvilaite, A.
Velden, H. I., van der. Phenomenological study of the effect of some factors on the behavior of brick products during drying, (11) 300*g*.
Velden, P. F. van. Thermal conductivities of some lead and bismuth glasses, (2) 32*d*.
Velev, D. S. Calculating the cooling basins of glass tanks, (4) 92*c*.
Velica, P. See Abramovici, R.
Venable, R. H., Jr. Some refractory problems arising from vacuum treatment of molten steel, (9) 239*f*.
Venables, J. D. Identification of precipitates on grown-in dislocations in MgO, (2) 50*i*.
Venediktova, R. I., and Rudnyi, N. M. Mass transfer in the extraction of moisture from capillary porous materials, (6) 168*e*.
Venet, P. See Fleischhauer, G.
Venevtsev, Yu. N. See Ivanova, V. V.
Veo, L. E., Stevens, D. E., Jr., Mitman, E. T., French, A. H., Zimmerman, C. A., and Bast, C. H. Apparatus and method for processing material, P (5) 119*c*.
Verbeek, L. H. Electric lamp, P (10) 278*d*.
Verduch, A. G. Advances in the field of glass, (6) 146*j*. Early stages of the reaction between cristobalite and calcium carbonate, (2) 49*c*. Manufacture of high silica lightweight products, (7) 186*j*. Moisture expansion of ceramic products, (2) 35*h*. See Garcia Verduch, A.
Verein Deutscher Zementwerke (editor). Microscopy of Cement Clinker—Picture Atlas, B (4) 115*i*.
Vereinigte Ultramarinfabriken Aktiengesellschaft vorm. Leverkus, Zeltner & Consorten. Yellow [inorganic] pigment and method of preparation, P (11) 313*b*.
Veres, F. Luminescent ceramic material of cadmium, boron, and manganous oxides, P (5) 123*f*.
Vereshchagina, V. I. Fusibility in the system Li_2F_2–BaF_2–Na_2Cl_2, (3) 82*d*.
Vergette, N. Ceramics in the United States, (9) 229*i*.
Verhoeven, A. C. J. See Spaapen, J. B. M.
Verkhorobin, L. F. See Matyushenko, N. N.
Verkhorobin, L. F., Ivanov, V. E., Matyushenko, N. N., Nechiporenko, E. P., Pugachev, N. S., and Somov, A. I. Reaction diffusion in the systems Mo–Si, W–Si, and Ta–Si, (10) 290*d*.
Verkhorobin, L. F., and Matyushenko, N. N. Thermal expansion of disilicides of some transition metals, (2) 53*a*.
Verlotskii, A. A. See Rogovoi, M. I.
Vermaak, J. S., and Merwe, J. H. van der. Misfit dislocations in the diffusion zone of a bicrystal system (II) forces in the redistribution of misfit dislocations, (2) 50*c*.
Vermeulen, G. A. W., and Gravesteijn, J. C. Method of manufacturing display screens for cathode-ray tubes, P (4) 105*b*.
Vermont American Corp. Abrasive article backed with stretchable-compressible material, P (2) 27*f*.
Vernetti, R. A., and Cook, R. L. Effect of metal oxide additions on the high-temperature electrical conductivity of alumina, (5) 128*c*.
Vernon, R. W. See Wahlberg, J. S.
Vershinina, I. A. See Styunkel', T. B.
Verstraten, J. See Seldenrath, T. R.
Vertes, P. See Delange, M.
Vertes, P., Huet, H., and Delange, M. Method and apparatus for continuously obtaining uranium dioxide with predetermined characteristics from uranium trioxide, P (4) 100*j*.
Vescovi, V. C. Method for producing borosilica gels, P (7) 184*i*.
Vesper, R. M. See Carvelas, J.
Vessey, E. W., and Linton, R. W. Organic phosphates—stabilization of silica sols and dispersions or suspensions of silica and siliceous materials, P (9) 247*f*.
Vest, R. W. See Tallan, N. M.
Vice, C. L. Method of making a transducer, P (7) 193*f*.
Vicente, J. G. See Garcia Vicente, J.
Victory Engineering Corp. Method of covering resistor bead, P (7) 193*j*. Method of making bead type thermistors, P (3) 73*a*.
Vidro, L. I., Khorol'skii, Yu. M., and Mironenko, L. A. Apparatus for controlling the degree of homogeneity of glass, (9) 232*i*.
Vigdergauz, V. Sh. See Avgustinik, A. I.
Vigileva, E. S. See Yarembash, E. I.
Vigutova, T. N. See Palkin, A. P.
Viktorova, Yu. N. See Brekhovskikh, S. M.
Vilanova, J. M. V. See Villalonga Vilanova, J. M.
Villalonga Vilanova, J. M. Firing of electrical porcelain in tunnel kilns, (3) 71*f*.
Villinger, G. "Top-hat" kiln in the ceramic industry, (8) 224*j*.
Vilnis, K. K. Design of glass melting furnaces (I), (6) 147*d*; (II), (8) 209*c*. See Stepanenko, M. G.
Vincent, T. C. Luminescent niobates, P (6) 159*c*.
Vinz, O. Effect of repeated temperature changes on the thermal shock resistance of glasses, (2) 31*k*.
Viscakas, J. See Smilga, A.; Stonkus, S.; Vaitkus, J.
Viscakas, J., and Kavaliauskiene, G. Dependence of dark discharge of xerographic selenium layers on temperature, (6) 166*d*. Examination of complex xerographic layers with *np* and *pp* junctions, (6) 167*d*.
Viscakas, J., and Vaitkus, J. Influence of background light intensity on steady-state photoconductivity of CdSe polycrystalline layers, (6) 168*d*. Spectral dependence of photoconductivity in CdSe polycrystalline layers, (6) 170*c*.
Visconti, Y. S. Clay minerals interstratified in "taguas," (3) 78*c*.
Viskanta, R. Heat transfer by conduction and radiation in absorbing and scattering materials, (1) 22*c*. Influence of internal thermal radiation on heat transfer in UO_2 fuel elements, (3) 67*i*.
Viswanathan, K. See Bambauer, H. U.
Vitali, R., and Fuhrman, Z. A. Technique for preparing samples of small fragile particles for electron microscope examination by means of replicas, (11) 310*f*.
Vitman, F. F., Bartenev, G. M., Pukh, V. P., and Tsepkov, L. P. Method of measuring the strength of sheet glass, (4) 94*j*.
Vitman, F. F., and Pukh, V. P. Method of determining the strength of sheet glass, (5) 121*d*.
Vitokhina, V. M. See Nosova, Z. A.
Vitter, G. See Deportes, C.
Vivaldi, J. L. M. See Martin Vivaldi, J. L.
Vivante, C. See Sayers, J. B.
Vladimirov, L. P., Shusterman, M. I., Konikova, R. S., and Komarova, L. P. Corrosion and erosion resistance of chromium carbide alloys in multicomponent corrosive environments, (11) 300*j*.
Vlasov, K. R. See Serdyuk, S. M.
Vlasov, L. G. See Berdonosov, S. S.
Vlasov, V. A. See Botvinkin, O. K.; Gorokhovskii, V. A.
Vlasov, V. G. See Bessonov, A. F.; Zhukovskii, V. M.
Vlasov, V. V. See Buzdov, K. A.
Vodenicharov, M. See Brashnarova, A.
Vodopyanov, L. K. See Ehrenberg, W.
Vogel, A. See Raentsch, K.
Vogel, M. J. Uranium and lanthanide activated alkaline earth molybdate and tungstate phosphors, P (10) 279*i*.
Vogel, W. Interrelations between microheterogeneity, nucleation, and crystallization in glasses, (5) 120*j*. Structure and Crystallization of Glasses, B (1) 26*c*.
Vogel, W., and Heindorf, W. Optical glass and its manufacture, P (10) 269*f*.
Vogelpohl, R. L. See Mayhew, R. W.
Vogt, W. See Sennewald, K.
Vohler, O. See Fitzer, E.
Vohler, O., and Sperk, E. Fibrous carbon, (9) 238*h*.
Voigtlaender-Tetzner, G. Method and apparatus to dry powdery substances under a vacuum using electrical gas discharges, P (6) 161*d*.
Voitsekhovskii, V. N., and Mokievskii, V. A. Problem of the interrelation of the growth and solution of crystals, (9) 254*a*.
Volchenkova, Z. S., and Pal'guev, S. F. Electrical conductivity of systems of solid oxides (II) ZrO_2–CaO system—electrical conductivity and transport numbers; (III) ThO_2–CaO system, B (1) 26*i*; (VII) systems ThO_2–BeO, ThO_2–MgO, ThO_2–SrO, and ThO_2–BaO, B (1) 26*b*.
Vol'fkovich, S. I. See Smirnova, Z. G.
Volk, D. Lens generating apparatus, P (10) 268*b*. Lens generating method, P (2) 33*e*. Lens surface generator, P (6) 150*e*.
Volk, W. See Johnson, C. A.
Volkmann, H. See Klemm, W.
Vollick, C. A. Additives for concrete, mortar, and grout, P (2) 29*f*.
Vollmer, R. Incandescent lamp for projectors, P (10) 268*f*.
Voloshinova, L. M. See Dubova, O. A.
Volpe, M. L., and Paschali, C. E. Device for cleaving crystals, (10) 280*h*.
Vol'ski, V. Magnetic and catalytic properties of the ferrites of nickel and zinc, (5) 138*d*.
Volzer, J. B., and Wenig, L. Bent end electric lamp having lead wires anchored at ends of bend and provided with expansion portion, P (5) 128*h*.
Volzhenskii, D. S., Pashkovskii, M. V., and Svekolkina, L. G. Some physical properties of vanadium oxide bronzes of copper and silver (1) 25*c*.
Vondra, B. L., Jr. Method of dissolving ceramic containing beryllia, P (1) 11*i*.
Vondracek, C. H. Inorganic potting compounds for high temperatures, (2) 40*h*. See Merry, J. D.
Von Funk, I. Pneumatic material conveyor, P (9) 244*j*.
Von Vick, G. Accelerometers (I), (3) 75*d*.
Vook, R. W., and Witt, F. Structure and annealing behavior of metal films deposited on substrates near 80°K (I) copper films on glass; (II) gold films on glass, (11) 305*d*.
Voorheis, T. S. Apparatus and method for providing constant-heat variable-pattern burner flame, P (2) 46*c*.
Vorob'eva, O. V. Preparation of transparent electrical conducting films on glass, (1) 5*b*. See Botvinkin, O. K.; Nozdracheva, T. F.
Vorob'eva, O. V., and Bessonova, E. S. Preparation of oxide films from iron chloride, (1) 5*b*. Study of conditions of formation of iron oxide films, (10) 266*c*.
Vorob'eva, O. V., and Nozdracheva, T. F. Semiconductor films of vanadium oxide on glass, (1) 5*j*.
Voronin, N. I., Krasotkina, N. I., and Yudin, V. F. Heat resistant electrical insulating coatings for steel tubes in heating installations, (6) 145*g*.
Voronov, N. M., Danilin, A. S., and Kovalev, I. T. Determination of the rate of vaporization of metallic oxides on samples heated by electric current, B (6) 175*g*.
Vorontsova, A. A. Investigation of the reaction which forms alkaline earth metal carbonates by the method of measuring the volume of precipitates, (1) 23*b*.
Vos, K. J. de. See Hokkeling, P.

Voskresenskaya, N. K. See Berul, S. I.
Voskresenskaya, N. K., and Berul, S. I. Transformation of CeO_2, Nd_2O_3, and Sm_2O_3 and their interactions with molten chlorides of lithium and potassium and with the carbonate and sulfate of sodium, (3) 87*f*.
Votava, W. See Burgyan, A.
Vranken, F. M. Gravity bending furnace particularly for manufacturing bent glass sheet, P (7) 183*h*.
Vranken, J. P. L. G. F. Method and apparatus for the production of curved and hardened panes of glass, P (8) 213*e*.
Vries, E. R. de. Process of peening metals with coated glass beads, P (4) 98*c*.
Vrolijks, M. H. M. See Peloschek, H. P.
Vuillard, G. Welding of boron carbide to silicon, (8) 216*f*.
Vukasovich, M. S. See Harkulich, T. M.; Kiss, K.; Wainer, E.
Vuyk, J., and Kreuter, J. C. Physical properties of low firing ground enamels, (2) 30*a*.
Vydrevich, E. Z. Isothermal cross section of the system Na_2O–Al_2O_3–CaO–SiO_2–H_2O at 250°, (5) 137*i*.
Vydrevich, E. Z., and Gal'perin, E. L. Equilibrium phases of the system Na_2O–Al_2O_3–CaO–SiO_2–H_2O, (5) 136*c*.
Vyrakaya, L. A. See Korshunov, B. G.
Vyse, J. See Clements, J. F.
Vyzkumny ustar energeticky. Automatic analyzing device and method, P (9) 246*c*.

Waal, H. de. Fracture strength of glass, (8) 209*h*. Quantitative differential thermal analysis with an isothermal microcalorimeter, (3) 76*h*.
Waal, P. de. See Kriek, H. J. S.
Wachtel, A. Longwave light-emitting zinc sulfide phosphors, P (8) 221*e*. Thallium-activated zinc sulfide phosphor, P (1) 15*d*.
Wachtman, J. B., Jr. See Peiser, H. S.
Wachtman, J. B., Jr., and Corwin, W. C. Internal friction in ZrO_2 containing CaO, (3) 82*i*.
Wacker-Chemie G.m.b.H. Basic welding powders, P (1) 3*f*. Method of applying protective silicone rubber tape covering layer to hollow glass articles, P (4) 97*j*. Process for separating solids from suspensions, P (6) 161*f*.
Wackman, P. H. See Hirthe, W. M.
Wada, K. Ammonium chloride-kaolin complexes (I) structural and bonding features; (II) release of interlayer NH_4Cl, (9) 248*a*. Intercalation of water in kaolin minerals, (6) 168*g*.
Wada, K., and Ohba, H. Factors affecting the measured value of load softening points (I) method and position of measuring temperature and atmosphere within the furnace; (II) effects of carbon rod expansion, (3) 67*h*.
Wada, K., Ohba, H., Sugita, K., and Shimada, K. Changes in the physical and chemical properties of three types of magnesia during firing at 1600°, 1800°, and 2000°C, (6) 151*h*.
Wada, S. See Yamaguchi, G.
Wada, T. Records of temperature rise after drying out new or repaired furnaces of various types, (3) 68*i*.
Waddell, B. L., and Brown, W. K. Method of making crystals and capacitors formed therefrom, P (7) 193*c*.
Waddell Dynamics, Inc. Method of making crystals and capacitors formed therefrom, P (7) 193*c*.
Wade, W. H., Teranishi, S., and Durham, J. L. Microcalorimetric estimation of the surface acidity of $NiSO_4 \cdot xH_2O$ and catalytically active Al_2O_3, (3) 83*g*.
Wade, W. L. Method of making manganese ferrite film from nitrate solution, P (11) 306*f*.
Wade, W. L., Stern, R. A., Collins, T., and Skudera, W. J. Chemically deposited ferrite films for application at millimeter wavelengths, (7) 191*c*.
Wadleigh, W. See Kahn, J. S.
Wadsley, A. D. See Roth, R. S.
Wagenfeld, W. Manufactured ware, (2) 31*j*.
Waggoner, J. H. Method of forming fibrous structures from a combination of glass fibers and cellulosic fibers, P (4) 97*b*.
Waghorne, R. H. See Delaune, L. J.
Wagner, C. Conduction and diffusion in ionic crystals, B (9) 259*e*.
Wagner, H. B. Polymer-modified hydraulic cements, (1) 2*i*.
Wagner, J. B. See Geiger, G. H.
Wagner, J. W. See Austerman, S. B.
Wagner, P. Loss of UO_2 from molybdenum-UO_2 cermets by high temperature diffusion, (3) 68*f*.
Wagner, P. W. See Alexander, J. G.
Wagner, R. Semiconductor devices with silver-gold lead wires attached to aluminum contacts, P (11) 307*h*.
Wagner, R. B. Process of making an impregnated ceramic, P (7) 189*f*.
Wagner, S. E. See Miller, G. L.
Wagner, W. A., Hamman, D. J., Palinchak, S., Stang, J. H., and Shober, F. R. Effect of space environment on materials, (2) 54*f*.
Wagstaff, F. E., and Richards, K. J. Kinetics of crystallization of stoichiometric SiO_2 glass in H_2O atmospheres, (4) 112*b*.
Wahl, E. A. Automation in material flow aided by hoppers and feeders, (2) 35*d*. Vibratory bin activator, P (9) 245*a*.
Wahlbeck, P. G., and Gilles, P. W. Reinvestigation of the phase diagram for the system titanium–oxygen, (5) 140*a*.
Wahlberg, J. S., Baker, J. H., Vernon, R. W., and Dewar, R. S. Exchange adsorption of strontium on clay minerals, (1) 21*i*.
Wahlgren, M. A. See Orlandini, K. A.
Wainer, E. Method of preparing fiber reinforced metals, P (2) 38*f*. See Lockhart, R. J.
Wainer, E., and Vukasovich, M. S. Preparation of carbide structures, P (11) 303*c*.
Wainio, A. W., and Meister, G. Electrode coating material and discharge device, P (7) 192*j*.
Waitkus, J. Rotary regenerative waste heat recovery for the glass industry, (6) 148*h*.
Wajda, R. L. See Nessim, A. A.
Wakabayashi, A. Creep of refractories, (8) 215*a*. See Katsura, K.; Ota, T.
Wakamatsu, S. Study on chemical analysis of basic slag (VI) determination of metallic iron in basic slag, (9) 246*d*.
Wakao, Y., and Hibino, T. Effects of metallic oxides on α-transformation of alumina, (4) 110*c*.
Wakefield, J. See Freck, D. V.
Wakefield Corp. Reinforced snagging wheel, P (9) 229*g*.
Wakelyn, N. T., and Jewell, R. A. Apparatus for producing high purity silicon carbide crystals, P (4) 100*b*. Method of coating carbonaceous base to prevent oxidation destruction and coated base, P (10) 274*d*.
Wal, J. van der, and Alphen, P. M. van. Sodium vapor lamp having a tin oxide coating, P (3) 64*i*.
Walberg, A. C. See Cook, C. M.
Wald, F., and Stormont, R. W. Investigations of the constitution of certain binary boron–metal systems, (11) 318*d*.
Waldbaum, D. R. Thermodynamic properties of mullite, andalusite, kyanite, and sillimanite, (1) 25*d*.
Waldo, W. H. Better Report Writing, B (6) 171*h*.
Waldorf, D. M. See Ch'in, N. C. H.
Walkden, J. R. B. Conveying and feeding glass articles into a lehr, P (9) 235*h*.
Walker, B. Enamel-sheet steel reactions, (11) 295*f*.
Walker, C. W. E. Liquid flow control device having improved surface for operative engagement with relatively moving paper machine forming wire, P (7) 190*i*.
Walker, D. G., and Hickman, B. S. X-ray line broadening in neutron irradiated magnesium oxide, (2) 54*a*.
Walker, J. A. J., and Campion, P. Continuous monitor for hydrogen in gases, (9) 245*b*.
Walker, P. L., Jr. Molecular sieves, (4) 102*d*. See Short, M. A.
Walker, R. M. See Brill, R. H.
Walker, W. A., Jr. Individual communion service glasses, P (9) 230*e*.
Walker Mfg. Co. Ceramic coated muffler with liquid flow gaps between partitions and shell, P (5) 120*a*. Ceramic coated muffler and process, P (1) 3*g*. Method of manufacturing a muffler including coating with ceramic, P (7) 179*e*. Muffler manufacturing method, P (1) 3*f*.
Walkow, A. M. See Trueb, R. E.
Wall, F. M. Industrial burner, P (3) 77*g*.
Wallace, A. V. See Miller, D. G.
Wallace, C. A. See Greenham, A. C.
Wallace, C. C., Jr. Impact pulverization-classification, P (3) 78*i*.
Wallace, G. G. See Malhotra, V. M.
Wallace, L. A. See Galer, R. E.
Wallace, L. F. Silicon carbide unipolar transistor, P (8) 222*a*.
Wallace, R. W. See Ruh, E.
Wallace, R. W., and Ruh, E. Analog calculator for solving steady-state heat flow problems, (4) 99*a*.
Wallace, T. C. See Bowman, A. L.
Wallen, E. O. L. Grinding apparatus, P (1) 18*e*.
Wallmark, J. T. Nonlinear tunnel resistor and method of manufacture, P (6) 160*i*.
Walsh, B. R. See Davis, O. A., Sr.
Walsh, J. B., Brace, W. F., and England, A. W. Effect of porosity on compressibility of glass, (1) 4*b*.
Walsh, P. N. See White, D.
Walsh, R. J. Process for producing oxides in the form of hollow shells, P (11) 303*f*.
Walter, A. See Markin, T. L.
Walter, L. S. Experimental studies on Bowen's decarbonation series (I) *P-T* univariant equilibria of the monticellite and akermanite reactions; (II) *P-T* univariant equilibria of the reaction forsterite + calcite = monticellite + periclase + CO_2, (9) 250*c*.
Walter, R. J., and Chandler, W. T. Compatibility of tantalum and columbium alloys with hydrogen, (8) 207*f*.
Walters, E. L. Sheet handling apparatus, P (2) 34*h*.
Walters, E. L., Warren, R. E., Young, O. V., and Miklosek, M. Method for surfacing glass, P (10) 269*c*.
Walters, J. P., and Malmstadt, H. V. Emission characteristics and sensitivity in a high-voltage spark discharge, (2) 44*e*.
Walther, F. H., Ryan, J. R., and Smoot, T. W. Glass furnace lining, P (4) 100*c*.
Walton, A. G. See Hlabse, T.
Walton, J. D., Jr., and Sullivan, R. R. Felted ceramics, (7) 186*g*.
Walton, R. W. See Holl, W. W., Jr.
Walworth, C. B. See Price, C. E.
Walz, A. Electric furnace, P (4) 96*f*.
Wampler, D. M. See Carson, F. J.
Wandrey, J. Development of the Craftsmen Potters' Association, (10) 261*i*.
Wang, C. H. See Wilbanks, W. H.
Wang, Chang-wen, Wang, Yun-fu, Chu, Er-chang, Huang, I-hsuan, and Chen, Yu-ying. Neodymium barium crown glass laser, (5) 139*d*.
Wang, Chao. See Chien, Ju-chung.
Wang, Cheng-yuh, and Wang, Jing-shen. Study of surface cracks on glass fibers, (8) 211*i*.
Wang, E. C. S. Method for preparing vitreous silica fibers, P (10) 269*j*.
Wang, Jing-shen. See Wang, Cheng-yuh.
Wang, S. See Thomas, G.
Wang, Wen-yee. See Huang, Dah-neng.
Wang, Yan-mou. See Tung, Shue-li; Wei, Fan-chun.
Wang, Yun-fu. See Wang, Chang-wen.
Wanie, W. Chromium as a pigment in glasses (glazes) and ceramic colors (I) the element chromium; (II) chromium compounds; (III) pink pigments; (IV) glaze for "pink red;" (V) pinks as underglaze and overglaze colors; (VI) pink coloration of glazes as a defect, (7) 190*d*. Crystalline glazes and crystal glazes (I), (6) 156*a*. Kiln furniture, (2) 36*j*. Pneumatic transport—its systems and problems, (3) 74*j*. Setting and shapes of kiln furniture, (3) 69*b*.
Wanlass, C. L., and Nelson, S. H. Ferroelectric memory element, P (10) 278*h*.
Ward, C. K. Apparatus for drawing glass, P (5) 122*d*. Apparatus for drawing sheet glass, P (3) 62*g*. Glass drawing apparatus, P (1) 6*a*. Heat exchanger for sheet glass drawing apparatus, P (8) 212*d*.
Ward, C. R., and Rau, F. J. Method and apparatus for drawing glass sheet, P (3) 63*f*.
Ward, J. J. See Alexander, C. A.
Ward, L. See Bunn, J. P.
Ward, R. See Dickson, J. G.; Longo, J. M.
Ward, R. G., and Henderson, J. Density of liquid iron oxide in noble gases and nitrogen, (5) 134*i*.
Ward, R. G., and Sachdev, P. L. Density of iron oxide-silica melts, (1) 20*d*.
Ward Leonard Electric Co. Electrical resistor, P (2) 41*g*. Metal alloy resistors, P (7) 193*h*. Resistor, P (7) 194*d*.
Wargons Aktiebolag and Topsoe, H. F. A. Catalyst for the synthesis of ammonia and method of producing same, P (6) 154*a*.
Warner, H. O. See Vassiliou, B. E.
Warner, M. M. Cementation as a clue to structure, drainage patterns, permeability, and other factors, (5) 134*d*.
Warren, R. E. See Walters, E. L.
Warren, W. C. See Lang, W. B.
Warthen, W. P. Apparatus for indicating material stream characteristics by calorimetry, P (5) 122*f*. Attenuated mineral filaments, P (4) 96*j*.
Warwick, W. H. See Johnson, R. C.
Wasag-Chemie Akt.-Ges. Method of manufacturing foamed silicate structures, P (9) 240*b*. Process for making molded vitreous porous bodies, P (8) 218*e*.
Washburn, J. See Cass, T. R.
Washington, W. Spray sulfuric acid pickling for one-coat enameling, (8) 208*c*.
Wasserman, R. D., and Quaas, J. F. Flux-cored carbide welding rod, P (11) 295*i*. Flux-coated welding electrode, P (8) 208*e*. Hard-facing electrode, P (1) 3*d*.
Watabe, S. See Sakurai, S.
Watanabe, A. See Ohashi, T.
Watanabe, H. Magnetic properties of perovskites containing strontium (II) lanthanum-strontium manganites, (4) 112*i*. See Kohra, K.
Watanabe, H., Manabe, T., Ochiai, T., Ikeda, J., and Ishiki, H. Results of measuring ladle brick erosion by radioactive isotope, (8) 216*h*.
Watanabe, H., Manabe, T., Ochiai, T., Imai, H., and Fujikake, Y. Studies on the corrosion of ladle brick and improvement in brick quality by changing the lining method, (3) 69*c*.
Watanabe, H., Manabe, T., Takahashi, Y., and Asaki, S. Comparative study on the use of fired and unfired ladle brick, (1) 8*e*.
Watanabe, J. See Kameyama, A.
Watanabe, K. See Imoto, S.
Watanabe, M. See Ikeda, T.
Watanabe, S. See Goss, N. P.
Watanabe, T. See Ando, J.
Waterbeemd, J. G. W. van de. See Van Gils, C. L. M.
Watkin, T. D. Flow measurement by infrared tracer, (9) 245*h*.
Watkins, A. E. See Certa, A. J.
Watkins, R. A. Cathode heater having an aluminum oxide and tungsten coating, P (7) 179*c*.
Watson, A. I., and Parke, S. Excitation spectrum of 1μ fluorescence of Mo^{3+} in glass, (9) 233*a*.
Watson, D. R., Hrishikesan, K. G., and Deutscher, J. S. Method of molding alumina, P (11) 302*c*.
Watson, G. G. Techniques for measuring surface temperature (I), (5) 131*j*; (II), (6) 163*f*; (III), (8) 224*b*.
Watson, J. C. Kiln shut-off device, P (7) 196*a*.
Watson, J. E. High temperature spark plug, P (4) 105*b*.
Watson, O. L. Method of and apparatus for heavy media separation, P (7) 196*j*.
Watson, P. K., and Clancy, T. M. Electron injection technique for investigating conduction processes in insulating liquids and solids, (11) 310*c*.
Watson, W. C. See Schweiker, M. A.
Watson, W. I., and Glaser, P. W. Silicon carbide recovery, P (9) 229*h*.

Watt, D. A. Theory of thermal diffusivity by pulse technique, (5) 141*h*.
Wattenbach, H. L. Spark tube having activated thermionic electrodes, P (11) 308*e*.
Watts, C. H., and Horton, R. A. Ceramic shell molds and methods of production, P (7) 188*j*.
Watts, C. H., Shields, A. A., and Krohn, H. W. Apparatus for forming ceramic shell molds, P (5) 125*g*.
Waugh, J. A. See Marzocchi, A.
Wax, G. L. Insulating container and method of making same, P (5) 123*c*.
Waxler, R. M., and Weir, C. E. Effect of hydrostatic pressure on the refractive indices of some solids, (1) 20*c*.
Waye, B. E. Dry-pressing, (5) 130*e*.
Wayt, T. R. See Grebe, J. J.
Weart, H. W. See Sarian, S.
Weaver, C. Structure and properties of dielectric films, (1) 13*j*.
Weaver, E. J. See Hinkle, J. H., Jr.
Weaver, E. P. Refractory, P (8) 218*a*. See Davies, B.; Leatham, E.; Wilson, A. B.
Weaver, E. P., and Davies, B. Burned impregnated brick, P (10) 273*a*. Refractory with improved resistance to certain slag, P (5) 126*j*. Refractory procedures, P (5) 127*a*.
Webb, B. A. Method of preventing carburization of fuel element cladding metals by uranium carbide fuels, P (2) 38*g*.
Webb, J. E. Apparatus for measuring thermal conductivity, P (6) 163*a*. GaAs solar detector using manganese as a doping agent, P (11) 306*f*.
Webb, J. M. See Mellen, E. J., Jr.
Weber, B. C. Baddeleyite of Phalaborwa (Transvaal, South Africa), (3) 77*i*.
Weber, J. N. Dehydration of diaspore at water pressures of 15 to 15,000 psi, (11) 315*h*.
Weber, J. N., and Roy, R. Dehydroxylation of kaolinite, dickite, and halloysite—heats of reaction and kinetics of dehydration at P_{H_2O} = 15 psi, (6) 166*b*.
Weber, N. Strengthened glass article and method of producing same, P (2) 34*i*.
Weber, O. Steam pressing in the structural clay products industry, (2) 35*j*.
Webster, H. K., Co. Apparatus for continuously formulating multicomponent mixtures, P (4) 106*i*.
Webster, R. K. Apparatus for continuously formulating multicomponent mixtures, P (4) 106*i*.
Webster, R. R. See Trent, R. L.
Wecht, P. Hot-blast Koppers stove with silica brick lining, (7) 186*h*.
Wecht, P., and Schulz, E. X-ray fluorescence analysis in the heavy clay industry, (5) 132*a*.
Wedag Westfalia Dinnendahl Groppel Akt.-Ges. Apparatus for the preheating of raw cement material, P (1) 3*c*.
Wege, E. Time factor in graphitization process, (9) 257*f*.
Wehner, A. Resiliently suspended screen vibrated by impact, P (2) 43*b*.
Wehr, R. L. Flat glass washer, P (10) 267*j*.
Wehr Corp. Apparatus for compressing material, P (4) 106*j*. Hammer press, P (4) 106*j*.
Wehrea, P. See Maeder, H. J.
Wei, Fan-chun, Chou, Tsai-lu, Tung, Shue-li, and Wang, Yan-mou. Carbonation chamber with adjustable CO_2 concentration and humidity, (6) 144*h*.
Weichardt, H. H. See Carvelas, J.
Weidel, R. A. Apparatus for processing a vitreous composition, P (5) 122*h*.
Weidner, A. See Moertl, G.
Weiland, W. Bodo Mans—painting with oxides, (3) 57*i*. Crackles, lava, and crystals—work of E. Michels, (1) 1*j*.
Weimer, G. What are the main difficulties in enameling plants? (3) 59*i*.
Weinberg, E. L. See Costain, T. S.
Weinberg, G. D. Parallel to the Highdown Hill glass, (2) 27*j*. *Vasa diatreta* in Greece, (4) 90*c*.
Weinberg, S. S. Ceramics and the supernatural—cult and burial evidence in the Aegean world, B (6) 172*f*.
Weindel, H. F. Castable fibrous refractory compositions and articles obtained therefrom, P (8) 217*f*.
Weiner, A. L. Keep control air dry, (1) 15*j*.
Weininger, J. L. See Grams, W. R.
Weinstein, H. Temperature compensated silicon controlled rectifier, P (11) 308*b*.
Weir, A. H. Potassium retention in montmorillonites, (3) 85*a*. See Brown, G.
Weir, C., Block, S., and Piermarini, G. Single-crystal X-ray diffraction at high pressures, (3) 85*f*.
Weir, C. E. Infrared spectra of the hydrated borates, (8) 226*g*. See Waxler, R. M.
Weir, J. R. See Martin, W. R.
Weis, J. D. See Scribner, W. G.
Weisberg, L. R. Electrical measurements for pure materials analyses, (3) 75*f*. See Tietjen, J. J.
Weisenborn, H. E. New method for reclaiming porcelain enamel frit, P (8) 207*j*.
Weiser, K., and Woods, J. F. Evidence for avalanche injection laser in *p*-type GaAs, (10) 286*a*.
Weiss, A., and Rollof, G. Role of organic derivatives of the mica type layer silicates in the formation of petroleum, B (2) 56*j*.
Weiss, A., and Rothenstein, W. Mechanism of the dehydration of kaolinite and kaolinite addition compounds, B (2) 56*d*.
Weiss, A., and Russow, J. Rolling of kaolinite crystals to halloysite-like tubes and the difference between halloysite and tube-shaped kaolinite, B (2) 56*c*.
Weiss, A., and Thielepape, W. Improvement of the technical properties of kaolinite by the formation of addition compounds, B (2) 56*a*.
Weiss, D., Kurtz, P., and Knapp, W. J. Strength of specimens containing parallel cylindrical holes, (9) 246*d*.
Weiss, E. J. See Lin, W.; Ramsey, T. H.
Weiss, G. Development of porcelain manufacture, (2) 39*d*.
Weiss, G., and Cornely, K. W. Method of molding a combustion element of ceramic fibers on a porous support, P (11) 302*c*.
Weiss, H. Means for compensating the inertia forces in jaw crushers, P (2) 47*g*.
Weiss, H., and Brand, H. Jaw crushing roller, P (4) 109*h*.
Weiss, H., and Wilhelm, M. Electronic semiconductor members and method of their manufacture, P (4) 104*f*. Galvanomagnetic semiconductor devices, P (10) 278*i*.
Weiss, W. See Schilling, G.
Weiss, W. R. See Smith, H. D.
Weissenberger, E. G. How bare wire and sheathed thermocouples compare, (4) 107*e*.
Weissmann, S., and Nakajima, K. Defect structure and density decrease in neutron-irradiated quartz, (2) 49*e*.
Weissmann, T. S. See Kling, H. P.
Weisz, R. S. Ferrite memory cores, P (5) 128*e*.
Weizmann Institute of Science. See Yeda Research & Development Co., Ltd.
Welch, J. H. See Nurse, R. W.
Weldes, H. H. W., and Derolf, M. R. Compositions of matter containing organic silicates, P (7) 190*h*.
Welker, R. H. See Ritter, G. F., Jr.
Wellborn, W. W. Inspecting abrasive grinding wheels, P (2) 27*g*.
Weller, J. F. See Gandy, H. W.
Weller, W. W. Replaceable hammer tip for hammer mills, P (11) 312*j*.
Wells, J. E., III. See Downing, J. H.
Wells, L. J. See Lusher, K. G.; Meyers, W. F.
Wellsville Fire Brick Co. Bauxite brick, P (8) 217*d*.
Welty, D. E. Luminaire, P (7) 183*d*.
Wendlandt, W. W. Thermal Methods of Analysis, B (2) 56*f*. See Simmons, E. L.
Wendle, E. F. Parison forming apparatus, P (11) 299*b*.
Wendt, P. H. Method of making clay pipe, P (6) 151*g*.
Wenig, L. See Volzer, J. B.
Wennin, E. S. Process of aging tubes, P (8) 221*g*.
Wentorf, R. H., Jr. Diamond-cubic boron nitride *pn* junction, P (10) 278*d*. High pressure method and apparatus, P (11) 308*j*. *N*-type semiconducting cubic boron nitride, P (2) 42*j*. See Bundy, F. P.
Wentorf, R. H., Jr., and De Lai, A. J. Cubic boron nitride compact and method for its production, P (5) 117*h*.
Wenzel, F. E., and Merkel, H. Method of producing III–V semiconductor compounds in crystalline form, P (11) 307*a*.
Wenzel, R. G. See Bowman, A. L.
Werner, A. E. See Bimson, M.
Werner, H. G., and Wilson, L. F. Method and apparatus for drawing sheet glass, P (4) 97*e*.
Wernick, J. H. See Treuting, R. G.
Wertz, J. E. See Kirklin, P. W.
Wertz, J. E., and Coffman, R. E. Thermoluminescent formation of Cr^{3+} in magnesium oxide, (3) 87*g*.
Wessling, B. Method of capacitor manufacture, P (2) 41*i*.
West, H. W. H., Everill, J. B., and Beech, D. G. Development of a standard 9-in. cube test for brickwork, (7) 185*a*.
West, P. Materials for deep submergence vessels—where do we stand? (2) 54*j*. Super materials get set for tomorrow's designs, (7) 203*j*. Whisker composites—where do they stand today? (2) 37*i*.
West, P. W. See Morales, R.
West, S. F. See Alexander, G. B.
Westbrook, J. H. Sources of strength and brittleness in intermetallic compounds, B (2) 55*h*. Temperature dependence of hardness of some common oxides, (11) 301*e*.
Western Electric Co., Inc. Apertured thin-film circuit components, P (10) 277*g*. Apparatus for assembling switches, P (11) 297*d*. Beta tantalum [oxide] thin-film capacitors, P (11) 305*j*. Etching of silicon and germanium, P (11) 306*c*. Heat-treating method for modifying permeability and quality factor of nickel-zinc-cobalt ferrite, P (6) 150*i*. Method and [high frequency] apparatus for measuring semiconductor volume resistivity by transmission loss in a resonant cavity, P (2) 42*a*. Methods of determining semiconductor thickness and resistivity by loss in a transmission line, P (2) 42*g*. Process for producing cadmium-bearing ferrites, P (5) 129*c*. Substrates having solderable gold films formed thereon and methods of making the same, P (4) 106*d*.
Westinghouse Air Brake Co. Cover glass for light signals, P (5) 122*b*.
Westinghouse Electric Corp. Apparatus for and preparation of silicon carbide single crystals, P (11) 311*h*. Apparatus [furnace] for producing crystalline semiconductor material, P (1) 14*e*. Apparatus for producing crystalline semiconductor material, P (8) 220*j*. Apparatus for producing crystals, P (6) 158*e*. Arsenate and phosphate phosphors, P (1) 14*f*. Baseless double-ended electric incandescent lamp, P (10) 277*i*. Calcium and magnesium silicate phosphors with activator comprising terbium, P (9) 242*j*. Cathode heater having an aluminum oxide and tungsten coating, P (7) 179*c*. Ceramic type electroluminescent device with moisture penetration prevention seal, P (11) 305*c*. Decorative electric lamp with specular coating, P (2) 33*f*. Dendrite pulling and reeling mechanism, P (1) 14*j*. Double epitaxial layer functional block, P (5) 128*b*. Electrical stress-grading coatings, P (1) 11*c*. Electrode coating material and discharge device, P (7) 192*j*. Electroluminescent devices and materials, P (1) 14*j*. Electroluminescent lamp with built-in rearwardly disposed input terminals, P (8) 221*a*. Fabricating apparatus for a vitreous lamp member, P (1) 6*j*. Formation of *pn* junctions in silicon, P (11) 306*e*. Furnace with means for adjusting a crucible in growing crystals, P (5) 132*h*. Glass-metallizing technique, P (8) 212*a*. Glass tube cooling device and method of cooling glass tubing, P (9) 236*c*. Halophosphate phosphor material of improved luminosity and maintenance characteristics for fluorescent lamps, P (8) 221*c*. Improving efficiency of infrared radiation generation by alkali metal vapor lamps and prolonging their useful lives, P (9) 243*g*. Insulated electrical members and process for producing the same, P (8) 221*d*. Integrated semiconductor tunnel diode and resistance, P (2) 41*g*. Iodine-containing electric incandescent lamp with heat conserving envelope, P (2) 41*h*. Longwave light-emitting zinc sulfide phosphors, P (8) 221*e*. Method and apparatus for semiconductor wafer handling, P (11) 306*b*. Method for making incandescent lamps, P (11) 299*d*. Method of making semiconductor devices, P (6) 159*j*. Method for processing electroluminescent phosphor, P (7) 193*b*. Phosphor, P (1) 15*b*. Piezoelectric ceramic composition of lead titanate and 0.1 to 5% (mole) calcium fluoride, P (7) 194*a*. Plural emitter semiconductor device, P (1) 15*b*. Positive temperature coefficient bead thermistor, P (1) 15*c*. Processing semiconductive material, P (11) 307*h*. Sealed articles and methods of forming the same, P (1) 15*f*. Silicon carbide unipolar transistor, P (8) 222*a*. Stress-relieved seal structure for accurate fluorescent lamp or the like, P (11) 299*h*. Thallium-activated zinc sulfide phosphor, P (1) 15*d*. Thermoelectric materials, P (9) 244*b*. Welding electrode, P (1) 3*g*.
Westman, A. E. R. Constitution of phosphate glasses, (9) 233*b*. See Murthy, M. K.
Westman, A. E. R., and Beatty, R. Equations for calculating chain length distributions in polyphosphoric acids and polyphosphate glasses, (3) 61*d*.
Weston, N. E. See Thomas, J., Jr.
Westover, R. F. New kinds of extruders, (7) 194*i*.
Westrum, E. F., Jr., and Gronvald, F. Chemical thermodynamics of the actinide element chalcogenides, B (6) 175*e*.
Westwood, W. D. See Lewis, D. C.; Sadler, A. G.
Westwood, W. D., Sadler, A. G., and Lewis, D. C. Infrared reflectivity of ferrimagnetic oxide ceramics, (6) 158*a*.
Wetzig, J. M., III. Hot top and seal signal device therefore, P (5) 126*a*.
Wexler, A. S. Determination of acetate additions in cement by gas chromatography, (11) 293*k*.
Weyl, F. G. Clay deposits in central Eifel and the determination of their extent by the electrogeophysical method, (3) 78*b*. Searching for a clay deposit by geophysical electrical methods, (6) 164*j*.
Weymueller, C. R. Materials for advanced technologies, (4) 114*i*.
Whalen, T. J. See McHugh, C. O.
Whaley, J. A. See Candelise, A.
Whaley, T. P., and Norman, V. Carbonaceous solid bodies and processes for their manufacture, P (8) 217*f*.
Whapham, A. D., and Sheldon, B. E. Radiation damage in uranium dioxide, (4) 112*g*.
Whately, T. L. See Smythe, L. E.
Wheat, L. C. Sheet material handling device, P (8) 214*b*.
Wheel Trueing Tool Co. Diamond drill bit, P (6) 143*h*.
Wheeler, M. J. Thermal conductivity of uranium monocarbide, B (6) 172*j*. See Norreys, J. J.
Wheeler, R. W. Method and apparatus for vertically supporting and heat treating a glass sheet, P (3) 64*b*.
Wheeler, W. R. Demountable metal-to-ceramic seal, P (10) 278*c*.
Wheildon, W. M., Jr. Oxide coated articles with metal undercoat, P (9) 232*d*.
Whip-Mix Corp. Investment mixer with enlarged mold supporting platform, P (7) 188*e*.
Whippey, P. W. See Faulkner, E. A.
Whipple, E. R., and Ridgley, D. H. Volumetric determination of arsenic and antimony in mixed manganese arsenide, antimonide, and phosphide compounds, (11) 310*i*.
White, A. E. S. See Billington, S. R.
White, D. See Varty, A.
White, D., Walsh, P. N., Ames, L. L., and Goldstein, H. W. Thermodynamics of vaporization of the rare-earth oxides at elevated temperatures—dissociation energies of the gaseous monoxides, B (6) 175*b*.
White, D. B. See Hodge, N.
White, E. A. D. Recent advances in crystal growing techniques, (2) 43*g*.
White, G. D. See Shalek, P. D.
White, G. K. Thermal expansion of alkali halides at low temperatures, (2) 53*f*.

White, G. K., and Anderson, O. L. Grueneisen parameter of magnesium oxide, (5) 136*f*.
White, J. See Briggs, G.; Gadalla, A. M. M.
White, J. F. See Duderstadt, E. C.
White, J. G. See Dismukes, J. P.
White, J. W. See Heller, G. L.
White, L. C. Method of attaching metallic leads to silicon layers of seimconductor devices, P (2) 41*h*.
White, R. C. Vibratory conveyor with inversion diverter, P (1) 16*d*.
White, W. B. See Berkes, J. S.; Ulmer, G. C.
White, W. B., and McIlvried, K. E. Solid solutions in the system MnO–ZnO and their possible use as pigments, (2) 51*d*.
White, W. S. Bauxite deposits of the Warm Springs district, Meriwether County, Ga., (1) 18*b*.
White, W. S., and Denson, N. M. Bauxite deposits of northwest Georgia, (11) 312*a*.
White, W. W. Gravimetric determination of germanium in germanium-rich alloys, (5) 131*i*.
Whitehead, E. C. See Skeggs, L. T.
Whitehead, J. See Jackson, P. F. S.
Whitehurst, B. M. See Booth, C. F.
Whitham, L. E. Method of crushing ores with explosive energy released in a liquid medium and apparatus therefor, P (1) 18*i*.
Whitmore, D. H. See Blumenthal, R. N.
Whitney, J. B. Method of bonding sheets of metal, P (3) 60*a*.
Whittaker, H., and Gainer, T. M. Molding methods and associated apparatus, P (6) 157*b*.
Whittaker Corp. Composite ceramic body and method of forming the same, P (1) 14*g*. Method and composition for exothermic brazing of metal joints, P (11) 296*a*.
Whittemore, D. S., and Hanson, D. C. Refractory shapes, P (5) 127*b*.
Whittemore, D. S., and Smoot, T. W. Refractory shapes, P (9) 241*a*.
Whittemore, O. J., Jr. Silicate minerals having increased surface area and absorption properties and method of preparation thereof, P (11) 303*f*.
Whitton, J. L. Removal of thin (20 A) layers of metals, metal oxides, and ceramics by mechanical polishing, (5) 140*a*.
Wichert, H. W. Heat sink for a ferrite material employing metal oxides as the dielectric material, P (7) 193*c*.
Wick, M. See Nitzsche, S.
Wickersheim, K. A. See Lefever, R. A.
Wickham, D. G. See Im, H. B.
Wickstrom, A. S. Hot top, P (10) 274*a*.
Widaj, J. See Gasiorek, S.
Widmann, H. Hydrostatic pressing, (3) 71*d*.
Wieczorowski, K., Kawalec, M., and Witkowski, H. Use of statistical quality control of glass cylinders for syringes, (11) 297*b*.
Wiedemann, T. High strength porcelains (I), (9) 241*h*.
Wieden, P. Carbonation process in sand-lime mortar, (8) 206*f*.
Wiedenmann, H. See Schilling, W.
Wiedmann, T. Studies on the circulation of material in the manufacture of electrical porcelain, (1) 12*j*.
Wiegand, H., and Schoenbrunn, G. Strength of hollow glass building blocks as affected by the material and form, (3) 62*g*.
Wiegel, E. Effect of metallic impurities on the hot leaching of silicate glasses, (3) 61*b*.
Wiegert, R. E., and Byrne, T. J. Foamed zirconia insulating materials, P (3) 70*h*. Method for preparing foamed insulating material, P (3) 70*e*. Zirconia based foam insulating material and method, P (9) 241*e*.
Wiegman, F. B. J. See Bekkering, H. M.
Wiegmann, D. See Koltermann, M.
Wienert, F. O. Grinding apparatus, P (3) 78*f*.
Wiesner, R. Method of producing a *pn* junction in a monocrystalline semiconductor device, P (9) 243*e*.
Wigginton, R. J. Manufacture of titanium dioxide, P (1) 18*g*.
Wihsmann, F. G. See Petzold, A.
Wijburg, M. A. T. Method of joining metal component parts with glass leading-in members, P (1) 14*i*.
Wilbanks, W. H. Lead-in seal for evacuated envelope of an electron discharge device [CRT] for connecting electrodes located within said envelope to a voltage source positioned outside said envelope, P (11) 306*i*.
Wilbanks, W. H., Johnson, R. H., Wang, C. H., and Erzen, F. C. Electron beam display device, P (1) 14*j*.
Wilcox, P. D., and Cutler, I. B. Strength of partly sintered alumina compacts, (6) 170*d*.
Wilcox, W. R. See Chase, A. B.; Crishal, J. M.
Wilcox, W. R., and Fullmer, L. D. Growth of $KTaO_3$-$KNbO_3$ mixed crystals, (9) 250*e*.
Wild, R. K. See Evans, T.
Wilder, A. H. See Park, R. C.
Wilder, D. R. See Manning, W. R.; Wirkus, C. D.
Wilder, D. R., and Wirkus, C. D. Oxidation-resistant coating on articles of yttrium metal, P (10) 263*i*.
Wildt, H. A., and Rundell, H. J. Process for removing chloride impurity from TiO_2 product, P (8) 225*h*.
Wiley, E. H. Electric incandescent lamp, P (1) 6*g*.
Wiley, R. F. Axially separable neck ring mold assembly, P (6) 149*d*. Glassblowing machine blowhead and article cooling tube combination, P (5) 123*b*. Tubulated hollow article forming and molding apparatus therefor, P (9) 237*d*.
Wilhelm, J. Method and system for the automatic controlling of grid coolers or traveling grids, P (1) 3*a*.
Wilhelm, M. See Weiss, H.
Wilhelm Loh K. G. Loading mechanism for machines for working on optical lenses, P (9) 236*e*.
Wilhelmi, K. A. Crystal structure of Cr_3O_{12}, (1) 19*f*.
Wilhelmi, K. A., and Jonsson, O. X-ray studies of some alkali and alkaline-earth chromates(V), (3) 87*i*.
Wilhelmsson, E. I. See Fahlstrom, P. A. H. H.
Wilkinson, W. T. See Bruce, R. H.; Dinsdale, A.
Wille, H. W., and Schlaefer, H. L. Pressure resistance of bomb tubes, (4) 94*h*.
Willenbrock, H. C. See Ruh, E.
Williams, A. E. Zircon in ceramics and refractories, (1) 10*e*.
Williams, A. L. W., and Hamlin, H. H. Piezoelectrically powered X-ray tube, P (2) 45*j*.
Williams, D. J. See Challis, L. J.
Williams, F. V. Article having a silicon carbide substrate with an epitaxial layer of boron phosphide, P (1) 14*f*.
Williams, G. H. See Carley-Macauly, K. W.
Williams, H. See Dietzel, A.
Williams, J. See Hedger, H. J.
Williams, J. R. Industrial burner, P (1) 17*j*.
Williams, L. E. See Mays, R. K.
Williams, L. S. Infiltrated oxide cermets, B (11) 320*f*. See Hickman, B. S.
Williams, N. R. Production of spheroids, P (4) 107*b*.
Williams, N. R., and George, D. Development of a process for the preparation of uranium monocarbide and of a pilot plant for UC pellet manufacture, B (6) 172*c*.
Williams, P. G. See Catherall, D.
Williams, R. Photoemission of electrons from silicon into silicon dioxide—effects of ion migration in the oxide, (9) 253*f*. Surface layer and decay of the switching properties of barium titanate, (7) 203*g*.
Williams, R. H. See Hughes, O. H.
Williams, R. S. See Bauman, H. D.; Casciani, F.
Williams, W. S. Dispersion hardening of titanium carbide by boron doping, (11) 315*h*. High-temperature thermal conductivity of transition metal carbides and nitrides, (4) 111*i*.
Williamson, G. K. Predictions of macroscopic flow characteristics from dislocation behavior in graphite, B (2) 55*g*.
Williamson, J., and Glasser, F. P. Crystallization of Na_2O·$2SiO_2$-SiO_2 glasses, (11) 296*g*.
Willis, B. T. M. Structures of UO_2, UO_{2+x}, and U_4O_9 by neutron diffraction, B (2) 55*i*.
Willmott, K. N., and Farrell, M. R. Method of preparing indirectly heated cathodes, P (2) 42*d*.
Wilson, A. B., and Davies, B. Metallurgical furnace linings, P (9) 240*j*.
Wilson, A. B., and Weaver, E. P. Refractory practices, P (2) 38*f*.
Wilson, A. J. C., Thomsen, J. S., and Yap, F. Y. Minimization of the variance of parameters derived from X-ray powder diffractometer line profiles, (10) 288*g*.
Wilson, C. P., Jr., Jones, J. B., and Ciapetta, F. G. Process for preparing a silica-alumina-magnesia cracking catalyst, P (10) 274*f*.
Wilson, D. W. See Gingerich, K. A.
Wilson, H. C. Etch rates of various enameling steels, (4) 91*f*.
Wilson, I. See Riviere, J. C.
Wilson, J., and Cook, C. G. Discharge lamp manufacture, P (7) 192*e*.
Wilson, K. M. Glastenbury Glass Factory Company, (3) 58*a*.
Wilson, L. F. See Werner, H. G.
Wilson, R. C., Jr. See Dwyer, F. G.
Wilson, R. E. Pitch-bonded refractory composition, P (5) 126*c*.
Wilson, W. A. Prospecting and development of fireclays, (8) 225*h*.
Wilson, W. J. See Blocher, J. M., Jr.
Wilson, W. L. Production of pigmentary titanium oxide, P (2) 48*a*.
Winegard, W. C. See Bell, J. A. E.
Wing, R. M. See Cotton, F. A.
Winget, J. O. See Lindstrom, R. E.
Winkel, A. Comparative dust measurements in working places in the ceramic industry and their evaluation, (10) 280*i*.
Winklepleck, R. G. See Cooper, R. S.
Winkler, E. O. See Turner, R. F.
Winners, L. See Muller, F.
Winogradow, L., and Kordek, M. Effect of vibratory grinding on some properties of feldspars, (3) 78*d*; of quartz, (3) 78*d*.
Winogradow, L., and Plewczynski, J. Effects of frit additions on properties of raw glazes for semiporcelain and earthenware, (8) 219*a*.
Winscott, F. E. See Jones, R. G.
Winter, A. Some special aspects of color change in smoky quartz, (5) 140*j*.
Winter, L., and O'Hanlon, A. Making articles of aluminum nitride, P (5) 126*a*.
Winterburn, J. A. Methods for the production of vitreous silica, P (11) 299*g*. See Jack, K. H.
Wirkus, C. D. See Wilder, D. R.
Wirkus, C. D., and Wilder, D. R. High-temperature oxidation of molybdenum disilicide, (5) 125*g*.
Wise, S. See Feder, H.
Wiseman, G., and Teferra, A. Relation between liquid limit and shear strength of soils, (3) 85*a*.
Wiseman, R. M. Splitter blender apparatus, P (4) 107*b*.
Wishnie, F. T. See Barr, L. C.; Broderick, J. P.
Wishon, B. E. See Stock, D. F.
Wishon, B. E., and Stock, D. F. Alumina refractories, P (6) 154*f*.
Wismer, M., and Bosso, J. F. Novel process for preparation of inorganic foams, (10) 272*e*.
Wissenschaftlich-Technisches Zentrum der Feinkeramischen Industrie. Process for making ceramic hotel ware, P (9) 242*b*.
Witkowski, H. See Wieczorowski, K.
Witt, F. See Vook, R. W.
Witt, W. Thin film signal translating device utilizing emitter comprising CdS film, insulating layer, and means for applying potential thereacross, P (2) 43*a*.
Wittman, A., and Nowotny, H. Crystal structure of the so-called technetium disilicide, (10) 284*b*.
Wittner, H. See Schmitt, J.
Wodtcke, F., and Jost, K. H. Reaction of anhydrous layer silicates with molten silver nitrate, and the lattice costants of Ag_2SiO_4, (3) 85*g*.
Woeckel, H. See Lehmann, H. A.
Woelk, H. Corrosion behavior of alumina- and zirconia-containing glassy phase fusion-cast refractory brick in a soda-lime glass melt, (7) 186*c*.
Woelke, C. D. See Boyd, D. R.
Wohlberg, C. See Criss, F. F.
Wohlleben, K. See Konopicky, K.
Wold, A. See Menyuk, N.
Wolf, E. Mixing device for admixing additives to a melt, P (3) 64*d*.
Wolf, F. See Ziessler, G.
Wolf, W. P. See Ball, M.
Wolfe, K. J. B. See Beattie, J. R.
Wolff, R. G. Infrared absorption patterns (OH region) of several clay minerals, (1) 22*i*.
Wolfke, S. Investigation of the chemical composition and of the phases of soluble substances occurring in typical brick clays (I), (8) 225*e*; (II), (11) 300*d*. Theoretical calculation of the permissible content of soluble sulfates in heavy clay bodies, (2) 35*j*.
Wollank, G., Eckerlin, P., and Stute, J. Electric incandescent lamp, P (7) 192*f*.
Wollast, R. Chemical aspects of the mode of formation of bauxite in the Lower Congo, (9) 248*c*. See Keyser, W. L. de.
Wolstenholme, S. See Everglades, Ltd.
Womeldorph, R. C. See Veazie, F. M.
Wondratschek, H., Merker, L., and Mueller, P. F. Behavior of holes in glass plates on heating—flow phenomena in glasses under the influence of surface tension, (8) 208*j*.
Wones, D. R., and Eugster, H. P. Stability of biotite—experiment, theory, and application, (9) 256*h*.
Wonn, G. C. See Leary, J. A.
Wood, A. A. R. See Bull, G. H.
Wood, A. A. R., Timms, P. L., and Bull, G. H. Production of titanium diboride, P (7) 189*f*.
Wood, D. C. See Ainsley, R.
Wood, D. L. See LeCraw, R. C.
Wood, D. L., and Ballman, A. A. Blue synthetic quartz, (11) 314*a*.
Wood, D. L., and Remeika, J. P. Optical transparency of rare-earth iron garnets, (9) 252*h*.
Wood, G. W., and Lloyd, H. L. Fuel [gas] burner with adjustable nozzle, P (5) 132*g*.
Wood, W. G. E., and Thomas, P. B. Method of constructing a nuclear reactor core from graphite blocks, P (2) 38*c*.
Woodcock, R. F. Fiber optical image transfer devices and method of making the same, P (2) 33*h*. Fiber type light transferring devices and method of making the same, P (4) 96*g*. Method for making fiber optical devices, P (2) 34*h*.
Woodcock, R. F., and Bazinet, W. P., Jr. Method of making glass clad energy-conducting fibers, P (8) 213*h*.
Woodhall, W. Manufacture of oxides, P (5) 133*e*.
Wooding, W. H. See Reilley, J. M.
Woodrooffe, H. M. See Malhotra, V. M.
Woodruff, R. W. See Davies, B.
Woods, J. A. See Badger, A. E.
Woods, J. F. See Weiser, K.
Woodward, R. M. See Slayter, G.
Woodward, R. M., and Satterfield, E. L. Lamellar structure, P (7) 183*d*.
Worthington, P. See Adams, R. V.
Wright, H. D., Barnard, W. M., and Halbig, J. B. Solid solution in the system ZnS–ZnSe and PbS–PbSe at 300°C and above, (9) 255*g*.
Wright, R. D. Corrosion of fusion cast and high alumina refractories by white opal glass, (2) 36*e*.
Wright, W. J. See Rotsey, W. B.
Wuensch, B. J., and Prewitt, C. T. Corrections for X-ray absorption by a crystal of arbitrary shape, (7) 198*a*.
Wuensch, B. J., and Vasilos, T. Origin of grain-boundary diffusion in MgO, (9) 252*i*.
Wuerker, R. F. See Brooks, R. E.
Wulff, J. See Rauch, G. C.
Wunnik, J. van. See Phelps, G. W.
Wurst, E. C., Jr. See Johnson, R. E.
Wurst, J. C., Hjelm, L. N., and James, D. R. Standard tests needed for high-temperature protective coatings, (6) 146*e*.
Wurttembergische Metallwarenfabrik. Method for the production of an improved metal/ceramic material and articles, P (5) 120*a*.
Wuttig, M. Grain-boundary diffusion of Ni^{2+} in MgO, (3) 82*d*.
Wyandotte Chemicals Corp. Stabilization of calcium carbonate slurries, P (7) 178*d*.
Wyatt, A. F. G. See Ball, M.
Wyckoff, R. W. G. Crystal Stuctures (Vol. 3), B (11) 319*f*.

Wyllie, P. J., and Raynor, E. J. DTA and quenching methods in the system $CaO–CO_2–H_2O$, (11) 315*j*.
Wynne-Jones, W. F. K. See Marsh, H.
Wyss, A. Early history of the Roirant machines, (6) 144*a*. Type AW 45 single-mold machine with electrical control, (4) 95*h*.
Wyss, R. L. Meissen porcelain in the Historical Museum of Berne, (3) 58*b*. Swiss majolica from Winterthur, (3) 58*b*.

Xan, Wen-ching. See Ke, Wen-min.
Xerox Corp. Photoconductive cadmium sulfide powder and method for the preparation thereof, P (5) 129*c*.

Yakimenko, L. F. See Vasyutinskii, B. M.
Yakovleva, K. P. See Okhotin, M. V.
Yakovleva, N. G. See Borovik, E. S.
Yakunina, V. M. See Fedorov, P. I.
Yamada, H. See Horibe, T.
Yamada, H., Hamano, K., and Kuroda, Y. Reaction between Fe_2O_3 and MgO and its effect on the sintering of MgO, (5) 140*g*.
Yamada, H., and Kimura, S. Coprecipitation of alumina and silica gels and their transformation at higher temperatures, (5) 134*d*. Nature of mullite formed from the coprecipitate of alumina and silica gels, (5) 139*b*.
Yamada, M. See Kato, M.; Minowa, S.
Yamada, T. See Machida, J.; Ozawa, U.
Yamadaya, T. See Okada, T.
Yamaguchi, G., Ono, Y., Kawamura, S., and Soda, Y. Differential thermal analysis and high temperature powder X-ray diffraction of $2CaO·SiO_2$, (5) 135*f*. Synthesis of the modifications of Ca_2SiO_4 and the determination of X-ray powder diffraction patterns, (2) 29*a*.
Yamaguchi, G., Uchikawa, H., and Kawamura, S. Influence of sodium oxide on the formation and the crystal structure of tricalcium silicate solid solution in the system $CaO–SiO_2–Al_2O_3–Fe_2O_3$, (5) 137*j*.
Yamaguchi, G., Yanagida, H., Ono, S., Soejima, S., and Wada, S. Method for growing single crystals of corundum under hydrothermal conditions, (9) 244*g*.
Yamaguchi, J. See Horiuchi, S.
Yamaguchi, T. Fundamental study on ferrite manufacturing process (IV) grain growth in ferrites (continued), (6) 157*i*. Galvanomagnetic properties of glassy carbon, (4) 111*f*.
Yamakov, I. See Jamakov, I.
Yamamoto, H. See Ohba, H.
Yamamoto, K. See Imoto, S.; Karube, N.
Yamamoto, M. See Iwata, M.; Nakamichi, T.
Yamamoto, R. See Kato, S.
Yamamoto, T. See Ota, T.
Yamashita, H. See Ibuki, S.
Yamashita, I. See Aihara, M.
Yamashita, S. Results of using 42 to 44% Al_2O_3 brick for ladle bottom, (3) 69*a*.
Yamashita, T. See Kitamura, S.
Yamauchi, S. See Matsumoto, H.
Yanagi, T. See Kawakubo, T.
Yanagida, H. See Yamaguchi, G.
Yanagihara, Y. See Morita, S.
Yanase, A. See Kubota, B.
Yancey, H. F., and Geer, M. R. Behavior of clays associated with low-rank coals in coal-cleaning processes, (9) 247*b*.
Yang, J. C. Method of applying silicate to wet asbestos-slag cement sheets after formation but prior to consolidation of such sheets, P (11) 302*g*. See Redican, F. W.
Yang, Kuo-ching, and Yen, Tung-sheng. Kinetics of phase transformation of alumina, (9) 251*h*.
Yang, L. See Carpenter, F. D.
Yanshin, S. I. See Pivovarov, L. Kh.
Yap, F. Y. See Wilson, A. J. C.
Yarembash, E. I., and Vigileva, E. S. Interactions of the selenides of bismuth and arsenic, (1) 22*i*. Interactions of the tellurides of bismuth and arsenic, (1) 22*j*.
Yarembash, E. I., Vigileva, E. S., Eliseev, A. A., and Antonova, L. I. Tellurides of lanthanum, (10) 291*g*.
Yaremenko, Z. A. See Tresvyatskii, S. G.
Yariv, A. See Nassau, K.
Yariv, Sh. See Bodenheimer, W.
Yarnell, J. L. See Bowman, A. L.
Yaroslavtseva, I. A. See Nyankovskaya, R. N.
Yasinskaya, G. A., and Groisberg, M. S. Interaction of titanium boride with niobium and tungsten, (1) 22*f*.
Yasinskaya, G. S. See Samsonov, G. V.
Yasunaga, K. See Higuchi, S.
Yasunami, K. Very high pressure apparatus, P (9) 245*a*.
Yatabe, Shun-ichi. See Moriya, T.
Yates, B. See James, B. W.
Yates, G. See Batey, W.
Yates, P. C. See Alexander, G. B.
Yavorsky, P. J. Properties and high temperature applications of zirconium oxide, (1) 9*f*.
Yazima, T. See Nakazumi, Y.
Yeakley, L. M. See Lindholm, U. S.
Yeaple, F. Fluid amplifiers go commercial, (2) 44*h*.
Yeasting, M. C. Apparatus for conveying powdery material [by vibration], P (4) 106*i*.
Yeda Research & Development Co., Ltd., and Weizmann Institute of Science. Fluorine containing spinel-type ferrites, P (4) 104*h*.
Yedavalli, B. V. S., Bose, A. K., Prasad, T. V., and Rao, H. V. B. Effect of certain constituents of high alumina cements on their properties, (2) 28*d*.
Yen, L. C., and Alexander, R. E. Estimation of vapor and liquid enthalpies, (1) 21*h*.
Yen, Tung-sheng. See Kuo, Chu-kun; Yang, Kuo-ching.
Yeo, Loy Meng. See McCartney, E. R.
Yerouchalmi, D. Material structures and testing for open-cycle MHD conversion, B (6) 173*d*.
Yevfimovskii, I. V. See Gubskaya, G. P.
Yevtushchenko, L. A., and Levitin, R. Z. Anomalies in the modulus of elasticity in shear of the antiferromagnetic materials MnO, CoO, and Cr_2O_3, (10) 283*h*.
Yocom, P. N. See Larach, S.
Yocom, P. N., Kestigian, M., and Goldsmith, G. J. Alkaline earth halide divalent dysprosium laser materials, P (6) 158*c*.
Yocom, P. N., and Thomsen, S. M. Process for preparing luminescent [silicate] materials, P (1) 15*c*.
Yokokawa, T. See Conroy, L. E.
Yonemitsu, H. See Hasiguti, R. R.
Yorke Scientific Corp. Crystal puller, P (5) 128*a*.
Yoshida, H., and Ninomiya, H. Comparative study of the Japanese soft nozzle and the American nozzle, (1) 8*d*. Comparative study on the results of using American stopper heads and their transformed Japanese counterparts, (1) 8*d*.
Yoshida, H., Ninomiya, H., and Kadota, Y. Relations between sonic property of stopper heads and results of its practical use, (8) 216*g*.
Yoshida, I. Thermal conduction in ferroelectric ceramics, (10) 277*a*.
Yoshida, N., and Fukunaga, J. Mineralogical studies on Izumiyama pottery stone, (1) 18*g*.
Yoshihara, H. Comparison of brick laid vertically and horizontally for ladle linings (I), (1) 8*j*; (II), (7) 185*i*. Condition of used siliceous ladle brick, (7) 186*a*. Results of ramming clinker made of dead-burned Korean dolomite on the floor of an open-hearth furnace, (8) 216*h*. Results of service tests on brick used for lining the ladle wall and bottom, made to find the average degree of corrosion, (3) 68*j*.
Yoshihara, T. See Maeno, M.
Yoshikawa, H. H. High temperature radiation effects in lampblack-based graphites, (4) 111*i*.
Yoshimatsu, M. Polygonization of bent LiF crystals by the Berg-Barrent method, (10) 289*f*.
Yoshimori, T. See Miwa, T.
Yoshino, H. See Nameishi, N.
Yost, M. C. See Osborn, R. H.
Youman, S. Ultrafinish grinding of carbide, (7) 177*g*.
Young, C. J. T. Apparatus for indicating presence of predetermined color in sample, P (1) 17*d*.
Young, D. R. See Maissel, L. I.
Young, E. J. Critique of methods for comparing heavy mineral suites, (8) 223*b*.
Young, H. F. Glass lined fitting and process for glass lining of pipe fitting, P (5) 120*a*. See Bange, G. R.
Young, J. A., and Lucas, R. T. Process for molding a glass fiber aerosol filter, P (7) 184*f*.
Young, J. R. Ceramic coated muffler and process, P (1) 3*g*.
Young, O. V. See Walters, E. L.
Yudin, I. A. See Loshkarev, B. A.
Yudin, N. A., and Nikonov, N. P. Industrial melting of glasses colored with rare-earth elements in the form of concentrates and ores, (4) 93*e*.
Yudin, N. A., and Syritskaya, Z. M. Synthesis and study of glasses for tableware using rare-earth elements, (7) 181*i*.
Yudin, V. F. See Voronin, N. I.
Yudkovskii, S. I. See Funke, V. F.
Yurchenko, B. D. See Kunin, N. F.
Yur'eva, E. K. See Gendelev, S. Sh.
Yushina, L. D. See Neuimin, A. D.
Yushina, L. D., and Pal'guev, S. F. Transport numbers in systems $CeO_2–BeO$, $CeO_2–MgO$, $CeO_2–CaO$, and $CeO_2–SrO$, B (1) 26*b*.
Yust, C. S. See Potent, L. E.
Yuza, H. See Saito, S.

Zabinska, T. Assessment of the quality of Korvisit blocks by ultrasonics, (11) 300*i*.
Zablotny, W. See Akerman, K.
Zackay, V. F. (editor). High-Strength Materials—Proceedings of the Second Berkeley International Materials Conference Held at the University of California, June 1964, B (2) 55*d*.
Zadron, E. Frangible [ceramic] welding plug, P (1) 11*e*.
Zadumin, O. S. See Makhnavetskii, A. S.
Zagar, L. Thermal conductivity of refractory materials according to measurements by V. V. Pustovalov, (9) 239*b*.
Zagorcheva, E., and Angelov, B. Properties of Bulgarian mineral [silicate] fibers, (5) 125*a*.
Zagray, H. F. Metal channels and frames for walls formed of interlocking building blocks, P (5) 124*k*.
Zagyvai, I. See Erdey, L.
Zaionts, L. A., and Rogozhin, Yu. V. Investigation of acid corrosion of Pyrex-type glass, (8) 209*g*. Investigation of kinetics of dehydration of glasses by method of thermography, (1) 4*a*.
Zaionts, R. M., and Pankratova, G. F. Cordierite kiln furniture from fireclays and magnesite, (6) 152*a*.
Zaitseva, N. D. See Vasil'kova, I. V.
Zak, T. J. See Apple, J. M.
Zakarka, A. See Babonas, G.
Zakharchenko, M. A., and Aslanov, S. M. Ternary system of the chlorides of lithium, sodium, and barium, (10) 291*j*.
Zakharchenko, M. A., and Gontar, K. V. Ternary system of the chlorides of lithium, potassium, and barium, (5) 141*g*.
Zakharchenko, M. A., and Mkrtchyan, S. M. Ternary reciprocal system of the bromides and nitrates of sodium and barium, (10) 291*j*.
Zakharenko, N. I. See Tsaritsyn, M. A.
Zakharikov, N. A., and Blokh, S. A. Rapid drying of porcelain, (2) 39*g*.
Zakharikov, N. A., and Kononko, V. P. Controlling the annealing of sheet glass, (4) 92*a*.
Zakharikov, N. A., Rozhanskii, A. I., and Sukhovei, V. A. Evaporative cooling of the walls of glass tanks, (4) 93*f*.
Zakhar'ina, T. N. See Makhnavetskii, A. S.
Zalizniyak, A. A. Glass tank furnace without a conditioning tank, (10) 265*a*.
Zaplatynsky, I. Observations on zeta phase in the system Ta–C, (3) 84*f*.
Zaporozhtseva, O. K., and Gorbai, Z. V. Use of $Al(OH)_3$ in melting plate glass drawn without a debiteuse, (10) 267*c*.
Zapp, A. D. Bauxite deposits of the Andersonville district, Georgia, (3) 77*j*.
Zapp, A. D., and Clark, L. D. Bauxite in areas adjacent to and between the Springvale and Andersonville districts, Georgia, (5) 132*i*.
Zapp, F. Improving the strength of hard porcelain, (3) 71*d*.
Zappia, A. T., and Bough, M. O., Jr. Lehr loader, P (6) 150*d*.
Zarembowitch, A. Theoretical study and optical determination of the elastic constants of single crystals, (7) 203*b*.
Zaromb, S. Apparatus and method for separating slurries into solid and fluid components, P (1) 18*b*.
Zartman, R. E. Geochronologic study of the Lone Grove pluton from the Llano Uplift, Texas, (11) 317*e*.
Zarubitskaya, A. N. See Murav'ev, V. I.
Zaslavsky, D., and Kinsky, J. F. New method for measuring bulk density of soil and porous stones, (6) 162*g*.
Zaucha, P. A. Support and drain tile, P (4) 98*i*.
Zauner, O. Method of and apparatus for reshaping glass tubes, P (9) 236*i*.
Zavarzina, E. I., and Kordonskaya, R. K. Causes of glaze failure on battery tanks, (2) 39*c*.
Zavasnik, F. J. Apparatus for determining rheological properties, P (6) 163*a*.
Zeblisky, R. J. See Schneble, F. W., Jr.
Zecca, J. J. See Preziosi, L. M.
Zecchin, L. Glass recipes of Montpellier, (4) 89*j*. In "Rio dei Verieri" between 1564 and 1575, (8) 206*c*. Nineteenth-century Muranese recipe book, (3) 58*c*. Origin of glassmaking at Altare, (8) 206*a*.
Zedginidze, E. N. See Kutateladze, K. S.
Zednicek, W. See Moertl, G.
Zega, B. See Luescher, J.
Zegzhda, D. P., Arzumanov, M. A., Levitas, E. G., and Frolova, A. I. Properties of chamotte obtained by firing certain clays in rotary kilns, (5) 124*k*.
Zeiger, H. J. Electrons and holes in semiconductors, B (9) 259*f*.
Zeiger, H. J., Keyes, R. J., Krag, W. E., Lax, B., McWhorter, A. L., Quist, T. M., and Rediker, R. H. Semiconductor infrared maser, P (9) 244*c*.
Zeitman, S. A. See Pritchard, C.
Zelentsov, V. V. Stereochemistry of inner complex compounds of copper and vanadium having anomalous magnetic properties, (4) 113*d*.
Zellers, J. T., Jr. Apparatus for forming sheet glass, P (9) 235*c*. Apparatus for producing sheet glass, P (6) 149*a*. Glass furnace with muffle lip-tile, P (6) 150*a*. Glass sheet support roll, P (1) 6*d*. See George, J. E.
Zener, C. Principles of energy conversion, B (9) 259*g*.
Zenith Radio Corp. Ceramic microphone, P (8) 220*d*.
Zentrale Forschungsstelle fuer die Kali-Industrie Beim VEB Kaliwerk "Gluckauf" Sondershausen. Process for the production of magnesium oxide from magnesium chloride hydrate, P (11) 303*g*.
Zerlant, G. A., and Krupnick, A. C. Integrating-sphere reflectometer for the determination of absolute hemispherical spectral reflectance, (11) 310*i*.
Zezin, M. A., Rakov, I. D., and Popov, N. T. Automatic control of the flame reversal in tank furnaces, (4) 92*c*.
Zhdanov, G. S. See Ivanova, V. V.
Zheleztsov, V. A. See Barsukova, N. F.
Zheleztsov, V. A., and Barsukova, N. F. Recording apparatus for determining optical distortions in glass sheets, (5) 121*i*.
Zheludev, I. S. See Sonin, A. S.
Zhitomirskaya, E. Z. See Brekhovskikh, S. M.
Zhmud', E. S., Ivanova, A. B., Kotlyar, A. A., and Ostapchenko, E. P. X-ray study of melts in the system $BaO–GeO_2$, (2) 54*c*.
Zhukov, A. V., and Kamenetskii, S. P. Very light heat- and sound-insulating inorganic materials and their application, (7) 188*d*.
Zhukovskii, V. M., Vlasov, V. G., and Lebedev, A. G. Electrical properties in the range UO_3 to U_3O_8, (11) 316*b*. Electrical properties of the system uranium–oxygen in the composition range U_3O_8 to UO_2, (11) 316*b*.
Zhurakovskii, E. A., and Dzeganovskii, V. P. X-ray spectral investigation of the homogeneity region of titanium nitride, (10) 291*j*.
Zhuravlev, A. K. See Pavlushkin, N. M.
Zhuravleva, R. A. See Litvinov, P. I.

Ziegler, G. Zone melting gallium in a recycling arsenic atmosphere, P (9) 244*e*. See Miederer, W.
Ziegler, W. T. See Godbee, H. W.
Ziemba, B. See Grochowski, F.
Ziemba, W. Glass fabrics for the purification of combustion gases in the cement industry, (11) 296*f*.
Ziemke, M. C. See Snyder, E. F.
Ziessler, G., and Wolf, F. Surface deformation in large astronomical mirrors, (2) 32*c*.
Zijlstra, H. See Hokkeling, P.
Zimar, F. See Martin, F. W.
Zimmerman, C. A. See Veo, L. E.
Zimmerman, R. E. Abrasive articles with iron sulfide and potassium aluminum fluoride filler, P (7) 177*h*.
Zimmermann, E. Method for flame cutting and sealing planar ends of a glass container, P (2) 34*e*.
Zimmermann, G. See Jenemann, H.
Zimmermann, K. Color designation of fired clays, (3) 75*d*.
Zine, A. R., Jr. See Tomb, W. H.
Zink, J. S. See Reed, R. D.
Zink, John, Co. See John Zink Co.
Zinov'ev, A. A. See Krivtsov, N. V.
Ziolkowski, D. See Bretsznajder, S.
Zirngibl, H. Process for the working up of hydrolysis acids obtained in the production of titanium dioxide, P (1) 19*b*.
Zirngibl, H., and Kappey, H. J. Process for the decomposition of titanium dioxide-containing minerals with hydrochloric acid, P (5) 133*j*.
Zitkeviciute, I., and Aleinikov, F. K. Resistance to alkali of some silicate glasses (III) interaction between surface deposit and sodium hydroxide solution, (8) 210*c*.
Zitkeviciute, I., Aleinikov, F. K., and Slizys, V. Resistance to alkali of some silicate glasses (II) investigation of alkali etched glass surfaces by electron microscopy, (8) 210*c*.
Zitkeviciute, I., Molchanov, V. S., and Aleinikov, F. K. Resistance to alkali of some silicate glasses (I) dependence of alkali resistance on glass composition, (8) 210*c*.
Zlochevskaya, K. M. See Budnikov, P. P.
Zlomanov, V. P., Popovkin, B. A., Tananaeva, O. I., and Novoselova, A. V. Study of some properties of the selenite and oxyselenites of lead, (2) 52*c*.
Zmii, V. I. See Ivanov, V. E.
Znachko-Yavorskii, I. L. History of Cementing Materials from Antiquity to the Middle of the Nineteenth Century, B (7) 204*f*.
Zneimer, J. E. See Nielsen, J. W.
Zoerb, H. M. See Gasparac, R. J.
Zoldners, N. G. See Malhotra, V. M.
Zolotarev, E. K., and Kalinina, V. E. Change in thermodynamic functions on hydration of trivalent cations of lanthanides, (4) 109*j*.
Zolotarev, I. S. See Bobrova, T. N.
Zonneveld, P. van. Apparatus for melting glass with charging means, P (7) 182*i*.
Zorina, G. V. See Syritskaya, Z. M.
Zott, H. See Glenk, H.
Zubekhin, A. P. See Ponomarev, I. F.
Zubler, E. G. See English, J. F.
Zubova, S. K. See Chernyak, M. G.
Zuercher, E. M. See Hardinge, H.
Zukowski, K. Method and device for sealing together glass parts, P (11) 298*i*.
Zumaquero, F. J. Process for rendering ceramics slightly conductive, P (4) 106*c*. See Budde, M. C.
Zumwalt, L. R. Unpurged fuel element, P (11) 303*j*.
Zumwalt, L. R., Gethard, P. E., and Anderson, E. E. Fission-product release from monogranular UC_2 particles, (3) 67*j*.
Zurheide, G. B. See Green, F. H.
Zuzelo, E. A. Abrasive tool, P (7) 177*f*.
Zvorykin, A. Ya. Some inorganic polymers based on rubidium phosphate, (1) 25*b*.
Zvyagin, B. B. Structural modifications of the layer silicates and possibilities of their determination by means of electron and X-ray diffraction, B (2) 56*b*.
Zwart, H. C. Errors in humidity measurements, (10) 281*b*.
Zwicker, J. D. Sieve analysis to below two microns using micromesh sieves, (9) 245*j*.
Zykova, Z. K. See Bluvshtein, M. N.

SUBJECT INDEX TO CERAMIC ABSTRACTS FOR 1966

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position on the page. For more complete indexing of papers published in the *Journal of The American Ceramic Society* and the *American Ceramic Society Bulletin*, see indexes to the *Journal* and the *Bulletin*.

Ablation, in high shear environment, (10) 263*c*.
  melting, about decelerating spherical bodies, (4) 99*e*.
  properties, of refractories, (1) 7*i*.
Abrading apparatus. See *Grinding apparatus.*
Abrasion, resistance, of ceramic-bonded and fused cast refractory brick at high temperatures, (1) 9*a*.
Abrasives. See also *Aluminum oxide; Carbides; Diamonds; Grinding apparatus; Polishing apparatus; Silicon, carbide.*
  article, backed with stretchable-compressible material, P (2) 27*f*.
  on flexible backing, P (7) 177*i*.
  with iron sulfide and potassium aluminum fluoride filler, P (7) 177*h*.
  with zirconium tetrafluoride filler, P (11) 293*f*.
  blasting, to treat surfaces to be enameled, (4) 91*b*.
  brown electrocorundum, change of strength by heat treatment, (5) 117*f*.
  coated, P (10) 261*f*.
  cloth, flexible, P (5) 117*f*.
  selection for enameling, (4) 91*c*.
  supersize film forming resins on, P (8) 205*g*.
  compact, cubic boron nitride and method of production, P (5) 117*h*.
  cutting disk, and method of making, P (3) 57*f*.
  cutting tools, microstructure in, (1) 1*h*.
  disk, and magnetic holder, P (4) 89*g*.
  disks, ribbon dispenser for, P (10) 261*f*.
  epoxy resin structures, P (4) 89*f*.
  flap-type device, P (6) 143*g*.
  grains, coated, P (11) 293*f*.
  cold-pressing high density resin coated, P (1) 1*h*.
  sizing of, (7) 177*f*.
  why do they cut? (6) 143*h*.
  leaves, method of fabricating, P (1) 1*g*.
  molded rotatable, internal reinforcement, P (10) 261*g*.
  powders, grain strength of, (5) 117*g*.
  products, mounting for, P (9) 229*f*.
  rotary tool, P (7) 177*f*.
  sandpaper cot, P (3) 57*g*.
  sheet, resin bonded, P (8) 205*h*.
  sintered alumina, shear strength to interpret friction processes, (9) 229*g*.
  sponge, P (8) 205*g*.
  stone, resilient-backed, P (4) 89*g*.
  surfaces, method of producing, P (1) 1*g*.
  tester for, P (4) 108*b*.
  tool structure, P (7) 177*h*.
  volume fractions, of grains, bond, and pores for grinding wheels, (4) 89*f*.
  wear, mechanisms of sapphire on steel, (5) 119*g*.
  wheels. See *Grinding apparatus.*
Absorption, of Al_2O_3, on sheet glass, (8) 208*g*.
  atomic, quantitative analysis by, (1) 17*a*.
  bands, in crystalline α-quartz, (6) 170*b*.
  bands, assignment of infrared in silicates, (3) 84*b*.
  capacity of building brick, effect on bearing strength of masonry, (10) 270*d*.
  coefficient, and wavelength dependence of quantum efficiency in $ZnSiO_3$/Mn powder phosphor, (4) 114*h*.
  of electrons in MgO crystals, effect of inelastic scattering on, (4) 110*c*.
  measurement of anomalous of electrons for MgO crystals, (10) 288*d*.
  edge, effect of pressure and temperature on CdTe, (3) 81*g*.
  intrinsic of CdTe under hydrostatic pressure, (9) 251*f*.
  optical, of barium titanate, (9) 252*d*.
  in Se crystals, effect of temperature on optical, (3) 81*f*.
  of ZnS polytypes determined, (1) 20*g*.
  gamma-induced, of arsenic borate glass, (9) 233*e*.
  gamma-radiation, to determine bulk density and density variations in glass tank, (6) 152*d*.
  infrared, band of arsenic-sulfur glasses, (7) 180*d*.
  band in glasses, (7) 180*f*.
  defect-activated one-phonon in diamond coat, (3) 84*e*.
  of lead potassium pyrosilicate, lead potassium pyrogermanate, and their solid solutions, (8) 227*e*.
  by oxide impurities in glass, (11) 296*j*.
  patterns (OH region) of clay minerals, (1) 22*i*.
  in single crystal stannic oxide, (5) 137*b*.
  template to characterize bonds of silicate minerals in OH region, (7) 203*c*.
  of iron, in silicate and borate glass, (3) 61*e*.
  optical, of heat treated Si, (10) 289*d*.
  radiation induced in quartz and silica, (4) 112*i*.
  of reduced $BaTiO_3$ single crystal, (10) 289*b*.
  relation to thermoluminescence in borate glasses, (5) 120*i*.
Absorption (*continued*)
  order/disorder and infrared, systems $MgAl_2O_4$-Al_2O_3 and $MgAl_2O_4$-$LiAl_5O_8$, (3) 84*f*.
  of sound waves, in dielectric crystals, (2) 48*e*.
  spectra. See *Spectra.*
  ultraviolet, topography of diamonds, (7) 203*g*.
  water, of granular materials, (9) 246*a*.
  of water, rate in bricks, (7) 184*j*.
  X-ray, by crystal of arbitrary shape, corrections for, (7) 198*a*.
Accelerometers, (3) 75*d*.
Acids. See also specific types.
  boric, reaction with sintered magnesia, (10) 272*h*.
  boric, system. See *Systems.*
  chloranilic, spectrophotometric determination of sulfur in glass as, (3) 60*h*.
  fatty, complexes of Ca montmorillonites with, (9) 248*f*.
  fluorides, mechanism of solution of zircon in, (9) 252*c*.
  mandelic, to determine zirconium in zirconium metal and powder, (11) 309*j*.
  mixed H_3PO_4 and H_2SO_4, crystal growth and transition rate of $CaSO_4 \cdot 2H_2O$, (11) 315*a*–*c*.
  organic, effect of setting time of gypsum plaster, (9) 230*i*.
  rosin, contact angles of water on solid surfaces of, and abietic and primary series and technical, B (7) 204*f*.
  silicic, determination of small quantities, (3) 75*j*.
  solutions, formulas of sexivalent and quadrivalent uranium ions in, (7) 201*h*.
  sulfurous-caustic purification process, for production of alumina from clay, (9) 247*e*.
Acoustics. See also *Insulation, acoustical; Sound.*
  method, for nondestructive testing of fireclay brick, (1) 7*j*.
  pulses, propagation and reflection of slant-mode in quartz, (10) 289*j*.
  thermal analysis, possibilities of use, (10) 286*j*.
Actinide, element chalcogenides, chemical thermodynamics of, B (6) 175*e*.
  monocarbide, preparation of, P (7) 189*c*.
  oxide-actinide nitride eutectic compositions, and their method of manufacture, P (4) 99*i*.
  oxide particles, coating with zirconia sols, P (5) 126*d*.
  oxides, sols of zirconia and hafnia with, P (10) 283*e*.
Adhesion, of enamel on steel, factors affecting, (6) 145*d*.
  mechanism, of molybdenum-manganese metallizing layers on corundum, (6) 157*d*.
Adhesives, for extreme temperatures, (2) 54*e*.
  patching composition, P (8) 207*d*.
  for refractories, P (11) 302*a*.
Adsorption, behavior, of carbon films, (3) 79*f*.
  of coordination complexes, on silica gel, (3) 79*g*.
  data, calculation of pore size distribution from, (11) 310*h*.
  exchange, of Sr on clay minerals, (1) 21*i*.
  of helium, by carbonaceous solids, (4) 109*i*.
  of impurity, hole formation in surfaces by, (3) 82*j*.
  interlayer, thermodynamics of water in clays, (4) 114*c*.
  of phosphate ions, by Egyptian clays, (6) 165*a*.
  physical, analysis in ultra-high-vacuum range, (9) 248*c*.
  under irradiation, of oxygen and carbon monoxide on alumina, (11) 313*f*.
Aerosols. See *Colloids.*
Aerospace. See *Space.*
Agglomeration, coagulation, solutions to equations for kinetics of, (4) 113*b*.
Aggregates, apparatus to make, P (9) 237*f*.
  in concrete, reaction involving nondolomitic limestone, (9) 231*a*.
  Danish, experiments on mortar bars prepared with, (8) 207*a*.
  effect, on elasticity of concrete and cement paste and mortar, (2) 28*i*.
  glassy, for roads, P (10) 263*a*.
  lightweight, automation of production in Kingston, N. Y., (2) 35*d*.
  gas producing agents in production of, (9) 237*f*.
  preparation of coal refuse for, (7) 185*c*.
  process for making, P (1) 7*k*; P (2) 36*a*.
  shale fines reclaimed at plant for, (4) 98*f*.
  soft alluvial clay as raw material, (6) 151*g*.
  polycrystalline, theoretical distortion under stresses, (1) 25*i*.
  properties, effect on concrete shrinkage, (2) 28*g*.
Air, cleaning, electrostatic dust removal, (11) 308*i*.
  for control, methods to keep dry, (1) 15*j*.
  pollution, abatement in ceramic industry, (10) 292*b*.
  pollution control, in UK 1950–1964, (5) 125*f*.
Aircraft ceramics. See *Cermets; Spacecraft; Turbines.*
Albite, alteration, by H_2O containing dissolved CO_2, (8) 227*e*.
Alkaline earths. See also specific types.
  fluorides, spectra of divalent rare earth ions in crystals of, (9) 256*d*.
  metal carbonates, investigation of forming reaction, (1) 23*b*.
  oxides, effect on viscosity and structure of glass, (10) 264*e*.
  phases, including crystal structure of $Ba_2SrTa_2O_9$, (6) 165*c*.
  silicoalumlate glass, controlled crystallization of, (11) 296*i*.
Alkalis. See also specific types.
  aluminogermanates, solid state reactivity and glass crystallization behavior of, (4) 95*h*.
  borate and alkali silicate glass, cerous-ceric equilibrium in, (3) 60*h*.
  borate glass, manganous-manganic equilibrium in, (11) 296*h*.
  Nd^{3+} fluorescence in, (6) 148*h*.
  thermal and mechanical investigations, (4) 95*d*.
  in cements, flame photometry to determine, (3) 58*j*.
  compounds, vapor pressure and decomposition pressure of several in glass melt, (3) 62*b*.
  content, change during melting of lamp glass, (4) 95*b*.
  determined in silicate chemistry by ion exchange and volumetric methods, (3) 76*a*.
  effect of expansion of porcelain, (10) 275*h*.
  effects on cement, (5) 118*f*.
  elements, decomposition of Al_2O_3-SiO_2 system compounds to determine, (11) 309*j*.
  error, of glass electrode, (8) 208*g*-*h*.
  error, of glass electrodes, equation to calculate, (8) 209*e*.
  from glass, effect of temperature on water-extraction of, (6) 147*c*.
  halide crystals, containing ion impurities, hardness of, (3) 82*h*.
  halides, anharmonic interactions in, (3) 79*i*.
  steady-state excess conductivity during plastic deformation of, (7) 202*e*.
  thermal expansion at low temperatures, (2) 53*f*.
  hydroxide systems. See *Systems.*
  metal cations, ion exchange with sodium aluminosilicate gel, (10) 287*j*.
  metal chlorides, with tin chloride, study of systems formed by ammonium and, (9) 257*j*.
  phosphate glasses, thermal expansion of, (6) 149*i*.
  resistance, of enamels, test to determine, (6) 146*d*.
  of silicate glasses, (8) 210*c*.
  test for enamel, (9) 232*d*.
  variables affecting determinations for enamels, (6) 146*c*.
  systems. See *Systems.*
Alkoxides, decomposition, metastable transitions of zirconium oxide obtained from, (6) 168*f*.
  preparation, of transition and rare-earth metals and formation of powders and coatings of ultrahigh purity zirconia, B (11) 320*f*.
Allevardite, from Hungary, B (2) 56*c*.
Allophane, coordination number of aluminum in, (2) 52*j*.
  from USSR, B (2) 56*b*.
Alloys, cemented carbide, P (2) 37*j*.
  chromium carbide, strength of hard, (10) 272*d*.
  compositions, method to formulate for dispersion hardened compacts, P (11) 302*j*.
  Ge-rich, gravimetric determination of Ge in, (5) 131*i*.
  gold-rhodium-platinum, microstructure and mechanical properties of, (5) 122*b*.
  junction, formation temperature, (11) 313*h*.
  ordered, dislocations in, B (6) 175*d*.
Alumina. See *Aluminum, oxide.*
Aluminates. See also *Alkaline earth.*
  hydro-, composition of trisodium, (5) 140*d*.
  melts, activities of MnO, sulfide capacities, and activity coefficients in, (1) 7*j*.
Aluminoborosilicate, alkali-free, strength of fibers coated with, (10) 266*j*.
  glass films, and glass plastics, effect of chemical treatment of surface on properties of, (9) 233*f*.
Aluminosilicates, compound, blooming optical components with, P (10) 267*f*.
  refractories, research on, (7) 187*d*.
Aluminum, in allophane, coordination number of, (2) 52*j*.
  alloy, effect of surface oxide film on lifetime of vacancies in, (9) 249*f*.
  alum, proton magnetic resonance study of structure of single crystal, (6) 169*h*.
  Al^{3+}, effect on polymorphism of tricalcium silicate, (2) 49*d*.

Aluminum (*continued*)
Al-Al_2O_3-Al, photovoltage measurements on thin film sandwich of, (9) 253*j*.
-Al_2O_3-metal diodes, potential barrier parameters in thin-film, (5) 128*e*.
-Al_2O_3, triodes, hot electron transfer through thin-film, (5) 137*d*.
Al_2BaO_4, crystallography of some silicates and germanates of, (6) 166*j*.
Al_2SiO_5 polymorphs, and $Al_6Si_2O_{13}$, re-evaluation of heats and free energies of formation, (1) 25*e*.
anodized, method to enamel, P (3) 60*a*.
antimonide, effective coefficient of distribution of Te in, (1) 20*i*.
antimonide, interaction with S, (9) 251*e*.
-bonded, titanium carbide cermets, (8) 214*i*.
-ceramic, low density composite of, (9) 232*a*.
chloride complex, viscosities of kaolin-water suspensions with additions of, (5) 127*i*.
chloride, systems. See *Systems*.
-chromium spinels, pigments of, (5) 139*i*.
and coating for, prebrake anodes for electrolytic production of, P (5) 126*e*.
color finishing, (1) 3*d*.
enameled, new spall test for, (6) 140*c*.
fluoride, systems. See *Systems*.
Ga, and In, analysis of mixtures by solvent extraction and gas chromatography, (2) 43*i*.
hydroxide, in melting plate glass drawn without debiteuse, (10) 267*c*.
and iron, determination by solvent extraction and gas chromatography, (6) 161*i*.
MgO-Al_2O_3 solid solutions, mechanism of precipitation of, (5) 138*a*.
methylsiloxy-, thermal transformation of SiO_2-Al_2O_3 gels prepared from, (9) 257*a*.
nitride, articles of, P (5) 126*a*.
and boride, composition containing, P (9) 240*a*.
preparation of purified, P (7) 189*e*.
refractory components from, (3) 69*j*.
oxide. See also *Boehmite; Corundum; Refractories*.
absorption on sheet glass, (8) 208*g*.
advances in whisker technology, (4) 99*c*.
agglomerating, P (10) 282*i*.
alpha, production of ultrafine, P (10) 283*b*.
analysis of impurities in, (9) 245*g*.
based cermet, effect of additives on sintering of, (6) 151*g–j*.
bodies, metallizing sintered, P (6) 154*j*.
bodies, temperature dependence of fatigue strength, (2) 40*c*.
brick for ladle lining, (4) 99*c*.
brittle-ductile transition in polycrystalline, (9) 248*d*.
casting slips, P (9) 240*c*.
catalytically active, estimation of surface acidity of, (3) 83*g*.
cements, effect of inclusions on properties of, (2) 28*e*.
ceramics, B (11) 320*f*.
coating on Ni, (1) 24*j*.
-cobalt-gold composition, P (4) 109*b*.
cracking catalysts, coke formation on, (5) 125*d*.
creep of dense, pure, fine-grained, (4) 110*c*.
dc conductivity of single crystals, (5) 134*f*
dispersion-strengthened, (10) 284*h*.
effect of compressive stress on creep behavior, (2) 39*c*.
effect on crystal growth rate of slags, (6) 167*f*.
effect as impurity in magnesia refractories and dolomite, (6) 152*b*.
effect of manganese oxide on sintering of, (1) 20*e*.
effect of metal oxide additives on electrical conductivity of, (5) 128*c*.
effects of metallic oxides on α-transformation of, (4) 110*e*.
electrical conductivity at temperatures in a reactor environment, (2) 49*i*.
electron diffraction study of, (7) 199*e*.
in electronics, (10) 276*h*.
electron paramagnetic resonance in ceramics based on, (5) 136*a*.
enhanced activity and characterization of ball-milled, (2) 50*a*.
γ-, Moessbauer effect for finely divided iron oxide on, (1) 23*a*.
γ-, preparation by water hydrolysis, P (10) 283*d*.
etching by sputtering, (8) 226*e*.
experimental and theoretical thermal conductivities of, (6) 170*e*.
final stage densification in vacuum hot-pressing of, (1) 21*c*.
high, evaluation of materials, (2) 36*f*.
high, service of refractories in tank furnaces, (10) 266*g*.
high density grinding balls and rods of, (4) 102*h*.
high-temperature elastic properties of polycrystalline, (8) 226*g*.
honeycomb for uniform reaction processes, (9) 237*j*.
hydrate, P (10) 273*h*.
hydrate casting slips, P (9) 240*d*.
hydration of α-, (9) 250*c*.
hydrothermal solubility in $Na_2B_2O_7$ solution, (3) 82*b*.
kinetics of phase transformation of, (9) 251*h*.
lattice vibration frequencies, thermal expansion, Grueneisen parameter, and temperature dependence of, (1) 25*a*.
-PbO, phase diagram of, (9) 252*i*.
making of trihydrate, P (10) 283*e*.
measurement of particle size by centrifuging, (7) 195*d*.
melting point and related observations, (2) 50*b*.

Aluminum, oxide (*continued*)
method to determine in cement, (3) 58*h*.
method for grinding articles of high, (2) 43*e*.
method to make low soda of small crystal size, P (10) 283*c*.
method to mold, P (11) 302*c*.
method to produce active, P (3) 79*a*.
method to produce active nodules, P (3) 79*b*.
method to produce from clay, (9) 247*e*.
method for producing active and resulting product, P (4) 109*b*.
monofilaments of, P (11) 303*a*.
particles, growth during preparation of Ni specimens, (1) 21*j*.
photoelastic observation of stress distribution single crystal, (10) 289*b*.
polyphase heterojunction, electrical properties of, (1) 21*a*.
porous products based on, P (10) 274*j*.
preparation of foamed, (10) 272*e*.
preparation of nordstrandite, P (3) 78*c*.
pressure derivatives of sound velocities of, (5) 140*c*.
producing crystalline as abrasive, P (2) 27*f*.
product, P (10) 282*j*.
production of, P (6) 184*j*.
production of anhydrous, P (3) 79*d*; P (10) 283*a*.
production of kappa-phase, P (4) 109*f*.
production of readily dispersible, P (3) 79*a*.
reactions in glass melting, (4) 96*a*.
reactive hot-pressing of, (10) 290*e*.
reagent for chromatographic analyses, (5) 131*j*.
refining process for, P (7) 189*b*.
shear strength of sintered to interpret friction processes, (9) 229*g*.
in sheet glass, determined by photoelectric emission spectral analysis, (3) 62*b*.
SiO_2, developments in refractories from, (3) 69*h*.
-SiO_2-ZrO_2, refractories for ladles, (9) 239*f*.
sintered, thin sections subjected to acid and thermal treatment examined by electron microscope, (11) 310*f*.
stability in H, (2) 10*a*.
strength of partly sintered compacts, (6) 170*d*.
sublimation in hydrogen, (2) 52*c*.
surface energy of a running crack in calculated from crack-branching measurements, (6) 170*i*.
systems. See *Systems*.
trends, development, and use, (6) 184*b*.
under irradiation, adsorption of oxygen and carbon monoxide on, (11) 313*f*.
and zinc oxide, kinetics and mechanism of reaction between, (1) 23*f*.
-zirconia-silica refractories, corrosion resistance of, (6) 152*b*.
oxide on, chemically formed, (8) 207*h*.
polarographic determination of, (3) 76*a*.
powder, nitriding under pressure, (7) 178*i*.
reaction of phosphate enamels with, (2) 30*e*.
-silica, kinetics of reaction, (9) 251*h*.
silicate, high surface area and method of making, P (3) 78*g*.
in silicate materials, polarographic determination of, (2) 44*i*.
single and polycrystalline, dynamic deformation of, (10) 285*d*.
sulfate, effect on refractory clays and on fired products, (3) 66*f*.
systems. See *Systems*.
titanate, formation and properties, (7) 197*b*
Alushite, mixed layer phase in, B (2) 56*f*.
Amethyst, twinning, lattice imperfections, and impurity distribution in, (3) 86*g*.
Amines, primary, complexes with montmorillonite and vermiculite, (9) 248*i*.
Ammonium, chloride, reactions with clay minerals, (9) 248*c*.
chloride-kaolin, structural and bonding features, release of interlayer NH_4Cl, (9) 248*a–b*.
dihydrogen phosphate crystals, effects of pH on shape of, B (11) 319*h*.
study of systems, formed by tin chloride with chlorides of alkali metals and, (9) 257*j*.
sulfate, for intensifying glass melting, (10) 267*d*.
Analcime, and halloysite, paragenesis in Bathonian sediments of Georgia, B (2) 56*f*.
Analysis. See also *Chromatography; Colorimetry; Electron diffraction; Microscopy; Particles; Photometry; Quality control; Screens and sieves; Spectrography; Spectrometry; Spectrophotometry; Spectroscopy; Testing; Thermal analysis; Thermodynamics; Thermogravimetry; Titration; X rays*.
analytical chemistry, theory and practice, B (3) 88*e*.
by beta-ray back-scattering, improved by filter method, by spectroscopy with magnetic field, and by pulse height analysis, (11) 309*e*.
of carbon deposition kinetics, in isothermal flow systems, (4) 109*j*.
chemical, automatic apparatus for, P (9) 246*c*.
determination of metallic iron in slag, (9) 246*d*.
to determine thickness of disturbed layer on quartz powder, (3) 87*h*.
of high-alumina refractories, (8) 216*b*.
of metallic elements, B (3) 88*a*.
new methods to identify materials, (2) 44*d*.
of phosphate glasses, (1) 5*c*.
complexometric, of glass, (10) 264*d*.
complexometric, of zirconia and oxides of Al, Fe, and Ti, (6) 163*b*.
continuous, automatic, P (3) 77*a*.
derivatographic, of synthetic zeolites, (6) 166*g*.
differential cathode-ray polarography, of lead titanate-zirconate ceramics, (7) 194*j*.

Analysis (*continued*)
dispersion, to study glass production processes, (10) 267*e*.
electrochemical, to determine alumina in cement, (3) 58*h*.
electrogravimetric, of water in clays, (2) 49*j*.
electrophysical, results for hexaborides of rare earth elements, (10) 290*j*.
gas. See *Gases*.
of glass defects, with laser microprobe, (4) 94*e*.
gravimetric, to determine Ge in Ge-rich alloys, (5) 131*i*.
for impurities in metals, quantitative spark mass spectrometry to determine, (2) 45*g*.
methods, to investigate Rothschild Lycurgus cup, (2) 27*j*.
micro-, computer program for electron probe, (1) 16*g*.
mineralogical modal, with electron microprobe X-ray analyzer, (7) 195*d*.
multivariate, of montmorillonite, (5) 134*b*; (6) 169*b*.
neutron-activation, of impurities in gelatin and alumina, (9) 245*g*.
neutron activation, of microgram amounts of Th in U ores and process liquors by means of ^{233}Th, (11) 310*b*.
for phosphate, interference from silica in, (7) 195*b*.
of K_2O-SrO-SiO_2 glass, changes in composition during electron microprobe, (9) 232*j*.
power-spectrum, of Canadian argillites, (5) 140*a*.
profile, of abrasive grains, (6) 143*i*.
of pure materials, electrical measurements in, (3) 75*f*.
of pure SiC, neutron activation, (6) 153*f*.
quantitative, by atomic absorption, (1) 17*a*.
of rare earth mixtures, qualitative and quantitative by means of magneto-optical rotation, (6) 162*j*.
relaxation mode, correlation of atomic steps in crystals by, (1) 19*j*
sieve, with micromesh sieves, (9) 245*j*.
in silicate chemistry, determination of alkali content by ion exchange and volumetric methods, (3) 76*a*.
of silicates, methods, B (6) 173*b*.
size, transformations for any method of, (5) 142*a*.
of small quantities of material, apparatus for automatic chemical treatment and, P (2) 45*h*.
spectrochemical, of Nb-Ta mixtures, buffer effects in, (6) 161*j*.
spectrochemical, using beta-ray source, (4) 107*f*.
statistical, of power consumed by glass industry in the Federal Republic of Germany, (9) 234*i*.
statistical correlation, to evaluate methods of characterizing particle size of powders in subsieve range, (8) 223*e*.
of stress problems, transparent polurethane rubber can solve, (2) 44*a*.
supercentrifugal dispersion, study of fine fractions of clays and kaolins with, (2) 45*c*.
techniques, for hydraulic cements and concretes, (11) 293*h*.
time-trend, for environmental interpretation of limestones, (1) 25*g*.
volumetric, determination of As and Sb in mixed manganese arsenid, antimonide, and phosphide compounds, (11) 310*i*.
Analyzers. See also *Gases*.
automatic, to determine thoria in thoria-urania mixtures, (5) 131*d*.
electron probe X-ray micro-, to identify inhomogeneity in glass, (9) 235*g*.
Anatase, twinning in, structural interpretation of, (6) 170*e*.
and ZrO_2, formation of $ZrTiO_4$ form, (11) 304*j*.
Anchors, metal, for refractory concrete, (8) 215*i*.
Andalusite, crystal structure, refinement of, (3) 85*i*.
Andesite, a new building material, (3) 71*b*.
Anelasticity, in crystalline α-quartz, (6) 170*b*.
Anhydrite, mining, at Billingham, (3) 78*h*.
phospho-, increased resistance to water, (1) 2*b*.
solubility and hydration, effect of Na_2SO_4 and NaCl on, (1) 2*h*.
Anions, metaborate, new type, (3) 84*c*.
Anisotropy, of glass fibers, test for, (10) 265*g*
magnetic, theory of pyrocarbons, (4) 112*f*.
of $Ni_xFe_{3-x}O_4$, frequency dependence of ferromagnetic crystalline, (10) 286*j*.
of photoconductivity, in single CdSe crystals, (11) 313*i*.
Annealing, of glass. See *Glass*.
magnetic, effect of cation vacancies on $Co_xFe_{3-x}O_4$, (10) 285*f*.
Anodes. See also *Electrodes*.
from Ta-Ti alloys, solid electrolyte capacitors using, (8) 220*f*.
Anomalies, structural, determination in SiO_2-Al_2O_3-Na_2O-Li_2O glasses, (6) 148*j*.
Anthophyllite, crystal chemistry, and thermal behavior, (3) 80*h*.
Antiferromagnetism. See *Ferromagnetism*.
Antimonides, of Ta, (3) 79*h*.
Antimony, Sb_2O_3, vitreous range in three-component systems based on and physicochemical properties of Sb glasses, (7) 182*c*.
Sb_2S_3, optical properties and zone structure of single crystals of, (9) 252*e*.
in mixed manganese arsenid, antimonide, and phosphide compounds, volumetric determination of, (11) 310*i*.
oxide, systems. See *Systems*.
selenide, systems. See *Systems*.
sulfide, X-ray sensitivity of single crystals of, (3) 87*g*.
systems. See *Systems*.
telluride, systems. See *Systems*.
yellow, composition and preparation, (4) 102*d*.

Apatite, fluor- and hydroxyl-, heat of formation of α and β modifications of, (5) 136*i*.
lead, (3) 83*j*.
Apparatus. See *Instruments; Machinery and equipment; Testing;* and specific types.
Aquagels. See *Silicon, dioxide, gels.*
Archeology, items found in excavation in Virginia, (10) 261*j*.
recent discovery, contribution to study of Syrian glass of Roman period, (5) 117*i*.
Architecture, architectural shapes, of basalt, (8) 214*d*.
Argillites, Canadian, power-spectrum analysis of, (5) 140*a*.
Argon, residual, partial pressure changes due to ionization gage in ultrahigh vacuum, (10) 281*a*.
sorption, by glass in gas-discharge lamp, (9) 234*f*.
Arsenates, and phosphates, chemical effects of thermal neutron capture in, (3) 79*j*.
Arsenic, and Bi, interactions of selenides of, (1) 22*i*.
and Bi, interaction of tellurides of, (1) 22*j*.
borate glass, gamma-induced absorption and structural studies of, (9) 233*c*.
P and Ge, simultaneous determination and separation of Si and As by solvent extraction, (9) 246*a*.
in mixed manganese arsenid, antimonide, and phosphide compounds, volumetric determination of, (11) 310*i*.
systems. See *Systems.*
Arsenides, of Ta, (3) 79*h*.
Art and artware. See also *Archeology; Decoration; Design; Majolica; Pottery; Tile.*
Angerstein service, origin of, (8) 205*i*.
Caerleon window glass, analyses and discussion, (9) 229*i*.
ceramic, (6) 144*b*.
catalog of Illinois exhibit, B (9) 258*b*.
designers of Swedish, (10) 261*h*.
exhibit of German, (6) 144*b*.
formation of group to study period 1450 to 1750, (2) 27*i*.
early Spanish, (2) 28*b*.
German postage stamps featuring, (10) 262*i*.
international seminar in Gmunden, Germany, (9) 230*b*.
work of Bern, Switzerland school, (8) 206*d*.
Chinese, Museum in Stockholm, (8) 206*a*.
contribution of American Indian, (2) 27*h*.
enamel work, decorative translucent of 19th-century, (4) 90*a*.
glass, analysis of technical and ancient, (2) 28*c*.
ancient, brought to Scandinavia from the Roman Empire, (2) 28*a*.
ancient, discovery at Herculaneum, (3) 57*i*.
ancient cameo at Corning, Florence, and Besancon, (4) 90*a*.
ancient Roman, (4) 89*h*.
beads from Malay, (9) 229*j*.
blown, of the Acre cementery, Israel, (5) 117*j*.
Bulgarian factory, 9th and 10th century, (5) 117*j*.
cage cup construction, (4) 89*i*.
cage cups, descriptions, corrections, and analysis, (2) 27*i*.
cage cup fragments from Athens and Corinth compared to similar vessels, (4) 90*c*.
-cased, (3) 57*j*.
collection of English and continental, (5) 118*a*.
composition of 3rd century Russian compared with others, (4) 89*j*.
contributions to knowledge of ancient, (6) 144*b*.
cup from 1st century, (5) 118*c*.
cut, of the Empire period, (3) 57*i*.
early bottle factory in Connecticut, (3) 58*a*.
effect of heat on museum pieces, (4) 89*i*.
Egyptian sand-core technique for, (9) 229*j*.
and enamel, Muranese recipes, (4) 80*j*.
enameler's in form of beads or cakes, (2) 27*i*.
engraved, (5) 117*j*.
engravings and sketches on, (5) 118*b*.
15th century Venetian bottles, (4) 89*j*.
flask, European compared with Highdown Hill goblet, (2) 27*j*.
foreign influence on Baden, (8) 206*a*.
fourth-century jar with applied masks, (4) 89*i*.
fragments of Roman cameo cup, (4) 90*b*.
goblet with monogram of Landgraf Carl von Hessen, (5) 118*d*.
individual communion, P (9) 230*e*.
Italian 12th and 13th century, (9) 230*a*.
Japanese modern industrial, (1) 26*e*.
Jena, (2) 28*b*.
Jewish gold, (9) 230*b*.
late-Roman goblets, (9) 230*c*.
manufacture and marketing of adjagba beads in Ghana, (5) 118*c*.
means to determine age, (4) 89*h*.
medallions of tomb at Cigarralejo, (4) 90*a*.
Mesopotamian bottle, (4) 90*b*.
mosaic from Iran, (9) 230*d*.
near eastern acquired by museum in Leiden, (9) 230*c*.
new diatret of Cologne, shell goblet and, (5) 118*c*.
origin at Altare, (8) 206*a*.
from Pengkalan Bujang, Malaya, (5) 118*e*.
portraits, commemorative, (9) 230*c*.
problems of dating ancient by counting layers in weathering crust, (5) 118*d*.
recent acquisitions by collections, (5) 118*a*; (9) 230*e*.
recent publications, (5) 117*j*; (9) 229*j*.
recipe book for Murano, (3) 58*c*.
in Rio dei Verieri, (8) 206*c*.
Roman square bottles, (9) 230*f*.
Roman window from Wales, (9) 230*a*.
of royalty in late Middle Ages, (6) 144*b*.
Russian from 11th to 17th century, (9) 230*a*.
Art and artware, glass (*continued*)
Russian in first half of 19th century, (4) 90*c*.
seventeenth-century cup in Danish Royal collection, (2) 28*a*.
Sidonian mold-blown vessels in Museum Haaretz, (4) 90*d*.
signatures on Galle, (9) 230*b*.
Swabian tumbler in Spain, (10) 262*b*.
Syrian of Roman period discovered at Homs, Syria, (5) 117*i*.
trends in early Bohemian, (2) 28*b*.
unusual coatings for stemware, (10) 261*i*.
Venetian in the Museo Civico at Brescia, (8) 206*b*.
Wolfenbuettel from A.D. 1500, (2) 28*c*.
glazes, low-lead borosilicate for, (11) 304*b*.
glazes, recipe for basic, (8) 206*b*.
Iranian, 7000 years of, B (6) 174*h*.
Japanese, collectors' handbook, B (1) 26*a*.
jewelry, enameled on Al base, (5) 118*a*.
jewelry, enameled silver, (8) 206*a*.
lid forming, (8) 206*d*.
porcelain, automatic tunnel kiln for, (9) 246*h*.
of Berlin State Factory, (8) 205*j*.
decorated with geometric designs, (2) 27*j*.
early history of Royal Rockingham, (8) 206*b–c*.
means to authenticate historic, (3) 58*b*.
Meissen, increase in exports, (10) 275*j*.
Meissen in museum at Berne, (3) 58*b*.
regence casket, with engraved glass panels, (5) 118*b*.
Roman, shapes of, (10) 261*j*.
sculpture, of children, (8) 206*c*.
slab project, for children, (8) 206*c*
stoneware, British award winning, (10) 261*i*.
Sieburg, possible method to date, (1) 1*j*.
vases, oxblood glazes for, (10) 275*i*.
stoves, renaissance at the castle at Eferding, Austria, (8) 206*a*.
of T'ang dynasty, copies, (6) 144*a*.
terra cotta, pre-Columbian in National Museum of Anthropology in Mexico City, (3) 58*a*.
tiled heating stoves, changes in, (6) 144*b*.
Turkish, in the Munich City Museum, (8) 206*c*.
Artists, Aristeas, (5) 118*c*.
Aschan, Marit, (8) 206*d*.
Bampi, Richard, (3) 58*b*.
Barbini, Gian Battista, (3) 58*c*.
Baumann, Hans Theo, (2) 27*j*.
Bernstiel, Liefriede, (1) 1*j*.
Biemann, Dominik, (5) 117*j*.
Brameld, (8) 206*b*.
Crumbiegel, Dieter, (8) 205*j*.
designers, review of Swedish, (10) 261*h*.
Ellwanger, Dorothea and Volker, (8) 205*j*.
Fischer, Cuno, (1) 1*j*.
Galle, Emile, (3) 57*j*; (9) 230*b*.
German, exhibit in Germany, (10) 262*a*.
Grove, Helga and Jan, (3) 57*j*.
Killinger, Georg Friedrich, (5) 118*d*.
Koppenhoefer, Ruth, (10) 261*j*.
Larson, Lisa, (3) 58*a*.
Lehmann, Signe, (1) 2*a*.
Mandray, Michelle, (1) 1*j*.
Mans, Bodo, (3) 57*i*.
Michels, E., (1) 1*j*.
Modigell, Karl Heinz, (1) 1*g*.
Quillmann, Konrad, (6) 144*b*.
Schneider, Christian Gottfried, (5) 118*b*.
Asbestos, aluminized suits, for use in hot tunnel kilns, (3) 77*e*.
cement, articles, apparatus to manufacture, P (5) 126*h*.
binders, analysis of, (6) 144*d*.
pieces, machine to manufacture, P (5) 126*a*.
product, P (2) 38*b*.
structural sheet, P (3) 70*b*.
tubes, apparatus to make, P (7) 188*h*.
fibers, products of, P (11) 302*j*.
-glass fiber, saturating paper containing thermoplastic resin and aluminum acid phosphate, P (1) 10*h*.
1904 figures, (1) 18*b*.
sulfur treated, P (8) 218*f*.
Ascorbic acid, glass resistant to, (6) 147*e*.
Ash, fly, lime, carbonation resistance of brick from, (2) 35*e*.
Atmospheres, effects on slag corrosion, (8) 215*e*.
firing, effect on chromite-magnesite refractories, (7) 186*f*.
in furnace, method and position to measure, (3) 67*h*.
furnaces, effect on refractories during erosion test of slag, (4) 99*h*.
heated, effect on dolomite and magnesia clinker, (3) 66*i*.
oxidizing, behavior of steel cladding on basic refractories in regard to temperature requirements in oxidizing atmospheres, (8) 214*i*.
residual, effect on Si surfaces, (11) 316*e*.
various, furnace to operate in, (10) 282*a*.
Atomic energy. See *Nuclear energy.*
Atomization, method, to prepare films on glass, (1) 5*b*.
in preparation of wall-tile dust, compared with traditional processes, (7) 190*f*.
Atoms, building from, B (9) 259*d*.
counter, determination of yttrium by, (4) 107*g*.
in graphite, energy of interstitial, (4) 111*e*.
Attapulgite, clay, glycol coated and compositions including, P (4) 109*e*.
clay, method to improve yield, P (3) 78*j*.
Attrition. See *Crushing; Grinding.*
Autoclaves, micro-, to observe reactions in powders, (11) 310*j*.
Automation, of aggregate company, in Kingston, N. Y., (2) 35*d*.
Automation (*continued*)
of batch preparation, at Sighisoara glass factory in Rumania, (2) 30*j*.
of glass making, (6) 146*i*.
of glass tank furnaces, (7) 179*g*.
in heavy clay industry, (6) 151*c*.
of kilns, development of design in respect to, (2) 46*c*.
Autoradiography. See *Radiography.*
Avalanches, and gas breakdown, B (9) 259*f*.

Baddeleyite, South African deposit, (3) 77*i*.
Balances (scales). See also *Weighing.*
thermo-, device to control program of, (9) 245*g*.
Ball clay, English, processing of, (1) 18*i*.
Ball mills. See *Mills.*
Barium, $BaCdO_2$, crystal structure, (3) 80*b*.
$BaSrTa_2O_6$, alkaline earth-Ta-O phases including crystal structure of, (6) 165*c*.
borate, extinction of lead borates in glasses in admixture with, (5) 121*h*.
bromide, systems. See *Systems.*
chloride, systems. See *Systems.*
$BaFe_{12}O_{19}$, effect of fluoride-compensated Co^{2+} on anisotropy of, (2) 49*e*.
^{140}Ba-^{140}La mixture, method to separate ^{140}La from, (4) 107*c*.
$BaO \cdot 6Fe_2O_3$, magnetization dynamics of single crystals using pulsed magnetic fields, (4) 112*g*.
Ca and K, fusibility diagram of system of chlorides of, (4) 111*f*.
carbonate, systems. See *Systems.*
fluoride, systems. See *Systems.*
hexaborate, physical-chemical properties of, (11) 319*a*.
metaplumbate, formation and properties of (1) 21*c*.
nitrate, systems. See *Systems.*
orthotitanate, Raman scattering spectrum of, (2) 51*j*.
oxide effect on clinker formation, (5) 118*g*.
photoluminescence of, (3) 84*c*.
reactions of, (9) 254*b*.
substituted soda-lime-silica glass, properties of, (4) 95*i*.
systems. See *Systems.*
peroxide, to control ferrous sulfate in nickel tan, (6) 145*c*.
selenite, heat of formation of, (9) 250*f*.
Na, K, and Sr, fusibility diagram of system of fluorides of, (4) 111*f*.
strontium ferrites, effect of texture on magnetic properties of mixed, (11) 317*d*.
and strontium ferrites, properties of mixed, (10) 290*c*.
systems. See *Systems.*
titanate. See also *Dielectrics.*
capacitance increased by La^{3+}, (8) 220*b*.
compounds with hexagonal structure of, (6) 165*f*.
crystals, Hall mobility of Te films deposited on, (2) 50*g*.
crystals, polarization reversal electroluminescence at low frequencies in, (8) 226*j*.
crystals, surface layers on ferroelectric, (5) 141*d*.
crystals, thickness dependence of switching time, (9) 242*f*.
dielectric and electrooptic properties of, (10) 290*b*.
domain structure of ferroelectric and its effect on dielectric properties, (7) 198*j*.
domain wall velocities and surface layer in, (3) 81*e*.
effect of TiO_2 on semiconduction of, (3) 72*f*.
effect of two-dimensional pressure on permittivity of, (2) 49*h*.
etched hillocks in, (2) 50*a*.
forward velocity of ferroelectric domain walls in, (9) 250*c*.
interferometric studies of domain structure in ferroelectric, (3) 82*f*.
interferometric study of microtopography from domain walls in, (3) 82*h*.
light phase modulator, (4) 103*h*.
mechanism of microwave dielectric dispersion in polycrystalline, (4) 104*a*.
movements of transition fronts in, (5) 139*a*.
optical absorption edge of, (9) 252*d*.
optical absorption and electrical conductivity of reduced single crystal, (10) 289*b*.
phenomenological theory of high permittivity in, (2) 40*f*.
photoemission studies on, (9) 253*g*.
semiconductors containing controlled amounts of neodymium, (10) 277*h*.
strain-free electrooptic effect in single crystal, (10) 290*f*.
structure of transition fronts in, (5) 141*c*.
surface layer of, (9) 257*b*.
surface layer and decay of switching properties of, (7) 203*g*.
theory of dielectrics constants of, (11) 305*h*.
thin layers for capacitors, (7) 191*f*.
$-UO_2$ and $BaTiO_3$-$BaUO_3$, crystal chemistry and dielectric properties in, (6) 157*i*.
whiskers, surface-charge layers of, (3) 86*b*.
titanium citrate, barium titanate, and processes for making, P (4) 104*a*.
titanyl oxalates, thermal analysis of, (1) 25*j*.
trisoxalatoferrates(III), thermal decomposition of, (7) 203*d*.
tungsten bronze, preparation and properties, (6) 202*e*.
zirconylcarbonate, synthesis and production of barium zirconate, (10) 291*d*.

Basalt, makes inexpensive stoneware and architectural shapes, (8) 214*d*.
Volnovakha, as raw material for casting brick, (6) 164*e*.
Base exchange. See *Cations; Ions.*
Batch, batching, ceramic, automation of and mechanized mill loading, (6) 155*j*.
batching, theoretical principles for compounding, (2) 55*a*.
glass, methods to analyze, (9) 234*b*.
glass, preparation of, (6) 146*j*.
transporting, working cycles for pneumatic-vacuum installations, (6) 161*e*.
Bauxite, adsorbent granules, spherical, P (4) 101*j*.
brick, P (8) 217*c*.
Congolese, chemical aspects of formation, (9) 248*c*.
deposits, in Georgia, (3) 77*j*; (5) 132*i*; (11) 312*b*.
of Tennessee, (3) 77*j*.
in Warm Springs district, Meriwether County, Ga., (1) 18*c*.
fines, agglomeration of, P (3) 78*d*.
in southern France, geochemical stratification, B (2) 56*h*.
as tumbling medium, P (6) 143*h*.
Bearings, carbon, friction and wear, (2) 44*h*.
composition, P (11) 301*i*.
with glass content, P (9) 235*f*.
of zirconium boride, P (1) 12*f*.
Bending. See *Deformation.*
Beneficiation. See also *Classification; Classifiers; Crushing; Grinding; Filters; Flotation; Screens and sieves; Separation; Separators.*
of Lithuanian quartz sands, (7) 196*e*.
Bentonites, in Alberta, study of clays from Upper Cretaceous, (3) 86*d*.
aqueous dispersions, rheological properties of, (6) 169*h*.
clays, method to activate, P (6) 164*g*.
of Georgian SSR, genesis of, B (2) 56*f*.
mechanial properties, (2) 50*a*.
winning and processing, (3) 78*c*; (6) 164*e*.
Beryl, crystals, growth of, P (5) 128*g*.
natural, phase transformations in, (8) 226*e*
water in, nuclear magnetic resonance study of, (7) 201*j*.
Beryllia. See *Beryllium, oxide.*
Beryllium, basic, production of high purity, P (9) 247*g*.
BeF_2 glasses, kinetics of dissolution of some containing fluorides in water, (6) 148*d*.
chloride, production and recovery, P (7) 196*j*.
on copper, electrolytic plating from fused salts, B (1) 26*a*.
nitride, systems. See *Systems.*
oxide, brittle and plastic behavior of hot-pressed, (1) 19*f*.
cation diffusion in, (3) 79*j*.
crystals, degradation of growth perfection by silica, (1) 20*c*.
determination of water in, (7) 194*j*.
elastic constants of single-crystal at room temperature, (4) 110*i*.
electron transmission microscopy of polycrystalline, (7) 199*g*.
growth of micro- and macrocrystals, (2) 51*i*–52*d*.
growth of single-crystal Si on, (11) 317*g*.
and magnesia as high frequency insulator, sintered mixture of, (11) 305*a*.
means to bond to Ta or Nb, P (2) 37*c*.
method to produce from Be containing ores, P (5) 133*j*.
sintering kinetics of, (4) 113*b*.
sintering to variable densities and grain sizes, (1) 10*j*.
systems. See *Systems.*
tunnel kiln improves product of, (8) 219*b*.
-UO_2 mixtures, compressive creep of, (1) 19*h*.
X-ray of defect structures of single crystal, (5) 141*a*.
Bibliographies, ceramic, Brazilian, (2) 54*f*.
of chemical durability of glass, B (3) 88*h*.
enamel, and abstracts, 1965, B (7) 204*a*.
glass, recent articles and books, (5) 117*j*.
physics-electronics, 1960, B (6) 174*b*.
Binders, for abrasives. See *Abrasives.*
asbestos-cement, analysis of, (6) 144*d*.
carbon and organic, products and processes based on, P (10) 274*b*.
gypsum, new type, (11) 294*a*.
mold and core, for foundry use, P (1) 11*h*.
new wax, for ferrites, (9) 247*f*.
pitch, factors influencing performance in baking carbon electrodes, (4) 111*i*.
for sand, for foundry cores and molds, P (2) 38*f*.
temporary, epoxy resins as, (6) 156*b*
tufaceous, hardening and setting of, (2) 29*d*.
Biotite. See *Mica.*
Birefringence. See *Refraction.*
Bismuth, and As, interaction of selenides of, (1) 22*i*.
and As, interaction of tellurides of, (1) 22*j*.
$Bi_4Ba_{m-1}Ti_{m+1}O_{3(m+2)}$, switching properties of ferroelectrics of, (11) 305*g*.
Bi_2O_3-PbF_2, habit modification of corundum crystals grown from molten, (6) 167*h*.
ferrite, piezoelectric ceramics of lead zirconate-titanate modified by, (10) 277*g*.
germanate, crystal growth and electro-optic effect of, (3) 80*j*.
glass, thermal conductivity, (2) 32*d*.
selenide, systems. See *Systems.*
telluride, systems. See *Systems.*
trioxide, systems. See *Systems.*
Blasting, of metal panels, glass beads for, (6) 143*g*.
Blending. See *Mixing.*
Blending apparatus. See *Mixers.*
Bloating, characteristics, of Texas clays, (8) 225*a*.
of clays and causes, B (2) 56*j*.
Bodies, ceramic. See also *Dielectrics.*
kaolin for, test to determine suitability of, (6) 162*d*.
permissible stresses, determination as basis for rapid firing, (11) 299*j*.
plastic, machinery for wet preparation, (10) 280*c*.
surface, microscope to observe, (11) 310*a*.
vitreous, of mica and glass, P (2) 43*a*.
ZnO-TiO_2, properties of, (10) 290*a*.
Boehmite, kinetics, thermal decomposition of, (9) 257*k*.
stability, phase boundaries at pressures above 50 atm., (7) 200*i*.
Bolometers, carbon, static response characteristics, (3) 76*g*.
Bonding. See also *Seals and sealing.*
in basic refractories, quantitative study of, (7) 187*i*.
with cement-water suspensions, structure forming role of solid surfaces during, (3) 59*c*.
ceramics to metal, P (4) 104*i*
chemical, at glass-metal interfaces, adherence oxides in development of, (2) 30*c*.
energy, of diatomic ionic molecules, interatomic forces and, (7) 200*b*.
material, between grains in basic high-fired brick, (10) 270*e*.
material, thermoelectric, P (5) 130*b*.
of nitrogen, in oxide glass melts, (1) 3*i*.
pyrochemical, method to control for clay-carbon system, P (6) 164*a*.
silicon, technology, P (6) 160*j*.
of solids, B (5) 142*i*.
Bonds, chemical, effect on solubility of solid inorganic materials, (1) 22*g*.
chemical, and geochemical distribution of elements, (4) 109*j*.
delay line, P (8) 220*e*.
insulating, method of forming, P (4) 129*a*.
intermediate, to seal glass-ceramics to metals, (11) 297*h*.
in metal borides, electron requirements of, (4) 111*e*.
new adhesives and sealants, (4) 115*a*.
one coat enamel, metal pretreatment and, (6) 146*b*.
Bone china, method of making, P (6) 149*d*.
technical control of, (10) 276*d*.
Borates, alkali, solubility of water vapor in melts of, (10) 266*h*.
constitution and chemistry of, (3) 80*b*
fluxes, growth of rutile in controlled composition from, (3) 82*f*.
glasses, density measurements on, (5) 120*g*.
glasses, relation between optical absorption and thermoluminescence of, (5) 120*i*.
hydrated, infrared spectra of, (8) 226*g*.
magnesium lithium, (3) 80*c*.
meta-, new type anion, (3) 84*c*.
ortho-, structural analogy with diorthosilicates, (4) 113*e*.
Borax, effects on growth rate of alum crystals from solutions, B (11) 319*i*.
Boric oxide, systems. See *Systems.*
Borides, chemistry and applications, B (11) 319*e*.
hardness, at 1625°C, (5) 136*i*.
hexa-, of rare earth elements, electrophysical and X-ray spectral analysis of, (10) 290*j*.
hexa-, of rare-earth metals, (9) 250*h*.
metal, production of, P (9) 241*e*.
structures, packing of B_{12} groups in, (7) 202*b*.
of transition metals, investigating by NMR method, (10) 287*f*.
Boron, albite, crystal structure and its relation to feldspar crystal chemistry, (11) 314*g*.
alloys, in abrasion resistant material bonding process, P (8) 216*j*.
alpha-, derivates, crystal chemistry of, (7) 198*b*.
β-, interstitial derivatives of, (7) 200*c*.
B_2O, group IV analogs and high pressure, high temperature synthesis of, (1) 21*h*.
carbide, elementary unit cell of, (6) 167*j*.
and nitride, production of sintered bodies of, (9) 238*i*.
oxidation of, (3) 68*a*.
preparation of crystalline, (3) 68*e*.
welding to Si, (8) 216*f*.
crystalline, NMR method to study, (10) 289*b*.
with diaminochrysazin, spectrophotometric determination of, (3) 75*d*.
diffusion in Si, through oxide layer, (10) 284*c*.
doping, dispersion hardening of TiC by, (11) 315*h*.
effect, on structure and mechanical properties of pyrocarbon at high temperature, (11) 301*c*.
hexa-, silicide, method to make, P (11) 302*e*.
in materials, means to determine, (9) 245*c*.
nitride, bonded, P (6) 158*f*.
continuous production, P (1) 12*d*.
conversion of hexagonal to new shape, P (1) 11*h*.
method to prepare, P (6) 155*a*.
in polymer products, P (9) 239*i*.
process to produce, P (6) 155*i*.
new structure, P (1) 10*h*.
relation of molar refraction to cordination in polymorphs of carbon and, (8) 227*i*.
turbostratic, thermal transformation to ordered-layer-lattice form, (8) 228*d*.
oxide, glass, effect of OH content on acoustic spectra of, (4) 93*b*.
in glasses determined by neutrons, (3) 76*i*.
-SiO_2 glasses, electrical conductivity of those containing Li or Na, (5) 120*d*.
systems. See *Systems.*
phosphate, in glazes, (10) 275*e*.
phosphide, P (9) 247*e*.
epitaxial layer on silicon carbide substrate, P (1) 14*f*.
Boron, phosphide (*continued*)
method to prepare cubic, P (8) 217*e*.
-Si alloys, preparation of, (11) 301*i*.
sorption, by clay minerals, (3) 85*b*.
structures, packing of B_{12} groups in, (7) 202*b*.
systems. See *Systems.*
triiodide-phosphorus triiodide, new compound, (7) 201*f*.
trioxide, viscosity and density, (1) 6*b*.
Brazing. See *Soldering.*
Breithauptite, rotation properties, photometric measurement of, (9) 253*i*.
Brick. See also *Refractories.*
behavior, factors effecting during drying, (11) 300*g*.
or block for paving, manufacture of, P (6) 151*f*.
building, effect of absorptive capacity on bearing strength of masonry, (10) 270*d*.
building, kiln for, (9) 237*g*.
clays, composition and structure, (2) 35*c*.
clays, Hungarian wall covering from common, (2) 36*a*.
clinker, process to manufacture by dry-press method, (2) 35*g*.
coloring, low cost, (1) 7*i*.
cube, strength and elastic properties of, (10) 270*c*.
efflorescence, frost resistance, and silicone treatment of, (10) 270*d*.
face, methods to prepare dry-press bodies for, (9) 261*j*.
first mechanical face setting, (8) 214*d*.
handmade, modernizing production, (11) 300*g*.
hollow, comparison of Austrian and foreign for heat insulation, (2) 35*b*.
hollow, from fired clay, (2) 36*a*.
laying, methods compared, (8) 214*e*.
lime-fly ash, carbonation resistance of, (2) 35*e*.
manganese-colored, discoloration of mortar joints by, (4) 98*g*.
package, P (7) 185*a*.
panels, method to precast, P (4) 98*h*.
prefab, (8) 214*g*.
prefab brick, (8) 214*g*.
panel system, unlimited design, (8) 214*g*.
production, automated soft-mud, (2) 35*d*.
raw materials, firing of, (2) 35*f*.
setting, by machine, (2) 35*i*.
setting machine, automatic, (4) 98*e*.
stacking device, P (6) 151*e*.
and structural clay products, glazes for, (2) 35*g*.
walls, as γ-radiation shield, (2) 35*d*.
work, practical, B (3) 88*j*.
Brick industry. See also *Structural clay products industry.*
Austrian, 1945–1965, (2) 35*c*.
British, modernized and production expanded, (10) 270*c*.
Italian, effect of rapid dryers on, (11) 300*a*.
motor maintenance, (11) 300*f*.
new Florida plant, (4) 98*i*.
plant, description of South African, (4) 98*f*.
techniques and problems, (9) 237*h*.
transfer car system in, (3) 65*d*.
transport, trackless, (7) 185*c*.
Brickmaking apparatus and equipment. See also *Dryers; Kilns; Materials handling; Presses.*
P (9) 239*i*.
for adobe, P (4) 98*f*.
comparison, of hydraulic press and pneumatic hammer, (2) 35*h*.
for refractories, P (9) 239*h*.
Brines, subterranean, industrial importance in Lithuania, (6) 164*d*.
Brittle, materials, grain boundary energies, method to measure, (7) 198*a*.
heterogeneous, measurement of fracture energies of, (1) 20*a*.
strength and weakness of, (5) 121*g*.
Bromellite, synthetic, formation of micro- and macrocrystals, (2) 51*j*–52*d*.
synthetic, optical properties of, (11) 319*c*.
Bromides, tri-, of vanadium at high temperatures, disproportionation of, (4) 110*a*.
Bromine, residue compounds, thermal expansion of pyrolytic graphite-, (4) 113*j*.
systems. See *Systems.*
Bronze, barium tungsten, preparation and properties of, (6) 202*e*.
lithium tungsten, electrical conductivity and carrier mobility in, (7) 203*c*.
silver vanadium oxide, hydrothermally grown crystals, (1) 22*f*.
vanadium oxide, of Cu and Ag, physical properties of, (1) 25*c*.
Bubbles, formation, in fused cast refractories at high temperature, (4) 93*b*.
on molten glass, (1) 5*d*.
in reaction of glass melts with refractory materials, (6) 146*j*.
spontaneous in silicate melts at high temperature, (11) 297*i*.
in glass, formed by electrochemical processes, (11) 296*e*.
in glazes, development and clearance, (7) 190*d*.
growth conditions, in fining of glass, (7) 181*f*.
movement, determination of rate in melt, (4) 93*g*.
movement, in tank furnaces for melting sheet glass, (6) 148*b*.
rise, rate in glass with unstable temperature, (10) 266*a*.
structure, effect on properties of enamels, (2) 30*a*.
structure, effect on properties of ground coat enamels, (6) 145*g*.
Buffing compounds. See *Grinding; Polishing.*
Building materials. See also *Aggregates; Brick; Enamels; Insulation, thermal; Structural clay products.*
andesite, (3) 71*b*.
concrete block, production increased, (9) 230*j*.

Building materials (*continued*)
enamel on steel, review of Lustron house, (8) 207*j*.
glass, strength of blocks as affected by material and form, (3) 62*g*.
glass fiber products in (3) 60*e*.
hydrothermal and pneumatic processing of, (4) 98*g*.
metal panels, finished by blasting with glass beads, (6) 143*g*.
thermal conductivity, means to determine, (1) 7*e*.
wall covering, from Hungarian brick clays, (2) 36*a*.
Bulbs. See *Glass*.
Burners. See also *Flames*.
assembly, P (11) 311*j*.
atomizer, for spectroscopy, P (10) 281*g*.
control apparatus, P (3) 77*f*.
design, improving for glass tank furnaces, (9) 233*f*.
fuel oil gasification, P (6) 163*j*.
for furnaces, P (1) 17*i*.
gas, P (11) 311*f*.
gas with adjustable nozzle, P (5) 132*g*.
industrial, P (1) 17*j*; P (2) 46*e*; P (3) 77*g*.
industrial, with recuperative means, P (10) 282*c*.
means, for furnaces, P (7) 195*g*.
oil, designs and controls for glass, (10) 265*e*.
oil, regulating group for different oil weights, (6) 163*g*.
plate, P (8) 224*e*.
radiant, P (10) 282*f*.
gas, P (2) 46*f*; P (7) 196*c*.
with vented burner surface, P (5) 132*h*.
radiating, P (5) 132*h*.
self-stabilizing, P (11) 311*j*.
spark monitor for, P (9) 246*j*.
throat, P (2) 46*d*.
tube-firing gas, P (4) 108*g*.
Burning. See also *Calcination; Combustion; Firing; Lime*.
clinker, three-stage, (7) 178*e*.
process, in flames in glass melting furnaces, (1) 17*e*.
Burnishing. See *Polishing*.

Cadmium, bromide, systems. See *Systems*.
$CdCl_2$-KCl and $CdCl_2$-NaCl melts, capacity of the double layer in, (6) 165*e*.
chloride, systems. See *Systems*.
ions, diffusion in solid potassium chloride, (7) 198*c*.
manganite, magnetic properties of, (3) 83*b*.
oxide, conductivity in high-frequency electromagnetic field, (3) 80*f*.
oxide, Hall coefficient and conductivity measurements in terms of sintering temperature, (6) 167*i*.
rhenium oxide, $CdRe_2O_7$, preparation and structure, of, (1) 24*j*.
selenide, crystals, anisotropy of photoconductivity in single, (11) 313*i*.
effect of Se atmosphere partial pressure on electrical conductivity of single crystals, (3) 81*h*.
effect of background light on steady-state photoconductivity of polycrystalline layers of, (6) 168*d*.
high-voltage photovoltaic effect in films of, (6) 167*j*.
real structure of single crystals deformed by uniaxial pressure, (6) 168*j*.
spectral dependence of photoconductivity in polycrystalline layers of, (6) 170*c*.
systems. See *Systems*.
sulfate, study of vapor-grown crystal platelets, (3) 81*h*.
sulfide, and CdSe, photoconductivity in polycrystalline, (8) 226*h*.
and CdSe films, effects of fabrication on structural and electronic properties of, (7) 191*g*.
crystallization from solutions of cadmium halides, B (11) 320*c*.
effect of O on photoconducting films of, (10) 276*i*.
effects of substrate on films of spray deposited, (9) 242*h*.
electrical conductivity and Hall coefficient of single crystal, (4) 103*j*.
enhancement of photoconductivity in single crystals of, (4) 111*h*.
interactions of O with surfaces of, (11) 317*i*.
layers, photoconductivity of sintered, (10) 289*b*.
microwave emission from *n*-type, (7) 201*c*.
Nd ion bombarded, (10) 288*g*.
photoconductive powder and preparation method, P (5) 129*c*.
photovoltaic effect on single crystals, (10) 276*j*.
search for methods of growing crystals from solution, (1) 24*j*.
SiO layers, multilayer enhancement of microwave piezoelectric conversion in, (10) 288*b*.
X-ray of moire patterns with superposed crystals of, (10) 291*j*.
telluride, effect of doubly ionizable vacancy acceptors on conductivity of donor doped, (11) 316*a*.
effect of pressure and temperature on absorption edge of, (3) 81*g*.
electrical properties as film contacts with metals and film *pn* junctions, (3) 81*d*.
film contacts, photoelectric properties with metals, (3) 72*i*.
films, effect of substrate temperature on macro- and microstructure of, (11) 316*g*.
films, with impurities of groups I and III and Cu, (6) 158*c*.

Cadmium, telluride (*continued*)
intrinsic absorption edge under hydrostatic pressure, (9) 251*f*.
photoelectric properties of *pn* junctions of, (3) 84*b*.
structural dependence on Cu concentration and base temperature, (3) 83*a*.
temperature dependence of band gap in, (5) 141*e*.
Calcia. See *Calcium, oxide*.
Calcination. See also *Firing*.
of cement. See *Cement, burning*.
of ceria, (2) 48*h*.
Calcining, of cement and lime, world standards and trends, (2) 29*d*.
Calcite, + aqueous solution, system $CaCO$-CO_2-H_2O in, (2) 52*h*.
deformed and annealed, X-ray line broadening in, (3) 87*e*.
dislocations, chemical consequences, (3) 81*b*.
and dolomite, O and C isotopic fractionation between coexisting metamorphic, (10) 289*e*.
monocrystals, growth under hydrothermal conditions, B (11) 319*j*.
systems. See *Systems*.
Calcium, aluminate hydrates, (7) 177*j*.
aluminoborate and aluminosilicate glasses, electrical conduction and O diffusion in, (3) 60*i*.
aluminoferrite hydrates, properties of, (11) 294*c*.
boroaluminate glasses, nuclear magnetic resonance studies of, (9) 234*e*.
(Ca,Na)CO_3, cancrinites, atomic arrangement and structure refinement of, (7) 197*i*.
$CaSb_2$, properties obtained by method of S. A. Vekshinskii, (3) 85*h*.
$CaCoSiO_4$ and $CaFeSiO_4$, magnetic properties of, (6) 168*a*.
CaF_2:Dy^{2} lasers, quenching of Dy^{2+} fluorescence by Y^{3+} in, (1) 24*e*.
$CaMn_7O_{12}$, marokite, a new mineral, (6) 168*d*.
$CaMnSiO_4$, magnetic structure of, (5) 138*d*.
$Ca(NO_3)_2$-KNO_3 glass, electrical conductivity of, (2) 31*j*.
$3CaO \cdot Al_2O_3$, calorimetric studies on hydration of, (2) 28*j*.
$3CaO \cdot Al_2O_3$, hydration of, (6) 165*f*.
$2CaO \cdot Fe_2O_3$ and $2CaO(Al,Fe)_2O_3$, IR spectra of, (2) 50*i*.
$2CaO \cdot SiO_2$, DTA and high temperature powder X-ray diffraction of, (5) 135*f*.
Ca_2SiO_4-$CaMgSiO_4$, join, (9) 251*h*.
Ca_2SiO_4 modifications, synthesis and determination of X-ray powder diffraction patterns, (2) 29*a*.
$CaNa_2(SO_4)_2$, glauberite, crystal structure of, (7) 198*d*.
$CaSO_4 \cdot 2H_2O$, crystal growth and transition rate in mixed acid H_3PO_4 and H_2SO_4, (11) 315*a*.
carbide nitriding, effect of liquid phase in fluidized bed on, (5) 137*i*.
carbonate, and cristobalite, early stages of reaction between, (2) 49*c*.
manufacture, P (10) 283*b*.
reaction with clay minerals, (9) 248*c*.
reaction with portland cement, (2) 29*d*.
slurries, stabilization of, P (7) 178*e*.
systems. See *Systems*.
chlorate, systems. See *Systems*.
chloride, systems. See *Systems*.
di-, silicate, infrared absorption spectra of polymorphic modifications of, (1) 22*j*.
diferrite, electrical properties of Y_2O_3 doped, (11) 304*j*.
in feldspars, determination of, (3) 75*h*.
ferrous, silicate, systems. See *Systems*.
fluoride, aqueous slips of, (6) 155*j*.
doped with NaF, dipole relaxation in, (9) 249*i*.
effect of Y^{3+} on reduction of Sm^{3+} in, (1) 20*g*.
precipitation from homogeneous solution, (11) 310*d*.
systems. See *Systems*.
hydroxide, crystals in cement paste, (1) 2*e*.
crystals, preparation and thermal decomposition of, (11) 294*b*.
electrical conductivity of, (6) 167*h*.
magnesium, silicate, systems. See *Systems*.
mono- and di-, ferrites, existence of solid solutions between, (1) 13*h*.
montmorillonites, complexes with fatty acids, (9) 248*f*.
oxide, -Al_2O_3-SiO_2, dissolution of fused silica in melt of, (4) 93*b*.
antiferromagnetic magnetostriction in single crystal, (4) 109*j*.
and containing Sr, comments on sintering in, (8) 226*a*.
electrical conductivity of, (5) 135*d*.
internal friction in ZrO_2 containing, (3) 82*i*.
means to determine, (4) 107*e*.
possible increase during fusion of cement, (2) 28*j*.
production of crystalline in an electric arc furnace, P (8) 218*a*.
reaction with kaolinite, (6) 160*j*.
reactions of, (9) 254*b*.
refractive index of, (9) 254*c*.
in sheet glass, determined by photoelectric emission spectral analysis, (3) 62*b*.
slaking reaction, (1) 10*j*.
stabilized zirconia, cationic self-diffusion in, (6) 165*e*.
stabilized zirconia, O exchange and diffusion in, (4) 112*e*.
systems. See *Systems*.
in tetragonal zirconium oxide, P (3) 79*d*.
-UO_2-ZrO_2, nuclear fuels, (7) 188*a*.
phosphate, nucleation from solution, (2) 44*e*.
K and Ba, fusibility diagram of the system of chlorides of, (4) 111*f*.

Calcium (*continued*)
silicate, hydrates, hydrothermal formation of, (1) 22*f*.
hydrates, morphology and combination with water related to structure of hardened cement paste, (2) 28*f*.
materials, method of making, P (5) 126*g*.
powder from acid clays, preparation and use, (9) 247*i-g*.
in silicate rocks, titrimetric determination of, (2) 45*e*.
sodium, borate, systems. See *Systems*.
and Sr, chromatographic separation, (2) 43*j*.
sulfate hemihydrates, hydration kinetics of α- and β-, (7) 200*f*.
sulfate plaster slurries, effect of impurities and additions on hydration of, (11) 293*f*.
systems. See *Systems*.
and Ta, new double oxide $Ca_2Ta_2O_{12}$, (7) 197*f*.
tri-, phosphate, P (6) 165*a*.
tri-, silicate, effect of Fe^{3+} and Al^{3+} on polymorphism of, (2) 49*d*.
trisilicate, means to determine lattice, (7) 198*i*.
tungstate, trivalent rare earth substitution and theory of coupled substitution, (9) 248*e*.
vanadium bismuth iron garnet, *L*-band properties of, (9) 251*a*.
vanadium-substituted garnets, magnetic and microwave properties of, (9) 251*d*.
Calorimeter, micro-, quantitative DTA with, (3) 76*h*.
Calorimetry, determination, of Zr in South African granites, (11) 309*j*.
of vanadium carbides, (11) 314*e*.
Cameras. See *Photography*.
Cancrinites, (Ca,Na)CO_3, atomic arrangement and structure refinement of, (7) 197*i*.
Capacitors, P (6) 158*i*; P (7) 192*a*; P (8) 220*a*; P (11) 305*a*.
with aluminum silicate scavenger, P (2) 41*b*.
beta tantalum thin-film, P (11) 305*j*.
capacitive impedance element, multilayer, P (3) 74*a*.
ceramic, P (11) 305*b*.
ceramics, thermogravimetry of, (6) 170*i*.
from crystals, and method of making crystals, P (7) 193*c*.
decoupling, P (10) 278*b*.
dielectric-coated foil, P (2) 41*c*.
dielectric materials for, P (3) 74*e*.
disk, multiple variable, P (2) 42*i*.
electrical, P (10) 278*d*; P (11) 305*j*, 306*c*.
with electrodes of metal-coated particles, P (5) 128*j*.
element, for high temperature operation, P (8) 221*k*.
hermetically sealed, P (10) 278*j*.
hermetic seal for, P (10) 278*e*.
high tension, ceramics for, (9) 241*j*.
junction, (8) 219*h*.
manufacture method, P (2) 41*i*.
manufacture, by sputtering tantalum oxide on a Si substrate, P (9) 243*a*.
metal-oxide semiconductor, to measure surface state parameters, (10) 288*a*.
method to make, P (4) 105*a*; P (6) 159*i*.
mixed metal-ceramic, P (3) 73*j*.
of modified barium titanate, P (4) 105*g*.
monolithic, P (11) 305*h*.
multilayer, process to make, P (5) 129*d*.
of *n*-type semiconductor and compensated layer, P (10) 277*j*.
probe, used with conveying means to determine dielectric properties of bulk material, P (11) 311*d*.
regenerative, P (5) 129*g*.
of silvered mica, P (10) 279*f*.
solid, P (8) 221*b*.
solid electrolyte, with anodes from Ta-Ti alloys, (8) 220*f*.
solid electrolytic, with layer of silica on electrolyte layer, P (6) 161*b*.
Ta, with glass-to-metal seal and resilient support for terminal, P (6) 161*b*.
thick film, how to make, (8) 220*a*.
thin barium titanate layers for, (7) 191*f*.
thin-film, electrical properties in Dy_2O_3-B_2O_3-SiO_2 system, (8) 219*j*.
TiO_2, P (3) 73*c*.
UHF bushing-type, (8) 220*h*.
Carbides. See also specific types.
bodies, cemented, containing oxide in matrix metal, P (7) 177*g*.
-carbon, eutectic temperatures of group IVB and VA metal, (11) 317*h*.
cemented, high temperature hardness of, (6) 152*f*.
cemented, structure of two-phase, (9) 256*g*.
composites, new class of hypereutectic, (10) 272*d*.
cubic, effect of high pressure on compressibility of, (11) 316*c*.
dies, diamonds to finish, (6) 143*f*.
fuel, pyrolytic-carbon-coated for reactor, (3) 66*a*.
grinding, diamond wheel for, (7) 177*e*.
highly refractory, porous ceramics from, (7) 187*f*.
hypereutectic, B (5) 142*i*.
interactions, with metals, (7) 178*j*.
metal, high-temperature thermal conductivity of transition, (4) 111*i*.
metal, method to form coating on carbon base, P (10) 274*g*.
metallic, welding to metals, (7) 179*d*.
metal-like, contact interaction with graphite at high temperature in vacuum, (3) 65*j*.
and nitrides, of transition metals, relation between properties and their electronic structure, (9) 254*g*.
in nuclear energy, proceedings of symposium, B (6) 171*j*–172*b*.

Carbides (*continued*)
oxy-, of Nb, formation conditions of, (6) 165*d*.
Si, solid solution, P (9) 241*f*.
sludge, in manufacture of portland cement, (3) 59*d*.
with NaCl structure, superconducting critical temperatures, (7) 203*f*.
structures, preparation of, P (11) 303*c*.
submicron, method of making, P (5) 126*j*.
transition metal, superconductivity in, (9) 257*a*.
tungsten-cobalt, mechanism of fracture in sintered, (10) 288*e*.
ultrafinish grinding of, (7) 177*g*.

Carbon. See also *Graphite*.
agglomerated, compression at high temperature, (11) 314*d*.
aluminate, systems. See *Systems*.
article, composite, and method to produce, P (5) 126*a*.
containing rare earths, process to graphitize, P (9) 240*c*.
continuously forming, P (10) 274*e*.
base, method to form metal carbide coating on, P (10) 274*g*.
bolometer, static response characteristics, (3) 76*g*.
carbonaceous base, and oxidation resistant coating for, P (10) 274*d*.
carbonaceous solids, adsorption of helium by, (4) 109*i*.
$C_2Al_2B_{10}$, phases and twinning in, (8) 226*g*.
C-Fe solid solutions, thermodynamics of dilute, (5) 141*i*.
in clays, determination of, (2) 46*h*.
-coated, duplex fuel particles, (3) 66*d*.
deposition kinetics, analysis in isothermal flow systems, (4) 109*j*.
diffusion, in solid iron, relation to adherence of coating, (4) 91*b*.
diffusion, into W and Mo at low C concentrations, (10) 284*d*.
diffusivity, determined in Ta and Nb carbides by layer-growth measurements, (5) 135*b*.
dioxide, alteration of albite by H_2O containing, (8) 227*e*.
carbonation chamber with adjustable concentration, (6) 144*h*.
determination in soda-lime-silica glasses, (1) 5*f*.
solubility in glass, (9) 232*j*.
systems. See *Systems*.
dislocations, energy losses due to motion of, (4) 112*a*.
effect, on wear of tar-impregnated burned magnesite furnace linings, (11) 301*d*.
electrodes, from bituminous mixes, P (9) 240*f*.
factors influencing performance of pitch binders in baking of, (4) 111*i*.
for reduction of O in fuel cell, (8) 215*f*.
elements, method to produce porous, P (7) 188*i*.
fibrous, forming articles of, P (5) 126*e*.
fibrous, properties, production, and applications, (9) 238*h*
films, adsorption behavior, (3) 70*f*.
in fireclay, catalytic separation of, (7) 185*f*.
free spin centers in, interaction of strongly adsorbed O with, (4) 111*j*.
glassy, galvanomagnetic properties of, (4) 111*g*.
or graphite, process to join to similar materials or refractory metals, P (10) 263*j*.
-graphite bearings, friction and wear, (2) 44*h*.
graphitized, oxidation resistant bodies, P (9) 241*a*.
magnetism, re-evaluation of, (4) 112*j*.
metal carbide-, eutectic temperatures of group IVB and VB, (11) 317*h*.
molar refraction, relation to coordination in polymorphs of boron nitride and, (8) 227*i*.
molecular sieves, (4) 102*d*.
monoxide and oxygen, adsorption under irradiation on alumina, (11) 313*f*.
oxidation of, (4) 113*i*.
oxidized by atomic oxygen, electron microscopy of surface changes, (2) 51*f*.
oxidized by atomic oxygen, kinetics of, (2) 51*c*.
and O, isotopic fractionation between coexisting calcite and dolomite, (10) 289*e*.
powder, mold for Ti casting, (6) 153*d*.
in products, determination by a high frequency combustion furnace, (4) 107*h*.
pyro-, effect of B on structure and mechanical properties at high temperature, (11) 301*c*.
pyro-, magnetic anisotropy theory of, (4) 112*f*.
pyrolytic-, coated fuel, fission-gas release during irradiation, (6) 152*d*.
coating nuclear fuel particles with, (9) 237*j*.
films, kinetics of deposition from methane and carbon suboxide, (4) 112*c*.
manufacture of reactor fuel elements and their coating with, (9) 238*a*.
spiral and whisker growth in, (9) 256*e*.
Young's modulus of in relation to preferred orientation, (2) 54*a*.
refractories. See *Refractories*.
rod, effects of expansion on measuring refractoriness under load, (3) 67*h*.
-silica, reactions in charred silica-reinforced phenolic resins, kinetic studies of high-temperature, (8) 215*e*.
in sintered nickel-base materials, determined by spectral analysis, (3) 66*c*.
-sulfur, amber glass, (3) 60*g*.
systems. See *Systems*.
turbostratic, measurement of interlayer spacings and crystal sizes in, (4) 112*a*.
-U alloys, mechanical behavior at high temperature and fabrication by extrusion, (11) 301*g*.

Carbonates, alkaline earth metal, investigation of forming reaction, (1) 23*b*.

Carbonates (*continued*)
and clay minerals, solid-phase interaction during thermal analysis, B (2) 56*b*.
of Ireton formation, central Alberta, Canada, (2) 46*j*.
sediments, deep-sea from Red Sea and their implications on marine lithification, (11) 315*d*.
sediments, geochemical evolution of early paleozoic of central Bohemia, (11) 317*d*.
stability, in system $MgO-CO_2-H_2O$, (3) 85*j*.

Carbonation, of cement mortars, effect of repeated wetting and drying, (8) 206*g*.
chamber, with adjustable CO_2 concentration and humidity, (6) 144*h*.
de-, Bowen's series, (9) 250*c*.
of mortars, changes in weight and dimensions in, (1) 2*d*.
process, in sand-lime mortar, (8) 206*f*.
resistance, of lime-fly ash brick, (2) 35*e*.

Casting. See also *Molding; Molds; Refractories; Slip casting*.
apparatus, inlet orifice for, P (10) 274*b*.
behavior and properties of earthenware bodies, effect of new deflocculants for, (6) 156*j*.
fusion, with hot tops, (5) 125*f*.
lost wax, silicon nitride as accelerator for gelation of silicic acid sol in, (6) 153*f*.
mold, method using casting slag, P (2) 38*c*.
mold, slag composition for, P (3) 71*a*.
precision, pattern material for investment, P (9) 240*c*.
process, review of slips, (2) 39*h*.
process, using borax-silica slag, P (4) 100*g*.
property, of clays and its control, (2) 39*b*.
refractory, method to form, P (5) 123*c*.
refractory, method to improve grain structure and soundness in, P (7) 188*g*.
Shaw, of refractory molds and dies, (3) 68*i*.
slip, apparatus, P (4) 103*a*.
slips. See *Slips*.
of UC, B (6) 172*f*.

Castings, monolithic investment shell, P (1) 11*h*.

Cast iron. See *Enameling metals; Iron*.

Catalysts, carrier, high temperature-resistant and method of making, P (5) 125*j*.
composite, synthetic alumina, silica-alumina hydrocarbon cracking, and method for cracking, P (9) 241*c*.
composition, of manganese oxide-coated alumina with Ni or Co chromites and product, P (4) 101*g*.
mangano-chromia-manganite containing alkali metal and alkaline earth metal manganates, P (4) 100*f*.
of the oxides of alkali and Cr on eta alumina, P (6) 154*a*.
of oxides of iron, rare earth, and zirconium, P (4) 100*h*.
containing activated bauxite, P (4) 100*i*.
containing vanadium and tin oxides, process for making, P (6) 155*h*.
conversion, comprising aluminosilicate from hydrogen organoperoxymetalloaluminosilicate, P (4) 100*i*.
cracking, coke formation on silica-alumina, (5) 125*d*.
and process of cracking, P (8) 225*b*.
of silica-alumina-magnesia, P (10) 274*f*.
method to prepare with cobalt oxide, molybdenum oxide, and alumina, P (1) 18*j*.
of molybdenum oxide, tellurium oxide, and manganese phosphate, P (4) 100*h*.
nucleation, in glass ceramics, (10) 265*a*.
pellets, diffusivities in pressed, (2) 36*c*.
pellets, of sintered metallic oxide, P (10) 274*e*.
plasma arc sprayed, P (10) 274*j*.
Pt, effect on crystallization of $Li_2O-MgO-SiO_2$ glass, (7) 179*g*.
preparation process, for platinum metal-crystalline zeolite, P (4) 101*f*.
role, in crystallization of glass, (1) 5*i*.
siliceous, attrition resistant and method of preparation, P (4) 100*d*.
for synthesis of ammonia, P (6) 154*a*.
of tin and antimony oxides, process for making, P (6) 155*i*.
vanadium pentoxide potassium pyrosulfate, and method of making, P (4) 102*b*.

Cathode-ray tubes. See *Tubes*.

Cathodes, base structure, P (6) 158*g*.
cold, with Ni base, CaO interface and MgO layer, P (6) 159*a*.
dispenser, P (6) 159*b*.
indirectly heated, method of preparing, P (2) 42*d*.
method to make, P (10) 279*a*.
multi-work-function, P (6) 160*h*.
of radio receiving tubes, shock and vibration resistant heater for indirectly heated, P (10) 279*e*.
sputtering, apparatus to coat articles by, P (7) 192*h*.
structure, P (9) 243*c*.
thermionic, P (11) 305*g*.
thermionic, vacuum breakdown in presence of, (10) 277*b*.

Cations, diffusion, in BeO, (3) 79*j*.
distribution, redetermination for $MgAl_2O_4$ by neutron diffraction, B (2) 55*i*.
exchange, in clay minerals, nature of hydration of, (3) 83*j*.
of lanthanides, change in thermodynamic functions on hydration of trivalent, (4) 109*j*.
sensitive glass electrodes, additional studies of, (6) 146*h*.
vacancies, effect on magnetic annealing of $Co_zFe_{3-z}O_4$, (10) 285*f*.
preparation of spinels with, (7) 202*i*.
role in disaccommodation of manganese ferrite, (10) 290*a*.

Cells, electroluminescent, P (8) 221*f*.
electroluminescent, with phosphor-conductor adhesion, P (8) 220*j*.
galvanic, platinum/glass-refractory material/-platinum, effect of atmospheric oxygen on bubble formation in, (1) 4*c*.
photoconductive, optically immersed, P (6) 150*e*.

Celsian, type color, for underglaze blue, (4) 103*b*.

Cement industry, combustion gases, glass fabric to purify, (11) 296*f*.
plant layout, to produce keramzit, (11) 294*i*.

Cements. See also *Concrete; Mortars; Plasters; Refractories*.
accelerator, for noncorrosive, P (1) 3*b*.
alkalis in, flame photometry to determine, (3) 58*j*.
alumina, effect of inclusions on properties, (2) 28*e*.
alumina in, means to determine, (3) 58*h*.
aluminous slag, and method of increasing strength of, P (10) 262*g*.
-asbestos binders, analysis of, (6) 144*d*.
binding composition, and method of making, P (2) 29*f*.
blast-furnace, effect of diatomaceous earth on properties of, (3) 59*b*.
bottle-hydrated, sorption of water by compacts of, (10) 262*d,f*.
bulk, method to store, (1) 2*c*.
burning, phase formation reactions during, (1) 2*g*.
calcining, world standards and trends, (2) 29*d*.
calcium aluminate, P (4) 90*j*.
cementing materials, history, B (7) 204*f*.
clinker, change in lattice constant of magnesia and seawater magnesia during heating, (6) 152*d*.
effect of mineralizing additives on formation of, (8) 206*f*.
improvement of formation by mineralizers, (7) 178*b*.
method and arrangement for making, P (6) 144*j*.
microscopy of, B (4) 115*i*.
from tailings of nepheline rocks, effect of mineralizer on, (1) 2*d*.
three-stage burning, (7) 178*e*.
composition, P (5) 119*d*.
and method of utilizing, P (2) 29*g*.
and preparation, P (5) 119*e*.
in concrete, kinetics of hydration at elevated temperatures, (9) 231*d*.
concrete and mortar, effect of wind on creep and drying shrinkage of hardened, (3) 58*f*.
and concrete products, carbonation chamber to study, (6) 144*h*.
content, determination in concrete and mortar, (10) 262*g*.
elastic constants, method to determine, (6) 144*i*.
erosion, mechanism of cavitation, (4) 90*j*.
expansive and shrinkage-compensated, P (8) 207*d*.
ferrite phase in, and its behavior during hydration, (3) 58*g*.
fibrous, method and apparatus for corrugating sheets of, P (4) 101*a*.
fineness, new method to determine, (6) 144*g*.
hardened paste, electron microscopy by replica method, (11) 310*d*.
hardening, and hardness, relation of particle size to, (3) 58*d*.
process, of building materials from, (5) 118*g*.
in zone of contact with different solid phases, (3) 58*g*.
high-alumina, P (9) 231*d*.
in high temperature mortars, behavior of, (3) 65*g*.
for high temperature wells, P (7) 178*d*.
hydration, during heat treatment, (10) 262*c*.
hydraulic, additives, P (2) 29*f*.
analysis techniques, (11) 293*h*.
polymer-modified, (1) 2*i*.
Iraquian, properties of, (2) 29*a*.
kilns. See *Kilns*.
low calcium aluminate, concrete from as liner for rotary kiln, (2) 36*j*.
magnesia, magnesium hydrosilicates as stabilizers for, (2) 28*f*.
magnesium oxy-, melamine-formaldehyde added to improve water resistance of, P (5) 119*a*.
materials and techniques, (11) 293*j*.
method and apparatus to make, P (5) 119*a*.
mills. See *Mills*.
mineral admixtures for, methods of estimating activity of, (4) 90*g*.
mortars. See *Mortars*.
paste, and concrete under load, temperature change effect on, (5) 118*i*.
effect of water/cement ratio on structure and strength of, (8) 206*h*.
and fresh mortars, rheology of, (1) 3*b*.
hardened, morphology and combination with water of calcium silicate hydrates and structure of, (2) 28*f*.
hardened portland, $Ca(OH)_2$ and ettringite crystals in, (1) 2*e*.
photochromic, P (2) 29*i*.
portland, apparatus and method to process raw feed, P (5) 119*c*.
carbide sludge in, (3) 59*d*.
determination of Poisson's ratio by measurement of elasticity, (6) 144*j*.
effect of MgO on, (8) 206*j*.
effect of sulfate solutions on, (9) 230*j*.
heat of hydration, (11) 294*e*.
large increase of free CaO and MgO in during fusion, (2) 28*j*.
limestone containing flint as raw material for, (2) 28*f*.

Cements, portland (*continued*)
means to determine SO_3 in, (4) 90*h*.
method to form gypsum crystals in, (8) 207*c*.
particle size distribution determined from Wagner turbidimeter data, (3) 59*c*.
reaction with calcium carbonate, (2) 29*d*.
and slag, development of strength and hydration at 20°, 5°, and 1°C, (1) 2*f*.
water requirements and occurrence of minor and trace elements in, (11) 293*j*.
portland clinker, (7) 178*d*.
effect of BaO on formation of, (5) 118*g*.
knowledge of phase composition, (10) 262*h*.
method to detect K_2SO_4 in, (8) 207*e*.
phase computation on an equivalent basis, (2) 28*h*.
production and properties, effects of alkalis on, (5) 118*f*.
products, reactivity of, (5) 118*f*.
quick setting, mass production problems in, (8) 207*f*.
raw materials. See *Raw materials*.
raw mix, X-ray emission analysis, (9) 231*b*.
raw mixes, computers to calculate composition of, (8) 206*e*.
raw slurry, control of water in, (9) 230*h*.
from red mud, manufacture of low-silica high-iron, (6) 144*f*.
research, conditions of, (10) 262*e*.
rheology, effect of agitation on, (3) 58*j*.
sack pallet, and handling equipment, P (4) 91*a*.
setting, effect of chemicals on, (2) 28*j*.
setting, effect on durability of wall and floor tile, (2) 39*b*.
sheets, method to apply silicate to wet asbestos-slag before setting, P (11) 302*g*.
silicate, for technical and dental use, (2) 29*g*.
slag in, determination of, (8) 206*j*.
stable, with high MgO content, (2) 29*h*.
strength, aspects of mechanical, (6) 144*f*.
method to predetermine 28-day in 5 hours, (4) 90*h*.
pressing method to test, (2) 29*c*.
system, hard setting, nonshrinking, P (5) 119*f*.
-water suspensions, structure forming role of solid surfaces during bonding with, (3) 59*c*.
Cerallte, synthetic, (5) 142*d*.
Ceramic industry, air pollution abatement in, (10) 292*b*.
apparel for workers, (2) 54*f*.
dust measurements in, (10) 280*i*.
dust protection apparatus, (10) 280*c*.
in India, (2) 54*g*.
insertion paper for, P (10) 276*f*.
R & D in, (6) 171*d*.
Swedish, (10) 292*c*.
Zsolnay Porcelain Factory, Pecs, Hungary, products range from statuettes to high tension insulators, (2) 54*g*.
Ceramic-metal systems. See also *Enamels*.
composite, low-density aluminum-ceramic, (9) 232*a*.
composites, state of the art, (3) 59*h*.
and enamel, 1965 bibliography and abstracts, B (7) 204*a*.
fish scaling, etching to control, (6) 145*d*.
flame-spraying technique, applications of, (6) 145*b*.
interfaces, adherence oxides in development of chemical bonding at, (2) 30*c*.
laminated, composite material, (1) 3*e*.
sheets, formability of, (9) 231*i*.
units, means to fasten, (9) 231*g*.
Ceramics, batches, compounding according to their formability, (2) 54*h*.
electrotechnical and electronic, microscopy in field of, (11) 310*h*.
history, group to study period 1450 to 1750, (2) 27*i*.
International Competition Faenza, 1965, (2) 27*i*.
mechanical behavior of, (6) 171*c*.
to metal, art of bonding, P (4) 104*i*.
mysteries of, (7) 203*i*.
origin of word, (10) 292*b*.
product, and process of producing, P (6) 149*c*.
products, trends in evolution of, (7) 203*i*.
special, (2) 55*a*.
in the U. S., (9) 229*i*.
Ceramsite. See *Keramzit*.
Ceria. See *Cerium, oxide*.
Cerium, Ce^{3+} ions in glass, infrared absorption of, (3) 61*i*.
Ce_2S_3 and CeS, comparison of methods for preparing, (6) 164*f*.
dioxide, transformation of and interactions with chlorides of Li and K and with the carbonate and sulfate of Na, (3) 87*j*.
dioxide and TiO_2, color produced in glass by, (3) 62*c*.
equilibrium, in alkali borate and alkali silicate glasses, (3) 60*h*.
oxide, calcination and sintering, (2) 48*h*.
extraction from rare earth ores, P (8) 225*f*.
interaction with fluoride melts, (10) 287*a*.
systems. See *Systems*.
quadrivalent, thermal decomposition of hydroxide of, (10) 291*b*.
thin films, dielectric properties of, (11) 315*b*.
valency, in synthetic and natural cerium aluminates and silicates, (5) 142*d*.
Cermets, alloy, crucibles and their use for chemical analysis, (8) 215*i*.
alumina base, effect of additives on sintering mechanism of, (6) 151*g–j*.
with bonded metal members, P (5) 126*b*.
construction materials, protection from corrosion, (1) 8*a*.
economic factors in production of, (3) 66*e*.
Cermets (*continued*)
improved, method to produce and articles from, P (5) 120*b*.
infiltrated oxide, B (11) 320*f*.
means to make, P (9) 232*g*.
method to make, and articles from, P (10) 264*a*.
molybdenum-UO_2, loss of UO_2 by high temperature diffusion, (3) 68*f*.
parts, use of hard-alloyed tools when pressing on transfer presses, (3) 69*j*.
porous, broaching of, (3) 65*j*.
refractory, laboratory apparatus for electron-beam vacuum melting and machining of, (1) 17*h*.
resistors, of nichrome-silicon monoxide for compatible thin-film monolithic circuits, (7) 191*i*.
shapes, fabrication by pneumatic impaction, P (1) 11*d*.
SiC, durability in stressed state, (10) 285*b*.
strength, estimate for complex stressed state, (1) 8*g*.
technology, (10) 270*f*.
Ti carbide, Al-bonded, (8) 214*i*.
UC and UC-iron, bonding to canning materials, B (6) 172*g*.
zirconium-boride, end caps to protect thermocouples, (1) 16*h*.
zirconium-boride, tips on thermocouples, (3) 76*b*.
Cesium, alum, Cs compounds from, P (1) 19*a*.
bromides, interaction with di-, tri-, and tetrabromides of Ti, (11) 317*e*.
$CsGeCl_3$, crystal structures of, (1) 21*a*.
chloride, interaction with those of Nb and Rb in melts, (5) 141*b*.
chloride, systems. See *Systems*.
chromate, systems. See *Systems*.
oxide, systems. See *Systems*.
silicate glasses, electrical conductivity and NMR chemical shift in, (5) 120*c*.
sulfate, systems. See *Systems*.
systems. See *Systems*.
Chalcogenides, glass, forming regions, variations in properties, infrared absorption by oxide impurities, and structure, (11) 296*h*.
Chalk, deposits, arrangement of quaternary and prequaternary in Lithuania, (6) 164*c*.
Chamotte. See also *Refractories*.
properties, obtained by firing clays in rotary kilns, (5) 124*h*.
Checker-brick. See *Refractories*.
Chemical analysis. See *Analysis*.
Chemical industry, glassware in, (1) 5*j*.
Chemical properties, of runner brick, related to physical properties and damage done to them, (9) 239*c*
Chemisorption, of collectors, B (7) 204*f*.
Chemistry. See also *Analysis; Electrochemistry; Geochemistry; Thermodynamics*.
analytical, effect of recent developments, (1) 17*c*.
analytical, of metallic elements, B (3) 88*a*.
chemical apparatus, progress of glass, (5) 131*f*.
chemical data, B (9) 258*b*.
chemical procedure, to isolate Th from siliceous materials, (2) 44*c*.
chemical process equipment, materials for, (4) 108*i*.
chemists, optical determination methods and devices for, B (6) 174*h*.
colloid and crystal, relation in clay minerals, (2) 56*i*.
crystal, of alpha-boron derivates, (7) 198*b*.
of laminar silicates, (9) 249*a*.
in systems $BaTiO_3$-UO_2 and $BaTiO_3$-$BaUO_4$, (6) 157*i*.
defect, relation with density in crystalline solids, (9) 254*f*.
in determination of age of radiogenic minerals, (11) 317*e*.
of emery-like rocks, from Scotland, (11) 314*j*.
high temperature, selected topics in, B (10) 292*f*.
of palygorskites, colloid, B (8) 228*f*.
of silicates, present and future, (2) 54*g*.
surface, Scandanavian symposium, B (7) 204*e*.
Chert, (2) 47*e*.
Chervetite, lead pyrovanadate, $Pb_2V_2O_7$, new mineral, (6) 169*d*.
new data on, (9) 252*b*.
China, graceful, of Blackpool, (6) 144*b*.
China clay. See *Kaolin*.
Chinaware. See also *Art and artware; Bone china; Dinnerware; Porcelain*.
hotel, developments in, (2) 39*c*.
Chlorides, ferroelectric, of perovskite type, (1) 21*a*.
-kaolin, ammonium, structural and bonding features, release of interlayer NH_4Cl, (9) 248*a,b*.
molten, behavior of TiO + C and Ti_2O_3 + C anodes during electrolysis of, B (1) 26*i*.
of Nb, interaction with chlorides of Rb and Cs in melts, (5) 141*b*.
of tin, interaction with chlorides of Ta, Nb, Fe, and Al, (11) 317*d*.
of type Me_2MoCl_8, fusibility diagrams of, (10) 284*c*.
Chlorine, activated sintering based on, (10) 272*a*.
systems. See *Systems*.
Chlorite, iron plus Mn content, relation between magnetic susceptibility and, (3) 85*b*.
regular mixed-layer clay mineral, high-aluminous chlorite-swelling, (7) 200*e*.
Chromates, (V), X-ray studies of alkali and alkaline-earth, (3) 87*i*.
Chromatography, apparatus to prepare specimens for, P (10) 281*f*.
cation-exchange, to separate rare earths from other elements, (6) 163*c*.
Chromatography (*continued*)
elution, P (4) 108*a*.
gas, fuel-gas analysis by, (4) 107*e*.
-liquid partition, to study high pressure vapor-liquid equilibria of multicomponent systems, (1) 21*g*.
radio frequency cell for, P (3) 77*d*.
of rocks and minerals, (2) 44*b*.
and solvent extraction to determine Al and Fe, (6) 161*i*.
measurements, preparation of porous sampler for, (2) 45*d*.
self-labeling, alumina as reagent for, (5) 131*j*.
to separate, Ca and Sr by elution with ammonium sulfate solution, (2) 43*j*.
separation, of rare earths combined with chemical detection, (8) 223*j*.
Chrome. See *Chromium; Refractories*.
Chrome-magnesite brick. See *Refractories*.
Chromia. See *Chromium, oxide*.
Chromite. See also *Refractories*.
grains, X-ray study of behavior of sesquioxides deposited in, (5) 142*b*.
magnetic susceptibility of, (6) 168*a*.
ores, effect on properties of fireclays, (8) 225*a*.
rare earth, crystal parameters of, (6) 166*d*.
Chromium, carbide alloys, corrosion and erosion carbide alloys, resistance in corrosive environments, (11) 300*j*.
strength of, (3) 68*d*.
strength of hard, (10) 272*d*.
carbides, electrical properties of, (11) 316*a*.
carbides, free energy of formation of, (11) 317*b*.
chloride systems. See *Systems*.
Cr^{3+}, ion, microwave paramagnetic resonance in MgO, (7) 201*e*.
ions, Jahn-Teller distortion induced in spinels by, (10) 287*e*.
thermoluminescent formation in MgO, (3) 87*g*.
CrB, NMR method to study, (10) 289*b*.
Cr^{3+}-Cr^{4+} equilibrium, in binary alkali silicate glasses, (3) 60*g*.
Cr_5Ge, preparation of, (8) 220*e*.
Cr_5O_{12}, crystal structure, (1) 19*f*.
concentrates, production, P (2) 48*c*.
dioxide, anomalous temperature dependence of lattice constant of, P (10) 283*i*.
electrical resistivity of ferromagnetic, (4) 111*c*.
hot-pressing of, (2) 50*h*.
method to prepare rutile type crystalline structure of, P (6) 164*h*.
disilicide, boundaries of region of homogeneity and nature of, (11) 314*d*.
(II) fluoride, and dissociation energy of chromium(I) fluoride, mass spectrometry of, (9) 251*h*.
in glass, physical and chemical estimation of trivalent and hexavalent, (3) 61*i*.
in glazes and colors, (7) 190*d*.
-Li vanadate, crystallography of, (6) 166*i*.
and magnesium oxides, solid phase reactions between, (7) 187*g*.
and Mn oxides, reaction with MgO, (10) 271*c*.
ore, beneficiation of, P (2) 47*c*.
oxide, α-, initial sintering of, (2) 50*j*.
anomalies in modulus of elasticity in shear of, (10) 283*h*.
colloidal hydrous, mutual adsorption of clay minerals and, (10) 288*d*.
effect on high-fired basic brick, (10) 271*g*.
growth of monocrystals by verneuil method, B (11) 320*c*.
and lime, sintering reactions between, (4) 113*g*.
magnetoelectric effect in, (10) 289*e*.
-MgO, electrical conductivity in mixtures and at different stages of sintering, (3) 81*b*.
modified by vanadium oxide, magnetic properties of, (10) 288*a*.
phase relations with IrO_2 in air, (6) 160*e*.
systems. See *Systems*.
spinellids, and transformations which occur during calcining, (10) 284*a*.
trioxide, process for continuous production of, P (4) 109*e*.
trivalent, light absorption incorporated into garnet structure, (3) 80*e*.
from vapor phase, formation of textured nitride layers on, (10) 286*i*.
Chrysotile, asbestos, increasing = Si—OH surface groups in, (5) 137*h*.
treatment, and product, P (2) 47*j*.
Circuits, components, apertured thin-film, P (10) 277*g*.
electronic, miniaturized, P (9) 243*j*.
integrated, GaAs epitaxial technology for, (7) 191*f*.
micro-, preparation of oxide-isolated silicon wafers for, (11) 304*g*.
micro-, with series and parallel connections, P (9) 243*j*.
monolithic, cermet resistors for compatible thin-film, (7) 191*i*.
printed, method to make, P (4) 105*j*.
oxide underlay for, P (3) 74*c*.
reusable transfer plate for making, P (4) 106*e*.
on substrates, advances in applying, (10) 276*h*.
Ta, substrates for thin-film, (9) 242*e*.
thin film R-C, method to fabricate on glass substrate, P (9) 243*i*.
Classification. See also *Separation; Separators*.
of clay minerals, B (7) 204*a*.
of finely divided materials, apparatus for, P (2) 47*b*.
-pulverization, impact, P (3) 78*i*.
Classifiers, P (11) 311*c*. See also *Beneficiation*.
for air, mechanical, P (5) 131*c*.
and pulverizer, P (3) 79*b*.
and reducer, fluid comminutor type, P (8) 225*b*.
for solids, in gaseous suspension, P (5) 130*j*.

Clays. See also *Ball clay; Fireclay; Kaolin.*
acid, properties of clays and silica hydrogels from, (9) 247*f,g.*
Albany slip, (9) 247*b.*
alumina from, production of, (9) 247*e.*
apparatus to whiten, P (5) 133*c.*
beneficiation, P (2) 47*d.*
from bentonites and shales in Alberta, study of Upper Cretaceous, (3) 86*d.*
bloating type, instead of zircon for ladles for killed steel, (8) 216*i.*
Brazilian, (2) 46*g.*
brick, chemical composition and phases of soluble substances occurring in, (8) 225*e.*
chemical composition and phases of soluble substances occurring in typical, (11) 300*d.*
mineralogy of British, (5) 124*f.*
Bulgarian, physicochemical and technological properties of, (5) 139*g.*
casting property, and its control, (2) 39*b.*
china, for ceramic uses, (11) 312*b.*
china, processing of English, (1) 18*j.*
deposits, in central Eifel and determination of their extent by electrogeophysical method, (3) 78*b.*
deposits, prospecting by geophysical electrical methods, (6) 164*j.*
determination, of carbon and organic matter in, (2) 46*h.*
Egyptian, adsorption of phosphate ions by, (6) 165*a.*
elasticity, in relation to their heat treatment, (10) 282*g.*
enameling, properties and performance, (4) 91*j.*
in English granites, factors bearing on natural synthesis of, (5) 133*i.*
En value, instrument to determine, (9) 245*c.*
extrusion, electrolytes in, (3) 65*c.*
fine fractions, study with supercentrifugal dispersion analysis, (2) 45*c.*
fired, color designation of, (3) 75*d.*
in rotary kilns, properties of chamotte obtained by, (5) 124*h.*
use of hollow brick from, (2) 36*a.*
flint, middle and late Pennsylvanian, (2) 46*i.*
flint, properties of those from Montes Claros, Minas Gerais, (3) 78*a.*
heat of wetting, effects of drying and heating pretreatments on, (4) 111*k.*
Indian, examination by DTA, X-ray, and electron microscopy, (7) 203*b.*
infrared absorption spectra and electron microscopy, (3) 84*d,e.*
kaolinitic, dehydroxylation reaction kinetics of, (2) 49*g.*
occurrence and characteristics of, (6) 169*f.*
international conference, B (2) 55*i.*
of Ireton formation, central Alberta, Canada, (2) 46*j.*
Lithuanian quaternary and prequaternary, physical and chemical properties of, (9) 253*a–b.*
mineral analysis, X-ray diffraction techniques in, (3) 75*h.*
mineralogy, of Pennsylvanian redbeds and associated rocks in Colorado, (5) 132*j.*
mineralogy, of some Upper Devonian sediments from New South Wales, (4) 108*h.*
minerals. See also specific types.
analysis by quantitative dilatometric tests, (7) 197*f.*
change of infrared absorption spectra by dehydration and rehydration of, (5) 134*f.*
change in infrared spectra by dehydration, (5) 134*h.*
and colloidal hydrous chromium oxide, mutual absorption of, (10) 288*d.*
exchange adsorption of Sr on, (1) 21*i.*
fraction and surface layer in Spanish soils, (9) 247*b.*
high-aluminous chlorite-swelling chlorite regular mixed-layer, (7) 200*e.*
infrared absorption patterns (OH region) of, (1) 22*i.*
infrared absorption spectra of, (6) 168*e.*
infrared study of mixed-layer, (9) 250*f.*
interstratified in "taguas," (3) 78*c.*
mutual adsorption of clay minerals and colloidal hydrous chromium oxide, (10) 288*d.*
nature of hydration of exchange cations in, (3) 83*j.*
particle sizes determined by small-angle X-ray scattering, (6) 162*i.*
(phyllosilicate) classification, B (7) 204*a.*
reactions with calcium carbonate and ammonium chloride, (9) 248*c.*
salt resistance of dispersions of, (10) 290*j.*
sorption of B by, (3) 85*b.*
thermal expansion of, (2) 53*i.*
mobility of hydrogen and mechanical properties of, (7) 201*e.*
moistening, with steam, (2) 35*i.*
Montana, 1962–1964, (8) 225*h.*
in 1964, (1) 18*b.*
from northeastern Brazil, properties of, (2) 47*b.*
in Ontario, (6) 164*d.*
Pennsylvania, properties and uses, (11) 312*h.*
plastic, interpretation of torsional hysteresis in, (1) 13*b.*
pot, effect of glass composition on corrosion of, (8) 209*e.*
preparation, theory and practice, (6) 164*h.*
process, vinyl amine modified, P (10) 283*e.*
products, apparatus to produce hardened, P (II) 300*d.*
combustible materials in heavy, (II) 300*c.*
review of Canadian industrial, (1) 18*e.*
raw materials, sampling and winning of heavy, (3) 78*a.*

Clays (*continued*)
reactive hot-pressing of, (10) 290*e.*
refractory, effect of aluminum sulfate on properties of, (3) 66*f.*
exploratory drilling of, (8) 225*b.*
relations between densification, mullite formation, slag resistance, and firing, (2) 36*i.*
from Suzano, Brazil, physicochemical properties of, (11) 312*g.*
resources, Kentucky's, (8) 225*h.*
saponite and lizardite, veins on Isle of Rum, (5) 133*h.*
sedimentary, composition of, (7) 197*j.*
sediments, geochemical evolution of early paleozoic of central Bohemia, (11) 317*d.*
sensitivity to drying, new method to determine, (2) 44*e.*
sensitivity to drying, quantitative evaluation of, (5) 130*h.*
slurries, treated, P (5) 134*a.*
slurry, viscosity stabilized, P (10) 283*g.*
soft alluvial, use in lightweight aggregate, (6) 151*g.*
soil, chemical dissolution in study of, (2) 48*f.*
Spanish, (2) 46*h–j.*
Spanish, infrared spectrography and X-ray diffraction of, (9) 250*j.*
for structural products, elimination of harmful effect of limestone inclusions in, (6) 151*d.*
studies, significance of structure determinations of layer silicates for, (8) 227*c.*
surface area, determination by DTA, (7) 198*a.*
swelling, dispersion, and hydration of, (7) 203*h.*
systems. See *Systems.*
Texas, bloating characteristics of, (8) 225*a.*
thermal treatment, new principles of, (11) 312*f.*
for tile, (2) 35*g.*
ultramicrotome sections, for microscopy, (3) 85*f.*
in various atmospheres, firing behavior of, (5) 136*g.*
water in, electrogravimetry of, (2) 49*j.*
wet, special handling, (7) 185*d.*
Cleaning, alkaline, improvement for enameling industry, (4) 91*h.*
cleanability, report on test for enamel, (7) 179*b.*
glass, composition for, P (7) 183*b.*
of metal, for enameling, (8) 208*b.*
solutions, effect on enameled surfaces, (3) 59*i.*
steel, methods and composition for, P (9) 232*d.*
Clinker. See *Cement; Dolomite.*
Coagulation. See *Agglomeration.*
Coal. See also *Fuels.*
refuse, preparation for manufacture of lightweight aggregate, (7) 185*c.*
-shale, gangue contamination of, (7) 194*g.*
Coatings. See also *Enamels; Glazes; Resins.*
adherence, diffusion of carbon in solid iron as related to, (4) 91*b.*
Al_2O_3, on Ni, (1) 24*j.*
application. See *Electrostatic processes.*
for automobile exhausts, (9) 231*g.*
CdSe, high-voltage photovoltaic effect in poly crystalline, (6) 167*j.*
CdS and CdSe, effects of fabrication parameters on structural and electronic properties of, (7) 191*g.*
CdTe, effect of substrate temperature on macro- and microstructure of, (11) 316*g.*
with groups I and III impurities, (3) 83*a.*
with impurities of groups I, III, and Cu, (6) 158*c.*
thin film, photoelectric properties of *pn* junctions of, (3) 84*b.*
carbon, application to nuclear fuel particles, (9) 237*j.*
of ceramics, by W, (10) 277*b.*
for cermet, protective and decorative electroplated and chemical, (1) 8*a.*
clay, means to control foaming during application, P (11) 309*c.*
coated articles, wear- and strain-resistant, P (3) 60*b.*
color, for aluminum, (1) 3*d.*
composition, for casting molds, P (1) 11*h.*
composition, for molds and cores, P (6) 155*c.*
copper and gold, structure and annealing on glass, (11) 305*d.*
diamond, electron spin resonance in, (3) 81*f.*
diamond, infrared absorption in, (3) 84*e.*
dielectric, deposition by rf sputtering, (7) 198*b.*
dielectric, structure and properties, (1) 13*j.*
electrically insulating, for lightning arrester, P (1) 14*f.*
electrical stress-grading, P (1) 11*c.*
electroconductive, application and article, P (10) 268*d.*
electroconductive, method to form a patterned, P (6) 159*i.*
electrostatic. See *Electrostatic processes.*
epitaxial, P (9) 244*a.*
evaporated, electrical conductivity in silicon oxide, (7) 199*a.*
ferrite, chemically deposited at mm wavelengths, (7) 191*c.*
films, preparation for transmission electron microscopy, (5) 136*e.*
flame-sprayed, (2) 30*e;* (4) 91*d.*
to inside of tubes, P (7) 179*b.*
on strain gage, (3) 30*b.*
technique for, (6) 145*b.*
types, (2) 30*f.*
glass, application to inside of steel pipes, (1) 3*e.*
forming, (9) 233*d.*
on metal tube for electrostatic processing, P (2) 30*g.*
method to determine breaking and elastic characteristics of, (9) 233*i.*

Coatings, glass (*continued*)
method of forming and product produced, P (1) 3*e.*
obtained by evaporation, electron microscopy of, (10) 264*h.*
to protect, insulate, encapsulate, and seal, (2) 30*a.*
on steel, P (11) 295*j.*
on glass, insulating electroconducting, (9) 233*f.*
on glass, transparent electrical conducting, (1) 5*b.*
for glass envelope, P (9) 235*g.*
ground, measurement and control of slip for, (6) 145*j.*
growth, scanning electron diffraction of, (10) 281*c.*
heat resistant electrical insulating, for steel tubes in heating installations, (6) 145*h.*
high emissivity, for furnaces, (9) 232*a.*
high temperature, for metals, (7) 178*i.*
protective, standard tests needed for, (6) 146*f.*
resistant self-healing, and application method, P (11) 296*c.*
ion-sputtered, as multifunctional finishes, (3) 72*j.*
iron, technique for preparing single-crystal on sodium chloride substrates, (4) 104*e.*
iron oxide, for glass, formation conditions of, (10) 266*e.*
for lampshades, batching fluorine glasses as, (10) 264*i.*
PbTe, thermoelectric properties of vacuum evaporated, (1) 14*d.*
$MgAl_2O_4$ and $MgFe_2O_4$, growth of single-crystal and polycrystalline, (6) 167*h.*
magnetic, display of critical switching curves on a TV picture tube, (6) 157*g.*
of magnetic oxides, (6) 158*b.*
metal, to increase life of grinding wheel, (7) 177*e.*
with metal oxides and silica composition, P (11) 296*d.*
oxide, new films from, (1) 4*i.*
metallic, method to form on glass, P (7) 184*c.*
metallized, for ceramics, (6) 171*e.*
metallizing, corundum with molybdenum-manganese, adhesion mechanism of, (6) 157*d.*
metallizing, methods and materials for ceramic or glass bodies, P (2) 42*h.*
mold, and method of pouring ingots, P (1) 11*g.*
Mo, for electron tubes, (11) 304*j.*
organosilicon, application by aerosol method to glass sheet during drawing, (6) 146*i.*
oxidation resistant, for carbonaceous base, P (10) 274*d.*
oxidation-resistant, for V metal, P (10) 263*i.*
oxide, for articles with metal undercoat, P (9) 232*d.*
chemically formed on Al, (8) 207*h.*
grain boundaries in growing, (2) 50*e.*
from iron chloride, (1) 4*b.*
at low temperature, microwave discharge deposition of, (10) 277*f.*
surface film, effect on lifetime of vacancies in quenched specimens, (9) 249*f.*
thermally grown on molybdenum silicides, structure and chemistry of, (1) 25*f.*
paint, high reflectivity surface, P (3) 59*j.*
photoelectric resistant, P (10) 279*i.*
praseodymium fluoride, dielectric properties of, (6) 157*j.*
protective, for heat-resistant article, P (6) 146*f.*
protective, properties of those applied to metals by atomization, (4) 91*j.*
reflection, production by evaporation, P (10) 279*g.*
refractory, properties of Mo and Ti-Mo alloys protected by, (6) 152*a.*
for refractory metal, P (11) 295*f.*
of refractory metal oxides and refractory metals, method and apparatus for vapor deposition, P (1) 14*h.*
rhenium, oxidation of thin evaporated, (7) 192*a.*
for sanitary ware, P (1) 13*f.*
semiconductor, of vanadium oxide on glass, (1) 5*j.*
silicon, oxide, stress anisotropy in, (2) 51*h.*
properties and structure of those sputtered on quartz, (7) 192*c.*
texture and electrical properties of vacuum evaporated, (2) 40*h.*
single-crystal film, growth and properties of yttrium iron garnet, (3) 82*e.*
sprayed, to protect equipment, (9) 232*c.*
structure, study of those applied on glass by aerosol method, (6) 148*a.*
on substrates, angle-of-incidence and stress, (10) 276*h.*
on substrates, method to prepare by electric discharge, P (6) 160*b.*
thickness, measured by X-ray emission-spectroscopy using ^{147}Pm beta ray source, (11) 310*h.*
thin, determination of density, (10) 281*d.*
observation of nucleation and growth by electron microscopy, (10) 281*i.*
passive components, materials and processes for, (10) 277*e.*
thin film, in study of sodium silicate glasses in the infrared, (3) 62*j.*
thin film, vacuum system for residual gas analysis before, during, and after deposition, (9) 246*e.*
thin foil, diffusion creep of, (9) 249*h.*
SnO_2, effect of γ-radiation on properties of, (10) 264*g.*
titania, stress as related to properties of, (6) 146*a.*
titanoceramic, method to produce thin, P (3) 73*j.*
for turbine blades, cause of failure, (10) 263*c.*
types, for flame spraying, (6) 145*g.*

Coatings (*continued*)
vapor, apparatus for, P (5) 128*g*.
zinc sulfide and magnesium fluoride, for cold mirrors on high production basis, (5) 134*i*.
zircon-born ablation, P (4) 91*i*.
ZrO_2, electrical conductivity at intermediate temperatures, (3) 81*c*.
ZrO_2, optical properties and structure of, (2) 51*b*.
Cobalt, additions, effect on hysteresis loop of nickel-zinc ferrites, (11) 316*g*.
alloys, dispersion-strengthened, (11) 301*b*.
chromite, ferrimagnetic spiral configurations in, B (2) 55*c*.
Co^{2+}, fluoride-compensated, effect on anisotropy of $BaFe_{12}O_{19}$, (2) 49*e*.
$CoAl_2O_4$-$MgAl_2O_4$, stability of $MgAl_2O_4$ from measurements of solid solutions of, (3) 86*b*.
$Co_3B_2O_6$, neutron-diffraction of, (9) 252*b*.
$CoGeO_3$, orthopyroxene and clinopyroxene polymorphs of, (1) 23*i*.
cobaltous oxide, short-time high temperature oxidation of, (5) 140*g*.
Co_2SiO_4-Fe_2SiO_4, solid solutions at 1180°C, activity-composition relations in, (7) 197*b*.
as coloring agent, in ancient glass, (6) 144*a*.
distortion of oxide spinels containing, (10) 291*a*.
ferrite with cobalt, activity of oxygen over solid solutions of, (11) 313*f*.
niobate, systems. See *Systems*.
oxide, anomalies in modulus of elasticity in shear of, (10) 283*h*.
oxide, systems. See *Systems*.
spectrophotometric determination of, (5) 131*i*.
systems. See *Systems*.
tantalate, systems. See *Systems*.
titanate, magnetic properties of, (11) 304*i*.
-TiC-WC alloys, effect of production conditions on composition and properties of, (8) 215*d*.
trivalent, in high alkali glasses, (2) 32*f*.
-WC alloys, structural dependence of electrical resistivity of, (10) 290*g*.
in ZnS type crystals, optical transitions in, (9) 252*g*.
Colloids. See also *Silicon, dioxide gels*.
alumina and silica gels, nature of mullite formed from coprecipitate of, (5) 139*b*.
gels, borosilica, P (7) 184*i*.
coprecipitation with silica gels and their transformation at higher temperatures, (5) 134*d*.
crystal growth in, (6) 166*a*.
method to produce, P (8) 217*g*.
preparation for hydrothermal experimentation, (1) 21*g*.
glass filters for, (5) 120*c*.
macromolecular phenomena, (5) 120*d*.
particles, interaction with special reference to the role of macromolecules in van der Waals' interaction, (6) 168*f*.
sols, method to produce stable titania coated silica, P (6) 164*h*.
rare earth actinide metal, P (10) 274*b*.
silicic acid, accelerator for in lost wax process, (6) 153*f*.
xerogels, magnesia in extruded, P (10) 274*g*.
Color. See also *Pigments*.
apparatus to indicate predetermined, P (1) 17*d*.
for brick, low cost method of producing, (1) 7*i*.
bright pastels, containing daylight fluorescent pigments, P (4) 104*c*.
center, symmetry in MgO, (9) 257*b*.
comparator, P (5) 132*c*.
and constitution, of inorganic solids, (3) 80*e*.
control, new specialty, (6) 146*g*.
designation, of fired clays, (3) 75*d*.
differences, precise measurement of small, (1) 12*j*.
discoloration, of green-emitting zinc-cadmium sulfide phosphors in color tubes, (11) 305*b*.
display, cascaded phosphor layers including one of discrete coherent particles for, P (4) 104*c*.
effect of Zr opacifiers on, (1) 12*j*.
formulas, for underglaze and staining, (3) 71*c*.
fundamentals, review, (8) 218*j*.
of glass, produced by Cu_2O, (3) 60*e*.
for glass, rare earths as, (9) 235*b*.
gold content, means to determine, (6) 161*j*.
of minerals, apparatus to sort by, (11) 312*f*.
mixing chart, P (10) 262*a*.
pink, Cr as cause, (7) 190*d*.
red, produced in glass without selenium, (2) 32*f*.
red, silver compounds to produce in glass, (4) 95*c*.
removers, effect on oxidation of iron in glass, (4) 92*j*.
standards, occurrence of thermochromism in, (1) 16*j*.
TV screens, slurry method to apply phosphor to, (8) 208*g*.
vanadium-zircon combinations for, (10) 275*f*.
yellowish orange, produced in glass by CeO_2 and TiO_2, (3) 62*c*.
and workability of frits, effect of fineness of grind on, (6) 145*i*.
zircon, for glazes, (10) 276*g*.
Colorimetry.
to determine Se in ruby glasses, (10) 264*c*.
of screens, for color TV, (8) 219*i*.
Coloring materials. See *Decoration; Pigments*.
Columbium. See *Niobium*.
Combustion. See also *Burners; Firing; Flames; Furnaces; Heat; Kilns*.
chamber, liner for well gas and air burner, P (3) 70*f*.
chamber, pressure regulation by electric or hydraulic transmission, (7) 179*i*.
characteristics, determination for oil-fired tunnel kiln, (2) 46*b*.
Combustion (*continued*)
element, molding from fibers on porous support, P (11) 302*c*.
Comminution. See *Crushing*.
Compaction. See also *Pressing*.
explosive, of materials, (4) 106*i*.
of granular powders, effects of pressure and bonds on, (2) 39*i*.
methods, comparison for mixes of dry-press consistency, (2) 35*i*.
of particulate materials, P (4) 106*j*.
pressures, for powders, (2) 9*h*.
vibratory, of angular shapes, (5) 125*f*.
Composites, graphite-based, B (5) 142*i*.
Compressibility, of cubic carbides, effect of high pressure on, (11) 316*c*.
Compression, of agglomerated carbon, at high temperature, (11) 314*d*.
measurement, in MgO by reflectivity, (9) 215*i*.
process, of spherical glass powders, (8) 208*h*.
Computers, analog, to calculate composition of raw cement mixes, (8) 206*e*.
analog, for solving steady-state heat flow problems, (4) 99*a*.
data processing system, in calculation of glaze formulas, (1) 12*h*.
to determine rock properties, (4) 107*j*.
memories, low-induction ferrites for, (3) 72*g*.
for operation of glass container plant, (8) 210*i*.
program, for electron probe microanalysis, (1) 16*g*.
programs, of distribution moments, (4) 108*j*.
Concentration, pre-, of trace elements by precipitation ion exchange using organic-hydrochloric acid systems, (2) 45*a*.
Concretes. See also *Cement; Masonry; Mortars*.
block, kiln for making, P (8) 207*e*.
block, production increased, (9) 230*j*.
cemeat in, kinetics at elevated temperatures, (9) 231*d*.
and cement paste and mortar, effect of aggregate and voids on elasticity of, (2) 28*i*.
corrosion, and its prevention, (7) 178*a*.
dolomitic limestone, effect of additives on quality of, (6) 144*d*.
high strength, from hydraulic cement, aggregate, an aldehyde, and a phenol, P (2) 29*h*.
holding time, selection prior to hydrothermal treatment, (2) 29*f*.
hydraulic, analysis techniques, (11) 293*h*.
lightweight, P (11) 295*a*.
materials and techniques, (11) 293*j*.
nondolomitic limestone in, reaction involving, (9) 231*a*.
polymer, mechanism of cavitation erosion of, (4) 90*j*.
products, kiln to cure, P (5) 119*c*.
refractories, metal anchors for, (8) 215*i*.
refractoriness, (2) 29*e*; (9) 231*a*.
refractory, B (6) 174*c*.
flue gas ducts, (8) 216*f*.
properties of pneumatically placed, (2) 36*f*.
wetting by molten glass, (9) 235*i*.
resistance, to frost and salt, (1) 2*j*.
shrinkage, effect of aggregate properties on, (2) 28*g*.
silicate, effect of carbonaceous and feldspar impurities on, (9) 230*h*.
slab, measurement of thickness by gamma ray, (9) 231*e*.
slag, relation between impermeability and pore structure, (8) 207*g*.
strength, aspects of mechanical, (6) 144*f*.
means to calculate, (9) 230*g*.
under biaxial compression, (2) 29*i*.
stresses in, determination of, (4) 108*j*.
structural lightweight, improved procedure for proportioning mixes of, (3) 58*j*.
structural testing, improved instruments for, (3) 59*c*.
Condensers. See *Capacitors*.
Conductivity, electrical, and(or) **Conduction, electrical,** of alumina, effect of metal oxide additives on, (5) 128*c*.
of alumina, at temperatures in a reactor environment, (2) 49*i*.
of $BaTiO_3$, (7) 203*g*.
and breakdown, B (9) 259*f*.
of cadmium oxide, in high-frequency electromagnetic field, (3) 80*f*.
of CdSe crystals, effect of Se atmosphere partial pressure on, (3) 81*h*.
of CdS, single crystal, (4) 103*j*.
of $Ca(NO_3)_2$-KNO_3 glass, (2) 31*j*.
of Ca and Sr oxides, (5) 135*d*.
of $Ca(OH)_2$ and amorphous SiO_2 aqueous solutions, (6) 167*h*.
in cesium silicate glasses, (5) 120*c*.
change, in high resistance semiconductors in powerful field of superhigh frequency, (11) 314*f*.
dc, of alumina single crystals, (5) 134*f*.
in fused silica, bombardment induced, (4) 110*j*.
of Ge and Si, effect of surface finish in high electric fields, (3) 72*d*.
of granular materials, effect of low moisture content on, (9) 250*g*.
of hematite, containing Ti or Ca, (5) 135*e*.
of industrial glasses, in molten state, (9) 233*i*.
in lithium tungsten bronzes, (7) 203*c*.
in MgO-Cr_2O_3, (3) 81*b*.
in MgO, induced by electron bombardment, (7) 199*b*.
of a melt, simultaneous recording of the thermogram and polytherm by a Kurnakov pyrometer, (4) 107*f*.
of melts, in system Sb-Sb_2Se_3 in solid and liquid states, (1) 21*a*.
in nickel ferrous ferrites, (4) 103*i*.
of Nb_2O_5, α-, in range of 900° to 1400°C, (4) 111
Conductivity (*continued*)
of *n*-type Ge and Si in crossed electrical fields, (11) 316*i*.
phenomena, in rutile crystals, (4) 110*b*.
of reduced $BaTiO_3$ single crystal, (10) 289*b*.
of rutile, near-stoichiometric at 600° to 1400°C, (1) 20*j*.
of rutile, variation with time, (3) 87*a*.
of SiO_2-B_2O_3 glasses, containing Li or Na, (5) 120*d*.
in silicon oxide films, (7) 199*a*.
through SiO films, (9) 242*h*.
in single crystals of rhenium trioxide, relation to conductivities of Sr_3MgReO_6 and Na_xWO_3, (9) 254*f*.
of transition metal oxides, variations as function of equilibrium O pressure at high temperature, (9) 242*g*.
of ZrO_2 films, at intermediate temperatures, (3) 81*c*.
Conductivity, electronic and(or) **ionic,** of calcia-stabilized zirconia, (5) 128*c*.
steady-state excess, during plastic deformation of alkali halides, (7) 202*e*.
Conductivity, thermal. See also *Heat*.
apparatus for comparative determination, P (9) 246*c*,
apparatus to determine, P (10) 281*e*.
apparatus to measure, P (6) 163*a*.
of basic O furnace refractories, (8) 216*d*.
of building and insulating materials, automatic apparatus to determine, (1) 7*e*.
of crucibles, as variable in crystal growing, (5) 139*e*.
experimental and theoretical, of MgO, Al_2O_3, and ZrO_2 powders, (6) 170*e*.
of ferrimagnetic insulators, low temperature, (9) 242*j*.
in ferroelectric ceramics, (10) 277*a*.
of glass, measurement in −150° to 50°C range, (8) 210*c*.
of granular beds, (1) 8*f*.
of granular materials, effect of low moisture content on, (9) 250*g*.
high-temperature, of transition metal carbides and nitrides, (4) 111*i*.
instrument to measure, (9) 245*d*.
of lead and bismuth glasses, (2) 32*d*.
measurements, for stopper heads, (8) 216*i*.
of pyrolytic graphite, (7) 203*c*.
of refractories, effect of moisture on, (11) 301*e*.
of refractories, powdered and sintered, (2) 37*h*.
of refractory materials, apparatus to determine, (6) 161*i*.
of refractory materials, measurements, (9) 239*b*.
of Si, SiC, and diamond, (6) 170*h*.
of SiC stopper head, as related to corrosion of stopper rod, (3) 68*j*.
of some electrically conducting compounds, B (11) 320*g*.
Conductors, electrical. See also *Semiconductors*.
device, P (7) 192*f*.
elements, and their manufacture, P (7) 192*i*.
of fiber glass, method to make, P (11) 299*e*.
gas-impervious, between two zones of differing pressures, P (2) 41*c*.
material, for electrical connection, P (7) 192*f*.
photo-, P (10) 279*e*.
based on chalcogenides, P (10) 279*f*.
method to make, P (9) 243*a*.
and preparation of gallium sulfide flakes for, P (10) 279*j*.
super-, P (6) 161*a*.
super-, process for making niobium stannide, P (2) 42*d*.
Cones. See *Pyrometric cones*.
Conferences, on ceramic firing, forum of British Pottery Managers' Association, (1) 17*f*.
on clay, international, B (2) 55*i*.
on glass, VIIth International, (6) 146*j*.
on high-strength materials, international, B (2) 55*d*.
on metallography, B (6) 173*f-b*.
proceedings, of pouring pit refractory subcommitte, (4) 99*g*.
on silicate industry, in Budapest, B (2) 56*b*.
on steelmaking, B (3) 88*j*.
Contacts, Al-Ge, P (3) 72*d*.
cadmium telluride, electrical properties with metals and *pn* junctions, (3) 81*d*.
CdTe film, photoelectric properties with metals, (2) 72*i*.
electrical, for continuous measurement of dust concentration, (2) 44*a*.
impurity-type semiconductor, P (11) 306*e*.
silver-refractory metal, P (3) 74*h*.
semiconductor, P (4) 106*f*; P (11) 307*e*.
on semiconductors, P (10) 278*i*.
to thermoelectric elements, method to connect, P (6) 150*f*.
Containers. See *Glass*.
Controls. See also *Temperature*.
air, methods to keep dry, (1) 15*j*.
for annealing, of sheet glass, (4) 92*a*.
automatic, of firing cycle in tunnel kilns, (2) 46*b*.
automatic, method and system for grid coolers or traveling grids, P (1) 3*a*.
of color, new specialty, (6) 146*g*.
device, for program of thermobalance, (9) 245*g*.
devices, history and applications of solid-state, (7) 192*g*.
of dry-pressing, (10) 276*i*.
of glass composition, by density measurements, (8) 209*a*.
of glass level in tank, probe for, (7) 180*c*.
of kilns, above 3000°F, (7) 195*f*.
method, improvement for homogeneity of glass batch, (4) 93*e*.
by optical properties, of chemical composition of glass, (10) 264*d*.

Controls (*continued*)
of particle size, of nonplastic materials, (2) 44*g*.
procedures, for glass melting tanks, (7) 180*i*.
programming apparatus, P (4) 108*f*.
of property variability, (2) 44*a*.
technical, of bone china, (10) 276*d*.
of temperature, static characteristics in combustion chamber of glass melting tank furnace, (8) 211*c*.

Conveyors. See also *Materials handling*.
auger type, P (5) 130*h*.
discharge system, P (8) 222*g*.
for dry pulverulent solid in liquid-like state, (10) 280*d*.
for fine material, P (5) 130*f*.
for glassworking, P (2) 33*b*.
international fair in Switzerland, (9) 244*f*.
-line system, for producing and processing glassware, (4) 92*b*.
mechanized, for making sanitary ware, (6) 156*h*.
modern, for internal transport, (10) 280*b*.
orienting, for glass articles, P (2) 33*b*.
pneumatic, with mixing chamber, P (9) 244*j*.
special problems of density, (3) 74*j*.
system for bulky materials, P (1) 16*b*.
for tile, P (9) 242*d*.
to transport and cut plate glass, (10) 264*e*.
vibratory, with inversion diverter, P (1) 16*d*.
for materials, (2) 43*f*.
particularly bin-discharge, P (1) 16*e*.
for powders, P (4) 106*i*.

Coolers, stationary, for calcined lime and other materials, P (11) 295*c*.

Cooling, apparatus, for calcined materials, P (11) 311*i*.
basins, calculating for glass tanks, (4) 92*c*.
element, design for "cascading by shaping" thermomagnetic, P (3) 72*i*.
evaporative, of glass tank walls, (4) 93*f*.
of glass, structural shear formation during, (1) 5*c*.
thermoelectric, of infrared detectors, (2) 40*j*.
under-, effect on crystal growth rate in slags, (6) 167*f*.
under-, and growth of eutectics, (3) 80*g*.

Copper, acetate, magnetic properties at low temperatures, (3) 83*d*.
aventurine glass, with large crystal precipitates on surface, (2) 32*h*.
chloride, interaction of pentachlorides of Nb and Ta with, (10) 287*c*.
chloride, systems. See *Systems*.
(I) chloride, interaction with chlorides of Ga, Na, and Ag, (11) 317*g*.
concentration, structural dependence of CdTe films on, (3) 83*a*.
$CuFeO_2$, replacement of iron in, (6) 169*g*.
determination, with *m*-(mercaptoacetamido)phenol as gravimetric reagent, (3) 75*e*.
ferrite, reaction kinetics of formation and sulfating of, (9) 254*a*.
ferrite-chromite series, crystal distortion in, (4) 110*c*.
films, structure and annealing on glass, (11) 305*d*.
impurities, CdTe films with, (6) 158*c*.
inner complex compounds, stereochemistry of those with anomalous magnetic properties, (4) 113*d*.
iodide, systems. See *Systems*.
metallic, equilibria of molten $Na_2O \cdot 2SiO_2$ glass in contact with, (11) 297*d*.
oxide, crystal, electron distribution in, (4) 111*d*.
crystals, X-ray of binding properties, (10) 292*a*.
color of glass produced by, (3) 60*e*.
systems. See *Systems*.
polyamine-clay complexes, B (2) 56*j*.
ruby glass, (7) 179*j*.
sulfate, systems. See *Systems*.
systems. See *Systems*.
vanadium oxide bronzes, properties of, (1) 25*c*.

Cordierite, body, methods to develop dense, (10) 272*b*.
fusion-cast, crystallization and properties of, (10) 271*e*.
kiln furniture, from fireclays and magnesite, (6) 152*a*.

Cores, magnetic, for electrical devices, P (11) 306*j*.
thin-walled, for machining operations, P (10) 273*g*.

Corrosion, acid, of Pyrex-type glass, (8) 209*g*.
of Al_2O_3-ZrO_2 refractories, in soda-lime glass, (7) 186*c*.
anti-, properties of unburned ladle brick, (3) 68*h*.
atmospheric, of U-C alloys, B (6) 172*h*.
average, results of tests on brick for lining ladle wall and bottom, (3) 68*j*.
of cermet, protection methods, (1) 8*a*.
of concrete, and its prevention, (7) 178*a*.
of cupola refractory, (10) 272*f*.
of glass, mechanism of, (2) 32*a*.
inhibition, with phosphate glasses, P (11) 296*a*.
of ladle brick, brick quality improved by lining method change, (3) 69*c*.
of ladle brick, comparison under various conditions, (3) 65*h*.
of pot clays, effect of glass composition on, (8) 209*e*.
of refractories, and nonmetallic inclusions in steel, (10) 271*e*.
of refractories, by opal glass, (2) 36*e*.
resistance, of alumina-zirconia-silica refractories, (6) 152*b*.
resistance, of chromium carbide alloys in corrosive environments, (11) 300*j*.
of slag, effects of atmosphere on, (8) 215*e*.
of stopper rod, related to thermal conductivity of SiC stopper head, (3) 68*j*.
stress, of E glass fibers, (5) 121*g*.
of tank blocks, study of upward drilling as cause, (9) 234*d*.

Corundum. See also *Aluminum, oxide; Refractories*.
ceramics, interrelation between electrical and mechanical strengths of, (1) 23*a*.
ceramics, mechanism of deformation during heating of unfired, (10) 288*e*.
-containing fireclay, causes of expansion and contraction in, (7) 185*h*.
crystallization, kinetics of, (5) 137*j*.
crystals, growth during sintering, (6) 167*g*.
crystals, habit modification of those grown from molten PbF_2-Bi_2O_3, (6) 167*h*.
deformation twinning in, (9) 249*d*.
electro-, strength change of brown by heat treatment, (5) 117*f*.
enthalpy of, in range 678° to 1330°K, (11) 316*c*.
etching, with Si, (9) 250*a*.
metallized with molybdenum-manganese, adhesion of, (6) 157*d*.
single crystals, method to grow hydrothermally, (9) 244*g*.
stability, phase boundaries at pressures above 50 atm., (7) 200*i*.

Cost, determination, of individual glass containers, (4) 92*d*
indirect, of glass bottles, (5) 120*h*.
reduction, through kiln car engineering, (6) 163*g*.
of wages, in production of heavy clay products in Common Market, (1) 7*h*.

Cracking, of glass, caused by underwater spark, (6) 147*i*.
micro-, in lead titanate, effect of grain size on, (5) 135*b*.

Cracks, equilibrium, stress distribution at edge of, (1) 25*f*.
in porcelain, ultrasonic testing for, (2) 40*e*.
propagation, method to measure grain boundary energies in brittle materials, (7) 198*a*.
reinitiation in F-colored NaCl, evidence of dislocation feeding mechanism for, (6) 167*b*.
surface, on glass fibers, (8) 211*i*.
tip stresses, relaxation in α-quartz, (3) 84*i*.

Creep, of alumina, effect of compressive stress on, (2) 39*c*.
compressive, of BeO-UO_2 mixtures, (1) 19*h*.
of dense, pure, fine-grained aluminum oxide, (4) 110*c*.
diffusion, of thin foil, (9) 249*h*.
of glass, under high strain, (2) 31*b*.
of hardened cement mortar and concrete, effect of wind on, (3) 58*f*.
in immersed specimens, gage to measure, (6) 162*a*.
of magnesia brick, caused by compressive load at high temperature, tests on, (9) 239*a*.
measurements, on high-alumina refractories, (7) 186*e*.
model, (1) 19*d*.
of polycrystalline thorium dioxide, (9) 249*a*.
of refractories, (8) 215*a*.
of refractories, relation to sintering, (8) 216*g*.
in rock salt, (1) 19*d*.
in tension and compression, method to predict from bending tests, (5) 138*c*.

Cristobalite. See also *Silicon, oxide*.
and calcium carbonate, early stages of reaction between, (2) 49*c*.
-containing ceramics, X-ray diffraction and thermal expansion of, (10) 291*g*.
determined by X-ray diffraction, problems in, (6) 162*h*.
features of polymorphous transformation of, (9) 256*c*.
internal stress in ceramics containing, (10) 287*e*.
low, structure of, (8) 227*i*.
polymorphous transformation, effect of dislocations on temperature characteristics of, (9) 249*b*.
-tridymite, relations and solid solutions, discussion, (6) 166*j*.

Crocite, $PbCrO_4$, crystal structure of, (6) 166*e*.
single crystals, growth of, (3) 82*d*.

Cronstedtite, etch pits and dislocations in, (3) 81*g*.
stacking faults in, (7) 202*e*.
thermal transformation of, formation of spinel and hexagonal ferrite by, (7) 199*h*.

Crucibles. See also *Refractories*.
coating, of reaction product of Al and boron nitride, P (7) 188*j*.
metal melting, rotational method of making, P (3) 70*j*.
thermal conductivity, as variable in crystal growing, (5) 139*e*.

Crushing. See also *Crushing apparatus; Mills*.
of materials, in theory and practice, (7) 186*g*.
principles of, B (4) 115*d*.

Crushing apparatus. See also *Mills*.
centrifugal unit and method, P (1) 18*c*.
clearing system, P (11) 312*e*.
cone, P (4) 109*d*.
gyratory, bowl liner for, P (5) 133*c*.
gyratory, seal for, P (11) 312*j*.
in heavy clay industry, (8) 214*e*.
jaw, construction, P (6) 164*f*.
crushing roller, P (4) 109*h*.
means for compensating inertia forces in, P (2) 47*g*.
with reciprocating movement, P (1) 18*d*.
for ores, and method with energy in liquid medium, P (1) 18*i*.
pulverizer, and classifier, P (3) 79*b*.
pulverizer, with ultrasonic drive, P (3) 79*b*.
roll, dual-pivoting cradle type, P (1) 18*d*.
with variable opening screen grate, P (4) 109*e*.
yielding bowl locking ring for, P (11) 313*a*.

Cryolite, phase transitions and structure of high-temperature phases of, (3) 84*h*.
product, and fine crystals, process of agglomerating, P (2) 48*b*.

Crystalline materials, poly-, chemical strengthening of, (7) 197*i*.

Crystallization, behavior, effect of La_2O_3 and ThO_2 in optical glass, (2) 31*g*.
behavior, of fusion-cast cordierite, (10) 271*e*.
catalytic, of vitreous phase of magmatic rocks, glasses, and metallurgical slags, (11) 296*e*.
controlled, of alkaline-earth silicoaluminate glasses, (11) 296*i*.
of glass, B (1) 26*e*.
behavior of alkali aluminogermanates, (4) 95*h*.
catalyzed controlled in lithium aluminosilicate system, B (3) 88*g*.
DTA to study, (9) 234*j*.
effect on structure of foam glass, (4) 93*a*.
interrelations with microheterogeneity and nucleation, (5) 120*j*.
origin and development of, (6) 148*a*.
reasons for deformation during, (10) 266*b*.
relation to microheterogeneity and nucleation, (5) 120*j*.
role of catalyst in, (1) 5*i*.
vitreous phase, (11) 296*e*.
kinetics, of stoichiometric SiO_2 glass in H_2O atmospheres, (4) 112*b*.
of lithium silicate melts, under different cooling conditions, (9) 249*b*.
in mafic magmas, solubility of water and effects of O fugacity and water content on, (7) 202*b*.
nuclei, production at surface of aqueous solution by spark discharge, B (11) 319*i*.
primary, of glasses in system Na_2O-TiO_2-SiO_2 and its relation to immiscibility, (9) 234*a*.
and re-, of quartz in piston-cylinder device, (1) 19*i*.
of reduced silica glass, in an oxidizing atmosphere, (2) 31*c*.
of slags, Thomas pig-iron, (8) 206*g*.
of Na_2O-$2SiO_2$-SiO_2 glasses, (11) 296*g*.
studies, of lithium silicate glasses, (7) 181*d*.
textures and fabrics, terminology for sedimentary rocks, (2) 47*h*.
upper limit, for sodium-calcium-magnesium-aluminosilicate glasses containing 15% Na_2O, (1) 5*f*.
of zincite, under hydrothermal conditions, B (11) 320*c*.

Crystallography, crystallographic pointed groups and systems, scheme of subordination of, (9) 255*f*.
data, of anhydrous lithium chromate, (7) 198*f*.
data, Li_2ZnF_4, (7) 198*g*.
of deformation twinning, theory of, (3) 86*g*.
device, for high temperature in controlled atmosphere, (8) 223*d*.
of Li orthoniobates and orthotantalates, (9) 249*c*.

Crystals. See also specific kinds.
of arbitrary shape, corrections for X-ray absorption by, (7) 198*a*.
atomic lattices, point defects in, (5) 137*c*.
AX and AX_2 compounds, systematic derivation of close-packed structures, sequence of equal layers, (7) 203*a*.
compounds, process and apparatus to produce single, P (6) 160*b*.
crystallographic point groups, reduction to subgroups by homogeneous stress, (1) 24*f*.
defect structure, effect on reactivity of solids, (11) 315*j*.
defect structure, of semiconducting oxides, (11) 315*f*.
deformation twinning, in corundum, (9) 249*d*.
device to cleave, (10) 280*h*.
dislocations. See *Dislocations*.
elastically deformed, Pendelloesung fringes in, (1) 23*f*.
excitations in, types of waves, (10) 286*b*.
faces, principles of structural-geometrical analysis of, (9) 253*j*.
field-ion micrographs of, interpretation of streak contrast, (3) 82*j*.
flux-grown, elimination of inclusions from, (9) 247*d*.
formation. See *Crystallization*.
growing, apparatus, P (10) 278*a*.
magnetic fields in arc system for, P (5) 131*b*.
new manipulable variable in, (5) 139*e*.
plural directional, P (6) 160*j*.
techniques, recent advances, (2) 43*g*.
growth, B (11) 319*j*.
container, P (11) 306*b*.
defects in flux-grown rubies, (10) 286*c*.
hole formation in by surface adsorption of impurity, (3) 82*j*.
from melt, B (8) 228*i*.
in metals, statistical mechanics, B (7) 204*d*.
method and apparatus for, P (3) 75*b*.
of mixed oxides, (5) 139*f*.
and solution, interrelation of, (9) 254*a*.
and transition rate, of $CaSO_4 \cdot 2H_2O$ in mixed acid H_3PO_4 and H_2SO_4, (11) 315*a*.
of zinc oxide by chemical reaction of zinc fluoride with air, (10) 284*b*.
hydrates, interactions of materials with solid, (1) 22*h*.
ionic, defects in, B (9) 259*e*.
method to calculate thermal expansion of, (2) 51*c*.
type, effects of point defects in, (6) 170*b*.
irregularities, periodograms to study, B (2) 56*a*.
lattice, correlation of atomic steps by relaxation mode analysis, (1) 19*j*.
cubic, calculations of Madelung constants of, (6) 167*i*.
light absorption to determine structure, (3) 80*e*.
parameters, two methods to determine hexagonal from Debye-Scherer patterns, (1) 21*i*.
lattice constant, of CrO_2, anomalous temperature dependence of, (10) 283*i*.

Crystals (*continued*)
micro-, electrooptic effect in glass matrix, (10) 285*j*.
microscopic, determination of lattice and application to different forms of calcium trisilicate, (7) 198*i*.
mixed, single-phase, P (5) 129*j*.
molds, in dolomite, origin and interpretation, (11) 314*f*.
mono-. See *Crystals, single.*
monoclinic, determination of elastic constants from diffuse X-ray reflections, (7) 198*i*.
nuclei, formation on substrates, (3) 80*i*.
origin, in glass ceramics, (10) 265*a*.
piezoelectricity in, B (8) 228*j*.
powders, determination of lattice distortion in brittle, (5) 131*f*.
puller, P (5) 128*a*.
pulling, orbital-spin, P (4) 106*a*.
pulling apparatus, P (10) 278*b*.
radiation damage effects in, (8) 227*e*.
silicon carbide, defect structure and polytypism in, (11) 315*g*.
single-, deformation, resolution of stresses in, (8) 227*j*.
from incongruently melting material, P (11) 307*j*.
method for taking back reflection oscillation photographs of, (6) 162*f*.
mounting device for Philips diffractometer, (3) 76*c*.
preliminary orienting procedure with Weissenberg camera, (9) 253*e*.
theoretical study and optical determination of elastic constants of, (7) 203*b*.
X-ray diffraction at high pressures, (3) 85*f*.
sizes, measurement in turbostratic carbons, (4) 112*a*.
with spinel structure, phase transitions in, (5) 139*f*.
splitting, under homogeneous stress, (3) 85*i*.
structure, B (11) 319*f*.
apparatus and method to produce single, P (6) 158*d*.
minimization of variance of parameters derived from X-ray powder diffractometer line profiles, (10) 288*g*.
of reedmergnerite, its relation to feldspar crystal chemistry, (11) 314*g*.
in solid state reactions of clays and related minerals, B (2) 56*d*.
of technetium disilicide, (10) 284*b*.
surfaces, study of mass transport mechanisms at, (2) 53*c*.
symmetries and space groups, X-ray intensity statistics to determine, (11) 313*e*.
thermal vibrations, scattering of high energy electrons by, (3) 85*d*.
twinning, structural interpretation in anatase, (6) 170*e*.
Currents, space-charge-limited, B (9) 259*f*.
Cutting, device, to slice crystalline material, P (11) 305*f*.
sonic, limits and possibilities of, (7) 195*c*.
Cutting tools. See *Tools.*

Dalyite, crystal structure of, (7) 198*b*.
Data storage, memory cells, with inductive sensing tunnel diode, P (3) 74*b*.
memory cores, ferrite, P (5) 128*e*.
memory element, ferroelectric, P (10) 278*h*.
memory element, magnetic, P (10) 278*b*.
thin film storage electrode, P (1) 15*f*.
Decals. See *Decoration.*
Decomposition, of glass, in soil, (6) 144*c*.
thermal, of Ba and Sr trisoxalatoferrates(III), (7) 203*d*.
of calcium hydroxide crystals, (11) 294*b*.
of gypsum, (4) 90*i*.
of hydroxides of samarium and cerium, (10) 291*b*.
of kaolinite from standpoint of solid phase reactions, (8) 227*i*.
kinetics of boehmite, (9) 257*h*.
of magnesium nitrate, (2) 53*d*.
of magnesium silicates, (3) 86*j*.
of potassium chloroplatinate, (8) 228*a*.
variation of surface area of solids during, (2) 53*f*.
Decoration. See also *Art and artware; Color; Engobes; Glazes.*
animal ornamentation, and contour reliefs, (1) 1*j*.
of Attic pottery, attempts to reproduce, B (9) 259*e*.
of ceramics, oxides and minerals in, (10) 216*j*.
decalcomania, P (9) 242*c*.
of glass, P (10) 267*c*.
process to attach to glaze, P (9) 242*a*.
vitrifiable, P (11) 304*e*.
decorative arts, of Sweden, B (7) 204*c*.
of glass, back painting, (9) 229*j*.
bottles, P (10) 268*h*.
ceramics, method and composition, P (10) 268*g*.
of glassware, cliche method, (4) 92*g*.
of heated glass, electrostatic screen printing, P (6) 150*j*.
of hot glass, electrostatic, P (5) 122*e*.
hot-screen, of enameled products, (11) 295*h*.
painting, with oxides, (3) 57*i*.
for procelain, lusters as, (2) 39*f*.
of pottery, glazes for, (1) 1*j*.
of pottery, precious metals for, (8) 219*d*.
printing, electrostatic screen, (2) 43*e*.
process, for whiteware, P (2) 40*d*.
screen printing, on enamels, (5) 119*j*.
screen process, B (3) 88*g*.
underglaze, brush exercises for, (8) 205*j*.

Decoration (*continued*)
underglaze, colors for, (3) 71*c*.
variety, by custom glass manufacturer, (8) 209*a*.
Defects. See also *Crystals; Enameling; Enamels; Glass; Structure.*
spots and discolorations, detector for, (9) 245*b*.
ultrasonic defectoscope to detect, (10) 281*d*.
Deflocculants. See *Electrolytes.*
new, for earthenware bodies and their effects on casting behavior and properties of bodies, (6) 156*j*.
Deflocculation. See *Dispersion.*
Deformation, behavior, of polycrystalline SiC, (6) 166*a*.
bending tests, method to predict creep in tension and compression from, (5) 138*c*.
during heating, mechanism for unfired corudnum ceramics, (10) 288*e*.
dynamic, of single and polycrystalline Al, (10) 285*d*.
elastic and residual, effect on forming processes, (2) 43*d*.
equipment, high-temperature compressive, (6) 162*d*.
of fireclay refractory, analysis of, (7) 185*e*.
of glass, during crystallization, (10) 266*b*.
of ice, void formation by, (9) 258*a*.
of magnesite-chrome refractories, under changing torsional load, (7) 185*g*.
of MgO, at elevated temperatures, (1) 20*c*.
plastic, of diamond plates, (3) 84*g*.
of diamond at temperatures below 1800°C, (8) 226*i*.
of materials, B (7) 204*e*.
patterns on cleavage surfaces of lithium fluoride, (9) 253*c*.
pyroplastic, prediction by mechanical analogy, (7) 187*g*.
of rock salt crystals, submicroscopic morphology of mechanical, (3) 86*j*.
single-crystal, resolution of stresses in, (8) 227*j*.
of sintered WC-Co hard alloys, (8) 215*a*.
surface, of large astronomical mirrors, (2) 32*c*.
of thoria, (1) 20*b*.
of Y_2O_3, thermomechanical, (4) 114*e*.
Dehumidifiers. See *Dryers.*
Dehydration, of clay minerals, change of infrared spectra by, (5) 134*h*.
of diaspore, at water pressures of 15 to 15,000 psi, (11) 315*h*.
of glasses, kinetics investigated by thermography, (1) 4*a*.
mechanism, of kaolinite and kaolinite addition compounds, B (2) 56*d*.
of montmorillonite and saponite, infrared spectroscopy of, (1) 22*b*.
products, of calcium sulfate dihydrate, oriented growth of, (7) 178*d*.
products, of gypsum, (9) 257*h*.
of pyrophyllite, (6) 166*a*.
and rehydration, change in infrared absorption spectra of clay minerals by, (5) 134*f*.
Dehydroxylation. See *Decomposition, thermal.*
Delafossite, composition in doubt, (7) 199*i*.
Delay line, method to make microwave, P (10) 278*h*.
Dendrites, pulling and reeling mechanism, P (1) 14*j*.
semiconductor, method to produce with both planes uniform, P (6) 160*d*.
Densification, during sintering in presence of liquid phase, capillary phenomena in, (9) 255*a*.
final stage, in vacuum hot-pressing of alumina, (1) 21*c*.
of glass, at high pressure, (2) 31*e*.
and grain growth, of hot-pressed lead zirconate-lead titanate ceramics containing bismuth, (4) 103*i*.
of NbC compacts, effect of particle dispersion, (1) 8*d*.
Density, apparent, device to determine for small samples of porous materials, (2) 45*j*.
of aqueous alkali silicate solutions, relation to composition, (10) 266*d*.
of arsenic-sulfur glasses, relation of composition and, (7) 181*e*.
of boron trioxide, (1) 6*b*.
bulk, method to measure for soil and porous stones, (6) 162*g*.
bulk and variations, determination in glass tank blocks, (6) 152*d*.
and defect chemistry, relation in crystalline solids, (9) 254*f*.
of dehydrated phosphoric acids, (7) 197*i*.
determination, with air comparison pycnometer, (3) 75*f*.
of iron oxide-silica melts, (1) 20*d*.
of liquid, apparatus to measure, (10) 280*j*.
of materials, related to pneumatic conveying, (3) 74*j*.
measurements, on borate glasses, (5) 120*g*.
to control glass composition, (8) 209*a*.
of lead selenide, (11) 315*j*.
principles of, (5) 131*e*.
packing, of powders, theorems to calculate maximum weight ratios, (7) 203*b*.
of Na_2O-ZrO_2-SiO_2 glass, as function of composition, (1) 4*e*.
of solids, direct determination of, P (7) 195*b*.
of thin films, means to determine, (10) 281*d*.
Dental ceramics, crowns, method to build, P (4) 103*c*.
for fillings, P (8) 219*f*.
impression materials, P (10) 263*a*.
material for impressions, P (5) 127*f*.
restorations, methods of making, P (7) 191*a*.
review, (3) 71*e*.
silicate cements for, (2) 29*g*.
siliceous filling, P (7) 191*a*.

Deposition, chamber, with heater element enveloped by quartz workholder, P (3) 72*j*.
device, gettering means in a vacuum, P (5) 128*f*.
electrophoretic, of enamels, (5) 119*i*.
Design. See also *Art and artware; Decoration.*
considerations, for manned deep-sea vehicles, (2) 54*i*.
designer, in industry, (4) 89*j*.
exhibition of the Federation of Swiss Ceramists, third, (3) 57*i*.
for fracture toughness, (4) 114*i*.
of glass melting furnaces, (6) 147*d*; (8) 209*c*.
of high temperature fans, for kilns, (8) 224*c*.
of hollow glassware, illustrates different periods, (4) 90*d*.
modern European, German contribution to, (10) 261*h*.
molecular, of materials and devices, session at Cambridge, Mass., B (9) 258*h*–259*g*.
new, for British china, (6) 144*c*.
relations, in nineteenth centrury American glass, (3) 57*j*.
tool, hollow spheres as, (4) 108*j*.
trends, International Ceramic Competition, Faenza, 1965, (2) 27*j*.
variety, by custom glass manufacturer, (8) 209*a*.
Detectors. See also *Tubes, electron.*
automatic, for metals in raw materials, (7) 194*f*.
for defects, spots, and discolorations, (9) 245*b*.
leak, to calibrate ion gage, (10) 281*c*.
for level, of liquids, slurries, or solids, (5) 131*j*.
radiation, black coating for infrared, P (10) 277*i*.
semiconductor, radiation, P (11) 307*g*.
solar, GaAs with manganese as doping agent, P (11) 306*f*.
for thermal radiant energy, P (9) 244*b*.
ultraviolet, P (2) 43*c*.
Deuterium, exchange, with silica surfaces, γ-radiation-induced, (9) 250*e*.
Devitrification, of vacuum-melted glasses, of lithium metasilicate-silica, (1) 3*j*.
Diamonds, in abrasive wheels. See *Grinding apparatus.*
articles, process to make metal bonded abrasive, P (7) 177*i*.
coat, electron spin resonance in, (3) 81*f*.
infrared absorption in, (3) 84*e*.
nature of, (10) 288*f*.
crystals, wetting by metals and alloys, (1) 1*g*.
dielectric constant, variation with pressure, (7) 203*f*.
explosive method to produce, P (5) 117*h*.
as lap, to finish carbide dies, (6) 143*f*.
natural, X-ray topographic study of planar growth defects in, (2) 54*d*.
origin, in drift of North Central United States, (1) 23*h*.
particles, in metal matrix, P (6) 143*h*.
particles, synthesizing by electric discharge, P (1) 1*h*.
plastic deformation, at temperatures below 1800°C, (8) 226*i*.
plates, plastic bending of, (3) 84*g*.
research, microscope in, (9) 229*f*.
structure, revealed by etching, (1) 25*g*.
synthetic, made by electric discharge shock, (4) 110*f*.
thermal conductivity of, (6) 170*h*.
wheels, test procedure for dry grinding tungsten carbide with bonded, (8) 205*f*.
wheels, trends in, (9) 229*f*.
X-ray Bragg and spike reflections, and ultraviolet absorption topography of, (7) 203*g*.
X-ray diffraction spikes of, diffraction topography of, (4) 110*h*.
Diaspore, dehydration, at water pressures of 15 to 15,000 psi, (11) 315*h*.
stability, phase boundaries at pressures above 50 atm., (7) 200*i*.
Dicalcium silicate. See *Calcium.*
Dickite, dehydroxylation of, heats of reaction and kinetics of dehydration, (6) 166*b*.
Dictionaries, red book issue, B (10) 292*f*.
of refractories, Portugese, French, English, Italian, and German, (2) 54*f*.
Dielectrics. See also *Ferrites; Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials; Glass; Porcelain, electrical; Steatite; Titanates; Whiteware.*
barium titanate, devitrified, (5) 128*b*.
ceramic, coating for, P (7) 192*i*.
constants, of, barium titanate, effect of two-dimensional pressure on, (2) 49*h*.
determining for irregular crystals, P (11) 306*c*.
method to determine for material using calibrated standards, P (5) 132*b*.
phenomenological theory in barium titanate, (2) 40*f*.
production and properties of materials with high, (2) 40*g*.
of silica as function of specific surface, (9) 249*f*.
variation in diamond with pressure, (7) 203*f*.
crystals, absorption of sound waves in perfect, (2) 48*e*.
films, deposition by rf sputtering, (7) 198*b*.
films, structure and properties, (1) 13*j*.
loss, in MgO, effect of water vapor on, (8) 226*b*.
materials, instrument to study conduction processes in insulating liquids and solids, (11) 310*c*.
materials, methods and apparatus to electrically pierce microscopic holes in, P (4) 105*g*.
panels, P (9) 235*i*.
power, absorbing means, P (5) 130*d*.
properties, of $BaTiO_3$ single crystals, (10) 290*b*.
of ceramics, (3) 72*d*.
domain structure of ferroelectric barium titanate and its effect on, (7) 198*f*.

Dielectrics, properties (*continued*)
of praseodymium fluoride films, (6) 157*j*.
regularity of change in electronic glass in wide range of temperatures and frequencies, (6) 148*f*.
of $NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$ single crystals, (5) 135*d*.
in systems $BaTiO_3$-UO_2 and $BaTiO_3$-$BaUO_3$, (6) 157*i*.
studies, of glasses in PbO-MgO-BaO-SiO_2 system, (8) 211*a*.
titanates, body improvement, (6) 157*e*.
Dies. See also *Extrusion*.
carbide, diamonds to finish, (6) 143*f*.
design, for pressure sintering, (10) 280*a*.
glass backup, for multigun welders, (11) 295*g*.
graphite for, (5) 130*f*.
of metal silicides, extrusion of ferrous metals through, P (1) 11*c*.
refractory, by Shaw casting, (3) 68*i*.
Differential thermal analysis. See *Thermal analysis*.
Diffraction. See *Electron diffraction; Neutrons; X rays*.
grating, reflecting for minimizing anomalies, P (5) 132*c*.
neutron-, of $Co_3B_2O_6$, (9) 252*b*.
of neutrons, B (2) 55*h*.
pattern, caused by temperature diffuse scattering, general theory, (4) 110*g*.
X-ray, divergent beam and its application in irradiated magnesia, (2) 49*a*.
Diffractometers. See also *Electron diffraction; X rays*.
Philips, single crystal mounting device for, (3) 76*c*.
Diffractometry, X-ray, to determine lattice distortion in brittle crystal powder, (5) 131*f*.
Diffusion, binary, extension of Darken's equation to, (6) 167*e*.
cationic, dislocation dependence in $SrTiO_3$, (11) 315*g*.
of cations, in BeO, (3) 79*j*.
controlled, oxidation of lanthanides, (11) 315*d*
creep, of thin foil, (9) 249*h*.
grain-boundary, of Ni^{++} in MgO, (3) 82*d*.
grain-boundary, origin in MgO, (9) 252*i*.
of He, in glass melts, (9) 234*e*.
of H, in fused quartz, (4) 110*h*.
of impurities, in semiconductor melt, (11) 304*i*.
impurity, dislocation enhanced, (3) 80*j*.
of iron, in hematite, (11) 318*i*.
in metals and slags, effect of variable temperature on unsteady-state, (3) 67*b*.
method, P (2) 41*c*.
multicomponent, model for; correction (9) 234*d*.
of neutrons, B (2) 55*h*.
of Nb, in TiC and in the solid solution TiC-NbC, (10) 284*f*.
processes, between quartz and molten glass, (4) 92*i*.
of radioisotopes in basalt, (7) 198*e*.
self-, cationic in calcia-stabilized zirconia, (6) 165*e*.
self-, and sintering kinetics of vanadium carbide, (9) 255*g*.
studies, of Na_2O-SiO_2-Fe_2O_3 melts at 1200°C, (11) 315*f*.
surface, and growth of oxide particles on metal surfaces, (2) 52*g*.
surface- and volume, contribution to morphological changes driven by capillarity, (5) 141*c*.
technique, for making composite optical maser crystals, (2) 41*d*.
zone, of bicrystal system, forces in redistribution of misfit dislocations in, (2) 50*c*.
Diffusivity, anisotropic, in pressed catalyst pellets, (2) 36*c*.
thermal, theory by pulse technique, (5) 141*h*.
Dilatometers. See also *Expansion*.
for heated specimens, P (5) 132*d*.
improved, (11) 310*g*.
tests, (6) 162*b*.
Dinnerware, (2) 39*g*. See also *Art and artware; Pottery; Whiteware*.
Angerstein, origin of, (8) 205*i*.
design and method, P (11) 304*c*.
developments, recent and current, (3) 71*g*.
glass, synthesis and study of that with rare-earth elements, (7) 181*i*.
hotel, P (9) 242*b*.
impulse buying, (8) 219*a*.
industry, automatic equipment for, (7) 190*j*.
manufacture, in Mexican plant, (4) 102*f*.
multicolor stamping machine for, P (7) 191*c*.
plates, Italian installation for manufacturing and once-firing, (1) 12*h*.
plates, semiautomatic machine for shaping, P (6) 157*c*.
semiporcelain, from Philippine materials, (8) 219*f*.
shipping carton, P (4) 103*d*.
teapot, protective cover for, P (8) 219*c*.
Diodes, P (5) 129*f*. See also *Tubes, electron; Rectifiers*.
Al-Al_2O_3-metal, potential barrier parameters in thin-film, (5) 128*e*.
enclosed crystal, P (1) 14*h*.
GaP, containing shallow donor and acceptor levels, electroluminescence near band gap in, (1) 13*h*.
germanium, method to produce variable-capacitance and product, P (6) 160*e*.
pn, integrated semiconductor tunnel, P (2) 41*g*.
semiconductive, of single-crystal rutile and method of making, P (1) 15*h*.
semiconductor, enhancement of reverse current in by electron bombardment, (10) 276*j*.
GaAs, P (11) 306*g*.
Diodes, semiconductor (*continued*)
high conduction, P (4) 104*j*.
and manufacture, P (6) 160*h*.
and method of making, P (7) 194*e*.
Si-SiO_2-metal, rectification phenomena in, (10) 277*i*.
solid state, contact for, P (11) 305*d*.
temperature compensated zener, P (6) 161*c*.
tunnel, with junctions on faces, P (9) 244*d*.
method of making, P (6) 160*a*.
solid state, P (11) 306*i*.
zener, P (8) 222*b*.
Disilicides, mutual solubility, of transition metals from groups IV, V, and VI, (9) 252*j*.
Disintegrators. See *Crushing apparatus*.
Dislocations, Burgers vector of, determined in deformed uranium carbide, (9) 249*f*.
in calcite, chemical consequences, (3) 81*b*.
in cronstedtite, (3) 81*g*.
damping, kilocycle-range in MgO, (5) 138*b*.
damping, in rutile single crystals, (2) 49*j*.
edge, and circular inclusion, interaction between, (1) 22*e*.
edge, inside circular inclusion, (1) 20*c*.
effect, on temperature characteristics of polymorphous transformation of cristobalite, (9) 249*b*.
enhanced, impurity diffusion, (3) 80*j*.
etch pits, on planes of magnesium oxide, (7) 198*g*.
as fracture sources, (1) 20*b*.
in graphite and carbons, mechanical energy losses due to motion of, (4) 112*a*.
loop, in graphite structure, vacancy condensation and transformation to, (4) 109*i*.
misfit, forces in redistribution in diffusion zone of bicrystal system, (2) 50*c*.
multiplication, (3) 81*a*.
network, in neutron-irradiated LiF crystal, (4) 110*j*.
origin, in solution-grown crystals, (7) 201*g*.
and oxide particles in Mg, interaction between, (1) 21*e*.
in quartz, observed by transmission electron microscopy, (3) 81*d*.
in quartz crystals, (11) 315*g*.
in NaCl crystals, means to make visible, (9) 249*i*.
Dispersion, of fine particles, in nonpolar organic solvent, (6) 156*c*.
infrared rotary, sublattice contributions to in YIG, (10) 291*c*.
of optical glass, dependence on frequency of glass, (2) 31*g*.
-strengthened, Co alloys, (11) 301*f*.
Dissolution. See *Solutions*.
Distortions, crystal, in copper ferrite-chromite series, (4) 110*c*.
crystal, of FeO on cooling past its Néel temperature, (10) 284*a*.
Jahn-Teller, induced by tetrahedral-site Cr^{3+} ions in spinels, (10) 287*a*.
theoretical plastic, of polycrystalline aggregate under combined and reverse stresses, (1) 25*i*.
Distribution, of elements, chemical bond and geochemical, (4) 109*j*.
of isomorphous substitutions, in muscovite, (7) 198*g*.
probability, generalized with special reference to mineral industries, (4) 108*j*.
of Zn, in indium antimonide, (9) 249*j*.
Dolomite. See also *Refractories*.
and calcite, O and C isotopic fractionation between coexisting metamorphic, (10) 289*e*.
clinker, effect of heat on, (3) 66*i*.
clinker, properties and manufacture of, (10) 272*h*.
crystal molds in, origin and interpretation, (11) 314*f*.
dead-burned Korean, ramming clinker on floor of open-hearth furnace, (8) 216*h*.
limestone concrete, effect of dispersed additives on quality of, (6) 144*d*.
synthesis, crystal particularities in, (3) 80*a*.
tar-, automatic preparation of brick from, (2) 36*h*.
Domains. See *Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials*.
Dopes, behavior, in tungsten sorts produced by powder metallurgy, (11) 313*i*.
Drawing, vertical, glass stratified by, (1) 5*c*.
Drills, diamond, bit for, P (6) 143*h*.
Dryers. See also *Drying*.
for aggregate material, P (8) 224*g*.
air, making them efficient, (1) 17*i*.
gas contact spray, P (11) 308*j*.
for granular or powdery materials, P (3) 77*i*.
and heater, for granular materials, P (4) 100*a*.
loading, apparatus for, P (8) 222*g*.
rapid, effect on mechanization of Italian brickworks, (11) 300*a*.
spray, P (11) 309*c*.
steam, with air recovery means for brick, P (9) 246*j*.
synchronized charge and removal for, P (6) 161*f*.
Drying. See also *Dryers*.
brick, factors effecting, (11) 300*g*.
of clays, evaluation of sensitivity to, (5) 130*h*.
clays, new method to determine sensitivity to, (2) 44*e*.
of furnaces, records of temperature rise after, (3) 68*i*.
of halloysite, mineral changes on, (10) 288*f*.
molded products, automatic handling equipment for, P (7) 195*g*.
of mortars, changes in weight and dimensions in, (1) 2*d*.
Drying (*continued*)
of powders, method and apparatus using electrica gas discharges under a vacuum, P (6) 161*d*.
radiant, of particulate material, (8) 224*g*.
with radiant heat, method and apparatus, P (2) 46*f*.
rapid, of porcelain, (2) 39*g*.
rapid, of sanitary ware, (2) 39*h*.
Dry pressing. See *Pressing*.
Dunite, serpentinized, high-pressure reactions and shear strength of, (11) 317*i*.
Dusts. See also *Air, pollution; Particles; Powders*.
apparatus to produce, P (3) 78*e*.
from cement kiln, effect on vegetation, (11) 294*g*.
collector, fabric tube type and method of operating, P (2) 43*f*.
collector, in refractory industry, (8) 215*c*.
concentration, continuous measurement by electrical contacts, (2) 44*a*.
density, apparatus to measure, (1) 16*h*.
extraction, efficiency of bag filters, (10) 280*a*.
in stoneware industry with electrofilter, (10) 275*g*.
system for dry recovery, (1) 16*d*.
measurements, evaluation in ceramic industry, (10) 280*i*.
measurements, with konimeter, (10) 280*i*.
particles, electrostatic apparatus to remove from gas stream, P (2) 43*e*.
protection apparatus, (10) 280*c*.
refractory, to reduce electron concentration in gas plasma, (5) 140*j*.
removal, electrostatic, (11) 308*i*.
removal, from hot gases by fabric filters, (1) 17*h*.
toxicity, of oxides of gadolinium and dysprosium in form of, (2) 55*a*.
Dysprosium, aluminum garnet, thermal properties near Néel temperature, (2) 53*c*.
oxide, temperature and porosity dependence of Young's modulus of, (5) 141*g*.
oxides, toxic in dust form, (2) 55*a*.

Earthenware, bodies, intensifying vitrification with combined additives, (6) 156*g*.
bodies, new deflocculants for and their effects on casting behavior and properties of, (6) 156*j*.
glazes for, effect of frit additions to, (8) 219*a*.
tile, improving quality of glazes for, (6) 156*e*.
tile, new compositions for white, (6) 156*i*.
Education, silicate engineering, at Technologisches Gewerbemuseum, Vienna, (2) 54*j*.
Elasticity. See also *Anelasticity*.
behavior, of fiber reinforced materials of arbitrary transverse phase geometry, (1) 20*i*.
and breaking characteristics, method to determine for glass films, (9) 233*i*.
of clays and kaolins, in relation to their heat treatment, (10) 282*g*.
coefficients of quartz, third-order, (5) 141*j*.
constants, determination for cement by resonance method, (6) 144*i*.
determination for monoclinic crystals from diffuse X-ray reflections, (7) 198*i*.
of silicon carbide, (7) 198*j*.
of single-crystal BeO at room temperature, (4) 110*i*.
of single-crystal MgO, pressure derivatives of, (9) 253*i*.
of synthetic sapphire at 27°C, (2) 49*h*.
theoretical study and optical determination for single crystals, (7) 203*b*.
ultrasonic wave propagation velocity in ferrite and, (11) 305*i*.
moduli, approximate relation with thermal expansivities, (2) 48*g*.
determination of Poisson's ratio of cement by the Young and torsional, (6) 144*j*.
measurement in fireclay brick, (1) 7*j*.
measurement of third-order of YIG, (9) 252*c*.
method to calculate for powder from compressibility and Debye temperature data, (7) 202*j*.
modulus, anomalies in shear of antiferromagnetic materials, (10) 283*h*.
of concrete and cement paste and mortar, effect of aggregate and voids on, (2) 28*i*.
test to determine for refractories at high temperature, (6) 152*f*.
of two-component material, (10) 288*h*.
properties, of brick cube, (10) 270*c*.
of glasses, effect of heat treatment on, (6) 147*j*.
of polycrystalline MgO and Al_2O_3 at high temperature, (8) 226*g*.
and thermoeleastic properties, of gypsum, (7) 199*a*.
wave, propagation in $LiNbO_3$, (10) 285*j*.
Young's modulus, of pyrolytic carbon in relation to preferred orientation, (2) 54*a*.
Young's modulus, temperature and porosity dependence for polycrystalline dysprosium oxide and erbium oxide, (5) 141*g*.
Electrets, glass, (7) 180*b*.
Electrical ceramics. See also *Electronics*.
apparatus for slip casting, P (4) 103*a*.
for high-voltage applications, improved mechanical properties of, (6) 157*h*.
Electrical conductivity. See *Conductivity, electrical*.
Electrical properties, of alumina polyphase heterojunction, (1) 21*a*.
of cadmium telluride contacts, (3) 81*d*.
of capacitors, of Dy_2O_3-B_2O_3-SiO_2 system, (8) 219*j*.
of ceramics, B (5) 142*i*.
of chromium carbides, (11) 316*a*.
of crystallized glasses, in system MgO-Al_2O_3-SiO_2-TiO_2, (2) 31*j*.
of glass, in system Na_2O-RO-SiO_2, (3) 61*c*.

Electrical properties (*continued*)
of higher silicide of Mn, (11) 316*a*.
of semiconducting oxides, (11) 315*f*.
of thorium carbide, (11) 316*b*.
of vacuum evaporated silicon films, (2) 40*h*.
of Y_2O_3, (9) 249*h*.
of Y_2O_3 doped calcium diferrite, (11) 304*j*.
Electric components, protection, from damage by arcing or plasma discharges in vacuum systems, (4) 107*h*.
sealed assembly, P (11) 307*c*.
Electric resistors. See *Resistors, electrical*.
Electroanalysis. See *Analysis*.
Electrochemistry. See also *Corrosion*.
aspects, of hydrolysis of UC-10%Fe, (10) 285*f*.
of electrolytes, molten and solid, B (1) 26*g*.
process, to form bubbles in glass, (11) 296*e*.
theory, for O reboil, (11) 296*i*.
Electrodes. See also *Heating elements*.
activated C, for reduction of O in fuel cell, (8) 215*f*.
capacitor, and method, P (7) 192*j*.
carbon, P (10) 273*c*.
apparatus to make, P (10) 273*h*.
from bituminous mixes, P (9) 240*f*.
-metal, for fuel cells, (7) 191*d*.
coated, for welding and hard-surfacing cast irons, P (8) 208*b*.
coating, and discharge device, P (7) 192*j*.
effects, in degradation of ceramics at high temperature, B (11) 320*f*.
for electron tube, P (8) 220*i*.
fuel cell, improvement of lithiated nickel oxide, P (4) 105*h*.
for fuel cells, method to make, P (1) 11*c*.
glass, alkali error of, (8) 208*g-h*.
equation to calculate alkali error of, (8) 209*e*.
measurement of pH under pressure and at high temperatures, (5) 131*i*.
method to make, P (1) 7*b*.
and method of making, P (4) 96*i*.
studies of cation sensitive, (6) 146*h*.
hard-facing, arc welding, P (1) 3*d*.
of high intensity C, P (9) 243*f*.
Ni, vacuum breakdown in presence of thermionic cathodes, (10) 277*b*.
from porous carbon, P (1) 12*a*.
for semiconductive barium titanate, electroless, (9) 242*i*.
of silver oxide palladium, P (1) 15*a*.
small carbon, factors influencing performance of pitch binders in baking of, (4) 111*i*.
spark machining, P (1) 12*d*.
stationary, measurement of glass level with, (2) 31*c*.
storage, P (5) 130*d*.
Ta, preanodization of, P (3) 74*d*.
thin film electron emissive, P (10) 279*g*.
triggered, as spark gap, P (2) 43*b*.
of two metals, continuously graded for semiconductor devices, P (11) 305*e*.
vapor deposition of, making masks for, P (11) 306*h*.
welding, consumable, P (1) 3*g*.
flux-coated, P (8) 208*e*.
flux-coated and composition, P (5) 120*b*.
Electroluminescence. See *Luminescence*.
Electrolytes, additions, effect on rheology of lime suspension, (4) 90*e*.
in extrusion of clays, (3) 65*c*.
molten and solid, electrochemistry of, B (1) 26*g*.
solid oxide, factors effecting performance in high-temperature thermodynamic measurements, (7) 199*c*.
solutions, etching of surfaces by electric discharge in, (5) 136*d*.
on water dispersions of montmorillonite, criteria to evaluate coagulation action of, (9) 256*f*.
Electromotive force, of silicate melt concentration cells, with semipermeable bridges, (5) 135*h*.
Electron diffraction, of aluminum oxides, (7) 199*e*.
scanning, of film growth, (10) 281*c*.
Electronic equipment, acoustic delay line, cold diffusion bond between back electrode or acoustic absorber and, P (7) 192*d*.
bonded metal-ceramic elements, P (5) 128*i*.
cold cathode display device, with fluorescent indicia anodes, P (9) 243*a*.
compact bodies, of manganic oxide and/or iron oxide, P (8) 221*c*.
control unit, for electrostatic image recorder, P (10) 278*a*.
cryotrons, method to fabricate high gain, P (6) 159*g*.
cup-shaped bodies, method to mold, P (9) 243*c*.
delay line, method to make flux free bonded, P (5) 129*c*.
device, packaged, P (9) 243*j*.
device, of semiconductor body with at least one contact, P (9) 243*a*.
discharge device, P (6) 159*c*; P (8) 220*f*.
cathodic glow gaseous, P (5) 128*a*.
electric with improved dispenser cathode, P (11) 305*h*.
leakage inhibiting supporting structure, P (3) 73*h*.
dosimeter shield, thermoluminescent, P (4) 106*f*.
double epitaxial layer functional block, P (5) 128*b*.
electrical resistance device, electroconductive coating patterning, P (6) 159*c*.
electrical unit, with molded coating, P (4) 106*h*.
electroluminescent device, P (5) 128*c*.
electron-beam, for vacuum melting and machining of refractory cermets, (1) 17*h*.
electron-optical reticles, art of making, P (4) 104*j*.
energy converter, P (11) 306*b*.

Electronic equipment (*continued*)
enclosures, drying using boron nitride hot sealing, P (6) 159*b*.
ferrite frequency converter, P (9) 243*d*.
ferroelectric disk, shock-loaded short-circuited, (5) 128*a*.
ferroelectric signal-translating device, with voltage-controlled signal delay, P (6) 159*g*.
filament wound, reinforcing holes in, (2) 40*g*.
fluid amplifiers, material for, (2) 44*h*.
frequency selector, with ferrite elements biased to different resonant frequencies, P (11) 306*f*.
generator, pulsed ferromagnetic microwave, P (8) 221*j*.
helix, method to wind, P (11) 307*c*.
heterojunction elements, P (10) 279*a*.
igniter, incandescent electrical, P (2) 41*f*.
impedance devices, thin film, P (9) 243*g*.
impedance element, method of making encapsulated, P (3) 73*b*.
intensifying devices, electron image, P (5) 128*c*.
metallized components, P (10) 278*b*.
metal vacuum systems, installation of terminals by electron beam welding, (10) 277*b*.
magnetic amplifiers, with ferrite cores, (8) 220*g*.
magnetic heads, method to make with bonding gap-filling materials, P (7) 193*f*.
masking fixture, method to form by expitaxial growth, P (5) 129*b*.
microwave element, method of making, P (3) 73*b*.
phase shifter, temperature compensated reciprocal ferrite, P (11) 308*a*.
photoconductor, from cadmium oxide, P (8) 221*d*.
read-out device, with glass coated metal wires, P (5) 128*d*.
read-out device, with panels and bonds having corresponding indices of refraction, P (11) 307*a*.
resonance electroluminescent display panel, P (6) 160*d*.
resonant cavity device, method to make, P (7) 193*a*.
solid delay line, P (8) 222*a*.
solid state devices, methods to achieve, (6) 157*h*.
solion cell, comprising porous cathode on each side of the anode, P (1) 15*a*.
solions, with graphite separators and electrodes, P (1) 15*a*.
superconductor, Nb-Zr, P (8) 221*f*.
thin-film components, materials and process for passive, (10) 277*e*.
thin film translator, with emitter of CdS film, insulating layer, and means for applying potential across, P (2) 43*a*.
transmission line, low impedance coupled and solid state tunnel diode, P (11) 306*i*.
visual indicator, electroluminescent frequency sensitive, P (5) 128*c*.
voltage regulator, P (6) 161*c*.
Electronics. See also *Electric ceramics; Electronic equipment*.
aluminas and titanates in, state-of-the-art, (10) 276*h*.
components, effects of radiation on, (4) 103*h*.
electroceramics, technology of, (7) 192*g*.
glass in, symposium, (11) 297*e*.
materials, bonds for oxidized, P (6) 158*g*.
materials, fabrication, properties, and uses, (6) 157*h*.
micro-, technology of materials for, (1) 14*c*.
new materials for, (4) 108*i*.
-physics, 1960 titles, B (6) 174*b*.
properties, of CdS and CdSe films, effects of fabrication parameters on structural and, (7) 191*g*.
of materials, B (1) 26*c*.
of solid solutions and intermetallic compounds, B (6) 171*f*.
of titanium monoxide, (5) 136*c*.
resistor bead, method to cover, P (7) 193*j*.
Electrons, beam, display device, P (1) 14*j*.
beam heating, as research tool, (5) 135*j*.
bombardment, electrical conductivity induced in MgO by, (7) 199*b*.
to enhance reverse current in diodes, (10) 276*j*.
fabrication of uranium monocarbide by, B (6) 172*f*.
to make dislocations in NaCl visible, (9) 249*i*.
d, properties imparted by, B (9) 259*e*.
diffraction, of graphite, low energy, (6) 168*j*.
distribution, in Cu_2O crystal, (4) 111*d*.
emission, method and means to improve from refractory conducting material, P (7) 193*g*.
free, in gas plasma, refractory dust to reduce, (5) 140*j*.
gun, supporting technique, P (1) 14*a*.
high energy, scattering by thermal vibrations of crystals, (3) 85*d*.
and hole trapping levels in quartz, optical studies of, (9) 252*f*.
hot, emission by silicon, (6) 167*a*.
hot-, transfer through thin-film Al-Al_2O_3 triodes, (5) 137*d*.
in MgO crystals, effect of scattering on mean and anomalous absorption coefficients of, (4) 110*c*.
mobility, in $GaAs_{1-x}P_x$ alloys, (10) 285*h*.
photoemission, from Si into SiO_2, effects of ion migration in the oxide, (9) 253*f*.
probe, to study grain-boundary reactions in magnesia-chrome refractories, (11) 301*e*.
source, solid-state, P (2) 42*j*.
transmission, studies of magnesium oxide crystals, (2) 53*e*.
Electron tubes. See *Tubes*.
Electrooptic, effect, of ferroelectric microcrystals in glass matrix, (10) 285*j*.

Electrooptic (*continued*)
effect, strain-free in single-crystal barium titanate, (10) 290*f*.
properties, of $BaTiO_3$ single crystals, (10) 290*b*.
Electrophoresis, in application of enamel, (9) 231*i*.
Electrostatic processes, to apply enamels, (6) 145*j*.
charge, study of glass surfaces by generation of, (10) 266*f*.
glass-coated metal for use in, P (2) 30*g*.
screen printing, (2) 43*e*.
Elements, chemical bond, and geochemical distribution of, (4) 109*j*.
groups IV and V, reactions between ZnO and oxides of, (2) 51*j*.
heating. See *Heating elements*.
radioactive, to automatically determine moisture, (3) 76*b*.
trace, preconcentration by precipitation ion exchange using organic-hydrochloric acid systems, (2) 45*a*.
zirconia-based refractory, electroprotection of, P (6) 146*e*.
Emission, phonon-photon double quantum, ultrasonic maser amplification in MgO by, (10) 291*e*.
stimulated, in a *Q*-spoiled ruby laser, (1) 25*e*.
-transmission, X-ray quantitative analysis by, (3) 76*i*.
Emittance, heat, properties of materials, (2) 54*g*.
Emitters, electron, P (9) 243*d*.
electron, with nitride emissive material, P (11) 306*a*.
thermionic, and method, P (4) 106*e*; P (6) 159*j*.
thermionic, uranium monocarbide, P (5) 127*b*.
Enameled ware, mechanical strength of, (11) 295*i*.
Enameling, abrasives and grinding for, (4) 91*c*.
clays, properties and performance, (4) 91*j*.
with colored thermoplastics, for hot-screen decorating, (11) 295*h*.
direct-on, and conventional of steel sheets, (10) 263*d*.
of decarburized steels, (7) 178*g*.
flexosmalt technique for sheet steel, (10) 263*e*.
dry process, for bathtubs, (10) 263*e*.
equipment. See also *Spraying*.
frits, opacification systems in powdered white, (7) 178*h*.
furnaces. See *Furnaces*.
industry, improved cleaning methods in, (4) 91*h*.
on metal, aspects of, (4) 91*b*.
method, P (9) 232*c*.
one-coat, spray sulfuric acid pickling for, (8) 208*c*.
plant, acid pickling facilities for, (10) 263*j*.
main difficulties in, (3) 59*i*.
in Monterrey, Mexico, (4) 91*f*.
problems of metal cleaning for, (8) 208*b*.
sheets, formability of, (9) 231*i*.
sheets, method to prevent fish scaling, (6) 145*c*.
of sheet metal, pretreatment for, (10) 263*j*.
sheet steel, effect of water vapor in furnace on (9) 231*i*.
of silver, (8) 206*a*.
tips, (8) 208*c*.
Enameling apparatus. See *Furnaces; Spraying*.
Enameling metals, cast iron, thermal stress effects in, (10) 263*e*.
decarburized steel, enameling of, (10) 263*d*.
fish scaling, elimination in iron and steel sheets, P (11) 295*h*.
pickling. See *Pickling*.
seam welding for, (11) 295*c*.
sheet, pretreatment for enameling, (10) 263*j*.
sheet, tooling parts of, (4) 91*e*.
steels, comparison of, (4) 91*e*.
effects of firing temperature on properties of, (9) 231*h*.
etch rates of, (4) 91*f*.
flexosmalt technique to enamel, (10) 263*e*.
formability of extra-low-carbon, (4) 91*g*.
manufacture and properties of sheet, (10) 263*i*.
sheet, enamels for, (2) 30*d*.
sheet producers, cooperation of enameled ware producers urged, (2) 30*e*.
Enamels. See also *Coatings*.
(2) 30*c*.
adhesion on steel, factors affecting, (6) 145*d*.
alkali resistance, test for, (6) 146*d*; (9) 232*d*.
alkali resistance, variables affecting determination, (6) 146*c*.
on Al, new spall test for, (6) 146*c*.
on appliances, reduce shipping damages, (8) 208*c*.
bond, metal pretreatment and one coat, (6) 146*b*.
for cast-iron, bubbles and pinholes in, (3) 59*g*.
cleanability, report on test for, (7) 179*b*.
coating, effect of bubble structure on properties of, (2) 30*a*.
method and apparatus, P (4) 91*g*.
standardized test for continuity of, (7) 178*j*.
color and appearance, methods to measure, (7) 178*h*.
composition, P (4) 91*f*.
defects. See also *Enamels, fish-scaling*.
defects, tool design to reduce, (2) 30*c*.
direct-on, problems of, (4) 91*g*.
effect of washing materials on, (3) 59*i*.
electrophoretic deposition of, (5) 119*i*; (9) 231*i*.
electrostatic application of, (5) 119*j*; (6) 145*j*.
electrostatic spraying of, (8) 207*i*.
finishes, tests for, (11) 295*d*.
fish scale control, on decarburized enameling sheets, (6) 145*c*.
fish-scaling, etching to control, (6) 145*d*.
flexible, (4) 91*d*.
frits. See *Frits*.
glasses, surface tension measurement of, (1) 3*f*.
granules, computation and experimental determination of coefficient of expansion, (2) 30*c*.
ground, physical properties of low firing, (2) 30*a*.

Enamels (*continued*)
ground coat, effect of bubble structure on properties of, (6) 145*g*.
ground coat, new for sheet iron, (2) 30*g*.
iron-containing, effect of composition on whiteness, (2) 30*d*.
lead arsenic, for thermometers, (10) 264*f*.
majolica, lead-containing and lead-free, (10) 263*h*.
new applications, (8) 207*j*.
one-coat, cooperation between producers of enameled ware and sheet steel urged, (2) 30*e*.
one-coat, review, (2) 30*i*.
opacification, with zircon, (6) 156*d*.
and organic finishes, comparison of, (9) 231*h*.
phosphate, evolution of gases during reaction with Al, (2) 30*e*.
pickling waste, treatment of, (8) 208*e*.
plant, systems concept for, (8) 208*d*.
problems, means to solve, (9) 232*b*.
process equipment, factors in purchasing, (6) 145*f*.
R & D, instrumentation in, (6) 145*i*.
screen printing on, (5) 119*j*.
-sheet steel reactions, (11) 295*f*.
slips. See *Slips*.
spontaneous spalling of, (5) 119*j*.
spraying, factors and equipment in, (7) 178*i*.
for steels, properties of, (2) 30*d*.
sulfur in, (3) 59*h*.
systems. See *Systems*.
Ti, discoloration of, (6) 145*e*.
vitreous, frit compositions for, P (2) 30*f*.
luster finishes on, (3) 59*g*.
tension strength of, (5) 119*g*.
versatility with regard to base metal and fabrication, (5) 119*j*.
weather resistance, (11) 295*e*.
weather resistance, results of seven-year tests, (6) 146*b*.
white ground coat, (10) 263*f*.
zirconium, effect of composition on whiteness and water resistance of, (6) 145*h*.

Energy, activation, calculation for solid state reactions of polydisperse mixtures, (10) 283*i*.
activation, thermal release of gas trapped in sites with a continuum of, (4) 113*j*.
consumption, norms in glass industry, (2) 31*b*.
conversion, principles of, B (9) 259*g*.
defect, levels in reduced TiO_2, (10) 285*f*.
electron binding, in Compton scattering from graphite, (9) 249*h*.
interfacial, equalization processes by material exchange processes in silicate glass, (4) 94*d*.
radiant, measuring device, P (10) 281*i*.
surface, in Na_2O-ZrO_2-SiO_2 glass, (1) 4*h*.
for surface mobility, of gold films on mica, (7) 191*i*.

Engineering, chemical, granulation in, (1) 15*i*.
silicate, education in Vienna, (2) 54*j*.

Engobes, white and colored, for facing tile, (3) 71*g*.

Enthalpy. See *Heat, content*.

Equations, for calculating chain length distributions in polyphosphoric acids and polyphosphate glasses, (3) 61*d*.
conversion, to change frequency representation from weight to number basis for phi-normal size distributions, (5) 142*b*.
Darken's, extension to binary diffusion in ceramics, (6) 167*e*.
solid state reaction, numerical data for common, (8) 226*a*.
transport, in surface space-charge layer, (10) 284*h*.
vacuum pumping, effect of pipeline outgassing in, (2) 44*e*.

Equilibrium studies. See also *Systems*.
equilibria, *P-T* univariant of monticellite and akermanite reactions and reaction forsterite + calcite = monticellite + periclase + CO_2, (9) 250*c*.
of PbO-Al_2O_3, (9) 252*i*.
phase diagrams, construction for reciprocal systems using weight percentages, (6) 165*g*.
of crystal hydrates of $MgSO_4$ at high pressures, (10) 289*g*.
factors determining type in binary systems formed by refractory oxides, (10) 290*c*.
prediction of high temperature metallic, B (2) 55*g*.
and structure of melts in systems Bi_2Se_3-Sb_2Te_3 and Bi_2Te_3-Sb_2Se_3, (11) 318*e*.
of systems, B(10) 292*i*.
of system Sc_2O_3-MgO, (9) 252*j*.

Equipment. See *Machinery and equipment* and specific types.

Erbium, oxide, temperature and porosity dependence of Young's modulus of, (5) 141*g*.
titanate, determination of crystal structure, (5) 134*j*.

Erosion, action, on acidic firebrick for cupolas, (1) 8*h*.
cavitation, mechanism in cement and polymer concretes, (4) 90*j*.
of center brick, for bottom casting, (1) 8*g*.
of high alumina brick, comparison of alkali-containing atmospheres and soda-lime glass melts in, (1) 8*f*.
of ladle brick, methods to reduce in converter mills, (9) 238*e*.
of ladle lining, results of measurement by radioactive isotope, (8) 216*h*.
of LD converter zircon ladle brick, (9) 238*f*.
mechanism, of basic brick in a copper reverberatory furnace, (6) 152*g*.
mechanism, of tar-dolomite brick for open-hearth wall, (3) 67*d*.
rate, of clay-bonded SiC brick by molten iron and qualities of raw materials, (4) 99*a*.

Erosion (*continued*)
of refractories, in melting zone, relation to cupola operation, (1) 9*j*.
resistance, of chromium carbide alloys in corrosive environments, (11) 300*j*.
of fireclay to high calcareous slag, (6) 152*g-j*.
resistance, to slag of BOP brick, (8) 216*b*.
of silicon nitride refractories, by iron, (9) 238*f*.
of slag, test results, (4) 99*g*.
of tar-dolomite lining where perforated lance is used, (8) 216*c*.
test methods, attempts to standardize Japanese, (9) 238*g*.

Etch, patterns, in TiO_2 single crystals, (10) 286*a*.
pits, in cronstedtite, (3) 81*g*.
dislocation, on planes of magnesium oxide, (7) 198*g*.
studies of magnesium oxide crystals, (2) 53*c*.
spirals, in graphite, (7) 199*b*.

Etching, by alkali, of silicate glasses, electron microscopy of, (8) 210*e*.
of $BaTiO_3$, (2) 50*a*.
baths, low-cost regeneration of ferric sulfate, (4) 91*i*.
cathodic, to control fish-scaling, (6) 145*d*.
corundum, with Si, (9) 250*a*.
of glass sheet, to improve strength, (7) 181*i*.
means, for glass, P (10) 269*h*.
methods, their application to optical metallography, B (6) 173*g*.
pits, compared to whisker growth sites on sapphire, (4) 110*a*.
rates, of enameling steels, (4) 91*f*.
to reveal diamond structure, (1) 25*g*.
of Si, room temperature oxidation during and after, (5) 140*c*.
solution, for Si and Ge, P (11) 306*c*.
by sputtering, of alumina and fused silica, (8) 226*e*.
of $SrTiO_3$, (3) 81*g*.
of surfaces, by electric discharge in electrolyte solutions, (5) 136*d*.

Ethane, diffusion, in zeolites, (5) 135*h*.

Ethylene, glycol-montmorillonite, X-ray study of, (6) 171*a*.

Ettringite, crystals, in cement paste, (1) 2*e*.

Eucryptite, synthetic and natural, (5) 141*f*.

Europium, -activated, Y and Gd oxides, cathodoluminescence of, (8) 219*g*.
-activated phosphors, performance in color picture tubes, (8) 220*d*.
beryllides, of composition ABe_{13}, (11) 313*j*.
divalent ions, spectra in crystals of alkaline earth fluorides, (9) 256*d*.
Eu_2O_3 and $EuGd_2O_4$, magnetic ordering in, (9) 251*e*.
fluoride, magnetic and chemical properties of, (7) 200*i*.
glasses, preparation and Faraday rotation of divalent, (6) 148*d*.
magnetic structure of, (9) 251*f*.
orthoniobates of, (11) 318*c*.

Eutectics, growth, constitutional undercooling and, (3) 80*g*.
hyper-, carbide composites, new class of, (10) 272*d*.

Evaporation, flux, oxide crystals grown by, (11) 318*d*.
of stannic oxide, Knudsen and Langmuir studies, (4) 112*c*.
of water, from sodium silicate glass, (4) 93*e*.

Expansion. See also *Dilatometers*.
coefficient, effect of alkali content in porcelain on, (10) 275*h*.
and a contraction, causes of degrees in corundum-containing fireclay, (7) 185*h*.
data, for zinc phosphates and vanadates, (2) 49*i*.
enamel granules, computation and experimental determination of coefficient of, (2) 30*c*.
low, of tungsten based alloys, (11) 305*h*.
moisture, of porous products, (2) 35*h*.
problems, in high strength basic brick, (1) 9*a*.
rate of roof brick, relation to rate of temperature rise in reheating furnace, (3) 70*a*.
of raw materials, (7) 198*e*.
sulfate and autoclave, of cement, (11) 294*e*.
tests, to analyze clay minerals, (7) 197*f*.
thermal, of alkali halides at low temperatures, (2) 53*f*.
approximate relation with elastic moduli, (2) 48*g*.
of basic O furnace refractories, (8) 216*d*.
calculation for ionic crystals, (2) 51*c*.
of clay minerals, (2) 53*i*.
coefficients for Fe and its oxides from X-ray diffraction measurements at elevated temperatures, (2) 53*j*.
dependence on composition of Na_2O-ZrO_2-SiO_2 glass, (1) 4*g*.
of disilicides of some transition metals, (2) 53*a*.
of glass, (1) 5*g*.
of Illinois limestones, (8) 225*i*.
of niobium carbide-graphite, (8) 216*e*.
properties, of cristobalite-containing ceramics, (10) 291*g*.
of pyrolytic graphite-bromine residue compounds, (4) 113*j*.
of sodium fluoride and Grueneisen parameters of, (3) 87*a*.
of W and Mo disilicides, (9) 257*i*.
of zirconium carbides, (9) 257*h*.

Exports, of glass and glassware, performance, prospects, and problems, (2) 31*c*.

Extraction, of dust, system for dry recovery, (1) 16*d*.
solvent, of metal ions with trifluoroacetylacetone, (3) 76*f*.
solvent, studies with hydrochloric acid-2-ethylhexanol system, (3) 76*g*.

Extruders, new, (7) 194*i*.
wire guide for, P (7) 190*b*.

Extrusion. See also *Dies*.
of clays, electrolytes in, (3) 65*c*.
to fabricate U-C alloys, (11) 301*g*.
of ferrous metals, through dies of metal silicides, P (1) 11*c*.
hints and experiences in, (6) 161*d*.
machinery, P (3) 75*c*.

Fabrication, of ceramics, B (5) 142*i*.

Faraday, effect, in diamagnetic glasses, (9) 233*b*.

Faujasite, preparation of synthetic, P (10) 283*c*.

Feeding apparatus, for glass, batch, P (7) 184*c*.
for glass, fibers, electrically heated, P (7) 184*h*.
furnaces, trends in development of, (8) 211*b*.
gob, plunger mechanism for, P (7) 184*e*.
gob, tube mechanism for, P (6) 151*b*.
streams, P (11) 298*i*.
for multicomponent mixtures, P (4) 106*i*.
to produce fibers, P (11) 298*c*.
vibrating screw, for clay materials, (2) 35*d*.
vibratory, for materials, (2) 43*f*.
vibratory, screw feeder, P (1) 16*e*.

Feldspars, from coal-ash slags, study of medium to calcic plagioclase, (6) 170*f*.
determination, of K, Na, and Ca in, (3) 75*h*.
detrital, identification of, B (6) 172*i*.
in Illinois sands, (7) 196*h*.
in 1964, (1) 18*b*.
previously melted, effect on porcelain, (2) 39*g*.
properties, effect of vibratory grinding on, (3) 78*d*.
sand, arkoses, mining and preparation from Triassic basin at Weiherhammer, (3) 78*h*.
from Strzeblow, methods to enrich and technological tests, (3) 78*f*.
systems. See *Systems*.

Ferric, Ferrous, etc. See *Iron*.

Ferric oxide. See *Iron, oxide, ferric*.

Ferrimagnetism. See *Ferromagnetic materials; Ferromagnetism*.

Ferrites. See also specific types.
P (11) 306*c*.
cadmium-bearing, process to produce, P (5) 129*e*.
of cobalt with magnetite, activity of oxygen over solid solutions of, (11) 313*f*.
compositions, and manufacture method, P (4) 104*g*.
cores, assembly for magnetic storage devices, P (5) 129*i*.
fabrication of, P (6) 159*f*.
fabrication of magnetic, P (8) 221*h*.
magnetic amplifiers with, (8) 220*g*.
multiaperture, P (1) 15*a*.
development and present state of, (6) 157*j*.
devices, with metallized facing, P (10) 278*c*.
devices, for modulation and switching of microwaves, (11) 306*c*.
films, chemically deposited at mm wavelengths, (7) 191*c*.
formation, of precipitate from solution of divalent metallic and ferric ions, (9) 253*f*.
grain boundary and electrical resistivity, effect of impurities on, (9) 242*g*.
hexagonal, formation by thermal transformation of cronstedtite, (7) 199*h*.
hexagonal, magnetic susceptibility of granular, (11) 318*a*.
high iron magnesium manganese, P (3) 73*e*.
low-induction, for computer memories, (3) 72*g*.
magnetic head, glass bonded, P (2) 41*c*.
manganese-zinc-ferrous, P (8) 221*d*.
manufacture and grain growth in, (6) 157*i*.
materials, handbook of microwave, B (4) 115*c*.
heat sink for using metal oxides as the dielectric material, P (7) 193*c*.
and production, P (9) 243*e*.
method of firing, P (4) 105*b*.
new wax binder for, (9) 247*f*.
Ni-Mn-Al-Co, P (7) 193*i*.
Ni-Zn-Co, heat-treating method to modify permeability and quality factor of, P (6) 159*i*.
particles, method to compact, P (10) 278*e*.
parts, device to investigate properties in sonic and ultrasonic frequency ranges, (1) 13*g*.
phase in cement, its behavior during hydration, (3) 58*g*.
polycrystalline, (6) 157*i*.
polycrystalline, new method to distinguish different phases, (2) 50*e*.
process, P (11) 306*d*.
raw materials and compounds, DTA of, (6) 157*f*.
relaxation loss in, as function of ferrous ion content, (4) 104*d*.
sheet, method to make magnetic with embedded conductors, P (7) 193*e*.
with spinel structure, equilibrium with O, (7) 191*j*.
with spinel structure, oxidation of crystals during growth by verneuil method, B (11) 320*b*.
spinel-type, fluorine containing, P (4) 104*h*.
square loop, Mo modified, P (3) 74*a*.
ultrasonic wave propagation velocity in and elastic constant, (11) 305*i*.
variable inductor, P (10) 279*j*.
waveguide phase shifter, reciprocal with means to rotate magnetic field, P (10) 279*b*.

Ferroelectricity. See also *Barium, titanate; Ferroelectric materials*.
of monocrystals, of new perovskite compounds, (4) 111*i*.
of solid solutions, in system Ba(Ti, Zr, Sn)O_3, (4) 111*j*.
of SrBa titanate, (4) 111*a*.

Ferroelectric materials. See also *Barium, titanate; Ferroelectricity*.

Ferroelectric materials (*continued*)
and anti-, search for new not belonging to oxide group, B (11) 320*d*.
$Bi_4Ba_{m-2}Ti_{m-1}O_{3m+2}$, switching properties of, (11) 305*g*.
bodies, with high thermal shock resistance, P (8) 221*a*.
ceramic type, processing, P (10) 279*b*.
composition, P (10) 278*g*.
compound, and devices including elements of, P (5) 128*e*.
device and body, method of fabrication, P (1) (1) 14*b*.
with diffuse phase transitions, (4) 111*b*.
disk, current from shock-loaded short-circuited, (5) 128*a*.
lead barium niobate, P (3) 73*g*.
lithium niobate, behavior of, (10) 286*g*.
microcrystals, electrooptic effect in glass matrix, (10) 285*j*.
new, of complex composition, (4) 112*c*.
sodium-strontium niobates, dielectric properties and phase transitions of, (8) 219*i*.
thermal conduction in, (10) 277*a*.
and transducer with, P (2) 41*b*.

Ferromagnetic materials. See also *Ferromagnetism*.
CrO_2, electrical resistivity of, (4) 111*c*.
garnets, magnetic behavior of substituted, (9) 251*c*.
oxide, infrared reflectivity of, (6) 158*a*.
oxides, (6) 157*i*.
vanadium-containing, P (1) 15*g*.

Ferromagnetism. See also *Ferromagnetic materials; Magnetic materials*.
anti-, of $LiCuVO_4$ spinel, (11) 313*c*.
anti-, of spinel $MnGa_2O_4$, (11) 313*d*.
antiferromagnetic magnetostriction, in CaO and NiO single crystals, (4) 109*j*.
ferrimagnetic insulators, low temperature thermal conductivity of, (9) 242*j*.
and ferrimagnetism, of oxygen spinels containing trivalent Mn, (11) 317*a*.
ferromagnetic resonance line width, nickel ferrite and porosity broadening of, (3) 72*c*.
interactions, in nonmetallic perovskites, (11) 316*j*.
parasitic, of α-Fe_2O_3, (10) 286*e*.

Fibers, aluminum-coated silica, as reinforcement of epoxy resin, (4) 95*f*.
asbestos-glass, saturating paper containing thermoplastic resin and aluminum acid phosphate, P (1) 10*h*.
body, method to heat treat inorganic for moisture transfer and/or heat, P (4) 101*e*.
ceramic and graphite, B (5) 142*d*.
crystal, separation from boric anhydride matrix, P (3) 71*a*.
drawing device, control system for, P (4) 108*g*.
energy-conducting, P (8) 213*h*.
formation, effect on quality of slag wool, (9) 233*g*.
gamma-alumina, method to make (6) 154*j*.
glass. See also *Mineral wool*.
glass, P (11) 299*f*.
acoustical panel of, P (6) 149*j*.
antistatic sizing for, P (7) 184*e*.
of As and S for infrared transmission, P (1) 6*g*.
binder containing tall oil patch for, P (6) 149*j*.
for brush bristles, P (5) 122*f*.
in building industry, (3) 60*e*.
change in strength of aluminoborosilicate and soda lime during aging, (6) 147*c*.
coating for, P (10) 270*a*.
coating yarns of, P (11) 297*i*.
composite products and process for preparation, P (2) 33*e*.
composite supported optic strip, P (11) 298*a*.
conductive yarn from, P (3) 64*a*.
on conductor, devitrifying glass around, P (11) 298*a*.
in conveyor belt for ovens, P (8) 213*i*.
crystalline, P (8) 212*c*.
doubly clad light-conducting with outer cladding partially light absorbing, P (8) 212*e*.
effect of tensile stress on weakening during heat treatment, (2) 31*h*.
elastomeric products and process, P (8) 212*e*.
electrooptic light coupling of, P (1) 6*i*.
failure of aluminoborosilicate under combined loadings of tension and torsion, (10) 265*g*.
filter tubes, P (10) 268*b*.
in flexible article, P (9) 237*b*.
in foam core, P (11) 297*j*.
forming crystal-free, P (10) 268*j*.
in fused energy-conducting device, P (3) 64*d*.
glass currents in furnaces producing, (9) 235*a*.
heat cleaning fabrics of, P (8) 212*c*.
high strength, P (1) 6*f*.
image display device from ribbons of, P (7) 182*d*.
improved for reinforced roofing paper, (11) 296*g*.
insulating blanket from coated, P (8) 212*c*.
manufacture in East Germany, (9) 233*d*.
with metal core, P (10) 269*f*.
mats, method of applying binder to porous, P (5) 123*c*.
melting borosilicate, P (11) 297*g*.
method to align in multiple fiber bundle, P (8) 212*h*.
method and apparatus for fine, P (7) 183*h*.
method and apparatus for forming, P (2) 33*h*; P (5) 123*h*.
method and apparatus for forming by spinning fluid blast and rotor, P (5) 123*i*.
method and apparatus to make web or mat from, P (3) 63*g*.
method and apparatus to produce, P (5) 123*a*.

Fibers, glass (*continued*)
method and apparatus to produce from minerals, P (2) 34*a*.
method and apparatus to produce from thermoplastic material, P (2) 34*b*.
method to coat flexible, P (4) 97*a*.
method to condition strands of, P (11) 298*h*.
method for continuously producing mats of, P (5) 123*d*.
method to control production of continuous filaments, P (2) 34*c*.
method to curl, P (5) 123*h*.
method to improve adhesion of polymers to, P (5) 123*g*.
method to make containers from bonded, P (2) 34*g*.
method to make curly, P (9) 236*b*.
method to form, P (11) 298*j*.
method to form and wind, P (11) 298*j*.
method to make optical image transmitter from, P (7) 184*g*.
method to prepare reinforcements of, P (3) 64*j*.
method to produce, P (8) 213*c*.
method to size and epoxy resin emulsion for, P (7) 184*a*.
micro-, filters for aerosols, (5) 120*c*.
molding products reinforced with, (9) 234*d*.
optical faceplates with different numerical aperture values in two directions, P (11) 298*d*.
optical image transfer device with light absorbing elements, P (7) 182*i*.
and other thermoplastic materials, method and apparatus to make, P (7) 183*i*.
as pipe insulation, P (9) 236*h*.
possible causes of high strength of, (7) 181*c*.
process to coat with product of amino silane and copolymerizable monomer, P (8) 213*g*.
process to dull with oxalic acid, P (9) 237*b*.
process for molding into aerosol filter, P (7) 184*g*.
product of, P (8) 212*j*.
and quartz, high strength at −196° in liquid N, (8) 209*b*.
reinforced resinous body, method to form, P (7) 184*b*.
as reinforcement of low density structures, P (2) 34*h*.
relation of strength to melt treatment, (4) 95*d*.
resin binder for, P (2) 33*d*.
and resin rod, method to reinforce, P (8) 213*c*.
sized, P (1) 7*b*.
sizing for, P (9) 236*a*; P (10) 268*b*.
strand, P (11) 299*e*.
strands with different coatings, P (10) 269*f*.
strength of those coated with aluminoborosilicate glass, (10) 266*j*.
stress corrosion of E, (5) 121*g*.
stress development in plastics, (6) 148*j*.
structural panel and method to produce, P (4) 98*c*.
study of surface cracks on, (8) 211*i*.
tension development in synthetic resins reinforced by, (4) 95*d*.
yarn, bobbin for, P (9) 236*h*.
yarn, method to make, P (1) 7*b*.
high-strength, high-modulus, nonlinear behavior in three-point bending of, (4) 112*d*.
inorganic, fabrics of, (2) 54*h*.
length, apparatus to classify, P (10) 283*c*.
metal, reinforced composites, (6) 146*a*.
metal and glass, structures and electrical devices using, P (6) 159*e*.
mineral, P (9) 237*d*.
method, system, and apparatus for, P (11) 299*h*.
spinner to produce, P (5) 124*c*.
mineral, structures comprising vitrified and devitrified, P (3) 64*j*.
optical, photosensitive reader using, P (8) 213*d*.
reinforcement, for rocket nozzles, (2) 30*b*.
of sapphire cladded with quartz, energy conducting, P (4) 96*g*.
silicate, properties of Bulgarian, (5) 125*a*.
sodium silicate, continuous, P (6) 149*h*.
sodium silicate, method to coat, P (10) 268*g*.
-strengthened, materials, B (2) 55*g*.
structures from, method to make from glass and cellulosic fibers, P (4) 97*b*.
thermoplastic, apparatus for making, P (4) 96*h*.
vitreous, production of products from, P (4) 98*c*.
vitreous silica, P (10) 269*j*.
whiteware reinforced with, (10) 275*f*.

Fibrous materials. See also *Aluminum, oxide; Asbestos; Fibers; Mineral wool; Refractories*.
composite, seminar on, B (3) 88*i*.

Filaments. See also *Fibers, glass*.
attenuated mineral, P (4) 96*j*.
glass, method to continuously wrap about an internal rotor core, P (7) 183*j*.
inorganic, new lighter and stiffer than metals, (6) 171*e*.
for metallizing, P (7) 193*i*.
of pyrolytic titanium diboride, for composites, (4) 99*i*.
to semiconducting material, method to connect, P (3) 73*g*.

Films. See *Coatings*.
carbon, adsorption behavior of thin, (3) 79*f*.

Filters, for aerosols, (5) 120*c*.
aids, of perlite, P (5) 124*f*.
air, of glass fiber, P (6) 149*i*.
bag, efficiency for dust extraction, (10) 280*a*.
body, composite adsorbent, P (5) 127*e*.
for cement bag house, method to clean, P (10) 262*h*.
device, for spray-painting booth, P (2) 43*e*.

Filters (*continued*)
dipole, (9) 242*e*.
electrostatic, to extract dust in stoneware industry, (10) 275*g*.
endless web, P (10) 280*f*.
fabric, to remove dust from hot gases, (1) 17*k*.
glass, traveling wave laser amplifier with, P (2) 34*j*.
mass, in glass research, (8) 210*a*.
presses, to separate solids from liquids, P (11) 308*i*.
rotary leaf, P (11) 309*c*.
sintered, from refractory compounds, (1) 10*g*.
various, comparison for nickel-dip solutions, (8) 207*i*.
wave, with piezoelectric wafer, P (3) 74*g*.

Fine ceramics. See *Whiteware*.

Fineness, of cement, new method to determine, (6) 144*g*.
of grind, effect on color and workability of frits, (6) 145*i*.

Firebrick. See *Refractories*.

Fireclay. See also *Refractories*.
analysis, composition, and deformation at high temperatures, (3) 65*j*.
in China, mineral type and chemical composition of, (5) 138*f*.
fired properties, effect of Mn and chromite ores on, (8) 225*a*.
firing, testing degree of, (2) 37*c*.
firing, vibrated volume and Enslin value to determine degree of, (3) 66*e*.
mullite in, morphology and crystal size distribution, (2) 36*c*.
prospecting and development of, (8) 225*h*.
wall tile, with reduced-fire glaze, (6) 156*b*.

Firing. See also *Burners; Calcination; Combustion; Flames; Furnaces; Kilns; Sintering*.
atmosphere, effect on properties of chromite-magnesite refractories, (7) 186*f*.
behavior of clays, in various atmospheres, (5) 136*g*.
chamber, large, (11) 311*g*.
cycle, control in tunnel kilns, (2) 46*b*.
degree, cones to assess, (3) 77*g*.
of electrical porcelain, in tunnel kilns, (3) 71*f*.
fast, considerations in regard to vitrified bodies, (6) 156*j*.
of fireclay, testing degree of, (2) 37*c*.
of fireclay, vibrated volume and Enslin value to determine degree of, (3) 66*e*.
forum, British Pottery Managers' Association, (1) 17*f*.
glost, open placed, (7) 195*g*.
of grinding wheels, (6) 143*f*.
in heavy clay and refractories industries, 1950–1964, (5) 125*f*.
kiln car settings for, (5) 125*e*.
of kilns, above 3000°F, (7) 195*f*.
method, for tunnel kiln, P (11) 311*i*.
oil, (6) 163*j*.
oil, of Washington brick, (8) 224*d*.
rapid, determination of permissible stresses in heavy clay bodies, (11) 299*j*.
rapid, for wall tile, (9) 241*g*.
of refractory clays, as related to densification, mullite formation, and slag resistance, (2) 36*i*.
schedule, for large drain tile, (2) 35*h*.
of SiC, behavior during, (5) 125*a*.
techniques, revolution in, (3) 77*f*.
temperature, of brick, (2) 35*f*.
effects on electrical resistivity of carbon composite sintered materials, (4) 103*j*.
effects on properties of enameling steels, (9) 231*h*.
of vitreous china, once only, (1) 12*h*.

Fission products, disposal, in glass, importance of gas temperature in, (4) 94*f*.
rare gas, study of solid reaction between zinc oxide and ferric oxide by, (4) 113*j*.
release, from UC_2 particles, (3) 67*j*.

Flame photometry. See *Photometry*.

Flames. See also *Burners; Firing*.
counterflow, regenerative glass furnace with, (10) 266*c*.
in glass melting furnaces, burning process in, (1) 17*e*.
luminous, radiation from, (1) 17*f*.
oxyhydrogen, production of titania particles in, (8) 225*f*.
pattern, kiln nozzle to vary, P (2) 46*c*.
reversal, automatic control in tank furnaces, (4) 92*c*.
for spalling minerals, P (1) 18*i*.
-spraying, application technique for, (6) 145*b*.
structure, and thermoplastic working of glass, (10) 266*a*.

Flaws. See *Defects*.

Flint, (2) 47*e*.
clays, middle and late Pennsylvanian, (2) 46*i*.
distinguished from quartz, (3) 78*j*.

Flocculation, of fine particles, in nonpolar organic solvent, (6) 156*c*.
-sedimentation efficiencies, measurement of, (9) 245*c*.

Flotation. See also *Beneficiation*.
collectors in, oppositely charged mixed, B (7) 204*f*
froth, (7) 194*f*.
of glass sands, as possibility to purify, (4) 94*f*.
index for 1964, B (2) 55*d*.
of mica ore, Californian, (3) 78*e*.

Flow, convection, calculation in glass tanks, (3) 60*f*.
equation, new for pseudoplastic systems, (1) 24*i*.
of glass, modeling in relation to output, (10) 265*j*.
measurement, by infrared tracer, (9) 245*h*.

Flow (*continued*)
plastic, induced by X-ray irradiation of NaCl, (1) 24*h*.
properties, of granular dry-press powders, (8) 219*c*.
rate pattern, calculation along depth of molten glass, (8) 208*i*.
of refractory materials, at high temperatures, (2) 36*h*.
systems, analysis of carbon deposition kinetics in isothermal, (4) 109*j*.
viscous, past a flat plate with uniform injection, (7) 203*f*.
Flue gases. See *Gases*.
Fluidization, fluidizing means, pneumatic, P (3) 75*b*.
static, study of, (11) 312*b*.
Fluids. See also *Liquids*.
incompressible, viscous flow past a plate with uniform injection, (7) 203*f*.
samples, method and apparatus to sequentially analyze, P (6) 163*b*.
thixotropic and antithixotropic, rheological behavior of inelastic reversible, (3) 84*a*.
viscous non-Newtonian, mixing in packed beds, (1) 23*j*.
Fluorapatite. See *Apatite, fluor-*.
Fluorescence, Dy^{3+}, quenching by Y^{3+} in CaF_2:-Dy^{3+} lasers, (1) 24*e*.
of Mo^{3+} in glass, excitation spectrum of 1*μ*, (9) 233*a*.
Nd^{3+}, in alkali borate glasses, (6) 148*h*.
and stimulation, in Nd-doped glass, (6) 147*e*.
X-ray, analysis of glass, (2) 32*h*.
X-ray, for quantitative analysis of nonmetallics, (11) 310*g*.
Fluorides. See also *Glass*.
melts, interaction of CeO_2, Nd_2O_3, and Sm_2O_3, (10) 287*a*.
metaborate mixtures, vibrational spectrum of, (2) 53*h*.
sodium neodymium, crystal structure of hexagonal, (6) 166*b*.
in water, instrument to determine, (11) 309*h*.
of zirconium, constants of instability of complex fluorides of, (4) 110*c*.
Fluorine, based, optical glasses, (2) 32*d*.
glass, opaque and clear as coatings, (10) 264*i*.
systems. See *Systems*.
-titanium flint glass, volatilization of, (4) 96*c*.
Fluorite, or fluorite-like structures, heterotype mixed phases in predominantly oxide host lattices, (7) 200*a*.
Fluorphlogopite. See *Mica*.
Fluorspar, ores, concentrating by froth flotation, P (1) 18*h*.
-quartz, gangue contamination of, (7) 194*g*.
Fluxes, electric arc welding and method, P (1) 3*g*.
evaporation, oxide crystal growth by, (11) 318*d*.
grown ruby, properties and growth of, (9) 254*c*.
growth, and characterization of β-Ga_2O_3 single crystals, (4) 111*c*.
-line attack, causes in glass tanks, (4) 94*c*.
origin, nature, and effect in a body, (4) 102*i*.
using fluorocarbon, and submerged arc welding process, P (11) 296*d*.
Fly ash. See *Ash*.
Foam, core, with glass fibers, P (11) 297*j*.
Foaming agent, Balcrete, to produce lightweight plaster board, (11) 294*j*.
Forming, of ceramics, B (5) 142*i*.
ceramic sheets, with Fourdrinier machine, P (7) 190*i*.
by flame spraying, (5) 130*f*.
processes, effect of elastic and residual deformation on, (2) 43*d*.
Forsterite, formation, by solid state reaction, kinetics and mechanism, (3) 83*c*.
porcelain insulators, relation of microstructure to thermal expansion and electrical and mechanical properties, (8) 219*i–j*.
from Spanish serpentines, effect of mineralizers on reaction speed in calcination, (8) 225*d*.
Forums. See *Conferences*.
Fractionation. See *Separation*.
Fracture, of abrasive grains, (6) 143*i*.
brittle, of ceramics, B (5) 142*i*.
energies, measurement of brittle heterogeneous materials, (1) 20*a*.
of glass, (2) 31*c*.
in MgO, Al_2O_3, and glass, surface energy of crack, (6) 170*i*.
mechanism, in sintered tungsten-cobalt carbides, (10) 288*e*.
mirror size, relation of tempered glass strength to, (1) 5*h*.
modes, statistics of two, (1) 19*h*.
process in glass, wire explosions to investigate, (6) 149*i*.
propagation, mechanism of, (1) 23*g*.
single, distribution of fragment size in brittle solids, (3) 81*j–82c*.
sources, dislocations as, (1) 20*b*.
theory, for dispersion-strengthened glass, (3) 62*b*.
of thoria, (1) 20*b*.
toughness, designing for, (4) 114*i*.
velocity, sonic method to determine in glass, (7) 179*f*.
Freezing, of water, (8) 226*d*.
Friction, internal, of LiF at low temperatures, (10) 287*d*.
internal, in ZrO_2 containing CaO, (3) 82*i*.
peak, low-temperature internal in rutile, (9) 251*b*.
processes, shear strength of alumina abrasives to interpret, (9) 229*g*.
sliding, characteristics of deep drawing lubricants, (4) 91*d*.
Frits, cover-coat, effect of fineness of grind on color and workability of, (6) 145*i*.
enamel, new method to reclaim, (8) 207*j*.
enameling, opacification systems in powdered white, (7) 178*h*.
for fast firing of glazes, report of testing, (6) 157*c*.
titania-zirconia, (5) 119*i*.
Frost, heaving of mineral soils, physics of, B (7) 204*g*.
Frost resistance, of brick, (10) 270*d*.
of concrete, (1) 2*j*.
Fuel elements, carburization, method to prevent, P (2) 38*g*.
graphite, for high temperature reactors, (9) 238*g*.
matrix-type with graphite exterior, P (3) 70*e*.
metal-clad with copper foil interlayer, P (4) 100*h*.
method to leak test, (2) 43*j*.
nuclear, P (1) 11*c*; P (6) 154*c*; P (8) 217*a,b*; P (10) 274*c*; P (11) 302*f*.
with carbon jacket, P (1) 12*a*.
rods, closure means for those with thin sheaths, P (10) 273*c*.
with helical fissionable wire, P (11) 302*j*.
unpurged, P (11) 303*j*.
process for preparation of uranium monocarbide-plutonium monocarbide, P (5) 126*h*.
reactor, manufacture and coating with pyrolytic carbon, (9) 238*a*.
uranium dioxide, effect of internal thermal radiation on heat transfer in, (3) 67*i*.
Fuels. See also *Ash, fly; Coal; Combustion; Gases; Oils*.
cell, carbon-metal electrodes for, (7) 191*d*.
electrodes for reduction of O in, (8) 215*f*.
elements, method of making, P (2) 38*d*.
cost, in glass industry, (2) 31*i*.
experimental, performance for gas-cooled reactor, (3) 68*d*.
-gas, comprehensive analysis by gas chromatography, (4) 107*c*.
irradiated, α-autoradiographic method to examine, (3) 65*f*.
matrixes, molten oxides as possible, (6) 153*e*.
nuclear, P (4) 101*b*.
method to compact, P (1) 11*j*.
method to process, P (2) 38*j*.
particles, irradiation studies of coated, (3) 68*c*.
production of monocarbides from higher carbides, P (11) 302*g*.
production of spheroids from powder, P (4) 99*j*.
uranium-nitrogen, (9) 239*g*.
from UO_2-ZrO-CaO, (7) 188*a*.
uranium nitride-iron cermets for, P (5) 126*b*.
oil, aspirating spray nozzle for, P (11) 311*j*.
oil, and oil burning, (2) 46*e*.
particles, coated with pyrolytic carbon and silicon carbide, P (7) 189*b*.
coating nuclear with carbon, (9) 237*j*.
duplex carbon-coated, (3) 66*d*.
fission-gas release from pyrolytic-carbon-coated during irradiation, (6) 152*d*.
preparation for electron microscopy by replica method, (11) 310*f*.
properties of coated nuclear, (2) 36*e*.
spherical pyrolytic-carbon-coated UC_2 and $ThUC_2$, (3) 66*i*.
peat and coal, in Swedish glass industry up to 1913, (4) 93*j*.
PuO_2-UO_2, fabrication processes, (6) 152*c*.
and power, in glass industry, report on, (11) 297*e*.
problems, for Swedish glass industry up to 1913, (1) 17*g*.
pyrolytic-carbon coated carbide, (3) 66*a*.
reactor, dissolution by aqueous processes, (9) 238*c*.
reactor, UN as, (3) 69*d*.
structures, high-temperature nuclear and their production, P (1) 11*f*.
swarf, conversion of irradiated for long-term storage, (1) 8*i*.
in Swedish glass industry, (8) 209*i*.
from ThO_2-UO_2, (7) 187*j*.
trends in, (3) 77*f*.
U, Pu enriched for reactors, P (8) 218*b*.
UO_2, improvements in fabrication of, (6) 154*b*.
uranium mononitride, and method of making, P (1) 12*e*.
Fuller's earth, resources, in Kentucky, (7) 196*i*.
Fungus, growth on glasses, (5) 120*g*.
Furnaces. See also *Burners; Fuels; Glassmaking apparatus and equipment; Kilns; Ovens; Refractories*.
arc, production of refractory siliceous body for, P (7) 189*f*.
arc, surface heating rates with, (9) 246*f*.
atmospheres. See *Atmospheres*.
blast-, effect of diatomaceous earth on cement for, (3) 59*b*.
slag-metal systems, reduction of silica in, (1) 9*h*.
stockline, wear-resistant element, P (7) 190*a*.
workability of tar-bonded taphole materials, (9) 238*b*.
container glass, tracer studies in, (2) 32*f*.
continuous, for enameling, (11) 295*j*.
continuous, heating device, P (9) 246*h*.
for continuous drawing of quartz tubing, P (11) 298*d*.
copper reverberatory, erosion mechanism of basic brick in, (6) 152*g*.
core type induction, bushing insulator for, P (3) 70*c*.
crucible-free zone melting, for semiconductor material, P (11) 305*j*.
for crystal growing, means to adjust crucible in, P (5) 132*h*.
electric, P (2) 37*d*.
Furnaces, electric (*continued*)
arc, mechanism of wear of tar-bonded dolomite in, (7) 187*a*.
condition of refractories used in, (7) 187*f*.
developments in basic gunning, (9) 239*b*.
fused cast basic refractories in, (7) 186*g*.
glass currents in fiber producing, (9) 235*a*.
investigation of silica for roofs of, (6) 152*h*.
measuring physicochemical quantities for modeling glass melting in, (2) 32*b*.
to operate in various atmospheres, (10) 282*a*.
for softening apparatus glass, (7) 180*f*.
types for glass melting, (7) 180*f*.
enameling, luminous wall type, (3) 59*j*.
glass, construction with an eduction tunnel provided with a vault, P (8) 212*a*.
device for protection of barriers in, P (4) 96*d*.
electric, P (4) 96*f*.
fining means for, P (6) 149*j*.
heat exchange in zonal, (9) 233*f*.
heating apparatus for tempering lehr, P (1) 6*e*.
heating with natural gas, (10) 265*f*.
with means to agitate molten glass, P (10) 268*c*.
method of feeding to and melting in, P (6) 150*a*.
method to treat bottom, P (7) 183*d*.
with muffle lip-tile, P (6) 150*a*.
problems with refractories, (1) 4*g*.
and process for melting and working, P (3) 64*f*.
process to prevent scale in, P (5) 124*d*.
process to treat roof and walls, P (6) 151*a*.
regenerative with counterflow flame, (10) 266*c*.
with refining chamber, P (9) 236*a*.
refractory development in, (2) 36*h*.
for sheet, P (9) 235*d*.
small with low fuel consumption for melting special glasses, (8) 211*a*.
stream heating in continuous ribbon, P (8) 212*b*.
use of flue gas heat in, (10) 264*g*.
viscometer for, P (6) 151*b*.
zone type, (9) 235*j*.
glass bending, with glass actuated control for conveyor, P (3) 63*g*.
glass melting, behavior of magnesite in regenerative checkerwork of, (7) 185*f*.
behavior of siliceous plastic refractory in hot repair of, (2) 36*d*.
with bridge wall, P (6) 150*a*.
bubbler for, P (1) 6*d*.
burning process in flames in, (1) 17*e*.
design of, (6) 147*d*; (8) 209*c*.
with divided zones, (10) 265*h*.
fused quartz bricks in, (4) 99*c*.
and method of working, P (10) 267*a*.
port and checker details, (11) 296*e*.
regulated flow, P (6) 151*b*.
static characteristics in temperature control of combustion chamber in, (8) 211*c*.
with submerged gas burners, P (7) 183*e*.
thermal insulation of, (9) 246*h-g*.
trends in development of charging systems for, (8) 211*b*.
glass tank, P (10) 268*j*.
automatic control of flame reversal in, (4) 92*c*.
automation of, (7) 179*g*.
bubble movement in those for melting sheet, (6) 148*b*.
calculating cooling basins of, (4) 92*c*.
calculation of convective flow in, (3) 60*f*.
currents in a problem of equilibrium, (9) 233*b*.
development of, (4) 92*g*.
economy of service campaigns, (3) 60*j*.
electrically heated, P (1) 6*h*.
evaporative cooling of walls, (4) 93*f*.
fundamentals of temperature control in small container, (7) 180*b*.
gas-electric heating for container production, (9) 235*h*.
improving burner design for, (9) 233*f*.
intensifying work with electric booster heating, (4) 94*a*.
kinetics of mixing in continuous, (5) 121*b*.
linings for, (6) 151*h*.
measurement and control procedures for, (7) 180*i*.
measurement of homogeneity of glass to characterize output of, (3) 61*b*.
for melting colored and coating, (9) 235*a*.
melting of glass ZS-4 in, (5) 121*c*.
melting lead crystal in, (10) 265*h*.
operation of, (8) 211*c*.
probe to control level in, (7) 180*c*.
simplified means to calculate heat exchange in, (4) 95*f*.
for sheet, composition of bubbles in different zones of, (4) 92*h*.
study of upward drilling as cause of corrosion, (9) 234*d*.
with submerged heating and cooling, P (2) 33*a*.
surface effects on hot face of silica crown, (10) 265*b*.
temperature conditions cause change in composition of bubbles in sheet glass, (1) 3*j*.
upward drilling and flux-line attack in, (4) 94*e*.
without conditioning tank, (10) 265*a*.
for gravity bending glass sheets, P (7) 183*h*.
gravity flow, (5) 132*d*.
heating, rate of temperature rise after repair, (7) 187*b*.
high emissivity coatings for, (9) 232*a*.
high frequency combustion, to determine carbon in products, (4) 107*h*.
high temperature, P (1) 17*i*; P (5) 132*e*.
electrode holder for, P (7) 195*j*.

Furnaces, high temperature (*continued*)
method to make shielding for, P (5) 132*h*.
remotely operated, (8) 224*i*.
horizontal, for growing fluoride crystals, P (11) 305*j*.
hot-blast Koppers, with silica lining, (7) 186*h*.
industrial, gaseous and liquid burner for, P (6) 164*a*.
making regenerators for, P (6) 155*g*.
pulsed oil feeding system for, P (2) 46*f*.
LD converter, refractories for, (8) 216*f*.
linings. See also *Refractories*.
metallurgical, linings for, P (3) 70*f*.
or metallurgical vessels, refractory for, P (10) 282*e*.
new or repaired, records of temperature rise after drying out, (3) 68*i*.
open hearth, comparison between U. S. periclase and Japanese seawater magnesite in basic brick for roofs of, (3) 65*i*.
effect of factors on unit refractory consumption for, (8) 215*d*.
gunned refractories to lengthen life, (7) 186*i*.
improvement of brick shape for, (8) 215*b*.
lengthening roof life by gunned refractories, (7) 186*i*.
Mg-Cr in front wall of, (7) 187*e*.
method to water-cool front and rear walls, (3) 65*g*.
results of using cased refractories made of waste basic in hearth of, (7) 187*e*.
spinel-type checker built in, (7) 187*i*.
operation, method of, P (1) 17*j*.
performance, assessment, (2) 46*a*.
pot, fundamentals of control, (7) 180*a*.
heat exchange process in bottom of, (4) 93*d*.
intensification of glass melting in, (4) 93*j*.
with Pt liner, P (7) 183*c*.
regulation of, (7) 180*j*.
process, (7) 195*h*.
to produce oriented graphite, P (4) 108*d*.
pusher-type, testing method for refractories in, (9) 239*i*.
radiant tube, for water tanks, (6) 146*d*.
recuperative tank, unique, (4) 93*f*.
refractories for. See *Refractories*.
regenerator, method to lay checker brick in and prolonging life of checker, (10) 271*j*.
reheating, electrocast refractories in, (11) 301*f*.
resistance, P (1) 18*a*.
roofs. See *Refractories*.
side-entry fluid fuel injection system for, P (1) 18*a*.
steelmaking, P (11) 303*j*.
tank, cooling section, effect of dimensions on readiness of glass to be handled, (1) 4*c*.
cooling section, effect of dimensions on readiness of glass to be handled, (1) 4*c*.
service of high alumina refractories in, (10) 266*g*.
for thermocouple calibrations, (9) 245*h*.
controlling cooling in, P (10) 282*d*.
Fuses, with arc extinguishing material, P (4) 104*i*.
precision electrical, P (11) 307*f*.
Fusion, diagram, in system $GaCl_3$-AlCl, (1) 21*d*.
of system $InCl_3$-TlCl, (1) 21*d*.
of system of pyrophosphates of Li and K and NaF, (1) 21*e*.
diagrams, in systems $LiClO_4$-$Ca(ClO_4)_2$ and $NaClO_4$-$Ca(ClO_4)_2$, (1) 21*f*.
flame, synthesis of mullite by, (4) 99*f*.
in system Li_2F_2-BaF_2-Na_2Cl_2, (3) 82*d*.

Gadolinium, $Gd_3Ga_5(GaO_4)_3$, *a-c* exchange in garnets of, (11) 313*b*.
Gd^{3+} to Tb^{3+}, Tb^{3+} fluorescence and nonradiative energy transfer in borate glass, (6) 149*f*.
iron garnet, ferroacoustic resonance and acoustical birefringence in, (7) 199*d*.
molybdate, unit cell and space group of, (8) 228*a*.
oxide, systems. See *Systems*.
oxides, cathodoluminescence of Eu-activated, (8) 219*g*.
oxides, toxic in dust form, (2) 55*a*.
Gages, assembly, nude ion, P (11) 307*e*.
for bottles, P (11) 297*h*.
ion, calibration using a leak detector, (10) 281*c*.
ionization, in ultrahigh vacuum, residual argon partial pressure changes due to, (10) 281*a*.
to measure level of liquids or solids, (5) 131*j*.
periscope-type strain, to measure creep in immersed specimens, (6) 162*a*.
strain, P (8) 222*d*.
strain, that can be encapsulated with flame-sprayed coating, (3) 30*b*.
Gallium, Al, and In, analysis of mixtures by solvent extraction and gas chromatography, (2) 43*i*.
arsenide, body containing Cu, P (9) 243*f*.
epitaxial technology for integrated circuits, (7) 191*f*.
evidence for avalanche injection laser in *p*-type, (10) 286*a*.
films on NaCl substrates, effect of gaseous environment on structure of sputtered, (9) 249*d*.
identification of laser transitions in electron-beam-pumped, (10), 286*g*.
interaction with Ge, (11) 317*h*.
intrinsic and extrinsic photomixing in semi-insulating, (7) 200*c*.
laser-action threshold in electron-beam excited, (10) 287*e*.
method to produce stable and semiconductor diodes from, P (7) 193*h*.
production of monocrystals of, B (11) 320*d*.
rods, crucible-free production from alkyl galliums and arsenic compounds, P (4) 105*e*.
temperature dependence of iron acceptor level in, (10) 291*i*.

Gallium (*continued*)
chloride, interaction with chlorides of Na, Cu(I), and Ag, (11) 317*g*.
$GaAs_{1-x}P_x$ alloys, electron mobility in, (10) 285*h*.
$GaAs_xP_{1-x}$, microwave oscillations in alloys of, (1) 23*i*.
melting, in arsenic, P (9) 244*e*.
oxide, *β*-, flux growth and characterization of single crystal, (4) 111*c*.
phosphide, electroluminescence in single crystals of, (10) 285*h*.
phosphide, electroluminescence near band gap in, (1) 13*h*.
trichloride, systems. See *Systems*.
Garnets, *a-c* exchange in, (11) 313*b*.
-biotite-sillimanite gneisses, from Quebec, analyses of equilibrium in, (7) 197*d*.
calcium vanadium bismuth iron, *L*-band properties of, (9) 251*a*.
calcium vanadium-substituted, magnetic and microwave properties of, (9) 251*d*.
composition, small adjustments in, (1) 13*g*.
dysprosium aluminum, thermal properties near Néel temperature, (2) 53*c*.
ferromagnetic, magnetic behavior of substituted, (9) 251*c*.
fine-grain high-power, microwave characteristics of, (9) 252*e*.
gadolinium iron, ferroacoustic resonance and acoustical birefringence in, (7) 199*d*.
mixed rare earth iron, magnetic moments of, (10) 277*d*.
polycrystalline, dynamic squareness of, (2) 49*b*.
polycrystalline $Y_3Fe_{5-n}Al_{1-n}O_{12}$, control of magnetic properties of, (11) 314*e*.
rare earth Al, growth by floating zone technique, (7) 191*h*.
rare-earth iron, optical transparency of, (9) 252*h*.
structure, light absorption of Cr incorporated into, (3) 80*e*.
refinement by neutron diffraction, B (2) 55*i*.
vanadates $A_3B_2V_3O_{12}$ with, (1) 25*j*.
vanadium-containing, P (10) 279*i*.
Y Al, impurity distributions in single crystal, (3) 84*c*.
laser, for optical second-harmonic generation, (10) 285*h*.
low-temperature thermal expansion of, (9) 251*b*.
oscillations from ions in, (10) 284*a*.
yttrium-gallium, Czochralski growth, (2) 49*e*.
YI, CW-pumped and amplification of elastic waves in, (6) 166*c*.
factors effecting domain configurations in, (5) 136*j*.
growth and properties of films, (3) 82*e*.
measurement of third-order elastic moduli of, (9) 252*c*.
in near infrared, optical transparency of, (1) 23*g*.
spin-wave excitation of magnetoacoustic modes and bearing of modes in, (10) 290*e*.
sublattice contributions to infrared rotary dispersion in, (10) 291*c*.
vapor growth of, (6) 171*a*.
Gases, analyzer, electrochemical, P (3) 77*d*.
from brickmaking shales, analysis of, (10) 270*c*.
cement kiln exit, apparatus to analyze, P (2) 45*h*.
combustion, glass fabric to purify in cement industry, (11) 296*f*.
evolution, during reaction of phosphate enamels with Al, (2) 30*e*.
fission-, in-pile release from UO_2, (3) 67*j*.
release from pyrolytic-carbon-coated fuel during irradiation, (6) 152*d*.
retention of UO_2 produced by different methods, (3) 67*i*.
flow, principles through porous bodies, (5) 140*c*.
flue, analysis applied to glass melting and conditioning, (6) 147*e*.
in a fluid, apparatus to electrolytically determine, P (9) 246*d*.
in fused silica, solubility of, (10) 265*j*.
hydrogen in, monitor for, (9) 245*b*.
jets, to change temperature of objects, P (10) 282*b*.
liquefied, heat balance calculations for tunnel kiln using, (10) 282*b*.
mechanical properties of, B (5) 142*h*.
mixer for, P (6) 163*j*.
mixing, P (5) 132*d*.
natural, in ceramic industry, (8) 224*c*.
natural, heating of glass furnaces with, (10) 265*f*.
noble, density of liquid iron oxide in, (5) 134*i*.
O in, apparatus to analyze for, P (7) 195*a*.
O in, method and means to analyze, P (3) 77*b*.
phase adsorption, BET apparatus to determine for minerals, (5) 136*d*.
producing agents, in production of lightweight aggregates, (9) 237*f*.
release phenomena, and ion trapping, (4) 112*a*.
removal, procedures for glass ultrahigh-vacuum systems, (10) 281*i*.
residual, system for analysis before, during, and after thin film deposition, (9) 246*e*.
temperature, measurement and control in the FINGAL process, (4) 94*f*.
thermal release, of those trapped in sites with a continuum of activation energies, (4) 113*j*.
thermometer, with constant bulb temperature, (4) 107*d*.
tracer, to test for leaks, (2) 43*j*.
Gels. See *Colloids; Silicon dioxide*.
Generators, thermoelectric, P (5) 130*c*.
Geochemistry, evolution, of clayey and carbonate sediments of early paleozoic of central Bohemia (11) 317*d*.
Geology, of magnesite belt in Washington, (9) 247*e*.

Geology (*continued*)
physical constants for calculations for, B (10) 292*g*.
Geophysics, physical constants for calculations for, B (10) 292*g*.
Germanates, of type Al_2BaO_4, crystallography of, (6) 166*j*.
Germania. See *Germanium, dioxide*.
Germanides, Mo_5Ge and Cr_5Ge, preparation of, (8) 220*e*.
Germanium, As and P, simultaneous determination and separation of Si and As by solvent extraction, (9) 246*a*.
dendrites, crystallization of film between parallel growing, B (11) 320*a*.
systems. See *Systems*.
Ge^{4+}, site preference in magnetic spinels, (5) 140*h*.
$GeNi_2O_4$, magnetic structure and properties of, B (2) 55*j*.
in high electric fields, effect of surface finish on electrical conductivity, (3) 72*d*.
interactions, with arsenides of Ga and In, (11) 317*h*.
selenide, and related binary IV/VI compounds, structure of, (1) 25*i*.
selenide, semiconducting properties of, (4) 104*e*.
and Si, electrical conductivity of *n*-type in crossed electrical fields, (11) 316*i*.
solid selenides and tellurides of, determination of saturation pressure of vapors of, (4) 110*f*.
third-order elastic constants of, (3) 87*i*.
wafer, rapid etching process for flat-bottomed pit in, P (10) 279*a*.
Getters, alkaline earth metal, application of, P (10) 278*e*.
cryo-, pump, performance of simple, (2) 44*g*.
gettering processes, (9) 245*i*.
Glass. See also *Art and artware; Furnaces; Glass industry; Glassmaking apparatus and equipment*.
(2) 31*d*.
advances in, (6) 146*j*.
after atmospheric exposure, evolution of water vapor from, (9) 233*i*.
alkali, metal titanium phosphate, P (4) 96*e*.
phosphate, thermal expansion of, (6) 149*i*.
silicate, Cr^{3+}-Cr^{6+} equilibrium in, (3) 60*g*.
silicate, ferrous-ferric equilibrium in, (3) 61*e*.
alkali borate, and alkali silicate, cerous-ceric equilibrium in, (3) 60*h*.
manganous-manganic equilibrium in, (11) 296*h*.
thermal and mechanical investigations of, (4) 95*d*.
alkaline-earth silicoaluminate, controlled crystallization of, (11) 296*i*.
AlF_3-PbO-B_2O_3 and B-F-O, effect of fluorine ions on physicochemical properties of vitreous state in, (10) 286*h*.
amber, C-S, (3) 60*g*.
analysis, of Al_2O_3, Fe_2O_3, MgO, and CaO in by photoelectric emission spectral analysis, (3) 62*b*.
complexometric, (10) 264*d*.
for low sulfur contents, (3) 60*h*.
of water content, (3) 60*i*.
X-ray fluorescence methods, (2) 32*h*.
annealing, control for sheets, (4) 92*a*.
antimony, vitreous range in three-component system based on Sb_2O_3 and physicochemical properties of, (7) 182*c*.
apparatus, electric furnace for softening, (7) 180*f*.
area, measuring device for, P (10) 267*d*.
arsenic borate, gamma-induced absorption and structural studies of, (9) 233*e*.
arsenic-sulfur, infrared absorption band in, (7) 180*d*.
arsenic-sulfur, relation of composition and density of, (7) 181*e*.
article, flux free bonded, P (7) 182*j*.
lid making method, P (10) 269*c*.
means to strengthen and produce from soda glass, P (2) 34*i*.
method to produce heterogeneously distributed stresses, P (9) 236*d*.
attenuated, surface treatment of, P (5) 124*c*.
back painting of, (9) 229*j*.
backup dies, for multigun welders, (11) 295*g*.
banding, for motor coil, (2) 31*e*.
bangles, production of red without selenium, (2) 32*e*.
batch, comparison of ancient Russian with others, (4) 89*j*.
granulation of that containing coarse sand, (4) 93*d*.
improved method to control homogeneity of, (4) 93*e*.
and method, P (5) 122*h*.
method to treat, P (3) 65*b*.
mixing, (3) 62*h*.
role of sulfate in melting and fining of, (6) 148*g*.
batching, analysis of, (9) 234*b*.
beads, to blast finish panels, (6) 143*g*.
coated to polish metal, P (4) 98*c*.
method to assemble on wire, P (11) 298*h*.
blocks, method to make hollow with built-in exhaust ducts, P (10) 268*i*.
bodies, high strength devitrified, P (11) 299*a*.
bodies, and treatment, P (11) 298*e*.
body, with crystalline surface layer, P (11) 298*f*.
body, with semicrystalline surface layer, P (8) 212*f*.
bonded mica, constitution and properties, (2) 40*f*.
new electronic composite, (6) 158*i*.
uses expanded, (8) 220*a*.
borate, for lasers, P (8) 212*a*.
Tb^{3+} fluorescence and nonradiative energy transfer from Gd^{3+} to Tb^{3+} in, (6) 149*f*.

Glass, borate (*continued*)
time and temperature effects on silica distribution in, (3) 62*b*.
B_2O_3, determined with neutrons in, (3) 76*i*.
effect of OH content on acoustic spectra of, (4) 93*b*.
GeO_2, properties of, (6) 148*e*.
borosilicate, low-lead in glazes for artware, (11) 304*b*.
orientation effect and birefringence, (4) 94*c*.
studies in annealing of, (8) 209*j*.
bottles, aluminous alkaline materials to produce dark green, (9) 235*f*.
devitrification of, (9) 233*d*.
effect of surface damage on internal pressure resistance of, (4) 93*j*.
handling costs, (5) 120*h*.
internal pressure resistance of those subject to stress for long and short times, (4) 94*b*.
breaks. See *Glass, fractures*.
bubble formation, effect of atmospheric oxygen in galvanic cell platinum/glass-refractory material/platinum, (1) 4*c*.
bubbles in, electrochemical process to form, (11) 296*e*.
Buddhas, (3) 57*j*.
building blocks, strength as affected by material and form, (3) 62*g*.
building elements, process and equipment for production of, P (5) 124*a*.
bulb, capsulated, P (11) 305*b*.
method, P (10) 269*d*.
method to make from tube, P (1) 7*b*.
photoflash and method, P (2) 34*d*.
calcium aluminoborate and aluminosilicate, electrical conduction and O diffusion in, (3) 60*i*.
calcium boroaluminate, nuclear magnetic resonance studies of, (9) 234*e*.
$CaO–B_2O_3–Al_2O_3$ and $CaO–B_2O_3–Al_2O_3–SiO_2$, chemical durability of, (3) 60*j*.
capsules, for buoyancy of deep submergence vehicles, (2) 54*i*.
carbon dioxide solubility in, (9) 232*j*.
caustic soda in, (2) 31*f*.
-ceramic, article from, P (7) 184*f*.
bodies, P (8) 212*g*.
body and method of making, P (5) 124*a*.
electron microscopy of fractured, (2) 31*a*.
materials, developments in Europe, (7) 181*a*.
and method of making, P (4) 96*b*.
method of making article from, P (10) 269*h*.
microscopically crystallized, stabilized products from, P (4) 98*a*.
microscopy of production, (2) 31*a*.
nucleation of catalyst and origin of crystals in, (10) 265*a*.
phase separation and nucleation in preparation of, (4) 94*d*.
products of and process for, P (5) 124*c*.
semicrystalline and method, P (4) 98*d*.
in system $ZnO–Al_2O_3–SiO_2$, (8) 211*e*.
and ceramics, joining to metals, (2) 40*i*.
$CeO–Al_2O_3–P_2O_5$, density and refractive index, (10) 266*f*.
chalcogenide, forming regions, variations in properties, infrared absorption by oxide impurities, and structure, (11) 296*h*.
changes with time, (6) 147*i*.
chemical apparatus, progress in, (5) 131*f*.
chemical durability, (7) 179*g*.
bibliography of, B (3) 88*h*.
method to improve, P (7) 184*h*.
chromatographic capillary columns, method and means to produce, P (6) 150*b*.
Cr in, physical and chemical estimation of trivalent and hexavalent, (3) 61*i*.
cloth, P (10) 268*a*.
cloth, method to pigment with silanes, P (6) 150*c*.
coated apparatus, apparatus to attach parts to, P (9) 232*e*.
coatings, application to inside of steel pipes, (1) 3*e*.
applied from transfer tapes, (2) 30*a*.
of sensitized metal oxide, P (7) 184*c*.
coatings on, metal oxide, resistance to ionizing radiation, (10) 266*f*.
Co, in measurement of electron irradiation, (10) 284*j*.
colloidal macromolecular phenomena, (5) 120*d*.
color, produced by Cu_2O, (3) 60*e*.
colored, by CeO_2 and TiO_2, (3) 62*c*.
colored and colorless, alternate melting without stopping furnace, (9) 232*h*.
colored with rare-earth elements, industrial melting of, (4) 93*e*.
coloring, rare earths for, (9) 235*h*.
component, Brazilian sodium carbonate as, (6) 146*j*.
compositions, P (2) 33*j*; P (8) 212*h*.
change during continuous flow, (1) 3*j*.
control by density measurements, (8) 209*a*.
control by optical properties, (10) 264*d*.
effect on corrosion of pot clays, (8) 209*e*.
methods to convert binary and ternary from wt% to mole %, (3) 61*g*.
phototropic, P (8) 213*d*.
resistant to glucose and ascorbic acid, (6) 147*e*.
compressibility, effect of porosity on, (1) 4*b*.
constitution, of mixed-alkali phosphate and lithium-cesium phosphate, (7) 179*i*.
containers, banded constructions, P (6) 149*d*.
determining cost of each, (4) 92*d*.
effect of water content, (2) 32*e*.
inspecting for horizontal checks with light beam, P (7) 183*j*.
inspecting rims of open mouth, P (10) 268*h*.
light to detect crizzles, P (7) 182*f*.

Glass, containers (*continued*)
with lug finishes, calipering method to inspect, P (7) 183*j*.
method to impart thermal conductivity to, P (3) 63*c*.
method to measure shape by cathode ray tube, P (7) 183*i*.
steam cure of siloxane-coated, (10) 266*h*.
containing GeS, P (2) 33*a*.
continuously rolled, complex studies of, (11) 296*f*.
cords, analysis of, (7) 179*f*.
cords, problems of surface, (2) 31*e*.
corrosion, mechanism of, (2) 32*a*.
cracking, caused by underwater spark, (6) 147*i*.
creep, under high strain, (2) 31*b*.
crystal, with low PbO content, (7) 179*j*.
crystalline phase in, orgiin and development of, (6) 148*a*.
crystallization. See *Crystallization*.
crystallized, electrical properties in system $MgO–Al_2O_3–SiO_2–TiO_2$, (2) 31*j*.
cylinders for syringes, quality control of, (11) 297*b*.
decoration. See *Decoration*.
defects, crystal optical method to determine, (4) 92*b*.
detection by crystal-optical method, (6) 147*d*.
development of terminology and classification of, (8) 209*d*.
due to batch segregation, (4) 93*a*.
laser microprobe analysis of, (4) 94*e*.
deformation, reasons during crystallization, (10) 266*b*.
dehydration, kinetics investigated by thermography, (1) 4*a*.
densification, at high pressure, (2) 31*e*.
diamagnetic, Faraday effect in, (9) 233*b*.
dielectric, synthesis of $SiO_2–Al_2O_3–CaO–MgO$ with addition of BaO, TiO_2, ZnO, (5) 121*i*.
diffusion of hydrogen in, (5) 120*e*.
dissolution kinetics, in systems where diffusion and free convection are rate controlling, (6) 147*f*.
double-glazed units. See *Glass, glazing units*.
drawn, method to determine distortions of surfaces, (9) 234*a*.
drinking, with self-contained light, P (2) 33*g*.
durability of, (3) 60*j*.
durability test, (3) 61*j*.
elastic properties, effect of heat treatment on, (6) 147*j*.
electrets, (7) 180*b*.
electric melting and boosting, (4) 94*j*.
electrodes. See *Electrodes*.
electronic, change of dielectric properties in wide range of temperatures and frequencies, (6) 148*f*.
in electronics, symposium on, (11) 297*e*.
enamel, surface tension measurement of, (1) 3*f*.
encased metal wire, method to prepare, P (2) 34*i*.
evolution, in fused cast refractories at high temperature, (4) 93*b*.
excitation spectrum of 1μ fluorescence of Mo^{3+} in, (9) 233*a*.
fabric, novel, P (10) 269*e*.
fabric, to purify combustion gases in cement industry, (11) 296*f*.
facing materials, (9) 233*a*.
faceplate, for TV, P (10) 269*c*.
fibers. See *Fibers, glass*.
film, forming of, (9) 233*d*.
and glass plastics from it, effect of chemical treatment of surface on properties of, (9) 233*f*.
method to determine breaking and elastic characteristics of, (9) 233*i*.
space-charge polarization in, (9) 234*g*.
films on, transparent electrical conducting, (1) 5*b*.
filters. See *Filters*.
fining, best cycles, (10) 266*a*.
kinetics and mechanisms of, (9) 233*i*.
study of bubble growth conditions in, (7) 181*f*.
finishing, by impact lapping at ultrasonic frequency, (4) 93*c*.
fission products in, importance of gas temperature during disposal in, (4) 94*f*.
flakes, on reflecting material, P (8) 213*i*.
flat. See also *Glass: plate, sheet, window*.
flat, manufacture of, P (2) 33*f*; P (3) 63*c–e*.
method to make, P (10) 268*h*.
method to manufacture, P (6) 150*b*.
"pencil edging," (2) 32*e*.
process for manufacture, P (2) 34*g*.
production of double glazed welded, P (10) 269*a*.
flaws, method and apparatus to detect, P (7) 182*j*.
fluoberyllate, kinetics of dissolution of some in water, (6) 148*d*.
fluorescent U, (6) 147*h*.
fluorine, calculations for opaque and clear coatings, (10) 264*i*.
foam, effect of crystallization on, (4) 93*a*.
pellets, method of making, P (1) 6*a*.
radiation resistance of, (7) 181*d*.
relation between temperature and specific resistance, (11) 297*j*.
formation, cooperative phenomena with special reference to SiO_2, (5) 120*f*.
regions in systems $R_2O–PbO(Bi_2O_3)–P_2O_5$, (8) 210*a*.
in system $CeO_2–Al_2O_3–P_2O_5$, study of fields of, (6) 149*b*.
in system $Li_2O–SiO_2$, (4) 93*c*.
fracture, (2) 31*c*.
process in, wire explosions to investigate, (6) 149*i*.
proposed theory for dispersion-strengthened, (3) 62*b*
strength, (8) 209*h*.

Glass, fracture (*continued*)
velocity, sonic method to determine, (7) 179*f*.
-frit, properties of suspensions of, (6) 146*d*.
fungus growth on, (5) 120*g*.
fusible, significance of polarization properties of ions for developing, (4) 95*e*.
and glassware, export performance, prospects, and problems, (2) 31*c*.
glazing unit, laminated, P (4) 97*a*.
glazing units, method to produce, P (3) 64*a*.
grinding. See *Grinding*.
ground and polished, strength of, (10) 266*j*.
ground surface, in apparatus for film-type distillation, P (7) 182*g*.
hardness, in vacuum, (6) 148*i*.
heat absorbing, P (3) 63*e*.
heat and infrared responsive, and method of making, P (8) 212*e*.
heat treating of preformed, P (7) 184*b*.
heterogeneity, comment on "Assessment of, (9) 233*a*.
heterogeneity, measurement with standard spectrophotometers, (1) 4*f*.
high alkali, trivalent cobalt in, (2) 32*f*.
high expansion, for sealing to metals, P (6) 150*c*.
high-strength, obtaining, (4) 94*b*.
high temperature resistant, and method of producing, P (5) 123*b*.
hollow articles, method to apply protective silicone tape covering layer to, P (4) 97*j*.
homogeneity, apparatus to control, (9) 232*i*.
method to determine, (8) 209*g*.
new method to determine and control, (7) 181*b*.
honeycomb, P (11) 299*c*.
hot, symposium on contact with metal, B (2) 55*c*.
impregnated, porous photochromic, P (11) 298*j*.
inclusions, identified by crystal-optical method, (6) 147*d*.
industrial, electrical conductivity in molten state, (9) 233*i*.
infrared absorption spectra of Ce^{3+} ions in, (3) 61*i*.
infrared band in, (7) 180*f*.
infared optical constants, (3) 61*j*.
inhomogeneity in, analyzer to identify, (9) 235*g*.
inorganic, strength calculated from acoustic-dilatometric measurements, (6) 147*a*.
insulated microwire, production directly from liquid metal, P (9) 232*f*.
insulating container, and method of making, P (5) 123*c*.
insulating electroconducting films on, (9) 233*f*.
insulators, power line, production and control of hardened, (7) 181*d*.
interface, processes between refractory material and, (5) 125*h*.
ion bombardment of, (9) 233*g*.
ion sensitive, P (5) 123*e*.
ions in, function of mobile, (7) 180*j*.
iron in, effect of decolorizers on oxidation of, (4) 92*j*.
irradiated, modifications in, (5) 121*e*.
irradiated, by ultraviolet, X and γ rays, thermal glow of, (7) 181*j*.
laboratory ware, method to strengthen, P (9) 236*g*.
laminated, P (7) 183*c*, 184*h*; P (9) 236*e*.
laminated safety, P (11) 298*c*.
lamp, change in alkali content during electric melting of, (4) 95*b*.
with lanthanide activators, luminescence of, (6) 148*f*.
laser oscillations and self *Q*-switching in, (7) 180*g*.
laser rods, damage thresholds for, (8) 209*j*.
laser rods, thermal effects in optically pumped, (2) 53*e*.
lasers, neodymium barium crown, (5) 139*d*.
lead, skin on silica, (1) 4*d*.
lead borate, microseparation in, (3) 61*e*.
lead oxide-silica, nature of molten glasses in, (9) 234*e*.
lenses. See *Glass, optical*.
level, measurement with electrodes, (2) 31*c*.
-lined containers, impact-resistant, P (3) 63*b*.
liquid, measurement of electrical resistance of, (8) 210*a*.
lithium, crystallization of, (10) 264*h*.
$Li_2O–MgO–SiO_2$, effect of Pt catalyst on crystallization of, (7) 179*g*.
$LiO_2–Na_2O–Al_2O_3–SiO_2$, determination of structural anomalies in, (6) 148*j*.
lithium silicate, crystallization of, (7) 181*d*.
lithium silicate, properties and application, B (4) 115*i*.
luminaire, P (11) 298*c*.
luminaire, design, P (7) 183*d*.
luminescent material, of Cd, B, and Mn oxides, P (5) 123*f*.
magnetic resonance in, (4) 94*e*.
-making processes, potassium compounds as radioactive indicator to study, (4) 94*h*.
manmade, means to determine age, (4) 89*h*.
Mn in, absorption and fluorescence spectra of, (3) 60*d*.
manufacture, quartz sands from Bulgaria for, (2) 32*g*.
matrix, electrooptic effect of ferroelectric microcrystals in, (10) 285*j*.
melt, determination of bubble movement rate in, (4) 93*g*.
vapor pressure and decomposition pressure of alkali compounds in, (3) 62*b*.
melting, ammonium sulfate to intensify, (10) 267*d*.
and conditioning, flue gas analysis applied to, (6) 147*e*.
convective flow in, (3) 62*e*.
distinguished from glaze melting, (4) 92*g*.
economics of gas vs. electric, (8) 224*c*.
electrical, (7) 180*f*.

Glass, melting (*continued*)
formation of inhomogeneities during, (4) 93*h*.
with freshwater limestones, (10) 264*j*.
in furnaces with divided zones, (10) 265*h*.
high temperature service of refractories during, (2) 37*a*.
hydraulics and convection flows in, (8) 209*i*.
infrared sensors aid control, (8) 209*e*.
instructions for placing sodium fluosilicate in charge to accelerate, (6) 148*c*.
intensification in pot furnaces, (4) 93*j*.
new refractories for high-temperature use, (1) 10*f*.
process, (9) 233*e*.
producing lamellar metal structure for, P (2) 34*j*.
rapid, (4) 95*b*.
tracer study of flow in glass tank, (2) 32*f*.
under action of gamma rays, (7) 180*i*.
velocity of reactions in, (4) 96*a*.
with and without sulfate, hot-microscopy of processes in, (6) 148*a*.
melts, bubble formation in reaction with refractories, (6) 146*j*.
containing nitrogen in solution, vibrational spectra of, (1) 6*a*.
effect of inhomogeneities on viscosity and flow homogenization of, (5) 120*i*.
homogeneity of small-scale laboratory, (3) 61*g*.
ionic formulation of redox equilibria in, (5) 121*b*.
orientation induced birefringence and structural constitution of, (10) 265*e*.
oxidation-reduction reactions in, (10) 264*j*.
oxide, bonding of dissolved nitrogen in, (1) 3*i*.
solubility and diffusion of He in, (9) 234*e*.
solubility of N in, (10) 265*j*.
-metal combinations, calculation of temperature distribution in, (2) 31*a*.
-to-metal metallizing technique, P (8) 212*a*.
sealing. See *Seals and sealing*.
method to laminate, P (4) 97*c*.
microinhomogeneity, determined by refractive index distribution, (8) 210*f*.
microsphere, and fiber filled polyester resin composition, P (4) 96*j*.
microtome knife of, P (4) 97*j*.
mirrors. See *Mirrors*.
molds. See *Molds*.
molten, calculation of flow rate pattern along depth of, (8) 208*i*.
diffusion processes with quartz, (4) 92*i*.
froth formation on surface, (1) 5*d*.
mechanism of dissolution of metallic iron in, (4) 94*g*.
modeling of hydraulics and flow in relation to output, (10) 265*j*.
rate of bubble rise with unstable temperature, (10) 266*a*.
reactions with refractories, (10) 266*g*.
in system lead oxide-silica, (9) 234*e*.
wetting of refractory concrete by, (9) 235*i*.
natural, ion-exchange constants by electrode method, (7) 180*f*.
Nd-doped, fluorescence and stimulation in, (6) 147*e*.
Nd-doped, laser action in from energy transfer, (10) 287*c*.
opal, corrosion of refractories, by, (2) 36*e*.
with low thermal expansion, P (11) 299*a*.
and pearl, colloidal and colloid-chemical processes in, (10) 264*b*.
phosphate, effect of constituents on opacity of, (3) 61*a*.
opaque, stress optical studies at wavelengths between 1 and 3μ, (8) 211*d*.
optical, P (7) 184*c*; P (10) 269*f*.
advances in melting, (2) 32*d*.
blooming components with aluminosilicate, P (10) 267*f*.
crown, P (2) 34*c*.
dispersion in region of 0.33 to 2.0μ and its dependence on frequency of glass, (2) 31*g*.
effect of internal stress on rigidity of large lens, (2) 31*g*.
guide to selection, (2) 31*f*.
infrared-transmitting, P (6) 150*d*.
inhomogeneous magnesia-alumina lens, P (1) 6*h*.
lens blocks, P (11) 298*c*.
method to correct refractive index during melting, (8) 210*e*.
method of forming apertured disks of, P (6) 150*a*.
multicomponent systems for production, (2) 32*d*.
new definitions, (1) 4*i*.
pitch lens blocker ball and blanks, P (11) 299*d*.
properties. See *Optical properties*.
radiation resistant, (9) 234*b*.
sandwiched, P (3) 63*j*.
stabilization of micro- and macrostructure, (11) 297*j*.
volatility of, (7) 182*e*.
optical lenses, P (7) 184*g*.
generating method, P (2) 33*e*.
multifocal, P (7) 184*g*.
ornamented drinking, P (9) 236*h*.
outgassing, causes of, (9) 234*h*.
oxidic, light dispersion, ultraviolet vibrations, and light transmission in ultraviolet, (1) 4*e*.
packaging, P (4) 98*a*.
packaging, spacer retaining clip for, P (4) 98*b*.
pallet package, P (11) 298*h*.
phase, in fused-cast tank blocks, (2) 36*i*.
phase separation, initial stages, (2) 31*h*.
phosphate, chemical analysis of, (1) 5*c*.
composition for, P (7) 183*b*.
constitution of, (9) 233*b*.

Glass, phosphate (*continued*)
equations for calculating chain length distributions in, (3) 61*d*.
for lasers, P (7) 184*c*.
structural and thermodynamic aspects of, (1) 5*d*.
phototropic, P (11) 299*c*.
phototropic, means to control light transmission source, P (8) 212*g*.
pipe. See *Pipe*.
planing process, P (7) 183*f*.
-plastic assembly, laminating techniques for, P (5) 123*f*.
laminates, pressing of, P (7) 184*c*.
layers, stress-optical investigations of, (3) 62*h*.
plate. See also *Glass: flat, sheet, window*.
drawn without debiteuse, $Al(OH)_3$ in melting, (10) 267*c*.
effect of stress and strain on producing hackle in, (2) 31*h*.
effect of surface tension on behavior of holes and heat flow phenomena in, (8) 208*j*.
polishing. See *Polishing*.
porous, with polymers and metals, possibility of submicroscopic compatibility of, (8) 211*g*.
porous, salt rejection by, (5) 121*j*.
K_2O-SrO-SiO_2, changes in composition during analysis of, (9) 232*j*.
pots. See *Glassmaking apparatus and equipment; Refractories*.
powder, to protect and lubricate metals at high temperature, P (8) 213*h*.
powders, compression process of spherical, (8) 208*h*.
pressed, new developments, (4) 94*b*.
printing, P (8) 213*a*.
progress in, (11) 297*e*.
properties, as function of composition, (10) 266*d*.
method to calculate, (10) 265*j*.
and structure, in system alkali-TiO_2, reply to discussion, (1) 5*i*.
in system Na_2O-ZrO_2-SiO_2, (1) 4*e-a*.
Pyrex, catalytic efficiency for recombination of N ions, (8) 208*j*.
Pyrex, reflection of X rays by surface of, (3) 85*i*.
Pyrex-type, acid corrosion of, (8) 209*g*.
quartz, defective structure of fused, (8) 209*b*.
effect of X-radiation, (2) 31*i*.
radiation-optical stability at different temperatures of irradiation with γ rays, (8) 210*i*.
viscosity of, (10) 266*j*.
raw materials, geological-petrographic and physical properties of, (3) 78*f*.
sonic-chemical method to process, (9) 234*e*.
X-ray fluorescence spectroscopy of, (6) 146*j*.
recipe book, of New England Glass Company, (5) 118*c*.
recipes, B (3) 88*i*.
recrystallized, performance and use, (2) 31*d*.
red, colored by silver compounds, (4) 95*c*.
red, selenium loss and problem of reducing in melting of, (9) 235*d*.
redox equilibrium, effect of O ion activity on, (3) 61*g*.
redox pairs in, mutual interaction of different, (5) 121*f*.
redox reactions in, (4) 95*c*.
reflective spheroids, P (8) 213*i*.
reflector, P (11) 298*j*.
refraction, change by tensile stress, (2) 31*a*.
refractor, glare reducing, P (7) 183*a*.
-reinforced plastics, production of and articles from, (6) 148*e*.
research, mass filter in, (8) 210*a*.
-resin interaction, of filament-wound composites, (5) 120*g*.
-resin interface, effect of water vapor on, (2) 31*h*.
ribbon, method to anneal, P (8) 212*i*.
ruby, copper, (7) 179*j*.
determination of Se in, (10) 264*c*.
-red, rod with metallic precipitates and goldlike surface crystals, (2) 32*h*.
selenium to produce, (4) 95*c*.
safety. See *Glass, laminated*.
sand. See *Sands*.
scale, method to produce, P (4) [illegible]7*d*.
sealing. See *Seals and sealing*.
with selective reflection properties, (10) 264*c*.
Se in, chemistry of, (3) 60*d*.
selenium-ruby, mechanism of reaction, (9) 233*i*.
Se ruby, structure of pigment in, (8) 211*d*.
semiconducting, P (9) 237*b*.
semiconductor vanadium oxide film on, (1) 5*j*.
semicrystalline, method to make high strength, P (8) 213*i*.
sheet. See also *Glass: flat, plate, window*.
absorption of Al_2O_3 on surface of, (8) 208*g*.
bubble movement in tank furnaces for, (6) 148*b*.
changes of bubble composition throughout furnace zone, (1) 3*i*.
coating to improve strength of, (6) 146*i*.
coating while deformable and supported on gas, P (3) 63*c*.
continuous line for breaking, severing, and packaging, (4) 92*a*.
controlling annealing of, (4) 92*a*.
double glazed, P (10) 268*e*.
effect of permanent mechanical strains on, (4) 93*b*.
inspection of tempered, P (10) 269*e*.
length and area partitioning methods and apparatus, P (7) 183*c*.
manufacture of, P (6) 150*e*.
mass production and accuracy in cutting, (3) 61*b*.
mechanized production of selenium ruby, (4) 94*h*.
melting at high temperatures, (10) 265*i*.

Glass, sheet (*continued*)
method to analyze for cutting, P (2) 33*g*.
method to bend and temper, P (10) 268*e*.
method to control temperature, P (9) 236*j*.
method to determine strength of, (5) 121*d*.
method to measure strength, (4) 94*j*.
method to remove surface defects, P (9) 236*e*.
method to temper on bending mold, P (10) 269*e*.
physicomechanical properties of, (11) 297*f*.
production of multiple glazing units, P (9) 237*a*.
relation between waviness and thickness variation, (1) 5*h*.
shipping crate for packages of, P (4) 98*a*.
simultaneous surfacing of both sides, P (10) 269*c*.
snapping of, P (10) 270*a*.
strength improved by etching, (7) 181*i*.
structural tempered, P (8) 214*c*.
studies of physicomechanical properties of continuously rolled, (8) 210*h*.
surface structure of vertically drawn, (4) 95*h*.
thermoplastic, means to make, P (2) 33*i*.
thickness, optical device to measure, P (9) 237*c*.
tracing and breaking, P (2) 33*b*.
transparent electrically conducting and article from, P (8) 213*b*.
silica, crystallization in oxidizing atmosphere of reduced, (2) 31*c*.
silica, dissolution of schlieren in by diffusion and flow, (8) 209*d*.
silicate, acoustic-dilatometric studies, effect of composition on structure, (9) 232*h*.
alkali resistance of, (8) 210*c*.
and borate, iron adsorption in, (3) 61*e*.
coactivated with Yb^{3+} and Ho^{3+}, energy transfer and Ho^{3+} laser action in, (7) 199*g*.
containing Ti, EPR of, (7) 180*i*.
effect of composition on strength, (10) 264*b*.
effect of heat treatment on properties and structure of, (7) 179*i*–180*b*.
effect of metallic impurities on hot leaching of, (3) 61*b*.
effect of oxides on diffusion of helium through, (7) 181*g*.
hot water attack on, (8) 209*e*.
microindentation hardness and atomic significance, (2) 32*d*.
model of polymerization/depolymerization relations in, (2) 32*i*.
model of polymerization relations in; correction, (5) 121*f*.
oxygen tracer investigation of diffusion of "water" in, (9) 234*h*.
physicochemical properties, (4) 95*c*.
and their components, vapor pressure of, (4) 95*i*.
silvering, desalted water for, (9) 233*a*.
sized fabric, and method, P (4) 98*b*.
slagceram, constructional metallurgical slag, (8) 210*j*.
soda-alumina-silica, diffusion of radiotracer sodium by residual surface counting technique in, (9) 233*e*.
soda-lime, absence of devitrification at bubble surfaces in, (8) 208*f*.
separation plan for complete analysis of sample, (4) 107*f*.
structure of, (10) 266*b*.
soda-lime-silica, effect of additives on properties of, (7) 180*d*.
properties of strontia and baria substituted, (4) 95*i*.
radiological determination of CO_2 in, (1) 5*f*.
refining with sodium sulfate, (3) 62*c*.
soda-limestone-quartz, effect of additions on reaction rate in basic batch, (4) 96*a*.
sodium borate, relation between viscosity and composition of, (9) 234*d*.
sodium borosilicate, stresses originating during leaching of, (9) 234*j*.
sodium-calcium-magnesium-aluminosilicate, containing 15% Na_2O, temperature of upper limit of crystallization, (1) 5*f*.
Na_2O-GeO_2, acoustic spectra of, (4) 92*a*.
Na_2O-RO-SiO_2, electrical properties of, (3) 61*c*.
Na_2O·$2SiO_2$, optical spectra of V in, (1) 4*j*.
Na_2O·$2SiO_2$, oxidation-reduction equilibria in molten in contact with metallic Cu and Ag, (11) 297*d*.
Na_2O·$2SiO_2$-SiO_2, crystallization of, (11) 296*g*.
sodium silicate, study in the infrared by thin films, (3) 62*j*.
sodium-strontium-silicate, physico-chemical properties of, (1) 4*j*.
solder, composition, P (2) 33*e*.
solder, magnetic and method, P (7) 183*d*.
sorption of Ar, in gas-discharge lamp, (9) 234*f*.
spacers, to separate steel plates, P (5) 123*h*.
spheres, P (6) 150*c*.
on reflectors, P (8) 213*j*.
strength of small, (7) 181*i*.
stopcock and plug retainer, P (11) 299*h*.
stratification, by drawing, (1) 5*c*.
stream, delivery method, P (10) 268*a*.
strength, below room temperature, (10) 265*j*.
method to improve, P (7) 184*h*.
methods to increase mechanical, (9) 234*c*.
relation to fracture mirror size, (1) 5*h*.
relation to structure, (5) 121*g*.
strengthened, with semicrystalline surface layer, P (8) 212*f*.
strengthening, by built-in surface compression, B (2) 55*h*.
stress, measurements by scattered light with laser source in tempered, (3) 62*g*.
opticopolarization measurement, (8) 210*h*.
research on elimination by ultrasonics, (4) 95*d*.
Sr, properties and applications, (7) 181*b*.

Glass (*continued*)
structural shear formation, during heating and cooling, (1) 5*c*.
structure, and crystallization, B (1) 26*e*.
effect of alkaline earth oxides on, (10) 264*e*.
investigation with electron microscope, (1) 4*j*.
investigations using ultrathin, (7) 182*b*.
status of research on, (5) 121*f*.
substrates, structure and annealing of Cu and Au films on, (11) 305*d*.
surface damage, strength reduced by, (7) 181*g*.
surfaces, effect and behavior of silicones on, (5) 120*h*; (7) 179*g*.
effect of container molds on, (4) 92*e*.
energy of a running crack in, calculated from crack-branching measurements, (6) 170*i*.
flaws, and statistics of flaw distribution, (6) 149*d*.
formation of chip cavities in scratching, (2) 31*c*.
means to increase chemical resistance, P (2) 34*f*.
research with radioactive phosphorus, (2) 32*h*.
silicone treatment of, (5) 121*a*.
silver ion sorption properties of, (5) 121*d*.
stresses in, (7) 181*j*.
study by electrostatic charges, (10) 266*f*.
study of coatings applied to by aerosol method, (6) 148*a*.
tension in air and N_2, (8) 211*j*.
in system La_2O_3-SiO_2-P_2O_5, effect of metaphosphates on properties, of, (8) 211*f*.
in system lithium aluminosilicate, catalyzed controlled crystallization of, B (3) 88*g*.
in system LiF-BeF_2, vibration damping and structure of glasses in, (8) 211*c*.
in system Li_2O-MgO-Al_2O_3-SiO_2, effect of crystallization on properties of, (4) 93*h*.
in system M_2O-Al_2O_3-GeO_2 properties and structure, (2) 32*f*.
in system SiO_2-Al_2O_3-MgO, phase transformations in crystallization of, (9) 253*b*.
in system NaF-Na_2O-B_2O_3, nuclear magnetic resonance study of structure, (6) 148*i*.
systems. See *Systems*.
for tableware, chemical composition, (11) 297*a*.
tableware, with rare-earth elements, synthesis and study of, (7) 181*i*.
technical, P (10) 270*a*.
technical, viscosity of, (5) 120*d*.
technology, practice, B (4) 115*b*.
technology, review, (10) 265*b*.
television tubes. See *Tubes*.
telluride, infrared transmission of, (6) 148*b*.
tempered safety, technological parameters of manufacture, (9) 235*b*.
tempering, method for, P (8) 212*d*.
terminology, German-English, B (6) 172*i*
testing, new instrument for torsion and tension, (7) 180*j*.
thermal conductivity, measurement in −150° to 50°C range, (8) 210*c*.
thermal and elastic aftereffects, structural significance, (5) 122*a*.
thermal expansion and structure, (1) 5*g*.
thermal shock resistance, effect of repeated temperature changes on, (2) 31*h*.
thermometers, lead arsenic enamels for, (10) 264*f*.
toughened, method to produce, P (4) 97*e*.
transformation range of, (7) 181*i*.
transformation temperature, thermographic determination of, (7) 182*a*.
transition, conductivity anomaly associated with in vitreous selenium, (6) 165*e*.
transparent crystalline, P (6) 151*a*.
treatment, to produce reverse stresses and product, P (9) 237*d*.
tubes. See *Tubes*.
under stress, rheology in transformation range, B (9) 259*j*.
vacuum-melted, devitrification of lithium metasilicate-silica series, (1) 3*j*.
vacuum seal, for high temperature, (10) 281*b*.
vacuum vessels, automated production, (6) 146*i*.
vessel, joining of handle, P (10) 269*e*.
viscosity, effect of alkaline earth oxides on, (10) 264*e*.
new method to measure, (4) 94*j*.
and structure of, (1) 6*b*.
vitreous, composition, P (8) 214*a*.
process for increasing thermal insulating properties and cohesion to coherent substances, P (3) 64*h*.
silica, method of fine annealing transparent, P (4) 97*a*.
silica, method of tempering by heat treating, P (4) 97*i*.
volatilization, of fluorine-titanium flint, (4) 96*c*.
VVS, interfacial angles of wetting and their effect on bubble size during clarification, (1) 4*d*.
ware, in chemical industry, (1) 5*j*.
conveyor-line system for producing and processing, (4) 92*b*.
manufactured, (2) 31*j*
water-extraction of alkali from, effect of temperature, on, (6) 147*c*
wetting, of platinum and its alloys, (4) 96*c*; (5) 122*b*.
window. See also *Glass: flat, sheet, plate*.
analyses and discussion of Caerleon, (9) 229*i*.
ceramic sealed for waveguide structures, P (1) 6*f*.
and glass block for, P (3) 65*a*.
with heat screen for vehicles, P (6) 149*g*.
history of Ontario factory that produced in 19th century, (4) 90*b*.
identification of stones in, (3) 61*d*.
sound insulation of single and double glazed, (4) 95*a*.

Glass, window (*continued*)
transmission of daylight, (1) 5*h*.
weathering products on, (6) 144*b*.
wool. See *Fibers, glass*.
working, thermoplastic, structure of flame and, (10) 266*a*.
yarns. See *Fibers, glass*.
ZnO-Al_2O_3-SiO_2, effect of heat treatment on crystallization of, (6) 147*h*.
ZS-4, melting in tank furnaces, (5) 121*c*.
Glass industry, American, trends in, (4) 95*h*.
apparel for workers, (2) 54*f*.
batch plants, technical weighing problems in, (3) 62*b*.
batch preparation, (6) 146*j*.
batch preparation, automatic in Sighisoara, Rumania, (2) 30*j*.
bottle plant, description of Mexican, (4) 96*b*.
British, directory and buyers' guide, B (2) 55*b*.
Bulgarian, factory of 9th and 10th century, (5) 117*j*.
Bulgarian, seventy years of, (6) 148*i*.
container plant, first computer operated, (8) 210*i*.
custom, variety of decoration and design, (8) 209*a*.
energy consumption norms in, (2) 31*b*.
of Federal Republic of Germany, statistical analysis of power consumed by, (9) 234*i*.
flat, Mexican plant described, (4) 96*b*.
flat, X-ray fluorescence in, (4) 92*a*.
flowsheet, selection for machine-tank and cutting departments, (5) 121*a*.
fuels, cost of, (2) 31*i*.
in India, (2) 54*g*.
isotopes and radiation in, prospective uses of, (4) 95*b*.
Jablonec, history of, (6) 144*b*.
mixing equipment, (3) 74*i*.
Polish, developments in, (10) 264*e*.
pot furnace factory, selection of raw materials, batch mixing, and transport in, (3) 62*c*.
production, statistics to study processes of, (10) 267*e*.
rotary regenerative waste heat recovery for, (6) 148*k*.
Swedish, fuel problems and raw materials up to 1913, (1) 17*g*.
fuels and raw materials up to 1913, (8) 209*i*.
providing fuels and raw materials up to 1913, (3) 93*j*.
symposium, on fuel and power in, (11) 297*e*.
300 tons per day melted at Mexican plant, (4) 93*h*.
-works, conical stacks at old, (4) 92*j*.
Glassmaking apparatus and equipment. See also *Burners*.
for admixing additives to melt, P (3) 64*d*.
to agitate molten, P (6) 150*f*.
for ampules, P (3) 62*j*.
for annealing, sheet, P (4) 97*c*.
for armored, P (2) 33*j*.
for aspheric surfaces, on mirrors or lenses, P (1) 7*c*.
for banding articles with adhesive, P (6) 149*c*.
for batch, handling granular materials for, P (9) 236*c*.
handling with pneumatic-vacuum transport, (7) 181*c*.
method and apparatus, P (9) 236*f*.
mixing, P (2) 34*a*.
for beads, P (8) 211*i*.
for beads, by dispersion of molten glass, P (6) 150*h*.
bending, P (2) 33*j*.
continuously produced bands to exact shape, P (7) 182*g*.
curved panes with conical surface portions, P (5) 122*g*.
with pivot support points, P (3) 63*h*.
by pressing, P (8) 211*h*.
and tempering, of sheets, P (5) 122*c*.
tube to circular shape, P (2) 33*f*.
bending mold, P (1) 6*a*; P (7) 182*f*.
with heat absorber, P (10) 267*f*.
with heat absorber for sheet, P (10) 268*d*.
hold down device for, P (3) 63*b*.
with leading apertured plate, P (2) 33*c*.
with pivoted end sections, P (7) 183*a*.
for sheet, P (3) 63*b*; P (5) 122*i*; P (7) 182*c*; P (11) 297*f*.
for sheet, with horizontal support surfaces, P (10) 268*d*.
for sheet, pivoted, P (7) 184*d*.
with sheet guide, P (3) 63*i*.
for bending sheets, P (3) 64*c*; P (4) 96*f*; P (4) 97*d*; P (5) 122*a*; P (5) 123*g*; P (6) 150*j*; P (7) 183*f*; P (1) 236*i*.
to compound curvatures, P (3) 64*c*.
with compressional zone, P (4) 97*j*.
on conveyor, P (7) 184*d*.
with guide for sheet, P (4) 96*j*.
with outrigger support for sheet, P (3) 62*e*.
or plates, P (3) 62*c*; P (4) 96*f*.
for bent and toughened, P (3) 63*h*.
for blowing, blowhead and article cooling tube combination, P (5) 123*b*.
for blowing bulbs, P (3) 62*f*.
blowing frame, for tempering sheets, P (4) 96*a*.
for bonded fibrous products, P (11) 298*g*.
bottles, flasks, etc., machine to invert, P (1) 6*i*.
bottle width selector, photosensitive, P (7) 184*d*.
bubblers, P (2) 33*d*.
casting machine, temperature distribution and heat transfer in top roller of, (10) 264*g*.
casting machine, temperature inside top roller of, (10) 267*a*.
casting rolls, for sheet, protective atmosphere for, P (4) 98*d*.
for chemical polishing, P (4) 97*b*.

Glassmaking apparatus and equipment (*continued*)
for coating bottles, P (8) 212*a*.
container, for processing, P (5) 122*h*.
continuous rolling, to make U-shaped profiles, P (4) 96*c*.
control, for heat of forehearths, P (7) 182*g*.
with control device, for drawing sheet, P (3) 62*f*.
to control movement of flame heating means to form spiral lamp tubes, P (6) 149*j*.
conveyor, to transport and cut plate, (10) 264*e*.
conveying of sheet at deformation temperature, P (3) 64*a*.
to cool drawn, P (5) 122*c*.
to cool tube, P (9) 236*c*.
for curved and hardened panes, P (8) 213*e*.
cutter, with computer control, P (11) 298*g*.
cutter, for sheets, P (5) 123*d*; P (6) 149*j*; P (8) 211*g*.
for cutting, P (11) 298*e*.
method, P (7) 184*a*.
of sheet, mass production and accuracy in, (3) 61*b*.
by thermal shock, P (2) 32*j*.
for decorating, P (7) 182*b*; P (8) 212*j*.
bottles, P (3) 63*f*; P (8) 212*b*; P (11) 298*d*.
containers, P (11) 298*f*.
for delivering, fusible material furnace, P (2) 32*i*.
to deliver multifilament strands, P (10) 267*g*.
to detect breaks, during molten fiber formation, P (10) 267*g*.
to detect surface unevenness, P (7) 183*g*.
to determine distortions in plate, (9) 234*a*.
to determine heterogeneity, (4) 92*b*.
for dip-coating, bottles, P (11) 298*b*.
for discharge of molten, P (4) 96*e*.
to draw fibers from rods, P (10) 267*h*.
for drawing, P (1) 6*a*; P (2) 34*f*; P (5) 122*d*; P (7) 183*a*.
chamber, with heated air to improve surface of glass, (10) 265*f*.
nonstaged electric drive for, (9) 234*e*.
pivotal cooler equipped, P (11) 298*h*.
sheet, P (3) 62*g*,63*g*; P (4) 97*e*; P (5) 122*e*.
tubes, rods, etc., P (2) 32*i*.
worm drive for, P (5) 124*d*.
zone, transmission baffle in, P (4) 98*d*.
electrostatic screen for printing, (2) 43*e*.
enclosed chamber, for float on molten bath, P (7) 182*f*.
with energy transmitter, for drawing sheet, P (1) 6*d*.
expandable collet, P (7) 182*h*.
feeder, means to protect plunger, P (4) 96*i*.
feeder, for melting spheres for fiber drawing, P (7) 182*h*.
for fibers, P (5) 122*f*,*i*; P (7) 182*a*; P (8) 211*e*,*g*; 213*a*–*b*,*f*; P (9) 235*b*,236*g*; P (10) 267*h*; P (11) 297*e*.
burner to produce gaseous mixtures in, P (8) 212*b*.
fine, P (5) 122*j*.
forming, P (11) 298*g*.
forming and collecting, P (3) 62*g*.
metal laminate, P (7) 183*b*.
method and apparatus, P (1) 7*a*.
reinforced materials, P (9) 235*i*.
for filaments, P (5) 122*i*; P (8) 213*c*.
for film, P (9) 235*c*.
filter flask, P (10) 267*j*.
to finish surface, P (5) 123*e*.
for flake, P (9) 235*d*.
flake breakout detector, and method to control breakout, P (3) 63*f*.
for flat, P (3) 63*a*; P (8) 212*f*.
for float, P (6) 150*g*.
fluid transporting, of sheets, P (3) 65*b*.
to form, and collect fibers, P (10) 267*h*.
and deliver, P (6) 150*a*.
solid ware, in carbon die, P (10) 267*i*.
for forming, P (4) 96*g*; P (5) 122*g*; P (8) 211*e*; P (9) 235*b*.
an airborne curtain of liquid, P (2) 32*i*.
conveyor drive for, P (7) 182*e*.
hollow articles, P (4) 96*g*; P (4) 97*g*.
invert mechanism for, P (5) 123*d*.
lens surface, P (4) 97*g*.
long stroke single gob, P (4) 97*b*.
neck mold inverter for, P (6) 150*d*.
optical elements, P (3) 62*i*.
silica articles, P (9) 236*a*.
take-out mechanism for double gob, P (3) 65*b*.
with timing valve assembly, P (1) 6*e*.
tubes, P (5) 122*j*.
ware, P (3) 63*j*.
and welding, automatic flame regulator for, P (10) 267*d*.
furnaces. See *Furnaces*.
gage, with automatic reject, P (10) 267*j*.
for grinding. See *Grinding apparatus*.
for handling, bottles, P (1) 6*e*.
for handling containers, P (8) 212*h*.
with heater, for continuous strip forming, P (5) 122*a*.
to heat treat, sheet, P (3) 63*a*.
heat treatment, of sheets, P (3) 64*e*.
for hollow fibers, P (10) 268*i*.
for hollow ware with stem and foot, P (11) 299*b*.
to homogenize, P (10) 267*j*.
for homogenizing, molten in forehearth, P (3) 62*j*.
with hydraulic control, for pressing ware, P (10) 268*d*.
to improve thermal uniformity of molten, P (6) 150*j*.
to indicate material stream characteristics, by calorimetry, P (5) 122*f*.
to inspect hollow syringes, P (10) 267*j*.
to inspect and sort containers, P (10) 268*g*.

Glassmaking apparatus and equipment (*continued*)
inspection, automatic for ampoules, P (2) 32*h*.
electrically actuated gaging, P (7) 183*b*.
photosensitive means, of cylindrical objects, P (5) 123*i*.
for laminated panes, P (7) 182*h*.
lathe, to graduate tubes, (5) 121*e*.
lehr, loader, P (6) 150*d*.
for annealing and decorating, P (9) 235*a*.
for annealing ware, P (9) 236*d*.
method to convey and feed articles into, P (9) 235*h*.
for lens blocking, P (3) 63*c*.
lens generating, P (10) 268*h*.
lens surface generator, P (6) 150*e*.
to locate streaks, in optical glass, (10) 264*d*.
machine to bevel, (9) 233*i*.
for making straight precision syringe bodies, P (7) 182*j*.
for marking, P (4) 97*c*.
melter, with charging means, P (7) 182*i*.
for melting, P (5) 122*f*.
melting, with submerged combustion heaters, P (9) 236*d*.
and method, for fusing fiber optical image transfer devices, P (1) 6*i*.
molding, programmed valve system for, P (7) 184*g*.
molds. See *Molds, glass*.
for molten, to thermally condition before shaping, P (4) 97*i*.
for moving newly formed articles onto a conveyor, P (7) 182*j,a*.
for ophthalmic lens, to harden, P (9) 236*g*.
optical, homogeneous gas-free, P (6) 150*i*.
optical lense, aligning and blocking, P (9) 236*e*.
optical lenses, loading mechanism for machines for working on, P (9) 236*e*.
for packaging, filamentary materials, P (4) 97*h*.
for panel lamps, P (8) 211*g*.
for panel with optical effects, P (5) 124*b*.
photoelectric inspection, for dirt, P (5) 123*j*.
for polishing. See *Polishing apparatus*.
for polychrome striped screens, for color television receiver, P (8) 213*b*.
for positioning and orienting, bending mold, P (7) 183*a*.
pots, softening under torsion, (1) 5*b*.
for pressing, P (9) 236*b*.
pressure rollers, to temporarily seal mouths of containers, P (6) 150*i*.
for printing, bottles etc., P (5) 122*h*.
to process high temperature batch, P (10) 268*b*.
for processing ophthalmic lens, P (4) 97*i*.
to produce fibers, P (10) 267*c*.
to produce propulsion stream to attenuate fibers, P (7) 182*b*.
to protect sheets, from metal bath, P (7) 183*j*.
recorder, to determine optical distortions in sheets, (5) 121*i*.
to remove floating impurities, P (3) 63*h*.
for reshaping tubes, P (9) 236*i*.
ribbons, forming of, P (4) 97*b*.
radiant type cooler in, P (11) 299*f*.
scoring of continuously moving, P (6) 149*a*.
Roirant machines, early history of, (6) 144*a*.
to roll channels from flat strips, P (7) 184*f*.
roller, to paint flat surfaces, P (5) 124*e*.
rotor, to form filaments, P (7) 184*g*.
roving, treating, P (6) 150*c*.
to score sheet, P (6) 150*i*.
to seal glass ampuls, P (10) 267*f*.
sensing device for movable parts, with digital readout for position of, P (6) 150*g*.
to sever, a liquid stream, P (6) 149*b*.
mold charges of molten, P (10) 268*c*.
tube, P (15) 123*a*.
to shape, P (1) 7*c*.
shaping apparatus, for containers or vials, P (6) 149*g*.
to shear optical, P (4) 97*g*.
for sheet, P (4) 97*h*; P (6) 149*a*; P (6) 150*h*; P (9) 235*c*.
bending and annealing, P (8) 211*d*.
bending roll, P (11) 299*g*.
bending and tempering, P (10) 268*a*.
continuous fire-polished, P (5) 123*j*.
continuous line to break, sever, and package, (4) 92*a*.
divider for, P (9) 236*i*.
down-drawing, P (11) 298*h*.
drawing, heat exchanger for, P (8) 212*d*.
gas module systems for heat transfer and/or fluid support of, P (3) 63*g*.
handling, P (3) 63*j*.
handling device for, P (8) 214*b*.
heat treating, P (7) 182*h*.
improvements in drawing, (10) 265*f*.
improving surface by heating air in drawing chamber, (10) 265*f*.
means to convey and treat, P (3) 64*b*.
means to toughen curved, P (2) 34*b*.
means to vertically support and heat treat, P (3) 64*b*.
to measure and control thickness, (2) 31*j*.
self-gripping tongs for, P (11) 299*g*.
shaping on metal bath, P (8) 214*e*.
support means, P (3) 63*j*.
support roll, P (1) 6*d*.
wire reinforced, P (1) 6*c*.
sizing, machine and method, P (1) 6*e*.
skimming and stirring, for molten, P (2) 32*j*.
to skim molten, P (5) 123*b*.
slitter, for flexible sheet material, P (2) 34*i*.
for softening and hardening auto glasses, (10) 264*i*.
spinner, continuous cylinder, P (7) 182*d*.
for spray coating, irregular objects, P (7) 184*f*.
stirrer guide, simple, (4) 95*g*.

Glassmaking apparatus and equipment (*continued*)
for stirring, P (5) 122*i*.
for strand delivery, P (10) 270*b*.
for strand packages, of uniform length, P (8) 211*i*.
for strip, fire-polished, P (9) 236*j*.
support, while polishing, P (4) 97*h*.
to surface, P (2) 34*j*.
for surfacing optical elements, P (8) 211*f*.
tempering means, P (4) 97*a*.
for thermopanes, P (1) 6*j*.
thickness indicator, P (2) 35*a*.
turnover device, P (6) 151*b*.
for unwoven fabric, P (11) 298*h*.
for ware, blowing and cooling, P (5) 122*c*.
wareholder, shaker for, P (2) 35*b*.
washer, for flat, P (10) 267*j*.
washing-drying, for flat instrument glass, (10) 267*f*.
for welding containers, P (8) 212*f*.
for windows, all-glass multiple sheet, P (11) 297*f*.
for windows, double glazed, P (11) 297*e*.
to work tubes, P (4) 96*j*.
Glauberite, $CaNa_2(SO_4)_2$, crystal structure of, (7) 198*d*.
Glazes. See also *Decoration*.
for artware, low-lead borosilicate, (11) 304*b*.
basic, recipe for, (8) 206*b*.
boron phosphate in, (10) 275*e*.
black, for porcelain, (2) 39*a*.
for brick, and structural clay products, (2) 35*g*.
celedon, (8) 218*i*.
crystalline and crystal, (6) 156*a*.
for earthenware tile, improving quality of, (6) 156*e*.
failure, causes on battery tanks, (2) 39*c*.
fast firing of, report on testing frits for, (6) 157*c*.
formulas, computer data processing system calculation of, (1) 12*h*.
frits. See *Frits*.
hardness, determination of, (8) 218*j*.
light colored, for tile, (2) 39*d*.
maturing behavior of, (7) 190*d*.
maturing, effect of body on, (10) 275*e*.
melting, distinguished from glass melting, (4) 92*g*.
opacification, with zircon, (6) 156*d*.
oxblood, for stoneware vases, (10) 275*i*.
pink, Cr as coloring agent, (7) 190*d*.
on porcelain, machines for applying, (2) 39*g*.
raw, effects of frit additions on properties, (8) 219*a*.
red, for oxidizing firing, (4) 102*e*.
reduced-fire, fireclay wall tile with, (6) 156*b*.
for sanitary ware, control of pigment for, (2) 39*d*.
semiconducting, process to make, P (10) 276*e*.
soda-lime-silica, mineralogy of, (5) 127*g*.
suspensions, segregation during application and defects from, (6) 156*i*.
thickness, optical method to determine, (3) 76*e*.
for whiteware, effects of substitution of Li_2O for PbO in, (2) 39*j*.
wollastonite, status for sanitary ware, (2) 40*a*.
zircon, (2) 40*e*.
zircon colors for, (10) 276*g*.
Glazing, salt, in tunnel kilns, (10) 276*c*.
Gloss, measurements, complicated in practice, (10) 281*b*.
Glossaries. See *Nomenclature*.
Glucose, glass resistant to, (6) 147*e*.
Gold, -boron alloy, and method of making, P (1) 11*e*.
coating, under silver coating on stemware, (10) 261*i*.
content, determination in colors, (6) 161*j*.
effect, on rhodium-platinum alloys, (4) 96*c*.
films, on mica, energy for surface mobility of, (7) 191*i*.
films, structure and annealing on glass, (11) 305*f*.
$AuSb_2$, crystal structures of, (3) 85*h*.
-rhodium-platinum alloys, microstructure and mechanical properties of, (5) 122*b*.
on sodium chloride, role of contaminants in epitaxial growth of, (4) 112*j*.
spectrophotometric determination of, (5) 131*i*.
Grain boundaries, energies, method to measure in brittle materials, (7) 198*a*.
of ferrites, effect of impurities on, (9) 242*g*.
in growing oxide films, (2) 50*e*.
reactions, electron probe to study in magnesia-chrome refractories, (11) 301*e*.
role, in high temperature fracture behavior of magnesia, (9) 255*d*.
Grain growth, and densification, of hot-pressed lead zirconate-lead titanate ceramics containing bismuth, (4) 103*i*.
in ferrites, (6) 157*i*.
inhibition studies, (7) 191*e*.
Grains. See *Particles*.
Granite, of England, factors bearing on natural synthesis of clays in, (5) 133*i*.
Northern Nigerian, occurrence of montmorillonite in younger, (5) 133*e*.
South African, determination of zirconium in, (11) 309*j*.
Granular materials. See also *Powders*.
agitator for, P (11) 308*j*.
fine, pneumatic conveyor for, P (3) 75*h*.
in gas current, method and apparatus for heat-treating, P (2) 36*b*.
low moisture content, effect on conductivities of, (9) 250*g*.
method to prepare, P (8) 217*h*.
method to separate and compress with gas, P (10) 262*j*.
mixing, calculation of shaft torque for, (3) 75*a*.
and powders, process and apparatus to thermally treat, P (7) 194*h*.

Granular materials (*continued*)
for roofing, P (1) 13*b*; P (8) 214*f*.
solid systems, power consumption in discontinuous rotary cylinders, (1) 15*j*.
water absorption of, (9) 246*a*.
Granulation. See *Crushing; Grinding*.
in chemical engineering, (1) 15*i*.
Granulometry. See *Particle size*.
Graphite. See also *Carbon*.
atom in, energy of interstitial, (4) 111*e*.
-base reactor fuels, dissolution by aqueous processes, (9) 238*c*.
bodies, gas and liquid tight to house reactor element, P (9) 240*b*.
brick, in molding board for top casting, (1) 9*d*.
carbide coatings on, P (1) 10*i,j*.
-carbon bearings, friction and wear, (2) 44*h*.
coated, P (11) 302*b*.
coated, heat exchanger, P (10) 273*d*.
Compton scattering from, electron binding energy effects in, (9) 249*h*.
correlation among pore-size distribution, permeability, and diffusion in, (10) 284*i*.
damage in, enhanced nucleation of radiation, (4) 111*f*.
for dies, (5) 130*f*.
dislocation behavior, to predict flow characteristics, B (2) 55*g*.
dislocations, energy losses due to motion of, (4) 112*a*.
etch spirals in, (7) 199*b*.
fuel elements, for high temperature reactors, (9) 238*g*.
fueled, with pyrolytic-carbon-coated carbide particles for reactor systems, (3) 66*g*.
graphitization process, time factor in, (9) 257*f*.
at high temperature, thermal and electrical conductivity of, (11) 318*c*.
at high temperature in vacuum, contact interaction with metal-like carbides, (3) 65*j*.
H4LM, longitudinal tensile properties in range of −253° to 500°C, (4) 112*e*.
H4LM, tested in helium and in vacuum, effects of temperature and strain rate on transverse tensile properties of, (4) 110*i*.
lamellar compounds, with nitrogen pentoxide as possible reactor hazards, (3) 83*h*.
lampblack-based, high temperature radiation effects in, (4) 111*i*.
lattice, dimensional changes in irradiated, (4) 110*i*.
lattice defects, electron microscopy of, (4) 112*e*.
low-energy electron diffraction of, (6) 168*j*.
matrix, containing coated particles, method to extrude, P (8) 217*e*.
neutron irradiated polycrystalline, temperature variation of electronic paramagnetic resonance signal of, (4) 114*h*.
-nickel compositions, operation in steam atmospheres at industrial parameters, (11) 313*h*.
oxidation, by dissociated oxygen, high temperature kinetics of, (1) 22*e*.
oxidized by atomic oxygen, electron microscopy of surface changes, (2) 51*f*.
oxidized by atomic oxygen, kinetics of, (2) 51*c*.
physical properties, effects of radiation on, (4) 110*f*.
protective coating for, P (7) 189*g*.
pyrolytic, effect of stress on graphitization of, (5) 135*j*.
-bromine residue compounds, thermal expansion of, (4) 113*j*.
process for coating radioactive spheroids with, P (7) 189*f*.
thermal conductivity of, (7) 203*c*.
radiation damage, nucleation of, (2) 50*j*.
reactions, with silica, (8) 227*h*.
shell molds, P (9) 240*c*.
single crystal, magnetoresistance, (7) 201*b*.
single crystals, Hall effect in, (2) 50*f*.
stopper head, shape of screw bolt for, (1) 10*f*.
structure, cavity growth by vacancy condensation and transformation to dislocation loop in, (4) 109*i*.
sublimation, at hypersonic speeds, (4) 99*f*.
surfaces, localized oxidation rates by optical microscopy, (4) 112*d*.
wetting, by metals and alloys, (1) 1*g*.
whiskers and fibers, (5) 142*d*.
Gravimetric analysis. See *Analysis*.
Greases. See *Lubricants*.
Grinding (*Comminution*). See also *Crushing apparatus; Mills*.
of cement, problems in, (3) 58*d*.
of coarse kaolin, continuous closed-circuit attrition, (5) 133*a*.
costs, common sense approach to, (2) 35*b*.
dry, P (5) 130*j*.
fineness, effect of, (3) 71*e*.
of glass, (10) 265*e*.
jet pulverization, (1) 15*i*.
media, research on resonant motion in vibration mill, (5) 130*i*.
of refractory materials, (7) 186*h*.
vibratory, effect on feldspars and quartz, (3) 78*d*.
Grinding (*Material removal*). See also *Abrasives; Diamonds; Polishing*.
of carbide, ultrafinish, (7) 177*g*.
dry, in a ball mill, P (8) 222*h*.
dry, of tungsten carbide, test procedure with bonded diamond wheels, (8) 205*f*.
insulators, to shape, (8) 219*d*.
materials, for glass, recovery of waste, P (9) 237*b*.
method, for articles of high-alumina content, (2) 43*e*.
thin sections, improved holder for, (7) 195*b*.

Grinding apparatus, P (1) 18*e*; P (3) 78*f*. See also *Abrasives*.
also mixes, P (5) 131*a*.
for aspheric lens, P (6) 149*c*.
autogenous, beneficiation means and methods for, P (4) 109*c*.
for balls, P (7) 194*g*.
for beveling glass, (9) 233*i*.
disk, rejuvenator for, P (6) 143*i*.
for glass, how to choose, (3) 61*i*.
for glass edge, P (10) 267*g*.
jet mill, with interchangeable liners, P (4) 106*j*.
and method for hard materials, P (4) 109*b*.
new, for platens, (6) 143*g*.
for optical lens, P (5) 123*g*.
pin, with axial flow, P (2) 48*b*.
rods and balls, production of high density, (4) 102*h*.
semiautomatic, for porcelain articles, (2) 39*i*.
wheel, P (9) 229*f*.
abrasive, P (11) 293*f*.
composition graphically presented, (4) 89*f*.
diamond, armored for carbide grinding, (7) 177*e*.
dressers for diamond, P (10) 261*g*.
dressing tool for abrasive, P (10) 261*g*.
early, for engraving and cutting, (4) 90*c*; (5) 118*d*.
firing of bonded, (6) 143*f*.
for flat glass, P (6) 151*b*.
foamed polyurethane, P (8) 205*h*.
liquid-cooled abrasive, P (5) 117*g*.
method to make, P (8) 205*f*.
method to make grinding point assembly, P (10) 261*f*.
reinforced snagging, P (9) 229*g*.
reinforcement of molded, P (10) 216*f*.
securing means, P (7) 177*h*.
of Si, Al, and B, P (3) 57*g*.
tool life of, (8) 205*f*.
trends in diamond, (9) 229*f*.
wheel abrasive, flap-type, P (3) 57*h*.
inspection method, P (2) 27*g*.
method of making electrolytic, P (2) 27*g*.
Gunning, basic, developments for electric furnaces, (9) 239*b*.
composition, P (10) 274*i*.
dry, to hot-repair furnace roof, (10) 271*e*.
method, for hot repair of hot metal mixer and its effects, (10) 271*j*.
mix, prolonging life and increasing efficiency by repairing regenerator roof with, (10) 272*g*.
refractories, for ladle maintenance, (8) 216*e*.
Guns. See also *Spraying*.
airless spray, air atomizer for, P (1) 16*e*.
powder melting torch, P (3) 60*b*.
spray, for high pressure coating materia', P (2) 43*h*.
solenoid airless, P (1) 16*c*.
and techniques, (2) 30*e*.
Gypsum. See also *Plaster*.
β-$CaSO_4 \cdot 1/2H_2O$, hydration during first 7 days, (8) 207*d*.
calcined, effects of gum arabic on water requirement of, (8) 207*b*.
calcined, improved accelerator for, P (10) 263*b*.
combined water in, rapid determination of, (3) 75*e*.
composition, for floors and roofs, P (11) 295*a*.
crystals, means to form in portland cement, (8) 207*c*.
elastic and thermoelastic properties of, (7) 199*a*.
plaster, effect of acetates on setting time of, (9) 230*i*.
plaster of Paris, bandage with, P (3) 59*e*.
properties and testing, (2) 29*b*.
rock, process and apparatus for continuous calcining of powdered, P (5) 119*d*.
solubility and hydration, effect of $NaSO_4$ and NaCl on, (1) 2*h*.
SO_3 in, means to determine, (4) 90*f*.
thermal decomposition of, (4) 90*i*.
transformation, and its dehydration products, (9) 257*h*.

Hafnium, oxide, permeability to O, (6) 169*d*.
oxide, sols with actinide oxides, P (10) 283*e*.
separation, by introducing as dry solid into central step of liquid-liquid partition system, P (10) 283*d*.
systems. See *Systems*.
tetrabromide, X-ray study of, (2) 54*b*.
and Zr values, separation by solvent extraction, P (11) 312*j*.
Halides, alkali, anharmonic interactions in, (3) 79*i*.
alkali, steady-state excess conductivity during plastic deformation of, (7) 202*e*.
Hall effect, in graphite single crystals, (2) 50*f*.
of Te films, deposited on $BaTiO_3$ crystals, (2) 50*g*.
Halloysite, dehydroxylation of, heats of reaction and kinetics of dehydration, (6) 166*b*.
mineral changes, on drying, (10) 288*f*.
as raw material, (8) 225*d*.
Hardening, of Al powder, under pressure, (7) 178*i*.
control, for fused cast refractories, (6) 151*j*.
crystallization of cements in zone of contact with solid phases, (3) 58*g*.
process, of cement based building materials, (5) 118*g*.
of weak rocks, mineral formation and structure in electrochemical, B (9) 258*d*.
Hardness, of alkali halide crystals, containing ion impurities, (3) 82*h*.
of borides, at 1625°C, (5) 136*i*.
of common oxides, temperature dependence of, (11) 301*e*.
Hardness (*continued*)
determinations, accuracy at high temperatures, (11) 313*c*.
of glazes, determination of, (8) 218*j*.
high temperature, of WC, TiC, TaC, NbC and their mixtures, (6) 152*f*.
micro-, anisotropy and slip in single crystal tungsten disilicide, (5) 138*d*.
micro-, in Na_2O-ZrO_2-SiO_2 glass, (1) 4*h*.
microindentation, of silicate glasses and their atomic significance, (2) 32*d*.
and scratch, testing on broken glass surfaces in vacuum, (6) 148*i*.
Health. See also *Air, pollution; Dusts; Silicosis*.
possible hazard, radon leakage as, (1) 12*h*.
Heat. See also *Conductivity, thermal; Temperature*.
balance, calculations for tunnel kiln, (10) 282*b*.
balance, new approach for Hoffmann kiln, (8) 224*g*.
capacities, of $NbC_{0.705}$, $NbC_{0.825}$, $NbC_{0.910}$, and Nb_2C below 329°K, (9) 250*f*.
capacity, anomaly of U_4O_9 near room temperature, (10) 290*j*.
capacity, of iron silicides at 55° to 300°K, (10) 291*b*.
conduction, of molybdenum silicides, (7) 199*j*.
conduction and transfer, (6) 161*b*.
content, estimation of liquid and vapor, (1) 21*h*.
effects, testing and evaluating for materials, (4) 114*j*.
emittance, properties of materials, (2) 54*g*.
exchange, process in bottom of pot furnace, (4) 93*d*.
simplified means to calculate in tank furnace, (4) 95*f*.
in vacuum flasks, (8) 209*b*.
in zonal glass furnace, (9) 233*f*.
exchanger, graphite-plate, P (4) 100*d*.
refractory, P (8) 217*g*.
refractory, and process for making, P (7) 189*j*.
flow, calculator to solve steady-state problems, (4) 99*a*.
flow phenomena, in glasses under surface tension, (8) 208*j*.
flue-gas, utilization in glass furnaces, (10) 264*g*.
of formation, of barium selenite, (9) 250*f*.
of fluorapatite, hydroxylapatite, and tricalcium phosphates, (5) 136*i*.
of tantalum carbide, (1) 22*c*.
thermochemical methods to determine, B (6) 175*g*.
protection, apparatus for hypersonic aircraft, P (11) 296*b*.
recovery for glass industry, rotary regenerative waste, (6) 148*h*.
resistant, glass pipe, (10) 265*a*.
-resistant, whiteware, production of, (6) 156*g*.
storage, novel method with off-peak electricity and lime-water reaction, (6) 163*i*.
transfer, calculation in glass casting machine, (10) 264*g*.
by conduction and radiation in materials, (1) 22*c*.
effect of variable properties with forced convection, (4) 93*b*.
in incompressible viscous fluid between two concentric rotating spheres, (1) 22*d*.
problems, solution of, (8) 223*e*.
radiative in absorbing, emitting, and scattering media, (1) 24*e*.
thermodynamic methods applied to, (7) 197*g*.
through solid disperse systems, (6) 167*i*.
in UO_2 fuel elements, effect of internal thermal radiation on, (3) 67*i*.
treating, building materials, (4) 98*g*.
treatment, effect on crystallization of glasses in system SiO_2-Al_2O_3-ZnO, (6) 147*h*.
effect on elastic properties of glasses, (6) 147*j*.
effect on silicate glass, (7) 179*i*–180*b*.
effect of tensile stress on glass fibers, (2) 31*h*.
of silica gel, effect on properties of high-silica foam materials, (6) 147*b*.
of tungsten carbide-cobalt alloys, (3) 67*c*.
of vaporization, correlation of latent, (1) 19*i*.
of wetting of clay, effects of drying and heating pretreatments, (4) 111*h*.
Heat conductivity. See *Conductivity, thermal*.
Heaters. See also *Thermoelectricity*.
cathode, with coating of aluminum oxide and tungsten, P (7) 179*c*.
infrared, P (5) 132*f*.
infrared, gas fired, P (4) 108*e*.
pre-, high temperature, (2) 46*f*.
water, method to assemble lined, P (11) 296*d*.
Heating. See also *Thermoelectricity*.
dielectric, high frequency, (8) 224*h*.
electric booster, to intensify work of glass tank furnaces, (4) 94*a*.
electron beam, as research tool, (5) 135*j*.
element, electrical resistance, P (8) 224*h*.
element, sintered resistance body for, P (11) 303*h*.
gas-electric, in tank furnaces for glass container production, (9) 235*h*.
of glass, structural shear formation during, (1) 5*c*.
of glass furnaces, with gas, (10) 265*f*.
of glass museum pieces, danger of, (4) 89*i*.
induction, for melting above 2000°C, (2) 53*e*.
installations, heat resistant electrical insulating coatings for steel tubes in, (6) 145*h*.
means, of refractory materials, P (7) 188*d*.
pre-, of clay products increases kiln output, (4) 98*e*.
radiation, theory of thermal shock resistance of semitransparent ceramics under, (3) 86*i*.
rates, anomalous surface, (9) 246*f*.
Heating elements. See also *Electrodes; Thermoelectricity*.
electrical, with improved aluminum oxide coating, P (3) 73*d*.
Heavy clay industry. See *Structural clay products industry*.
Hectorite, crystal chem stry, and thermal behavior, (3) 80*h*.
study, by microscopy and electronic microdiffraction, (8) 227*f*.
Helium, adsorption, by carbonaceous solids, (4) 109*i*.
diffusion through silicate glasses, effect of oxides on, (7) 181*g*.
permeation, through electron tube glasses, (1) 4*b*.
separation apparatus, P (11) 298*d*.
solubility, in UO_2, (6) 153*i*.
Hematite. See also *Iron, oxide, ferric*.
crystals, neutron diffraction measurements on pure and doped synthetic, (3) 84*a*.
diffusion of Fe in, (11) 318*i*.
doped with Ti or Ca, electrical conductivity and reduction to magnetite in CO/CO_2 mixtures, (5) 135*e*.
Heterogeneity, in glass, comment on "Assessment" of, (9) 233*a*.
Homogeneity, of glass, apparatus to control, (9) 232*i*.
of glass, batch, improved control method, (4) 93*e*.
measurement to characterize output of tanks, (3) 61*b*.
method to determine, (8) 209*g*.
new method to determine and control, (7) 181*b*.
in-, effect on viscosity and flow homogenization of glass melts, (5) 120*i*.
formation during melting process, (4) 93*h*.
in glass, analyzer to identify, (9) 235*g*.
microin-, determination by refractive index distribution in glass, (8) 210*f*.
region of chromium disilicide, boundaries of, (11) 314*d*.
of small-scale laboratory glass melts, (3) 61*g*.
Honeycomb, glass, P (11) 299*c*.
structure, P (11) 304*d*.
Hot tops. See *Refractories*.
Humidity. See also *Moisture; Water*.
adjustable, in carbonation chamber, (6) 144*h*.
measurements, errors in, (10) 281*b*.
resistance tester, P (10) 281*g*.
system, inlet-gas for electrostatic precipitator, (5) 118*j*.
Hydrates, calcium aluminate, (7) 177*j*.
calcium aluminoferrite, properties of, (11) 294*c*.
of potassium oxide and potassium borohydride, fusibility diagram in system of, (4) 111*e*.
of zirconyl, thorium, and uranyl perchlorates, thermal studies on, (8) 228*b*.
Hydration, of α-alumina, (9) 250*c*.
behavior, of ferrite phase in cement, (3) 58*g*.
of β-$CaSO_4 \cdot 1/2H_2O$, during first 7 days, (8) 207*d*.
of $3CaO \cdot Al_2O_3$, (6) 165*f*.
of $3CaO \cdot Al_2O_3$, calorimetric studies on, (2) 28*j*.
of calcium sulfate plaster slurries, effect of impurities and additions on, (11) 293*j*.
of cement, during heat treatment, (10) 262*c*.
of cements, at 20°, 5°, and 1°C, (1) 2*f*.
of dolomitic lime, (10) 262*j*.
kinetics, of α- and β-calcium sulfate hemihydrates, (7) 200*f*.
kinetics, of cement in concrete at elevated temperatures, (9) 231*d*.
nature, of exchange cations in clay minerals, (3) 83*j*.
of portland cement, heat of, (11) 294*e*.
resistance, of periclase brick, (8) 215*i*.
of trivalent cations of lanthanides, change in thermodynamic functions on, (4) 109*j*.
Hydraulic, of molten glass, modeling in relation to output, (10) 265*j*.
properties, rapid method to determine for granulated blast-furnace slags, (8) 207*e*.
Hydrides, of La and Nd, properties of, (4) 113*d*.
Hydrochloric acid, -2-ethylhexanol system, solvent extraction studies with, (3) 76*g*.
Hydrofluoric acid, decomposition, of rocks and minerals by, (3) 76*d*.
solubility of ZrO_2 in, as determination of glassy phase in refractory glass tank blocks, (6) 153*j*.
38 to 40%, investigation of composition of the precipitates formed by decomposition of silicate rocks in, (7) 200*d*.
Hydrogen, in α-quartz, (5) 137*e*.
compatability of Ta and Nb alloys with, (8) 207*j*.
diffusion, in fused quartz, (4) 110*h*.
in gases, monitor for, (9) 245*b*.
in glass, diffusion of, (5) 120*e*.
HCl and H_2SO_4, reactions of reactor-irradiated uranium monocarbide with water and, (3) 68*h*.
ions, thermoelectric powers and entropies of, (3) 87*e*.
lead silicate glasses in, effect of oxides on reduction of, (4) 93*f*.
in MgO, trapped hole center, (5) 137*e*.
mobility, and mechanical properties of clays, (7) 201*e*.
stability of alumina and zirconia in, (1) 10*a*.
sublimation of aluminum oxide in, (2) 52*c*.
systems. See *Systems*.
Hydrogen ion concentration, under pressure and at high temperatures, glass electrode measurement of, (5) 131*i*.
Hydrolysis, acids, obtained in production of TiO_2, process for the working up, P (1) 19*b*.

Hydrolysis (*continued*)
of niobium pentachloride and tantalum pentachloride, (11) 317*b*.
of UC, in aqueous solution, B (6) 172*h*.
between 25° and 100°, (7) 200*f*.
10%Fe, electrochemical aspects of, (10) 285*f*.
Hydrothermal experimentation, gel preparation of starting materials, (1) 21*g*.
Hydrothermal process, to grow corundum, (9) 244*g*.
Hydrothermal synthesis. See *Synthesis*.
Hydroxides, ferric, in separation of ^{140}La from ^{140}Ba-^{140}La mixtures, (4) 170*c*.
Hygrometers, electrical, P (7) 195*c*.
hair and wet/dry-bulb, techniques for accuracy, (10) 281*b*.
Hysteresis, torsional, in plastic clay and its interpretation, (1) 13*b*.

Ice, crystals, void formation by nonbasal glide in single, (9) 258*a*.
Ignition, behavior, of powders, (3) 67*e*.
Ilmenite, and similar ores, reduction of, P (3) 79*c*.
Immiscibility, metastable liquid, in alkali metal oxide-silica systems, (3) 83*e*.
Impact, apparatus, centrifugal, P (4) 109*c*.
loads, setup for applying, (2) 45*b*.
tester, drop hammer, P (10) 281*g*.
Impurities, carbonaceous and feldspar, effect on quality of silicate concrete, (9) 230*h*.
content, of synthetic quartz and its effect on mechanical *Q*, (6) 168*a*.
diffusion, dislocation enhanced, (3) 80*j*.
diffusion, in semiconductor melt, (11) 304*i*.
distribution, in amethyst, (3) 86*g*.
distribution, in MgO, (10) 286*h*.
effects, relation in crystal growth to pH of solution, B (11) 319*h*.
in gelatin and alumina, analysis of, (9) 245*g*.
nonuniform distributions, in Y Al garnet single crystals, (3) 84*c*.
in solid materials, method to extract, P (11) 312*f*.
substitutional, interpretation of infrared spectrum of α-quartz in the 3μ region on basis of modes due to, (9) 251*d*.
trace, determination in electrocast refractories, (7) 186*c*.
Indexes, flotation for 1964, B (2) 55*d*.
indexing, graphical method for X-ray powder diffraction patterns, (7) 195*a*.
Index of refraction. See *Refractive index*.
Indium, Al, and Ga, analysis of mixtures by solvent extraction and gas chromatography, (2) 43*i*.
antimonide, distribution of Zn in, (9) 249*j*.
antimonide crystals, method to lower surface recombination velocity, P (1) 14*i*.
Sb, high pressure transition in, (1) 22*d*.
Sb, surface inversion and accumulation of anodized, (10) 291*d*.
arsenide, interaction with Ge, (11) 317*h*.
iodide, systems. See *Systems*.
selenide, systems. See *Systems*.
sulfide, vapor pressure, (2) 53*f*.
-Te, properties of thin films containing 50 to 60% Te, (9) 254*d*.
systems. See *Systems*.
trichloride, systems. See *Systems*.
Infrared, detection, method for forming *pn* junctions in indium antimonide with special application to, P (2) 42*a*.
detectors, thermoelectric cooling, (2) 40*j*.
optical constants, of glasses, (3) 61*j*.
radiation, of refractory materials, (1) 9*f*.
reflectivity, of ferrimagnetic oxides, (6) 158*a*.
region, in Na_2O-ZrO_2-SiO_2 glasses, reflection spectra in, (1) 4*i*.
sensing, of temperature of transparent objects, (7) 195*g*.
sensors, in glass melting control, (8) 209*e*.
sodium silicate glasses in, study by thin films, (3) 62*j*.
study, of mixed-layer clay minerals, (9) 250*j*.
transmission, of telluride glasses, (6) 148*b*.
Infrared absorption. See *Absorption*.
Infrared spectra. See *Spectra*.
Inspection. See *Quality control*.
Instability. See *Stability*, in-.
Instruments. See also specific types.
acoustic particle counter, (8) 222*h*.
air permeability apparatus, calibration to determine specific surface, (8) 222*j*.
analyzer, to determine fluoride in natural waters, (11) 309*h*.
to cleave crystals, (10) 280*h*.
for crystallographic study at high temperature in controlled atmosphere, (8) 223*d*.
defectoscope, ultrasonic, (10) 281*d*.
to determine surface area and pore volume, P (10) 281*h*.
dielectric test cell, to study conduction processes in insulating liquids and solids, (11) 310*c*.
for DTA of materials at high temperature, (8) 224*a*.
dipping electrode electrical conductance, for use to 1700°C, (11) 310*b*.
in enamel R & D, (6) 145*i*.
Enslin apparatus, investigations with, (9) 245*c*.
flowmeter, spectrometer as for vacuum processes, (9) 245*j*.
high-temperature compressive deformation, (6) 162*d*.
improvements, for structural cement testing, (3) 59*e*.
konimeter, to measure dust, (10) 280*i*.
mercury volumenometer, (6) 162*d*.
to monitor hydrogen in gases, (9) 245*b*.
plasma arc jet, hottest thing in testing, (5) 131*e*.
Instruments (*continued*)
quartz crystal monitors, to determine thin film densities, (10) 281*d*.
reflectometer, to determine absolute hemispherical spectral reflectance, (11) 310*i*.
rotating-needle stage, to determine light indices of transparent minerals, (5) 131*h*.
simple, for trimming thin sections, (6) 163*e*.
stroboscopic illuminator with TV camera, to observe pattern from spray nozzle, P (11) 311*b*.
to test glass in torsion and tension, (7) 180*j*.
thermobalance, automatic substitution with graphic recording and digital indication, (8) 222*j*.
Insulating material, calcium silicate, method to cure, P (4) 101*a*.
thermal, means to determine conductivity, (1) 7*e*.
Insulation, acoustical, P (1) 7*c*.
glass fiber containing sheets for, P (9) 237*e*.
of glass and glazing, (4) 95*a*.
porous, refractories as, (2) 37*b*.
refractory, very light and application of, (7) 188*e*.
tile, of molded mineral fiber, P (7) 189*a*.
Insulation, electrical. See also *Dielectrics; Glass; Porcelain*.
coating, for steel tubes in heating installations, (6) 145*k*.
coating, for wire, P (10) 263*h*.
glass composition, and apparatus encapsulated therewith, P (3) 73*b*.
of high voltage across solid insulators in vacuum, (10) 277*b*.
interaction between metals and ceramics at high temperature, B (11) 320*g*.
members, and process to produce, P (8) 221*d*.
processes, instrument to study in liquids and solids, (11) 310*c*.
sintered mixture of magnesia and vanadium pentoxide as, (4) 102*j*.
Insulation, thermal. See also *Fibers, glass; Mineral wool; Refractories, insulating*.
P (10) 273*j*; 274*a*.
and ablative structure, and method of making, P (1) 11*f*.
assembly and package, P (4) 97*a*.
brick, comparison of Austrian and foreign as, (2) 35*b*.
of calcium silicate and method of producing, P (4) 100*e*.
foamed, P (3) 70*e*.
foamed zirconia as, P (3) 70*h*.
in glass melting furnaces, (9) 246*h-g*.
new, (4) 114*j*.
panels, method to produce glass envelope type, P (7) 184*j*.
refractory, for high temperature, (6) 153*e*.
refractory, very light and application of, (7) 188*e*.
Insulators, electrical, of alumina porcelain, P (4) 103*a*.
barrier effect, P (10) 277*h*.
with blue titania layer, P (6) 159*b*.
ferrimagnetic, low temperature thermal conductivity of, (9) 242*j*.
forsterite porcelain, relation of microstructure to thermal expansion and electrical and mechanical properties, (8) 219*i-j*.
grinding to shape, (8) 219*d*.
high-frequency, reduced pressure sintering of MgO as, (10) 290*f*.
high-frequency, sintered mixture of magnesia and beryllia as, (11) 305*a*.
high strength porcelains for, (9) 241*h*.
high tension, made by Gladding Insulator Co., San Jose, Calif., (2) 39*a*.
porcelain, microstructure studies by electron microscope, (11) 304*d*.
porcelain, nondestructive determination of mechanical strength of, (11) 304*c*.
production and control of hardened glass for line suspension, (7) 181*d*.
at room temperature, ultrasonic attentuation in, (8) 220*h*.
solid, surface conductivity and flashover in, (10) 277*b*.
steatite, long rod, (9) 241*i*.
Interferometry, study, of domain structure in ferroelectric barium titanate, (3) 82*f*.
study, of single crystals of barium titanate, (3) 82*h*.
Intermetallic compounds, strength and brittleness, sources in, B (2) 55*h*.
Iodides, of phosphorus, Lewis basicity and structure, (3) 83*c*.
Ions. See also *Cations*.
Ca, as network formers in soda-lime glass, (10) 266*b*.
Cr^{2+}, Jahn-Teller distortion induced in spinels by, (10) 287*e*.
Cr^{2+}, in MgO, microwave ultrasonic paramagnetic resonance of, (7) 201*e*.
bombardment, of glass, (9) 233*g*.
bombardment, to prepare TiO_2 for transmission electron microscopy, (9) 253*e*.
chromous, in spinel solid solution series $FeCr_2O_4$-$MgCr_2O_4$, (2) 50*b*.
content, relaxation loss in ferrites as function of ferrous, (4) 104*d*.
distribution, problem in silicates, (3) 79*f*.
exchange, between alkali metal cations and sodium aluminosilicate gel, (10) 287*j*.
constants of glass by electrode method, (7) 180*f*.
to determine SO_3 in gypsum and cement, (4) 90*f*.
in extraction of soda-lime glasses with dilute salt solutions, (6) 148*c*.
and hydrated volume of cation in silicates, (8) 227*d*.
in sedimentary zeolites, (5) 141*a*.
Ions, exchange (*continued*)
using organic-hydrochloric acid systems, preconcentration of trace elements by precipitation, (2) 45*a*.
Fe^{3+}, in spinel structure, (10) 289*a*.
ferric and ferrous, simultaneous precipitation from solution of, (9) 253*f*.
hydrogen, thermoelectric powers and entropies of, (3) 87*e*.
impurities, hardness of alkali halide crystals containing divalent, (3) 82*h*.
ionic crystals, conduction and diffusion in, B (9) 259*e*.
ionic forces, effect on constants of instability of complex compounds, (5) 137*i*.
manganic and ferrous, resonance relaxation in $Mn_xFe_{3-x}O_4$ by slow relaxing, (9) 254*i*.
metal, solvent extraction with trifluoroacetylacetone, (3) 76*f*.
migration, effects in SiO_2, (9) 253*f*.
mobile, function in glass, (7) 180*j*.
neodymium, bombarded CdS, (10) 288*g*.
N, catalytic efficiency of Pyrex glass for recombination of, (8) 208*j*.
oxygen, activity in sodium silicate melts, (10) 265*j*.
oxygen, activities in sodium silicate and sodium borate melts, (1) 19*g*.
paramagnetic, phonon scattering in MgO by, (8) 226*g*.
polarization properties, significance for developing fusible glasses, (4) 95*c*.
polymer, vibrational spectrum of, (2) 53*h*.
positive impurity, from α-quartz, (9) 253*d*.
rare earth, photometric determination of, (8) 223*k*.
-sputtered coatings, as finishes, (3) 72*f*.
Tm^{3+}, Ho^{3+}, Yb^{3+}, and Er^{3+}, oscillations from in Y Al garnet, (10) 284*a*.
trapping, and gas release phenomena, (4) 112*a*.
U, in acid solutions, formulas of sexivalent and quadrivalent, (7) 201*h*.
U^{3+}, U^{4+}, and UO_2^{2+}, in NaCl-KCl melt, diffusion coefficients of, B (1) 26*a*.
V, properties of Ti sesquioxides containing, (10) 290*c*.
Iridium, IrO_2, phase relations with Cr_2O_3 in air, (6) 169*e*.
Iron. See also *Enameling metals; Steel*.
absorption, in silicate and borate glass, (3) 61*e*.
acceptor level, temperature dependence in GaAs, (10) 291*i*.
and aluminum, determination by solvent extraction and gas chromatography, (6) 161*i*.
atoms in silicides, atomic interaction and inner electron state of, (11) 313*i*.
carbide, identification of Eckstrom-Adcock as Fe_7C_3, (7) 200*a*.
carbonates, products of thermal dissociation of solid solutions of, (1) 23*b*.
cast-, bubbles and pinholes in enamels for, (3) 59*g*.
chloride, interaction with Sn chlorides, (1) 22*e*.
chloride, oxide film from, (1) 5*b*.
compacts, magnetic properties of those containing P, (6) 158*e*.
content of chlorite, relation between magnetic susceptibility and Mn plus, (3) 85*b*.
diffusion, in hematite, (11) 318*i*.
in enamels, effect on whiteness, (2) 30*d*.
ferric, systems. See *Systems*.
ferrous, method to determine in rocks and minerals, (10) 281*g*.
ferrous, silicate, systems. See *Systems*.
ferrous-ferric, equilibrium in alkali silicate glasses, (3) 61*e*.
films, ferromagnetic resonance in single-crystal, (2) 50*c*.
films, technique to prepare single-crystal on sodium chloride substrates, (4) 104*e*.
(II) fluoride, sublimation pressure of, (9) 251*i*.
formations, $^{18}O/^{16}O$ ratios of minerals from Quebec, (1) 23*d*.
in glass, effect of decolorizers on oxidation of, (4) 92*j*.
glaze, red, for hard oxidizing firing, (4) 102*e*.
Fe^{2+}, Fe^{3+}, and Zn^{2+}, precipitation from solution containing, (9) 253*h*.
Fe^{2+}-Mg^{2+}, order in an orthopyroxene, $Mg_{1.33}Fe_{1.67}Si_2O_6$, (7) 201*c*.
Fe^{2+}, effect on polymorphism of tricalcium silicate, (2) 49*d*.
ions, effect on tetrahedral sites on magnetic properties of $ZnFe_2O_4$, (9) 250*c*.
ions in spinel structure, (10) 289*a*.
Fe-C solid solutions, thermodynamics of dilute, (5) 141*i*.
$FeCO_3$-$MgCO_3$ solid solutions, formation of magnesium ferrites in, (6) 167*e*.
$FeCr_2O_4$-$MgCr_2O_4$, existence of chromous ion in, (2) 50*b*.
$FeCr_2S_4$, study by neutron diffraction, B (2) 55*c*.
$Fe_{1-x}O$-MgO, electrical conductivity in solid solutions of, (3) 81*a*.
Fe_2SiO_4-Co_2SiO_4, solid solutions at 1180°C, activity-composition relations in, (7) 197*b*.
Fe_3W_3C, double carbide, preparation of, (2) 51*e*.
Mg-Fe-O alloys, solid solution and precipitation hardening in, (6) 169*j*.
-magnesium ratio, X-ray determination in biotites, (7) 203*h*.
Mn-Zn ferrite, with rectangular hysteresis loop, (6) 158*k*.
metallic, determination in slag, (9) 246*d*.
metallic, mechanism of dissolution in molten glass, (4) 94*g*.
molten, mechanism of change in properties of siliceous refractory mortar in, (10) 271*i*.
molten, reactions with MgO crucibles under reduced pressures, (6) 153*c*.

Iron (*continued*)
-Nb oxides, phase relations at 1180°C, (5) 136*g*.
oxidation, scanning electron microscopy applied to, (5) 140*e*.
oxide, α-, magnetic properties of single crystals, (4) 103*j*.
α-, memory effect in, (10) 286*e*.
α-, parasitic ferromagnetism of, (10) 286*e*.
α-, residual magnetization at low temperature transition in, (10) 277*f*.
α-ferric, electrical properties of that containing Mg, (4) 111*b*.
-bonded magnesia clinker, comparison with SiO_2-bonded, (7) 185*j*.
density of liquid in noble gases and N, (5) 134*i*.
ferric, dissolving excess in NiZn ferrite, (4) 110*a*.
ferric, preparation of sols and sol particles, P (10) 283*d*.
ferric, reaction with MgO and its effect on sintering of MgO, (5) 140*g*.
ferric, systems. See *Systems*.
ferric, and zinc oxide, solid reaction between, (4) 113*j*.
ferric crystals, production of gamma-, (8) 225*b*.
ferrous, crystal distortion on cooling past its Néel temperature, (10) 284*a*.
films, conditions of formation on rolled glass, (10) 266*e*.
grain growth of magnesium oxide containing, (2) 50*f*.
in MgO, magnetic susceptibility of solid solution of, (4) 112*j*.
magnetic acicular gamma, P (11) 306*j*.
migration in basic refractories, (10) 272*g*.
pigments, P (10) 283*a*.
on porous π-alumina, silica, and silica-alumina, Moessbauer effect for, (1) 23*a*.
process to produce with low silica content, P (5) 133*j*.
reactions with magnesia, (9) 238*i*.
in sheet glass, determined by photoelectric emission spectral analysis, (3) 62*b*.
-silica melts, density of, (1) 20*d*.
systems. See *Systems*.
Tiron procedure to determine in glass, (4) 107*e*.
and its oxides, thermal expansion coefficients, (2) 53*j*.
pig, related to life of open-hearth roof, (3) 68*c*.
replacement, in $CuFeO_2$ and $NaFeO_2$, (6) 169*g*.
sheet, new ground coat enamels for, (2) 30*g*.
in silicates, spectrophotometric determination of, (2) 44*b*.
silicides, heat capacity at 55° to 300°K, (10) 291*b*.
solid, relation between diffusion of carbon in and adherence of coating, (4) 91*b*.
in spinel oxides, Moessbauer spectra of, (5) 138*g*.
sulfate, systems. See *Systems*.
systems. See *Systems*.

Irradiation. See also *Radiation*.
electron, dose estimation from glass, (10) 284*j*.
γ-, blackening natural quartz by, (11) 314*c*.
gamma ray, of quartz glass, (8) 210*i*.
of graphite, as cause of dimensional changes in lattice, (4) 110*i*.
irradiated fuel, α-autoradiographic method to examine, (3) 65*f*.
irradiated substances, dissolution processes studies, (1) 24*f*.
neutron, effect on Mo, Nb, and Zr disilicides, (5) 135*b*.
irradiated, magnesium oxide, X-ray line broadening in, (2) 54*a*.
of quartz, defect structure and density decrease in, (2) 49*e*.
thermal history of LiF crystals during, (9) 257*j*.
partial X-ray, to induce plastic flow in NaCl, (1) 24*h*.
studies, of coated nuclear fuel particles, (3) 68*c*.
ultraviolet, X, and γ, thermal glow of glasses treated by, (7) 181*j*.

Isotopes. See also *Radioactive tracers*.
radio-, diffusion in basalt, (7) 198*e*.
prospective uses in glass industry, (4) 95*b*.
results of measuring ladle erosion by, (8) 216*h*.
in X-ray emission analysis of cement raw mix, (9) 231*b*.

Jewelry. See *Art and artware*.
Joining, ceramics and glass, to metals, (2) 40*i*.
improvements in, P (9) 243*g*.
means, for parts to glass coated apparatus, P (9) 232*e*.
method, for metal parts with glass leading-in members, P (1) 14*i*.
Joints, polyurethane, for clay pipe, (4) 98*j*.
for sewer pipe, (6) 151*e*.
for sewer pipe and the like, P (7) 185*d*.
Junctions, area, reduction of semiconductor, P (9) 243*f*.
device, semiconductor *pn*, P (11) 308*a*.
np and *pp*, examination of complex xerographic layers in, (6) 167*d*.
passivation, semiconductor material for, P (6) 160*i*.
pn, diamond-cubic boron nitride, P (10) 278*d*.
direct measurement of depletion layer width variation vs. applied bias for, (10) 284*f*.
formation in Si, P (11) 306*e*.
method to form, P (9) 243*j*.
photoelectric properties of CdTe, (3) 84*b*.
on semiconductor, P (9) 243*e*.
simultaneous fabrication of plurality of semiconductor, P (11) 307*d*.
in $ZnSe_xTe_{1-x}$, visible injection electroluminescence from, (10) 285*i*.
Si rectifying, for electric power, P (11) 308*b*.

Kaolin, (6) 164*b*.
ammonium chloride-, structural and bonding features, release of interlayer NH_4Cl, (9) 248*a–b*.
bodies, of increased density for glass pot refractories, (6) 152*j*.
Brazilian, (2) 46*g*.
Chinese, increasing ≡Si—OH surface groups in, (5) 137*h*.
clay, beneficiation, P (3) 78*j*.
coarse, continuous attrition grinding of, (5) 133*a*.
deposit, of Georgia, (3) 77*j*.
deposits, in Poland, (7) 196*j*.
elasticity, in relation to their heat treatment, (10) 282*g*.
fine fractions, study with supercentrifugal dispersion analysis, (2) 45*c*.
OH groups in, B (2) 56*c*.
inner structure, shrinkage between 600° and 1200°C, (9) 255*b*.
kaolinitic clays, high-temperature phase changes in, (5) 137*b*.
Korean, effects of metallic oxides or salts on erosion resistance of, (6) 152*j*.
-lime-water, microtexture and composition of reaction products in, (8) 226*j*.
of Mad-Kiralyghegy, Hungary, preparation of lean and study of the slip, (2) 47*c*.
minerals, intercalation of water in, (6) 168*g*.
minerals, mullite formation from, (4) 111*d*.
molecular sieves, synthesis of, (2) 47*g*.
nitriding of, (6) 153*g*.
from northeastern Brazil, properties of, (2) 47*b*.
raw, of Sedlec (Zettlitz) near Karlsbad, (1) 18*h*; (2) 47*d*.
rose, from Fazenda Floresta, Brazil, physicochemical properties of, (11) 312*g*.
slips, new coagulants for, (6) 156*c*.
suspensions, factors effecting dilation, (7) 190*g*.
systems. See *Systems*.
testing, to determine its suitability for bodies, (6) 162*d*.
treating, P (8) 225*e*.
type silicates, stacking faults in, (7) 202*e*.
of the Valencia region, B (4) 115*b*.
-water suspensions, viscosities with additions of basic aluminum chloride complex, (5) 127*i*.
Kaolinite, autoclaved, to form coagulation structures, (3) 81*i*.
crystals, rolling to halloysite-like tubes and difference between halloysite and tube-shaped kaolinite, B (2) 56*c*.
dehydroxylation of, heats of reaction and kinetics of dehydration, (6) 166*b*.
group minerals, order and disorder of, (7) 201*e*.
high shear viscosity, method to reduce, P (11) 312*d*.
meta-, state, recent evidence for, (6) 169*d*.
physical factors, effect on DTA of, (1) 20*e*.
reaction with calcium oxide, (6) 169*j*.
synthetic, high-temperature transformations of, (11) 317*j*.
systems. See *Systems*.
thermal decomposition, from standpoint of solid phase reactions, (8) 227*i*.
Keramzit, production, plant layout for, (11) 294*i*.
Kiln furniture, cordierite, from fireclays and magnesite, (6) 152*a*.
materials for, (2) 36*j*.
saggers, standardization for porcelain flatware, (2) 39*j*.
setting and shapes of, (3) 69*b*.
support, for mounting glazed ware for firing, P (10) 275*a*.
Kilns. See also *Burners; Furnaces; Ovens*.
car engineering, cost reduction through, (6) 163*g*.
cars, comparison of various settings for, (5) 125*e*.
cement, effect of dust from on vegetation, (11) 294*g*.
and refractories, (9) 237*j*; (10) 270*f*.
temperature probe for, P (11) 294*j*.
construction, trends, (3) 77*f*.
continuous, P (7) 195*h*; P (10) 282*b*.
with movable plate, for structural clay products, P (8) 224*f*.
theoretical design problems of, (2) 46*f*.
crown structure, ancient, (2) 28*d*.
electric tunnel, (6) 163*h*.
to fire hard porcelain in reducing atmosphere, (8) 224*d*.
for high temperatures, (2) 46*e*.
equipment for burning refractory products, P (4) 108*g*.
fans for, design of high temperature, (8) 224*c*.
fast-firing, development of, (2) 46*c*.
firing, and controlling above 3000°F, (7) 195*f*.
furnace section for, P (2) 46*d*.
gas, new for studio use, (9) 230*e*.
gun projectile for, P (5) 132*g*.
heat, detection of excess, (11) 311*f*.
high-temperature, P (4) 108*e*.
for industrial loads, (8) 224*g*.
oil-fired, (2) 46*e*.
Hoffmann, new approach to heat balance of, (8) 224*g*.
linings. See *Refractories*.
moving-envelope, at Jackson China, (1) 12*j*.
new, for open glaze firing, (7) 195*g*.
oil fired, (1) 17*j*.
output, increased by preheating clay products, (4) 98*e*.
rapid firing, (8) 224*f*.
rapid firing, for single layers of articles, P (11) 311*g*.
rotary, P (8) 224*i*.
automatic burner control system for, P (5) 132*f*.
calcining, P (11) 295*b*.
cement, behavior of high alumina brick in, (1) 2*b*.

Kilns, rotary (*continued*)
drive mechanism for, P (9) 246*i*.
with exchanger system, effect of draft conditions on, (11) 311*f*.
lining for, P (7) 196*d*.
material ring removal, P (3) 77*g*.
mechanism and rate of passage of materials in, (4) 108*c*.
and method of freeing of fire ring in, P (3) 77*h*.
refractory structure for, P (4) 108*f*.
shaft, P (7) 196*a*.
thermostat, for shut-off, P (7) 196*a*.
tile, development of design, (2) 46*c*.
top-hat, (8) 224*j*.
tunnel, P (10) 282*g*.
automatic for art porcelain, (9) 246*h*.
combustion characteristics for oil-fired, (2) 46*b*.
control board for, P (8) 224*f*.
control of firing cycle in, (2) 46*b*.
cuts cost and boosts production of brick, (9) 237*g*.
firing of electrical porcelain in, (3) 71*f*.
for firing miniature parts, (5) 132*e*.
gastight ceiling, P (9) 246*h*.
heat balance calculations and design modifications for porcelain kilns, (10) 282*b*.
improves beryllia product, (8) 219*b*.
operation, design, and selection of refractories for high temperature, (10) 282*d*.
planning and construction of, (6) 163*j*.
protective clothing to wear in hot, (3) 77*e*.
results in development of top fired, (2) 46*c*.
salt glazing in, (10) 276*c*.
system, P (7) 196*b*.
zircon bricks in glost, (2) 37*i*.
vertical, and method to prepare calcined products, P (9) 231*e*.
vibratory, P (7) 196*c*.
Kinetics, of coagulation, solutions to equations for, (4) 113*b*.
of corundum crystallization, (5) 137*j*.
dehydroxylation reaction, of Indian kaolinitic clays, (2) 49*g*.
and mechanisms, of fining glasses, (9) 233*i*.
reaction, of formation and sulfating of Cu ferrite, (9) 254*a*.
of reaction, of $SrTiO_3$ formation, (10) 287*a*.
of sintering, initial phase from standpoint of theory of absolute reaction rates, (4) 113*i*.
of sintering, mathematical-phenomenological study of, (5) 141*g*.
Kyanites, -silimanite, equilibrium at 750°C, (5) 138*c*.

Laboratories. See also *Research and research laboratories*.
apparatus, progress in glass chemical, (5) 131*f*.
Ladles. See *Refractories*.
Lamps. See also *Glass*.
aperture fluorescent, P (3) 72*e*.
arc, self-starting, P (11) 307*d*.
arc, as solar simulator, P (11) 308*c*.
base end structure for, P (8) 220*j*.
bent end electric, with lead wires anchored at ends of bend and provided with expansion portion, (5) 128*h*.
coating, fluorescent panel, P (7) 193*a*.
colored, bulb, P (9) 243*h*.
envelope, P (8) 212*f*.
sealed beam, P (11) 297*i*.
discharge, P (7) 192*e*.
electric, P (6) 158*j*.
electric high pressure of high luminous intensity, P (2) 41*e*.
electric, with integral pressure regulator, P (4) 104*e*.
electric, metallic halide, P (5) 128*j*.
high pressure metal vapor, P (4) 105*a*.
metal halide with near molten tip electrodes, P (9) 243*h*.
electric, P (9) 243*c*; P (10) 278*d*.
apparatus to make, P (4) 96*g*.
decorative, with specular coating, P (2) 33*f*.
filament or discharge tube, apparatus for evacuating, P (5) 128*f*.
filament support, P (11) 298*b*.
with fuse, P (11) 305*i*.
method of making, P (2) 42*b*.
with single ended pinch seal, P (11) 298*c*.
electrode, starting of high temperature, P (9) 244*e*.
electroluminescent, with built-in terminals, P (8) 221*a*.
with dielectric reflective material, P (2) 41*i*.
increasing light emission, stabilization, and rejuvenation, P (2) 42*d*.
and manufacture of, P (6) 159*e*.
filaments, method to form Ta carbide coated coiled, P (5) 129*b*.
fluorescent, annular, P (11) 297*c*.
halophosphate phosphor material for, P (8) 221*c*.
panel, P (4) 104*g*; P (8) 221*b*.
panel, with opaque striped faceplate, P (6) 159*h*.
with phosphor coating of platelike crystals, P (6) 159*g*.
reflector, P (11) 307*b*.
gas-discharge, sorption of Ar by glass in, (9) 234*f*.
gaseous discharge, P (10) 278*i*.
hollow-cathode discharge, for emission of atomic resonance lines, P (6) 159*j*.
incandescent, P (1) 6*g*; P (7) 192*f*; P (8) 220*f,g*; P (11) 299*d*.
apparatus for making microminiature, P (4) 96*h*.
baseless double-ended, P (10) 277*i*.
containing iodine, O, and inert gas, P (6) 159*a*.

Lamps, incandescent (*continued*)
discharge, glass for, P (8) 221*b*.
gas-filled electric, P (5) 128*f*.
with integral fuse, P (1) 6*g*.
iodine-containing with heat conserving envelope, P (2) 41*k*.
iodine cycle, P (6) 159*c*.
miniature, P (10) 267*g*.
for projectors, P (10) 268*f*.
tipless double-ended, P (1) 6*g*.
tubular, P (10) 279*k*.
infrared calibration, P (3) 73*f*.
manufacture, electroluminescent, P (4) 104*e*.
panel, with inlead structure with notched edge for lead-in conductors, P (5) 129*c*.
seal for, P (6) 150*f*.
with terminal bases, P (8) 221*f*.
photoflash, P (10) 279*g*.
seal and base, for high pressure quartz discharge, P (2) 41*d*.
sodium vapor, high pressure, P (7) 193*d*.
sodium vapor, with tin oxide coating, P (3) 64*i*.
tubular, integral reflector, P (1) 6*k*.
tungsten filament, with hexafluoride gas at partial pressure not over 10 torrs, P (10) 279*h*.
vitreous member, fabricating apparatus for, P (1) 6*j*.
Lanthanides, activators, luminescence of glass with, (6) 148*f*.
cations of, change in thermodynamic functions on hydration of trivalent, (4) 109*j*.
oxidation, diffusion-controlled, (11) 315*d*.
oxyorthosilicates, infrared spectra of, (5) 137*c*.
Lanthanons. See *Rare earths*.
Lanthanum, hydrides, some properties of, (4) 113*d*.
La^{3+}, to increase capacitance of $BaTiO_3$, (8) 220*b*.
^{140}La, separation from a ^{140}Ba-^{140}La mixture, (4) 107*c*.
LaB_6, NMR method to study, (10) 289*b*.
La_2O_3, effect on crystallization of optical glass, (2) 31*g*.
$LaVO_4$, single-crystal growth and properties of, (9) 255*e*.
oxide, systems. See *Systems*.
silicates, crystalline structure of, (7) 198*e*.
-strontium maganites, magnetic properties of, (4) 112*i*.
tellurides of, (10) 291*g*.
Lapping, impact, to finish glass, (4) 93*c*.
Lasers. See also *Masers*.
action, in Nd-doped glass from energy transfer, (10) 287*c*.
-action, threshold in electron-beam excited GaAs, (10) 287*e*.
amplifier and oscillator, Nd^{3+}-YAG, P (8) 221*e*.
avalanche injection, evidence in *p*-type GaAs, (10) 286*a*.
CaF_2: Dy^{2+}, quenching of Dy^{2+} fluorescence by Y^3 in, (1) 24*e*.
crown glass, neodymium barium, (5) 139*d*.
crystals, perfection of ruby, (4) 104*b*.
element, ytterbium activated glass sensitive, P (1) 14*e*.
materials, alkaline earth halide divalent dysprosium, P (6) 158*c*.
microprobe, analysis of glass defects, (4) 94*e*.
Nd glass, with output of 9180 A, P (11) 299*i*.
Nd^{3+}-glass, polarization of light from, (10) 289*e*.
oscillations, and self *Q*-switching in activated glass, (7) 180*g*.
pressure-tuned PbSe diode, (10) 289*i*.
rods, induced-damage thresholds for glasses, (8) 209*j*.
rods, thermal effects in optically pumped ruby, (2) 53*e*.
ruby, conventional and *Q*-switched, holographic high-speed photography with, (1) 13*j*.
effect of ground state ESR saturation on output at 90°K, (11) 316*b*.
mode competition and self-locking effects in *Q*-switched, (10) 288*g*.
mode-locking effects in internally modulated, (2) 40*j*.
and Nd-glass, internal self-damage of, (10) 287*d*.
stimulated emission in a *Q*-spoiled, (1) 25*e*.
semiconductor, with optical cavity, P (7) 194*a*.
transitions, identification in electron-beam-pumped GaAs, (10) 286*g*.
ultraviolet, emission by crystal excitons, (1) 25*i*.
use, in optical second-harmonic generation, (10) 285*h*.
using internal reflection techniques, P (7) 193*f*.
using rare earth activated Y and La trifluoride active media, P (5) 128*h*.
Lattices. See *Crystals*.
Lavas, Hawaiian, chemical composition of, (7) 197*g*.
Leaching, of glasses, effect of metallic impurities on, (3) 61*b*.
of sodium borosilicate glasses, stresses originating during, (9) 234*j*.
Lead. See also *Glass; Glazes*.
activated, pyrosilicate structures, luminescence of, (7) 200*h*.
apatites, and tertiary lead phosphate, (3) 83*j*.
arsenic enamels, for thermometers, (10) 264*f*.
borate glass, microseparation in, (3) 61*e*.
borates, extinction in glasses in admixture with barium borate, (5) 121*h*.
carbonate, dehydrated and highly basic, P (4) 109*h*.
chloride, systems. See *Systems*.
chlorides and bromides, fusibility diagram of system of, (9) 250*d*.
-containing and lead-free majolica enamels, (10) 263*h*.
crystal glass, melting in tank furnace, (10) 265*h*.
dioxide activator, composition and method for forming, P (1) 18*d*.
Lead (*continued*)
fluoride, systems. See *Systems*.
glass, thermal conductivity, (2) 32*d*.
$PbCrO_4$, crystal structure of, (6) 166*e*.
PbF_2-Bi_2O_3, habit modification of corundum crystals grown from molten, (6) 167*h*.
$Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$, piezoelectric properties of solid solutions, (1) 13*h*.
$Pb_2V_2O_7$, new mineral chervetite lead pyrovanadate, (6) 169*d*.
$Pb(Zr$-$Ti)O_3$ family, temperature and bias characteristics of, (6) 158*i*.
oxide, crystal glass with low content, (7) 179*j*.
-PbF_2 melt, vaporization during solution growth of YIG crystals, (3) 87*a*.
substituted for Li_2O in glazes, (2) 39*j*.
systems. See *Systems*.
oxide-Al_2O_3, phase diagram of, (9) 252*i*.
screen, intensification factor determined by radiography, (11) 310*i*.
selenide, density measurement and disorder of, (11) 315*j*.
method to produce photosensitive layers of, P (4) 105*e*.
pressure-tuned diode laser, (10) 289*i*.
systems. See *Systems*.
selenite and oxyselenites, properties, (2) 52*c*.
silicate glass in hydrogen, effect of certain oxides on reduction of, (4) 93*f*.
sulfate, systems. See *Systems*.
sulfide, effect of hydrostatic pressure on transmission spectrum of, (6) 167*a*.
systems. See *Systems*.
Tammann's method to grow monocrystals of, B (11) 320*a*.
vapor pressure, (2) 53*f*.
systems. See *Systems*.
telluride, thermoelectric properties of films, (1) 14*d*.
titanate, effect of grain size on microcracking in, (5) 135*b*.
preparation of ferroelectric materials from, P (2) 42*e*.
-zirconate ceramics, determination of Pb, Ti, and Nb in, (7) 194*j*.
-ZnS, effect of electric field on photoluminescence of, (9) 242*f*.
zirconate, high-temperature phase transitions in, (10) 286*f*.
-lead titanate, grain growth and densification of that containing bismuth, (4) 103*i*.
-titanate piezoelectrics, modified by bismuth ferrite, (10) 277*g*.
Lenses. See *Glass, optical*.
Light, absorption, of chromium incorporated into garnet structure, (3) 80*e*.
beacon, embedded for runways, P (10) 267*e*.
-conducting devices, method and apparatus for making of glass fibers, P (5) 123*j*.
dispersion and transmission in ultraviolet, of oxidic glasses, (1) 4*e*.
lighting, modern in porcelain factories, (1) 15*j*.
output, of color TV screens with Eu-activated phosphors as red component, (8) 220*c*.
polarization of, from Nd^{3+}-glass lasers, (10) 289*e*.
prismatic, transmitting panel, P (2) 34*e*.
signals, cover glass for, P (5) 122*b*.
transferring devices, fiber type and method of making, P (4) 96*g*.
waves, continuous second-harmonic generation, (10) 285*h*.
Lime. See also *Calcium, oxide; Glass*.
calcining, world standards and trends, (2) 29*d*.
in cement raw mixes, importance in burning process, (1) 2*g*.
chemistry and technology of, B (8) 228*e*.
and chromium oxide, sintering reactions between, (4) 113*g*.
dolomitic, production and hydration of, (10) 262*i,j*.
-kaolin-water, microtexture and composition of reaction products in, (8) 226*j*.
quick, apparatus to age, P (5) 119*b*.
quick-, cold water slaker, P (3) 59*e*.
saturation, method to compute for portland cement clinker, (2) 28*h*.
suspension, effect of addition of electrolytes on rheology of, (4) 90*e*.
testing, for use in cement, (2) 29*c*.
Limestone, chemistry and technology of, B (8) 228*e*.
concrete, effect of additives on quality of dolomitic, (6) 144*d*.
containing flint, as raw material for portland cement, (2) 28*f*.
crushed, used with red mud in cement, (6) 144*f*.
environment, time-trend analysis for interpretation, (1) 25*g*.
freshwater, glass melting with, (10) 264*j*.
Illinois, thermal expansion of, (8) 225*i*.
inclusions, elimination of harmful effect in clay for structural products, (6) 151*d*.
Mg in, determination of, (10) 280*j*.
nondolomitic aggregate, reaction in concrete, (9) 231*a*.
shaker, oscillating, P (5) 133*j*.
wetting, by melting soda, (5) 122*b*.
Linings. See also *Refractories*.
Liquids. See also *Fluids*.
density, apparatus to measure, (10) 280*j*.
immersion, preparation and determination of high refractive indices of, (6) 162*f*.
immiscibility, metastable in alkali metal oxide-silica systems, (3) 83*e*.
limit, relation with shear strength of soils, (3) 85*a*.
mechanical properties of, B (5) 142*k*.
phase in fluidized bed, effect on calcium carbide nitriding, (5) 137*i*.
Liquids (*continued*)
structure of silicates as, (7) 202*j*.
Lithia. See *Lithium, oxide*.
Lithium, aluminate, systems. See *Systems*.
aluminosilicate, crystallization in glasses of, B (3) 88*g*; (10) 264*h*.
borate, systems. See *Systems*.
bromide, systems. See *Systems*.
carbonate, systems. See *Systems*.
-cesium phosphate glass, constitution of, (7) 179*i*.
chlorate, systems. See *Systems*.
chloride, interaction of pentachlorides of Nb and Ta with, (10) 287*c*.
recovery from mixtures of other salts and metals, P (10) 283*c*.
-KCl, oxides and sulfides in molten eutectic, (5) 134*d*.
systems. See *Systems*.
chlorides and bromides, fusibility diagram of system of, (9) 250*d*.
chromate, crystallographic data of anhydrous (7) 198*f*.
-Cr vanadate, crystallography of, (6) 166*i*.
disilicate glass, devitrification of, (5) 120*g*.
ferrite, sublattice magnetizations as function of temperature, B (2) 55*j*.
fluoride, crystals, formation of skeletal cavities in, B (11) 319*j*.
deformation patterns on cleavage surfaces of, (9) 253*c*.
dislocation network in crystal of, (4) 110*j*.
internal friction at low temperatures, (10) 287*d*.
NMR of decomposition in neutron-irradiated, (9) 252*c*.
optical properties in extreme ultraviolet, (10) 289*d*.
polygonization of bent crystals by Berg-Barrent method, (10) 289*f*.
production, P (6) 164*f*.
radiation effects in crystals of, (10) 290*d*.
systems. See *Systems*.
thermal history of crystals during neutron irradiation, (9) 257*j*.
layer, being diffused into substrate, method of using protective coating over, P (1) 14*j*.
$LiAlGeO_4$, phenacite-spinel transition in, (10) 289*b*.
$LiAlO_4$, (3) 83*a*.
$LiAlO_2$, γ-, crystal structure of, (7) 198*e*.
$LiCuVO_4$, antiferromagnetism of spinel, (11) 313*c*.
$LiGaO_2$, high pressure phase of, (5) 136*j*.
$LiFeO_2$, magnetic susceptibilities of, (5) 138*f*.
Li_2O-NiO, solid solution, (10) 288*i*.
$LiPN_2$, preparation, structure, and properties of, B (11) 320*e*.
Li_2ZnF_4, crystallographic data on, (7) 198*g*.
metasilicate-silica series, devitrification of vacuum-melted glasses of, (1) 3*j*.
nickel ferrite, method to make with a substantially rectangular hysteresis loop, P (4) 105*i*.
niobate, elastic wave propagation in, (10) 285*j*.
niobate, ferroelectric behavior of, (10) 286*g*.
nitrate, systems. See *Systems*.
orthoniobates and orthotantalates, crystallographic study of, (9) 249*c*.
oxide, substitution for PbO in glazes, (2) 39*j*.
oxide, systems. See *Systems*.
phosphate, systems. See *Systems*.
recovery, from brines, P (10) 283*c*.
silicate, crystallization of melts under different cooling conditions, (9) 249*b*.
glass, crystallization of, (7) 181*d*.
properties and applications of vitreous, B (4) 115*i*.
in slips, enamels, and glazes, (1) 16*c*.
Na and K, fusibility diagram of system of bromides of, (9) 250*e*.
sulfate, systems. See *Systems*.
systems. See *Systems*.
tungsten bronzes, electrical conductivity and carrier mobility in, (7) 203*c*.
Lubricants, for deep drawing, sliding frictional characteristics of, (4) 91*d*.
dry film, for cold forming of steel, (4) 91*f*.
dry film, glass bonded, P (6) 149*i*.
silicone. See *Silicones*.
solid, industrial uses for, (8) 215*b*.
water-in-oil, process to apply to hot mechanisms, P (11) 311*g*.
Luminescence, electro-, devices, P (3) 73*g*; P (10) 278*f*.
electro-, devices and materials, P (1) 14*j*.
device with moisture preventing seal, P (11) 305*c*.
in gallium phosphide crystals, (10) 285*h*.
in 4H silicon carbide, (11) 313*h*.
lighting for instruments, P (2) 41*k*.
near band gap in GaP containing shallow donor and acceptor levels, (1) 13*h*.
output device, multilayer semiconductor, P (11) 307*d*.
panel, P (5) 129*g*.
polarization reversal at low frequencies in $BaTiO_3$ crystals, (8) 226*j*.
in SiC single crystals, (10) 276*j*.
visible injection from *pn* junctions in $ZnSe_xTe_{1-x}$, (10) 285*i*.
electron-excited, as petrological tool, (1) 21*b*.
of glasses, with lanthanide activators, (6) 148*f*.
measurement, to determine processes accompanying dissolution of irradiated substances, (1) 24*f*.
photo-, of BaO, (3) 84*c*.
photo-, of ZnS-Pb, effect of electric field on, (9) 242*f*.
of pyrosilicate structures, lead-activated, (7) 200*h*.
in quartz, shock-induced, (3) 85*e*.

Luminescence (*continued*)
radio- and photo-, efficiencies of various phosphors, (11) 304*j*.
self-luminous compositions, tritium activated, P (3) 74*d*.
in solids, B (9) 259*f*.
solid solutions, of Eu compounds with at least one other rare earth compound, P (7) 193*f*.
thermo-, of commercial glass irradiated by ultraviolet, X, and γ rays, (7) 181*j*.
thermo-, relation to optical absorption on glass, (5) 120*i*.
in ZnS phosphors, decay characteristics studied by pulse light excitation, (5) 134*f*.
Luminescent materials, P (1) 14*g*.
silicate, process for preparing, P (1) 15*c*.
Lutetium, $LuMnO_3$, scandium manganese(III) oxide, a compound isotypic with, (2) 51*b*.

Machinery and equipment. See also *Materials handling* and specific types.
automatic, for tableware industry, (7) 190*j*.
for enameling, factors in purchasing, (6) 145*f*.
fair, in Switzerland, (9) 244*f*.
filtration-dessication, of solids in liquid solids mixture, P (10) 280*a*.
for glazing porcelain, (2) 39*g*.
to make foamed products, P (5) 130*g*.
for measuring contents level in silo, (1) 16*a*.
to mix, agitate, abrade, or crush, P (2) 47*b*.
for moistening clays, (2) 35*i*.
to produce dry batch, P (5) 130*i*.
to produce high pressure, P (5) 131*a*.
to reduce liquid content of material containing both liquid and solid, P (10) 280*d*.
roller machine, plastic forming by, (5) 130*h*.
suction box cover, for Fourdrinier machine, P (7) 190*i*.
for tableting, feeding apparatus for, P (4) 107*a*.
for tile, blends and discharges on conveyor, P (7) 190*h*.
tile stamper, system and device to control membrane on, P (7) 191*b*.
transfer machine, (8) 222*e*.
vibratory bin activator, P (9) 245*a*.
for wet preparation of plastic bodies, (10) 280*c*.
wire belt, counterweight adjustments related to life of woven, (8) 222*d*.
Magnesia. See *Magnesium, oxide.*
Magnesite. See also *Refractories.*
-alumina, zonal studies in open-hearth roofs, (8) 216*g*.
belt, geology of Washington, (9) 247*e*.
brick, in glass furnaces, (1) 8*c*.
deposits, in Japan, (6) 153*b*.
rotor linings, wear mechanism of, (8) 215*g*.
seawater, in basic brick as compared to U. S. periclase, (3) 65*i*.
Spanish, (3) 78*b*.
Magnesium, in α-ferric oxide, electrical properties of, (4) 111*b*.
aluminate, systems. See *Systems.*
borate, Ti and Sn activated luminescent material of, P (4) 106*f*.
and chromium oxides, solid phase reactions between, (7) 187*g*.
concentrated, method to recover magnesian values from, P (11) 302*i*.
dislocations and oxide particles in, electron microscope study of interaction between, (1) 21*e*.
ferrite, formation in $MgCO_3$-$FeCO_3$ solid solutions, (6) 167*e*.
quantitative determination by measuring magnetic moment, (11) 319*d*.
temperature dependence of properties of, (6) 170*b*.
fluoride, as coating for cold mirrors, (5) 134*i*.
fluoride, production process, P (9) 247*i*.
hydride, infrared absorption spectrum of, (3) 82*f*.
hydrosilicates, to stabilize magnesia cements, (2) 28*f*.
hydroxide, method to produce with variable particle sizes, P (5) 133*i*.
-Fe-O alloys, solid solution and precipitation hardening in, (6) 169*j*.
-Fe ratio, X-ray determination in biotites, (7) 203*h*.
in limestone, determination of, (10) 280*j*.
lithium, borates, (3) 80*c*.
Mg^{2+}-Fe^{2+}, order in an orthopyroxene, $Mg_{0.93}Fe_{1.07}Si_2O_6$, (7) 201*c*.
$MgAl_2O_4$, redetermination of cation distribution in by neutron diffraction, B (2) 55*i*.
and $MgFeO_4$, growth of single-crystal and polycrystalline thin films of, (6) 167*h*.
-SiO_2, metastable solid solutions on the join, (3) 83*e*.
stability from measurements in $CoAl_2O_4$-$MgAl_2O_4$ solid solutions, (3) 86*b*.
$MgSO_4$, phase diagram of crystal hydrates at high pressures, (10) 289*g*.
-manganese ferrites, with rectangular hysteresis loop, domain structure of, (11) 316*j*.
montmorillonite, rheology of thixotropic suspensions of, (7) 190*f*.
nitrate, thermal decomposition of, (2) 53*d*.
oxide, -Al_2O_3, mechanism of precipitation of spinel from solid solutions of, (5) 138*a*.
apparatus for preparation by spouting bed technique, P (8) 217*d*.
and beryllia as high frequency insulator, sintered mixture of, (11) 305*a*.
brick, tests on creep caused by compressive load at high temperature, (9) 239*a*.
Cr_2O_3, electrical conductivity in mixtures of and at different stages of sintering, (3) 81*b*.
clinker, reaction of slags with, (10) 272*a*.
Magnesium, oxide (*continued*)
97% compared with 97% MgO clinker in basic refractories, (8) 215*a*.
composite structure of Mg particles coated by, P (2) 30*h*.
containing Fe_2O_3 or TiO_2, grain growth in, (2) 50*f*.
crucibles, reactions with molten iron under reduced pressures, (6) 153*c*.
deformation of polycrystalline at elevated temperatures, (1) 20*c*.
dependence of lattice parameter on crystallite size, (4) 110*e*.
dislocation etch pits on planes of, (7) 198*g*.
effect on content in magnesia clinker on slag penetration, (7) 186*g*.
effect on crystal growth rate of slags, (6) 167*f*.
effect of crystal orientation on, (3) 81*f*.
effect on portland cement, (8) 206*j*.
effect of water vapor on dielectric loss in, (8) 226*b*.
effect of water vapor on initial sintering of, (11) 316*i*.
electrical conductivity induced by electron bombardment, (7) 199*b*.
electron microscope study of precipitation in, (9) 249*i*.
exchange-coupled F-center pairs in, (9) 250*b*.
experimental atomic scattering factors for, (10) 286*c*.
experimental and theoretical thermal conductivities of, (6) 170*e*.
extruded xerogels containing, P (10) 274*g*.
formation of Cr^{3+} in, (3) 87*g*.
grain-boundary diffusion of Ni^{3+} in, (3) 82*d*.
grain boundary in high temperature fracture of, (9) 255*d*.
Grueneisen parameter of, (5) 136*f*.
as high frequency insulator, reduced pressure sintering, (10) 290*f*.
high-temperature elastic properties of polycrystalline, (8) 226*g*.
hot-pressed high purity polycrystalline, (4) 99*e*.
H-containing trapped hole center in, (5) 137*e*.
identification of precipitates on grown-in dislocations, (2) 50*i*.
impurity distribution in, (10) 286*h*.
-$Fe_{1-x}O$, electrical conductivity in solid solutions of, (3) 81*a*.
irradiated, divergent beam X-ray diffraction applied to, (2) 49*a*.
kilocycle-range dislocation damping in, (5) 138*b*.
93% and 96% in magnesia clinker basic brick, comparison of, (6) 151*j*.
from magnesium chloride hydrate, P (11) 303*g*.
-$MgFe_2O_4$, microstructures, (1) 13*g*.
magnetic susceptibility of solid solution of FeO in, (4) 112*j*.
and Mn and Cr oxides, reaction between, (10) 271*c*.
-Mn_xO, stoichiometry of solid solutions in air at high temperatures, (11) 319*b*.
maser amplification in, (10) 291*e*.
means to determine, (4) 107*e*.
measurement of absorption coefficients of electrons for crystals of, (10) 288*d*.
measurement of compressibility by reflectivity, (9) 251*i*.
mechanical behavior of polycrystalline at high temperatures, (8) 226*i*.
mechanical relaxation of point defect in, (3) 83*d*.
method to produce clinker from, P (2) 38*i*.
microwave ultrasonic paramagnetic resonance of Cr^{3+} ion in, (7) 201*e*.
origin of grain-boundary diffusion in, (9) 252*i*.
phonon scattering by paramagnetic ions in, (8) 266*g*.
possible increase during fusion of cement, (2) 28*j*.
pressure derivatives of elastic constants of single-crystal, (9) 253*i*.
prevention of hydration in refractories of, P (5) 126*g*.
production of dead-burned in shaft kiln, P (3) 70*g*.
properties of powders, (9) 248*h*.
pure and containing V, comments on sintering in, (8) 226*a*.
reaction between boric acid and sintered, (10) 272*h*.
reaction with Fe_2O_3 and its effect on the sintering of, (5) 140*g*.
reactions of, (9) 254*b*.
reactions with iron oxide, (9) 238*i*.
-Sc_2O_3, phase diagram of, (9) 252*j*.
seawater, production and characteristics of product, (9) 239*d*.
in sheet glass, determined by photoelectric emission spectral analysis, (3) 62*b*.
and SiO_2, solid state reaction to form forsterite, (3) 83*c*.
sound cements with high content of, (2) 29*h*.
surface energy of a running crack in calculated from crack-branching measurements, (6) 170*i*.
symmetry of color center in, (9) 257*b*.
systems. See *Systems.*
tar impregnating facility added to product line, (8) 215*f*.
test method for clinker of, (10) 273*a*.
third-order elastic constants of, (3) 87*i*.
three types, changes in properties during firing at three temperatures, (6) 151*h*.
-titania refractories, determination of titanium(III) in, (3) 69*b*.
uniaxial stress spectra in, (3) 87*j*.
Magnesium, oxide (*continued*)
and vanadium pentoxide, sintered mixture as high frequency insulator, (4) 102*j*.
whisker growth within single crystals of, (4) 114*a*.
X-ray line broadening in neutron irradiated, (2) 54*a*.
-ZrO_2, phase boundaries of cubic mixed crystal from 1800°C to melting point, (7) 202*c*.
oxide clinker, changes in physical properties of three types fired in different atmospheres, (6) 152*c*.
effect of heat on, (3) 66*i*.
effect of SiO_2 in, (3) 67*a*.
relation to size in basic open-hearth furnace roof and life of roof, (7) 187*c*.
oxide crystals, apparatus to make, P (7) 188*g*.
electron microscopy of effect of scattering on absorption coefficients of electrons in, (4) 110*c*.
electron transmission and etch pit studies of, (2) 53*c*.
structure of explosively shocked, (3) 86*b*.
in silicate, determined by spectroscopy, (11) 309*f*.
systems. See *Systems.*
thermal decomposition of hydrated, (3) 86*j*.
in silicate rocks, titrimetry to determine, (2) 45*e*.
systems. See *Systems.*
trisilicate, preparation, P (11) 312*h*.
Magnetic materials. See also *Ferrites; Ferromagnetic materials; Ferromagnetism.*
P (7) 193*g*.
acicular metal oxide particles, precipitation to prepare, P (6) 160*a*.
bodies, having magnetic anisotropy comprising conjoined films of Mo and Ni coated on a nonconductive substrate, P (6) 159*c*.
of controlled particle size, method of preparing improved, P (2) 42*d*.
development and present state of, (6) 157*j*.
fabrication, properties, and uses, (6) 157*h*.
films, on a TV picture tube, display of critical switching curves of, (6) 157*g*.
of high permittivity, P (8) 221*f*.
and non-, reference materials, interpretation of DTA of titanomagnetites using, (11) 318*a*.
oxides, process to make, P (5) 128*g*.
oxides, thin films of, (6) 158*b*.
and their preparation, P (6) 159*d*.
Magnetic properties. See also *Anisotropy; Resonance.*
of cadmium manganite, (3) 83*b*.
of $CaCoSiO_4$ and $CaFeSiO_4$, (6) 168*a*.
and catalytic, of ferrites of nickel and zinc, (5) 138*d*.
of chromium oxide, modified by vanadium oxide, (10) 288*a*.
of cobalt titanate, (11) 304*i*.
of Cu acetate, at low temperatures, (3) 83*d*.
dependence, of $Y_3Fe_{5-x}Ga_xO_{12}$ and $Y_3Fe_{5-x}Al_xO_{12}$ on thermal history, (11) 315*a*.
electro-, control of garnet $Y_3Fe_{3.75}Al_{1.25}O_{12}$, (11) 314*e*.
electromagnetic field, conductivity of cadmium oxide in high-frequency, (3) 80*f*.
of europium fluoride, (7) 200*i*.
galvano-, of glassy carbon, (4) 111*g*.
of ilmenite-hematite system, at low temperature, (4) 112*g*.
magnetic moment, quantitative determination of magnesium ferrite by measuring, (11) 319*d*.
of mixed barium strontium ferrites, effect of texture on, (11) 317*d*.
of niobium selenides and tellurides, (1) 23*f*.
of nonstoichiometric NiZn ferrites, (9) 242*e*.
ordering, in Eu_3O_4 and $EuGd_2O_4$, (9) 251*e*.
of sintered iron compacts, containing P, (6) 158*e*.
susceptibility, apparatus to simultaneously measure with thermogravimetry, (11) 309*f*.
of chromites, (6) 168*a*.
of granular hexagonal ferrites, (11) 318*a*.
of $LiFeO_2$, (5) 138*f*.
of lower Ti oxides, (9) 251*g*.
relation between specific magnetic and iron plus Mn content of chlorite, (3) 85*b*.
of U_4O_9, (10) 291*a*.
of synthetic single crystals of α-Fe_2O_3, (4) 103*j*.
of $ZnFe_2O_4$, effect of Fe^{3+} ions at tetrahedral sites on, (9) 250*e*.
Magnetism, of carbons, re-evaluation of, (4) 112*j*.
para-, anomalous susceptibility of shocked ZnS phosphors, (10) 283*h*.
Magnetite, reduction of doped hematite to, in CO/CO_2 mixtures, (5) 135*e*.
tantalian, nonstoichiometric, (4) 112*d*.
titano-, interpretation of DTA of using magnetic and nonmagnetic materials, (11) 318*a*.
Magnetization, dynamics, in $BaO{\cdot}6Fe_2O_3$ single crystals using pulsed magnetic fields, (4) 112*j*.
process, B (9) 259*e*.
residual, reversible appearance at low temperature transition in α-Fe_2O_3, (10) 277*f*.
Magnetoelectric effect, origin in Cr_2O_3, (10) 289*e*.
Magnetoplumbite, mixed-layer polytypes related to, (9) 252*h*.
Magnetoresistance. See *Resistivity, electrical.*
Magnets, electro-, for high temperature use, P (11) 296*b*.
electro-, of niobium stannide, P (11) 307*g*.
Heisenberg, magnetic ordering in, B (9) 259*e*.
permanent, magnetically anisotropic, P (11) 306*a*.
MnAl with tetragonal phase, P (10) 279*h*.
method of making machinable high energy, P (7) 193*c*.
Majolica, Swiss, from Winterthur, (3) 58*b*.
Management, Jackson's incentive programs, (1) 12*j*.
Manganese, carbonates, products of thermal dissociation of solid solutions of, (1) 23*b*.
and Cr oxides, reaction with MgO, (10) 271*c*.

Manganese (*continued*)
content of chlorite, relation between magnetic susceptibility and iron plus, (3) 85*b*.
dioxide, effect of crystal structure on surface properties of, (9) 249*a*.
and Mn_2O_3, DTA applied to dissociation of, (1) 19*e*.
or Mn_2O_3, solid state reactions with oxides of CaO, ZnO, MgO, or CdO, (2) 52*a*.
-sulfuric acid, oxidation of molybdenite, (5) 138*g*.
distortion of oxide spinels containing, (10) 291*a*.
ferrite, cation vacancies in disaccommodation of, (10) 290*a*.
^{55}Mn nuclear magnetic resonance in, (2) 50*d*.
method to make film from nitrate solution, P (11) 306*f*.
in glass, absorption and fluorescence spectra of divalent, (3) 60*d*.
-magnesium ferrites, with rectangular hysteresis loop, domain structure of, (11) 316*j*.
Mn_3FeO_6, magnetic structure of by neutron diffraction, B (2) 55*j*.
$Mn_2Fe_7O_6$, resonance relaxation in by slow relaxing manganic and ferrous ions, (9) 254*i*.
$MnGa_2O_4$, antiferromagnetism of, (11) 313*d*.
Mn_2O-MgO, stoichiometry of solid solutions in air at high temperatures, (11) 319*b*.
MnP-type phosphides, crystal structure refinements of, (2) 49*b*.
manganous-manganic equilibrium, in alkali borate glasses, (11) 296*h*.
ore, effect on properties of fireclays, (8) 225*a*.
oxide, anomalies in modulus of elasticity in shear of, (10) 283*h*.
β-, growth of crystals and magnetic properties of solid solutions of, (11) 317*f*.
effect on sintering of alumina, (1) 20*e*.
oxygen positional parameters of tetragonal, (4) 112*f*.
systems. See *Systems*.
silicide, electrical properties of higher, (11) 316*a*.
silicides, thermodynamic properties of, (10) 291*c*.
systems. See *Systems*.
trivalent, ferromagnetism and ferrimagnetism of oxygen spinels containing, (11) 317*a*.
-zinc ferrites, mechanism of disaccommodation in, (10) 277*e*.
-Zn-Fe ferrite, with rectangular hysteresis loop, (6) 158*h*.
Marokite, $CaMn_2O_4$, a new mineral, (6) 168*d*.
Masers. See also *Lasers*.
doubly doped titanium dioxide, P (11) 305*g*.
optical, of CaF_2:Nd, P (9) 243*h*.
of $CaWO_4$:Pr, (9) 243*i*.
comprising $CaWO_4$:Ho, P (7) 194*a*.
comprising $CaWO_4$:Tm^{3+}, P (7) 193*j*.
diffusion method for making composite crystals, P (2) 41*d*.
growth of large YVO_4 crystals for, (10) 277*a*.
of single crystal molybdate composition, P (6) 160*i*.
of $SrMoO_4$:Nd, $CaMoO_4$:Nd, and $PbMoO_4$:Nd, P (9) 243*i*.
with trivalent neodymium ions in calcium tungstate host lattice, P (3) 74*b*.
using internal reflection, P (2) 42*a*.
wave generation in ruby, (10) 277*j*.
ruby, transient phenomena in, (4) 104*g*.
semiconductor infrared, P (9) 244*c*.
ultrasonic, amplification by stimulated phonon-photon double quantum emission in MgO, (10) 291*e*.
Masonry, converter, changes in type as related to life of converter, (10) 270*f*.
durability of, (11) 299*j*.
mortars, testing tensile bond strength of, (11) 300*b*.
units, means to join, P (1) 7*g*.
waterproof coating for, P (3) 59*f*.
Mass, transfer, in extraction of moisture from capillary porous materials, (6) 168*d*.
transfer, thermodynamic methods applied to, (7) 197*g*.
transport, in impure ionic solids, (8) 226*i*.
Materials, for advanced technologies, B (5) 142*e*.
aerospace, (4) 114*i*.
aerospace, current and future, (2) 54*f*.
of arbitrary transverse phase geometry, elastic behavior of fiber reinforced, (1) 20*i*.
brittle, method and devices to split nonmetallic, P (2) 47*j*.
composite, strength analysis of, (8) 224*b*.
crystalline, continuous growth of, P (7) 192*d*.
for deep submergence, (2) 54*j*.
effect of space environment on, (2) 54*f*.
electronic properties, B (1) 26*c*.
engineering, strength and structure of, B (6) 174*i*.
explosive compaction of, (4) 106*i*.
high-silica foam, effect of heat treatment of silica gel on properties of, (6) 147*b*.
with high specific inductive capacitance, production and properties of, (2) 40*g*.
high strength, international conference, B (2) 55*d*.
high temperature, graphite and carbons as, (11) 301*f*.
high temperature, review of, (6) 171*e*.
loose and poorly consolidated, impregnation of, (7) 194*h*.
metallic and nonmetallic, testing with pressure bar, (1) 25*a*.
for microelectronics, technology of, (1) 14*c*.
modern, advances in development and applications, B (6) 174*g*.
modern, principles and concepts, B (5) 142*i*.
molecular design of, session at Cambridge, Mass., B (9) 258*h*–259*g*.
new applications, (4) 108*i*.

Materials (*continued*)
optical, guide to selection, (2) 31*f*.
porous. See *Porous materials*.
problems of, (4) 114*j*.
protection from heat, and properties of in heat environment, (4) 114*j*.
sciences, fundamental phenomena in, B (7) 204*e*.
selection of, (2) 46*h*.
for space stations, (5) 133*d*.
super, potential development and applications, (7) 203*j*.
two-component, modulus of elasticity of, (10) 288*h*.
volcanic, in Idaho, (7) 196*f*.
as whiteware fillers, (10) 275*i*.
Materials handling. See also *Conveyors; Feeding apparatus; Machinery and equipment*.
apparatus, for bulk, P (8) 222*f*.
to meter and discharge dry particles, P (11) 309*b*.
for pulverulent materials, P (4) 109*a*.
to stack brick, P (11) 308*f*.
to transport granular materials, P (9) 244*f*.
batch, working cycles for pneumatic-vacuum installations for, (6) 161*e*.
blowing floor, for conveying, storing, and/or mixing, P (5) 126*d*.
brick, process and apparatus to remove from pressing table, P (7) 194*h*.
for brickworks, trackless means, (7) 185*c*.
dry, transfer apparatus for, P (1) 16*a*.
granular, valve construction for pneumatic, P (8) 222*h*.
pneumatic, for granular material, P (11) 309*a*.
pneumatic, systems and problems, (3) 74*j*.
pneumatic apparatus for, P (4) 107*a*.
pulverulent, method and apparatus for, P (4) 107*a*.
solids, flow equalizer, P (1) 16*c*.
transfer machine, (8) 222*e*.
transfer means, for double parison, P (2) 33*g*.
Measurement, apparatus, for physical quantities, P (3) 77*a*.
of color differences, precision in small, (1) 12*j*.
continuous, of dust concentration by electrical contacts, (2) 44*a*.
of density, principles of, (5) 131*e*.
direct, of fracture energies of brittle heterogeneous materials, (1) 20*a*.
electrical, for pure materials analysis, (3) 75*f*.
of glass level, with electrodes, (2) 31*e*.
Hall coefficient and conductivity, of cadmium oxide in terms of sintering temperature, (6) 167*i*.
industrial-process-type, using γ-ray backscattering, P (11) 311*e*.
method, for afterexpansion or aftercontraction, (8) 216*a*.
to determine fractional-fill of ball mills, (2) 43*g*.
for physicochemical quantities of glass in electric furnaces, (2) 32*b*.
neutron diffraction, on synthetic hematite crystals, (3) 84*a*.
of optical flatness, (9) 245*g*.
photovoltage, on Al-Al_2O_3-Al thin film sandwich, (9) 253*j*.
of spectral reflectivity, with microphotometer, (8) 223*a*.
of surface straightness, P (1) 17*c*.
techniques, for surface temperature, (5) 131*j*.
of thickness of concrete, by gamma ray, (9) 231*e*.
Measurement devices, automatic, for particulate material streams, P (1) 16*b*.
automatic, to simultaneously measure thermogravimetry and magnetic susceptibility, (11) 309*f*.
for density, of smoke and dust in industry, (1) 16*h*.
for electrical resistance, of liquid glass, (8) 210*a*.
electronic, to measure mirror silvering thickness, (10) 280*h*.
for enamel, color and appearance, (7) 178*h*.
for flow, infrared tracer, (9) 245*h*.
magnetic and optical differential thickness, P (9) 246*d*.
modified spindle stage, for 2V, (6) 162*f*.
optical, for glass sheet, P (9) 237*c*.
and techniques, for surface temperature, (6) 163*f*.
teledix, for torque of small magnitude, (9) 246*e*.
thermal comparator, for conduction and surface finish, (9) 245*d*.
for thermal conductivity, of glass in range of −150° to 50°C, (8) 210*c*.
Mechanical properties, behavior, of ceramics, (6) 171*c*.
determination, of kaolin-water system, (7) 198*a*.
and hydrogen mobility, of clays, (7) 201*e*.
improved, of materials for high-voltage applications, (6) 157*h*.
of magnesium oxide, effect of crystal orientation on, (3) 81*f*.
of refractories, from hexaborides of rare earth metals, (10) 270*f*.
of refractories, at high temperature, (11) 301*d*.
of refractory materials, at high temperatures, (8) 223*j*.
of solids, at high temperature, (11) 301*a*.
of vitreous selenium, near its glass transition, (3) 85*g*.
Meetings. See *Conferences*.
Melting, and casting of UC, B (6) 172*f*.
electric, change in alkali content of lamp glass during, (4) 95*b*.
electric, problems for glass, (4) 94*j*.
floating zone, device for, P (5) 128*b*.
floating zone, induction heating above 2000°C for, (2) 53*e*.
glass, alternate of colored and colorless without stopping furnace, (9) 232*h*.

Melting, glass (*continued*)
economics of gas vs. electric, (8) 224*c*.
effect of gamma rays on, (7) 180*i*.
rapid, (4) 95*b*.
velocity of reactions in, (4) 96*a*.
improvement, without crucible for refractory oxides, (8) 215*j*.
industrial, of glasses colored with rare-earth elements, (4) 93*e*.
and machining of cermets, apparatus for electron-beam vacuum, (1) 17*h*.
process, for glass, (9) 233*e*.
of optical glass, advances in, (2) 32*d*.
point, of alumina and related observations, (2) 50*b*.
sheet glass, at high temperatures, (10) 265*i*.
of special glasses, small furnace with low fuel consumption for, (8) 211*a*.
temperature, of K_2TaF_7, (1) 23*h*.
of UO_2, by direct high frequency induction, (6) 153*b*.
Melts, alkali borate, solubility of water vapor in, (10) 266*h*.
changes in method of growing crystals from, B (11) 319*j*.
crystal growth from, B (8) 228*i*.
diabase, nucleation agents in, (8) 216*c*.
fibers from, B (2) 55*g*.
interactions of titanates and vanadates of Na in, (1) 22*j*.
sodium silicate, oxygen ion activity and solubility of sulfur trioxide in, (10) 265*j*.
in system BaO-GeO_2, X-ray study of, (2) 54*c*.
treatment, relation to glass fiber strength, (4) 95*d*.
Memory, effect, in α-Fe_2O_3, (10) 286*e*.
Memory cores. See *Data storage*.
Memory devices. See *Data storage*.
Mercury, porosimetry, breakthrough pressure for penetration between packed spheres, (4) 112*b*.
Metaborate, trimer, vibrational spectrum, (2) 53*h*.
Metallics, finishes, for vitreous enamel, (3) 59*g*.
Metallizing. See *Coatings*.
Metallography, modern, B (9) 258*g*.
specimens, mounting for edge retention, (9) 245*f*.
X-ray, developments of line profile analysis in, (8) 223*e*.
Metallurgy, powder. See *Powder metallurgy*.
Metals. See also *Enameling metals; Rare earths*.
alkali, interaction of chlorides of with niobium oxychloride, (11) 317*f*.
bodies, breaking up sintered, P (9) 240*h*.
borides, P (9) 241*c*.
borides, electron requirements of bonds in, (4) 111*e*.
carbide, P (10) 274*g*.
carbon coated for nuclear reactors, P (6) 154*j*.
-carbon, eutectic temperatures of group IVB and VB, (11) 317*h*.
-ceramics. See *Cermets*.
coatings for, high temperature use, (7) 178*i*.
complexes, molecular orbital theory for transition, (3) 83*h*.
contact of hot glass with, international symposium, B (2) 55*c*.
crystals, defects in, B (9) 259*e*.
divalent metallic ion, instead of ferrous ion and ferric ion, precipitation from solution of, (9) 253*f*.
enameling, aspects of, (4) 91*b*.
fabrication, problems and solutions, (4) 91*i*.
fiber reinforced, composites, (6) 146*a*.
fiber reinforced, method of preparing, P (2) 38*f*.
films, strain in thin on quartz, (9) 256*e*
foil, flexible enamel for, (4) 91*d*.
forming, sliding frictional characteristics of deep drawing lubricants for, (4) 91*d*.
-glass combinations, calculation of temperature distribution in, (2) 31*a*.
hard, production of powders from, P (1) 12*a*.
high-melting, welding of metallic carbides to, (7) 179*d*.
hot, gunning method for mixer for and its effects, (10) 271*j*.
hot, repair of mixer for with dry type gunning mix, (7) 187*c*.
interaction, with solid crystallohydrates, (1) 22*h*.
interactions of oxides and carbides with, (7) 178*j*.
ions, correlation of spin ordering temperatures for compounds containing divalent 3*d* transition, (6) 165*g*.
joining ceramics and glass to, (2) 40*i*.
layer type, for contact with molten materials at high temperature, P (5) 132*a*.
metallic salts or oxides, effects on erosion resistance of Korean kaolin, (6) 152*j*.
and metal oxides, removal of layers by mechanical polishing, (5) 140*a*.
molten, interaction between high-melting compounds and, (10) 271*e*.
nonferrous, erosion of silicon nitride brick by, (4) 99*a*.
nonferrous, use of silicon nitride and its corrosion by, (7) 188*b*.
nature of, B (4) 115*d*.
nonferrous, refractories for, (5) 125*a*.
oxides. See *Oxides*.
-to-O, properties of multiple bonds, (8) 227*c*.
point defects in, B (7) 204*d*.
with porous glass, possibility of submicroscopic compatiblity of, (8) 211*g*.
powder compositions, containing refractory metal oxide, P (2) 38*b*.
precious, to decorate pottery, (8) 219*d*.
preparation and pickling, tips for enamelers, (8) 208*c*.
pretreatment, and one coat enamel bond, (6) 146*b*.
protective coatings for, properties of those applied by atomization, (4) 91*j*.

Metals (*continued*)
radiation blistering, interferometric and microscopic observations, (9) 254*i*.
rare earth, dense parts and mechanical properties of hexaborides of, (10) 270*f*.
hexaborides of, (9) 250*h*.
interaction of Sn chlorides with chlorides of, (1) 22*e*.
with nonmetals, high-temperature compounds of, B (3) 88*i*.
in raw materials, detectors for, (7) 194*f*.
refractory, vacuum siliciding of, (10) 271*b*.
sealing glass-ceramics to, (11) 297*f*.
semi-, bonding and general properties, B (6) 175*c*.
sheets, method to bond, P (3) 60*a*.
siliceous and calcareous, means to determine sulfate in, (9) 245*f*.
spraying, to protect moldmaker's cases, (4) 102*g*.
study, application of electron microscope to, B (6) 173*h*.
surfaces, blasting abrasives to treat, (4) 91*b*.
surfaces, surface diffusion and growth of oxide particles on, (2) 52*g*.
symposium on, B (6) 171*f*.
systems. See *Systems*.
transition, from groups IV, V, and VI, mutual solubility of disilicides of, (9) 252*j*.
NMR to investigate borides of, (10) 287*f*.
question of zeolitic nature of ferrocyanides of, (4) 112*g*.
relation between carbides and nitrides of and their electronic structure, (9) 254*g*.
superconducting phosphides of, (9) 257*a*.
thermal expansion of disilicides of, (2) 53*a*.

Methane, and carbon suboxide, kinetics of deposition of pyrolytic carbon films from, (4) 112*c*.

Methanole, potassium-hydrosilicates from, (3) 85*e*.

Mica. See also *Refractories; Vermiculite*.
biotite, Fe-Mg ratio in, X-ray determination of, (7) 203*h*.
-garnet-sillimanite gneisses from Quebec, analysis of equilibrium in, (7) 197*d*.
stability of, (9) 256*h*.
composite sheet, and method, P (2) 42*i*.
crystals, delamination with sonic vibrations, P (6) 159*f*.
flakes and silicone, method of making paper from, P (6) 160*b*.
fluorphlogopite, apparatus for electrophoretic deposition of lamellar sheets, P (1) 14*e*.
growth of sheet crystals of, (4) 103*j*.
synthesis of large crystals, P (3) 79*c*.
glass-bonded, constitution and properties, (2) 40*f*.
new electronic composite, (6) 158*i*.
uses expanded, (8) 220*a*.
laminate, bonded synthetic, P (4) 104*b*.
micaceous material, in electronic tube, (1) 14*d*.
muscovite, between 700° and 1000°C, structure of anhydrous phase of, (7) 202*h*.
muscovite, distribution of isomorphous substitutions in, (7) 198*g*.
new, $KMg_{3.4}[Si_4O_{10}]D(OH)_2$, synthesis of, (6) 170*j*.
ore, flotation of Californian, (3) 78*e*.
phlogopite, decomposition by electrodialysis, B (2) 56*f*.
products, dehydrated and method of making, P (4) 104*d*.
proton delocalization in, (11) 319*b*.
substrates, energy for surface mobility of, gold films on, (7) 191*i*.
thermal properties of, (6) 164*d*.
trioctahedral, in sedimentary rocks, B (2) 56*e*.
type structures, infrared absorption spectra of, (6) 168*e*.

Micrography, field-ion, interpretation of streak contrast, (3) 82*j*.
field-ion, streak contrast in micrographs, (9) 246*c*.

Microhardness. See *Hardness*.

Microphones, P (8) 220*d*.

Microscopes, with attachment for anoptral phase contrast, to observe body surfaces, (11) 310*a*.
electron, to determine microstructure of porcelain insulators, (11) 304*d*.
in diamond research, (9) 229*f*.
to examine thin sections of sintered alumina subjected to acid and thermal treatment, (11) 310*f*.
of hardened cement pastes by replica method, (11) 310*d*.
to investigate structure of glass, (1) 4*j*.
preparation of fuel particles for by means of replicas, (11) 310*f*.
in study of production of glass-ceramics, (2) 31*a*.
ultrathin glass sections for structure investigations by, (7) 182*b*.
hot-stage, observation of slag melting conditions with, (9) 238*e*.
ore, in identification of polished isotropic minerals, (6) 162*b*.
petrological, to study materials, (8) 223*b*.
photoelectric, development of, (3) 75*j*.
stage, heated, P (2) 45*i*.

Microscopy, of cement clinker, picture atlas, B (4) 115*i*.
electron, of clays, ultramicrotome sections for, (3) 85*f*.
of fractured glass-ceramics, (2) 31*a*.
of glass films obtained by evaporation, (10) 264*h*.
to identify clay minerals in delta sediments, B (2) 56*g*.
of Indian clays, (7) 203*b*.
to investigate alkali-etched silicate glass, (8) 210*e*.
of lattice defects in graphite, (4) 112*e*.

Microscopy, electron (*continued*)
to observe thin-film nucleation and growth processes, (10) 281*i*.
of phase transformations, Kikuchi electron-diffraction and dark-field techniques in, (1) 16*f*.
in study of Indian clays, (3) 84*e*.
of surface changes of graphite and carbon oxidized by atomic oxygen, (2) 51*f*.
transmission, of polycrystalline beryllium oxide, (7) 199*g*.
in field of electrotechnical and electronic ceramics, (11) 310*h*.
field ion, (1) 16*j*.
handbook, in sintering technology, B (9) 258*c*.
hot-stage, of process in glass melting with and without sulfate, (6) 148*a*.
identification, of minerals, B (9) 258*h*.
optical, localized oxidation rates on graphite surfaces by, (4) 112*d*.
photometric measurement, of rotation properties, (9) 253*i*.
preparation of polished thin sections from heavy mineral residue, (8) 223*c*.
preparation of thin sections of friable sediments, (8) 223*d*.
scanning electron, applied to oxidation of iron, (5) 140*e*.
transmission electron, to observe quartz dislocations, (3) 81*d*.
preparation of foils for, (5) 136*e*.
preparation of TiO_2 for, (9) 253*e*.

Microstructure. See *Structure*.

Microwaves, characteristics, of fine-grain high-power garnets and spinels, (9) 252*e*.
components, high power, P (4) 104*j*.
dielectric dispersion, mechanism in $BaTiO_3$, (4) 104*a*.
discharge, deposition of oxide films at low temperature, (10) 277*f*.
emission, from *n*-type CdS, (7) 201*c*.
modulator, using single crystal ferrite, P (5) 129*b*.
ultrasonics, (5) 128*c*.

Milling. See *Crushing; Grinding*.

Mills. See also *Crushing apparatus; Grinding apparatus*.
attrition, and method, P (1) 18*c*.
ball, breakage in small continuous open-circuit wet, (5) 130*j*.
method to determine fractional-fill, (2) 43*g*.
rotating means for, P (1) 16*c*.
with tensional and wear resistant linings, P (11) 308*g*.
continuous and intermittent, grinding method and apparatus for, P (2) 43*f*.
from edge-runner to modern roller, (10) 282*h*.
grinding, P (4) 109*f*.
lining and control of wear, P (1) 16*a*.
and process, P (4) 109*g*.
steel liner for, P (7) 194*f*.
hammer, P (2) 47*f*; P (3) 78*g*; P (4) 109*f*.
feed control, P (9) 247*e*.
impact hammer for, P (1) 18*f*.
replacable hammer tip for, P (11) 312*j*.
jar, mounting for, P (4) 107*a*.
for lead oxide, P (1) 18*g*.
loading, mechanized for pottery industry, (6) 155*j*.
rotary, gearless, P (11) 308*j*.
rotary pulverizer, with classifying means, P (10) 283*d*.
tumbling, (6) 161*d*.
vibrating ball, method and apparatus, P (2) 43*h*.
vibration, research on resonant motion of grinding media in, (5) 130*i*.
vibratory, P (1) 19*c*; P (11) 309*d*.
characteristics of, (4) 106*i*.
drum type, P (1) 19*c*.
vibro-energy, P (10) 283*e*.
vibro-energy, roller-actuated, P (10) 280*e*.

Mineral fibers. See *Mineral wool*.

Mineralizers. See also *Fluxes*.
for clinker formation, (7) 178*b*.
effect on formation of cement clinker, (8) 206*f*.
effect on reaction speed in calcining Spanish serpentines, (8) 225*b*.
fluorine, effect on belite-containing clinker, (1) 2*d*.

Mineralogy, of alluvial sand, near Charsadda, Pakistan, (11) 312*e*.
of British brick clays, (5) 124*f*.
clay, of Pennsylvanian redbeds and associated rocks in Colorado, (5) 132*j*.
of emery-like rocks, from Scotland, (11) 314*j*.
of Izumiyama pottery stone, (1) 18*g*.
mineralogical modal analysis, with electron microprobe X-ray analyzer, (7) 195*d*.
mineralogists, optical determination methods and devices for, B (6) 174*h*.
of soda-lime-silica glazes, (5) 127*g*.
theoretical, aspects of in U.S.S.R., B (8) 228*e*.

Minerals. See also *Raw materials; Rocks;* and specific types.
admixtures for cement, methods to estimate activity of, (4) 90*g*.
analysis, at high temperatures and pressures, (3) 76*d*.
blow pipe for, P (5) 133*b*.
clay. See *Clays*.
color, apparatus to sort by, (11) 312*f*.
containing TiO_2, process to decompose with hydrochloric acid, P (5) 133*j*.
decomposition, method, (1) 16*i*.
electrostatic separation of, P (2) 47*e*.
ferrous iron in, determination of, (10) 281*g*.
flame working, P (7) 196*i*.
formation, and structure in electrochemical induration of weak rocks, B (9) 258*d*.

Minerals (*continued*)
fractions, variation in Lithuanian moraines, (9) 252*f–g*.
gangue, contamination of froth, (7) 194*g*.
gas chromatography of, (2) 44*b*.
grains, identification of, B (7) 204*g*.
heavy, concentrates and their granulometric composition in Lithuania, (9) 250*g*.
identification, microscopy in, B (9) 258*h*.
industrial, (6) 164*h*.
in Newfoundland, (1) 18*e*.
review of Canadian, (1) 18*e*.
industries, generalized probability distributions in, (4) 108*j*.
laminar, apparatus to delaminate, P (5) 133*b*.
micaceous, froth flotation of, P (2) 47*f*.
nonmetallic, containing calcite, flotation concentration of, P (7) 196*i*.
in ores, excited X-rays to identify in moving, (11) 312*c*.
$^{18}O/^{16}O$ ratios, from iron formations of Quebec, (1) 23*d*.
physical constants of, B (10) 292*g*.
polished isotropic, polarization figures as aid to identification of, (6) 162*b*.
radiogenic, chemical and mass spectrometry to determine age of, (11) 317*e*.
of sillimanite group, structure and transformation, (10) 287*h*.
solids, structure and topochemistry of, B (6) 175*b*.
in South Africa, (6) 164*i*.
suites, methods to compare heavy, (8) 223*b*.
surface, and water phase, B (7) 204*g*.
surface area, determined by BET apparatus, (5) 136*d*.
synthesis, by hydrothermal technique, (11) 318*b*.
tables, properties of 1500, B (9) 258*e*.
in Tennessee, (7) 196*f*.
of Texas, (8) 225*i*.

Mineral wool. See also *Fibers, glass*.
apparatus to make pipe insulation from, P (8) 211*f*.
board of, P (8) 217*j*.
fiber formation, effect on quality, (9) 233*g*.
quality test, P (3) 77*c*.

Mines and mining, anhydrite, at Billingham, (3) 78*h*.
of feldspar sand, from Triassic basin at Weiherhammer, (3) 78*h*.

Mirrors, astronomical, surface deformation of large, (2) 32*c*.
glass, sand quality requirements for, (3) 62*g*.
with magnifying portion, P (10) 269*e*.
silvering thickness, apparatus to measure, (10) 280*h*.
telescope, effect of internal stress on rigidity of large, (2) 31*g*.

Mixers, P (10) 280*c*; P (11) 309*a,b*.
agitated, velocity profiles and transfer operations at wall of, (9) 244*i*.
automatic vacuum-, for plaster, (10) 275*i*.
continuous, to mix and/or react materials, P (11) 308*g*.
for granular material, P (7) 194*g*.
for hot metal, gunning method for hot repair of and its effects, (10) 271*j*.
operation of 1300-ton, (7) 187*e*.
repair with dry type gunning mix, (7) 187*c*.
investment, with enlarged mold supporting platform, P (7) 188*e*.
for liquid and dry material, P (10) 280*c*.
for plaster, (5) 127*e*.
shaft torque, calculation for granular materials, (3) 75*a*.
slurry, and applicator, P (7) 189*j*.
splitter apparatus, P (4) 107*b*.
with weighing hopper, P (9) 244*g*.

Mixing, apparatus and method, for pulverulent material, P (5) 119*a*.
of batch, for pot furnace factory, (3) 62*c*.
of dry and wet solids, power consumption in rotary cylinders with blades, (1) 15*j*.
equipment, for glass factories, (3) 74*i*.
of glass batch, (3) 62*h*.
kinetics, in continuous glass melting tanks, (5) 121*b*.
in packed beds, of viscous non-Newtonian fluids, (1) 23*j*.

Models, classical, of solid solutions based on nearest-neighbor interactions which involve both central and linked-central forces, (11) 314*a*.
creep, (1) 19*d*.
experimental, of top fired tunnel kiln, (2) 46*c*.
modeling of glass melting, methods to measure physicochemical quantities for, (2) 32*b*.
for multicomponent diffusion, correction, (9) 234*d*.
simplified, to calculate heat exchange between flame and glass surface in tank furnace, (4) 95*f*.

Modulators, optical phase, (4) 103*h*.

Modulus of elasticity. See *Elasticity*.

Modulus of rupture. See *Rupture*.

Moisture. See also *Humidity; Steam; Water*.
effect on thermal conductivity of refractories, (11) 301*e*.
getter preparation, barium oxide, P (2) 41*a*.
radioactive elements to determine, (3) 76*h*.
sensing control, P (11) 311*b*.
in solids, how to measure, (10) 281*c*.

Molding, of articles, method of, P (5) 131*c*.
compositions, shell, P (9) 240*f*.
injection, of intricate shapes, (10) 277*a*.
injection, under pressure, P (8) 222*e*.
investment, P (1) 11*g*.
composition, P (10) 274*c*.

Molding, investment (*continued*)
using refractory material and organic bases, P (4) 100*e*.
for kitchen and bathroom walls, P (3) 71*j*.
method, for fiber glass reinforced products, (9) 234*d*.
methods, and apparatus for, P (6) 157*b*.
plastic, of aerospace components, (3) 68*j*.
pressure, of dry material, P (1) 16*b*.
process, shell, P (11) 303*f*.
sand-core, of Egyptian glass, (9) 229*j*.
Molds. See also *Slip casting; Slips.*
P (9) 240*e*.
blank, with pneumatic plunger for seamless optical glass, P (2) 33*c*.
brick, means to attach metallic members in, P (6) 154*i*.
of carbon powder, for Ti casting, (6) 153*d*.
cases, metal spraying to protect, (4) 102*g*.
casting, hot top for, P (2) 38*a*.
casting, for metals and method of making, P (4) 100*f*.
ceramic, apparatus to make, P (10) 274*d*.
coated, and method (for metal), P (10) 273*e*.
container, effect on glass surface, (4) 92*e*.
and core construction, for whitewares, P (1) 13*d*.
dressings, for foundry use, P (11) 302*j*.
to form balls, P (8) 213*g*.
foundry, refractory coating for, P (2) 37*f*.
of gelled refractory, P (5) 126*b*.
for glass, P (3) 63*i*.
air operated neck, P (7) 182*f*.
axially separable neck ring assembly, P (6) 149*d*.
blow with aligning means, P (10) 268*c*.
blowing, with movable support, P (8) 211*i*.
delivering means for, P (2) 34*b*.
means to release stress in glass during cooling, P (8) 212*h*.
method to clean equipment, P (10) 268*f*.
optical, with temperature regulator, P (6) 150*c*.
patch support, P (1) 7*a*.
from porous metal, P (8) 213*e*.
precision, P (2) 34*d*.
release during forming, P (8) 213*j*.
type AW 45 with electrical control, (4) 95*h*.
graphitic, P (9) 240*j*.
graphite, P (10) 273*i*.
ingot, method of making hot tops for, P (2) 38*e*.
investment, method of forming from SiO_2 with potassium sulfate additive, P (5) 126*f*.
investment, method of treating, P (2) 38*j*.
for lenses, P (11) 299*i*.
materials for permeable, (4) 102*e*.
for metal casting, P (10) 273*f*.
multilayer graphite, and method to make, P (7) 188*i*.
parison, forming apparatus, P (11) 299*b*.
for glassware, P (11) 299*b*.
pressing plunger for glass, P (11) 299*d*.
plaster, preparation for flatware, (5) 127*h*.
porous, removal of H_2O by electric current, P (4) 103*e*.
precision, and method of making, P (6) 155*e*.
precision casting, and methods and materials for, P (6) 155*e*.
press, hardcoated die for, P (2) 43*g*.
for pressed tile, (11) 308*h*.
for pressing glass, heat resistant steels for, (4) 95*i*.
to produce articles from slip, P (10) 280*e*.
refractory, P (3) 70*d*.
composition and method, P (8) 218*a*.
fabrication of exothermic self-hardening, P (2) 37*e*.
induction heating method to make, P (9) 240*e*.
method of forming, P (5) 126*f*.
production of, P (1) 12*b*.
by Shaw casting, (3) 68*i*.
for steel casting, P (8) 218*a*.
reusable, manufacturing process for, P (4) 100*g*.
sand, cured with carbon dioxide and using dry sodium silicate binder, P (4) 100*f*.
sand, and methods for metal casting, P (1) 12*c*.
shell, apparatus for forming, P (5) 125*g*.
of graphite, P (9) 240*c*.
and method to make, P (7) 188*j*.
split, windbox cooler for bottle machine, P (5) 124*d*.
for tile, P (8) 222*f*.
Molecules, diatomic ionic, interatomic forces and binding energy of, (7) 200*b*.
Molybdates, alkaline-earth, crystallization under hydrothermal conditions, B (11) 320*d*.
trivalent, of type $La_2(MO_4)_3$, study of, (10) 284*e*.
Molybdenite, manganese dioxide-sulfuric acid oxidation of, (5) 138*g*.
Molybdenum, carbide, relaxation phenomena during hot compacting of, (10) 290*i*.
diffusion of C into, at low C concentrations, (10) 284*d*.
disilicides, effect of neutron irradiation on, (5) 135*b*.
high-temperature oxidation of, (5) 125*g*.
oxidation kinetics of, (10) 289*e*.
thermal expansion of, (9) 257*i*.
disulfide, effect of water vapor on friction of, (9) 238*d*.
effect of stress on imperfection of silicide layers on, (11) 295*d*.
-manganese metallizing layers, adhesion mechanism on corundum, (6) 157*e*.
MoC, superconductivity of, (7) 203*f*.
Mo_2Ge, preparation of, (8) 220*e*.
Mo^{4+} in glass, excitation spectrum of 1μ fluorescence of, (9) 233*a*.
Mo_2P, crystal structure, (2) 48*j*.
Mo_4P_3 crystal structure, (1) 19*h*.
Molybdenum (*continued*)
$Mo_{0.8}Si_2C_{0.8}$, $Mo_{0.98}Hf_{0.02}C_{0.78}$, and Mo_2C, superconductivity in, (9) 257*a*.
oxide, systems. See *Systems.*
-to-O, properties of multiple bonds, (8) 227*c*.
pentachloride, systems. See *Systems.*
powder, very fine, (11) 304*i*.
silicides, heat conduction of, (7) 199*j*.
silicon carbide coatings on, B (11) 320*d*.
systems. See *Systems.*
and Ti-Mo alloy, properties of protected, (6) 152*a*.
-UO_2 cermets, loss of UO_2 by diffusion, (3) 68*f*.
Monazite, Y in, determination by X-ray fluorescence method, (9) 245*e*.
Montmorillonite, analysis, multivariate, (5) 134*b*.
autoclaved, to form coagulation structures, (3) 81*i*.
Ca, complexes with fatty acids, (9) 248*f*.
complexes, with amines, (9) 248*i*.
dehydration, infrared spectroscopy of, (1) 22*b*.
ethylene glycol-, X-ray study of, (6) 171*a*.
interfacial properties of, (8) 227*g*.
Mg, rheology of thixotropic suspensions of, (7) 190*f*.
mineral, occurrence in younger granites in Northern Nigeria, (5) 133*e*.
multivariate analysis of, (6) 169*b*.
potassium retention in, (3) 85*a*.
sorption, of glycol and glycerol by, B (2) 56*d*.
study, by microscopy and electronic microdiffraction, (8) 227*f*.
uses, (7) 196*g*.
water dispersions of, criteria to evaluate coagulation action of electrolytes on, (9) 256*f*.
water of hydration of, nuclear magnetic resonance study of thermal evolution at low temperatures of, (7) 201*h*.
Montroydite, crystals, possibility of production under hydrothermal conditions, B (11) 320*c*.
Moraines, Lithuanian, variation of rock and mineral fractions in granulometric spectrum and of deposits of different age, (9) 252*f–g*.
Mordenite, (ptilolite), crystal structure, (3) 80*c*.
Morphology, changes driven by capillarity, surface- and volume-diffusion contributions to, (5) 141*c*.
of solid particles, factors affecting in liquid matrix, (5) 136*e*.
submicroscopic, of deformation of rock salt crystals, (3) 86*j*.
Mortars, bars, from Danish aggregates, experiments on, (8) 207*a*.
cement, effect of repeated wetting and drying on carbonation and shrinkage of, (8) 206*g*.
hydraulic, P (6) 144*i*.
sand, effect of agitation on rheology of, (3) 58*j*.
at temperatures up to 80°C, effect of sulfate solutions on, (1) 2*j*.
^{60}Co impregnated, as tracer around graphite bricks beneath ingot molds, (1) 10*b*.
determining cement content in, (10) 262*g*.
joints, discolored by manganese-colored brick, (4) 98*g*.
for ladle bottom, (3) 68*h*.
masonry, effect of restraint on shrinkage, (3) 58*i*.
masonry, testing tensile bond strength of, (11) 300*b*.
portland cement, changes in weight and dimensions in drying and carbonation of, (1) 2*d*.
refractory, for joining burned basic brick, P (1) 11*i*.
refractory, method to simultaneously determine workability and water retention of, (7) 187*c*.
sand-lime, carbonation process in, (8) 206*f*.
siliceous refractory, mechanism of property change in molten iron, (10) 271*i*.
under load, temperature change effect on, (5) 118*i*.
Mosaics, hobby and art, B (6) 174*g*.
Mufflers, all-ceramic, P (4) 96*b*.
coated, with liquid flow gaps between partitions and shell, P (5) 120*a*.
manufacturing method, P (1) 3*g*.
method to make, P (7) 179*e*.
and process, P (1) 3*g*.
internal coating, of glass fibers, P (5) 123*i*.
porcelain coated, P (10) 263*i*.
with resilient sealing gaskets, P (4) 96*a*.
Mullite. See also *Refractories.*
in fireclay, morphology and crystal size distribution of, (2) 36*c*.
formation, from kaolin minerals, (4) 111*d*.
relation to erosion resistance, (6) 152*h*.
in system kaolinite-aluminum fluoride, (2) 53*e*.
nature of, formed from coprecipitate of alumina and silica gels, (5) 139*b*.
phase, formation in aluminosilicate refractories, (2) 36*h*.
spinel, synthesis and study of its properties, (9) 257*c*.
synthesis, by flame fusion technique, (4) 99*f*.
Muscovite. See *Mica.*

Neodymium, barium, crown glass laser, (5) 139*d*.
chloride, systems. See *Systems.*
doped glass, fluorescence and stimulation in, (6) 147*e*.
-doped glass, laser action in from energy transfer, (10) 287*c*.
-glass lasers, internal self-damage of, (10) 287*d*.
hydrides, some properties of, (4) 113*d*.
ion, bombarded CdS, (10) 288*g*.
Nd^{3+}, fluorescence in alkali borate glasses, (6) 148*h*.
Nd^{3+}-glass lasers, polarization of light from, (10) 289*e*.
Nd_2O_3, interaction with fluoride melts, (10) 287*a*.
Neodymium (*continued*)
Nd_2O_3, transformation of and interactions with chlorides of Li and K and with carbonate and sulfate of Na, (3) 87*j*.
systems. See *Systems.*
thin films, dielectric properties of, (11) 315*b*.
Nepheline, concentrate, in production of dark-green glass, (9) 235*f*.
rocks, effect of mineralizer on clinker from tailings of, (1) 2*d*.
Neutrons, -absorptive glass, P (2) 34*b*.
activation analysis, of pure SiC, (6) 153*f*.
-diffraction, of $Co_3B_2O_6$, (9) 252*b*.
to determine crystal structure of $Er_2Ti_2O_7$, (5) 134*j*.
and diffusion of, B (2) 55*h*.
measurements on synthetic hematite crystals, (3) 84*a*.
irradiated, graphite, temperature variation of resonance signal of, (4) 114*h*.
LiF, dislocation network in, (4) 110*j*.
LiF, nuclear magnetic resonance study of decomposition in, (9) 252*c*.
irradiation, thermal history of LiF crystals during, (9) 257*j*.
shielding, of graphite, boron carbide, and carbonized residue, P (4) 101*a*.
slow, determination of B_2O_3 in glass by weak source, (3) 76*i*.
thermal, as cause of glass outgassing, (9) 234*h*.
chemical effects of capture in mixed crystals of phosphates and arsenates, (3) 70*j*.
device to measure doses, P (3) 77*c*.
Nickel, Al_2O_3 coating for, (1) 24*j*.
-base materials, determination of C and Si in by spectral analysis in sintered, (3) 66*c*.
cadmium ferrite, temperature dependence of line width of ferrimagnetic resonance in polycrystalline, (4) 113*f*.
chloride systems. See *Systems.*
-dip solutions, filters for, (8) 207*i*.
ferrite, containing Co and Mn, P (5) 129*b*.
growth of single crystals, (10) 286*e*.
magnetic and catalytic properties of, (5) 138*d*.
oxygen content at 1300°C, (1) 13*g*; discussion, (6) 166*j*.
properties and porosity broadening of ferromagnetic resonance line width, (3) 72*c*.
ferrous ferrite, electrical conduction in, (4) 103*i*.
ferrous ferrite, square loop, (5) 129*j*.
-graphite compositions, operation in steam atmospheres at industrial parameters, (11) 313*h*.
-manganese-ferrous ferrite, P (5) 129*c*.
Ni^{2+}, grain boundary diffusion in MgO, (3) 82*d*.
$NiAl_2O_4$, formation by solid state reaction, (5) 136*j*
$Ni_xFe_{3-x}O_4$, frequency dependence of ferromagnetic crystalline anisotropy of, (10) 286*j*.
$NiSO_4 \cdot xH_2O$, estimation of surface acidity, (3) 83*g*.
$NiTiO_4$, stability of, (7) 202*d*.
oxide, antiferromagnetic magnetostriction in single crystal, (4) 109*j*.
Li_2O, solid solution, (10) 288*i*.
sintering in active, (1) 25*a*.
studies on properties of doped, (8) 227*d*.
systems. See *Systems.*
plating tank, control of ferrous sulfate in, (6) 145*c*.
specimens, growth of disperse Al_2O_3 particles during preparation of, (1) 21*j*.
sulfate, systems. See *Systems.*
-sulfur, absolute Seebeck coefficient of molten system, (1) 19*d*.
systems. See *Systems.*
zinc ferrite, dissolving excess of ferric oxide in, (4) 110*a*.
effect of small additions of Co on, (11) 316*g*.
magnetic properties of nonstoichiometric, (9) 242*e*.
magnetic spectra at different temperatures, (11) 318*a*.
Niobates, luminescent, P (6) 159*c*.
sodium-strontium, dielectric properties and phase transitions of ferroelectric, (8) 219*i*.
Niobium, alloys, compatibility with hydrogen, (8) 207*j*.
carbide, carbon diffusivity determined in, (5) 135*b*.
-graphite, thermal expansion behavior of, (8) 216*e*.
powder, effect of particle dispersion on densification of parts from, (1) 8*d*.
carbonitrides, critical supercurrents in, (6) 165*j*.
chloride, systems. See *Systems.*
compounds, with P, As, Sb, S, Se, and Te synthesis and chemical transport, niobium fluoride, (11) 314*h*.
disilicides, effect of neutron irradiation on, (5) 135*b*.
elements, chemistry of, (3) 80*d*.
-Fe oxides, phase relations at 1180°C, (5) 136*g*.
in lead titanate-zirconate ceramics, determination of, (7) 194*j*.
$NbC_{0.78}$, $NbC_{0.970}$, $NbC_{0.980}$, and Nb_2C, heat capacity of below 320°K, (9) 250*f*.
normal orthophosphates of, (1) 23*c*.
oxides, structures of, (10) 290*h*.
oxycarbides, formation conditions of, (6) 165*d*.
oxychloride, interaction with chlorides of alkali metals and thermal stability of pentachloroxyniobates, (11) 317*f*.
pentachloride, hydrolysis of, (11) 317*b*.
pentachloride, interaction with chlorides of Li and Cu, (10) 287*c*.
pentoxide, α-, defect structure of, (9) 256*h*.
α-, in the range of 900° to 1400°C, electrical conductivity of near-stoichiometric, (4) 111*a*.
single crystal growth and polymorphism of, (6) 169*j*.
systems. See *Systems.*

Niobium (*continued*)
thermodynamics of nonstoichiometric, (1) 25*g*.
in rocks and minerals, radiometric-spectrometric determination of microgram amounts, (2) 45*i*.
selenide, system. See *Systems*.
selenides, with approximate composition $NbSe_3$, (2) 50*i*.
selenides and tellurides, magnetic properties of, (1) 23*f*.
separation, by introducing as dry solid into central step of liquid-liquid partition system, P (10) 283*d*.
systems. See *Systems*.
-Ta mixtures, buffer effects in spectrochemical analysis of, (6) 161*j*.
telluride, system. See *Systems*.
thin films, method to sputter, P (11) 307*d*.
and W, interaction with titanium boride, (1) 22*f*.
Nitrides, Al, solid solution, P (9) 241*f*.
of Al and B, production, P (9) 240*g*.
and carbides, of transition metals, relation between properties and their electronic structure, (9) 254*g*.
carbo-, critical supercurrents in Ni, (6) 165*j*.
fluorination of, (7) 199*f*.
of group III elements, stability of, (1) 19*h*.
layers, formation on Cr, (10) 286*i*.
metal, high-temperature thermal conductivity of transition, (4) 111*i*.
metal, production of, P (9) 241*e*.
with NaCl structure, superconducting critical temperatures, (7) 203*f*.
submicron, method of making, P (5) 126*j*.
Nitrogen, content, of diamond coat and core, (10) 288*f*.
density of liquid iron oxide in, (5) 134*i*.
dissolved, bonding in oxide glass melts, (1) 3*i*.
in glass melts, physical and chemical solubility of, (10) 265*j*.
interaction with U, (11) 317*g*.
ions, catalytic efficiency of Pyrex glass for recombination of, (8) 208*j*.
pentoxide, with graphite as possible reactor hazard, (3) 83*h*.
in solution, vibrational spectra of glassy oxides containing, (1) 6*a*.
Nomenclature, of crystallization textures and fabrics, in sedimentary rocks, (2) 47*h*.
glass, German-English glossary, B (6) 172*i*.
of glass defects, development of, (8) 209*d*.
Nontronite, study, by microscopy and electronic microdiffraction, (8) 227*f*.
Nordstrandite, preparation of, P (4) 109*c*.
Nozzles. See *Refractories; Spacecraft*.
Nuclear center, in Puerto Rico, neutron diffraction studies, B (2) 55*i*.
Nuclear energy, beta-ray source for nondispersive X-ray spectrochemical analysis, (4) 107*g*.
symposium on, B (6) 171*j*–172*b*.
Nuclear materials, fuel, producing spheroids by agglomeration, P (4) 101*h*.
fuels, powder metallurgy in development and production of new, (3) 67*g*.
particles, properties of coated, (2) 36*e*.
refractories as, (2) 36*d*.
thermodynamics of, B (6) 175*d*–*g*.
Nuclear power. See *Energy*.
Nucleation, agents, in diabase melts, (8) 216*c*.
of calcium phosphate, from solution, (2) 44*e*.
enhanced, of radiation damage in graphite, (4) 111*f*.
in gas-metal reactions, phenomena of, B (6) 175*c*.
in glasses, interrelations with microheterogeneity and crystallization, (5) 120*j*.
of metals, statistical mechanics, B (7) 204*d*.
in preparation of glass-ceramics, (4) 94*d*.

Oils, different weights, regulating group of burners for, (6) 163*g*.
firing, of brick, (8) 224*d*.
firing, in industry, (6) 163*j*.
heavy, related to life of open-hearth roof, (3) 68*c*.
Opacification. See *Enamels; Glass; Glazes*.
Opacifiers, Zr, effect on colors, (1) 12*j*.
Opacity, of phosphate opal glass, effect of constituents on, (3) 61*a*.
Optical devices, of fiber glass, method to make, P (2) 34*h*.
fiber optics code apparatus, P (9) 235*j*.
of glass fiber, P (2) 33*h*.
for image enhancement, P (2) 33*h*.
image enhancement with image rotation, P (2) 33*i*.
infrared transmitting, of magnesium oxide, P (5) 123*g*.
to measure flatness, (9) 245*g*.
for mineralogists and chemists, B (6) 174*h*.
for scanning, glass fiber, P (6) 149*h*.
Optical properties, of glass, to control chemical composition, (10) 264*d*.
of lead-barium-borate glass, (5) 121*h*.
of LiF, in extreme ultraviolet, (10) 289*d*.
and structure, of ZrO_2 films, (2) 51*b*.
of synthetic bromellite, (11) 319*c*.
and zone structure, of single Sb_2S_3 crystals, (9) 252*e*.
Ores, minerals in, excited X-rays identify in moving, (11) 312*c*.
Orientation, crystal, effect on behavior of magnesium oxide, (3) 81*f*.
crystal, effect on hardness of β-SiC, (1) 20*c*.
effect, in sodium borosilicate glasses, (4) 94*c*.
preferred, Young's modulus of pyrolytic carbon in relation to, (2) 54*a*.

Orthopyroxenes. See *Pyroxenes, ortho-*.
Orthosilicates. See *Silicates, ortho-*.
Oscillations, laser, and self *Q*-switching in activated glass, (7) 180*g*.
magnetoacoustic, spin-wave excitation and beating in YIG, (10) 290*e*.
microwave, in $GaAs_xP_{1-x}$ alloys, (1) 23*i*.
Osmium, Os_3Al_2 and $OsAl_2$, crystal structures, (2) 49*d*.
Ovens. See also *Furnaces; Kilns*.
to curl resin impregnated fibrous mat, P (6) 150*f*.
microwave, operation of, (8) 224*h*.
Oxidation, anodic, removal of thin layers of *n*-type Si by, (7) 192*e*.
anodic, of Si in ethylene glycol solutions, (11) 313*j*.
of boron carbide, (3) 68*a*.
of C, (4) 113*i*.
of cobaltous oxide, short-time high temperature, (5) 140*g*.
of graphite, by dissociated O, (1) 22*e*.
high-temperature, of molybdenum disilicide, (5) 125*g*.
of iron, scanning electron microscopy applied to, (5) 140*e*.
kinetics, gas flow through porous oxide in relation to, (2) 50*c*.
kinetics, of molybdenum disilicide, (10) 289*e*.
of lanthanides, diffusion-controlled, (11) 315*d*.
mechanics, of Zr and its alloys, oxide plasticity in, (7) 202*a*.
of porous substances, macrokinetics of, (10) 287*j*.
products, of titanium carbide, (7) 201*h*.
rates, localized on graphite surfaces by optical microscopy, (4) 112*d*.
reduction, equilibria in glass melts, ionic formulation of, (5) 121*b*.
formulation of reactions in glass melts, (10) 264*j*.
pairs in glass, mutual interaction of different, (5) 121*f*.
potential, of sexivalent and quadrivalent uranium ions, (7) 201*h*.
of rhenium films, (7) 192*a*.
room temperature, of silicon during and after etching, (5) 140*c*.
of Si, in dry oxygen, (5) 139*f*.
of Si, relation for thermal, (5) 136*e*.
state, preparation of compounds of lower, (3) 85*d*.
thermal, of Si, (10) 291*c*.
of titanium nitride, in dry and moist air, (4) 112*e*.
of V, at high temperatures, (3) 68*c*.
Oxides. See also *Rare earths* and specific types.
adherence, in development of chemical bonding at glass-metal interfaces, (2) 30*c*.
of Al, Fe, and Ti, complexometric determination of, (6) 163*b*.
of CaO, ZnO, MgO, or CdO, solid state reactions with MnO_2 or Mn_2O_3, (2) 52*a*.
coating, chemically formed on Al, (8) 207*h*.
common, temperature dependence of hardness of, (11) 301*e*.
crystal growth, by flux evaporation, (11) 318*d*.
effect, on reduction of lead silicate glasses in hydrogen, (4) 93*f*.
electrolytes, factors effecting performance in high-temperature thermodynamic measurements, (7) 199*c*.
ferro-magnetic, P (11) 306*i*.
films, grain boundaries in growing, (2) 50*e*.
at low temperature, microwave discharge deposition of, (10) 277*f*.
thermally grown on molybdenum silicides, structure and chemistry of, (1) 25*f*.
flame-sprayed, to protect equipment, (9) 232*c*.
in form of hollow spheres, P (11) 303*f*.
of groups IV and V elements, zinc oxide reactions with, (2) 51*j*.
highly refractory, porous ceramics from, (7) 187*f*.
host lattices, heterotype mixed phases of fluorite or fluorite-like structures in predominantly, (7) 200*a*.
hot-pressed translucent, B (5) 142*i*.
interactions, with metals, (7) 178*j*.
layer, diffusion of B in Si through, (10) 284*c*.
nuclear reactions in study of, (9) 252*d*.
on U, structure of primary, (11) 318*b*.
manufacture of, P (5) 133*e*.
metal, of Co, Sb, and Ta and method to prepare, P (7) 193*e*.
effect of additions on high-temperature electrical conductivity of alumina, (5) 128*c*.
infrared absorption of, with spinel structure, (3) 84*g*.
process for producing, P (2) 48*c*.
production of, P (1) 19*b*.
resistance of films on glass to ionizing radiation, (10) 266*f*.
semiconductors, (6) 158*g*.
metallic, effects on α-transformation of alumina, (4) 110*e*.
mixed, microspheres, (10) 272*f*.
molten, dipping electrode electrical conductance instrument to use with to 1700°C, (11) 310*b*.
molten, as possible fuel matrixes for reactors, (6) 153*e*.
monofilaments, preparation of, P (11) 303*d*.
particles, and dislocations in Mg, interaction between, (1) 21*e*.
particles, surface diffusion and growth on metal surfaces, (2) 52*g*.
plasticity, in the oxidation mechanism of Zr and its alloys, (7) 202*a*.
production, by plasma process, P (11) 303*h*.
semiconducting, defect structure and electrical properties of, (11) 315*f*.

Oxides (*continued*)
semiconductive, factors affecting reactivity during spinel formation process, (11) 316*e*.
sesqui-, deposited in chromite grains, (5) 142*b*.
single-phase, Petch relation in, (1) 24*c*.
solid, type of conductivity determined by measuring emf, B (1) 26*i*.
in steel, origin of, (1) 10*b*.
surface film, effect on lifetime of vacancies in quenched specimens, (9) 249*f*.
with TiO_2-type and related structures, isomorphic and morphotropic relations of, (7) 200*g*.
transition metal, variations in electrical conductivity as function of equilibrium 0 pressure at high temperature, (9) 242*g*.
U and Pu carbides from, aspects of preparation, B (6) 172*c*.
volatile, of some materials used in nuclear technology, B (6) 175*c*.
-water interface, interrelation of zero point of charge and heat of immersion, (1) 24*a*.
Oxygen, activity, over solid solutions of ferrite of cobalt with magnetite, (11) 313*d*.
atmospheric, effect on bubble formation in galvanic cell platinum/glass-refractory material/platinum, (1) 4*c*.
atomic, kinetics of oxidation of carbons and graphites by, (2) 51*c*.
and C, isotopic fractionation between coexisting calcite and dolomite, (10) 289*e*.
and carbon monoxide, adsorption under irradiation on alumina, (11) 313*f*.
content, of nickel ferrites at 1300°C, (1) 13*g*.
deficiency, effect on bonded silicon carbide refractories, (10) 271*a*.
diffusion into surface layers, nuclear reactions to study, (9) 252*d*.
dissociated, high temperature kinetics of graphite oxidation by, (1) 22*e*.
dry, oxidation of Si in, (5) 139*f*.
effect, on sintered CdS photoconducting films, (10) 276*i*.
equilibrium between ferrites with spinel structure and, (7) 191*j*.
exchange and diffusion, in calcia-stabilized zirconia, (4) 112*e*.
fugacity, effects on crystallization in mafic magmas, (7) 202*b*.
interactions, with surfaces of cadmium sulfide single crystals, (11) 317*i*.
ion activity, its effect on redox equilibrium in glass, (3) 61*g*.
Mg-Fe-O alloys, solid solution and precipitation hardening in, (6) 169*j*.
metal-to-, especially molybdenum-to-, properties of multiple bonds, (8) 227*c*.
in Ni ferrites, discussion, (6) 166*j*.
phases, including crystal structure of $Ba_5SrTa_4O_{15}$, (6) 165*c*.
-platinum-rhodium, electrode in silicate melts, (5) 139*j*.
positional parameters, of Mn_2O_3, (4) 112*f*.
reboil, electrochemical theory for, (11) 296*i*.
relation, to life of open-hearth roof, (3) 68*c*.
solid, study by neutron diffraction, B (2) 55*j*.
spinels, containing trivalent Mn, ferromagnetism and ferrimagnetism of, (11) 317*a*.
strongly adsorbed, interaction with free spin centers in carbon, (4) 111*j*.
systems. See *Systems*.
in Th and Y, carbon-reduction to determine, (5) 131*e*.

Packaging, for glass, or fragile items, P (1) 7*b*.
palletized, for cylindrical products, P (5) 124*i*.
Palladium, decorating compositions, P (2) 48*a*.
$PdAs_2$ and $PdSb_2$, crystal structure of, (3) 85*h*.
weight, loss at high temperatures, (3) 83*a*.
Palygorskite, autoclaved, to form coagulation structures, (3) 81*i*.
colloid chemistry of, B (8) 228*f*.
crystal chemistry, and thermal behavior, (3) 80*h*.
Panels. See *Building materials*.
Paper, asbestos, containing C, P (11) 301*i*.
roofing, improved glass fibers to reinforce, (11) 296*g*.
Particles. See also *Colloids*.
abrasive, sizing of, (7) 177*f*.
acoustic counter, (8) 222*h*.
analyzer, P (11) 311*c*.
in basic refractories, bonding materials between, (10) 270*e*.
conducting and nonconducting, method and apparatus to separate, P (6) 161*e*.
constitution in mineral soils, geopractical effects of variable surface, B (7) 204*g*.
counter, head control for, P (3) 77*a*.
counter, optical device as, P (8) 224*a*.
ferroelectrics of ultrafine, (7) 191*e*.
fine, dispersion in nonpolar organic solvents, (6) 156*c*.
fine solid, apparatus for elutriating and measuring, P (11) 311*a*.
forming and drying, P (9) 244*j*.
grit, method to reclaim from wet blasting, P (5) 131*c*.
low micron size, centrifugal air separator for, P (2) 47*h*.
mixtures, whirlpool to separate, P (2) 48*c*.
packing, effect on whiteware bodies, (10) 275*j*.
rounded, process to produce finely divided, P (3) 75*b*.
sedimentation time, method to calculate, (7) 197*i*.
shape, size, roundness, as related to theory of sieving, (2) 43*h*.
sieving characteristics of symmetrical tabular, (2) 43*h*.

Particles (*continued*)
size, applications of distribution curves for, (6) 169*g*.
change in size during pressing, (10) 270*g*.
determined in sediments by radioactive radiation, (11) 309*g*.
effect of grinding, (3) 71*e*.
of heavy mineral concentrates, in Lithuanian beaches, (9) 250*g*.
of Lithuanian quaternary sands, (11) 314*c*.
measurement, of alumina by centrifuging, (7) 195*d*.
nomograph to convert average intercept size to, (8) 226*j*.
relation to properties of whiteware bodies, (10) 276*b*.
theory and industrial applications, B (9) 259*h*.
size analysis, transformation method for size-distribution moments, (5) 142*a*.
size analyzer, P (1) 17*a*.
size control, of nonplastic materials, (2) 44*g*.
size distribution, apparatus to analyze, P (11) 311*a*.
determined in portland cement from Wagner turbidimeter data, (3) 59*e*.
instrument to analyze, P (5) 132*c*.
thermal stability of sedimenting suspensions to measure, (2) 45*c*.
transformation of weight- and number frequencies for phi-normal, (5) 142*b*.
size reduction, jet pulverization, (1) 15*i*.
solid, factors affecting morphology in liquid matrix, (5) 136*e*.
solids of, perfect mixtures statistically defined, (5) 141*c*.
specific surface, calibration of apparatus to determine, (8) 222*j*.
spherical, estimation of dihedral angle between from measurements in a plane section, (7) 199*a*.
studying device, control circuit, P (11) 311*c*.
surface areas, measurement of, P (1) 17*d*.
in suspension, optical apparatus to analyze size and number of, P (11) 311*b*.
system to separate, P (6) 161*g*.
volume, determination in mixture, P (5) 132*c*.
Pelletization, rate, of zinc oxide powders, (3) 74*i*.
Perchlorates, zirconyl, thorium, and uranyl, thermal studies on hydrates of, (8) 228*b*.
Periclase, hydration resistance of, (8) 215*i*.
low silica, performance of open-hearth roof from basic iron-oxide bonded, (6) 153*i*.
U. S., in basic brick compared with brick containing Japanese seawater magnesite, (3) 65*i*.
Periodograms, to study, irregularities in crystals, B (2) 56*a*.
Perlite, in 1964, (1) 18*b*.
products, method of preparing, P (5) 124*i*.
Permeability. See also *Porosity*.
of monolayers, transport properties of, (4) 114*f*.
of porous materials, factors influencing, (9) 250*h*.
Permittivity. See *Dielectrics, constant*.
Perovskites, compounds, ferroelectric properties of monocrystals of, (4) 111*i*.
containing Sr, magnetic properties of, (4) 112*i*.
group, compounds of, (5) 142*d*.
$LaVO_3$ and YVO_3, single-crystal growth and properties of, (9) 255*c*.
nonmetallic, ferromagnetic interactions in, (11) 316*j*.
-type structure, magnetic compounds of hexavalent rhenium with, (7) 201*a*.
Petalite, systems. See *Systems*.
thermal transformation and crystallography of, (3) 87*e*.
Petrography, carbonate, of rocks of West Flank Teton Mountains, Wyoming, (2) 47*e*.
and derivation, of Jurassic-Cretaceous clastic rocks, southern Rocky Mountains, Canada, (3) 78*i*.
of Duperow formation (Upper Devonian) in North Dakota, (2) 46*j*.
Petrology, of Paleocene-Eocene Aquia formation, Virginia, Maryland, and Delaware, (2) 47*a*.
of redbeds, in Texas and New Mexico, (5) 133*f*.
of sandstones, in Arkansas and Oklahoma, (5) 133*c*.
tool, electron-excited luminescence as, (1) 21*b*.
pH. See *Hydrogen ion concentration*.
Phase, composition, of portland cement clinker, (10) 262*h*.
liquid, capillary phenomena in densification during sintering in presence of, (9) 255*a*.
liquid, chemical aspects and reactivity in porcelain, (2) 39*e*.
relations, subsolidus, in systems $BaCO_3$-$SrCO_3$, $SrCO_3$-$CaCO_3$, and $BaCO_3$-$CaCO_3$, (2) 52*d*.
transformations, Kikuchi electron-diffraction and dark-field techniques in electron-microscopy studies of, (1) 16*f*.
transformations, in natural beryl, (8) 226*e*.
transitions, and competitive structures, B (9) 259*d*.
ferroelectrics with diffuse, (4) 111*b*.
of second kind in SnSe, (9) 253*c*.
and structure of high-temperature phases of cryolite, (3) 84*h*.
Phase diagrams. See *Equilibrium studies*.
Phenacite, -spinel, transition in $LiAlGeO_4$, (10) 289*b*.
Phlogopite. See *Mica*.
Phosphates. See also *Glass* and specific types.
as ammonium 12-molybdophosphate, effects of arsenate and transition-metal ions on precipitation of, (2) 44*c*.
analysis for, interference from silica in, (7) 195*b*.
and arsenates, chemical effects of thermal neutron capture in, (3) 79*j*.
bond, castable refractories, (8) 216*e*.
Phosphates (*continued*)
content, means to determine, (4) 107*e*.
ions, adsorption by Egyptian clays, (6) 165*a*.
opal glass, effect of constituents on opacity of, (3) 61*a*.
pyro-, of Li and K and NaF, fusibility diagram of system, (1) 21*e*.
rocks, constitution and citric solubility of Japanese, (9) 247*c*.
tricalcium, heat of formation of α and β modifications of, (5) 136*i*.
Phosphides, MnP-type, crystal structure, refinements of, (2) 49*b*.
superconducting, of transition metals, (9) 257*a*.
Ti, preparation and phase studies of, (8) 227*a*.
Phosphoanhydrite. See *Anhydrite*.
Phosphoric acid, dehydrated, composition and density, (7) 197*i*.
dehydrated, solidification of, (7) 202*j*.
inhibited, for high-alumina refractories, (8) 215*e*.
poly-, equations for chain length distributions in, (3) 61*d*.
Phosphors, P (1) 15*b*.
alkaline earth molybdate and tungstate, uranium and lanthanide activated, P (10) 279*i*.
arsenate and phosphate, P (1) 14*f*.
calcium and magnesium silicate, with activator of terbium, P (9) 242*j*.
coating, adherence method, P (11) 306*j*.
electroluminescent, P (10) 278*f*.
containing moisture absorbents, P (4) 104*e*.
increasing light emission, stabilization, and rejuvenation, P (2) 42*d*.
method to process, P (7) 193*h*.
Eu-activated, effect as red component on color TV screens, (8) 220*c*.
Eu-activated, performance in color TV tubes, (8) 220*d*.
layers, slurry method to apply to color TV screens, (8) 208*g*.
method to produce, P (4) 105*d*.
particle sizing, P (11) 308*c*.
photoconducting, B (9) 259*f*.
silver halide, means to increase storing ability, (2) 49*g*.
various, radioluminescence and photoluminescence efficiencies of, (11) 304*j*.
YVO_4:Eu, for color TV, (8) 220*i*.
zinc-cadmium sulfide, discoloration of color tubes by, (11) 305*b*.
ZnS, anomalous paramagnetic susceptibility of shocked, (10) 283*h*.
longwave light-emitting, P (8) 221*e*.
thallium-activated, P (1) 15*d*.
Phosphorus, As and Ge, simultaneous determination and separation of Si and As by solvent extraction, (9) 246*a*.
iodides of, Lewis basicity and structure, (3) 83*c*.
magnetic properties of iron compacts containing, (6) 158*e*.
phosphatic ore, recovery of P values and cement clinker from, P (5) 119*e*.
phosphatization, of compact zirconium, (9) 253*e*.
radioactive, research on glass surfaces with, (2) 32*h*.
in SiO_2, effect shown by infrared spectroscopy, (10) 285*g*.
triiodide-boron triiodide, new compound, (7) 201*f*.
Photoconductive effect, and(or) **Photoconductivity,** of CdSe, effect of background light intensity on steady-state, (6) 168*d*.
in CdSe polycrystalline layers, spectral dependence of, (6) 170*c*.
in CdS and CdSe, (8) 226*h*.
of CdS films, effect of O on, (10) 276*i*.
enhancement, in CdS single crystals, (4) 111*h*.
mixing, intrinsic and extrinsic in semi-insulating GaAs, (7) 200*c*.
photoconductive layer, method to produce, P (3) 73*i*.
in single CdSe crystals, anisotropy of, (11) 313*i*.
of sintered (Cd,Zn)S layers, (10) 289*b*.
Photoconductors. See *Conductors, electrical, photo-*.
Photoelectric effect, properties, of CdTe film contacts with metals, (3) 72*i*.
Photography, contact, with UV to determine absorption edges of ZnS polytypes, (1) 20*g*.
holographic, high-speed with conventional and *Q*-switched ruby lasers, (1) 13*j*.
of single crystals, method for back reflection oscillation, (6) 162*f*.
Weissenberg camera, preliminary orienting procedure for single crystals with, (9) 253*e*.
Photometers. See also *Spectrophotometers*.
micro-, to measure spectral reflectivity, (8) 223*a*.
Photometry, determination, of rare earth ions, (8) 223*h*.
flame, to determine alkalis in cements, (3) 58*j*.
to determine Mg in limestone, (10) 280*j*.
to determine K, Na, and Ca in feldspars, (3) 75*h*.
to determine Na in U ores, (2) 44*g*.
Photovoltaic effect, anomalous, of CdS single crystals, (10) 276*j*.
in polycrystalline films of CdSe, high-voltage, (6) 167*j*.
Phyllites, formation, by direct attack of different minerals, (7) 199*g*.
Physical properties, changes, in three types of magnesia clinker fired in different atmospheres, (6) 152*e*.
and chemical properties, of Cupoline, a patching material, (1) 9*d*.
of French patching material, RP-1, (1) 9*e*.
of ground coat enamels, effect of bubble structure on, (6) 145*g*.
Physical properties (*continued*)
of Lithuanian quaternary and prequaternary clays, (9) 253*a–b*.
of low-firing ground enamels, (2) 30*a*.
of runner brick, related to chemical properties and damage done to them, (9) 239*c*.
of titania cover coats, stress as related to, (6) 146*a*.
variations, in chalcogenide glass, (11) 296*h*.
of whiteware, conceptions of viscosity, workability, plasticity, and binding power, (3) 71*g*.
Physicochemical properties, of barium hexaborate, (11) 319*a*.
of glass, as function of composition, (10) 266*d*.
of Indian clays, (3) 84*d*; (6) 169*f*.
of kaolins and clays used in Sao Paulo ceramic industry, (11) 312*g*.
of sodium silicates, high in silica, (2) 28*i*.
of sodium-strontium-silicate glasses, (1) 4*j*.
Physicomechanical properties, of glass, studies of continuously rolled, (8) 210*h*.
Pickling, facilities, for enameling plants, (10) 263*j*.
operations, effect of synthetic wetting agents on, (8) 207*h*.
processes, survey of one-coat, (7) 179*c*.
spray sulfuric acid, for one-coat enameling, (8) 208*c*.
waste, treatment of enamel, (8) 208*e*.
Piezoelectricity, crystal, P (4) 106*a*.
in crystals, B (8) 228*j*.
hybrid filter for, (6) 159*j*.
materials, compositions, P (10) 279*g*.
of lead titanate and 0.1 to 5%(mole) calcium fluoride, P (7) 194*a*.
lead zirconate-titanate, modified by bismuth ferrite, (10) 277*g*.
piezoelectric, applications, bodies for, P (7) 192*a*.
transducers, vapor-deposited thin-film, (10) 277*e*.
unit, ruggedized low frequency, P (3) 72*g*.
use, process to make ceramic bodies for, P (7) 194*b*.
piezoresistive material, P (8) 221*g*.
properties, of $Pb(Mg_{1/3}Nb_{2/3})O_3$–$PbTiO_3$–$PbZrO_3$ solid solutions, (1) 13*h*.
wave filter, (9) 242*e*.
Pigments, amorphous hydrogen aluminosilicate, P (9) 247*d*.
antimony yellow, composition and preparation, (4) 102*d*.
celsian type, for underglaze blue, (4) 103*b*.
Cr as, (7) 190*d*.
color-reactable adsorbent, and coating with P (3) 71*j*.
color-reactable inorganic adsorbent, and sensitized sheet coated with, P (4) 109*d*.
possibility of MnO–ZnO solid solutions as, (2) 51*d*.
quality, TiO_2, P (8) 225*d*.
in sanitary-ware glazes, control of manufacture, (2) 39*d*.
silica, apparatus to produce, P (8) 225*a*.
silica, and preparation of, P (7) 197*a*.
siliceous, method to produce finely divided, P (5) 133*h*.
slurries, process for classifying calcined conditioned titanium dioxide, P (4) 109*d*.
of spinels, titanium-tin and aluminum-chromium (5) 139*i*.
structure, in Se ruby glass, (8) 211*d*.
TiO_2, P (1) 19*b*.
analysis by spark-source mass spectrography, (10) 280*g*.
based, P (8) 225*j*.
ultramarine, thermographic study of formation, (2) 53*d*.
yellow, P (11) 313*b*.
Pipe. See also *Tile*.
BK-, concrete coated, (1) 7*g*.
clay, (2) 35*g*.
history of Broseley, (9) 229*j*.
improvements needed, P (9) 237*e*.
junctures and method, P (7) 185*a*.
method of making, P (6) 151*g*.
new Illinois plant, (8) 214*f*.
polyurethane for joints, (4) 98*j*.
take-out device for, P (4) 98*g*.
coupling, P (4) 98*a*.
fitting, glass lined and process for lining, P (5) 120*a*.
glass, coupling for, P (5) 122*i*.
coupling for sections of different diameter, P (5) 122*b*.
drain line coupling for plain end, P (5) 122*e*.
lined, apparatus and method to heal, P (7) 179*a*.
means to calculate strength for that laid in ground, (4) 92*e*.
production of heat resistant, (10) 266*a*.
reinforced resin, method and apparatus for forming, P (4) 97*f*.
sewer, Flex Lox jointed, (6) 151*e*.
stoneware, most modern plant in Europe, (1) 7*e*; (6) 151*d*.
Plagioclase, feldspars, from coal-ash slags, medium to calcic, (6) 170*f*.
igneous, patchy zoning in, (2) 54*c*.
low structural state, variations in X-ray powder patterns of, (6) 171*b*.
Plasma, arc, in powder metallurgy, (7) 178*f*.
arc jet, hottest thing in testing, (5) 131*e*.
discharges in vacuum systems, protection of electrical components from, (4) 107*h*.
a new technology, (11) 311*h*.
in semiconductors, doppler effects of drifting, (6) 157*h*.
spraying, variables in, (8) 208*e*.
Plaster of Paris. See *Gypsum; Plasters*.
Plasters, board, lightweight cellular, (11) 294*j*.

Plasters (*continued*)
calcium sulfate, effect of impurities and additions on hydration of slurries, (11) 293*j*.
coating, method to form highly bonded shrink resistant, P (5) 119*c*.
composition, P (4) 91*a*.
gypsum, effect of organic acids and salts on setting time, (9) 230*i*.
mixer for, (5) 127*e*.
new type, (11) 294*a*.
of Paris, coating compositions of and means to produce, P (8) 207*g*.
preparation, by vacuum mixer, (10) 275*i*.
properties and testing, (2) 29*b*.
Plasticity, of whiteware bodies, (10) 275*j*.
Plastometer, to measure rheology, of moldable materials, (3) 76*f*.
Plating. See *Coatings*.
Platinum, and its alloys, wetting by glass, (4) 96*c*; (5) 122*b*.
PtP_2, $PtAs_2$, $PtSb_2$, and α-$PtBi_2$, crystal structures of, (3) 85*h*.
-rhodium-oxygen, electrode in silicate melts, (5) 139*j*.
sheathing, of refractories for glass industry, (11) 301*i*.
weight loss, at high temperatures, (3) 83*a*.
Plutonium, -bearing carbides, work on, B (6) 172*b*.
borides, (1) 9*f*.
PuO_2-UO_2 fuels, fabricating processes, (6) 152*c*.
Polarization, of $NaNbO_3$-$KNbO_3$, solid solutions, (1) 24*i*.
space-charge, in glass films, (9) 234*g*.
Polarography, cathode-ray, to determine Te content, (2) 44*c*.
indirect, to determine Al, (3) 76*a*.
polarographic, determination of Al in silicate materials with use of Eriochrome Black T, (2) 44*i*.
Polishing. See also *Abrasives; Diamonds*.
capacity, of powders, (5) 121*i*.
chemical, of glass, (10) 264*j*.
chemical, of $SrTiO_3$, (3) 81*g*.
composition, of rare earth nitrates for glass, P (6) 150*b*.
fire, method for edges of hollow glass articles, P (8) 213*f*.
of glass, (10) 265*e*.
rare-earth oxides for, P (10) 269*j*.
relation between chemical and mechanical processes during, (4) 95*c*.
mechanical, to remove layers of metals and metal oxides, (5) 140*a*.
methods, their application to optical metallography, B (6) 173*g*.
process, for crystal or lead-crystal glass, P (10) 269*i*.
Polishing apparatus. See also *Abrasives; Diamonds*.
for both sides of glass ribbon, feed system for, P (6) 150*h*.
device, wear indicator for, P (6) 143*j*.
for glass, P (5) 122*d*.
pads, for glass, P (6) 150*i*; P (9) 236*i*.
semiautomatic, for porcelain articles, (2) 39*i*.
Pollucite, synthetic, in system Cs_2O-Al_2O_3-$4SiO_2$–Cs_2O-Fe_2O_3-$4SiO_2$–H_2O, their phase relationship and physical properties, (3) 86*b*.
Polymerization, /depolymerizations relations, model for silicate melts and glasses, (2) 32*i*.
/depolymerization, statistical model of relations in silicate melts and glasses—correction, (5) 121*f*.
Polymers, in hydraulic cements, (1) 2*i*.
inorganic, based on rubidium phosphate, (1) 25*b*.
inorganic, and ceramics, B (11) 320*e*.
with porous glass, possibility of submicroscopic compatibility of, (8) 211*g*.
Polymorphism, of sodium metavanadate, (3) 84*j*.
of tricalcium silicate, (9) 256*c*.
Polymorphs, silver iodide, (9) 255*c*.
Porcelain, art. See *Art and artware*.
articles, grinding and polishing, (2) 39*i*.
bodies, modulus of rupture and properties of, (4) 102*i*.
body, effect of previously melted feldspar on, (2) 39*g*.
decoration, lusters as, (2) 39*f*.
dental. See *Dental ceramics*.
electrical. See also *Insulators, electrical*.
developments in, (4) 102*f*.
effect of batch distribution on quality of, (1) 12*j*.
firing in tunnel kilns, (3) 71*f*.
ultrasonic testing for cracks, (2) 40*e*.
evolution of, (5) 127*d*.
expansion, effect of alkali content on, (10) 275*h*.
factories, modern lighting in, (1) 15*j*.
flatware, standardization of saggers for, (2) 39*j*.
German, artistic development, (8) 205*j*.
glaze, for black, (2) 39*a*.
hard, electrical tunnel kiln for firing in reducing atmosphere, (8) 224*d*.
hard, improving strength of, (3) 71*d*.
high strength, for insulators, (9) 241*h*.
history of, B (1) 26*d*.
household, machines for glazing, (2) 39*g*.
insulators, relation of microstructure to expansion and electrical and mechanical properties of forsterite, (8) 219*i–j*.
manufacture, development of, (2) 39*d*.
product range, from statuettes to high tension insulators in Hungarian factory, (2) 54*g*.
rapid drying, (2) 39*g*.
Royal Rockingham, early history, (8) 206*b–c*.
semi-, dinnerware from Philippine materials, (8) 219*f*.
semi-, effects of frit additions on raw glazes for, (8) 219*a*.
Porcelain (*continued*)
structure development, chemical aspects and reactivity of liquid phase, (2) 39*e*.
Pores, distribution, effect on strength of cross sections of specimens, (11) 316*d*.
size distribution, calculation from adsorption data, (11) 310*h*.
size distribution, rock properties computed from random, (4) 107*j*.
structure, relation between impermeability of activated slag concrete and, (8) 207*g*.
Porosity. See also *Permeability; Pores*.
of glass, effect on compressibility, (1) 4*b*.
measurement, of granular materials, (3) 76*c*.
reduction, in basic refractories in furnace roof to prolong life, (8) 216*e*.
Porous materials. See also *Cements; Concretes; Insulation, thermal*.
bodies, change in skeletal volume of fluid-filled under stress, (1) 19*g*.
moisture expansion of, (2) 35*h*.
principles of gas flow through finely, (5) 140*c*.
capillary, mass transfer in extraction of moisture from, (6) 168*d*.
macrokinetics of oxidation of, (10) 287*j*.
permeability, factors influencing, (9) 250*h*.
solid, heat transfer through, (6) 167*i*.
Portland cement. See *Cement, portland*.
Potassium. See also *Alkalis*.
-Bi titanates, determination of cell symmetry and high-temperature phase transformations by X rays, (5) 135*c*.
borates, (2) 52*i*.
bromide, systems. See *Systems*.
bromide, UV laser emission by crystals of, (1) 25*i*.
Ca and Ba, fusibility diagram of the system of chlorides of, (4) 111*f*.
systems. See *Systems*.
chloride, diffusion of Cd ions in, (7) 198*c*.
interaction with praseodymium chloride in melts, (2) 52*a*.
interaction with V trichloride, (11) 317*j*.
-LiCl, oxides and sulfides in molten eutectic, (5) 134*d*.
systems. See *Systems*.
chlorides, interaction with hexa- and pentachloride of Na, (11) 317*e*.
chloroplatinate, thermal decomposition of, (8) 228*a*.
compounds, as radioactive indicator to study glassmaking processes, (4) 94*h*.
dihydrogen phosphate, growth of monocrystals of, B (11) 319*j*.
in feldspars, determination of, (3) 75*h*.
fluoride, systems. See *Systems*.
fluorotantalate, melting temperature and thermal stability of, (1) 23*h*.
-hydrosilicates, preparation of $(KHSiO_3)x$, $KHSi_2O_5$(I), and $KHSi_2O_5$(II) from methanole, (3) 85*e*.
Li and Na, fusibility diagram of system of bromides of, (9) 250*e*.
niobate crystals, growth on seeds from potash melt, B (11) 320*b*.
nitrate, to reveal diamond structure, (1) 25*g*.
oxide, means to determine, (4) 107*e*.
and potassium borohydride, fusibility diagram in system of hydrates of, (4) 111*e*.
-SrO-SiO_2 glass, changes in composition during analysis of, (9) 232*j*.
peroxydicarbonate, synthesis of and properties, (4) 113*e*.
phosphate, systems. See *Systems*.
Kcl:Tl, thermal glow peaks at room temperature, (3) 87*c*.
$K_4Nb_6O_{17}$ single crystals, preparation of, (10) 289*f*.
$K_{1.70}Na_{0.30}ZrSi_6O_{15}$, daylite, crystal structure, (7) 198*b*.
K_2SO_4, method to detect in portland cement clinkers, (8) 207*e*.
$KTaO_3$-$KNbO_3$, growth of mixed crystals of, (9) 250*e*.
pyrophosphate, systems. See *Systems*.
retention, in montmorillonites, (3) 85*a*.
silicate, in slips, enamels, and glazes, (1) 16*c*.
and sodium, reciprocal system of chlorides and hexafluoroaluminates of, (4) 113*g*.
Na, Sr, and Ba, fusibility diagram of system of the fluorides of, (4) 111*f*.
sulfate, systems. See *Systems*.
systems. See *Systems*.
Potters, Craftsman Association, development of, (10) 261*i*.
handbook, materials, design, equipment, and production, B (10) 292*d*.
Pottery. See also *Archeology; Art and artware; Bodies, ceramic; Design; Dinnerware; Earthenware; Stoneware; Whiteware*.
art, (2) 27*h*.
from Black Forest, (8) 205*j*.
crown, survival in ancient Hungarian earthenware kilns, (2) 28*d*.
Davenport service, (3) 57*j*.
decoration. See *Decoration*.
exhibition, in Kempten, (1) 1*j*.
at Fauenwoerth on the Chiemsee, owned 360 years by Klampfleuthner family, (1) 1*i*.
by German potter, (10) 261*j*.
by German potters in Istanbul, (3) 57*j*.
Japanese, modern, B (1) 26*e*.
and man, B (6) 172*c–h*.
production, improved process, P (10) 276*a*.
stone, mineralization in deposits in Japan, (1) 18*f*.
stone, mineralogy of Izumiyama, (1) 18*g*.
studio, near Heidelberg, Germany, (1) 2*a*.
from studio near Hamburg, Germany, (1) 1*j*.
Pottery industry, jigger for, P (7) 190*j*.
Potterymaking apparatus and equipment. See also *Dryers; Kiln furniture; Kilns; Materials handling; Molds*.
automated for batching and mechanized mill loading, (6) 155*j*.
Potting compounds, inorganic, for high temperatures, (2) 40*h*.
for metallographic specimens, (9) 245*f*.
Powder metallurgy, arc plasma in, (7) 178*f*.
importance, to develop and produce nuclear fuels, (3) 67*g*.
sintering in, handbook of microscopy technology in, B (9) 258*c*.
Powders. See also *Granular materials*.
ceramic, effect of explosive shock waves on, (10) 285*f*.
compaction, method to explosively form dense body, P (3) 75*a*.
compaction pressures, (2) 9*h*.
disk samples, preparation for Seeman-Bohlin examination, (3) 76*h*.
elastic moduli, method to calculate from compressibility and Debye temperature data, (7) 202*j*.
fine, of thoria, urania, and mixtures of, P (1) 11*d*.
grain size in, process and apparatus to determine distribution, P (1) 17*c*.
granular dry-press, flow properties of, (8) 219*c*.
granular, effects of pressure and bonds on compaction, (2) 39*i*.
ignitability, (3) 67*e*.
mixtures, studies of dissolving process of those with different solubilties in water, (5) 141*d*.
mixtures, theorems to calculate weight ratios to produce maximum packing density, (7) 203*b*.
oxide, properties, (9) 248*h*.
powdered product, holder for firing or sintering, P (6) 163*j*.
reactions in, microautoclave to observe, (11) 310*j*.
size, methods to characterize in subsieve range, (8) 223*e*.
Power. See also *Energy*.
Praseodymium, chloride, interaction with chlorides of Na and K in melts, (2) 52*a*.
chloride, systems. See *Systems*.
fluoride films, dielectric properties of, (6) 157*j*.
systems. See *Systems*.
thin films, dielectric properties of, (11) 315*b*.
Precipitates, identification, on grown-in dislocations in MgO, (2) 50*i*.
washing of, (9) 253*g*.
Precipitation, of calcium fluoride, from homogeneous solution, (11) 310*d*.
co-, of alumina and silica gels and their transformation at higher temperatures, (5) 134*d*.
in MgO single crystals, electron microscope study of, (9) 249*i*.
of phosphate as ammonium 12-molybdophosphate, effects of arsenate and transition-metal ions on, (2) 44*c*.
simultaneous, to prepare magnetic ferrite, (9) 253*f–h*.
Precipitators, electrostatic, inlet-gas humidification system for, (5) 118*j*.
electrostatic, power connection for, P (2) 43*f*.
Presses, automatic, for industry, (2) 43*d*.
brick, improvement in, P (8) 222*e*.
hammer, P (4) 106*j*.
high pressure, P (9) 245*a*.
to press prepared specimens, P (11) 309*a*.
for specimen material, P (11) 308*j*.
hot-, for laboratory investigations, B (11) 320*h*.
hydraulic, compared to pneumatic hammer, (2) 35*h*.
molding, for tile, hydraulically moved control for lower pressing plungers in, P (10) 280*b*.
pressure intensifier, means to increase strength of anvil member for, P (9) 244*i*.
to produce high static pressures within a solid, P (9) 244*j*.
rotary and sliding, for tile, (11) 308*h*.
rotary table, constructional products from, (11) 308*g*.
for wafers, from drips of glass, P (11) 299*d*.
Pressing, analysis, thermal, (8) 216*e*.
apparatus for powders, P (4) 106*j*.
of cermet parts, use of hard-alloyed tools with transfer presses, (3) 69*j*.
dry, (5) 130*e*.
control of, (10) 276*i*.
in manufacture of clinker brick, (2) 35*g*.
presses and dies for special shapes, (2) 43*e*.
of firebrick, effects on physical properties, (3) 67*c*.
of granular mixtures, change in grain size during, (10) 270*g*.
hot-, (5) 130*g*.
of alumina, final stage densification in vacuum, (1) 21*c*.
of CrO_3, (2) 50*h*.
of clays and alumina, (10) 290*e*.
continuous, B (11) 320*h*.
graphite dies for, (5) 130*f*.
process for powder, P (4) 106*a*.
of thoria powders, (5) 125*d*.
hydrostatic, (3) 71*d*.
hydrostatic, as replacement for slip casting sanitary ware, (5) 127*f*.
isostatic, (5) 130*g*; (9) 241*h*.
of slurries, apparatus for, P (5) 130*h*.
steam, in structural clay products industry, (2) 35*j*.
of stoneware tile, (3) 71*e*.
thermal, analysis of, (8) 216*e*.
Pressure, bar, experiments with the split Hopkinson, (1) 25*a*.
breakthrough, for penetration of mercury between packed spheres, (4) 112*b*.

Pressure (*continued*)
dependence, of emf of thermocouples, (6) 162*g*.
derivatives, of elastic constants of single-crystal MgO, (9) 253*i*.
derivatives, of the sound velocities of polycrystalline alumina, (5) 140*c*.
high, dimension of gasket and relation to uniformity in generation of, (10) 289*g*.
hydrostatic, device for, P (3) 75*a*.
effect on lead sulfide transmission spectrum, (6) 167*a*.
effect on refractive index of solids, (1) 20*c*.
intrinsic absorption edge of CdTe under, (9) 251*f*.
intensifier, P (6) 161*e*.
internal, resistance of glass bottles subject to stress for long and short times, (4) 94*b*.
measurements, in aluminosilicate glass enclosure below 10^{-12} torr, (10) 281*f*.
regulation, method for combustion chamber, (7) 179*i*.
resistance, of bomb tubes, (4) 94*h*.
resistance of bottles, effect of surface damage on internal, (4) 93*j*.
saturation, determination for vapors of selenides and tellurides of Ge, (4) 110*f*.
two-dimensional, effect on permittivity of barium titanate, (2) 49*h*.
ultrahigh, apparatus for, P (6) 161*f*.
unit, replacing torr by millibar, (9) 248*h*.
vapor. See *Vapor pressure*.
Probes, thermocouple, P (5) 132*d*.
Prospecting, for clay, by geophysical electrical methods, (6) 164*j*.
Pugging, mechanization of, (3) 74*i*.
Pulverization, -classification, impact, P (3) 78*i*.
Pulverulent materials. See *Powders*.
Pumps, cryo-getter, performance of simple, (2) 44*g*.
diffusion, air-cooled and thermoelectrically cooled baffle to reach 10^{-9} torr, (1) 16*f*.
getter, performance of high speed with cooled Ti film, (3) 76*e*.
vacuum, properties of high, (1) 16*j*.
Purification, adsorption, solids drying, and membrane penetration as methods of, (11) 308*f*.
Pycnometer, air comparison, to determine density, (3) 75*f*.
Pyrolytic, materials, B (5) 142*i*.
Pyrometers; Pyrometry. See *Temperature measuring instruments*.
Pyrometric cones, Seger, to assess degree of firing, (3) 77*g*.
Pyrophyllite, dehydration of, (6) 166*a*.
in 1964, (1) 18*b*.
refractories, (4) 99*j*.
temperature, effect on solid-pressure transmission of, (6) 167*d*.
Pyroxenes, ortho-, and clino-, polymorphs of $CoGeO_3$, (1) 23*i*.
ortho-, $Mg_{0.9}Fe_{1.1}Si_2O_6$, Mg^{2+}-Fe^{2+} order in, (7) 201*c*.
system, liquidus surface in, (3) 83*f*.

Quality control, incentive program, at Jackson's, (1) 12*j*.
inspection, method for glass articles, P (4) 96*h*.
inspection apparatus, for glass sheet, P (11) 298*b*.
nondestructive, of tar-bonded basic brick, (3) 68*a*.
statistical, of glass cylinders for syringes, (11) 297*b*.
Quarries, walls, simple programmetric method to survey, (2) 47*f*.
Quartz. See also *Glass; Refractories; Silicon, dioxide*.
α-, hydrogen in, (5) 137*e*.
infrared spectrum, interpretation in 3μ region on basis of modes due to impurities, (9) 251*d*.
positive impurity ion emission from, (9) 253*d*.
relaxation of crack tip stresses in, (3) 84*i*.
Ag ion transport and deposition in, (2) 48*e*.
blue synthetic, (11) 314*a*.
coatings on, method to provide light diffusing and quartz articles with, P (4) 97*f*.
crystal device, radiation insensitive, P (10) 279*a*.
crystalline α-, absorption bands and anelasticity in, (6) 170*b*.
crystalline, radiation induced optical absorption in, (4) 112*i*.
crystallization and recrystallization, in piston-cylinder device, (1) 19*i*.
crystals, dislocations in, (11) 315*g*.
crystals, study of vibration in by X-ray diffraction topography, (3) 86*i*.
cultured, hillocks on prism faces of, (9) 250*b*.
cultured, spirals in growth of prism faces, (5) 140*b*.
dislocations, observed by transmission electron microscopy, (3) 81*d*.
distinguished from flint, (3) 78*j*.
electron and hole trapping levels in, optical studies of, (9) 252*f*.
fused, bricks in glass-melting furnaces, (4) 99*c*.
diffusion of H in natural and synthetic, (4) 110*h*.
strength in water vapor, (2) 51*f*.
glass, defective structure of fused, (8) 209*b*.
glass, radiation-optical stability at different temperatures of irradiation with γ rays, (8) 210*i*.
grit, sonic-chemical method to process, (9) 234*e*.
growth, hydrothermal, (7) 201*a*.
and molten glass, diffusion processes between, (4) 92*i*.
natural, blackening by γ-irradiation, (11) 314*c*.
neutron-irradiated, defect structure and density decrease in, (2) 49*e*.
optical grade, Indian, (2) 54*g*.

Quartz (*continued*)
for optical use, method to treat, P (3) 64*c*.
powder, with particle size of 1.5μ, thickness of disturbed layer, (3) 87*h*.
properties, effect of vibratory grinding on, (3) 78*d*.
samples, in ultraviolet and 3μ region, optical transmission in, (9) 252*h*.
sand, structure and transformations, (2) 47*e*.
survey of German and foreign deposits, (10) 282*j*.
ultrasonics for enriching, (2) 47*a*.
shock-induced luminescence in, (3) 85*e*.
slant-mode hypersonic waves in, propagation and reflection of, (10) 289*j*.
smoky, special aspects of color change in, (5) 140*j*.
strain in thin metal films on, (9) 256*e*.
structure, X-ray diffraction of changes during treatment, (10) 291*f*.
substrates, properties and structure of thin films of Si sputtered on, (7) 192*c*.
suspensions, properties of, (6) 146*d*.
synthetic, defects in, (7) 198*g*.
synthetic, impurity content and its effect on mechanical *Q*, (6) 168*a*.
thermometer, linear, (2) 44*j*.
third-order elastic coefficients of, (5) 141*j*.
transformation, in silica brick, (2) 36*g*.
twins in, X-ray topography to map, (10) 288*b*.
wetting, by melting soda, (5) 122*b*.
Quicklime. See *Lime*.

Radiation, blistering, interferometric and microscopic observations of oxides, (9) 254*i*.
damage, effects in crystals, (8) 227*e*.
in graphite, enhanced nucleation of, (4) 111*f*.
in graphite, nucleation of, (2) 50*j*.
in solids—a survey, (1) 9*g*.
in UC, UC_2, and U_2C_3, B (6) 172*b*.
in uranium dioxide, (4) 112*g*.
effects, on electronic components, (4) 103*h*.
in LiF crystals, (10) 290*d*.
on modifications of glasses, (5) 121*e*.
on physical properties of graphites, (4) 110*f*.
gamma, effect on glass melting, (7) 180*i*.
effect on properties of SnO_2 films, (10) 264*g*.
efficiency of brick walls as shield, (2) 35*d*.
induced exchange of deuterium with silica surfaces, (9) 250*e*.
to measure thickness of concrete slab, (9) 231*e*.
outgassing of glass caused by, (9) 234*h*.
heating, theory of thermal shock resistance of semitransparent ceramics under, (3) 86*i*.
high temperature, effects in lampblack-based graphites, (4) 111*i*.
infrared, improving generation by vapor lamps, P (9) 243*g*.
internal thermal, effect on heat transfer in UO_2 fuel elements, (3) 67*i*.
ionizing, effect on glasses, (5) 120*i*.
refractories as protection against, (11) 300*i*.
resistance of metal oxide films on glass to, (10) 266*f*.
from luminous flames, (1) 17*f*.
nuclear, method to measure, P (3) 77*b*.
prospective use in glass industry, (4) 95*b*.
protective materials, P (10) 274*e*.
radioactive, to determine particle size in sediments, (11) 309*g*.
recombination, device to produce, P (10) 278*c*.
resistance, of foam glass, (7) 181*d*.
resistant, optical glasses, (9) 234*b*.
sensitive, electroluminescent device, P (1) 15*e*.
shield, of synthetic stone with controlled properties, P (6) 145*a*.
shielding, composition of carbon and lead in cement, P (1) 3*c*.
thermal, shields for, (7) 195*j*.
ultraviolet, emission in potassium bromide crystals, (1) 25*i*.
X-, effect on quartz glass, (2) 31*i*.
Radioactive materials. See also *Isotopes*.
potassium compounds, as indicator to study glassmaking, (4) 94*h*.
wastes, disposal of, P (7) 190*j*.
wastes, disposal using colemanite, P (11) 303*j*.
Radioactive tracers. See also *Isotopes*.
^{60}Co impregnated mortar, around graphite bricks under ingot molds, (1) 10*b*.
studies, of flow in container glass furnaces, (2) 32*f*.
Radiography, alpha auto-, to examine irradiated fuel, (3) 65*f*.
γ-ray, intensification factor of lead screen, (11) 310*i*.
Radioisotopes. See *Isotopes*.
Radons, leakage, as possible health hazard, (1) 12*h*.
Rare earths (lanthanons). See also specific types.
Al garnets, growth by floating zone technique, (7) 191*h*.
aqueous, fraction separation using amines, P (9) 247*e*.
chromites, crystal parameters of, (6) 166*d*.
for coloring glass, (9) 235*h*.
elements, electrophysical and X-ray spectral analysis of hexaborides of, (10) 290*j*.
in form of concentrates and ores, industrial melting of glasses colored with, (4) 93*e*.
process for separating by ion exchange, P (4) 109*g*.
synthesis and study of glass tableware using, (7) 181*i*.
group VI systems, phase equilibria and crystal chemistry of, (5) 139*i*.
ions, photometric determination, (8) 223*h*.
iron garnets, optical transparency of, (9) 252*h*.

Rare earths (lanthanons) (*continued*)
manganites, preparation of monocrystals of, P (4) 106*b*.
metals with nonmetals, high-temperature compounds of, B (3) 88*i*.
metal values, process to separate, P (11) 312*i*.
minerals, visible region absorption spectra of, (3) 87*c*.
mixed, iron garnets, magnetic moments of, (10) 277*d*.
mixtures, qualitative and quantitative analysis by means of magneto-optical rotation, (6) 162*j*.
systems. See *Systems*.
rhodites, structural parameters of orthorhombic, (6) 170*e*.
sesquiselenides and sesquitellurides, with Sc_2S_3 structure, (8) 227*f*.
in steel, spectrographic determination of, (4) 107*g*.
trivalent, plus Sc(III), method to separate from other elements by chromatography, (6) 163*c*.
trivalent, substitution and theory of coupled substitution, (9) 248*e*.
Raw materials. See also *Sands; Rocks*.
cement, containing alkali, method and apparatus to heat and burn, P (1) 3*a*.
dressing of, P (8) 207*f*.
preheater for, P (1) 3*c*.
dilatometry of, (7) 198*c*.
glass, geological-petrographic and physical properties of, (3) 78*f*.
metals in, detectors for, (7) 194*f*.
origin and nature of fluxes, (4) 102*i*.
red mud and limestone, in low-silica high-iron cement, (6) 144*f*.
refractory, South African, (9) 239*c*.
a review, (5) 132*j*.
selection, for pot furnace factory, (3) 62*c*.
Swedish, for glass industry up to 1913, (1) 17*g*.
in Swedish glass industry, (8) 209*i*.
Reactors, absorbers for, P (7) 189*b*.
control elements, of hafnium oxide-europium oxide, P (2) 37*g*.
core bars, apparatus to make, P (10) 273*h*.
elements, method of making high strength nuclear, P (5) 126*h*.
environment, electrical conductivity of alumina at temperatures in, (2) 49*i*.
fuel elements, manufacture and coating with pyrolytic carbon, (9) 238*a*.
fuels, dissolution by aqueous processes, (9) 238*c*.
gas-cooled, performance of fuel for, (3) 68*d*.
gas-cooled, systems, fueled graphite for, (3) 66*g*.
hazards, compounds of graphite with nitrogen as possible, (3) 83*h*.
high temperature, graphite fuel elements for, (9) 238*g*.
high temperature gas-cooled, carbide fuel for, (3) 66*a*.
materials, processing of fissile and fertile, P (7) 189*c*.
neutronic, core bars for, P (10) 273*c*.
nuclear, core from graphite blocks, P (2) 38*c*.
core for low power, P (3) 70*c*.
fuel element for, P (4) 100*a*.
method to make components oxidation resistant, P (11) 302*f*.
moderator structures for, P (9) 240*i*.
radiation, P (10) 274*h*.
thermal nuclear, molten oxides as possible fuel matrixes for, (6) 153*e*.
Reagents. See also specific types.
gravimetric, *m*-(mercaptoacetamido)phenol to determine Cu, (3) 75*e*.
Recrystallization. See *Crystallization*.
Rectifiers, assembly, of stacked *pn* junction rectifiers, P (10) 279*c*.
controlled Si, comprising resistive plating connecting *n* and *p* layers, (11) 305*e*.
silicon controlled, P (6) 159*e*.
temperature compensated silicon controlled, P (11) 308*b*.
Rectorite, and allevardite, addition to identity, B (2) 56*c*.
Reduction, of Sm^{3+} in CaF_2, effect of V^{3+} on, (1) 20*g*.
Reedmergnerite, a boron albite, crystal structure and its relation to feldspar chemistry, (11) 314*g*.
Reflection, absolute hemispherical spectral, integrating-sphere reflectometer to determine, (11) 310*i*.
infrared, of ferrimagnetic oxides, (6) 158*a*.
method, to measure compressibility of MgO crystals, (9) 251*i*.
properties, glasses with selective, (10) 264*c*.
spectral, measurement with microphotometer, (8) 223*a*.
X-ray Bragg and spike, of diamonds, (7) 203*g*.
Reflectivity. See *Reflection*.
Refraction, birefringence, orientation induced in glass melts, (10) 265*e*.
form birefringence, in sodium borosilicate glasses, (4) 94*c*.
of glasses, change by tensile stress, (2) 31*a*.
molar, relation to coordination in polymorphs of boron nitride and carbon, (8) 227*i*.
Refractive index, of CaO, (9) 254*c*.
in glass, determination of microinhomogeneity from distribution of, (8) 210*f*.
of optical glass, method to correct during melting, (8) 210*e*.
of Na_2O-ZrO_2-SiO_2 glass, as function of composition, (1) 4*e*.
of solids, effect of hydrostatic pressure on, (1) 20*c*.

Refractive index (*continued*)
of transparent minerals, rotating-needle method to determine, (5) 131*h*.
of vitreous silica with pressure to 7 kbars, nonlinear variation of, (11) 318*c*.
Refractivity. See *Refraction*.
Refractories. See also *Aircraft ceramics; Insulation, thermal; Kiln furniture; Silicon, carbide.*
(2) 36*g*; P (4) 101*j*.
ablation properties of, (1) 7*i*.
abrasion resistance of ceramic-bonded and fused cast at high temperatures, (1) 9*a*.
abrasion resistant, P (8) 216*j*.
afterexpansion or aftercontraction, method to measure by volume, (8) 216*a*.
alumina, P (4) 99*j*, P 100*a*; P (6) 154*f–g*; P (11) 301*g*.
with aluminum nitride, P (11) 303*a*.
bonded, P (6) 154*h*.
fabrication of, P (3) 70*g*.
high, P (6) 154*c*.
high, behavior in rotary cement kiln, (1) 2*b*.
high, comparison of erosion by alkali-containing atmospheres and soda-lime glass melts, (1) 8*f*.
high, inhibited phosphoric acid for, (8) 215*c*.
high, for ladle lining for high Mn steel, (4) 99*c*.
high, methods to chemically analyze bakor and Corhart types, (8) 216*b*.
high, plastic installed by high frequency vibration, (8) 215*i*.
high, as roof for electric furnace,(8) 216*j*.
inserts for snow tires, P (11) 303*i*.
porous with metal filler, P (8) 218*d*.
preparation, P (9) 240*d*.
results of use in AYC furnace roof, (10) 271*c*.
service in tank furnaces, (10) 266*g*.
-silica, modulus of rupture at high temperatures, (9) 238*c*.
-silica, process of making, P (6) 155*c*.
-zirconia-silica, corrosion resistance of, (6) 152*b*.
aluminosilica, effect of secondary components (5) 125*c*.
aluminosilicate, formation of mullite in, (2) 36*h*.
processing, P (8) 217*a*.
research on, (7) 187*d*.
technical developments in refractories from, (3) 69*h*.
for Al, and other reducing metals, P (8) 218*e*.
aluminum nitride, components, (3) 69*j*.
Al_2O_3-ZrO_2, and method to make, P (7) 189*h*.
articles, and production method, P (2) 38*h*.
aspects of, (11) 301*f*.
bakor, control of shrinkage cavities in production of fused, (5) 125*f*.
based on alumina, zirconia, and silica, P (10) 275*a*.
basic. See also *Refractories, chrome-magnesite.*
basic, P (3) 70*b*; P (6) 155*f*.
behavior of steel claddings in regard to temperature requirements in oxidizing atmospheres, (8) 214*i*.
of bonding in, (7) 187*i*.
bonding materials between grains in high-fired, (10) 270*e*.
carbon, P (8) 217*b*.
change in texture in furnace wall, (10) 270*j*.
comparative test in open-hearth furnace, (10) 270*j*.
comparison of that containing U. S. periclase and Japanese-made seawater magnesite for open-hearth roofs, (3) 65*i*.
comparison of different contents of MgO clinker and Cr_2O_3 after use, (10) 271*b*.
comparison of 97% MgO and 97% MgO clinker in, (8) 215*a*.
comparison of used MgO 93% and MgO 96% magnesia, (6) 151*j*.
composition for support of basic facings, P (8) 217*c*.
development, properties, and service of direct-bonded, (1) 8*c*.
development of quality in direct bonded brick, (10) 272*g*.
effect of Cr_2O_3 on high-fired, (10) 271*g*.
effects of SiO_2 content and basicity of slag on element transition, (3) 66*b*.
erosion mechanism of that in a copper reverberatory furnace, (6) 152*g*.
expansion problems in high strength, (1) 9*a*.
fused, P (10) 273*i*.
in glass melting furnaces, (1) 8*a*.
of graded particle size, P (10) 275*b*.
of low silica, iron oxide bonded periclase, performance of open-hearth roof of, (6) 153*i*.
metal-clad brick unit, P (4) 100*d*.
or neutral, containing C for use in furnaces or metallurgical vessels, P (10) 282*e*.
or neutral, metal cased, P (10) 274*d*.
new composition, P (1) 11*j*.
nondestructive quality control of tar-bonded, (3) 68*a*.
for open-hearth floor, (3) 69*a*.
for oxygen steelmaking, P (9) 239*j*.
penetration of slag at high temperature, (8) 216*b*.
phosphate-bonded, P (4) 101*c*.
physicochemical behavior of cold-bonded, (9) 238*e*.
pitch-bonded, and process for making, P (3) 70*j*.
prevention of migration of iron oxide and silicate in, (10) 272*g*.
procedures to make, P (5) 127*a*.
prolonging life in furnace roof by decreasing porosity, (8) 216*e*.
recent improvement for cupolas, (1) 9*g*.
Refractories, basic (*continued*)
relation of life of open-hearth furnace roof to size of magnesia clinker used in, (7) 187*c*.
results of hot torsion test on, (11) 301*c*.
slag resistant, P (5) 126*j*.
for steel melting in Swedish induction furnaces, (3) 69*f*.
tar bonded, P (2) 38*g*.
tar-bonded, wear measurements in converter, (10) 273*f*.
testing thermal shock resistance by air quenching, (9) 239*j*.
tests on slagging at high temperature, (6) 154*c*.
texture analysis of, (8) 216*d*.
thermal conductivity and thermal expansion of, (8) 216*d*.
unfired, P (9) 241*f*.
for basic oxygen furnaces, (11) 301*b*.
bauxite, P (8) 217*c*.
bending device for, P (10) 273*j*.
blanks, machine to sever, P (8) 217*d*.
block, molding machine for, P (6) 155*b*.
block, ultrasonics to determine quality of Korvisit, (11) 300*i*.
change in grain size during pressing, (10) 270*g*.
bodies, manufacture of, P (6) 154*f*.
body, bonded by aluminum nitride-aluminum boride composition, P (5) 126*a*.
boehmite, as catalyst support, P (7) 188*i*.
bonded, with pitch, P (1) 12*c*.
bonded, process for making, P (7) 189*j*.
bonding, with cerium oxide-cerium sulfide mixtures and product, P (5) 125*h*.
BOP, slag erosion resistance of, (8) 216*b*.
borides, high-temperature thermodynamic properties of, B (6) 175*g*.
borides, purification of, P (6) 155*a*.
bottom lining, improvement for teeming ladle, (1) 9*e*.
brick, apparatus to make, P (9) 239*h*.
apparatus to plate, P (9) 239*i*.
automatic preparation of tar-dolomite, (2) 36*h*.
divided taper, P (3) 70*f*.
embossed metal-clad, P (8) 218*c*.
graphite and SiC beneath ingot molds, (1) 10*d*.
hanger, hinged, P (9) 240*d*.
machine and method for perforated, P (1) 11*g*.
magnesia, tests on creep caused by compressive load at high temperature, (9) 239*a*.
means to case, P (2) 37*b*.
with metal hanger, P (2) 38*e*.
method of making metal covered, P (2) 38*e*.
spall resistant, P (5) 127*a*.
suspension means, P (6) 155*d*.
Volnovakha as raw material for, (6) 154*e*.
burned impregnated, P (10) 273*a*.
calcium aluminate shapes, P (11) 301*j*.
calcium silicate, insulating materials, P (9) 240*a*.
calcium silicate-calcium aluminate, P (9) 240*f*.
carbides and graphite, contact interaction at high temperature in vacuum, (3) 65*j*.
carbon-containing, P (10) 273*b*.
carbon and graphite, fabrication of bodies, P (11) 302*c*.
carbon or graphite, porous shaped structures, process of preparing, P (2) 38*c*.
carbon and graphite bodies, production of low-permeability high-density, P (7) 189*e*.
carbon-metal, P (10) 274*j*.
car top, P (4) 108*e*.
cast, fused, for furnace, P (7) 189*i*.
castable, fibrous, and articles, P (8) 217*f*.
phosphate bond, (8) 216*e*.
and plastic, for joining runner brick, (1) 10*d*.
casting device for, P (9) 241*c*.
casting system, continuous, P (1) 11*b*.
cement, alumina with binder, P (11) 303*c*.
and cement kiln, (9) 237*j*; (10) 270*f*.
chamotte, problems in production of, (5) 125*g*.
chamotte, process to produce, P (7) 189*d*.
chamotte brick, superior to SiC-bearing chamotte brick, (1) 10*a*.
checker, spinel type built in open hearth furnace, (7) 187*i*.
checker block, and checker construction from, P (3) 70*e*.
checker brick, method to lay in open-hearth regenerator and prolonging life of checker, (10) 272*j*.
reduction of consumption in furnace slag chamber, (10) 272*b*.
results of using high alumina for top of hot-blast stove, (3) 69*b*.
chrome-magnesite. See also *Refractories, magnesite-chromite.*
chrome ore-containing, of high mechanical strength, (11) 300*i*.
chromite-magnesia, P (6) 155*a*.
chromite-magnesite, effect of firing atmosphere on, (7) 186*f*.
Cr-Mg, effect of high temperature firing on properties, (3) 66*j*.
in circular furnace roof, P (4) 100*i*.
clays. See *Clays.*
coatings. See *Coatings.*
composition, P (4) 102*b,c*.
composition, of silica and alumina, P (3) 70*i*.
compounds, deformation behavior, B (2) 55*h*.
concrete. See *Concrete.*
containing beryllia, method to dissolve, P (1) 11*i*.
converter masonry, changes in type as related to life of converter, (10) 270*f*.
cordierite, method to develop dense body, (10) 272*b*.
corrosion, at interface between glass or slag, (5) 125*h*.
Refractories (*continued*)
corundum containing, causes of expansion and contraction in, (7) 185*h*.
creep of, (8) 215*a*.
creep and sintering relations, (8) 216*g*.
crucible externally lined with filamentary carbon, P (4) 100*j*.
manufacture from cermet alloy and use for chemical analysis, (8) 215*i*.
reaction of MgO with molten iron under reduced pressures, (6) 153*c*.
for vacuum plating, P (2) 37*a*.
cupola, structural change and corrosion of, (10) 272*f*.
for cupola melting, types and application in Japan, (1) 10*c*.
dense, manufacture and mechanical properties of those from hexaborides of rare earth metals (10) 270*f*.
development, in glass furnaces, (2) 36*h*.
dictionary, Portuguese, French, English, Italian, and German, (2) 54*f*.
dolomite, brick, P (11) 302*c*.
contact behavior at 1600°C, (7) 186*a*.
deterioration in an open hearth and in a converter, (6) 152*b–d*.
electrically resistive, P (11) 303*a*.
electrocast. See *Refractories, fused cast.*
electrocast, in reheating furnaces, (11) 301*f*.
erosion, in bottom casting, (1) 8*g*.
in melting zone, relation to cupola operation, (1) 9*j*.
of pouring pit, (4) 99*h*.
rate of clay-bonded SiC by molten iron, (4) 99*a*.
tests, results of, (4) 99*g*.
felted, (7) 186*g*.
fiber material, forming with cationic starch and colloidal silica, P (3) 70*i*.
fibrous, P (11) 302*d*.
process to make heat insulating board, P (8) 218*d*.
process to make molded vitreous forms, P (8) 218*e*.
filters from, (1) 10*g*.
firebrick, acidic erosive in cupolas, (1) 8*h*.
firebrick, effects of pressing and pressure on physical properties of, (3) 67*c*.
fireclay, analysis of deformation, (7) 185*e*.
catalytic separation of carbon in, (7) 185*f*.
erosion resistance to high calcareous slag, (6) 152*g–j*.
nondestructive acoustic method to test, (1) 7*j*.
production of brick from grog, (4) 99*f*.
properties and use, (2) 36*h*.
torsional testing at high temperature, (9) 239*e*.
fireproof board, containing mineral and cellulosic fibers and metal oxide, P (3) 70*j*.
for fluidized bed, (7) 190*b*.
foamed, preparation of Al_2O_3 and SiO_2, (10) 272*e*.
foamed, production of, (6) 153*j*.
French, (6) 152*f*.
furnace, analyses of basic O, (6) 154*e*.
floor, clinker of Korean dolomite for, (8) 216*h*.
and pouring-pit, corrosion of, (10) 271*e*.
roof, cantilever structure for, P (6) 154*i*.
roof, durability of MgO-Cr_2O_3 compositions, (10) 270*h*.
fused cast, P (7) 188*b*; P (10) 273*h*.
articles, and method of making, P (5) 125*i*.
basic, in electric furnace walls, (7) 186*g*.
controlling hardening of, (6) 151*j*.
cordierite, crystallization of, (10) 271*e*.
corrosion behavior of alumina- and zirconia- in soda-lime glass melt, (7) 186*c*.
determination of trace impurities in, (7) 186*c*.
glass evolution and bubble formation in at high temperatures, (4) 93*b*.
glass phase in, (2) 36*i*.
glass phase in Al_2O_3 and ZrO_2, (1) 9*b*.
and high alumina, corrosion by white opal glass, (2) 36*e*.
and method of making, P (4) 100*b*.
for glass furnace, P (4) 100*c*.
in glass furnaces, problems with, (1) 4*g*.
for glass industry, platinum sheathing for, (11) 301*i*.
glass pot, kaolin bodies of increased density for, (6) 152*j*.
glass and slag resistant, and process of making, P (7) 188*c*.
glass tank, determination of bulk density and density variations in, (6) 152*d*.
solubility of ZrO_2 in HF to determine glassy phase in fused cast, (6) 153*j*.
upward drilling in, (4) 94*e*.
grain, production of, P (4) 101*i*.
graphite, set in molding board for top casting, (1) 9*d*.
shape of screw bolt for stopper head, (1) 10*f*.
with tungsten coating, P (8) 217*f*.
graphites and carbons, as high temperature materials, (11) 301*f*.
grooved, for brick construction, P (8) 217*c*.
gunned, (2) 36*j*.
gunned, to lengthen life of open-hearth roof, (7) 186*i*.
gunning, developments in basic composition for electric furnaces, (9) 239*b*.
for ladle maintenance, (8) 216*e*.
mix, repair of hot metal mixer with dry, (7) 187*c*.
in heating furnaces, rate of temperature rise after repair, (7) 187*b*.
high density, method to produce, P (4) 101*g*.
high-melting compounds, interaction with molten metals, (10) 271*e*.
high silica, lightweight products from, (7) 186

Refractories (*continued*)
at high temperature, mechanical and thermal properties of, (11) 301*d*.
hot metal mixer, operation of 1300-ton, (7) 187*e*.
hot pressing of powdered, P (9) 240*e*.
hot top, P (10) 274*a*.
consumable with inserts of exothermic material, P (1) 11*a*.
consumable with tie-down members, P (1) 11*b*.
with dead air space, P (2) 38*a*.
and/or exothermic unit, P (2) 38*a*.
fusion casting with, (5) 125*f*.
inflatable former for, P (5) 126*a*.
for ingot mold, P (6) 154*e*.
method and apparatus for lining, P (5) 126*d*.
method of making, P (3) 70*c*.
and seal signal device for, P (5) 126*a*.
thermosetting composition for exothermic, P (8) 218*g*.
two part, P (1) 12*e*.
hydration, prevention of, P (1) 12*b*.
immersion sampler, P (3) 70*j*.
impervious, preparation of, P (7) 189*d*.
industrial, silicon carbide in, (10) 272*c*.
insulating. See also *Refractories, firebrick*.
insulating, P (9) 240*h*.
corn stalks added to improve insulating qualities, P (7) 188*f*.
for high temperatures, (6) 153*e*.
products and production, P (5) 127*b*.
Japanese, production, exports, and imports for 1963 and 1964, (10) 271*h*.
for kiln furniture. See *Kiln furniture*.
ladles, P (2) 38*b*.
adjustment of slag basicity to extend life of, (9) 237*i*.
bloating type clay instead of zircon for killed steel, (8) 216*i*.
changes in composition during pouring, (7) 185*f*.
comparison of Japanese and American bottom sleeves for, (1) 8*c*.
durability with special reference to bottoms, (7) 186*e*.
prolonging service life of, (7) 187*f*.
service tests on unburned brick containing SiC, for electric furnace, (9) 239*e*.
various methods of use at Japanese converter mill, (3) 70*a*.
zircon, results in slag line only and in lower side wall, (7) 187*f*.
zircon brick for basic open-hearth, (9) 239*f*.
ZrO_2-SiO_2-Al_2O_3, (9) 239*f*.
ladle bottom, method of laying and life of brick for, (3) 68*i*.
quality and durability of brick and mortar for, (3) 68*h*.
results of using 42 to 44% Al_2O_3 brick for, (3) 69*a*.
ladle brick, anticorrosive properties of unburned, (3) 68*h*.
comparison of fired and unfired SiC, (1) 8*e*.
comparison of vertically and horizontally laid, (1) 8*f*.
corrosion under various conditions, (3) 65*h*.
effect of steelmaking on life of, (9) 238*d*.
erosion in converter mills and methods to reduce, (9) 238*e*.
erosion of LD converter zircon, (9) 238*f*.
merits of unburned, (1) 9*d*.
merits of unfired, (1) 10*b*.
method to make zircon, (7) 187*c*.
relation of life to temperature of molten steel, (1) 10*a*.
siliceous, of natural raw materials, results of tests on special, (9) 239*d*.
ladle linings, P (8) 218*h*.
changes in physical properties and mineral composition of zircon, (8) 214*i*.
comparison of vertical and horizontal laying, (7) 185*i*.
hot repairs with gun, (1) 9*e*.
results of measuring erosion by radioactive isotope, (8) 216*h*.
results of tests to find average corrosion in wall and bottom, (3) 68*j*.
of zircon and its condition after use, (7) 188*d*.
layered, method to cast and fire article, P (11) 302*h*.
for LD converter, (8) 216*f*.
lightweight, chamotte, (11) 301*c*.
high temperature, P (1) 11*d*.
powder press process to form articles of, P (10) 274*a*.
properties, (2) 36*c*.
rapid determination of content of combustible additions in manufacture of, (6) 153*b*.
lining, of cathode pots in electrolytic furnace for production of Al, P (8) 217*j*.
comparison in furnaces, (1) 8*c*.
of concrete from low calcium aluminate cement for rotary kiln, (2) 36*j*.
of converter, P (7) 188*e*.
effect of carbon on tar-impregnated for furnaces, (11) 301*d*.
erosion of tar-dolomite of an LD converter where perforated lance is used, (8) 216*c*.
extending life in large electric arc furnace, (3) 67*g*.
laboratory examination of, (3) 69*f*.
method to install in furnaces, P (9) 240*j*.
for metallurgical furnace, P (9) 240*j*.
for rotary kiln, P (11) 302*a*.
method of making monolithic in metallurgical vessels, P (5) 126*i*.
siliceous material for cupola repairs, (1) 10*b*.
study for oxygen converters, (3) 69*d*.
for tanks, (6) 151*h*.

Refractories, lining (*continued*)
with tongue and groove for circular tapered stack construction, P (11) 303*d*.
lithium aluminum silicate and method of making, P (4) 102*a*.
magnesia, chrome, process for making with increased strength at elevated temperatures, P (7) 189*h*.
-chrome, electron probe to study grain-boundary reactions, (11) 301*e*.
clinker, comparison of SiO_2-bonded and Fe oxide-bonded, (7) 185*j*.
clinker, effect of MgO content on slag penetration, (7) 186*g*.
deterioration in an open hearth and in a converter, (6) 152*b–d*.
or dolomite, molded, P (7) 189*i*.
effect of basicity and temperature on slag penetration of, (8) 215*c*.
gunning and method of producing, P (5) 126*j*.
high-fired in furnace wall, (10) 273*e*.
or magnesite, impregnation with organic acids, P (8) 218*d*.
product, P (9) 240*i*.
refractory and hydration resistant, P (8) 218*f*.
-titania, determination of titanium(III) in, (3) 69*b*.
magnesite. See also *Refractories, chrome-magnesite*.
magnesite, P (11) 303*j,a*.
-chrome, chemically bonded under changing torsional load, (7) 185*g*.
corrosion by alkali sulfates and by SO_3, (10) 271*c*.
in industrial furnaces, especially in regenerative checkerwork of glass melting tanks, (7) 185*f*.
Mg-Cr (MgO 95% magnesia clinker) in front wall of open-hearth furnace, (7) 187*e*.
MgO, changes in properties of three types during firing at three temperatures, (6) 151*h*.
-Cr_2O_3, durability of three compositions in open-hearth roof, (10) 270*h*.
and Cr_2O_3, solid phase reactions between, (7) 187*g*.
-Cr_2O_3, for vessels, P (7) 190*c*.
in electric furnace, (10) 270*i*.
of high purity in furnace wall, (10) 272*f*.
materials, apparatus to determine thermal conductivity, (6) 161*i*.
bubble formation in reaction of glass melts with, (6) 146*j*.
classification of, B (5) 142*i*.
cohesive with metallic and ceramic phase, production and use as coating, P (2) 38*f*.
crushing in theory and practice, (7) 186*g*.
determination of silicon carbide content of, (7) 186*i*.
determination of slagging resistance of, (7) 186*a*.
dispersion hardened and processes for, P (6) 154*b*.
endothermic reacted, P (3) 70*d*.
evaluation of high-alumina, (2) 36*f*.
flow at high temperatures, (2) 36*h*.
grinding of, (7) 186*h*.
hollow-cathode electron beams and their application to melting, B (11) 320*h*.
infrared radiation of, (1) 9*f*.
low friction, P (3) 70*a*.
making converter bottoms, brick, and electrodes based on, P (10) 274*b*.
manufacture of, P (6) 154*f*.
means to improve resistance of porous to corrosive action, P (8) 218*c*.
mechanical and thermal properties at high temperatures, (8) 223*j*.
and shapes, manufacture of thermal shock resistant, P (6) 154*i*.
a survey, (6) 153*d*.
metal cased, apparatus to make, P (11) 301*h*.
metals, mechanical properties at high temperature, (11) 301*a*.
metals, vacuum siliciding of, (10) 271*b*.
modulus of elasticity, at high temperature, automated test to determine, (6) 152*f*.
mold coating, process for casting metals into asbestos-containing, P (7) 189*f*.
molded, brake shoe, P (4) 101*a*.
molding, process and articles, P (8) 217*h*.
molds. See *Molds*.
monocrystalline B structures, method to produce, P (4) 101*i*.
monolithic, for metallurgical furnace, P (4) 100*i*.
mortar impregnated with ^{60}Co, effect as tracer around graphite bricks beneath ingot molds, (1) 10*b*.
mortars, high temperature behavior of those containing various cements, (3) 65*g*.
Japanese standards for, (6) 152*i*.
method to simultaneously determine workability and water retention of, (7) 187*c*.
new types, in high-temperature melting of glass, (1) 10*f*.
niobium carbide-graphite, thermal expansion behavior of, (8) 216*e*.
nitride-boride, P (8) 218*b,c*.
for nonferrous metals industries, (5) 125*a*.
nonplastic, containing pozzolan, lime, and blast furnace slag, P (4) 101*b*.
nozzle, high aluminous for high Mn steel, (1) 9*d*.
high temperature, P (4) 100*d*.
high temperature graphite for rocket motor, P (3) 70*j*.
hydrodynamic experiment on ladle pouring, (8) 215*i*.
Japanese from American materials, (1) 10*e*.

Refractories, nozzle (*continued*)
Japanese soft compared to American, (1) 8*d*.
results of service tests of SiC, (3) 69*a*.
soft, physical properties at high temperature, (1) 9*e*.
sonic testing for steel ladles, (2) 37*b*.
for tapping molten refractories, P (2) 38*i*.
thermal stress of, (6) 154*d*.
for nuclear applications, at Vallecitos, (2) 36*d*.
for open hearth, furnace bottoms, P (6) 154*d*.
hearth, results of using cased made of waste basic, (7) 187*e*.
roof, effect of SiO_2 content of magnesia clinker in magnesia-chrome brick for, (3) 67*a*.
oxides, and carbides, porous ceramics from, (7) 187*f*.
factors determining type of phase diagram in binary systems formed by, (10) 290*c*.
improvement of melting without crucible, (8) 215*j*.
molten-salt vaporization methods for growing crystals of, (5) 138*i*.
single crystal whiskers and their use, (7) 188*e*.
and thermoplastic binder for molded articles, composition based on, P (8) 217*i*.
patching material, Daubpax tested, (1) 10*d*.
properties of Cupoline, (1) 9*d*.
properties of French RP-1, (1) 9*e*.
RP-1 for a 2-ton cupola, (1) 10*e*.
pellets, diffusivities in pressed catalyst, (2) 36*c*.
pitch-bonded, P (5) 126*c*.
plastic, machine to form block, P (6) 155*d*.
method to form blocks, P (6) 154*j*.
molding, of aerospace components, (3) 68*j*.
trial in furnace regenerator roof, (10) 273*f*.
platen, for brazing fixture, P (10) 274*h*.
porous, impregnating, P (8) 217*e*.
porous, as sound absorber, (2) 37*b*.
of portland cement clinker with fused shell, P (9) 240*g*.
pouring pit, characteristics of roseki for, (3) 65*g*.
powder, continuous hot pressing, P (10) 274*f*.
powder, thermal treatment of, P (10) 275*b*.
powdered, ultrafine, P (8) 218*g*.
powdered and sintered, thermal conductivity of, (2) 37*h*.
powders, ignitability of, (3) 67*e*.
pressing, method for powdered carbon and other materials, P (7) 189*d*.
progress in, (9) 239*a*.
in pusher-type furnaces, testing method for, (9) 239*i*.
pyrophyllite, (4) 99*f*.
pyroplastic deformation, prediction by mechanical analogy, (7) 187*g*.
quartz, fused in glass-melting furnaces, (4) 99*c*.
radiation damage in, (1) 9*g*.
as radiation protection, (11) 300*i*.
ramming mix, P (8) 218*a*.
reactions of molten glass with, (10) 266*g*.
recuperator tubes, evaluation of, (3) 67*e*.
refractoriness, under-load, international study of testing method for, (1) 9*g*.
research, problems of modern, (3) 68*g*.
roof, P (2) 38*g*.
for furnace, P (7) 188*a*.
hot repair by dry gunning, (10) 271*e*.
open-hearth repair with gunning mix, (10) 272*g*.
rate of temperature rise in reheating furnace related to expansion rate, (3) 70*a*.
relation of lifespan to iron, O, and oil in open hearth, (3) 68*c*.
runner brick, relations between physical and chemical properties and damage done to them, (9) 239*c*.
selection, for high temperature tunnel kiln, (10) 282*d*.
service, during high-temperature melting of glass, (2) 37*a*.
shape, improvement for open-hearth furnace, (8) 215*b*.
sideboards, for ingot mold, P (9) 240*a*.
silica, P (2) 38*h*; P (5) 127*c*; P (7) 190*a*.
containing Fe_2O_3, (5) 125*c*.
for electric furnace roofs, (6) 152*h*.
lining, hot-blast Koppers stove with, (7) 186*h*.
quartz transformation in, (2) 36*g*.
-resin, ablation type, P (7) 189*g*.
semi, P (4) 102*a*.
surface effects on hot face in glass tank crown (10) 265*b*.
siliceous, condition of used ladle brick, (7) 186*a*.
siliceous plastic, behavior in hot repair of glass furnaces, (2) 36*d*.
SiC, clay bonded, erosion rates, (4) 99*a*.
silicon carbide, effect of O deficiency on bonded, (10) 271*a*.
silicon nitride, applicability and erosion of, (4) 99*a*.
erosion by iron, (9) 238*f*.
use and corrosion by molten nonferrous metals, (7) 188*b*.
sintered, manufacture, P (10) 274*h*.
sintering, activated based on chlorine, (10) 272*a*.
sintering, study up to 3000°C and 1000 kg/cm², (11) 301*h*.
sleeves, comparison of, (1) 8*f*.
of 90 to 93% SiO_2, unfired, (1) 10*d*.
siliceous, produced by dry process, (1) 10*g*, tarred, service test results, (1) 10*c*.
softening, under torsional stress, (10) 272*c*.
sorbent products, and method of making from attapulgite clay, P (6) 155*g*.
sphere, die to make flashless encapsulated, P (8) 217*a*.

Refractories (*continued*)
spheres (hollow), starting from silicates containing Mg, P (7) 189*a*.
for steelmaking, progress in, (5) 125*j*.
stopper heads, American and Japanese counterparts, (1) 8*d*.
causes and prevention of failure, (3) 65*g*.
method to test quality of materials for, (9) 238*d*.
relations between sonic property and practical use, (8) 216*g*.
and sleeve for steels, (9) 239*e*.
thermal shock test and thermal conductivity measurements on, (8) 216*i*.
X-ray examination and service test, (9) 2o7*j*.
stopper rod, P (10) 275*d*.
strength, development during drying, (9) 238*a*.
stress resistance, at high temperature, (2) 37*b*.
structural slabs, manufacture of, P (6) 154*g*.
supports, for articles during firing, P (8) 218*d*.
suspendable unit, P (5) 127*a*.
suspended, P (8) 218*g*.
suspended, metal clad, P (1) 12*e*.
tar-bonded blast-furnace taphole, workability of, (9) 238*b*.
tar-dolomite, erosion mechanism on open-hearth rear wall, (3) 67*d*.
mechanism of wear in electric arc furnace wall, (7) 187*a*.
structural change of that used for oxygen converter, (3) 69*c*.
testing, of refractoriness under load, (3) 68*a*.
testing, of refractoriness-under-load, factors affecting softening points, (3) 67*h*.
thermal conductivity, effect of moisture on, (11) 301*e*.
thermal conductivity measurements, (9) 239*b*.
thermal shock damage resistance, experimental evidence for, (8) 215*h*.
thermal shock resistance, (10) 273*b*.
titanium nitride, high temperature, P (8) 217*c*.
tungsten monocarbide, effect of high pressures and temperatures on, (10) 271*j*.
unit consumption, effect of factors in open-hearth furnaces, (8) 215*d*.
used, condition in electric furnace, (7) 187*f*.
for vacuum treatment of molten steel, problems, (9) 239*f*.
very light, heat- and sound-insulating and their application, (7) 188*e*.
wall, P (1) 303*d*.
wall and nose construction, P (6) 155*g*.
whiskers, state-of-the-art, (2) 37*i*.
zircon, composition and method, P (2) 37*d*.
in, (1) 10*e*.
in glost tunnel kilns, (2) 37*i*.
in open-hearth furnace ladles, (9) 237*i*.
zirconia, impregnated with carbon, P (9) 241*a*.
mechanism by which metal additions improve thermal shock resistance of, (7) 187*b*.
with 15%(mole) Ti, thermal shock resistance of, (7) 187*i*.
stabilized, P (5) 127*b*.
zirconium oxide, properties and high temperature applications, (1) 9*f*.

Refractories industry, American plant in Mexico, (4) 99*b*.
apparatus, for production of carbon and graphite bodies, P (6) 154*h*.
dust collector in, (8) 215*c*.
firing, 1950–1964, (5) 125*f*.
General Refractories, research pays off, (4) 99*e*.
market in Canada, (6) 153*d*.
modern plants, industrial planning for construction of, (6) 152*h*.
modern plants, planning construction, (1) 9*f*.
Pennsylvania plant, tar impregnating facility added to MgO product line, (8) 215*f*.
plant, in Washington, Pa., (8) 215*h*.
rationalization in, (2) 36*g*.

Relaxation, dipole, in CaF_2 doped with NaF, (9) 249*i*.
long-term, of surface conductivity of Si, (10) 287*h*.
mechanical, of point defect in MgO, (3) 83*d*.
phenomena, during hot compacting of molybdenum carbide, (10) 290*i*.
plastic, of crack tip stresses in α-quartz, (3) 84*i*.

Research, on aluminosilicate refractories, (7) 187*d*.
on cement, conditions of, (10) 262*e*.
and development, in industry, (6) 171*d*.
for floor and wall tile, (2) 39*c*.
on glass, mass filter in, (8) 210*a*.
structure, status of, (5) 121*f*.
surfaces, with radioactive phosphorus, (2) 32*h*.
pays off, at General Refractories, (4) 99*e*.
in progress, (4) 115*a*; (6) 171*e*.
in sanitary ware, (1) 12*j*.
of semiconductor materials, (5) 131*h*.
tools, electron beam heating as, (5) 135*j*.

Research and research laboratories, of International Pipe & Ceramics Corp., description of, (2) 54*h*.
State Silicate Research Institute (Vienna), (6) 171*e*.

Resins, epoxy, to impregnate materials for thin sections, (7) 194*h*.
reinforced with aluminum-coated silica fibers, (4) 95*f*.
as temporary binders, (6) 156*b*.
-glass interaction, of filament-wound composites, (5) 120*g*.
-glass interface, effect of water vapor on, (2) 31*h*.
phenolic, kinetic studies of high-temperature carbon-silica reactions in charred, (8) 215*e*.
synthetic, tension development in those with glass fiber reinforcement, (4) 95*d*.

Resistance, electrical. See also *Conductivity, electrical.*
compositions, elements, and methods of making, P (7) 192*h*.
element, of heat-resistant oxidation proof materials, P (7) 195*j*.
elements, of silicon carbide and metal silicide, P (7) 195*i*.
of foam glasses, relation to temperature, (11) 297*j*.
measurement, of liquid glass, (8) 210*a*.
negative, avalanche breakdown double-injection induced in semiconductors, (4) 103*f*.
surveying method, (3) 78*b*.

Resistivity, electrical, of carbon composite sintered materials, (4) 103*j*.
of C as effected by changes during sintering, (10) 285*c*.
of ferrites, effect of impurities on, (9) 242*g*.
of ferromagnetic CrO_2, (4) 111*c*.
in reduced TiO_2 at low temperature, (10) 285*f*.
of single crystal graphite, (7) 201*b*.
of tungsten carbide-cobalt alloy, dependence on its structure, (10) 284*c*, 290*g*.
of VO_2 powder, temperature dependence of, (10) 291*h*.
ZnO crystals of low and intermediate, (7) 191*h*.

Resistors, electrical, P (2) 41*f*,*g*; P (7) 194*d*; P (8) 220*h*; P (11) 305*j*, 306*d*, 307*b*.
bead thermistor, positive temperature coefficient, P (1) 15*c*.
carbon-film, glass enclosed, P (7) 193*b*.
compositions for, P (1) 15*e*; P (5) 129*h*; P (5) 130*a*.
composition and devices embodying, P (5) 129*i*.
integrated semiconductor, P (10) 278*b*.
of metal alloy, P (7) 193*h*.
metallic, method to sort out defective by sensing current noise index, P (7) 193*i*.
method to make, P (5) 129*b*.
method to mass produce, P (3) 73*f*.
monolithic, process of producing solid composition, P (2) 42*e*.
nonlinear tunnel, P (6) 160*i*.
photo-, high performance, P (1) 14*c*.
reversible temperature dependence of, (8) 220*f*.
semiconductor film, P (6) 160*h*.
Ta film, P (9) 243*i*.
Ta nitride film, P (6) 161*b*.
thermistors, P (4) 106*e*.
bead type, P (3) 73*a*.
and method of making, P (2) 42*b*.
positive temperature coefficient thin-film, (10) 277*i*.
thick film, how to make, (8) 220*a*.
two-stable high-resolution electron-actuated, P (11) 308*d*.

Resonance, electron paramagnetic, in alumina-based ceramics, (5) 136*a*.
electron paramagnetic, and endor spectra of Tb^{4+} in ThO_2, (1) 21*g*.
electron paramagnetic, in silicate glasses containing Ti, (7) 180*i*.
electron spin, in diamond coat, (3) 81*f*.
ferrimagnetic, temperature dependence of line width in polycrystalline nickel cadmium ferrite, (4) 113*f*.
ferromagnetic, in single-crystal films of iron, (2) 50*c*.
magnetic, in glasses, (4) 94*e*.
^{55}Mn, nuclear magnetic in Mn ferrite, (2) 50*d*.
method, to determine elastic constants of cement, (6) 144*i*.
microwave ultrasonic paramagnetic, of Cr^{2+} ion in MgO, (7) 201*e*.
nuclear magnetic, chemical shift, in cesium silicate glasses, (5) 120*c*.
of decomposition in neutron-irradiated LiF, (9) 252*c*.
to investigate borides of transition metals, (10) 287*f*.
investigations of compounds and glasses in systems PbO-B_2O_3 and PbO-SiO_2, (7) 201*f*.
studies of calcium boroaluminate glasses, (9) 234*e*.
of thermal evolution at low temperatures of water of hydration of montmorillonite, (7) 201*h*.
of the water in beryl, (7) 201*j*.
nuclear quadrupole, in thorium tetrachloride, (10) 285*a*.
proton magnetic, of structure of alum single crystal, (6) 169*h*.
relaxation, in $Mn_2Fe_2O_4$ by slow relaxing manganic and ferrous ions, (9) 254*i*.
signal, of neutron irradiated graphite, temperature variation of paramagnetic, (4) 114*h*.
vibration technique, to determine shear wave velocity, (8) 223*g*.

Rhenium, disilicide, as new high-melting point semiconductor, (11) 319*b*.
films, oxidation of thin evaporated, (7) 192*a*.
hexavalent, magnetic compounds with perovskite-type structure, (7) 201*a*.
$ReSe_2$, crystal structure, (3) 80*e*.

Rheology, behavior, characterization of inelastic fluids, (3) 84*a*.
of bentonite suspensions, as drilling muds, B (2) 56*h*.
of cement, pastes and fresh mortars, (1) 3*b*.
of fluids, non-Newtonian, flow equation for pseudoplastic systems, (1) 24*i*.
of glass, under stress in transformation range, B (9) 259*j*.
of lime suspension, effect of small additions of electrolytes on, (4) 90*e*.

Rheology (*continued*)
of moldable materials, plastometer to measure, (3) 76*f*.
properties, apparatus to determine, P (6) 163*a*.
of aqueous bentonite dispersions, (6) 169*h*.
effect of agitation on those of cement and cement-sand mortars, (3) 58*j*.
measurement of cover coat slips, (7) 178*f*.

Rhodites, rare earth, structural parameters of orthorhombic, (6) 170*e*.

Rhodium, -platinum alloys, effect of gold on, (4) 96*c*.
-platinum-oxygen, electrode in silicate melts, (5) 139*f*.
weight, loss at high temperatures, (3) 83*a*.

Rockets. See *Spacecraft.*

Rocks. See also *Phosphates; Silicates.*
alteration to pottery stone, mineralogy of deposits in Japan, (1) 18*f*.
cementation, as clue to structure, drainage patterns, permeability, etc., (5) 134*d*.
clastic, petrography and derivation of Jurassic-Cretaceous of southern Rocky Mountains, Canada, (3) 78*i*.
crusher, with braked head, P (1) 19*c*.
decomposition, method, (1) 16*i*.
emery-like, from Scotland, chemistry and mineralogy of, (11) 314*j*.
ferrous iron in, determination of, (10) 281*g*.
-forming minerals, X-ray-emission microanalysis techniques for, (4) 114*c*.
-forming silicate minerals, calculation of energies of formation from solubility data, (9) 248*f*.
fractions, variation in Lithuanian moraines, (9) 252*f*-*g*.
fragmentation, electrothermal, P (1) 18*e*.
gas chromatography of, (2) 44*b*.
igneous, from Texas, geochronologic study of, (11) 317*e*.
of Ireton formation, central Alberta, Canada, (2) 46*j*.
Lower and Middle Paleozoic, West Flank Teton Mountains, Wyoming, carbonate petrography of, (2) 47*e*.
magnetic, crystallization of vitreous phase of, (11) 296*e*.
of Paleocene-Eocene Aquia formation, Virginia, Maryland, and Delaware, (2) 47*a*.
properties, computed from random pore size distribution, (4) 107*j*.
red siltstone, petrology in Texas and New Mexico, (5) 133*f*.
resources, in Tennessee, (7) 196*f*.
sedimentary, terminology of crystallization textures and fabrics in, (2) 47*h*.
silicate, composition of precipitates formed by decomposition in 38 to 40% hydrofluoric acid, (7) 200*d*.
in South Africa, (6) 164*i*.
strength, indentation method to test, (7) 195*e*.
stresses in, determination of, (4) 108*j*.
of Texas, (8) 225*i*.
types, of Duperow formation (Upper Devonian) in North Dakota, (2) 46*j*.
weak, mineral formation and structure in electrochemical induration of, B (9) 258*d*.

Rock salt, creep in, (1) 19*d*.
crystals, morphology of deformation in, (3) 86*j*.

Rubidium, borates, (2) 52*i*.
bromide, Grueneisen parameter of, (3) 87*a*.
bromides, interaction with di-, tri-, and tetrabromides of Ti, (11) 317*e*.
chlorides, bromides, and nitrates of, exchange reactions in five-component reciprocal system, (1) 21*j*.
interaction with those of Nb and Cs in melts, (5) 141*b*.
interaction with V trichloride, (11) 317*j*.
systems. See *Systems.*
chromate, systems. See *Systems.*
fluoride, systems. See *Systems.*
phosphate, polymers based on, (1) 25*b*.
silicate, systems. See *Systems.*
systems. See *Systems.*

Ruby. See also *Lasers; Masers.*
crystals, growth of broad line width, (7) 199*i*.
flux-grown, growth defects in, (10) 286*c*.
flux grown, properties and growth of, (9) 254*c*.
laser, effect of ground state ESR saturation on output at 90°K, (11) 316*b*.
internal self-damage of, (10) 287*d*.
mode competition and self-locking effects in *Q*-switched, (10) 288*g*.
optical masers, wave generation in, (10) 277*j*.
-selenium reaction, mechanism of, (9) 233*i*.
whiskers, growth and characteristics, (9) 255*f*.

Rupture, mechanism, of tungsten carbide/cobalt alloys in compression, (10) 272*i*.
modulus, for alumina-silica refractories at high temperatures, (9) 238*c*.
of glass below room temperature, (10) 265*j*.
of porcelain bodies, (4) 102*i*.

Rutile. See also *Titanium, dioxide.*
electrical conductivity, B (11) 320*g*.
electrical conductivity, variation with time, (3) 87*a*.
friction peak, low-temperature internal, (9) 251*b*.
growth, of controlled composition from borate fluxes, (3) 82 *f*.
near-stoichiometric, electrical conductivity at 600° to 1400°C, (1) 20*j*.
single crystals, conduction phenomena in, (4) 110*b*.
single crystals, dislocation damping in, (2) 49*j*.
sintering, in presence of additives, (9) 255*f*.
and ZrO_2, formation of $ZrTiO_4$ from, (11) 304*j*.

Safety. See also *Health.*
protective clothing, in hot tunnel kilns, (3) 77*e.*
Saggers. See *Kiln furniture.*
Salts, molten, material exchange between silicate glass and, (4) 94*e.*
organic, effect on setting time of gypsum plaster, (9) 230*i.*
rejection, by porous glass, (5) 121*j.*
resistance, of dispersions of clay minerals, (10) 290*j.*
sevenfold reciprocal system of, (9) 255*h.*
solutions, ion exchange in extraction of soda-lime glasses with dilute, (6) 148*c.*
Samarium, beryllides, of composition ABe_{13}, (11) 313*j.*
chlorides, vapor pressure of anhydrous, (1) 20*i.*
divalent ions, spectra in crystals of alkaline earth fluorides, (9) 256*d.*
hydroxide, thermal decomposition of, (10) 291*b.*
orthoniobates of, (11) 318*c.*
oxide, B-form of, (10) 283*j.*
interaction with fluoride melts, (10) 287*a.*
systems. See *Systems.*
transformation of and interactions with chlorides of Li and K and with the carbonate and sulfate of Na, (3) 87*j.*
silicates, crystalline structure of, (7) 198*e.*
trichloride, systems. See *Systems.*
Sampler, P (2) 45*j.*
Sampling, to λ amount of items per sample, (4) 108*j.*
mechanism, P (6) 163*d.*
results, confirmation of, (4) 109*a.*
Sands, coarse, granulation of glass batch containing, (4) 93*d.*
glass, possibility of purifying by flotation, (4) 94*f.*
Illinois, feldspar in, (7) 196*h.*
Lithuanian, granulometric analysis of quaternary, (11) 314*c.*
method to upgrade, P (4) 101*j.*
mineralogy, of alluvial near Charsadda, Pakistan, (11) 312*e.*
quality, for production of mirror glass, (3) 62*g.*
quartz, beneficiation of Lithuanian, (7) 196*c.*
from region of Elena, Bulgaria for glass, (2) 32*g.*
survey of German and foreign deposits, (10) 282*j.*
Sandstones, dispersal and petrology, in Arkansas and Oklahoma, (5) 133*c.*
unit, trend and genesis of lowermost at Eagle Sandstone, Billings, Montana, (2) 47*j.*
Sanitary ware, (2) 39*h.*
bathtub, construction, P (7) 179*c.*
dry process enameling, (10) 263*c.*
removable panel, center drain, and wall sealing means, P (9) 230*d.*
of sheet steel, (6) 145*j.*
casting slips for, (2) 39*i.*
glazes, control of pigment for, (2) 39*d.*
industry, hydrostatic pressing to replace slip casting in, (5) 127*f.*
manufacture, in Mexican plant, (4) 102*f.*
mechanized conveyor for, (6) 156*h.*
modular bathrooms, (4) 102*f.*
plans for new plant, (1) 12*i.*
plant, plans for construction of, (6) 156*f.*
rapid drying, (2) 39*h.*
research in, (1) 12*j.*
slip casting, replaced byhydrostatic pressing, (5 127*f.*
status of wollastonite glazes for, (2) 40*a.*
toilet, P (11) 304*f.*
bowls, casting, P (2) 40*c.*
double trap, P (5) 127*g.*
flush tank, P (9) 230*e.*
with overflow trough, P (10) 262*b.*
sealing ring for outlet, P (5) 127*j.*
with siphonic flush, P (3) 58*c.*
Saponite, crystal chemistry, and thermal behavior, (3) 80*h.*
dehydration, infrared spectroscopy of, (1) 22*b.*
Sapphire, crystal, comparison of whisker growth sites and dislocation etch pits on single, (4) 110*a.*
strength of flame-polished, (7) 202*g.*
as thermocompression bonding chisel, P (1) 15*d.*
on steel, mechanisms in wear of, (5) 119*g.*
substrates, Si deposition on, (7) 191*e.*
synthetic, elastic constants at 27°C, (2) 49*h.*
Saws, circular, with diamond edge, P (3) 57*g.*
Scandium, manganese(III) oxide, a compound isotypic with $LuMnO_3$, (2) 51*b.*
oxide, systems. See *Systems.*
tungstate, unit cell and space group of, (8) 228*a.*
Sc_2O_3–MgO, phase diagram of, (9) 252*j.*
Scattering, beta-ray back-, analytical applications of, (11) 309*e.*
experimental atomic, factors for magnesium oxide, (10) 286*c.*
from graphite, electron binding energy effects in, (9) 249*h.*
phonon, by ions in MgO, (8) 226*g.*
temperature diffuse, general theory of diffraction pattern caused by, (4) 110*g.*
Screening, cylindrical apparatus, P (1) 16*a.*
device, for mixing and/or grinding drum, P (2) 48*b.*
problems, new method of solving, (6) 164*h.*
Screen process printing. See *Decoration.*
Screens, color, with electron- and light-absorptive material separating color strips, P (3) 72*i.*
color TV, colorimetry of phosphor, (8) 219*i.*
light output of those with Eu-activated phosphors as red component, (8) 220*c.*
slurry process to produce, (8) 208*g.*
glass, transparent luminescent, P (10) 269*j.*
lead, intensification factor determined by radiography, (11) 310*i.*
luminescent, for cathode ray tubes, P (11) 306*f.*
Screens and sieves, bodies, shaped crystalline zeolitic molecular, P (10) 276*d.*
Screens and sieves (*continued*)
to determine fineness of cement, (6) 144*g.*
micromesh, for sieve analysis, (9) 245*j.*
modified zeolitic, and process to produce, P (3) 79*c.*
molecular, (4) 102*d.*
bonded, P (2) 47*d.*
hardened agglomerates and manufacture of, P (5) 127*g.*
industrial applications, (7) 190*d.*
synthesis and applications, (2) 47*g.*
prolonging life, (2) 35*h.*
screen, resiliently suspended vibrated by impact, P (2) 43*h.*
sieving, theory of, (2) 43*h.*
sieving characteristics, of symmetrical tabular grains, (2) 43*h.*
small-diameter, maximum load for, (4) 107*i.*
vibrating, P (10) 280*e.*
vibratory, stepped, P (5) 131*b.*
Sculpture. See *Art and artware.*
Seals and sealing. See also *Bonding; Soldering.*
apparatus, for reeds through glass envelope, P (10) 267*a.*
articles, and methods of forming, P (1) 15*f.*
ceramic-metal, P (8) 220*c.*
ceramic-to-metal, vacuum tight, (9) 242*f.*
compositions for holes in glass, P (2) 33*e.*
compression, devitrified glass-to-metal, P (3) 63*d.*
devitrified glass, method to form with W or Mo, P (10) 269*b.*
for electrodes, P (8) 220*b.*
for electronic element, P (3) 73*h.*
of fused solder glass, P (9) 235*j.*
of glass, compositions and method of modifying, P (7) 183*g.*
glass-ceramics, materials and method to seal to metals, (11) 297*f.*
of glass-copper tubing, (10) 266*g.*
glass foil as, P (2) 33*d.*
glass-to-glass, method to supply heat of fusion to, P (1) 7*a.*
glass-to-glass, solder for, P (3) 64*j.*
glass-to-metal, P (10) 278*i.*
and glass-to-ceramic, P (11) 296*a.*
hermetic, P (10) 278*i.*
method of making, P (3) 64*g.*
process for bonding, P (3) 64*e.*
of glass parts, P (11) 298*i.*
of glass-type envelopes, P (10) 278*d.*
glass vacuum, for high temperature, (10) 281*b.*
hermetic, glass for, P (11) 296*a.*
lead-in, for tube of electron discharge device to connect electrodes in to outside power source, P (11) 306*i.*
metal to ceramic, P (1) 14*h.*
metal-to-ceramic, demountable, P (10) 278*c.*
method, P (6) 160*f.*
orifice disk, for glass receptacle wall, P (10) 269*g.*
pressure stopcock, P (10) 269*h.*
quartz to metal, P (1) 15*d.*
refractory vessel, containing radioactive wastes, P (1) 11*e.*
stress-relieved, for arcuate fluorescent lamp, P (11) 299*h.*
vacuum, of rough surfaces, (10) 277*d.*
for vacuum-tight spinel bodies, P (6) 160*c.*
Sedimentation, in centrifugal field, calculation of course of, (7) 197*i.*
-flocculation efficiencies, measurement of, (9) 245*e.*
Sediments, carbonate, deep-sea from Red Sea and their implications on marine lithification, (11) 315*d.*
from New South Wales, clay mineralogy of some Upper Devonian, (4) 108*h.*
particle size, determined by radioactive radiation, (11) 309*g.*
Selenates, sodium, crystal structure of, (6) 166*g.*
Selenide, sesqui-, rare earth with Sc_2Si_3 structure, (8) 227*f.*
systems. See *Systems.*
Selenite, and oxyselenites of lead, properties, (2) 52*c.*
Selenium, dioxide, production of, P (10) 283*g.*
in glass, chemistry of, (3) 60*d.*
losses, causes and problem of reducing in melting of red glasses, (9) 235*d.*
partial pressure, effect on electrical conductivity of CdSe single crystals, (3) 81*h.*
in ruby glass, determination of, (10) 264*c.*
ruby glass, (4) 95*e.*
mechanized production of sheet, (4) 94*h.*
structure of pigment in, (8) 211*d.*
-ruby reaction, mechanism of, (9) 233*i.*
single crystals, effect of temperature on optical absorption edge, (3) 81*j.*
systems. See *Systems.*
vitreous, conductivity anomaly associated with glass transition in, (6) 165*e.*
vitreous, mechanical properties near its glass transition, (3) 85*g.*
xerographic layers, dependence of dark discharge on temperature, (6) 166*d.*
Semiconductors, P (6) 160*d, g.*
articles, method to produce, P (6) 160*c.*
barium titanate, containing controlled amounts of neodymium, (10) 277*h.*
barium titanate, electroless electrode for, (9) 242*i.*
bodies, apparatus to dope and contact, P (9) 242*i.*
apparatus to produce elongated strip-shaped crystalline, P (11) 306*b.*
fabrication of, P (2) 41*a.*
method to control diffusion of an active impurity material into, P (7) 193*i.*
method to etch Si and Ge, P (10) 278*g.*
and method of forming, P (1) 14*g.*
method to provide alloy contacts on, P (4) 105*f.*
bonding of, *p*-type alloy using boron-gold alloy, P (2) 42*c.*
Semiconductors (*continued*)
compound, method to determine active impurities in gaseous decomposable, P (5) 132*b.*
compound bodies, ohmic contact to III–IV, P (2) 42*a.*
contact means, P (10) 279*c;* P (11) 307*e.*
contacts, method of fabricating, P (2) 41*j.*
counter circuit, microminiaturized, P (11) 307*j.*
crystalline, oxide coating on, P (9) 243*d.*
crystals, and apparatus, method to produce highly pure rod-shaped, P (3) 73*h.*
apparatus to pull rod-shaped from melt, P (9) 242*j.*
mercury-doped Ge, P (11) 306*i.*
method to mark, P (10) 279*b.*
method to measure electrical properties, P (2) 42*c.*
method to pull from melt, P (10) 279*d.*
production of rod-shaped, P (5) 129*g.*
current limiter, P (11) 307*g.*
devices, P (2) 42*h;* P (3) 74*f;* P (5) 129*g;* P (8) 221*j;* P (9) 243*g,* 244*b;* P (10) 279*d,e;* P (11) 306*i,* 307*e.*
with dielectric coatings, P (2) 42*h.*
electrically asymmetrical of symmetrical mechanical design, P (5) 129*h.*
fabricating, P (2) 41*j.*
fabrication by transmutation doping, P (8) 221*a.*
from gallium arsenide, P (9) 243*j.*
gold bonded boron containing, P (2) 41*d.*
gold-germanium alloy for contact and alloy medium on, P (6) 159*h.*
high voltage, (4) 105*c.*
and material, P (7) 194*d.*
and method, P (3) 73*j,* 74*f;* P (4) 105*a,* 106*g;* P (5) 130*b.*
method to attach electric connection to, P (4) 105*c.*
method of attaching metallic leads to silicon layers of, P (2) 41*h.*
method to fabricate a rectifying connection to a body of germanium, solder, and, P (6) 159*h.*
method to form enclosures for, P (3) 73*j.*
method to heat treat to stabilize current amplification factor, P (4) 105*f.*
method to improve electrical properties of gallium arsenide, P (8) 221*i.*
method to make, P (10) 278*h.*
method to make by alloying a gold disk to a Ge pellet, P (6) 159*h.*
method to make by forming damage layer on surface and then alloying through layer, P (5) 129*f.*
method to make low resistance contact to, P (8) 221*a.*
method to make supported, P (8) 221*j.*
method to produce, P (2) 42*f;* P (6) 160*d.*
method to produce with a monocrystalline semiconductor body, P (4) 105*e.*
method for surface treatment of junction type, P (4) 105*f.*
mixed-crystal, P (9) 243*h.*
multiple heterolayer composite, P (11) 307*e.*
photoelectric, P (9) 243*c.*
planar, P (11) 307*f.*
with plated area, P (8) 221*a.*
production of electrical, P (11) 307*a.*
quantum mechanical tunneling, P (4) 106*d.*
radiation powered, P (10) 279*b.*
with self-protection against overvoltage, P (9) 244*c.*
silicon, P (10) 279*d.*
Si for high frequency, P (9) 244*d.*
with silver-gold lead wires attached to Al contacts, P (11) 307*h.*
surface-potential controlled, P (2) 43*a.*
surface protection for tunneling, P (10) 279*f.*
diamond, method to create electrically, P (10) 278*f.*
diodes, enhancement of reverse current in by electron bombardment, (10) 276*f.*
doppler effects of drifting plasma in, (6) 157*h.*
electroluminescent, P (2) 42*g.*
electronic, members and method of manufacture, P (4) 104*f.*
electronic, method to produce, P (4) 105*c.*
electrons and holes in, B (9) 250*f.*
elements, foil ribbon to connect to thin film circuits, P (5) 128*a.*
masking process for, P (8) 221*g.*
multiple resistance, P (6) 160*g.*
encapsulation of, P (11) 307*i.*
films, P (4) 106*f.*
galvanomagnetic, P (10) 278*i.*
germanium, method to improve electrical characteristics of, P (4) 105*g*
glass-bonded mica, new electronic composite, (6) 155*i.*
glass-encased, P (11) 306*g.*
heterojunction device, P (5) 130*b.*
high-melting point, rhenium disilicide as new, (11) 319*b.*
high resistance, change in conductivity of in powerful field of superhigh frequency, (11) 314*f.*
high resistance, photosensitivity of, (6) 169*e.*
impurity diffusion method for, P (6) 159*a.*
ingots, preparation within a depression, P (9) 244*a.*
integrated, P (5) 129*d.*
junction, method to form, P (8) 221*h.*
materials, P (1) 15*h;* P (7) 194*a.*
apparatus for floating-zone melting, P (10) 278*d.*
apparatus to prepare, P (4) 104*h.*
apparatus for producing, P (8) 220*j.*
apparatus to produce crystals of, P (6) 158*e.*
bonding metal plates to, P (2) 41*a.*
device to pull rods of, P (9) 244*e.*
device to score crystalline, P (3) 73*a.*

Semiconductors, materials (*continued*)
device to treat and melt, P (9) 243*b*.
furnace for producing crystalline, P (1) 14*f*.
growing single crystals of, P (6) 159*h*.
method of crucible-free zone melting, P (3) 73*i*.
method of doping, particularly Si with B, P (6) 159*g*.
monocrystalline elongate polyhedral, P (4) 105*i*.
material, processing, P (11) 307*h*.
research, (5) 131*h*.
melt, impurity redistribution and determination of thickness of diffusion layer in, (11) 304*i*.
member, producing, P (11) 307*b*.
metal oxide, (6) 158*g*.
metal-oxide, enhancement transistors, (3) 72*c*.
and method to form by diffusion, P (6) 160*j*.
method of forming, P (4) 105*e*.
and method to make, P (6) 160*e–f*.
method to make, P (6) 159*j*.
method to make alloy connections to, P (4) 105*i*.
monocrystals, method of producing via vapor phase, P (2) 42*f*.
multistack, to regulate charging of storage cells, P (11) 308*a*.
negative resistance in, avalanche breakdown double-injection induced, (4) 103*f*.
networks, P (2) 42*i*.
n-type, cubic boron nitride as, P (2) 42*j*.
ohmic contacts for, P (5) 129*i*.
plates, method and apparatus to score, P (4) 105*c*.
plural emitter, P (1) 15*b*.
pn junction, P (10) 278*a*.
pupn, translating device and method of construction, P (2) 42*b*.
process to make, P (4) 106*c*.
properties, of SnSe and GeSe, (4) 104*e*.
and protective coatings for, P (7) 192*c*.
punch-through device, adjustable with three junctions, P (10) 277*g*.
rim, formed by sandblasting, P (10) 278*j*.
resistivity, device to measure, P (5) 129*h*.
rod, apparatus to prepare, P (4) 104*h*.
device for pulling monocrystalline, P (5) 128*b*.
material, support assembly for processing and method, P (5) 129*a*.
semiconducting compounds, (3) 72*j*.
semiconduction of $BaTiO_3$, effect of TiO_2 on, (3) 72*f*.
surface, calculations, tables for, (10) 277*j*.
surface, space-charge layer, conditions for quasi-equilibrium in, (10) 284*h*.
surfaces, Fermi level stabilization at, (10) 286*f*.
method to clean, P (3) 74*g*.
pyrolytic deposition of protective coatings of, (6) 160*d*.
relation to adsorption, catalysis, and adherence, B (6) 175*c*.
switch, P (6) 160*j*.
temperature compensating barrier layer, P (9) 244*a*.
thickness and resistivity, methods to determine by loss in transmission line, P (2) 42*g*.
III–V, in crystalline form, P (11) 307*a*.
tunnel-diode, small *pn*-junction, P (5) 130*c*.
volume resistivity, method and apparatus to measure, P (2) 42*a*.
wafer, apparatus to handle, P (11) 306*b*.
wafers, electrodes to, P (6) 159*d*.
Seminars, on energetics in metallurgical phenomena, B (7) 204*d*.
on fiber composite materials, B (3) 88*i*.
Separation. See also *Beneficiation; Classification; Flotation*.
adsorption, solids drying, and membrane penetration as methods of, (11) 308*f*.
catalytic, of carbon in fireclay, (7) 185*f*.
of heavy media, method and apparatus for, P (7) 196*j*.
of materials, electrostatic, P (7) 196*i*.
method, for trivalent rare earths plus Sc(III) from other elements by cation-exchange chromatography, (6) 163*c*.
micro-, in lead borate glasses, (3) 61*e*.
of particles, in a jig, P (8) 225*c*.
phase, initial stages in glasses, (2) 31*h*.
phase, in preparation of glass-ceramics, (4) 94*d*.
pyrohydrolytic, to determine B in materials, (9) 245*c*.
of slurries into solid and fluid components, method and apparatus for, P (1) 18*b*.
of solids from suspensions, process for, P (6) 161*f*.
Separators, air, with fluidized discharge, P (11) 308*j*.
centrifugal, for suspensions, P (11) 309*c*.
centrifuge, solid bowl with air circulation control, P (11) 309*c*.
cyclone, for high temperature operation, P (11) 308*h*.
electrostatic, for fine powder, P (11) 309*b*.
electrostatic, to size particles, P (9) 245*a*.
high-intensity magnetic, P (7) 196*j*.
for liquids and solids, P (8) 222*f*.
Sepiolite, crystal chemistry, and thermal behavior, (3) 80*h*.
Serpentine, Spanish, forsterite from, (8) 25*b*.
Settling. See *Sedimentation*.
Sewer pipe. See *Pipe*.
Shales, in Alberta, study of clays from Upper Cretaceous, (3) 86*d*.
body, burnout rates on, (4) 98*f*.
for brickmaking, analysis of gas from, (10) 270*c*.
expansible, resources in California, (7) 196*h*.
fines, reclaimed at lightweight aggregate plant, (4) 98*f*.
Montana, 1962–1964, (8) 225*h*.
in Ontario, (6) 164*d*.
from Osterwald, Germany, (3) 78*b*.
Pennsylvania, properties and uses, (11) 312*h*.
preparation, theory and practice, (6) 164*h*.
Shielding, radiation, of concrete and aggregates, P (5) 119*e*.
Shipment. See *Transportation*.
Shock, explosive, to form zinc orthosilicate, (10) 286*j*.
explosive waves, effect on powders, (10) 285*f*.
thermal, test of stopper heads, (8) 216*i*.
Shock resistance, thermal, of basic brick, testing by air-quenching, (9) 239*j*.
damage, evidence for, (8) 215*h*.
of glasses, effect of repeated temperature changes on, (2) 31*h*.
of materials, (2) 55*b*.
of refractories, (10) 273*b*.
theory, for semitransparent ceramics under radiation heating, (3) 86*i*.
of zirconia, with 15% (mole) Ti, (7) 187*i*.
of zirconia, mechanism by which metal additions improve, (7) 187*b*.
Shrinkage, of cement mortars, effect of repeated wetting and drying, (8) 206*g*.
of concrete, effect of aggregate properties on, (2) 28*g*.
of hardened cement mortar and concrete, effect of wind on drying, (3) 58*f*.
of kaolin, inner structure between 600° and 1200°C, (9) 255*b*.
of masonry mortars, effect of restraint on, (3) 58*i*.
Sieves. See *Screens and sieves*.
Silex. See *Quartz*.
Silica. See *Silicon, dioxide*.
Silicates, alkali, relation between density and composition in aqueous solutions of, (10) 266*d*.
alumino-, sodium zeolite as new synthetic, (6) 164*j*.
anhydrous layer, reaction with silver nitrate, (3) 85*g*.
and bodies from, P (10) 274*f*.
bonding of amines to, B (7) 204*f*.
cements, for technical and dental use, (2) 29*g*.
chemistry, determination of alkali content by ion exchange and volumetric methods, (3) 76*a*.
chemistry, physics, and technology, present and future, (2) 54*g*.
diortho-, structural analogy with orthoborates, (4) 113*e*.
engineering, education in Vienna, (2) 54*j*.
fibers, properties of Bulgarian, (4) 125*a*.
fibrous, B (11) 319*i*.
formable, P (10) 273*h*.
glass, acoustic-dilatometric studies of effect of composition on strength, (10) 264*b*.
acoustic-dilatometric studies of effect of composition on structure, (9) 232*h*.
coactivated with Yb^{3+} and Ho^{3+}, energy transfer and Ho^{3+} laser action in, (7) 199*g*.
containing Ti, EPR of, (7) 180*i*.
effect of heat treatment on properties and structure of, (7) 179*i*-180*b*.
effect of oxides on diffusion of helium through, (7) 181*g*.
effect of water content on transformation and softening behavior, (5) 120*j*.
hot water attack on, (8) 209*e*.
kinetics of material exchange at interface with molten salts and material transport in, (4) 94*d*.
microindentation hardness and atomic significance, (2) 32*d*.
and molten salts, kinetics of material exchange with molten salts and material transport in melts of, (6) 148*e*.
oxygen tracer investigation of diffusion of "water" in, (9) 234*h*.
systematology of, (4) 95*c*.
industry, proceedings of conference, B (2) 56*b*.
industry, theory of solid phase reactions in, (7) 203*c*.
iron in, spectrophotometric determination of, (2) 44*b*.
kaolin-type, stacking faults in, (7) 202*e*.
laminar, crystal chemistry of, (9) 249*a*.
with laminated structure, increasing ≡Si—OH surface groups in, (5) 137*h*.
layer, significance of structure determinations for clay studies, (8) 227*c*.
structural modifications and possibilities to determine by electron and X-ray diffraction, B (2) 56*b*.
-structure, assignment of infrared absorption bands in, (3) 84*b*.
liquid, approach to problem of ionic distribution in, (3) 79*f*.
Mg in, determination by spectroscopy, (11) 309*f*.
materials, polarographic determination of Al in, (2) 44*i*.
melts, activities of MnO, sulfide capacities, and activity coefficients in, (1) 7*j*.
electromotive force of concentration cells with semipermeable bridges, (5) 135*h*.
and glasses, model of polymerization/depolymerization relations in, (2) 32*i*; correction, (5) 121*f*.
Pt-Rh-O electrode in, (5) 139*j*.
spontaneous bubble formation at high temperature, (11) 297*i*.
methods to analyze, B (6) 173*b*.
microanalysis, (4) 107*d*.
migration, in basic refractories, (10) 272*g*.
minerals, calculation of formation energies from solubility data, (9) 248*f*.
with increased surface area and adsorption properties, P (11) 303*f*.
synthetic, P (8) 225*i*.
template to characterize in OH region of the infrared spectrogram, (7) 203*c*.
organic, composition containing, P (7) 190*h*.
ortho-, of divalent elements, infrared absorption spectra of, (10) 286*j*.
particle, method to produce metal coated, P (9) 240*b*.
Silicates (*continued*)
physical, chemical, and structural aspects of, (8) 227*d*.
pyro-, luminescence of lead-activated structures, (7) 200*h*.
refractory, decomposition method, (1) 16*i*.
rocks, composition of precipitates formed by decomposition in 38 to 40% hydrofluoric acid, (7) 200*d*.
sediments and rocks, determination of V in, (6) 166*f*.
-silicon, automatic determination in natural waters especially sea-, (11) 309*i*.
simplest, of La and Sm, crystalline structure of, (7) 198*e*.
sonic cutting, limits and possibilities of, (7) 195*c*.
structure, in liquid state, (7) 202*j*.
systems. See *Systems*.
tricalcium, stoichiometry and polymorphism of, (9) 256*c*.
of type Al_2BaO_4, crystallography of, (6) 166*j*.
Silicides, di-, transition metals, thermal expansion of, (2) 53*a*.
atomic interaction and inner electron state of iron atoms in, (11) 313*i*.
layers, on Mo, effect of stress on imperfection of, (11) 295*d*.
transition metal, shear moduli of, (9) 255*i*.
vacuum siliciding, of refractory metals, (10) 271*b*.
Silicon, and As, separation by solvent extraction and simultaneous determination of P, As, and Ge, (9) 246*a*.
-B alloys, preparation of, (11) 301*i*.
carbide. See also *Refractories*.
carbide, alloy junction formation temperature and electroluminescence in 4H, (11) 313*h*.
apparatus for and preparation of single crystals of, P (11) 311*h*.
apparatus to produce high purity crystals of, P (4) 100*b*.
behavior in kilns, (5) 125*a*.
β-, effect of crystal orientation on hardness, (1) 20*c*.
bodies, properties of those of various densities, (9) 239*a*.
colloidal and method of making, P (5) 125*h*.
comparison of four kinds of nozzles, (9) 237*j*.
defect structure and polytypism in, (11) 315*g*.
deformation behavior of dense polycrystalline, (6) 166*a*.
dense bodies of, P (11) 303*g*.
determination of content of refractory materials, (7) 186*i*.
durability in stressed state, (10) 285*b*.
effect of O deficiency on bonded refractories of, (10) 271*a*.
elastic constants of, (7) 198*j*.
electroluminescence of single crystal, (10) 276*j*.
growth of crystals from vapor state, B (11) 320*a*.
honeycomb, uniform, (9) 237*j*.
ladle brick, comparison of fired and unfired, (1) 8*e*.
luminescent, P (5) 128*i*.
method to grow single crystals, P (4) 101*d*.
method to prepare fibrous, P (7) 188*h*.
neutron activation analysis of, (6) 153*f*.
and nitride, as heat resisting material, P (2) 37*h*.
pigmentary, P (11) 303*a*.
pyrolytic, (9) 254*f*.
recovery from slurry, P (9) 229*h*.
in refractories, (10) 272*c*.
refractories containing, P (6) 154*e*.
results of tests on nozzle of, (3) 69*a*.
sintering of, B (11) 320*d*.
stopper head, thermal conductivity as related to corrosion of stopper rod, (3) 68*j*.
substrate with epitaxial layer of boron phosphide, P (1) 14*f*.
in unburned brick, service tests for electric furnace ladles, (9) 239*e*.
crystals, dislocation-free single, P (11) 307*i*.
deposition, on sapphire substrates, (7) 191*e*.
diffusion of B in, through oxide layer, (10) 284*c*.
dioxide. See also *Cristobalite; Glass; Quartz; Quartzite; Refractories; Sands*.
-alumina, cracking catalysts, coke formation on, (5) 125*d*.
-Al reaction, kinetics of, (9) 251*h*.
articles of fused, P (2) 40*j*.
beads, P (9) 241*d*.
body, effect of octadecylamine salts on workability of, (10) 288*j*.
-bonded magnesia clinker, comparison with Fe oxide-bonded magnesia clinker, (7) 185*j*.
in borate glasses, time and temperature effects on distribution of, (3) 62*b*.
-B_2O_3 glasses, electrical conductivity of those containing Li or Na, (5) 120*d*.
brick, surface effects on hot face of glass tank crown, (10) 265*b*.
cooperative phenomena and glass formation with special reference to, (5) 120*f*.
degradation of growth perfection of BeO crystals by, (1) 20*c*.
dissolution of fused in CaO-Al_2O_3-SiO_2 melt, (4) 93*b*.
dissolving of disperse in $Na_2O \cdot 2B_2O_3$ melt, (10) 284*h*.
effect on element transition in basic brick, (3) 66*b*.
effect as impurity in magnesia refractories and dolomite, (6) 152*b*.
effect of phosphorus in, (10) 285*g*.
electrical bombardment induced conductivity in fused, (4) 110*j*.
electrical conductivity of amorphous aqueous solutions, (6) 167*h*.
etching by sputtering, (8) 226*e*.

Silicon, dioxide (*continued*)
γ-radiation-induced exchange of deuterium with surfaces of, (9) 250*e*.
glass, crystallization in oxidizing atmosphere, (2) 31*c*.
glass, kinetics of crystallization in H_2O atmospheres, (4) 112*b*.
hydrothermal transformations, (8) 226*g*.
infrared absorption spectrum of, (1) 22*a*.
interface, measurement of strains at, (9) 252*b*.
interference in phosphate analysis, (7) 195*b*.
-iron oxide melts, density of, (1) 20*d*.
kinetics of solution in $Na_2O \cdot 2B_2O_3$ melt, (7) 200*g*.
lead glass skin on, (1) 4*d*.
in magnesia clinker, effect on magnesia-chrome brick, (3) 67*a*.
-$MgAl_2O_4$ join, metastable solid solutions on the, (3) 83*e*.
and MgO, solid state reaction to form forsterite, (3) 83*c*.
manufacture of finely divided, P (5) 133*d*.
means to determine in rocks and minerals, (3) 76*d*.
-metal diodes, rectification phenomena in, (10) 277*i*.
method to determine, (4) 107*d*.
method to make finely divided, P (2) 47*i*.
nonlinear variation of refractive index of with pressure to 7 kbars, (11) 318*c*.
phases of, B (6) 174*h*.
pigments from fluosilicic acid, P (11) 312*j*.
preparation for electric-field-responsive compositions, P (7) 194*b*.
preparation of foamed, (10) 272*e*.
preparing finely divided of varied properties, P (10) 283*f*.
process to prepare microspheroidal, P (6) 164*j*.
process to produce readily dispersible, P (3) 79*a*.
producing pigmentary, P (5) 134*a*.
production of alumina-coated in sol form, P (8) 225*c*.
production process, P (9) 247*h*.
properties and formation of gels from acid clay, (9) 247*f-g*.
properties of hydrogels from acid clay, (9) 247*f*.
pyrogenic, dielectric constant as function of specific surface, (9) 249*f*.
radiation induced optical absorption in fused, (4) 112*i*.
reactions with graphite, (8) 227*h*.
reduction in blast furnace slag-metal systems, (1) 9*h*.
refractories containing Fe_2O_3, (5) 125*c*.
refractory articles from, P (3) 70*h*.
secondary reaction in transformation of, (8) 227*a*.
and silica-alumina, Moessbauer effect for finely divided iron oxide on, (1) 23*a*.
solubility of gases in, (10) 265*j*.
stabilization of sols, dispersions, or suspensions and siliceous materials, P (9) 247*f*.
surfaces, factors affecting Si growth on amorphous, (11) 316*h*.
systems. See *Systems*.
treatment of pigmentary, P (11) 313*a*.
third-order elastic constants of fused, (3) 87*i*.
vitreous, P (11) 299*g*.
-ZrO_2-Al_2O_3, refractories for ladles, (9) 239*f*.
dioxide gels, adsorption and reaction of coordination complexes on, (3) 79*g*.
coprecipitation with alumina gels and their transformation at higher temperatures, (5) 134*d*.
effect of heat treatment of on properties of high-silica foam materials, (6) 147*b*.
nature of mullite formed from coprecipitate of alumina gels and, (5) 139*b*.
emission of hot electrons by, (6) 167*a*.
etching corundum with, (9) 250*a*.
in ethylene glycol solutions, anodic oxidation of, (11) 313*j*.
films, properties and structure of those sputtered on quartz, (7) 192*c*.
films, texture and electrical properties of vacuum evaporated, (2) 40*h*.
and Ge, electrical conductivity of *n*-type in crossed electrical fields, (11) 316*i*.
heat treated, optical absorption of, (10) 289*d*.
in high electric fields, effect of surface finish on electrical conductivity, (3) 72*d*.
monoxide, technique for observing surface microtopography, (2) 45*j*.
nitride, body and method, P (3) 73*d*.
brick, applicability and its erosion by nonferrous metals, (4) 99*a*.
engineering ceramic, (8) 216*j*.
as gelation accelerator of silicic acid sol in lost wax process, (6) 153*f*.
process to produce and product of, (4) 101*f*.
production of ultrafine, P (1) 12*e*.
refractories, erosion by iron, (9) 238*f*.
and silicon carbide, frictional properties of, B (11) 320*g*.
synthesis of fibrous, P (6) 155*g*.
systems. See *Systems*.
corrosion by molten nonferrous metals, (7) 188*b*.
n-type, removal of thin layers by anodic oxidation, (7) 192*e*.
oxidation, in dry O, (5) 139*f*.
oxidation, from room temperature etching, (5) 140*c*.
oxide, electrical conduction through films of, (9) 242*h*.
electrical conductivity in evaporated films, (7) 199*a*.
film formation, P (6) 161*a*.
films, stress anisotropy in, (2) 51*h*.

Silicon, oxide (*continued*)
systems. See *Systems*.
oxide-CdS layers, multilayer enhancement of microwave piezoelectric conversion in, (10) 288*b*.
radiation blistering, interferometric and microscopic observations, (9) 254*i*.
-silicate, determination in natural water especially sea-, (11) 309*i*.
and SiC, thermal conductivity of pure and impure, (6) 170*h*.
and SiO_2, capacitor to measure surface state parameters, (10) 288*a*.
SiO_2-Al_2O_3 gels, thermal transformation of those prepared from methylsiloxyaluminum compounds, (9) 257*a*.
into SiO_2, photoemission of electrons, effects of ion migration in the oxide, (9) 253*f*.
single-crystal, growth on beryllium oxide, (11) 317*g*.
in sintered nickel-base materials, determined by spectral analysis, (3) 66*c*.
subnitride, $(Si_4N_3)_n$, preparation of new, (3) 85*e*.
surface conductivity, long-term relaxation of, (10) 287*h*.
surfaces, effect of residual atmospheres on, (11) 316*e*.
thermal oxidation, (10) 291*c*.
thermal oxidation, relation for, (5) 136*e*.
wafers, preparation of oxide-isolated for microcircuits, (11) 304*g*.
welding, of B_4C to, (8) 216*f*.
Silicone, on glass, effect and behavior, (7) 179*g*.
on glass surfaces, effect and behavior of, (5) 120*h*.
treatment, of brick, (10) 270*d*.
treatment, of glass surfaces, (5) 121*a*.
Silicosis, (10) 292*c*.
index, testing of, (10) 280*i*.
Sillimanite. See also *Refractories*.
-garnet-biotite gneisses, from Quebec, analyses of equilibrium in, (7) 197*d*.
group, structure and transformation of minerals of, (10) 287*h*.
kyanite-, equilibrium at 750°C, (5) 138*c*.
Siloxanes, -coated glass containers, steam cure of, (10) 266*a*.
Silver, chloride, effect of thermal treatment on formation of trapping level spectrum in, (2) 49*g*.
chloride, interaction with chlorides of Ga, Na, and Cu(I), (11) 317*g*.
chloride, systems. See *Systems*.
coating, over gold coating on stemware, (10) 261*i*.
compounds, to color glass red, (4) 95*c*.
iodide, polymorphs, (9) 255*c*.
ion, sorption properties of glass surfaces, (5) 121*d*.
ion, transport and deposition in α-quartz, (2) 48*e*.
metallic, equilibria of molten $Na_2O \cdot 2SiO_2$ glass in contact with, (11) 297*d*.
on mirror, apparatus to measure thickness of, (10) 280*h*.
nitrate, reaction of silicates with, and lattice constants of Ag_2SiO_4, (3) 85*g*.
Ag_2O crystals, X-ray of binding properties, (10) 292*a*.
systems. See *Systems*.
tellurates, conditions for obtaining, (1) 19*i*.
vanadium oxide bronzes, hydrothermally grown, (1) 22*f*.
vanadium oxide bronzes, properties of, (1) 25*c*.
Single crystals. See *Crystals*.
Sintering, activated, based on chlorine, (10) 272*a*.
in active nickel oxide, (1) 25*a*.
of alumina, effect of manganese oxide on, (1) 20*e*.
behavior, of UC, B (6) 172*c*.
of BeO, to variable densities and grain sizes, (1) 10*j*.
bodies, apparatus for, P (7) 195*j*.
of C composites, changes during and their effects on resistivity, (10) 285*c*.
of ceria, (2) 48*h*.
growth of corundum crystals during, (6) 167*g*.
in impure ionic solids, (8) 226*i*.
initial, of α-Cr_2O_3, (2) 50*f*.
kinetics, of beryllia, (4) 113*b*.
mathematical-phenomenological study of, (5) 141*g*.
of vanadium carbide, (9) 255*g*.
of magnesia, effect of water vapor on initial, (11) 316*i*.
in MgO and CaO, effect of V and Sr, comments on, (8) 226*a*.
of materials, B (7) 204*e*.
mechanism of alumina based cermets, effect of, additives on, (6) 151*g-j*.
mechanism of material transport in, (11) 318*a*.
of preformed bodies, method and articles, P (7) 196*b*.
in presence of liquid phase, capillary phenomena in densification, (9) 255*a*.
pressure, die design for, (10) 280*a*.
processes, theoretical studies of, (4) 113*i*.
reactions, between lime and chromium oxide, (4) 113*g*.
reduced pressure, of MgO as high frequency insulator, (10) 290*f*.
of refractories, (2) 37*g*.
relation to creep, (8) 216*g*.
study up to 3000°C and 1000 kg/cm², (11) 301*h*.
of rutile, in presence of additives, (9) 255*f*.
sintered materials, presses and dies, for special shapes, (2) 43*e*.
technology, handbook of microscopy in, B (9) 258*c*.
temperature, Hall coefficient and conductivity measurements of cadmium oxide in terms of, (6) 167*i*.
temperatures, effect on densification of NbC compacts, (1) 8*d*.
of vanadium dioxide, (2) 51*c*.

Sintering (*continued*)
various stages, network topology to describe two-phase structures during, (5) 138*i*.
Slagceram. See *Glass*.
Slags, basic, determination of metallic iron in, (9) 246*d*.
basicity, adjustment in ladles to extend life of lining brick, (9) 237*i*.
basicity, effect on element transition in basic brick, (3) 66*b*.
blast-furnace, determination in cements, (8) 206*j*.
blast-furnace, effect of undercooling and MgO and Al_2O_3 contents on crystal growth rate in, (6) 167*f*.
coal-ash, medium to calcic plagioclase feldspars from, (6) 170*f*.
composition, changes in ladle during pouring, (7) 185*f*.
corrosion, effects of atmosphere on, (8) 215*e*.
diffusion in, effect of variable temperature, (3) 67*b*.
erosion, resistance of BOP brick, (8) 216*b*.
foamed, method to protect, P (8) 217*i*.
granulated blast-furnace, rapid method to determine hydraulic properties of, (8) 207*e*.
interface, processes between refractory material and, (5) 125*h*.
melting conditions, observation with hot-stage microscope, (9) 238*e*.
metallurgical, crystallization of vitreous phase, (11) 296*e*.
metallurgical, in making glass, (8) 210*j*.
natural and synthetic, results of erosion tests, (4) 99*g*.
penetration, of magnesia bricks, reaction of slag on, (8) 215*c*.
pig-iron, crystallization of acidic, (8) 206*g*.
picket wall, P (9) 241*c*.
reaction, with magnesia clinker, (10) 272*a*.
slagging, resistance, determination of refractory materials, (7) 186*a*.
slagging, tests on basic at high temperature, (6) 154*c*.
in steel, effect as barrier against N pickup in melt, (10) 290*b*.
wool. See *Mineral wool*.
Slip casting, of sanitary ware, hydrostatic pressing as replacement for, (5) 127*f*.
Slips. See also *Suspensions*.
aqueous, of tantalum pentoxide and calcium fluoride, (6) 155*j*.
for casting, P (9) 242*c*.
clay sanitary ware, (2) 39*i*.
control of, (6) 155*j*.
enamel, control of microbe growth in, (6) 145*h*.
enamel, rheology of cover coat, (7) 178*f*.
for ground coat, measurement and control of, (6) 145*j*.
kaolin, new coagulants for, (6) 156*c*.
whiteware, electrical dewatering, (2) 39*a*.
Smoke, density, apparatus to measure, (1) 16*h*.
Soapstone. See *Talc*.
Soda or Soda ash. See *Sodium, carbonate*.
Sodium. See also *Alkalis*.
aluminosilicate, with three-dimensional framework, properties of foreign anions in, (2) 51*h*.
aluminosilicate gel, ion exchange between alkali metal cations and, (10) 287*j*.
-Bi titanates, determination of cell symmetry by X-rays, (5) 135*c*.
borate glass, relation between viscosity and composition of, (8) 234*d*.
borosilicate glasses, orientation effect and form birefringence in, (4) 94*c*.
borosilicate glasses, stresses originating during leaching of, (9) 234*j*.
bromide, systems. See *Systems*.
carbonate, anhydrous dense, P (5) 133*a*.
Brazilian as glass component, (6) 146*j*.
caustic, how to use in glass, (2) 31*f*.
systems. See *Systems*.
carbonate-alumina-silica glasses, diffusion of radiotracer sodium by residual surface counting technique in, (9) 233*e*.
carbonate-lime glass, with dilute salt solutions, ion exchange in extraction of, (6) 148*c*.
initial stages of weathering process on surface of, (5) 120*i*.
structure of, (10) 266*b*.
chlorate, systems. See *Systems*.
chlorides, bromides, and nitrates of, exchange reactions in five-component reciprocal system, (1) 21*j*.
bromides, and sulfates of, (5) 140*g*.
effect of gaseous environment on structure of sputtered GaAs films on substrates of, (9) 249*d*.
evidence of dislocation feeding mechanism for crack reinitiation in F-colored, (6) 167*b*.
interaction with chlorides of Ga, Cu(I), and Ag, (11) 317*g*.
interaction with hexa- and pentachloride of W, (11) 317*e*.
interaction with praseodymium chloride in melts, (2) 52*a*.
interaction with Sn chlorides, (1) 22*e*.
interaction with V trichloride, (11) 317*j*.
means to make dislocations visible in single crystals, (9) 249*i*.
plastic flow induced by partial X-ray irradiation, (1) 23*h*.
resistance of concrete to, (1) 2*j*.
role of contaminants in epitaxial growth of gold on, (4) 112*j*.
systems. See *Systems*.
technique for preparing single-crystal Fe films on substrates of, (4) 104*e*.
whiskers, growth on single crystals of, (7) 199*j*.
chromate, systems. See *Systems*.
dodecyl sulfate, adsorption by kaolinite, B (2) 56*i*.

Sodium (*continued*)
in feldspars, determination of, (3) 75*h*.
fluoride, dipole relaxation in CaF_2 doped with, (9) 249*i*.
phosphate, systems. See *Systems*.
systems. See *Systems*.
thermal expansion at low temperatures and Grueneisen parameter of, (3) 87*a*.
fluosilicate, instructions for placing in charge to accelerate glass melting, (6) 148*c*.
hydroxide, interaction between surface deposit on silicate glasses and solution of, (8) 210*e*.
hydroxide solutions, reactions of thorium carbides with aqueous, (8) 227*h*.
Li and K, fusibility diagram of system of bromides of, (9) 250*c*.
metasilicate, spherical particles and method of making, P (1) 13*d*.
metavanadate, polymorphism of, (3) 84*j*.
neodymium fluoride, and related compounds, crystal structure of, (6) 166*b*.
nitrate, systems. See *Systems*.
oxide, means to determine, (4) 107*e*.
oxide, systems. See *Systems*.
phosphorus zeolites, and ion-exchanged derivatives of tetragonal Na-P, (4) 114*e*.
and potassium, reciprocal system of chlorides and hexafluoroaluminates of, (4) 113*g*.
K, Sr, and Ba, fusibility diagram of system of the fluorides of, (4) 111*f*.
pyrophosphate, systems. See *Systems*.
radiotracer, diffusion by residual surface counting technique in soda-alumina-silica glasses, (9) 233*e*.
selenate, crystal structure of, (6) 166*g*.
silicate, glass, evaporation of water from, (4) 93*e*.
oxygen ion activity and solubility of sulfur trioxide in melts of, (10) 265*j*.
physicochemical properties of high silica, (2) 28*i*.
in slips, enamels, and glazes, (1) 16*c*.
and sodium borate melts, oxygen ion activities in, (1) 19*g*.
solution, reactions with sodium fluosilicate, (5) 140*i*.
silicates, stable alkali-rich, P (9) 247*i*.
$Na_2B_4O_7$ solution, hydrothermal solubility of Al_2O_3 in, (3) 82*b*.
NaCl-KCl, melt containing uranyl chloride, equilibrium potentials of uranium dioxide electrodes in, B (1) 26*j*.
$Na_2O \cdot 2B_2O_3$ melt, dissolving disperse SiO_2 in, (10) 284*h*.
$Na_2O \cdot 2B_2O_3$ melt, kinetics of SiO_2 solution in, (7) 200*g*.
$Na_2O \cdot 2SiO_2$ glass, oxidation-reduction equilibria in molten in contact with metallic Cu and Ag, (11) 297*d*.
Na_2O-SiO_2-Fe_2O_3 melts, diffusion at 1200°C, (11) 315*j*.
$Na_2O \cdot 2SiO_2$-SiO_2 glass, crystallization of, (11) 296*g*.
$NaFeO_2$, replacement of iron in, (6) 169*g*.
$NaH_3(SeO_3)_2$ and $NaD_3(SeO_3)_2$ single crystals, dielectric properties of, (5) 135*d*.
NaOH, reactions of reactor-irradiated uranium monocarbide with water and, (3) 68*h*.
$NaNb_{13}O_{33}$, crystal structure and geometrical principles of homologous series $NaM_3^{+1}O_{9n}^{-2}$, (2) 49*a*.
Na_2O-GeO_2 glasses, acoustic spectra of, (4) 92*a*.
Na_2WO_4, relation of conductivity to electrical conductivity of rhenium trioxide, (9) 254*f*.
-strontium niobates, dielectric properties and phase transitions of ferroelectric, (8) 219*i*.
sulfate, behavior in melts and its decomposition products, (4) 94*d*.
refining soda-lime-silica glass with, (3) 62*c*.
and NaCl, effect on solubility and hydration of anhydrite and gypsum, (1) 2*h*.
systems. See *Systems*.
thermal and chemical decomposition of and material exchange between silicate glass melts and atmospheres containing SO_3, (6) 148*c*.
sulfide, solutions to extract stibnite, (11) 312*c*.
systems. See *Systems*.
tetraborate, systems. See *Systems*.
titanates and vanadates, interactions in melts, (1) 22*j*.
tri-, hydroaluminate, (5) 140*d*.
in U ores, flame-photometric determination, (2) 44*g*.
vermiculite, thermodynamics of interlayer adsorption of water in, (4) 114*c*.
zeolite, new synthetic crystalline alumino-silicate, (6) 164*j*.
Soils, bulk density, method to measure, (6) 162*g*.
mineral, physics of frost heaving of, B (7) 204*g*.
plastic limit of, (11) 300*a*.
plasticity, limit explained, (11) 300*a*.
shear strength, relation between liquid limit and, (3) 85*a*.
Spanish, clay minerals and fraction of surface layer, (9) 247*b*.
sulfate in, means to determine, (9) 245*f*.
Soldering. See also *Seals and sealing*.
fixture, platen for, P (10) 274*h*.
method, filler alloy, and flux, P (9) 232*b*.
Solidification, of dehydrated phosphoric acids, (7) 202*j*.
Solids, brittle, fracture of, (3) 81*j*–82*c*.
crystalline, relation between density and defect chemistry of, (9) 254*f*.
deformation and fracture of, B (9) 259*e*.
of different sizes, perfect mixtures mathematically defined, (5) 141*c*.
at high temperature, mechanical properties of, (11) 301*a*.
inorganic, color and constitution of, (3) 80*e*.

Solids (*continued*)
ionic, mass transport and sintering in impure, (8) 226*i*.
mechanical properties of, B (5) 142*h*.
moisture in, how to measure, (10) 281*c*.
particulate, method and apparatus to subdivide, P (2) 47*h*.
reactivity, effect of defect structure on reactivity of, (11) 315*j*.
substances, reactions of mixtures of, B (9) 259*j*.
thermal properties, transient methods to measure, (4) 108*a*.
Solid solutions. See *Solutions, solid*.
Solid state, devices, history and applications, (7) 192*g*.
devices, using metal between two semiconductor materials, P (7) 194*b*.
reaction equations, numerical data for common, (8) 226*a*.
reactions, between MnO_2 or Mn_2O_3 and the oxides of CaO, ZnO, MgO, or CdO, (2) 52*a*.
calculation of activation energy for polydisperse mixtures, (10) 283*i*.
determination of extent in formation of strontium titanate and zirconate by, (2) 49*g*.
formation of $NiAl_2O_4$ by, (5) 136*j*.
surface activity in, (3) 79*f*.
in system Fe-W-C, preparation of (Fe, W)$_3C_2$ type double carbide, (2) 51*e*.
reactivity, and glass crystallization behavior of alkali aluminogermanates, (4) 95*h*.
Solubility, citric, of Japanese phosphate rocks, (9) 247*c*.
of He, in glass melts, (9) 234*e*.
hydrothermal, of Al_2O_3 in $Na_2B_4O_7$ solution, (3) 82*b*.
hydrothermal, and growth of sphalerite, (3) 82*c*.
mutual, of disilicides of transition metals from groups IV, V, and VI, (9) 252*j*.
of N, in steel slags, (10) 290*b*.
of O and N, in uranium carbide, B (6) 171*j*.
physical, of gases in fused silica, (10) 265*j*.
physical and chemical, of N in glass melts, (10) 265*j*.
of solid inorganic materials, effect of chemical bond on, (1) 22*g*.
of U, in uranium-monocarbide, B (6) 171*i*.
in water, dissolving process for powder mixtures, (5) 141*d*.
of water, effects of O fugacity and water content on crystallization in mafic magmas, (7) 202*b*.
of water vapor, in alkali borate melts, (10) 266*h*.
Solutions, dis-, chemical, in study of soil clays, (2) 48*f*.
of disperse SiO_2 in $Na_2O \cdot 2B_2O_3$ melt, (10) 284*h*.
of irradiated substances, physical and chemical processes accompanying, (1) 24*f*.
kinetics of some fluoberyllate glasses in water, (6) 148*d*.
kinetics in viscous systems where diffusion and free convection are rate controlling, (6) 147*f*.
mechanism for metallic iron in molten glass, (4) 94*g*.
of silica in CaO-Al_2O_3-SiO_2 melt, (4) 93*b*.
of silica schlieren in glass by diffusion and flow, (8) 209*d*.
Solutions, solid. See also *Equilibrium studies*.
of carbonates of Fe and Mn, products of thermal dissociation of, (1) 23*b*.
$CoAl_2O_4$-$MgAl_2O_4$, stability of $MgAl_2O_4$ from measurements in, (3) 86*b*.
Co_2SiO_4-Fe_2SiO_4 at 1180°C, activity-composition relations in, (7) 197*b*.
existence, between mono- and di-calcium ferrites, (1) 13*h*.
ferrite, formation by precipitation, (9) 253*g*.
Fe-C, thermodynamics of dilute, (5) 141*i*.
of FeO in MgO, magnetic susceptibility of, (4) 112*j*.
$Fe_{1-x}O$-MgO, electrical conductivity in, (3) 81*a*.
formation of magnesium ferrites in $MgCO_3$-$FeCO_3$, (6) 167*e*.
formation in metals, B (7) 204*d*.
growth of crystals and magnetic properties of β-Mn_2O_3, (11) 317*f*.
$Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$, piezoelectric properties of, (1) 13*h*.
metastable, B (6) 171*f*.
metastable, with quartz-type structures on the join SiO_2-$MgAl_2O_4$, (3) 83*e*.
model, based on nearest-neighbor interactions which involve both central and linked-central forces, (11) 314*a*.
NiO-Li_2O, (10) 288*i*.
$NaNaO_3$-$KNbO_3$, polarization of, (1) 24*i*.
of $SrTiO_3$ with $SrZrO_3$, formation conditions and electrical properties, (5) 134*c*.
in system Ba(Ti,Zr,Sn)O_3, ferroelectric properties of, (4) 111*j*.
in system MnO-ZnO, their possibility as pigments, (2) 51*d*.
systems with, effect of displacement of equilibrium on fusibility diagrams of, (9) 249*c*.
ZrO_2-Y_2O_3, (5) 139*d*.
Sonics, cutting, limits and possibilities for silicates, (7) 195*c*.
to evaluate stopper heads, (8) 216*g*.
hyper-, air-breathing engine, ceramics in, B (11) 320*h*.
hyper-, speeds, sublimation of graphite at, (4) 99*f*.
method, to determine fracture velocity in glass, (7) 179*f*.
testing, of steel ladle nozzles, (2) 37*b*.
and ultra-, frequency ranges, device to investigate properties of ferrite parts in, (1) 13*g*.
ultra-, attenuation in insulators at room temperature, (8) 220*h*.
to determine quality of Korvisit blocks, (11) 300*i*.
for enriching quartz sands, (2) 47*a*.
microwave, (5) 128*c*.

Sonics, ultra-, (*continued*)
research on elimination of stress in glass by, (4) 95*d*.
testing of porcelain for cracks, (2) 40*e*.
wave propagation velocity in ferrite and elastic constant, (11) 305*i*.
waves, hydrophone to detect, P (8) 221*d*.
Sorption. See also *Absorption; Adsorption*.
of B, by clay minerals, (3) 85*b*.
in sedimentary zeolites, (5) 141*a*.
silver ion, properties of glass surfaces, (5) 121*d*.
of water, by cement, (10) 262*d*.
Sound, velocities of polycrystalline alumina, pressure derivatives of, (5) 140*c*.
waves, absorption in dielectric crystals, (2) 48*e*.
Space, aero-, current and future materials for, (2) 54*f*.
materials for, (4) 114*i*.
whisker materials for, (11) 295*e*.
environment, effect on materials, (2) 54*f*.
stations, materials for, (5) 133*d*.
Spacecraft, aircraft, new materials applications for, (4) 108*i*.
rocket, ablation cooled nozzle for, P (5) 125*g*.
rocket nozzle, composition, P (9) 241*d*.
fiber reinforced, (2) 30*b*.
method to form from refractory metal, P (4) 91*i*.
Spalling. See also *Refractories*.
of enamels, spontaneous, (5) 119*j*.
Spark plugs, with conical seat sealing washer, P (4) 106*a*.
high temperature, P (4) 105*b*.
with insulator nose spaced from center electrode, P (8) 222*c*.
with multiple conductive seals, P (11) 308*e*.
plant, description of Mexican, (4) 102*i*.
seal for, P (7) 194*c*.
and seal for, P (4) 106*c*.
with visual indicating discharge bulb, P (6) 161*c*.
Specific gravity. See *Density*.
Spectra, absorption, visible region of rare-earth minerals, (3) 87*c*.
absorption and fluorescence, of Mn in glass, (3) 60*d*.
acoustic, effect of OH content in B_2O_3 glass, (4) 93*b*.
acoustic, of Na_2O-GeO_2 glasses, (4) 92*a*.
excitation, of ZnS phosphors, theoretical analysis, experimental results, and low temperature effects, (11) 316*d*.
infrared, change in clay minerals by dehydration, (5) 134*h*.
of 2CaO·Fe_2O_3 and 2CaO(Al, Fe)$_2O_3$, (2) 50*i*.
of compounds in 15 to 35 and 15 to 200μ regions, (1) 22*a*.
of hydrated borates, (8) 226*g*.
interpretation of α-quartz in the 3μ region on basis of modes due to impurities, (9) 251*d*.
of lanthanide oxyorthosilicates, (5) 137*c*.
infrared absorption, of Ce^{3+} ions in glass, (3) 61*i*.
change by dehydration and rehydration of clay minerals, (5) 134*f*.
of clay minerals and mica type structures, (6) 168*e*.
of dicalcium silicate, (1) 22*j*.
of magnesium hydride, (3) 82*f*.
of orthosilicates of divalent elements, (10) 286*j*.
of silicon dioxide, (1) 22*a*.
study of Indian clays, (3) 84*d*.
magnetic, of nickel-zinc ferrites at different temperatures, (11) 318*a*.
Moessbauer, of some spinel oxides containing iron, (5) 138*g*.
optical, of V, in $Na_2O \cdot 2SiO_2$ glass, (1) 4*j*.
Raman scattering, of barium orthotitanate, (2) 51*j*.
reflection, in infrared region in Na_2O-ZrO_2-SiO_2 glasses, (1) 4*i*.
uniaxial stress, in MgO, (3) 87*j*.
vibrational, of glassy oxides containing nitrogen in solution, (1) 6*a*.
visible and infrared absorption, of uranium dioxide, (2) 53*i*.
Spectrochemical analysis. See *Analysis*.
Spectrography, to determine tin in low-grade tin ores, (11) 310*e*.
of glass, ancient and technical, (2) 28*c*.
grating and Littrow type, determination of yttrium by, (4) 107*g*.
infrared, of Spanish clay, (9) 250*j*.
spark-source mass, analysis of TiO_2 pigment by, (10) 280*g*.
X-ray emission, quantitative analysis by, (2) 45*f*.
Spectrometer, liquid scintillation, detection chamber with tray for supporting sample containers, P (11) 311*e*.
mass, design for vacuum analysis, (9) 245*j*.
as flowmeter for vacuum processes, (9) 245*j*.
survey, (10) 281*e*.
omegatron mass, to measure residual argon partial pressure changes, (10) 281*a*.
Spectrometry, determination, of Th with 8-quinolinol, (5) 131*h*.
emission, to describe high-voltage spark discharge, (2) 44*e*.
mass, of Cr and Fe at high temperatures, (9) 251*h-i*.
mass, to determine age of radiogenic minerals, (11) 317*e*.
using cryosorption pumping, quantitative spark source mass, (2) 45*g*.
Spectrophotometers. See also *Photometers*.
to determine, optical constants in vacuum ultraviolet region, (4) 107*h*.
standard, to measure heterogeneity of glass, (1) 4*f*.
Spectrophotometry. See also *Photometry*.
determination, of iron in silicates, (2) 44*b*.

Spectrophotometry (*continued*)
differential, to determine B with diaminochrysazin, (3) 75*d*.
radiometric, to determine microgram amounts of Nb in rocks and minerals, (2) 45*i*.
Spectroscopy, atomic absorption, to determine Mg in silicates, (11) 309*f*.
infrared, of dehydration of montmorillonite and saponite, (1) 22*b*.
effect of P in SiO_2 shown by, (10) 285*g*.
of structure of films applied on glass by aerosol method, (6) 148*a*.
X-ray, emission-, using ^{147}Pm beta ray source to measure plating thickness, (11) 310*h*.
fluorescence, of glass, (6) 146*j*.
new apparatus for, (4) 107*f*.
Sphalerite, flotation of, P (5) 133*d*.
growth, and hydrothermal solubility of, (3) 82*c*.
wurtzite inversion, *p-T* dependence in ZnS, (6) 169*i*.
Spheres, apparatus to produce, P (4) 107*b*.
from fusible particles, apparatus to make, P (4) 96*i*.
hollow, as design tool, (4) 108*j*.
hollow, of oxides, P (11) 303*f*.
micro-, preparation of thoria and mixed-oxide, (10) 272*f*.
packed, mercury porosimetry breakthrough pressure for penetration between, (4) 112*b*.
Spinel. See also *Refractories*.
with cation vacancies, preparation, (7) 202*i*.
Cr^{3+} ions in, Jahn-Teller distortion induced by, (10) 287*a*.
fine-grain high-power, microwave characteristics of, (9) 252*e*.
formation, by thermal transformation of cronstedtite, (7) 199*h*.
formation process, factors affecting reactivity of semiconducting oxides during, (11) 316*c*.
$LiCuVO_4$, antiferromagnetism of, (11) 313*c*.
from MgO-Al_2O_3 solid solutions, mechanism of precipitation of, (5) 138*a*.
magnetic, site preference of Ge^{4+} in, (5) 140*h*.
$MnGa_2O_4$, antiferromagnetism of, (11) 313*d*.
with only A-A interactions, magnetic properties of normal, B (2) 55*j*.
oxide, containing Co and Mn, distortion of, (10) 291*a*.
oxides, Moessbauer spectra of some containing iron, (5) 138*g*.
O deficient, in Li-Mn-O system, (5) 139*g*.
-phenacite, transition in $LiAlGeO_4$, (10) 289*b*.
preparation and mechanical properties of, B (11) 320*f*.
structure, Fe^{2+} ions in, (10) 289*a*.
structure, phase transitions in crystals with, (5) 139*f*.
tetragonally deformed, DTA of, (2) 49*b*.
Spodumene, crystal growth of β-, (6) 166*a*.
thermal transformation and crystallography of, (3) 87*e*.
Spraying. See also *Atomization*.
apparatus, for electrostatic coating, P (1) 3*h*.
for liquid, P (5) 131*b*.
method to break up agglomerated particles in, P (6) 161*g*.
electrostatic. See also *Electrostatic processes*.
new principles for enamel, (5) 119*j*.
reduces enamel overspray, (8) 207*i*.
of enamel, factors and equipment in, (7) 178*i*.
flame, clad powder of refractory and Ni or Co for, P (8) 208*c*.
guns and techniques, (2) 30*e*.
method to form bodies, (5) 130*f*.
methods for coatings, (6) 145*g*.
and plasma, review, (2) 30*f*.
torch for, P (8) 208*d*.
gun, with vent for material and air, P (5) 131*b*.
plasma, variables in, (8) 208*e*.
Sputtering, cathodic, for selective removal of material, P (11) 307*d*.
Stability, of biotite, experiment, theory, and application, (9) 256*h*.
chemical and thermal, of nitrides of group III elements, (1) 19*h*.
effects, in MOS enhancement transistors, (3) 72*c*.
in-, of complex compounds, influence of ionic forces on constants of, (5) 137*i*.
of Ni_2TiO_4, (7) 202*d*.
radiation-optical, of quartz glass at different temperatures of γ ray irradiation, (8) 210*i*.
thermal, of pentachloroxyniobates, interaction with niobium oxychloride, (11) 317*f*.
of K_2TaF_7, (1) 23*h*.
of zoisite, (1) 25*b*.
of zircon, in range of 1180° to 1366°C, (1) 25*d*.
Stabilization, Fermi level, at semiconductor surfaces, (10) 286*f*.
Staining, colors, for bodies and glazes, (3) 71*c*.
Stannic oxide. See *Tin, oxide*.
Statistical analysis. See *Analysis*.
Steam. See also *Moisture; Water*.
atmospheres, operation of nickel-graphite compositions in at industrial parameters, (11) 313*h*.
cure, of siloxane-coated glass containers, (10) 266*h*.
moistening, of clays, (2) 35*i*.
pressing, in structural clay products industry, (2) 35*f*.
for structural clay products, generation and use, (2) 35*b*.
Steatite. See also *Talc*.
insulators, (9) 241*i*.
manufacture, problems of, (4) 102*g*.
Steels. See also *Enameling metals; Iron*.
bathtubs, manufacture of two-piece, (6) 145*j*.
-clad refractories, behavior of claddings in regard to temperature requirements in oxidizing atmospheres, (8) 214*i*.
cold forming, dry film lubricants for, (4) 91*f*.
Steels (*continued*)
decarburized, direct-on enameling of, (7) 178*g*.
deoxidized, composition and method, P (11) 295*g*.
determination of nonmetallic compounds in, B (11) 319*h*.
enamel adhesion on, factors affecting, (6) 145*d*.
enameled, as joint for glazed lightweight concrete, P (8) 208*c*.
flux to treat, means and method, P (9) 232*a*.
heat resistant, for glass pressing molds, (4) 95*i*.
high Mn, high alumina brick used as ladle lining with, (4) 99*c*.
high Mn, high aluminous nozzle for, (1) 9*d*.
making, conference on, B (3) 88*j*.
processes, lining performance in, (3) 69*d*.
progress in refractories for, (5) 125*j*.
melt, effect of slag as barrier against N pickup in, (10) 290*b*.
melting furnaces, basic linings in Sweden, (3) 69*f*.
microstructure of, B (6) 173*h*.
molten, refractory problems arising from vacuum treatment of, (9) 239*f*.
molten, relation of temperature to life of ladle brick, (1) 10*a*.
nonmetallic inclusions, corrosion of, (10) 271*e*.
oxide inclusions, origin of, (1) 10*b*.
pipes, glass coatings on inside, (1) 3*e*.
rare earth in, spectrographic determination of, (4) 107*g*.
sheet, effect of vapor in furnace on enameling of, (9) 231*i*.
sheet, reaction with enamels, (11) 295*f*.
stainless, method and composition for cleaning, P (9) 232*d*.
stainless, reflection of X rays by surface, (3) 85*i*.
wear of sapphire on, mechanisms in, (5) 119*g*.
Stereochemistry, of compounds, of Cu and V with anomalous magnetic properties, (4) 113*d*.
Stibnite, extraction, with sodium sulfide solutions, (11) 312*c*.
Stoichiometry, of MgO-Mn_2O, solid solutions in air at high temperature, (11) 319*b*.
of tricalcium silicate, (9) 256*c*.
Stones. See also *Gems; Rocks*.
porous, method to measure bulk density of, (6) 162*g*.
pottery, alteration of rocks to in Japan, (1) 18*f*.
pottery, mineralogy of Izumiyama, (1) 18*g*.
in window glass, microscopic identification, (3) 61*d*.
Stoneware, British, award winning, (10) 261*i*.
chemical, development, manufacture, and use, (2) 39*c*.
industry, dust extraction in, (10) 275*g*.
pipe, most modern plant in Europe, (1) 7*e*; (6) 151*d*.
shapes, of basalt, (8) 214*d*.
tile, pressing, (3) 71*e*.
vases, oxblood glazes for, (10) 275*i*.
vessels, buckling of flat-bottomed, discussion and reply, (2) 40*a*.
Storage, bulk, bottom discharge hopper with agitator, P (3) 78*f*.
of cement, method for bulk, (1) 2*c*.
of heat, novel method, (6) 163*i*.
long-term, conversion of irradiated fuel swarf for, (1) 8*i*.
Strains, effect, on producing hackle in glass plate, (2) 31*h*.
formulas for, B (9) 258*c*.
limit, determination of that proportional to stress limit by direct readout, (3) 75*i*.
measurement, at Si-SiO_2 interface, (9) 252*b*.
mechanical, effect of permanent on glass sheet, (4) 93*b*.
rate, effects on tensile properties of graphite tested in helium and in vacuum, (4) 110*i*.
in thin metal films on quartz, (9) 256*e*.
torsional, and its interpretation in plastic clay, (1) 13*b*.
zirconium silicate, for glazes, P (9) 242*c*.
Strength, of abrasive grains, changed by heat treatment, (5) 117*f*.
of alumina compacts, partly sintered, (6) 170*d*.
of brickwork cube, (10) 270*c*.
of cement, development at 20°, 5°, and 1°C, (1) 2*f*.
method to predetermine 28-day in 5 hours, (4) 90*h*.
pressing method to test, (2) 29*c*.
of cermets, estimate for complex stressed state, (1) 8*g*.
of chromium carbide hard alloys, (10) 272*d*.
of concrete, means to calculate, (9) 230*g*.
ring test for tensile, (3) 59*f*.
under biaxial compression, (2) 29*i*.
of cross sections of specimens, effect of pore distribution on, (11) 316*d*.
crushing, of rocks, methods to determine, (2) 45*f*.
electrical and mechanical, interrelation in corundum, (1) 23*a*.
of engineering materials, B (6) 174*i*.
fatigue, temperature dependence of sintered alumina bodies, (2) 40*c*.
of fibers, coated with alumino borosilicate glass, (10) 266*j*.
of flame-polished sapphire crystals, (7) 202*g*.
fracture, of glass, (8) 209*h*.
of fused quartz, in water vapor, (2) 51*f*.
of glass, fibers, change during aging, (6) 147*c*.
fibers, relation to melt treatment, (4) 95*d*.
ground and polished, (10) 266*j*.
pipes, calculation for those laid in ground, (4) 92*e*.
relation to structure, (5) 121*g*.
spheres, (7) 181*i*.
of glass sheet, coating to improve, (6) 146*i*.
improved by etching, (7) 181*i*.
method to determine, (5) 121*d*.
method to measure, (4) 94*j*.
Strength (*continued*)
grain, of abrasive powders, (5) 117*g*.
high, of glass fiber, possible causes of, (7) 181*c*.
of glass and quartz fibers at −196° in liquid N, (8) 209*b*.
mechanical, chrome ore-containing brick of, (11) 300*i*.
improvement, for hard porcelain, (3) 71*d*.
of laminated materials, (8) 224*b*.
long-term, of chromium carbide alloys, (3) 68*d*.
of masonry, effect of absorptive capacity of brick on bearing, (10) 270*d*.
mechanical, of cement and concrete, (6) 144*f*.
development in refractories during drying, (9) 238*a*.
of enameled ware, (11) 295*i*.
methods to increase in glass, (9) 234*c*.
of porcelain and nondestructive determination of, (11) 304*c*.
new, with whiskers, (6) 171*c*.
reduction in glass, following mechanical surface damage, (7) 181*g*.
of rocks, indentation method to test, (7) 195*e*.
shear, of serpentinized dunite, (11) 317*i*.
of specimens, containing parallel round holes, (9) 246*d*.
strengthening, chemical, of polycrystalline ceramics, (7) 197*i*.
strengthening, means for holes in filament wound structures, (2) 40*g*.
of structural clay products, increasing, (6) 151*f*.
of tempered glass, relation to fracture mirror size, (1) 5*h*.
tensile, of tungsten carbide/cobalt alloys in compression, (10) 272*i*.
tensile bond, test for masonry mortars, (11) 300*b*.
tension, of vitreous enamels, (5) 119*g*.
theoretical, of glass, effect of composition on, (10) 264*b*.
theoretical and technical, of glass calculated from acoustic-dilatometric measurements, (6) 147*a*.
Stresses, analysis problems, transparent polyurethane rubber as model, (2) 44*a*.
anisotropy, in silicon oxide films, (2) 51*h*.
applied, effect on graphitization of pyrolytic graphite, (5) 135*j*.
combined and reversed, theoretical distortion of aggregate under, (1) 25*i*.
compressive, effect on creep of sintered alumina, (2) 39*c*.
development, in plastics with embedded glass fibers, (6) 148*j*.
distribution, at edge of equilibrium crack, (1) 25*f*.
distribution, photoelastic observation in single crystal alumina, (10) 289*b*.
effect, of coatings on rotating and stationary substrates, (10) 276*h*.
on imperfection of silicide layers on Mo, (11) 295*d*.
on producing hackle in glass plate, (2) 31*h*.
formulas for, B (9) 258*c*.
in glass, opticopolarization measurement, (8) 210*h*.
research on elimination by ultrasonics, (4) 95*d*.
surface, (7) 181*j*.
homogeneous, to reduce crystallographic point groups to subgroups, (1) 24*f*.
homogeneous, splitting of crystals under, (3) 85*i*.
internal, in ceramics containing cristobalite, (10) 287*e*.
internal, effect on rigidity of large glass lenses and telescope mirrors, (2) 31*g*.
limit, determination of that proportional to strain limit by direct readout, (3) 75*i*.
measurements, in tempered glass plates by scattered light method with laser source, (3) 62*g*.
normal and shearing, durability of SiC under, (10) 285*b*.
-optical, investigations of plastic layers, (3) 62*h*.
optical studies, on opaque glass at wavelengths between 1 and 3μ, (8) 211*d*.
permissible, determination in heavy clay bodies as basis for rapid firing, (11) 299*j*.
resistance, of refractories at high temperature, (2) 37*b*.
resolution, in single-crystal deformation, (8) 227*j*.
in rock and concrete, determination of, (4) 108*j*.
tensile, in change of refraction of glasses, (2) 31*a*.
tensile, effect on weakening glass fibers during heat treatment, (2) 31*h*.
thermal, effects in enameled cast iron, (10) 263*e*.
of a nozzle, (6) 154*d*.
relation to coating failure on turbine blades, (10) 263*c*.
torsional, softening of refractories under, (10) 272*c*.
Strontium, Ba, Na, and K, fusibility diagram of system of the fluorides of, (4) 111*f*.
barium ferrites, effect of texture on magnetic properties of mixed, (11) 317*d*.
and barium ferrites, properties of mixed, (10) 290*c*.
barium titanate, ferroelectric properties of, (4) 111*a*.
and Ca, chromotographic separation by elution of ammonium sulfate solution, (2) 43*j*.
carbonate, systems. See *Systems*.
on clay minerals, exchange adsorption of, (1) 21*i*.
-La manganites, magnetic properties of, (4) 112*i*.
oxide, electrical conductivity of, (5) 135*d*.
reactions of, (9) 254*b*.
substituted soda-lime-silica glass, properties of, (4) 95*i*.
systems. See *Systems*.
selenide, thermodynamic properties of, (9) 257*e*.
Sr_2MgReO_6, relation of conductivity to electrical conductivity of rhenium trioxide, (9) 254*f*.
systems. See *Systems*.
and Ta, crystallography of double oxide of, (6) 166*h*.

Strontium (*continued*)
titanate, dislocation dependence of cationic diffusion in, (11) 315*g*.
etching and chemical polishing of, (3) 81*g*.
formation reaction kinetics of, (10) 287*a*.
with $SrZrO_3$, formation conditions and electrical properties of solid solutions of, (5) 134*c*.
and zirconate, determination of extent of reaction in formation by solid state reaction, (2) 49*g*.
titanyl oxalates, thermal analysis of, (1) 25*j*.
trisoxalatoferrates(III) thermal decomposition of, (7) 203*d*.

Structural clay products. See also *Brick; Pipe; Tile.*
block, palletizing method to assemble, P (8) 214*e*.
stacking apparatus, P (9) 237*h-f*.
stacking method, P (9) 237*f*.
brick, effect of weathering on rate of water absorption, (7) 184*j*.
brickwork, development of standard crushing test for, (7) 185*a*.
building blocks, interlocking with metal channels, P (5) 124*h*.
heavy bodies, automatic equipment for storage, transport and mixing, (1) 7*f*.
heavy bodies, calculation of permissible content of soluble sulfates in, (2) 35*j*.
increasing strength of, (6) 151*f*.
light weight, P (11) 300*f*.
limestone inclusions, elimination of harmful effect of, (6) 151*d*.
mechanical handling apparatus, P (3) 65*d*.
mixes, of dry-press consistency, comparison of compaction methods for, (2) 35*i*.
preheating, increases kiln output, (4) 98*e*.
preparation, steam for, (2) 35*b*.
from rotary table press, quality of, (11) 308*g*.
wages, in Common Market, (1) 7*h*.
wall panel, external, P (7) 185*b*.
wall sections, brick and concrete and molds to produce, P (8) 214*g*.
wall units of, P (11) 300*g*.
yearbook 1965, B (3) 88*c*.

Structural clay products industry, Australian plant described, (4) 98*e*.
automation in, (6) 151*c*.
automation, of material flow, (2) 35*d*.
firing, 1950–1964, (5) 125*f*.
granulators in, (8) 213*e*.
pipe plant, new Illinois, (8) 214*f*.
South American plant, major renovation, (4) 98*i*.
steam pressing in, (2) 35*j*.
stoneware pipe, most modern plant in Europe, (1) 7*e*.
tile, production of South American plant, (4) 98*i*.
X-ray fluorescence analysis in, (5) 132*a*.

Structure, of AX and AX_2 compounds, derivation of close-packed, sequence of equal layers, (7) 203*a*.
of barium titanate, compounds with, (6) 165*f*.
change, in cupola refractory, (10) 272*f*.
close-packed, condensed way to represent, (7) 197*j*.
of crystals. See *Crystals*.
defects, of α-Nb_2O_5, (9) 256*h*.
in natural diamond, X-ray topographic study of planar growth, (2) 54*d*.
in synthetic quartz, (7) 198*g*.
of Y_2O_3, (9) 249*d*.
of engineering materials, B (6) 174*i*.
of glass, orientation induced in melts, (10) 265*e*.
investigations, by electron microscope, ultrathin glass sections for, (7) 182*b*.
magnetic, of $CaMnSiO_4$, (5) 138*d*.
micro-, of ceramics, B (5) 142*i*.
and macro-, stabilization in optical glass, (11) 297*i*.
of porcelain insulators determined by electron microscope, (11) 304*d*.
perovskite type, ferroelectric chloride of, (1) 21*a*.

Substrates, advances in applying circuitry to, (10) 276*h*.
crystallization on, work of formation of crystal nuclei, (3) 80*i*.
effects, of films of spray deposited CdS, (9) 242*h*.
with gold films, and methods of making, P (4) 106*d*.
rotating and stationary, angle-of-incidence and stress effects on, (10) 276*h*.
surface warp, optical method to determine, (3) 76*e*.
for Ta thin-film circuits, (9) 242*e*.

Sulfates, alkali, corrosion of magnesite regenerator brick by, (10) 271*c*.
content, means to determine, (4) 107*d*.
deposits in Lithuania, composition and importance of Permian, (11) 314*g*.
expansion and autoclave expansion, of cement, (11) 294*e*.
ferric, low-cost regeneration of etch baths of, (4) 91*i*.
ferrous, control in nickel tank with barium peroxide, (6) 145*c*.
role, in melting and fining of glass batch, (6) 148*g*.
in soils and metals, means to determine, (9) 245*f*.
soluble, calculation of permissible content in heavy clay bodies, (2) 35*j*.
solutions, effect on cement mortars up to 80°C, (1) 2*j*.
solutions, effect on portland cement, (9) 230*j*.

Sulfur, -carbon, amber glass, (3) 60*g*.
in enamels, (3) 59*h*.
interaction, with aluminum antimonide, (9) 251*c*.
low content, determination in glass, (3) 60*h*.
oxide, corrosion of magnesite regenerator brick by, (10) 271*c*.
systems. See *Systems*.
trioxide, means to determine in gypsum and portland cement, (4) 90*f*.
trioxide, solubility in sodium silicate melts, (10) 265*j*.

Sulfuric acid, manganese dioxide-, oxidation of molybdenite, (5) 138*g*.

Sungulite, nature of, B (2) 56*g*.

Surface, analyses, electron probe X-ray microanalyzer for, (10) 280*i*.
area, BET apparatus to determine for minerals, (5) 136*d*.
determination for clay by DTA, (7) 198*a*.
variation during thermal decomposition of solids, (2) 53*f*.
calculations, tables for semiconductor, (10) 277*j*.
finish, instrument to measure, (9) 245*d*.
of glass, studied by electrostatic charges, (10) 266*f*.
of metals, kinetics, thermodynamics, energy, diffusion, and growth by dissolution and evaporation processes, B (7) 204*d*.
properties, of manganese dioxides, effect of crystal structure on, (9) 249*a*.
rough, vacuum sealing of, (10) 277*d*.
solid, activity of, (3) 79*f*.
stress dependent surface reactions and strength, B (2) 55*h*.
structure, of vertically drawn sheet glass, (4) 95*h*.
temperature, measuring techniques for, (5) 131*j*; (8) 224*b*.

Surveying, quarry walls, method, (2) 47*f*.

Suspensions. See also *Slips*.
china clay, factors influencing dilation, (7) 190*g*.
and emulsions, method to examine separation of, P (6) 163*b*.
glass-frit and quartz, properties of, (6) 146*d*.
glaze, segregation during application and defects from, (6) 156*i*.
sedimenting, thermal stability to measure particle size distributions, (2) 45*c*.

Swelling. See *Expansion*.

Switches, with glass sleeve, P (11) 297*d*.

Symposiums, at British atomic energy establishment, B (6) 171*j*-172*b*.
on electrical power generation, B (6) 172*j*.
on fuel and power in glass industry, (11) 297*e*.
on glass in electronics, (11) 297*e*.
international, on contact of hot glass with metal, B (2) 55*c*.
on material sciences, B (7) 204*e*.
on metals, B (6) 171*f*.
special ceramics 1964, B (11) 320*e*.
of surface chemistry, Swedish, B (7) 204*e*.
on thermodynamics of nuclear materials, B (6) 175*d-g*.

Synthesis, of barium zirconylcarbonate, and production of barium zirconate, (10) 291*d*.
of B_2O, analogs, high pressure, high temperature, (1) 21*h*.
of Ca_3SiO_4 modifications, and determination of X-ray powder diffraction patterns, (2) 29*a*.
of clays, in English granites, factors bearing on natural, (5) 133*i*.
diamond, by electric discharge shock, (4) 110*f*.
of dolomite, crystal particularities in, (3) 80*a*.
hydrothermal, of aluminosilicates with three-dimensional framework, (2) 51*h*.
hydrothermal, of trigonal silicates and germanates of zinc, B (11) 320*d*.
mineral, by hydrothermal technique, (11) 318*b*.
of mullite, by flame fusion technique, (4) 99*f*.
of mullite spinel, and study of its properties, (9) 257*c*.
of a new mica, $KMg_{3.5}[Si_4O_{10}]D(OH)_2$, (6) 170*j*.
and physicochemical properties, of yttrium carbide, (4) 113*f*.
potassium peroxydicarbonate and study of its properties, (4) 113*e*.

Systems. See also *Equilibrium studies.*
alkali metal oxide-silica, metastable liquid immiscibility in, (3) 83*e*.
alkali-TiO_2, properties and structure of glasses in, reply to discussion, (1) 5*i*.
Al-CdSe-Se and Al-Sb_2Se_3-Se, xerographic layers in, (6) 167*d*.
M_2O-Al_2O_3-GeO_2, properties and structure of glasses in, (2) 32*j*.
Al_2O_3-SiO_2, decomposition of compounds in to determine alkali elements, (11) 309*j*.
Al_2O_3-SiO_2, investigations in, (5) 137*f*.
Al_2O_3-SiO_2, thermodynamic data for re-evaluation of formation of Al_2SiO_5 polymorphs and $Al_6Si_2O_{13}$, (1) 25*e*.
Al_2O_3-H_2O, hydrothermal investigations, (7) 200*i*.
Sb-Sb_2Se_3, in solid and liquid states, electrical conductivity and viscosity of melts in, (1) 21*a*.
Sb-Te, investigation in region of compound Sb_2Te_3 in solid and liquid states, (10) 287*f*.
As-Se, (2) 52*c*; (10) 284*d*.
$BaCO_3$-$SrCO_3$, $SrCO_3$-$CaCO_3$, and $BaCO_3$-$CaCO_3$, phase relations in, (2) 52*d*.
BaO-GeO_2, X-ray study of melts in, (2) 54*c*.
$Ba(Ti,Zr,Sn)O_3$, ferroelectric properties of solid solutions in, (4) 111*j*.
Be_3N_2-Si_3N_4, crystal structure of new modification of Be_3N_2, (3) 86*d*.
binary, relation between curves of the same property of, (9) 254*e*.
Bi_2O_3-SrO, electrical conductivity of, B (1) 26*c*.
Bi_2O_3-TiO_2-PbO, investigation of, (1) 23*b*.
Bi_2O_3-WO_3-PbO, investigation of, (1) 23*d*.
Bi_2O_3-V_2O_5-PbO, phase equilibria in, (11) 318*h*.
Bi_2Se_3-Sb_2Te_3 and Bi_2Te_3-Sb_2Se_3, electrical conductivity and thermal emf of solid solutions of, (11) 316*j*.
boron-metal, constitution of, (11) 318*d*.
B_2O_3-La_2O_3-ThO_2-Ta_2O_5-Nb_2O_5, in production of optical glass, (2) 32*d*.
$CaCO$-CO_2-H_2O, in two-phase region calcite + aqueous solution, (2) 52*h*.
$CaCO_3$-$MgCO_3$-$CoCO_3$ and $CaCO_3$-$MgCO_3$-$NiCO_3$, subsolidus phase relations in, (4) 113*b*.
CaO-Al_2O_3, in moisture-free atmosphere, (2) 48*j*.

Systems (*continued*)
CaO-silica gel-H_2O, long term study at 20°C, (2) 28*f*.
CaO-SiO_2-Al_2O_3-Fe_2O_3, effect of sodium oxide on formation and crystal structure of tricalcium silicate solid solution in, (5) 137*j*.
CaO-SiO_2-H_2O, under hydrothermal conditions, (2) 29*a*.
CaO-O_2-H_2O, DTA and quenching methods in, (11) 315*j*.
C_3A-$CaCO_3$-H_2O and C_4AF-$CaCO_3$-H_2O, reactions between, (2) 29*d*.
CeO_2-BeO, CeO_2-MgO, CeO_2-CaO, and CeO_2-SrO, transport numbers in, B (1) 26*c*.
CeO_2-La_2O_3, reduction of CeO_2 in and electrical conductivity of, B (1) 26*c*.
Cs_2O-Al_2O_3-$4SiO_2$-CsO-Fe_2O_3-$4SiO_2$-H_2O, phase relations and properties of synthetic pollucites in, (3) 86*b*.
of chlorides, of Pb, Li, Cd, (9) 257*g*.
of Li, K, and Ba, (5) 141*g*.
of Li, K, and Cd, (1) 25*i*.
of Li, K, and Pb, fusibility in, (11) 317*c*.
of Li, Na, and Ba, (10) 291*j*.
of Na, Cs, and Cd, (1) 25*i*.
$CoNb_2O_6$-$CoTa_2O_6$, phase relations in, (6) 169*e*.
CoO-SiO_2, phase relations in, (7) 202*e*.
Co-W-O, condensed phase relations in at high temperature, (6) 165*h*.
Cu-Fe-O, equilibrium relations in, (7) 199*i*.
CuO-Cu_2O-TiO_2, equilibrium relations in, (8) 226*b*.
CuO_2-MnO_2-FeO_2, phases in spinel region, (3) 84*j*.
feldspar-petalite-wollastonite, its use in bodies and glazes, (3) 86*e*.
of fluorides and chlorides, of K, Ca, and Ba, (9) 254*h*.
Gd_2O_3-Al_2O_3 and Sm_2O_3-Al_2O_3, (6) 170*h*.
Gd_2O_3-BeO, stable and metastable equilibrium relation in, (5) 141*j*.
$GaCl_3$-AlCl, fusibility diagram in, (1) 21*d*.
hafnium-carbon, (5) 136*g*.
ilmenite-hematite, magnetic properties at low temperature, (4) 112*g*.
$InCl_3$-In, interactions in, (11) 317*j*.
$InCl_3$-TlCl, fusibility diagram of, (1) 21*d*.
InSe, diagram of state of, (1) 20*j*.
In-Se, new data on phase diagram of, (10) 288*i*.
InI_3-CuI, (10) 291*e*.
Fe-Mn-Si-O, activities in olivine and pyroxenoid solid solutions of, (11) 313*d*.
Fe-W-C, solid state reactions in, preparation of $(Fe, W)_3C_3$ type double carbide, (2) 51*e*.
kaolinite-aluminum fluoride, thermogravimetric study of mullite formation in, (2) 53*e*.
kaolin-water, determination of structural and mechanical properties, (7) 198*a*.
La_2O_3-BeO, activity of BeO and BeO-rich melts in, (5) 141*h*.
lanthanum-tellurium, phase equilibria and crystal chemistry of, (5) 139*a*.
PbO-BaO-MgO-SiO_2, phase studies in subsidiary systems, (8) 211*j*.
PbO-B_2O_3 and PbO-SiO_2, nuclear magnetic resonance investigations of compounds and glasses in, (7) 201*f*.
lead oxide-lead selenide, (10) 291*f*.
PbO-SiO_2, investigation of compound in, (3) 87*e*.
PbO-TiO-ZrO, (4) 113*g*.
Li||F,Cl,Br, fusibility diagram of, (10) 286*b*.
Li-Mn-O, O deficient spinels in, (5) 139*g*.
Li_2CO_3-Li_2BO_3 and Na_2CO_3-$CaNaBO_3$, isomorphism between carbonates and borates, (3) 80*b*.
$LiClO_4$-$Ca(ClO_4)_2$ and $NaClO_4$-$Ca(ClO_4)_2$, fusibility diagrams in, (1) 21*f*.
Li_3F_2-BaF_2-Na_2Cl_2, fusibility in, (3) 82*d*.
Li_2O-Al_2O_3-TiO_2, crystallization in, (1) 5*i*.
Li_2O-MgO-Al_2O_3-SiO_2, effect of crystallization on properties of glasses in, (4) 93*h*.
Li_2O-SiO_2, glass formation in, (4) 93*c*.
M-W-O, equilibrium and stability of alkaline-earth tungstates in, (8) 226*a*.
$MgAl_2O_4$-Al_2O_3 and $MgAl_2O_4$-$LiAl_5O_8$, (3) 84*f*.
MgO-Al_2O_3-SiO_2-TiO_2, electrical properties of crystallized glasses in, (2) 31*j*.
MgO-Al_2O_3-ZrO_2-SiO_2, tetrahedra in, (9) 257*g*.
MgO-CO_2-H_2O, stability of carbonates in, (3) 85*j*.
MgO-Cr_2O_3-Al_2O_3-SiO_2, MgO-Cr_2O_3-Al_2O_3-TiO_2, and MgO-Cr_2O_3-Al_2O_3-ZrO_2, subsolidus structure of, (3) 86*j*.
MgO-FeO-Fe_2O_3, (2) 52*j*.
MgO-SiO_2 and MgO-Al_2O_3-SiO_2, (11) 318*e*.
MgO-ZrO_2, 1800°C to melting point, (7) 202*c*.
$MgSiO_3$-$CaMgSi_2O_6$-$CaFeSi_2O_6$-$FeSiO_3$, investigation of liquidus surface in, (3) 83*f*.
Mn-O_2-H_2O, stability relations at 25° and one atmosphere total pressure, (9) 256*a*.
Mn-Ta oxides, phase relations at 1200°C, (8) 226*j*.
MnO-ZnO, solid solutions their possibility as pigments, (2) 51*d*.
with many isometric components, ideality of, (10) 286*g*.
metallic, electrons in, B (9) 259*f*.
$MeTiO_3$-$MeWO_4(MoO_4)$, X-ray-phase analysis of, (3) 87*g*.
Mo-O, condensed-phase relations in, (6) 165*j*.
$MoCl_5$-$AlCl_3$-$FeCl_3$, fusibility diagram in, (10) 286*b*.
$MoCl_5$-MeCl, fusibility diagrams of, (10) 284*c*.
Mo-Si, W-Si, and Ta-Si, reaction diffusion in, (10) 290*d*.
multicomponent, chromatography to study, (1) 21*g*.
multicomponent reciprocal, method to determine degree of stable diagonals in, (1) 23*h*.
$NdCl_3$-Nd and $PrCl_3$-Pr, (10) 287*g*.
neodymium-tellurium, phase equilibria and crystal chemistry of, (5) 139*i-a*.

Systems (*continued*)
Ni-S, Seebeck coefficient in molten, (1) 19*d*.
Nb-H, observations on microstructure and superconductivity in, (7) 201*c*.
$NbCl_5$-NaCl-KCl, thermal analysis of melts in, (5) 141*i*.
$NbCl_5$-$ZrCl_4$-KCl, thermal and tensimetric study of, (1) 25*d*.
of niobium pentoxide, with oxides of common niobium alloying elements, (10) 283*h*.
-boric acid, phase equilibria in, (8) 226*b*.
-germanium dioxide, phase equilibria in, (8) 226*c*.
-WO_3, multiple phase formation, (6) 168*f*–169*a*.
of oxides of Sc and Si, phase diagram of, (5) 139*h*.
K_2SO_4-Li_2SO_4-Cs_2SO_4 and Li_2SO_4-Rb_2SO_4-$PbSO_4$, (10) 291*j*.
of pyrophosphates of Li and K and NaF, fusibility diagram of, (1) 21*e*.
quaternary reciprocal, of fluorides, bromides, and carbonates of Na and K, (1) 24*b*.
rare earth oxide-boric oxide, liquid immiscibility in, (10) 287*f*.
reciprocal, of bromides and nitrates of Na and Ba, (10) 291*i*.
of chlorides and bromides of Li and Tl, (10) 290*e*.
of chlorides and sulfates of Li and Ni, (2) 53*d*.
fusibility diagram of chlorides and bromides of K and Cd, (5) 136*c*.
of nitrates and chlorides of Li and Ba, (9) 254*c*.
of pyrophosphates and fluorides of Na and K, (10) 290*f*.
RbCl-$CrCl_3$ and CsCl-$CrCl_3$, fusibility diagrams of, (11) 317*c*.
Rb_2SiO_3-SiO_2, phase diagram of, (10) 289*j*.
samarium trichloride-potassium chloride, thermographic and calorimetric study of, (9) 257*f*.
selenide and telluride, of Nb and Ta, (8) 227*a*.
SiO_2-Al_2O_3-CeO_2, region of glass formation in, (9) 234*c*.
SiO_2-Al_2O_3-MgO, phase transformations in crystallization of glass in, (9) 253*b*.
SiO_2-Na_2CO_3, dissolution in water, (5) 141*d*.
SiO_2-NaCl, dissolution in water, (5) 141*d*.
silica-sodium tetraborate, (2) 53*b*.
silica-water and clay-water, processes of cementation in, (2) 29*a*.
$AgCl + Cu \rightleftharpoons CuCl + Ag$, interactions in, (1) 22*j*.
$AgCl + CuCl + Pb \rightarrow PbCl_2 + Ag + Cu$, interactions in, (11) 317*i*.
$AgCl + CuCl + Zn \rightarrow ZnCl_2 + Ag + Cu$, interactions in quaternary reciprocal system of substitution, (1) 22*i*.
Na,Ca,Ba||F,Cl, topological analysis of reciprocal, (10) 291*e*.
Na^+, Ca^{2+}, Ba^{2+}||F^-, Cl^-, cross sections of the reciprocal, (6) 166*a*.
NaCs,Pb||Cl, fusibility diagram of, (10) 286*c*.
Na^+, K^+, Ca^{2+}, Ba^{2+}||F^-, Cl^-, stable cross sections of tetrahedron of, (1) 25*e*.
Na_2CrO_4-Rb_2CrO_4 and Na_2CrO_4-Cs_2CrO_4, phase diagrams of, (1) 24*d*.
NaF-LiF, NaF-KF, and NaF-RbF, phase relations, (3) 84*g*.
Na_2O-Al_2O_3-CaO-SiO_2-H_2O, equilibrium phases of, (5) 136*c*.
Na_2O-Al_2O_3-CaO-SiO_2-H_2O, isothermal cross section of, (5) 137*i*.
Na_2O-SiO_2, phase separation and devitrification products of glasses in, (2) 32*a*.
Na_2O-SiO_2, thermography of crystallized glasses in, (4) 95*e*.
Na_2O-TiO_2-SiO_2, primary crystallization of glasses in and relation to immiscibility, (9) 234*a*.
Na_2O-ZrO_2-SiO_2, properties of glasses in, (1) 4*e*-*a*.
of sodium sulfate, with sulfates of copper(II) and iron(III), (11) 314*a*.
$Sr(NiW)_{0.5}O_3$-$Ba(NiW)_{0.5}O_3$, phase transition in, (10) 289*a*.
SrO-TiO_2-ZrO_2, solid phase reactions in, (5) 140*j*.
Ta-C, observations on zeta phase in, (3) 84*f*.
ternary, construction of a composition-property diagram of, (3) 83*f*.
ternary reciprocal, of fluorides and chlorides of K and Ta, (1) 23*e*.
Tl_2Cl_2-Tl_2Br_2-Na_2SO_4-K_2SO_4, (9) 254*i*.
ThO_2-BeO, ThO_2-MgO, ThO_2-SrO, and ThO_2-BaO, electrical conductivity of, B (1) 26*b*.
ThO_2-CaO, electrical conductivity, B (1) 26*j*.
Sn-Te, in region of compound SnTe, (11) 318*c*.
$SnCl_2$-KCl, electrochemical investigation of, (1) 21*b*.
titanium-oxygen, phase diagram for, (5) 140*a*.
Ti-V-C, isothermal section at 1450°C, (11) 318*j*.
TiO_2-CoO, solid state reaction in, (9) 255*j*.
W-O, magnetic susceptibilities in, (7) 203*c*.
WCl_6-$AlCl_3$-NaCl and WCl_6-$FeCl_3$-NaCl, physicochemical study of, (3) 84*g*.
uranium-carbon, phase relations determined by chemical, metallographic, and X-ray diffraction, B (6) 171*i*.
uranium-oxygen, electrical properties in composition range of U_3O_8 to UO_2, (11) 316*b*.
UP-UO_2, phase studies in, (1) 24*f*.
UO_3-U_3O_8, dissociation pressure of γ-UO_3, (1) 10*c*.
U^{VI}-U^{IV}, standard oxidation-reduction potential of, (7) 201*j*.
vanadium-oxygen, review of, (8) 228*b*.
water-alkali hydroxide, (2) 53*b*.
YF_3-PbF_2, phase diagram of, (5) 139*h*.
Y_2O_3-MgO, phase diagram of, (1) 24*c*.
Y_2O_3-ZrO_2, phase relations, physicochemical properties, and solid solutions, (5) 139*c*-*d*.
ZnS-ZnSe and PbS-PbSe, at 300°C and above, solid solution in, (9) 255*g*.
zirconium-carbon-oxygen, B (11) 320*d*.
ZrO_2-Al_2O_3-SiO_2, quantitative determination of crystalline substances from, (2) 32*g*.

Systems (*continued*)
ZrO_2-CaO, electrical conductivity and transport numbers, B (1) 26*i*.
ZrO_2-CaO-NiO and ZrO_2-CaO-Fe_2O_3, structural components and electrical conductivity of, B (1) 26*b*.

Tableware, bodies, fillers for, (10) 275*i*.
glass, composition of, (11) 297*a*.
Tagua, in valley of Paraiba and around Sao Paulo, (3) 78*c*.
Talcs. See also *Steatite*.
-based whiteware, production of, (6) 156*g*.
block, effect of temperature on solid-pressure transmission of, (6) 167*b*.
and soapstone, in 1964, (1) 18*b*.
Tanks. See also *Furnaces, glass*.
battery, causes of glaze failure on, (2) 39*c*.
Tantalum, alloys, compatibility with hydrogen, (8) 207*j*.
arsenides and antimonides of, (3) 79*h*.
and Ca, new double oxide $Ca_2Ta_8O_{25}$, (7) 197*f*.
carbide, carbon diffusivity determined in, (5) 135*b*.
heat of formation, (1) 22*c*.
means to form on Ta metal, P (10) 263*g*.
method to prepare crystal of, P (8) 217*f*.
chloride, systems. See *Systems*.
diselenide and triselenide of, (11) 315*f*.
elements, chemistry of, (3) 80*d*.
fluoride, systems. See *Systems*.
-Nb mixtures, buffer effects in spectrochemical analysis of, (6) 161*j*.
normal orthophosphates of, (1) 23*c*.
oxide, carburization of, (7) 197*c*.
systems. See *Systems*.
pentachloride, hydrolysis of, (11) 317*b*.
pentachloride, interaction with chlorides of Li and Cu, (10) 287*c*.
pentoxide, aqueous slips of, (6) 155*j*.
single crystal growth and polymorphism of, (6) 169*j*.
systems. See *Systems*.
phases, including crystal structure of $Ba_3SrTa_2O_9$, (6) 165*c*.
selenide, system. See *Systems*.
separation, by introducing as dry solid into central step of liquid-liquid partition system, P (10) 283*d*.
and Sr, crystallography of double oxide of, (6) 166*b*.
systems. See *Systems*.
Ta_2C, crystal structure, (3) 80*b*.
TaI_4, preparation, properties, and structure, (11) 314*i*.
$TaSe_3$, crystal structure of, (2) 49*c*.
telluride, system. See *Systems*.
thin-film circuits, substrates for, (9) 242*e*.
thin films, method to sputter, P (11) 307*d*.
-Ti alloys, solid electrolyte capacitors using, (8) 220*f*.
Technetium, disilicide, crystal structure of, (10) 284*b*.
Technical ceramics, vitrified, (9) 241*j*.
Technology, advanced, materials for, B (5) 142*e*.
cermet, (10) 270*f*.
developments, 1961–1962, (7) 203*i*.
of electroceramics, (7) 192*g*.
glass, new interest for ceramists, (7) 181*a*.
of glass, review of, (10) 265*b*.
new, availability of, (7) 203*i*.
new, plasma as, (11) 311*k*.
as related to art, (10) 261*j*.
of silicates, present and future, (2) 54*g*.
Television tubes. See *Tubes*.
Tellurides, glasses, infrared transmission of, (6) 148*b*.
of La, (10) 291*g*.
sesqui-, rare earth with Sc_2S_3 structure, (8) 227*f*.
Tellurium, in aluminum antimonide, effective coefficient of distribution, (1) 20*i*.
chloride, systems. See *Systems*.
content, determination by cathode-ray polarography, (2) 44*c*.
films, deposited on $BaTiO_3$ crystals, Hall mobility of, (2) 50*g*.
-In, properties of thin films containing 50 to 60% Te, (9) 254*d*.
oxidation products, X-ray investigation of, (10) 290*j*.
systems. See *Systems*.
Temperature, control, fundamentals in small container glass tanks, (7) 180*b*.
dependence, of band gap in CdTe, (5) 141*e*.
of dark discharge of xerographic selenium layers, (6) 166*d*.
of electrical resistivity of VO_2 powder, (10) 291*h*.
of iron acceptor level in GaAs, (10) 291*i*.
distribution, calculation in glass casting machine, (10) 264*g*.
calculation in glass-metal combinations, (2) 31*a*.
inside top roller of glass casting machine, (10) 267*a*.
effects, on transverse tensile properties of graphite tested in helium and in vacuum, (4) 110*i*.
of foam glasses, relation to specific resistance, (11) 297*j*.
furnace, method and position to measure, (3) 67*h*.
high, chemistry, selected topics in, B (10) 292*f*.
effect on solid-pressure transmission of talc and pyrophyllite, (6) 167*b*-*d*.
tests needed for protective coatings for, (6) 146*f*.
infrared sensing, of transparent objects, (7) 195*g*.
of objects, changed by gas jets, P (10) 282*b*.
sensitive device, P (11) 308*b*.
sensor, expendable plug-in unit, P (11) 311*d*.

Temperature (*continued*)
spin ordering, correlation for compounds containing divalent 3*d* transition metal ions, (6) 165*g*.
surface, techniques for measuring, (6) 163*f*.
Temperature measuring instruments, P (6) 163*e*.
for differences, P (7) 195*a*.
pyrometer, P (7) 195*d*.
errors and effects in optical measurements with, (6) 163*h*.
Kurnakov, to simultaneously record the thermogram and polytherm of electrical conductivity of a melt by, (4) 107*f*.
optical, with cyclically moving detector, P (1) 17*a*.
portable, P (4) 108*a*.
radiation, to measure color temperature, P (9) 246*e*.
radioactive, P (5) 132*c*.
remote reading, P (9) 246*c*.
sensors, P (3) 77*a*.
thermocouple, calibrations, furnace for, (9) 245*h*.
connector, P (4) 108*b*.
immersible assembly, P (7) 195*d*.
method to join to thermoelectric elements, P (7) 193*b*.
Pt30% Rh vs. Pt-6% Rh, reference tables for, (9) 245*h*.
pressure dependence of emf of, (6) 162*g*.
protected by cermet zirconium-boride end caps, (1) 16*h*.
ribbon, in the 3000° to 5000°F range, (7) 195*i*.
sealed glass, and adjustable thermostat, (9) 245*j*.
sheathed compared with bare wire, (4) 107*e*.
with zirconium boride cermet tips, to measure metal temperature in converters, (3) 76*b*.
Tension, surface, of commercial glasses in air and N, (8) 211*j*.
Terbium, Tb^{4+}, EPR and endor spectra in ThO_2, (1) 21*g*.
Tb^{3+}, fluorescence and nonradiative energy transfer from Gd^{3+} to Tb^{3+} in borate glass, (6) 149*f*.
Terminology. See *Nomenclature*.
Testing. See also *Analysis* and specific types.
basic brick, for thermal shock resistance by air-quenching, (9) 239*j*.
device, for tension or compression of ceramics, (6) 203*i*.
hardness and scratch, on broken glass surfaces in vacuum, (6) 148*i*.
impact, (6) 162*d*.
for leaks, back-pressuring technique for, (2) 43*j*.
method, international study for under-load refractoriness, (1) 9*g*.
to predetermine 28-day strength of cement in 5 hours, (4) 90*h*.
for quality of materials for stopper heads, (9) 238*d*.
for refractories in pusher-type furnaces, (9) 239*i*.
nondestructive, to measure and control property variability, (2) 44*a*.
torsional, of fireclay brick at high temperature, (9) 239*e*.
Tests, for alkali resistance, of enamel, (9) 232*d*.
for cleanability of enamel, progress report on, (7) 179*b*.
durability, preparation of glass grain samples for, (3) 61*j*.
for enamel finishes, (11) 295*d*.
erosion, attempts to standardize Japanese methods, (9) 238*g*.
hot torsion, results on basic refractories, (11) 301*c*.
method, for magnesia clinker, (10) 273*a*.
new spall, for enameled Al, (6) 146*c*.
service, to find average corrosion of brick lining, (3) 68*j*.
standardized, for continuity of enamel coatings, (7) 178*j*.
Texture, change, in magnesia in furnace wall, (10) 270*j*.
effect, on magnetic properties of mixed barium strontium ferrites, (11) 317*d*.
Thallium, bromide, systems. See *Systems*.
chloride, systems. See *Systems*.
chlorides, bromides, and nitrates of, exchange reactions in five-component reciprocal system, (1) 21*j*.
system, chlorides, bromides, and sulfates of, (5) 140*g*.
$ThUC_2$ fuel particles, spherical pyrolytic-carbon-coated, (3) 66*i*.
Thermal analysis, acoustic, possibilities of, (10) 286*j*.
apparatus, P (11) 311*c*.
apparatus, for dispersion materials, (8) 222*j*.
of barium and strontium titanyl oxalates, (1) 25*j*.
differential, applied to dissociation of MnO_2 and Mn_2O_3, (1) 19*e*.
of basic O furnace refractories, (6) 154*e*.
of 2CaO·SiO_2, (5) 134*f*.
to determine surface area of clay, (7) 198*a*.
of ferrite raw materials and compounds, (6) 157*f*.
for heat transfer problems, (8) 223*e*.
of Indian clays, (7) 203*b*.
interpretation for titanomagnetites using magnetic and nonmagnetic reference materials, (11) 318*a*.
introduction, present status, and background, (6) 162*a*.
of kaolinite, effect of physical factors on, (1) 20*e*.
of materials at high temperature, (8) 224*a*.
semiquantitative results from, (2) 44*f*.
in study of glass crystallization, (9) 234*j*.

Thermal analysis, differential (*continued*)
of tetragonally deformed spinels, (2) 49*b*.
of dispersion materials and melts, installation for, (8) 222*j*.
of melts, in system $NbCl_4$-NaCl-KCl, (5) 141*i*.
methods, B (2) 56*f*.
quantitative differential, with an isothermal microcalorimeter, (3) 76*h*.
types, B (9) 259*i*.
Thermal conductivity. See *Conductivity*.
Thermal decomposition. See *Decomposition*.
Thermal expansion. See *Expansion*.
Thermal properties, of ceramics, B (5) 142*i*.
of dysprosium, aluminum garnet near the Néel temperature, (2) 53*c*.
of mica, (6) 164*d*.
of refractories, at high temperature, (11) 301*d*.
of refractory materials, at high temperature, (8) 223*j*.
of solids, transient methods to measure, (4) 108*a*.
Thermal shock resistance. See *Shock resistance, thermal*.
Thermistors. See *Resistors, electrical*.
Thermochemistry. See *Thermodynamics*.
Thermocouples. See *Temperature measuring instruments*.
Thermodynamics, for compatibility studies, of metal-clad uranium carbide, B (6) 171*h*.
of formation, of TiF_6^{3-} complex anion in molten salts, B (1) 26*h*.
and high-strength materials, B (2) 55*g*.
measurements, factors effecting performance of solid oxide electrolytes in high-temperature, (7) 199*c*.
methods, applied to heat and mass transfer, (7) 197*g*.
of mullite, andalusite, kyanite, and sillimanite, (1) 25*e*.
of nonstoichiometric Nb_2O_5, (1) 25*g*.
observations, on reactions of high melting carbides, (9) 257*c*.
properties, of antimonide of Zn, (1) 25*d*.
of Mn silicides, (10) 291*c*.
of strontium selenide, (9) 257*e*.
relations, between immersional and adhesional wetting, (4) 114*b*.
of water sorption by cements, (10) 262*f*.
Thermoelectricity, conversion apparatus, P (8) 222*a*.
device, P (1) 15*e*; P (7) 194*d*.
device, materials for, P (7) 194*d*.
elements, method to join to thermocouple, P (7) 193*b*.
elements, production of lead telluride by vacuum hot-pressing, P (10) 279*c*.
thermoelectric power, of TiC, (8) 228*c*.
thermoelectric powers, and entropies of hydrogen ion, (3) 87*e*.
thermoelectric unit, to interconvert heat and electrical energy, P (9) 244*c*.
Thermoelectric materials, P (9) 244*b*.
alloy, P (3) 74*b*.
composition and preparation, P (1) 15*e*.
compositions and method to produce, P (3) 74*c*.
mixed-crystal, P (1) 15*a*.
Thermoelectric properties, of vacuum evaporated PbTe films, (1) 14*d*.
Thermography, analysis, of crystallized glasses of system Na_2O-SiO_2, (4) 95*e*.
contact, to measure surface temperature, (8) 224*b*.
determination, of glass transformation temperature, (7) 182*a*.
method, to determine kinetics of dehydration of glasses, (1) 4*a*.
study, of formation of ultramarine, (2) 53*d*.
in study of hardening and setting of tufaceous binders, (2) 29*d*.
Thermogravimetry, of basic O furnace refractories, (6) 154*e*.
of condenser ceramics, (6) 170*i*.
instrument to measure simultaneously with magnetic susceptibility, (11) 309*f*.
of mullite formation, in system kaolinite-aluminum fluoride, (2) 53*a*.
Thermoluminescence. See *Luminescence*.
Thermometers, P (1) 17*d*.
fever, physical processes in constriction of, (6) 148*d*.
gas, with constant bulb temperature, high temperature determination by, (4) 107*d*.
linear quartz, (2) 44*j*.
resistance, to measure surface temperature, (8) 224*b*.
Thermostats, adjustable and sealed glass thermocouple, (9) 245*j*.
encapsulated, switch with heater in stem, P (11) 306*a*.
Thickness, dependence, of $BaTiO_3$ switching time, (9) 242*f*.
variation, relation to waviness in sheet glass, (1) 5*h*.
Thixotropy, of plastic whiteware bodies, (10) 275*g*.
thixotropic properties, formulas to determine inelastic, (5) 134*c*.
Thoria. See *Thorium, oxide*.
Thorium, carbide, electrical properties of, (11) 316*b*.
carbides, reactions with aqueous sodium hydroxide solutions, (8) 227*h*.
dioxide, creep of polycrystalline, (9) 249*a*.
effect on crystallization of optical glass, (2) 31*g*.
preparation of granular, P (5) 126*f*.
systems. See *Systems*.
-UO_3, fuel from, (7) 187*j*.
metals, carbon-reduction to determine O in, (5) 131*e*.
Thorium (*continued*)
microgram amounts, analysis in U ores and process liquors by means of ^{232}Th, (11) 310*b*.
monophosphide, ThP_{1-x}, and phase studies of system Th-ThP, preparation and properties of, (7) 202*f*.
oxide, crystallite size, strain, and shape determined by X-ray line broadening studies, (4) 110*d*.
deformation and fracture of, (1) 20*b*.
EPR and endor spectra of Tb^{4+} in, (1) 21*g*.
extraction from rare earth ores, P (8) 225*f*.
method to determine in thoria-urania mixtures, (5) 131*d*.
microspheres, (10) 272*f*.
and mixed thorium oxides and method, P (2) 48*c*.
permeability to O, (6) 169*d*.
-plutonium oxide particles, compactible, P (9) 240*e*.
powders, studies on hot pressing of, (5) 125*d*.
properties of powders, (9) 248*h*.
sintering of, (6) 153*g*.
with 8-quinolinol, extraction and spectrometric determination of, (5) 131*h*.
from siliceous materials, chemical method to isolate, (2) 44*c*.
tetrachloride, nuclear quadrupole resonance in, (10) 285*a*.
and U, binary compounds of, P (11) 303*b*.
Tile. See also *Pipe*.
(2) 40*d*.
acoustic, method to make, P (11) 300*e*.
acoustical, apparatus to make, P (4) 98*g*.
apparatus for stacking in magazines, P (3) 71*j*.
clays for, (2) 35*g*.
clays, composition and structure, (2) 35*c*.
drain, P (3) 65*e*.
firing schedule for large, (2) 35*h*.
machine to produce and handle, P (6) 151*f*.
mechanical setting, (8) 213*f*.
and support for, P (4) 98*i*.
earthenware, improving quality of glazes for, (6) 156*e*.
earthenware, new compositions for white, (6) 156*i*.
facing, engobes for, (3) 71*g*.
fireclay wall, with reduced-fire glaze, (6) 156*b*.
floor and wall, pregrouted on flexible backing, P (6) 157*c*.
floor and wall, research, (2) 39*c*.
glaze, light colored, (2) 39*d*.
on heating stoves, changes in, (6) 144*b*.
hot preparation of, (11) 304*e*.
means to blend and discharge on conveyor, P (7) 190*h*.
mitered, cylinder press for, P (8) 214*e*.
mixing apparatus and method for, P (4) 103*b*.
plant, growth due to design and innovation, (8) 214*h*.
press, mechanism for, P (3) 72*a*.
pressed, molds for, (11) 308*h*.
production, of South American plant, (4) 98*i*.
for radiant gas burner, P (2) 38*a*.
roof, reversible design, P (3) 65*e*.
spacer strips, apparatus to apply, P (1) 13*c*.
stoneware, pressing, (3) 71*e*.
structural, combined with wood, P (1) 13*a*.
substratum, building, P (1) 13*d*.
surfaces, method to prepare, P (4) 98*h*.
thin-walled, continuous production, P (10) 276*c*.
T section, P (5) 127*i*.
wall, adhesion of, (3) 71*c*.
comparison of methods to prepare dust for, (7) 190*f*.
conditions for formation and use of synthetic wollastonite in, (8) 219*a*.
for dryer furnace, P (3) 77*f*.
rapid firing for, (9) 241*g*.
wall and floor, materials and methods for setting, (2) 39*b*.
methods to prepare dry-press bodies for, (9) 261*j*.
prespaced, P (11) 304*e*.
Time, factor, in graphitization process, (9) 257*f*.
Tin, chloride, with chlorides of alkali metals, study of systems formed by ammonium and, (9) 257*j*.
interaction with chlorides of rare-earth metals, Fe, and Na, (1) 22*e*.
interaction with chlorides of Ta, Nb, Fe, and Al, (11) 317*d*.
chlorine, systems. See *Systems*.
ores, spectrographic determination of tin in low-grade, (11) 310*e*.
oxide, effect of γ-radiation on films of, (10) 264*g*.
infrared absorption in single crystal, (5) 137*b*.
Knudsen and Langmuir evaporation studies of, (4) 112*d*.
selenide, phase transition of second kind in, (9) 253*c*.
selenide, semiconducting properties of, (4) 104*e*.
systems. See *Systems*.
Titanates. See also *Dielectrics* and specific types.
Al, formation and properties, (7) 197*b*.
powders, synthesis of ultrafine, (7) 191*e*.
Titania. See *Titanium, dioxide*.
Titanium, boride, interaction with Nb and W, (1) 22*f*.
boride, ultrafine, P (6) 155*h*.
carbide, cermets, Al-bonded, (8) 214*i*.
diffusion of Nb in and in the solid solution TiC-NbC, (10) 284*f*.
dispersion hardening by boron doping, (11) 315*h*.
oxidation products of, (7) 201*h*.
powders, maximum air content, (3) 68*g*.
thermoelectric power of, (8) 228*c*.
Titanium, carbide (*continued*)
WC-Co alloys, effect of production conditions on, (8) 215*d*.
X-ray diffraction intensities of, (10) 286*f*.
casting, mold of carbon powder for, (6) 153*d*.
(III), determination in magnesia-titania refractories, (3) 69*b*.
diboride, articles and method of making, P (2) 38*i*.
production, P (7) 189*f*.
pyrolytic filaments for composites, (4) 99*i*.
di-, tri, and tetrabromides, interaction with bromides of Rb and Cs, (11) 317*e*.
dioxide, apparatus to agglomerate and separate from gaseous vehicle, P (8) 225*a*.
and CeO_2, color produced in glass by, (3) 63*c*.
effect on semiconduction of $BaTiO_3$, (3) 72*f*.
electrical resistivity and defect energy levels at low temperatures in reduced, (10) 285*f*.
etch patterns in single crystals of, (10) 286*a*.
growth and properties of whiskers from fused salt baths, (1) 22*b*.
magnesia refractories, determination of titanium(III) in, (3) 69*b*.
manufacture, P (1) 18*g*; 19*c*.
manufacture of rutile, P (2) 47*g*.
method to cool gaseous suspension of, P (2) 47*h*.
mixed with carbon, behavior during electrolysis of molten salts, B (1) 26*h*.
particles produced in oxyhydrogen flame, (8) 225*f*.
pigment, analysis by spark-source mass spectrography, (10) 280*g*.
pigment, removing chloride impurity from, P (8) 225*h*.
pigment quality, P (8) 225*d*.
plasma production of, P (11) 312*g*.
preparation of fibrous, P (6) 155*f*.
preparation of fibrous and compositions useful for, P (6) 164*i*.
preparation by ion bombardment for transmission electron microscopy, (9) 253*e*.
production of concentrate from ilmenite and similar ores, P (8) 225*g*.
recovery, P (2) 48*a*.
relation of stress to physical properties of cover coats of, (6) 146*a*.
systems. See *Systems*.
type and related structures, isomorphic and morphotropic relations of oxides with, (7) 200*g*.
-zirconia, frits, (5) 119*i*.
enamels, discoloration of, (6) 145*e*.
film, performance of high speed getter pump with, (3) 76*e*.
-fluorine flint glass, volatilization of, (4) 96*c*.
higher oxides of, (9) 250*a*.
in lead titanate-zirconate ceramics, determination of, (7) 194*j*.
-Mo alloy, properties of protected, (6) 152*a*.
monoxide, electronic properties of, (5) 136*c*.
nitride, ceramics, (9) 239*c*.
method to grow crystals of, P (4) 107*b*.
oxidation in dry and moist air, (4) 112*e*.
region of homogeneity, X-ray spectral investigation of, (10) 291*j*.
and silicide powders, maximum air content, (3) 68*g*.
oxide, in electronics, (10) 276*h*.
grain growth of magnesium oxide containing, (2) 50*f*.
production of pigmentary, P (2) 48*a*.
systems. See *Systems*.
Tiron procedure to determine in glass, (4) 107*e*.
phosphides, preparation and phase studies of, (8) 227*a*.
pressure hull, possibility on deep submergence vehicles, (2) 54*i*.
sesquioxides, containing V ions, properties of, (10) 290*c*.
tetrachloride, tetrabromide, or tetraiodide, oxidation in presence of Th, P (9) 247*j*.
-tin spinels, pigments of, (5) 139*i*.
$TiP_{0.43}$, crystal structure, (3) 80*g*.
systems. See *Systems*.
thermal shock resistance of zirconia with, (7) 187*i*.
Titration. See also *Analysis*.
coulometric, to determine B in materials, (9) 245*c*.
hexaminecobalt(III) tricarbonatocobaltate(III) as, (2) 44*i*.
titrimetry, to determine Ca and Mg in silicate rocks, (2) 45*e*.
Tooling, sheet metal, for enameling, (4) 91*e*.
Tools. See also *Drills*.
broach, for curved graphite passages, P (11) 301*i*.
ceramic cutting, (8) 214*i*.
cutting. See also *Abrasives*.
cutting, microstructure in, (1) 1*h*.
for glassworking, method to clean, P (2) 34*b*.
hard refractories, use in pressing cermet parts on transfer presses, (3) 69*j*.
Topography, diffraction, of X-ray diffraction spikes of diamond, (4) 110*h*.
micro-, from domain walls in barium titanate, interferometric study of, (3) 82*h*.
micro-, silicon monoxide technique for observing surface, (2) 45*j*.
Topology, network, to describe sinter bodies at various sintering stages, (5) 138*i*.
Torch, flame-spraying, P (4) 91*h*; P (7) 179*d*; P (8) 208*d*; P (10) 263*h*.
flame spraying, remote powder feed for, P (11) 296*c*.
plasma, to treat refractory powders, P (9) 246*i*.
Tosudite, new mineral, forms mixed layer phase in alushite, B (2) 56*f*.

Tracers. See *Radioactive tracers.*
Transducers, diode pressure, and system, P (6) 158*j.*
electroacoustic, to detect low level acoustic signals, P (6) 159*c.*
electromechanical, and fabrication of, P (6) 159*e.*
encapsulated, P (1) 6*i.*
method to make, P (7) 193*f.*
open hemispherical, P (4) 105*j.*
piezoelectric, vapor-deposited thin-film, (10) 277*e.*
prestressed, P (4) 106*c.*
reinforced cylindrical, P (4) 106*e.*
stress sensitive tunnel diode, P (11) 308*a.*
temperature-independent, P (1) 15*b.*
Transformations, of alumina, kinetics of phase, (9) 251*h.*
crystallochemical, for Cr spinellids during calcining, (10) 284*a.*
high-temperature, of synthetic kaolinite, (11) 317*j.*
hydrothermal silica, (8) 226*g.*
of magnesite, oriented, (7) 201*f.*
phase, in reduction and oxidation of uranium oxides, (11) 318*j.*
polymorphous, of cristobalite, effect of dislocations on temperature characteristics of, (9) 249*b.*
Transistors, P (3) 74*c;* P (4) 106*g.*
circuits, junction capacitors for, (8) 219*h.*
closure device, P (1) 14*k.*
diffused-base, for high-frequency operation, P (3) 73*b.*
electrode connection, P (8) 222*b.*
field effect, P (11) 306*e.*
four-region switching, with controlled current path in emitter, P (10) 278*h.*
Ge, alloy-diffusion process to make, P (10) 277*g.*
insulating heat-sink holder for, P (7) 193*e.*
junction terminus, barrier coating for, P (3) 73*c.*
gallium arsenide, method of making, P (7) 193*d.*
Ge *pnp*, P (9) 244*d.*
with many depressions, P (4) 105*a.*
mesa, and other semiconductor devices, method to produce, P (6) 160*c.*
monocrystal, with region for isolating unit, P (9) 243*h.*
MOS enhancement, stability effects in, (3) 72*c.*
photo-, ultrasensitive device, P (3) 74*f.*
planar, method to fabricate, (5) 128*j.*
planar, with relatively higher resistivity base region, P (11) 307*f.*
silicon carbide unipolar, P (8) 222*a.*
switching, with controlled emitter-base breakdown, P (5) 130*b.*
Transitions, brittle-ductile, in polycrystalline aluminum oxide, (9) 248*d.*
fronts, movements in barium titanate, (5) 139*a.*
fronts, structure in barium titanate, (5) 141*c.*
high pressure, in InSb, (1) 22*d.*
laser, in electron-beam-pumped GaAs, (10) 286*g.*
optical, in ZnS type crystals containing cobalt, (9) 252*g.*
phase, in condensed systems, B (9) 259*e.*
phase, in $PbZrO_3$, high-temperature, (10) 286*f.*
Transmission, daylight, of window glass, (1) 5*h.*
-emission, X-ray quantitative analysis by, (3) 76*i.*
optical, of quartz samples in ultraviolet and 3μ region, (9) 252*h.*
Transport, mechanisms, technique to study at crystal surfaces, (2) 53*c.*
properties, of condensed monolayers, (4) 114*f.*
in sintering, mechanism of material, (11) 318*a.*
Transportation, damages, reduce on major appliances, (8) 208*c.*
Tridymite, -cristobalite, relations and solid solutions, discussion, (6) 166*j.*
Triodes, Al-Al_2O_3, hot-electron transfer through thin-film, (5) 137*d.*
semiconductor, P (3) 74*h.*
solid state, P (7) 194*c.*
Tubes, aluminosilicate, gage measurements at pressures below 10^{-12} torr, (10) 281*f.*
cathode ray, P (9) 235*g.*
display screens for, P (3) 73*d;* P (4) 105*b.*
method to form funnel portion of, P (9) 237*d.*
method to make stress free, P (7) 184*h.*
and others resistant to fracture and capable of controlled devacuation, P (3) 72*e.*
and others resistant to violent devacuation, P (3) 72*f.*
strengthened, P (4) 98*b.*
with transparent color screen, P (3) 72*f.*
using fiber optics faceplate, P (5) 128*j.*
ceramic, with self-supporting frame grid electrode system, P (2) 41*b.*
cold cathode discharge, method to construct, (4) 105*d.*
color, discolored by phosphors, (11) 305*b.*
color cathode ray, with index stripes on ultraviolet-emitting phosphor layer, P (11) 305*d.*
color TV, performance of Eu-activated phosphors in, (8) 220*d.*
electric discharge, with heat conserving shields and glass sleeve, P (7) 192*e.*
electron, comprising beryllium oxide ceramic, P (4) 104*f.*
electron mounting structure of a high frequency, P (6) 159*f.*
glass, permeation of helium through, (1) 4*b.*
hot cathode, P (2) 41*e.*
Mo coatings for, (11) 304*j.*
single multi-electrode with ceramic stem and recessed metal layer on one face, P (11) 308*c.*
electronic, inorganic bonded reconstituted micaceous products in, P (1) 14*d.*
faceplates, method to make cathode ray, P (8) 213*g.*
Tubes (*continued*)
fluorescent, with mercury amalgam on wall, P (10) 278*h.*
gas discharge, method to make miniature, P (4) 105*j.*
glass, device to bend to circular shape, P (2) 33*f.*
flame cutting and sealing ends for containers, P (2) 34*e.*
forming, P (7) 183*h.*
forming short-length, P (2) 33*i.*
high-pressure discharge, inlead construction, P (2) 33*b.*
lathe to graduate, (5) 121*e.*
method and apparatus for forming multiple-bore, P (6) 150*f.*
method to facilitate breaking, P (5) 123*i.*
method to form envelopes and beads from small, P (2) 34*f.*
method to form openings in sidewalls, P (1) 7*a.*
method of making, P (3) 64*f.*
method to measure outside diameter, P (10) 269*h.*
method to seal, P (9) 236*f.*
pressure resistance of bomb, (4) 94*h.*
reinforced envelope for light source and method of making, P (3) 64*i.*
glass-copper, sealing of, (10) 266*g.*
with heat conducting mount, P (3) 74*e.*
hollow-cathode discharge, for generating atomic resonance lines, P (5) 128*h.*
image, with external semiconductive layer on target of wires in glass matrix, P (3) 73*f.*
process for aging, P (8) 221*g.*
quartz, furnace for continuous drawing, P (11) 298*d.*
refractory, apparatus to form from asbestos-cement, P (7) 188*f,h.*
reinforced cathode-ray, method to manufacture for television, P (3) 64*i.*
and rod, method and device for mass production from glass, P (2) 34*d.*
spark, with thermionic electrodes, P (11) 308*e.*
television, method to strengthen, P (2) 34*a.*
television picture, display of critical switching curves of magnetic films on, (6) 157*g.*
and TV bulbs, containers for, P (4) 96*b.*
U-V responsive photoemissive, P (10) 278*j.*
X-ray, piezoelectrically powered, P (2) 45*j.*
Tungstates, alkaline-earth, equilibrium and stability in M-W-O systems, (8) 226*a.*
metal ion, growing Nd doped single crystal, P (9) 244*a.*
trivalent, of type $L_2(MO_4)_3$, study of, (10) 284*e*
Tungsten, alloys, sintering and properties of W-Ni and mechanical properties of sintered W-Ni-Fe alloys, (11) 305*h,i*
carbide, test procedure for dry grinding with diamond wheels, (8) 205*f.*
carbide, -TiC-Co alloys, effect of production conditions on, (8) 215*d.*
carbide-Co alloys, deformation of hard, (8) 215*a.*
dependence of its electrical resistivity on structure of, (10) 284*c.*
heat treatment of, (3) 67*c.*
structural dependence of electrical resistivity of, (10) 290*g.*
tensile strength and rupture of sintered in compression, (10) 272*i.*
chloride, systems. See *Systems.*
-cobalt carbides, mechanism of fracture in sintered, (10) 288*e.*
diffusion of C into, at low C concentrations, (10) 284*d.*
disilicide, microhardness anisotropy and slip in single crystal, (5) 138*d.*
disilicides, thermal expansion of, (9) 257*i.*
hexa- and pentachloride, interaction with chlorides, of Na and K, (11) 317*e.*
at high temperature, thermal and electrical conductivity of, (11) 318*c.*
metallizing, of ceramics, (10) 277*b.*
monocarbide, determination of slip systems in single crystal, (1) 20*g.*
monocarbide, effect of high pressures and temperatures on, (10) 271*j.*
and Nb, interaction with titanium boride, (1) 22*f.*
oxide, systems. See *Systems.*
powders, maximum air content, (3) 68*g.*
silicon carbide coatings on, B (11) 320*e.*
sorts, produced by powder metallurgy, behavior of dopes in, (11) 313*i.*
systems. See *Systems.*
trioxide, systems. See *Systems.*
$WNb_{12}O_{33}$ and $W_5Nb_{16}O_{55}$, structure and monoclinic phases, (6) 168*h.*
$W_3Nb_{14}O_{44}$ and $W_8Nb_{18}O_{69}$, structures of tetragonal phases, (6) 168*i.*
Turbines, blades, thermal stress in ceramics applied as thermal barrier layers to, (10) 263*c.*
gas, ceramics and, B (11) 320*h.*
gas, refractory nozzle vane, P (2) 37*g.*
Twinning, of crystals. See *Crystals.*

Ultrasonics. See *Sonics.*
Uranía. See *Uranium, oxide.*
Uranium, carbide, apparatus to shape, P (9) 239*i.*
determination of Burgers vector of dislocations in deformed, (9) 249*f.*
-10%Fe, electrochemical aspects of hydrolysis of, (10) 285*f.*
method to produce, P (7) 188*j.*
-C alloys, mechanical behavior at high temperature and fabrication by extrusion, (11) 301*g.*
compound, preparation in powder form, P (4) 101*d.*
dicarbide and sesquicarbide, B (6) 171*g.*
dioxide, in experimental reactor fuel, (3) 68*d.*
high-density particles, P (10) 274*i.*
Uranium, dioxide (*continued*)
improvements in fabrication of fuel from, (6) 154*b.*
in-pile fission-gas release from single crystal, (3) 67*j.*
loss from molybdenum-UO_2 cermets by diffusion, (3) 68*f.*
manufacture of, P (5) 126*c.*
manufacture of bodies from sintered, P (4) 100*f.*
melting by direct high frequency induction, (6) 153*b.*
method and apparatus for obtaining from uranium trioxide, P (4) 100*j.*
method to make high density, P (4) 101*f.*
method to make hollow spheres of, P (11) 302*b.*
method to prepare granular, P (8) 217*h.*
pellets, fission gas retention of those produced by different methods, (3) 67*i.*
- PuO_2 fuels, fabricating processes, (6) 152*c.*
powder, P (11) 302*h.*
properties of powders, (9) 248*h.*
radiation damage in, (4) 112*g.*
solubility of helium in, (6) 153*i.*
systems. See *Systems.*
-ThO_2, fuel from, (7) 187*j.*
from uranium hexafluoride, P (9) 241*b.*
visible and infrared absorption spectra of, (2) 53*i.*
ZrO_2-CaO, nuclear fuels, (7) 188*a.*
dioxide-BeO mixtures, compressive creep of, (1) 19*h.*
glasses, fluorescent, (6) 147*h.*
hexafluoride, method to make, P (11) 302*e.*
hexafluoride to uranium dioxide, fluid-bed process for direct conversion of, (3) 67*b.*
in household wares, health hazard of, (1) 12*h.*
interaction with N, (11) 317*g.*
ions, formulas of sexivalent and quadrivalent in acid solutions, (7) 201*k.*
Mo alloys, U compounds from, P (1) 19*a.*
monocarbide, method of stabilizing, P (1) 11*f.*
powder, P (3) 70*c.*
reactions of reactor-irradiated with water and aqueous solutions of NaOH, HCl, and H_2SO_4, (3) 68*h.*
mononitride, new reactor fuel, (3) 69*d.*
mononitride-uranium dioxide, nuclear fuel from, P (1) 12*d.*
monophosphite, properties of, (11) 319*b.*
monosulfide-uranium monophosphide solid solutions, P (10) 275*c.*
nitride, sintering with sintering aid depressant, P (1) 12*g.*
nitrides and carbides, for nuclear fuels, (9) 239*g.*
ores, flame-photometric determination of Na in, (2) 44*g.*
method to acid leach, P (7) 188*g.*
and process liquors, analysis of microgram amounts of Th in by means of ^{232}Th, (11) 310*b.*
oxide, dense, P (9) 241*b.*
in fluidized bed, preparation of uranium nitride and carbonitrides from, B (11) 320*d.*
phase transformations in reduction and oxidation processes of, (11) 318*j.*
sintering of, (6) 153*g.*
systems. See *Systems.*
-thoria mixtures, determination of thoria in, (5) 131*d.*
phosphide, systems. See *Systems.*
sesquicarbide, and mixtures of the sesquicarbide with monocarbide or dicarbide, hydrolysis products, (7) 200*f.*
structure of primary oxide layer on, (11) 318*b.*
sulfide and oxysulfide, vaporization and thermodynamic properties of, B (6) 175*c.*
systems. See *Systems.*
and Th, binary compounds of, P (11) 303*b.*
trioxide, systems. See Systems.
uranic oxide, method to granulate, P (1) 11*d.*
UC_2 fuel particles, spherical pyrolytic-carbon-coated, (3) 66*i.*
UC_2 particles, fission-product release from monogranular, (3) 67*j.*
$UCrO_4$, structure of, (7) 203*a.*
U_4O_9, anomaly of heat capacity near room temperature, (10) 290*f.*
U_3O_8, investigation by neutron diffraction, B (2) 55*i.*
U_4O_9, magnetic susceptibility of, (10) 291*a.*

Vacuum, analysis, mass spectrometer for residual, (9) 245*j.*
flasks, heat exchange in, (8) 209*b.*
leak, detection and location, (3) 76*g.*
pump, air-cooled with thermoelectrically cooled baffle, (1) 16*f.*
pumping equation, effect of pipeline outgassing in, (2) 44*e.*
surface conductivity and flashover in, (10) 277*b.*
systems, outgassing procedures for ultra-high-, (10) 281*i.*
protection of electrical components from damage by arcing or plasma discharges in, (4) 107*h.*
terminals installed in metal by electron beam welding, (10) 277*b.*
tight, seals, (9) 242*f.*
ultrahigh, porous materials to obtain, (3) 70*h.*
ultra-high-range, analysis of physical adsorption isotherms in, (9) 248*c.*
ultraviolet region, spectrophotometer to determine optical constants in, (4) 107*h.*
vessels, automated production of, (6) 146*i.*
Valves, ball, method to make, P (10) 276*c.*
Vanadates, $A_3B_1V_3O_{12}$, with garnet structure, (1) 25*j.*

Vanadates (*continued*)
alkaline and alkaline-earth, cryoscopic study of in molten vanadium hemipentoxide, (2) 48*j*.
Vanadium, carbides, calorimetry of, (11) 314*e*.
free energy of formation of, (11) 317*b*.
self-diffusion and sintering kinetics of, (9) 255*g*.
determination, in sea and natural waters, biological materials, and silicate sediments and rocks, (6) 166*f*.
dioxide, sintering, (2) 51*c*.
dioxide, temperature dependence of electrical resistivity of powder, (10) 291*h*.
hemipentoxide, cryoscopic study of alkaline and alkaline-earth vanadates in molten, (2) 48*j*.
at high temperatures, disproportionation of tribromide of, (4) 110*a*.
inner complex compounds, stereochemistry of those with anomalous magnetic properties, (4) 113*d*.
ions, properties of Ti sesquioxides containing, (10) 290*c*.
oxidation, at high temperatures, (3) 68*c*.
oxide, crystal growth, (3) 80*a*.
magnetic properties of chromium oxide modified by, (10) 288*a*.
semiconductor films on glass, (1) 5*j*.
pentoxide, systems. See *Systems*.
pentoxide and magnesia, sintered mixture as high frequency insulator, (4) 102*j*.
in $Na_2O \cdot 2SiO_2$ glass, optical spectra of, (1) 4*j*.
systems. See *Systems*.
trichloride, interaction with chlorides of Na, K, and Rb, (11) 317*j*.
trioxide, + carbon anodes during electrolysis of molten chlorides, behavior of, B (1) 26*i*.
V_2C, crystal structure, (3) 80*h*.
$VOSO_4$, crystal sructure (2) 49*c*.
-zircon, combinations for color, (10) 275*f*.
Vaporization, heats, correlation of latent, (1) 19*i*.
of PbO-PbF_2 melt, during solution growth of YIG crystals, (3) 87*a*.
method, to prepare films on glass, (1) 5*b*.
molten-salt, methods for growing crystals of refractory oxides, (5) 138*i*.
vacuum, of U and carbides of U, B (6) 175*e*.
Vapor pressure, and decomposition, of alkali compounds in glass melt, (3) 62*b*.
determination, of anhydrous chlorides of Y and Sm, (1) 20*i*.
saturation, determination for selenides and tellurides of Ge, (4) 110*f*.
of silicate glasses, and their components, (4) 95*i*.
of sulfides, of Pb and In, (2) 53*f*.
Vapors, barrier, method to form carbon, P (4) 101*c*.
deposition, method and apparatus, P (4) 106*g*.
Vermiculite, butylammonium-, swelling of, B (2) 56*i*.
complexes, with amines, (9) 248*i*.
treatment, and its use as thermal insulation, P (10) 283*a*.
Vibration, of crystals, scattering of high energy electrons by thermal, (3) 85*d*.
damping, of glasses in system LiF-BeF_2, (8) 211*c*.
high frequency, to install high alumina plastic refractory, (8) 215*i*.
lattice, frequency dependence on thermal expansion, Grueneisen parameter, and temperature of aluminum oxide, (1) 25*a*.
in quartz crystal, study by X-ray diffraction topography, (3) 86*i*.
technique, resonant to determine shear wave velocity, (8) 223*g*.
Viscometers, wide-range, rotating cylinder, (4) 96*d*.
Viscometry, cone-and-plate, formulas for shear stress and shear rate and determination of properties, (5) 134*c*.
Viscosity, of boron trioxide, (1) 6*b*.
of glass, new method to measure, (4) 94*j*.
of melts, in system Sb-Sb_2Se_3 in solid and liquid states, (1) 21*a*.
of molten glass, (1) 6*b*.
of quartz glass, (10) 266*j*.
of sodium borate glass, relation of composition to, (9) 234*d*.
of technical glasses, (5) 120*d*.
Vitrification, de-, absence at bubble surfaces in soda-lime glasses, (8) 208*f*.
of bottle glass, (9) 233*d*.
of lithium disilicate glass, (5) 120*g*.
of earthenware bodies, intensifying with combined additives, (6) 156*g*.
Volatility, of optical glass, (7) 182*e*.
Volume, change, caused by water sorption of cement, (10) 262*f*.
skeletal, change in fluid-filled porous body under stress, (1) 19*g*.
Volumeter, to determine porosity of granular materials, (3) 76*c*.

Water. See also *Humidity; Moisture; Steam.*
adsorbed, by cation in silicates, (8) 227*d*.
absorption, effect of weathering on rate in brick, (7) 184*j*.
absorption, of granular materials, (9) 246*a*.
atmospheres, kinetics of crystallization of SiO_2 glass in, (4) 112*b*.
in beryl, nuclear magnetic resonance study of, (7) 201*j*.
in BeO, determination of, (7) 194*j*.
cement ratio, effect on structure and strength of hardened cement paste, (8) 206*h*.
-cement suspensions, structure forming role of solid surfaces during bonding with, (3) 59*c*.
in clays, electrogravimetry of, (2) 49*j*.
containing dissolved CO_2, alteration of albite by, (8) 227*e*.
Water (*continued*)
content, control in cement raw slurry, (9) 230*h*.
content, effect on container glasses, (2) 32*c*.
desalted, for silvering glass, (9) 233*a*.
evaporation, from sodium silicate glass, (4) 93*e*.
extracts, electrical conductivity to determine sedimentary environment of clays, B (2) 56*h*.
freezing of, (8) 226*d*.
in glass, determined by nuclear magnetic resonance, (3) 60*i*.
in gypsum, direct rapid determination of combined, (3) 75*e*.
hot, attack on silicate glasses, (8) 209*e*.
of hydration of montmorillonite, nuclear magnetic resonance study of thermal evolution at low temperatures, (7) 201*h*.
kaolin-lime, microtexture and composition of reaction products in, (8) 226*j*.
in kaolin minerals, intercalation of, (6) 168*g*.
-kaolin suspensions, viscosities with additions of basic aluminum chloride complex, (5) 127*i*.
natural and sea-, means to determine fluoride in, (11) 309*h*.
natural especially sea-, determination of silicate-silicon in, (11) 309*i*.
-oxide interface, interrelation of zero point of charge and heat of immersion, (1) 24*a*.
phase, and mineral surface, B (7) 204*g*.
proportioning system, base and trim and method, P (4) 100*d*.
requirement, of calcined gypsum, effects of gum arabic on, (8) 207*b*.
requirements, of portland cement, (11) 293*j*.
resistance to, increase in phosphoanhydrite, (1) 2*b*.
retention of refractory mortars, method to simultaneously determine workability and, (7) 187*c*.
sea and natural, determination of V in, (6) 166*f*.
in silicate glass, effect on transformation and softening behavior, (5) 120*j*.
in silicate glass, oxygen tracer investigation of diffusion of, (9) 234*h*.
in sodium vermiculite, thermodynamics of interlayer adsorption of, (4) 114*c*.
solubility, and effects of content on crystallization in mafic magmas, (7) 202*b*.
sorption, by compacts of cement, (10) 262*d*.
systems. See *Systems*.
tanks, radiant tube furnaces for, (6) 146*d*.
vapor, effect on dielectric loss in MgO, (8) 226*b*.
effect on friction of MoS_2, (9) 238*d*.
effect in furnace on enameling sheet steel, (9) 231*i*.
effect on glass-resin interface, (2) 31*h*.
effect on initial sintering of magnesia, (11) 316*i*.
evolution from glass after atmospheric exposure, (9) 233*i*.
solubility in alkali borate melts, (10) 266*h*.
strength of fused quartz in, (2) 51*f*.
Water vehicles, deep submergence, materials for, (2) 54*i*.
submarines, design considerations for manned deep-diving, (2) 54*i*.
Wear, of abrasive grains, (6) 143*h*.
mechanism, of magnesite rotor linings, (8) 215*g*.
mechanism, of tar-bonded dolomite in electric arc furnace wall, (7) 187*a*.
Weathering. See also *Frost resistance.*
phenomenon, on Roman glass fragments, (6) 144*c*.
process, initial stages on soda-lime glass, (5) 120*i*.
resistance of enamels, (11) 295*e*.
resistance of enamels, results of seven-year tests, (6) 146*b*.
Weighing. See also *Balances; Thermogravimetry.*
problems, in glass batch plants, (3) 62*b*.
Welding, arc, method and electrode for, P (3) 60*b*.
of B_4C, to Si, (8) 216*f*.
brazing, exothermic, of metal joints, P (11) 296*a*.
electrodes. See *Electrodes*.
electron beam, of terminals in metal vacuum systems, (10) 277*b*.
multigun spot, glass backup dies for, (11) 295*g*.
plug, frangible, P (1) 11*e*.
powders, basic, P (1) 3*f*.
rod, carbide, P (8) 208*a*.
rod, flux-coated carbide, P (11) 295*i*.
seam, for enameling metals, (11) 295*c*.
submerged arc, and flux composition using fluorocarbon, P (11) 296*d*.
vacuum diffusion, of metallic carbides to high-melting metals, (7) 179*d*.
Wetting, agents, effect of synthetic on pickling operations, (8) 207*h*.
of clay, effects of drying and heating pretreatments on heat of, (4) 111*h*.
of diamond and graphite, by molten metals and alloys, (1) 1*g*.
immersional and adhesional, thermodynamic relations between, (4) 114*b*.
interfacial angles, effect on size of bubbles in glass during clarification, (1) 4*d*.
of limestone and quartz, by melting soda, (5) 122*b*.
of platinum, and its alloys by glass, (4) 96*c*; (5) 122*b*.
of refractory concrete, by molten glass, (9) 235*i*.
Whiskers. See also *Crystals.*
alumina, recent advances in technology, (4) 99*c*.
$BaTiO_3$, surface-charge layers in, (3) 86*b*.
ceramic and graphite, B (5) 142*d*.
composite materials, for aerospace design, (11) 295*c*.
engineered, new strength and ideas with, (6) 171*c*.
growth, within MgO, (4) 114*a*.
growth sites, compared with dislocation etch pits on sapphire, (4) 110*a*.
refractory, state-of-the-art, (2) 37*i*.
of refractory oxides, single crystals and their use, (7) 188*e*.
Whiskers (*continued*)
ruby, growth and characteristics, (9) 255*f*.
NaCl, growth on NaCl single crystals, (7) 199*j*.
and spiral growth, in pyrolytic carbon, (9) 256*c*.
zirconia and titania, from fused salt baths, (1) 22*b*.
Whiteware. See also *Art and artware; Bodies, ceramic; Bone china; Dielectrics; Dinnerware; Heating elements; Insulators, electrical; Porcelain; Pottery; Tile.*
batch, effect of distribution on electrical porcelain, (1) 12*j*.
blanks, machines for use on, P (3) 72*b*.
bodies, considerations regarding fast firing of, (6) 156*j*.
plastic, measuring thixotropy of, (10) 275*g*.
plasticity and packing of, (10) 275*j*.
process to form metalliferous coatings on, P (8) 219*e*.
properties related to particle size, (10) 276*b*.
body compositions, nonreactive, (6) 156*f*.
effect on glaze maturing, (10) 275*c*.
making monocrystalline, P (10) 276*d*.
distinguishing conceptions of viscosity, workability, plasticity, and binding power, (3) 71*g*.
fiber reinforced, physical properties, (10) 275*f*.
flatware, preparation of molds for, (5) 127*h*.
glazed articles, (1) P 13*a*.
gray, pigment of V_2O_5 and Al_2O_3 for, P (11) 304*b*.
industry, calculations in, B (3) 88*a*.
machines to finish, P (6) 157*a*.
manufacture, in Mexican plant, (4) 102*f*.
marking machine, P (9) 242*b*.
packing element, for treating tower, P (5) 127*h*.
plant, modernization of German, (3) 71*i*.
porous, of low thermal conductivity, P (8) 219*d*.
pressed, automatic production from plastic material, P (2) 40*a*.
pressed, scrap trimmer for, P (5) 127*g*.
slips, electrical dewatering, (2) 39*a*.
talc-based heat-resistant, production of, (6) 156*g*.
tile stamper, system and device to control membrane on, P (7) 191*b*.
wall-tile dust, comparison of preparation methods, (7) 190*f*.
Windows. See *Glass.*
Windshield, automobile, of laminated glass with embedded antenna wires, P (1) 6*e*.
Wire, coating apparatus, P (9) 232*f*.
electrically conductive, coated, P (3) 59*j*.
explosions, use of electric to investigate fracture process in glass, (6) 149*i*.
micro-, means to produce glass insulated directly from liquid metal, P (9) 232*f*.
Wollastonite, California, (2) 36*h*.
glazes, status for sanitary ware, (2) 40*a*.
synthetic, conditions for formation and use in wall tile, (8) 219*a*.
systems. See *Systems.*
Writing, of better reports, B (6) 171*h*.
Wurtzite, sphalerite inversion, p-T dependence in ZnS, (6) 169*i*.

Xenotime, Y in, determination by X-ray fluorescence method, (9) 245*e*.
X rays, absorption, by crystal of arbitrary shape, corrections for, (7) 198*a*.
absorption analysis technique, apparatus to measure concentration of element in mixture, P (11) 311*a*.
analysis, collection of papers on, B (7) 204*h*.
analysis, quantitative of multicomponent systems, (5) 131*f*.
analyzer, mineralogical model analysis with electron microprobe, (7) 195*d*.
beta-ray excited, industrial applications of, (4) 107*f*.
data, of oxidation products of Te, (10) 290*j*.
data, for zinc phosphates and vanadates, (2) 49*i*.
determination, of symmetry of unit cells of K-Bi and Na-Bi titanates and of high-temperature phase transformation of K-Bi titanates, (5) 135*c*.
diffraction, apparatus, high pressure-high temperature, P (7) 195*c*.
of cristobalite-containing ceramics, (10) 291*g*.
to determine crystal structure of $Er_2Ti_2O_7$, (5) 134*j*.
high temperature powder of $2CaO \cdot SiO_2$, (5) 134*f*.
intensities, of quenched TiC, (10) 286*f*.
to measure thermal expansion of Fe and its oxides, (2) 53*j*.
mounting techniques, error due to clay mineral segregation, (3) 75*h*.
patterns, new method to index for powders, (7) 195*a*.
problems in determination of cristobalite by and estimation of degree of crystalline disorder, (6) 162*h*.
of single crystals at high pressures, (3) 85*f*.
of Spanish clay, (9) 250*j*.
spikes of diamond, diffraction topography of, (4) 110*h*.
of structure changes of quartz during treatment, (10) 291*f*.
topography, of defect structures of single crystal BeO, (5) 141*a*.
topography, to study vibrations in quartz, (3) 86*a*.
from electron probe device, method for analysis of, P (9) 246*d*.
emission, analysis, (3) 76*b*.
analysis, of cement raw mix by radioisotopes, (9) 231*b*.
microanalysis for rock forming minerals, (4) 114*c*.
spectrography, quantitative analysis by, (2) 45*f*.

X rays (*continued*)
equipment, piezoelectrically powered, P (2) 45*j*.
excited, to identify minerals in moving ores, (11) 312*c*.
fluorescence, application in flat glass industry, (4) 92*a*.
in heavy clay industry, (5) 132*a*.
method for quantitative analysis of nonmetallics, (11) 310*g*.
methods for glass analysis, (2) 32*h*.
spectroscopy, of glass, (6) 146*j*.
intensity statistics, to determine crystal symmetries and space groups, (11) 313*c*.
investigation, of compound in system PbO–SiO_2, (3) 87*e*.
line broadening, crystallite size, strain, and shape determined by, (4) 110*d*.
line broadening, in neutron irradiated magnesium oxide, (2) 54*a*.
metallography, developments of line profile analysis for, (8) 223*e*.
microanalyzer, electron probe, (10) 280*i*.
of moire patterns, with superposed CdS crystals, (10) 291*j*.
nondispersive, spectrochemical analysis using nuclear beta-ray source, (4) 107*g*.
peak intensity measurements, to determine thickness of disturbed layer on quartz powder, (3) 87*h*.
phase analysis, of systems $MeTiO_3$–$MeWO_4$-(MoO_4), (3) 87*g*.
powder diffraction patterns, determination for modifications of Ca_2SiO_4, (2) 29*a*.
powder diffractometer line profiles, minimization of variance of parameters derived from, (10) 288*g*.
powder patterns, variations in low structural state plagioclase, (6) 171*b*.
quantitative analysis, by emission-transmission method, (3) 76*i*.
reflections, determination of elastic constants of monoclinic crystals from diffuse, (7) 198*i*.
scattering, particle sizes of clay minerals determined by small-angle, (6) 162*i*.
sensitivity, of single Sb_2S_3 crystals, (3) 87*g*.
of sesquioxides, deposited in chromite grains, (5) 142*b*.
soft, reflection by polished glass and steel, (3) 85*i*.
spectral analysis, results for hexaborides of rare earth elements, (10) 290*j*.
spectral investigation, of homogeneity region of titanium nitride, (10) 291*j*.
study, of alkali and alkaline-earth chromates(V), (3) 87*i*.
on binding properties of Cu_2O and Ag_2O, (10) 292*a*.
of hafnium tetrabromide, (2) 54*b*.
of Indian clays, (7) 203*b*.
of melts in system BaO–GeO_2, (2) 54*c*.
topography, to map Dauphine and Brazil twins in quartz, (10) 288*b*.
topographic study, of planar growth defects in natural diamond, (2) 54*d*.

Young's modulus. See *Elasticity*.
Ytterbium, beryllides, of composition ABe_{13}, (11) 313*j*.
divalent ions, spectra in crystals of alkaline earth, (9) 256*d*.
Yttrium, Al garnet, laser for optical second-harmonic generation, (10) 285*h*.
garnet, low-temperature thermal expansion of, (9) 251*b*.
nonuniform impurity distributions in single crystals, (3) 84*c*.
oscillations from ions in, (10) 284*a*.
carbide, synthesis and physicochemical properties of, (4) 113*f*.
chlorides, vapor pressure of anhydrous, (1) 20*i*.
determination, by grating and Littrow type spectrograph, (4) 107*g*.
fluoride, systems. See *Systems*.
-gallium garnet, Czochralski growth, (2) 49*e*.
iron garnet, crystals, vaporization of PbO–PbF_2 melt during solution growth of, (3) 87*a*.
CW-pumped and amplification of elastic waves in, (6) 166*c*.
factors effecting domain configurations in, (5) 136*j*.
growth and properties of films, (3) 82*e*.
measurement of third-order elastic moduli of, (9) 252*c*.
optical transparency in near infrared, (1) 23*g*.
spin-wave excitation of magnetoacoustic modes and beating of modes in, (10) 290*e*.
sublattice contributions to infrared rotary dispersion in, (10) 291*c*.
vapor growth of, (6) 171*a*.
metals, carbon-reduction to determine O in, (5) 131*e*.
oxide, cathodoluminescence of Eu-activated, (8) 219*g*.
electrical properties of calcium diferrite doped with, (11) 304*j*.

Yttrium, oxide (*continued*)
electrical properties and defect structure of, (9) 249*h*.
systems. See *Systems*.
thermomechanically deformed, (4) 114*e*.
vanadate, growth of large crystals for optical maser studies, (10) 277*a*.
Y^{3+}, in CaF_2: Dy^{3+} lasers, quenching of Dy^{3+} fluorescence by, (1) 24*e*.
YB_4, crystal structure of, (7) 198*d*.
$Y_3Fe_{5-x}Al_xO_{12}$, garnet, control of electromagnetic properties of, (11) 314*e*.
$Y_3Fe_{5-x}Ga_xO_{12}$ and $Y_3Fe_{5-x}Al_xO_{12}$, dependence of magnetic properties on thermal history, (11) 315*a*.
YVO_3, single-crystal growth and properties of, (9) 255*e*.
YVO_4: Eu, phosphor for color TV, (8) 220*i*.
in xenotime and monazite, determination by X-ray fluorescence, (9) 245*e*.

Zeolites, composition, preparation of crystalline, P (11) 312*f*.
crystalline, P (7) 196*g*.
high-silica molecular sieve, P (4) 103*c*.
L, crystalline, P (2) 47*e*.
pellets, pretreatment to improve crushing strength, P (6) 155*g*.
powders, compaction of, P (1) 12*d*.
sedimentary, sorption and ion exchange in, (5) 141*a*.
Na-P, and the ion-exchanged derivatives of tetragonal Na-P, (4) 114*e*.
synthetic, derivatographic examination of, (6) 166*g*.
synthetic, diffusion of ethane in, (5) 135*h*.
zeolitic nature, question of four ferrocyanides of transition metals, (4) 112*g*.
Zinc, -cadmium sulfide phosphors, discoloration in color tubes caused by, (11) 305*b*.
chloride, systems. See *Systems*.
ferrites, magnetic and catalytic properties of (5) 138*d*.
higher antimonide, thermodynamic properties, (1) 25*d*.
in indium antimonide, distribution coefficient of, (9) 249*j*.
-manganese ferrites, mechanism of disaccommodation in, (10) 277*e*.
Mn-Fe ferrite, with rectangular hysteresis loop, (6) 158*h*.
-nickel ferrites, effect of small additions of Co on, (11) 316*g*.
-nickel ferrites, magnetic spectra at different temperatures, (11) 318*a*.
orthosilicate, formation by explosive shock, (10) 286*j*.
oxide, P (10) 275*c*.
and aluminum oxide, kinetics and mechanism of reaction between, (1) 23*f*.
crystals, growth by chemical reaction of zinc fluoride with air, (10) 284*b*.
and ferric oxide, solid reaction between, (4) 113*j*.
hydrothermally grown crystals of low and intermediate resistivity, (7) 191*h*.
powders, pelletization rate of, (3) 74*i*.
reactions with oxides of elements of groups IV and V, (2) 51*j*.
systems. See *Systems*.
-zirconium dioxide sinters, properties of, (5) 140*e*.
phosphates and vanadates, dilatometric and X-ray data for, (2) 49*i*.
phosphide, monoclinic, P (4) 105*h*.
selenide, systems. See *Systems*.
sulfide, as coating for cold mirrors, (5) 134*i*.
crystals grown from melt, B (11) 320*c*.
electroluminescent of optimum luminosity, P (9) 243*c*.
layers, photoconductivity of sintered, (10) 289*b*.
-lead, effect of electric field on photoluminescence of, (9) 242*f*.
polytypes of absorption edges determined by contact photography with UV, (1) 20*g*.
p-T dependence of sphalerite wurtzite inversion in, (6) 169*i*.
systems. See *Systems*.
type crystals, optical transitions in those containing cobalt, (9) 252*g*.
sulfide phosphors, anomalous paramagnetic susceptibility of shocked, (10) 283*h*.
decay characteristics of luminescence studied by pulsed light excitation, (5) 134*f*.
rare earth activated and products, P (11) 306*j*.
theoretical analysis, experimental results, low temperature effects on excitation specta of, (11) 316*d*.
telluride, effect of doubly ionizable vacancy acceptors on conductivity of donor doped, (11) 316*a*.
Zn^{2+}, Fe^{3+}, and Fe^{2+}, precipitation from solution containing, (9) 253*h*.

Zinc (*continued*)
$ZnFe_2O_4$, effect of Fe^{2+} ions at tetrahedral sites on magnetic properties of, (9) 250*e*.
$ZnSe_xTe_{1-x}$, electroluminescence from *pn* junctions in, (10) 285*i*.
$ZnSiO_3$/Mn powder phosphor, wavelength dependence of quantum efficiency and absorption coefficient of, (4) 114*h*.
Zircon. See also *Refractories*.
in acid fluorides, mechanism of solution of, (9) 252*c*.
brick for basic open-hearth ladles, (9) 239*f*.
brick, in open-hearth furnace ladles, (9) 237*i*.
in ceramics, and refractories, (1) 10*e*.
colors, for glazes, (10) 276*g*.
glazes, (2) 40*e*.
grinding balls and rods, production of, (4) 102*h*.
ladle brick, erosion of LD converter, (9) 238*f*.
ladle lining, changes in physical properties and mineral composition of, (8) 214*i*.
ladle lining, use and condition of used, (7) 188*d*.
ladle refractories, results when used in slag line only and when used in lower side wall of, (7) 187*f*.
opacifier, for glazes and enamels, (6) 156*d*.
refractories, in glost tunnel kilns, (2) 37*i*.
stability, in range 1180° to 1366°C, (1) 25*d*.
-vanadium, combinations for color, (10) 275*f*.
Zirconia. See *Zirconium, oxide*.
Zirconium, and its alloys, oxide plasticity in the oxidation mechanism, (7) 202*a*.
carbides, thermal expansion of nonstoichiometric, (9) 257*h*.
chloride, systems. See *Systems*.
compact, phosphatization of, (9) 253*e*.
complex fluorides, constants of instability of, (4) 110*c*.
content, determination in metal and powder by mandelic acid, (11) 309*j*.
determination, in South African granites, (11) 309*j*.
dioxide, -CaO-UO_2 fuels, (7) 188*a*.
containing CaO, internal friction in, (3) 82*i*.
electrical conductivity of films at intermediate temperatures, (3) 81*c*.
experimental and theoretical thermal conductivities of, (6) 170*e*.
films, optical properties and structure of, (2) 51*b*.
-MgO, phase boundaries of cubic mixed crystal from 1800°C to melting point, (7) 202*c*.
properties of powders, (9) 248*h*.
-SiO_2-Al_2O_3, refractories for ladles, (9) 239*f*.
systems. See *Systems*.
-titania, frits, (5) 119*i*.
-zinc oxide sinters, properties of, (5) 140*e*.
disilicides, effect of neutron irradiation on, (5) 135*b*.
enamels, effect of composition on whiteness and water resistance of, (6) 145*h*.
and Hf values, separation by solvent extraction, P (11) 312*j*.
minerals, Brazilian, (1) 18*d*.
nitride, and hydride from dioxide, conditions for obtaining, (1) 9*h*.
opacifiers, effect on colors, (1) 12*j*.
oxide, apparatus to hot press, P (2) 37*i*.
based foam insulating material, P (9) 241*e*.
cationic self-diffusion in calcia-stabilized, (6) 165*e*.
complexometric determination of, (6) 163*b*.
containing calcium oxide, tetragonal, P (3) 79*d*.
electronic conductivity of calcia-stabilized, (5) 128*c*.
from decomposition of alkoxides, metastable transitions of, (6) 168*f*.
growth and properties of whiskers from fused salt baths, (1) 22*b*.
method to prepare, P (7) 188*h*.
O exchange and diffusion in calcia stabilized, (4) 112*e*.
permeability to O, (6) 169*d*.
preparation of stabilized, P (9) 247*f*.
production, P (8) 225*g*.
properties and high temperature applications, (1) 9*f*.
refractories, mechanism by which metal additions improve thermal shock resistance of, (7) 187*b*.
sols with actinide oxides, P (10) 283*e*.
solubility in hydrofluoric acid in determination of glassy phase in fused cast glass tank blocks, (6) 153*j*.
stability in H, (2) 10*a*.
separation, by introducing as dry solid into central step of liquid-liquid partition system, P (10) 283*d*.
silicate, opacified glaze compositions, P (1) 13*e*.
systems. See *Systems*.
$ZrTiO_4$, formation from ZrO_2 and rutile or anatase, (11) 304*j*.
Zoisite, thermal stability, (1) 25*b*.
Zone melting, of crystallizable rod, remelting P (5) 129*i*.

Publications on Ceramic Science

Large Scale Phase Diagrams of Oxide Systems

This series of ten large scale phase equilibrium diagrams of oxide systems is the work of Dr. E. F. Osborn and Dr. Arnulf Muan of The Pennsylvania State University. For basic data they have drawn upon the published works of many scientists. Each diagram lists principal literature references, providing sources for additional information.

Each diagram is on a 500 mm equilateral triangle, with a scale accurate enough to permit interpolation to within 0.1%. The base triangle, printed in light blue, has 5 mm divisions, each representing 1% in composition. Temperature contours are in green, compositions in red, and boundary curves and primary phases in black. Each is printed on map paper and measures $23^1/_4 \times 19^1/_2$ in.

The ten systems:

1. $CaO–Al_2O_3–SiO_2$
2. $CaO–MgO–SiO_2$
3. $MgO–Al_2O_3–SiO_2$
4. $Na_2O–Al_2O_3–SiO_2$
5. $K_2O–Al_2O_3–SiO_2$
6. $FeO–Fe_2O_3–SiO_2$
7. $CaO–FeO–SiO_2$
8. $MgO–FeO–SiO_2$
9. $FeO–Al_2O_3–SiO_2$
10. $CaO–Fe_2O_3–SiO_2$

Cost of the diagrams is $2.00 each or $15 for the complete set of ten.

Phase Diagrams for Ceramists

ERNEST M. LEVIN, CARL R. ROBBINS and HOWARD F. McMURDIE, National Bureau of Standards. Edited and published by the American Ceramic Society, 1964. 602 pp. $18.00 to non-members; $12.00 to members of the Society. Add $1.00 for each copy to be mailed outside the United States.

This volume combines the material from the six preceding editions, plus more than 1000 newly selected phase equilibrium diagrams for a total of 2066. Some of the diagrams that have appeared in previous editions have been deleted and others updated in keeping with more recent data.

The 33-page introductory section, containing a glossary of terms, discussion of the phase rule, interpretation of diagrams, experimental methods and selected bibliography, has been revised from the 1956 edition, and the bibliography enlarged. The glossary outlines 50 terms peculiar to the phase rule. There is a comparison of the three important temperature scales in degrees centigrade that have been used since 1914, methods of determining composition of phase assemblages, and a discussion on the interpretation and representation of multicomponent systems. The annotated bibliography covers theory, interpretation, methods and techniques, mathematical treatment, thermodynamic calculations, silicate chemistry, and phase diagrams in related fields.

Two appendices have been added, one tabulating the melting points of metal oxides and the other listing molecular weights of oxides.

Diagrams are organized in seven sections:
(a) metal-oxygen systems
(b) metal oxide systems
(c) systems with oxygen containing radicals
(d) systems containing halides
(e) systems containing halides and other substances
(f) systems containing cyanides, sulfides, etc.
(g) systems containing water

A more complete description of *Phase Diagrams for Ceramists* will be found on page 482 of the June 1964 issue of the CERAMIC BULLETIN.

Cumulative Index to Publications of The American Ceramic Society

This volume is a key to the rich literature of ceramic science and technical knowledge as developed during the past 38 years. It indexes completely the 72 annual volumes published by The American Ceramic Society from 1918 through 1955 . . . . 38 years of the Journal and 34 years of The Ceramic Bulletin. It has 16,803 references in the subject index and 6,288 in the index to authors. Price: $5.00 per copy. Add $.25 for each copy to be mailed outside the United States.

Ceramic Glossary

EMILY C. VAN SCHOICK, Alfred University, assisted by other members of the Society's Glossary Committee. Published by the American Ceramic Society. 32-page, self-cover. $5.00 to non-members; $4.00 to members of the Society.

This glossary covers 1714 terms of ceramic interest, from *abrasion hardness* through *zircon whiteware*. It is the result of five years work by Miss Van Schoick and her large committee, drawn from all Divisions of the Society, seeking to find definitions acceptable to all segments of the industry.

Ceramic-Metal Systems and Enamel Bibliography (1960–1969)

A loose leaf volume of abstracts pertaining to ceramic-metal systems, ceramic systems and porcelain enamels, including materials, processes, properties, and patents. This valuable ready reference for researchers, engineers and plant operators is sponsored by the Ceramic-Metal Systems Division of the American Ceramic Society.

Annual supplements to the 1960–1969 edition cost $3.00 each. The 1960–61, 1962, 1963–1964, and 1965 supplements with cumulative author and subject indexes, edited and compiled by Gordon H. Johnson, are available. Loose leaf binders for the edition sell for $2.00 each.

Enameling literature published before 1960 is indexed and abstracted as follows:

"Enamel Bibliography and Abstracts, 1928–1939" at $2.50 per copy.
"Enamel Bibliography and Abstracts, 1940–1949" at $4.00 per copy.
"Enamel Bibliography and Abstracts, 1956–1959" at $2.00 per year.
(The 1950–1955 supplements are out of print.)

Symposium on Nucleation and Crystallization in Glasses and Melts

This volume brings together 18 papers presented as a part of the Glass Division's meeting in April 1961. They provide studies in the fundamentals of glass crystallization and glass formation. Many of the papers deal with attempts to present in a more quantitative and explicit way the kinetics, spatial, structural, and chemical factors that influence crystallization. Others are directed at understanding and describing the genesis of crystallized glass and properties of these materials. A copy of the Table of Contents and explanatory Foreword will be sent upon your request. Price: $15.00 to non-members; $10.00 to members of the Society. Add $0.50 for each copy to be mailed outside the United States.

ORDER FROM

THE AMERICAN CERAMIC SOCIETY

4055 N. High St., Columbus, Ohio 43214

CERAMIC ABSTRACTS

1966

FRANK P. REID, *Editor*
MARY J. GIBB, *Associate Editor*
GERTRUDE M. BUSICK, *Assistant Editor*
BARBARA L. WHITE, *Assistant Editor*
SUSAN MCCLELLAN, *Editorial Assistant*

Committee on Publications: W. J. SMOTHERS, *Chairman;*
HOWARD F. MCMURDIE, SEYMOUR L. BLUM, CLARENCE L. BABCOCK, AND EDWARD E. MUELLER

Technical Adviser: R. S. SHELDON

Compiled by

The American Ceramic Society
4055 North High Street
Columbus, Ohio 43214

ABSTRACTERS FOR 1966

Abraham Aladjem—Israel
Eugene Aleshin—U. S.
Wilfred Ashworth—England
D. J. Barbour—U. S.
M. P. Bauleke—U. S.
Gerhard Bayer—Switzerland
M. D. Beals—U. S.
W. C. Beard—U.S.
K. E. Bell—Canada
Adli Bishay—Egypt
J. J. Borbas—U. S.
J. G. Brady—Canada
W. B. Campbell—U. S.
N. F. Cerulli—U. S.
G. W. Cleek—U. S.
J. J. Diamond—U. S.
Alfred Dube—Canada
R. H. Edwards—U. S.
Marie Farnsworth—U. S.
W. M. Fenton—U. S.
K. W. J. Fickert—Canada
J. R. Fisher—U. S.
J. H. Fishwick—U. S.
C. E. L. Franklin—England
Kanekoto Fujii—Japan
J. E. Gillott—Canada
F. W. Glaze—U. S.
H. T. Harrison—U. S.
H. S. Hartmann—U. S.
M. P. Haydon—U. S.
R. O. Heckroodt—South Africa
C. I. Helgesson—Sweden
S. B. Holmquist—U. S.
R. H. Insley—U. S.
B. Z. Kamich—U. S.
M. J. Kerper—U. S.
Herbert Kornguth—U. S.
A. M. Lacy—U. S.
B. B. Lane—U. S.
M. P. Lepie—U. S.
S. A. Lindroth—Sweden
J. R. Little—U. S.
Luigi Luciani—Italy
V. V. Mirkovich—Canada
Sylva Modry—Czechoslovakia
L. Mordecai—England
Taro Moriya—Japan
M. K. Murthy—Canada
J. F. Nicks—Canada
A. W. Norris—England
L. S. O'Bannon—U. S.
V. R. Palmeri—U. S.
L. N. Perkins—U. S.
W. W. Perkins—U. S.
V. S. Ramachandran—India
Don Satas—U. S.
J. O. Semmelman—U. S.
N. W. Severin—U. S.
Kenneth Shaw—England
L. E. Shipley—U. S.
W. K. Soderstrum—U. S.
Shigeyuki Somiya—Japan
I. L. Soreghy—U. S.
K. F. Sporek—U. S.
M. A. Stett—U. S.
Helmut Stoll—Germany
J. A. Sugden—England
Yuichi Suzukawa—Japan
V. D. Svikis—Canada
Ferenc Tamas—Hungary
R. F. Tatnall—U. S.
J. W. Taylor—Scotland
R. L. Thakur—India
Minoru Tomozawa—U. S.
P. K. Venkataraman—India
F. F. Y. Wang—U. S.
A. E. R. Westman—Canada
T. B. Weston—Canada
J. H. Weymouth—Australia
J. B. Whitney—U. S.
D. T. Williams—U. S.
W. O. Williamson—U. S.
Kazuo Yamasaki—Japan
J. C. Yang—U. S.